

# Review

# Stable Matching Problem

**Goal.** Given  $n$  men and  $n$  women, find a "suitable" matching.

- Participants rate members of opposite sex.
- Each man lists women in order of preference from best to worst.
- Each woman lists men in order of preference from best to worst.

	favorite ↓ 1 <sup>st</sup>	2 <sup>nd</sup>	least favorite ↓ 3 <sup>rd</sup>
Xavier	Amy	Bertha	Clare
Yancey	Bertha	Amy	Clare
Zeus	Amy	Bertha	Clare


*Men's Preference Profile*

	favorite ↓ 1 <sup>st</sup>	2 <sup>nd</sup>	least favorite ↓ 3 <sup>rd</sup>
Amy	Yancey	Xavier	Zeus
Bertha	Xavier	Yancey	Zeus
Clare	Xavier	Yancey	Zeus

*Women's Preference Profile*

# Propose-And-Reject Algorithm

Propose-and-reject algorithm. [Gale-Shapley 1962] Intuitive method that guarantees to find a stable matching.



```
Initialize each person to be free.
while (some man is free and hasn't proposed to every woman) {
    Choose such a man m
    w = 1st woman on m's list to whom m has not yet proposed
    if (w is free)
        assign m and w to be engaged
    else if (w prefers m to her fiancé m')
        assign m and w to be engaged, and m' to be free
    else
        w rejects m
}
```

## 1.2 Five Representative Problems


---

# Interval Scheduling

**Input.** Set of jobs with start times and finish times.

**Goal.** Find **maximum cardinality** subset of mutually compatible jobs.


↑  
jobs don't overlap



# Weighted Interval Scheduling

**Input.** Set of jobs with start times, finish times, and weights.


**Goal.** Find **maximum weight** subset of mutually compatible jobs.



# Bipartite Matching

Input. Bipartite graph.

Goal. Find **maximum cardinality** matching.




# Independent Set

Input. Graph.

Goal. Find **maximum cardinality** independent set.

↑  
subset of nodes such that no two  
joined by an edge






# Competitive Facility Location

**Input.** Graph with weight on each node.

**Game.** Two competing players alternate in selecting nodes.

Not allowed to select a node if any of its neighbors have been selected.

**Goal.** Select a **maximum weight** subset of nodes.



Second player can guarantee 20, but not 25.

# Five Representative Problems

Interval scheduling:  $n \log n$  greedy algorithm.

Weighted interval scheduling:  $n \log n$  dynamic programming algorithm.

Bipartite matching:  $n^k$  max-flow based algorithm.

Independent set: NP-complete.

Competitive facility location: PSPACE-complete.

## 2.2 Asymptotic Order of Growth

---

# Asymptotic Order of Growth

**Upper bounds.**  $T(n)$  is  $O(f(n))$  if there exist constants  $c > 0$  and  $n_0 \geq 0$  such that for all  $n \geq n_0$  we have  $T(n) \leq c \cdot f(n)$ .

**Lower bounds.**  $T(n)$  is  $\Omega(f(n))$  if there exist constants  $c > 0$  and  $n_0 \geq 0$  such that for all  $n \geq n_0$  we have  $T(n) \geq c \cdot f(n)$ .

**Tight bounds.**  $T(n)$  is  $\Theta(f(n))$  if  $T(n)$  is both  $O(f(n))$  and  $\Omega(f(n))$ .

**Ex:**  $T(n) = 32n^2 + 17n + 32$ .

- $T(n)$  is  $O(n^2)$ ,  $O(n^3)$ ,  $\Omega(n^2)$ ,  $\Omega(n)$ , and  $\Theta(n^2)$ .
- $T(n)$  is not  $O(n)$ ,  $\Omega(n^3)$ ,  $\Theta(n)$ , or  $\Theta(n^3)$ .

# Notation

**Slight abuse of notation.**  $T(n) = O(f(n))$ .

- Not transitive:
  - $f(n) = 5n^3$ ;  $g(n) = 3n^2$
  - $f(n) = O(n^3) = g(n)$
  - but  $f(n) \neq g(n)$ .
- Better notation:  $T(n) \in O(f(n))$ .

**Meaningless statement.** Any comparison-based sorting algorithm requires at least  $O(n \log n)$  comparisons.

- Statement doesn't "type-check."
- Use  $\Omega$  for lower bounds.

# Properties

## Transitivity.

- If  $f = O(g)$  and  $g = O(h)$  then  $f = O(h)$ .
- If  $f = \Omega(g)$  and  $g = \Omega(h)$  then  $f = \Omega(h)$ .
- If  $f = \Theta(g)$  and  $g = \Theta(h)$  then  $f = \Theta(h)$ .

## Additivity.

- If  $f = O(h)$  and  $g = O(h)$  then  $f + g = O(h)$ .
- If  $f = \Omega(h)$  and  $g = \Omega(h)$  then  $f + g = \Omega(h)$ .
- If  $f = \Theta(h)$  and  $g = O(h)$  then  $f + g = \Theta(h)$ .

# Asymptotic Bounds for Some Common Functions

**Polynomials.**  $a_0 + a_1n + \dots + a_dn^d$  is  $\Theta(n^d)$  if  $a_d > 0$ .

**Polynomial time.** Running time is  $O(n^d)$  for some constant  $d$  independent of the input size  $n$ .

**Logarithms.**  $O(\log_a n) = O(\log_b n)$  for any constants  $a, b > 0$ .

↑  
can avoid specifying the  
base

**Logarithms.** For every  $x > 0$ ,  $\log n = O(n^x)$ .

↑  
log grows slower than every polynomial

**Exponentials.** For every  $r > 1$  and every  $d > 0$ ,  $n^d = O(r^n)$ .

↑  
every exponential grows faster than every polynomial

## 2.4 A Survey of Common Running Times

---



## Linear Time: $O(n)$


**Linear time.** Running time is proportional to input size.

**Computing the maximum.** Compute maximum of  $n$  numbers  $a_1, \dots, a_n$ .

```
max ← a1
for i = 2 to n {
    if (ai > max)
        max ← ai
}
```

## Linear Time: $O(n)$

**Merge.** Combine two sorted lists  $A = a_1, a_2, \dots, a_n$  with  $B = b_1, b_2, \dots, b_n$  into sorted whole.



```
i = 1, j = 1
while (both lists are nonempty) {
    if (ai ≤ bj) append ai to output list and increment i
    else          append bj to output list and increment j
}
append remainder of nonempty list to output list
```

**Claim.** Merging two lists of size  $n$  takes  $O(n)$  time.

**Pf.** After each comparison, the length of output list increases by 1.

# $O(n \log n)$ Time

$O(n \log n)$  time. Arises in divide-and-conquer algorithms.



also referred to as linearithmic time

**Sorting.** Mergesort and heapsort are sorting algorithms that perform  $O(n \log n)$  comparisons.

**Largest empty interval.** Given  $n$  time-stamps  $x_1, \dots, x_n$  on which copies of a file arrive at a server, what is largest interval of time when no copies of the file arrive?

**$O(n \log n)$  solution.** Sort the time-stamps. Scan the sorted list in order, identifying the maximum gap between successive time-stamps.

## Quadratic Time: $O(n^2)$

**Quadratic time.** Enumerate all pairs of elements.

**Closest pair of points.** Given a list of  $n$  points in the plane  $(x_1, y_1), \dots, (x_n, y_n)$ , find the pair that is closest.

**$O(n^2)$  solution.** Try all pairs of points.

```
min ← (x1 - x2)2 + (y1 - y2)2
for i = 1 to n {
  for j = i+1 to n {
    d ← (xi - xj)2 + (yi - yj)2
    if (d < min)
      min ← d
  }
}
```

← don't need to  
take square roots

**Remark.**  $\Omega(n^2)$  seems inevitable, but this is just an illusion. ← see chapter 5

## Cubic Time: $O(n^3)$

**Cubic time.** Enumerate all triples of elements.

**Set disjointness.** Given  $n$  sets  $S_1, \dots, S_n$  each of which is a subset of  $1, 2, \dots, n$ , is there some pair of these which are disjoint?

**$O(n^3)$  solution.** For each pairs of sets, determine if they are disjoint.

```
foreach set  $S_i$  {  
    foreach other set  $S_j$  {  
        foreach element  $p$  of  $S_i$  {  
            determine whether  $p$  also belongs to  $S_j$   
        }  
        if (no element of  $S_i$  belongs to  $S_j$ )  
            report that  $S_i$  and  $S_j$  are disjoint  
    }  
}
```

## Polynomial Time: $O(n^k)$ Time

**Independent set of size  $k$ .** Given a graph, are there  $k$  nodes such that no two are joined by an edge?

$k$  is a constant

**$O(n^k)$  solution.** Enumerate all subsets of  $k$  nodes.

```
foreach subset S of k nodes {  
    check whether S is an independent set  
    if (S is an independent set)  
        report S is an independent set  
    }  
}
```

- Check whether  $S$  is an independent set =  $O(k^2)$ .
- Number of  $k$  element subsets =  $\binom{n}{k} = \frac{n(n-1)(n-2)\cdots(n-k+1)}{k(k-1)(k-2)\cdots(2)(1)} \leq \frac{n^k}{k!}$
- $O(k^2 n^k / k!) = O(n^k)$ .

poly-time for  $k=17$ ,  
but not practical

# Exponential Time

**Independent set.** Given a graph, what is maximum size of an independent set?

**$O(n^2 2^n)$  solution.** Enumerate all subsets.

```
S* ←  $\phi$ 
foreach subset S of nodes {
    check whether S is an independent set
    if (S is largest independent set seen so far)
        update S* ← S
}
```


# Connectivity

**s-t connectivity problem.** Given two node  $s$  and  $t$ , is there a path between  $s$  and  $t$ ?

**s-t shortest path problem.** Given two node  $s$  and  $t$ , what is the length of the shortest path between  $s$  and  $t$ ?

## Applications.


- Friendster.
- Maze traversal.
- Kevin Bacon number.
- Fewest number of hops in a communication network.





# Breadth First Search

**BFS intuition.** Explore outward from  $s$  in all possible directions, adding nodes one "layer" at a time.



**BFS algorithm.**

- $L_0 = \{ s \}$ .
- $L_1$  = all neighbors of  $L_0$ .
- $L_2$  = all nodes that do not belong to  $L_0$  or  $L_1$ , and that have an edge to a node in  $L_1$ .
- $L_{i+1}$  = all nodes that do not belong to an earlier layer, and that have an edge to a node in  $L_i$ .

**Theorem.** For each  $i$ ,  $L_i$  consists of all nodes at distance exactly  $i$  from  $s$ . There is a path from  $s$  to  $t$  iff  $t$  appears in some layer.


## 4.1 Interval Scheduling

---

# Interval Scheduling

## Interval scheduling.

- Job  $j$  starts at  $s_j$  and finishes at  $f_j$ .
- Two jobs **compatible** if they don't overlap.
- Goal: find maximum subset of mutually compatible jobs.



# Interval Scheduling: Greedy Algorithms

**Greedy template.** Consider jobs in some natural order.  
Take each job provided it's compatible with the ones already taken.



counterexample for earliest start time



counterexample for shortest interval



counterexample for fewest conflicts

# Interval Scheduling: Greedy Algorithm

**Greedy algorithm.** Consider jobs in increasing order of finish time. Take each job provided it's compatible with the ones already taken.

```
Sort jobs by finish times so that  $f_1 \leq f_2 \leq \dots \leq f_n$ .
```

↙ set of jobs selected

```
A ←  $\phi$ 
```


```
for j = 1 to n {
```

```
    if (job j compatible with A)
```

```
        A ← A  $\cup$  {j}
```

```
}
```

```
return A
```



**Implementation.**  $O(n \log n)$ .


- Remember job  $j^*$  that was added last to A.
- Job j is compatible with A if  $s_j \geq f_{j^*}$ .

# Interval Scheduling: Analysis

**Theorem.** Greedy algorithm is optimal.


**Pf.** (by contradiction)

- Assume greedy is not optimal, and let's see what happens.
- Let  $i_1, i_2, \dots, i_k$  denote set of jobs selected by greedy.
- Let  $j_1, j_2, \dots, j_m$  denote set of jobs in the optimal solution with  $i_1 = j_1, i_2 = j_2, \dots, i_r = j_r$  for the largest possible value of  $r$ .




# Minimum Spanning Tree

**Minimum spanning tree.** Given a connected graph  $G = (V, E)$  with real-valued edge weights  $c_e$ , an MST is a subset of the edges  $T \subseteq E$  such that  $T$  is a spanning tree whose sum of edge weights is minimized.



$G = (V, E)$



$T, \sum_{e \in T} c_e = 50$

# Greedy Algorithms

**Kruskal's algorithm.** Start with  $T = \emptyset$ . Consider edges in ascending order of cost. Insert edge  $e$  in  $T$  unless doing so would create a cycle.

**Reverse-Delete algorithm.** Start with  $T = E$ . Consider edges in descending order of cost. Delete edge  $e$  from  $T$  unless doing so would disconnect  $T$ .

**Prim's algorithm.** Start with some root node  $s$  and greedily grow a tree  $T$  from  $s$  outward. At each step, add the cheapest edge  $e$  to  $T$  that has exactly one endpoint in  $T$ .


**Remark.** All three algorithms produce an MST.



# Mergesort

## Mergesort.

- Divide array into two halves.
- Recursively sort each half.
- Merge two halves to make sorted whole.



Jon von Neumann (1945)

A	L	G	O	R	I	T	H	M	S
---	---	---	---	---	---	---	---	---	---

A	L	G	O	R
---	---	---	---	---

I	T	H	M	S
---	---	---	---	---

divide  $O(1)$

A	G	L	O	R
---	---	---	---	---

H	I	M	S	T
---	---	---	---	---

sort  $2T(n/2)$


A	G	H	I	L	M	O	R	S	T
---	---	---	---	---	---	---	---	---	---

merge  $O(n)$

# Weighted Interval Scheduling

## Weighted interval scheduling problem.

- Job  $j$  starts at  $s_j$ , finishes at  $f_j$ , and has weight or value  $v_j$ .
- Two jobs **compatible** if they don't overlap.
- Goal: find maximum **weight** subset of mutually compatible jobs.




# Weighted Interval Scheduling

**Notation.** Label jobs by finishing time:  $f_1 \leq f_2 \leq \dots \leq f_n$ .

**Def.**  $p(j)$  = largest index  $i < j$  such that job  $i$  is compatible with  $j$ .

**Ex:**  $p(8) = 5$ ,  $p(7) = 3$ ,  $p(2) = 0$ .



# Dynamic Programming: Binary Choice

**Notation.**  $OPT(j)$  = value of optimal solution to the problem consisting of job requests 1, 2, ..., j.


- Case 1:  $OPT$  selects job j.
  - collect profit  $v_j$
  - can't use incompatible jobs  $\{ p(j) + 1, p(j) + 2, \dots, j - 1 \}$
  - must include optimal solution to problem consisting of remaining compatible jobs 1, 2, ...,  $p(j)$
- Case 2:  $OPT$  does not select job j.
  - must include optimal solution to problem consisting of remaining compatible jobs 1, 2, ..., j-1

↖  
↙  
optimal substructure

$$OPT(j) = \begin{cases} 0 & \text{if } j = 0 \\ \max \{ v_j + OPT(p(j)), OPT(j-1) \} & \text{otherwise} \end{cases}$$

# Maximum Flow Problem


Max flow problem. Find s-t flow of maximum value.



# Residual Graph

Original edge:  $e = (u, v) \in E$ .


- Flow  $f(e)$ , capacity  $c(e)$ .



Residual edge.

- "Undo" flow sent.
- $e = (u, v)$  and  $e^R = (v, u)$ .
- Residual capacity:

$$c_f(e) = \begin{cases} c(e) - f(e) & \text{if } e \in E \\ f(e) & \text{if } e^R \in E \end{cases}$$



Residual graph:  $G_f = (V, E_f)$ .

- Residual edges with positive residual capacity.
- $E_f = \{e : f(e) < c(e)\} \cup \{e^R : f(e) > 0\}$ .

## Augmenting path



**Def.** An **augmenting path** is a simple  $s \rightarrow t$  path in the residual graph  $G_f$

**Def.** The **bottleneck capacity** of an augmenting path  $P$  is the minimum residual capacity of any edge in  $P$ .

**Key property.** Let  $f$  be a flow and let  $P$  be an augmenting path in  $G_f$ , then after calling  $f' \leftarrow \text{Augment}(f, c, P)$ , the resulting  $f'$  is flow and

$$v(f') = v(f) + \text{bottleneck}(G_f, P)$$

# Ford-Fulkerson Algorithm





# Augmenting Path Algorithm

```
Augment(f, c, P) {  
    b ← bottleneck(P)  
    foreach e ∈ P {  
        if (e ∈ E) f(e) ← f(e) + b  
        else      f(eR) ← f(eR) - b  
    }  
    return f  
}
```

forward edge

reverse edge

```
Ford-Fulkerson(G, s, t, c) {  
    foreach e ∈ E f(e) ← 0  
    Gf ← residual graph  
  
    while (there exists augmenting path P) {  
        f ← Augment(f, c, P)  
        update Gf  
    }  
    return f  
}
```

# Max-Flow Min-Cut Theorem

**Augmenting path theorem.** Flow  $f$  is a max flow iff there are no augmenting paths.

**Max-flow min-cut theorem.** [Elias-Feinstein-Shannon 1956, Ford-Fulkerson 1956]  
The value of the max flow is equal to the value of the min cut.

**Pf.** We prove both simultaneously by showing TFAE (the following are equivalent) :

- (i) There exists a cut  $(A, B)$  such that  $v(f) = \text{cap}(A, B)$ .
- (ii) Flow  $f$  is a max flow.
- (iii) There is no augmenting path relative to  $f$ .

(i)  $\Rightarrow$  (ii) This was the corollary to weak duality lemma.

(ii)  $\Rightarrow$  (iii) We show contrapositive.


- Let  $f$  be a flow. If there exists an augmenting path, then we can improve  $f$  by sending flow along path.

# Proof of Max-Flow Min-Cut Theorem

(iii)  $\Rightarrow$  (i)

- Let  $f$  be a flow with no augmenting paths.
- Let  $A$  be set of vertices reachable from  $s$  in residual graph.
- By definition of  $A$ ,  $s \in A$ .
- By definition of  $f$ ,  $t \notin A$ .

$$\begin{aligned} v(f) &= \sum_{e \text{ out of } A} f(e) - \sum_{e \text{ in to } A} f(e) \\ &= \sum_{e \text{ out of } A} c(e) \\ &= \text{cap}(A, B) \quad \blacksquare \end{aligned}$$



original network