CS202: COMPUTER ORGANIZATION

Lecture 10

Instruction-Level Parallelism

Recap

- Problem of single-cycle design:
  - Longest delay determines clock period
- Pipelining improves performance by increasing instruction throughput
  - Executes multiple instructions in parallel
  - Each instruction has the same latency
- Hazard: situations that prevent starting the next instruction in the next cycle
  - Structure hazard
  - Data hazard
  - Control hazard

Instruction-Level Parallelism (ILP)

- Instruction-level parallelism: parallelism among instructions
  - Pipelining is one type of ILP: because pipeline executes multiple instructions in parallel
- To increase ILP
  - Deeper pipeline
    - Less work per stage ⇒ shorter clock cycle
  - Multiple issue (start multiple instructions in one clock)
    - Replicate pipeline stages ⇒ multiple pipelines
    - Start multiple instructions per clock cycle
    - CPI (cycle per ins.)< 1, so use Instructions Per Cycle (IPC)
    - E.g., for a 4GHz 4-way multiple-issue, peak rate is 16 BIPS (billion ins. per second), peak CPI = 0.25, peak IPC = 4, but dependencies reduce this in practice.

Pipeline vs. Multiple-issue

- Pipeline:



- Multiple-issue:



Two key responsibilities of multiple issue

- Packaging instructions into issue slots
  - How many instructions can be issued
  - Which instructions should be issued
- Dealing with data and control hazards

Multiple Issue

- Static multiple issue – decision made by compiler
  - Compiler groups instructions to be issued together
  - Packages them into “issue slots”
  - Compiler detects and avoids hazards
- Dynamic multiple issue – decision made by processor
  - CPU examines instruction stream and chooses instructions to issue each cycle
  - Compiler can help by reordering instructions
  - CPU resolves hazards using advanced techniques at runtime

Static Multiple Issue

- Compiler groups instructions into “issue packets”
  - Group of instructions that can be issued on a single cycle
  - Determined by pipeline resources required
- Think of an issue packet as a very long instruction
  - Specifies multiple concurrent operations
  - ⇒ Very Long Instruction Word (VLIW)

MIPS with Static Dual Issue

- Two-issue packets
  - Divide instructions into two types:
    - Type 1: ALU or branch instructions
    - Type 2: load or store instructions
  - In each cycle, execute a type1 and a type2 ins simultaneously
  - 64-bit aligned instructions

Address	Instruction type	Pipeline Stages						
n	ALU/branch	IF	ID	EX	MEM	WB		
n + 4	Load/store	IF	ID	EX	MEM	WB		
n + 8	ALU/branch		IF	ID	EX	MEM	WB	
n + 12	Load/store		IF	ID	EX	MEM	WB	
n + 16	ALU/branch			IF	ID	EX	MEM	WB
n + 20	Load/store			IF	ID	EX	MEM	WB

MIPS with Static Dual Issue



Hazards in the Dual-Issue MIPS

- More instructions executing in parallel
- EX data hazard
  - Forwarding avoided stalls with single-issue
  - Now can't use ALU result in load/store in same packet
    - ```
      add  $t0, $s0, $s1
      load $s2, 0($t0)
      ```
    - Split into two packets, effectively a stall
- Load-use hazard
  - Still one cycle use latency, but now two instructions
- More aggressive scheduling required
      ```

Scheduling Static Multiple Issue

- Compiler must remove some/all hazards
  - Reorder instructions into issue packets
  - No dependencies with a packet
  - Possibly some dependencies between packets
    - Varies between ISAs; compiler must know!
  - Pad with nop if necessary

Scheduling Example

- Schedule this for dual-issue MIPS

```
Loop: lw   $t0, 0($s1)       # $t0=array element
      addu $t0, $t0, $s2     # add scalar in $s2
      sw   $t0, 0($s1)       # store result
      addi $s1, $s1,-4       # decrement pointer
      bne  $s1, $zero, Loop  # branch $s1!=0
```

	ALU/branch	Load/store	cycle
Loop:		lw $t0, 0($s1)	1
			2
			3
			4

Scheduling Example

- Schedule this for dual-issue MIPS

```
Loop: lw   $t0, 0($s1)       # $t0=array element
      addu $t0, $t0, $s2     # add scalar in $s2
      sw   $t0, 0($s1)       # store result
      addi $s1, $s1,-4       # decrement pointer
      bne  $s1, $zero, Loop  # branch $s1!=0
```

	ALU/branch	Load/store	cycle
Loop:		lw $t0, 0($s1)	1
			2
	addu $t0, $t0, $s2		3
			4

Scheduling Example

- Schedule this for dual-issue MIPS

```
Loop: lw   $t0, 0($s1)       # $t0=array element
      addu $t0, $t0, $s2     # add scalar in $s2
      sw   $t0, 0($s1)       # store result
      addi $s1, $s1,-4       # decrement pointer
      bne  $s1, $zero, Loop  # branch $s1!=0
```

	ALU/branch	Load/store	cycle
Loop:		lw $t0, 0($s1)	1
			2
	addu $t0, $t0, $s2		3
		sw $t0, 4($s1)	4

Scheduling Example

- Schedule this for dual-issue MIPS

```
Loop: lw   $t0, 0($s1)       # $t0=array element
      addu $t0, $t0, $s2     # add scalar in $s2
      sw   $t0, 0($s1)       # store result
      addi $s1, $s1,-4       # decrement pointer
      bne  $s1, $zero, Loop  # branch $s1!=0
```

	ALU/branch	Load/store	cycle
Loop:		lw $t0, 0($s1)	1
	addi $s1, $s1,-4		2
	addu $t0, $t0, $s2		3
		sw $t0, 4($s1)	4

Scheduling Example

- Schedule this for dual-issue MIPS

```
Loop: lw   $t0, 0($s1)       # $t0=array element
      addu $t0, $t0, $s2     # add scalar in $s2
      sw   $t0, 0($s1)       # store result
      addi $s1, $s1,-4       # decrement pointer
      bne  $s1, $zero, Loop  # branch $s1!=0
```

	ALU/branch	Load/store	cycle
Loop:		lw $t0, 0($s1)	1
	addi $s1, $s1,-4		2
	addu $t0, $t0, $s2		3
	bne $s1, $zero, Loop	sw $t0, 4($s1)	4

Scheduling Example

- Schedule this for dual-issue MIPS

```
Loop: lw   $t0, 0($s1)       # $t0=array element
      addu $t0, $t0, $s2     # add scalar in $s2
      sw   $t0, 0($s1)       # store result
      addi $s1, $s1,-4       # decrement pointer
      bne  $s1, $zero, Loop  # branch $s1!=0
```

	ALU/branch	Load/store	cycle
Loop:	nop	lw $t0, 0($s1)	1
	addi $s1, $s1,-4	nop	2
	addu $t0, $t0, $s2	nop	3
	bne $s1, $zero, Loop	sw $t0, 4($s1)	4

Scheduling Example

- Schedule this for dual-issue MIPS

```
Loop: lw   $t0, 0($s1)       # $t0=array element
      addu $t0, $t0, $s2     # add scalar in $s2
      sw   $t0, 0($s1)       # store result
      addi $s1, $s1,-4       # decrement pointer
      bne  $s1, $zero, Loop  # branch $s1!=0
```

	ALU/branch	Load/store	cycle
Loop:	nop	lw $t0, 0($s1)	1
	addi $s1, $s1,-4	nop	2
	addu $t0, $t0, $s2	nop	3
	bne $s1, $zero, Loop	sw $t0, 4($s1)	4

  - IPC = 5/4 = 1.25 (c.f. peak IPC = 2)

Loop Unrolling

- Replicate loop body to expose more parallelism
  - Reduces loop-control overhead
- Use different registers per replication
  - Called “register renaming”
  - Avoid loop-carried “anti-dependencies”
    - Store followed by a load of the same register
    - Aka “name dependence”
      - Reuse of a register name

Loop Unrolling Example

- IPC = 14/8 = 1.75
  - Closer to 2, but at cost of registers and code size

	ALU/branch	Load/store	cycle
Loop:	addi $s1, $s1,-16	lw $t0, 0($s1)	1
	nop	lw $t1, 12($s1)	2
	addu $t0, $t0, $s2	lw $t2, 8($s1)	3
	addu $t1, $t1, $s2	lw $t3, 4($s1)	4
	addu $t2, $t2, $s2	sw $t0, 16($s1)	5
	addu $t3, $t3, $s2	sw $t1, 12($s1)	6
	nop	sw $t2, 8($s1)	7
	bne $s1, $zero, Loop	sw $t3, 4($s1)	8

- Why do we choose to execute 4 intructions in a loop? How about 3 or 5?

Dynamic Multiple Issue

- The decision is made by the processor during execution
- also called “Superscalar” processors
- CPU decides whether to issue 0, 1, 2, … each cycle
  - Avoiding structural and data hazards
- No need for compiler scheduling
  - Though it may still help
  - Code semantics ensured by the CPU

Dynamic Pipeline Scheduling

- Hardware support for reordering the order of instruction execution
- Allow the CPU to execute instructions out of order to avoid stalls
  - But commit result to registers in order
- Example

```
lw    $t0, 20($s2)
addu  $t1, $t0, $t2
sub   $s4, $s4, $t3
slti  $t5, $s4, 20
```

  - Can start sub while addu is waiting for lw

Dynamically Scheduled CPU



Why Do Dynamic Scheduling?

- Why not just let the compiler schedule code?
- Not all stalls are predicable
  - e.g., cache misses
- Can’t always schedule around branches
  - Branch outcome is dynamically determined
- Different implementations of an ISA have different latencies and hazards

Speculation

- “Guess” what to do with an instruction
  - Start operation as soon as possible
  - Check whether guess was right
    - If so, complete the operation
    - If not, roll-back and do the right thing
- Common to static and dynamic multiple issue
- Examples
  - Speculate on branch outcome
    - Roll back if path taken is different
  - Speculate on load
    - Roll back if location is updated

Compiler/Hardware Speculation

- Compiler can reorder instructions
  - e.g., move load before branch
  - Can include “fix-up” instructions to recover from incorrect guess
- Hardware can look ahead for instructions to execute
  - Buffer results until it determines they are actually needed
  - Flush buffers on incorrect speculation

Speculation and Exceptions

- What if exception occurs on a speculatively executed instruction?
  - e.g., speculative load before null-pointer check
- Static speculation
  - Can add ISA support for deferring exceptions
- Dynamic speculation
  - Can buffer exceptions until instruction completion (which may not occur)

Does Multiple Issue Work?

- Yes, but not as much as we'd like
- Programs have real dependencies that limit ILP
  - Some dependencies are hard to eliminate
    - e.g., pointer aliasing
  - Some parallelism is hard to expose
    - Limited window size during instruction issue
  - Memory delays and limited bandwidth
    - Hard to keep pipelines full
- Speculation can help if done well

Power Efficiency

- Complexity of dynamic scheduling and speculations requires power
- Multiple simpler cores may be better

Microprocessor	Year	Clock Rate	Pipeline Stages	Issue width	Out-of-order/ Speculation	Cores	Power
i486	1989	25MHz	5	1	No	1	5W
Pentium	1993	66MHz	5	2	No	1	10W
Pentium Pro	1997	200MHz	10	3	Yes	1	29W
P4 Willamette	2001	2000MHz	22	3	Yes	1	75W
P4 Prescott	2004	3600MHz	31	3	Yes	1	103W
Core	2006	2930MHz	14	4	Yes	2	75W
Core i5 Nehalem	2010	3300MHz	14	4	Yes	1	87W
Core i5 Ivy Bridge	2012	3400MHz	14	4	Yes	8	77W

Cortex A8 and Intel i7

Processor	ARM A8	Intel Core i7 920
Market	Personal Mobile Device	Server, cloud
Thermal design power	2 Watts	130 Watts
Clock rate	1 GHz	2.66 GHz
Cores/Chip	1	4
Floating point?	No	Yes
Multiple issue?	Dynamic	Dynamic
Peak instructions/clock cycle	2	4
Pipeline stages	14	14
Pipeline schedule	Static in-order	Dynamic out-of-order with speculation
Branch prediction	2-level	2-level
1st level caches/core	32 KiB I, 32 KiB D	32 KiB I, 32 KiB D
2nd level caches/core	128-1024 KiB	256 KiB
3rd level caches (shared)	-	2- 8 MB

ARM Cortex-A8 Pipeline



ARM Cortex-A8 Performance



Core i7 Pipeline



Core i7 Performance



Core i7 Performance



Fallacies

- Pipelining is easy (!)
  - The basic idea is easy
  - The devil is in the details
    - e.g., detecting data hazards
- Pipelining is independent of technology
  - So why haven't we always done pipelining?
  - More transistors make more advanced techniques feasible
  - Pipeline-related ISA design needs to take account of technology trends
    - e.g., predicated instructions

Pitfalls

- Poor ISA design can make pipelining harder
  - e.g., complex instruction sets (VAX, IA-32)
    - Significant overhead to make pipelining work
    - IA-32 micro-op approach
  - e.g., complex addressing modes
    - Register update side effects, memory indirection
  - e.g., delayed branches
    - Advanced pipelines have long delay slots

Concluding Remarks

- ISA influences design of datapath and control
- Datapath and control influence design of ISA
- Pipelining improves instruction throughput using parallelism
  - More instructions completed per second
  - Latency for each instruction not reduced
- Hazards: structural, data, control
- Multiple issue and dynamic scheduling (ILP)
  - Dependencies limit achievable parallelism
  - Complexity leads to the power wall