

2022 Spring ME112 Introduction to MATLAB Final Exam

12011327 Liu Leqi

Problem 1

```
clear all; clc;  
R = 1:0.1:1000;  
L = 2000./R;  
cost = 50*pi*R+40*(2*L+4*R);  
fprintf('The minimum cost is %.2f RMB.',min(cost));
```


The minimum cost is 14245.40 RMB.

```
idx = find(cost==min(cost));  
fprintf('The value of R is %.2f meter, L is %.2f meter',R(idx),2000/R(idx));
```

The value of R is 22.50 meter, L is 88.89 meter

Problem 2


```
clear all; clc;  
% numerical  
[tnum,ynum] = ode23(@vdp1, [0 1.3], [1;1]);  
plot(tnum,ynum(:,1),tnum,ynum(:,2));  
legend('x-t','y-t');  
hold off;
```



```

% symbolic
syms x(t) y(t)
equ = [diff(x,t)+5*x+y==exp(t), diff(y,t)-x-3*y==0];
cond = [x(0)==1, y(0)==1];
[xsol(t), ysol(t)] = dsolve(equ,cond);
ezplot(xsol, [0,1.3]);
hold on;
ezplot(ysol, [0,1.3]);
legend('x-t', 'y-t');
hold off;


```



```

% compare
ex = ynum(:,1)-double(subs(xsol,t,linspace(0,1.3,21)))';
ey = ynum(:,2)-double(subs(ysol,t,linspace(0,1.3,21)))';
tt = linspace(0,1.3,21);
plot(tt,ex,tt,ey);
legend('ex-t', 'ey-t');

```



Problem 3

```
clear all; clc;
A = [1 1 -1 -1 0 1;
     0 0 1 1 -1 0;
     0 0 0 0 1 1;
     0 0 0 0 1 -2;
     0 0 1 -2 1 0;
     5 -2 -4 -1 0 1];
resT = zeros(6,1);
resW = 0;
for W = 1:1:600
    B = [W; W; W; 0; 0; 0];
    T = A\B;
    if all(T(T>0))
        if T(1)<=1300 && T(2)<=1300 && T(3)<=500 && T(4)<=500 && T(5)<=300 && T(6)<=300 && resW < W
            resT = T;
            resW = W;
        end
    end
end
fprintf('The maximum W is %.2f N.',resW);
```

The maximum W is 450.00 N.

Problem 4

```
clear all; clc;
% (a)
syms x y b
equc1 = ((x-3)^2+(y-5)^2==4);
equc2 = ((x-5)^2+(y-3)^2==b^2);
res = solve([equc1, equc2], [x y]);
fprintf('The coordinates of the intersection points (x1,y1) and (x2,y2) are: \n');
```

The coordinates of the intersection points (x1,y1) and (x2,y2) are:

```
fprintf('x1='); disp(res.x(1));
```

x1=

$$\frac{9}{2} - \frac{\sqrt{\frac{(-b^2 + 4b + 4)(b^2 + 4b - 4)}{16}}}{2} - \frac{b^2}{8}$$

```
fprintf('y1='); disp(res.y(1));
```

y1=

$$\frac{b^2}{8} - \frac{\sqrt{\frac{(-b^2 + 4b + 4)(b^2 + 4b - 4)}{16}}}{2} + \frac{7}{2}$$

```
fprintf('x2='); disp(res.x(2));
```

x2=

$$\frac{\sqrt{\frac{(-b^2 + 4b + 4)(b^2 + 4b - 4)}{16}}}{2} - \frac{b^2}{8} + \frac{9}{2}$$

```
fprintf('y2='); disp(res.y(2));
```

y2=

$$\frac{b^2}{8} + \frac{\sqrt{\frac{(-b^2 + 4b + 4)(b^2 + 4b - 4)}{16}}}{2} + \frac{7}{2}$$

```
% (b)
```

```
res_b = subs(res,b,sqrt(3));
```

```
fprintf('For b=sqrt(3), the coordinates of the intersection points (x1,y1) and (x2,y2) are: \n');
```

For b=sqrt(3), the coordinates of the intersection points (x1,y1) and (x2,y2) are:

```
fprintf('x1='); disp(res_b.x(1));
```

x1=

$$\frac{33}{8} - \frac{\sqrt{\frac{(4\sqrt{3}-1)(4\sqrt{3}+1)}{16}}}{2}$$

```
fprintf('y1='); disp(res_b.y(1));
```

y1=

$$\frac{31}{8} - \frac{\sqrt{\frac{(4\sqrt{3}-1)(4\sqrt{3}+1)}{16}}}{2}$$

```
fprintf('x2='); disp(res_b.x(2));
```

x2=

$$\frac{\sqrt{\frac{(4\sqrt{3}-1)(4\sqrt{3}+1)}{16}}}{2} + \frac{33}{8}$$

```
fprintf('y2='); disp(res_b.y(2));
```

y2=

$$\frac{\sqrt{\frac{(4\sqrt{3}-1)(4\sqrt{3}+1)}{16}}}{2} + \frac{31}{8}$$

Functions

```
function yp = vdp1(t,y)
yp = [exp(t)-5*y(1)-y(2); y(1)+3*y(2)];
end
```