

HW5

25. *Shannon code.* Consider the following method for generating a code for a random variable X which takes on m values $\{1, 2, \dots, m\}$ with probabilities p_1, p_2, \dots, p_m . Assume that the probabilities are ordered so that $p_1 \geq p_2 \geq \dots \geq p_m$. Define

$$F_i = \sum_{k=1}^{i-1} p_k, \quad (5.155)$$

the sum of the probabilities of all symbols less than i . Then the codeword for i is the number $F_i \in [0, 1]$ rounded off to l_i bits, where $l_i = \lceil \log \frac{1}{p_i} \rceil$.

- (a) Show that the code constructed by this process is prefix-free and the average length satisfies

$$H(X) \leq L < H(X) + 1. \quad (5.156)$$

- (b) Construct the code for the probability distribution (0.5, 0.25, 0.125, 0.125).

2. *How many fingers has a Martian?* Let

$$S = \begin{pmatrix} S_1, \dots, S_m \\ p_1, \dots, p_m \end{pmatrix}.$$

The S_i 's are encoded into strings from a D -symbol output alphabet in a uniquely decodable manner. If $m = 6$ and the codeword lengths are $(l_1, l_2, \dots, l_6) = (1, 1, 2, 3, 2, 3)$, find a good lower bound on D . You may wish to explain the title of the problem.