



# CSE5014 CRYPTOGRAPHY AND NETWORK SECURITY

Dr. QI WANG

Department of Computer Science and Engineering

Office: Room413, CoE South Tower

Email: [wangqi@sustech.edu.cn](mailto:wangqi@sustech.edu.cn)

# What does “pseudorandom” mean?

- Informal: **cannot** be distinguished from **uniform** (“random”)



# What does “pseudorandom” mean?

- Informal: **cannot** be distinguished from **uniform** (“random”)
- Which of the following is **pseudorandom**?
  - 0101010101010101
  - 0010111011100110
  - 0000000000000000

# What does “pseudorandom” mean?

- Informal: **cannot** be distinguished from **uniform** (“random”)
- Which of the following is **pseudorandom**?
  - 0101010101010101
  - 0010111011100110
  - 0000000000000000
- *Pseudorandomness* is a property of a *distribution*, **not** a string.



# Pseudorandomness

- Fix some distribution  $D$  on  $n$ -bit strings
  - $x \leftarrow D$  means “sample  $x$  according to  $D$ ”



# Pseudorandomness

- Fix some distribution  $D$  on  $n$ -bit strings
  - $x \leftarrow D$  means “sample  $x$  according to  $D$ ”
- Historically,  $D$  was considered *pseudorandom* if it “passed a bunch of statistical tests”
  - $\Pr_{x \leftarrow D}[1^{st} \text{ bit of } x \text{ is } 1] \approx 1/2$
  - $\Pr_{x \leftarrow D}[\text{parity of } x \text{ is } 1] \approx 1/2$
  - $\Pr_{x \leftarrow D}[A_i(x) = 1] \approx \Pr_{x \leftarrow U_n}[A_i(x) = 1]$   
for  $i = 1, \dots, 20$



# Pseudorandomness

- Fix some distribution  $D$  on  $n$ -bit strings
  - $x \leftarrow D$  means “sample  $x$  according to  $D$ ”
- Historically,  $D$  was considered *pseudorandom* if it “passed a bunch of statistical tests”
  - $\Pr_{x \leftarrow D}[1^{\text{st}} \text{ bit of } x \text{ is } 1] \approx 1/2$
  - $\Pr_{x \leftarrow D}[\text{parity of } x \text{ is } 1] \approx 1/2$
  - $\Pr_{x \leftarrow D}[A_i(x) = 1] \approx \Pr_{x \leftarrow U_n}[A_i(x) = 1]$   
for  $i = 1, \dots, 20$

This is **not** sufficient, since it is **not** possible to know what statistical test an attacker will use.



# Pseudorandomness

- Cryptographic definition of *pseudorandomness*
  - $D$  is *pseudorandom* if it passes all *efficient* statistical tests





# Pseudorandomness

- Cryptographic definition of *pseudorandomness*
  - $D$  is *pseudorandom* if it passes all *efficient* statistical tests

(Concrete) Let  $D$  be a distribution on  $p$ -bit strings.  $D$  is  $(t, \epsilon)$ -*pseudorandom* if for all  $A$  running in time **at most**  $t$ ,

$$|\Pr_{x \leftarrow D}[A(x) = 1] - \Pr_{x \leftarrow U_p}[A(x) = 1]| \leq \epsilon$$



# Pseudorandomness

- Cryptographic definition of *pseudorandomness*
  - $D$  is *pseudorandom* if it passes all *efficient* statistical tests

(Concrete) Let  $D$  be a distribution on  $p$ -bit strings.  $D$  is  $(t, \epsilon)$ -*pseudorandom* if for all  $A$  running in time **at most**  $t$ ,

$$|\Pr_{x \leftarrow D}[A(x) = 1] - \Pr_{x \leftarrow U_p}[A(x) = 1]| \leq \epsilon$$

(Asymptotic) *Security parameter*  $n$ , polynomial  $p$

**Definiton 3.2** Let  $D_n$  be a distribution over  $p(n)$ -bit strings.  $\{D_n\}$  is *pseudorandom* if for all probabilistic, polynomial-time (PPT) distinguishers  $A$ , there is a **negligible** function  $\epsilon$  such that

$$|\Pr_{x \leftarrow D_n}[A(x) = 1] - \Pr_{x \leftarrow U_{p(n)}}[A(x) = 1]| \leq \epsilon(n)$$

# Pseudorandom generators (PRGs)

- A *PRG* is an *efficient*, *deterministic* algorithm that expands a *short, uniform seed* into a *longer, pseudorandom* output



# Pseudorandom generators (PRGs)


- A *PRG* is an *efficient*, *deterministic* algorithm that expands a *short, uniform seed* into a *longer, pseudorandom* output
  - Useful whenever you have a “*small*” number of true random bits, and want lots of “*random-looking*” bits



# Pseudorandom generators (PRGs)

- A *PRG* is an *efficient*, *deterministic* algorithm that expands a *short, uniform seed* into a *longer, pseudorandom* output
  - Useful whenever you have a “*small*” number of true random bits, and want lots of “*random-looking*” bits

Let  $G$  be a deterministic, poly-time algorithm that is *expanding*, i.e.,  $|G(x)| = p(|x|) > |x|$ .



# Pseudorandom generators (PRGs)

- A *PRG* is an **efficient**, **deterministic** algorithm that expands a *short, uniform seed* into a *longer, pseudorandom* output
  - Useful whenever you have a “**small**” number of true random bits, and want lots of “**random-looking**” bits

Let  $G$  be a deterministic, poly-time algorithm that is *expanding*, i.e.,  $|G(x)| = p(|x|) > |x|$ .

$G$  defines a sequence of distributions.

- $D_n$  = the distribution on  $p(n)$ -bit strings defined by choosing  $x \leftarrow U_n$  and outputting  $G(x)$
- $\Pr_{D_n}[y] = \Pr_{U_n}[G(x) = y] = \sum_{x: G(x)=y} \Pr_{U_n}[x]$ 
$$= \sum_{x: G(x)=y} 2^{-n}$$
$$= |\{x : G(x) = y\}| / 2^n$$



- A *PRG* is an *efficient*, *deterministic* algorithm that expands a *short, uniform seed* into a *longer, pseudorandom* output

Let  $G$  be a deterministic, poly-time algorithm that is *expanding*, i.e.,  $|G(x)| = p(|x|) > |x|$ .

- For all *efficient* distinguishers  $A$ , there is a *negligible* function  $\epsilon$  such that

$$|\Pr_{x \leftarrow U_n}[A(G(x)) = 1] - \Pr_{y \leftarrow U_{p(n)}}[A(y) = 1]| \leq \epsilon(n)$$

**No** efficient  $A$  can distinguish whether it is given  $G(x)$  (for uniform  $x$ ) or a uniform string  $y$ !

- For all **efficient** distinguishers  $A$ , there is a **negligible** function  $\epsilon$  such that

$$|\Pr_{x \leftarrow U_n}[A(G(x)) = 1] - \Pr_{y \leftarrow U_{p(n)}}[A(y) = 1]| \leq \epsilon(n)$$

**No** efficient  $A$  can distinguish whether it is given  $G(x)$  (for uniform  $x$ ) or a uniform string  $y$ !



- For all **efficient** distinguishers  $A$ , there is a **negligible** function  $\epsilon$  such that

$$|\Pr_{x \leftarrow U_n}[A(G(x)) = 1] - \Pr_{y \leftarrow U_{p(n)}}[A(y) = 1]| \leq \epsilon(n)$$

**No** efficient  $A$  can distinguish whether it is given  $G(x)$  (for uniform  $x$ ) or a uniform string  $y$ !

- PRGs are **limited**
  - They have **fixed-length** output
  - They produce the entire output in “**one shot**”
  - In practice, PRGs are based on **stream ciphers**
  - Can be viewed as producing an “**unbounded**” stream of pseudorandom bits, on demand
  - Will revisit later


# Do PRGs/stream ciphers exist?

- We **don't** know ...
  - We will **assume** certain algorithms are PRGs
  - Can construct PRGs from **weaker** assumptions (later)




# Do PRGs/stream ciphers exist?

- We **don't** know ...
  - We will **assume** certain algorithms are PRGs
  - Can construct PRGs from **weaker** assumptions (later)



## Example

$s = (000100110101111)^{15}$




$$LC(s) = 4$$

$$P_s(x) = x^4 + x + 1$$

# Practical “PRGs”

## ■ RC4

```
i := 0
j := 0
while GeneratingOutput:
  i := (i + 1) mod 256
  j := (j + S[i]) mod 256
  swap values of S[i] and S[j]
  K := S[(S[i] + S[j]) mod 256]
  output K
endwhile
```



## Blum-Blum-Shub

```
num_outputted = 0;
while num_outputted < m:
  X := X*X mod N
  num_outputted := num_outputted + 1
  output least-significant-bit(X)
```

SIAM J. COMPUT.  
Vol. 15, No. 2, May 1986

© 1986 Society for Industrial and Applied Mathematics  
003

### A SIMPLE UNPREDICTABLE PSEUDO-RANDOM NUMBER GENERATOR\*

L. BLUM†, M. BLUM‡ AND M. SHUB§

**Abstract.** Two closely-related pseudo-random sequence generators are presented: The  $1/P$  generator, with input  $P$  a prime, outputs the quotient digits obtained on dividing 1 by  $P$ . The  $x^2 \bmod N$  generator with inputs  $N, x_0$  (where  $N = P \cdot Q$  is a product of distinct primes, each congruent to 3 mod 4, and  $x_0$  is a quadratic residue mod  $N$ ), outputs  $b_0 b_1 b_2 \dots$  where  $b_i$  = parity ( $x_i$ ) and  $x_{i+1} = x_i^2 \bmod N$ .

From short seeds each generator efficiently produces long well-distributed sequences. Moreover, both generators have computationally hard problems at their core. The first generator's sequences, however, are *completely predictable* (from any small segment of  $2|P|+1$  consecutive digits one can infer the “seed,”  $P$ , and continue the sequence backwards and forwards), whereas the second, under a certain intractability assumption, is *unpredictable* in a precise sense. The second generator has additional interesting properties: from knowledge of  $x_0$  and  $N$  but *not*  $P$  or  $Q$ , one can generate the sequence forwards, but, under the above-mentioned intractability assumption, one can *not* generate the sequence backwards. From the additional knowledge of  $P$  and  $Q$ , one *can* generate the sequence backwards; one can even “jump” about from any point in the sequence to any other. Because of these properties, the  $x^2 \bmod N$  generator promises many interesting applications, e.g., to public-key cryptography. To use these generators in practice, an analysis is needed of various properties of these sequences such as their periods. This analysis is begun here.

**Key words.** random, pseudo-random, Monte Carlo, computational complexity, secure transactions, public-key encryption, cryptography, one-time pad, Jacobi symbol, quadratic residuacity

# Where things stand

- We saw that there are some inherent **limitations** if we want *perfect security*
  - In particular, key must be as **long** as the message



# Where things stand


- We saw that there are some inherent **limitations** if we want *perfect security*
  - In particular, key must be as **long** as the message

We defined *computational security*, a **relaxed** notion of security



**Q**: Can we overcome prior limitations?



# Recall: one-time pad




# Recall: one-time pad






# Pseudo one-time pad



# Pseudo one-time pad



- Let  $G$  be a deterministic, with  $|G(k)| = p(|k|)$   
 $Gen(1^n)$ : output uniform  $n$ -bit key  $k$ 
  - Security parameter  $n \Rightarrow$  message space  $\{0, 1\}^{p(n)}$ $Enc_k(m)$ : output  $G(k) \oplus m$   
 $Dec_k(m)$ : output  $G(k) \oplus c$

# Proof by reduction

- 1. Assume that  $G$  is a *PRG*
  - 2. Assume toward a **contradiction** that there is an **efficient attacker**  $A$  who “breaks” the pseudo-OTP scheme
  - 3. Use  $A$  as a **subroutine** to build an efficient  $D$  that “breaks” *pseudorandomness* of  $G$ 
    - By assumption, **no such**  $D$  exists!
- ⇒ **No** such  $A$  can exist

# Proof by reduction

- 1. Assume that  $G$  is a *PRG*
  - 2. Assume toward a **contradiction** that there is an **efficient attacker**  $A$  who “breaks” the pseudo-OTP scheme
  - 3. Use  $A$  as a **subroutine** to build an efficient  $D$  that “breaks” *pseudorandomness* of  $G$ 
    - By assumption, **no such**  $D$  exists!
- ⇒ **No** such  $A$  can exist

**Theorem 3.3** If  $G$  is a pseudorandom generator (PRG), then the pseudo one-time pad (pseudo-OTP)  $\Pi$  is *EAV-secure* (i.e., *computationally secure*)



# The reduction

- **Proof.**



# The reduction

## ■ Proof.

Fix  $\Pi$ ,  $A$

Define a randomized experiment  $\text{PrivK}_{A,\Pi}(n)$ :

1.  $A(1^n)$  outputs  $m_0, m_1 \in \{0, 1\}^*$  of equal length
2.  $k \leftarrow \text{Gen}(1^n)$ ,  $b \leftarrow \{0, 1\}$ ,  $c \leftarrow \text{Enc}_k(m_b)$
3.  $b' \leftarrow A(c)$

Adversary  $A$  *succeeds* if  $b = b'$ , and we say the experiment evaluates to 1 in this case.

**Definition 3.1**  $\Pi$  is *computationally indistinguishable* (aka *EAV-secure*) if for *all PPT* attackers (algorithms)  $A$ , there is a *negligible* function  $\epsilon$  such that

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] \leq 1/2 + \epsilon(n)$$



# The reduction

## ■ Proof.

**Definition 3.1**  $\Pi$  is *computationally indistinguishable* (aka *EAV-secure*) if for **all PPT** attackers (algorithms)  $A$ , there is a *negligible* function  $\epsilon$  such that

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] \leq 1/2 + \epsilon(n)$$

# The reduction

## ■ Proof.

**Definition 3.1**  $\Pi$  is *computationally indistinguishable* (aka *EAV-secure*) if for **all PPT** attackers (algorithms)  $A$ , there is a *negligible* function  $\epsilon$  such that

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] \leq 1/2 + \epsilon(n)$$

Suppose to the **contrary** that there exists an **efficient** attacker  $A$ , s.t.

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] > 1/2 + 1/\text{poly}(n)$$



# The reduction

## ■ Proof.

**Definition 3.1**  $\Pi$  is *computationally indistinguishable* (aka *EAV-secure*) if for **all PPT** attackers (algorithms)  $A$ , there is a *negligible* function  $\epsilon$  such that

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] \leq 1/2 + \epsilon(n)$$

Suppose to the **contrary** that there exists an **efficient** attacker  $A$ , s.t.

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] > 1/2 + 1/\text{poly}(n)$$

This means,  $\Pr[A(\text{Enc}_{U_n}(m)) = 1] - \Pr[A(U_{p(n)}) = 1] > 1/\text{poly}(n)$

# The reduction

## ■ Proof.

**Definition 3.1**  $\Pi$  is *computationally indistinguishable* (aka *EAV-secure*) if for **all PPT** attackers (algorithms)  $A$ , there is a *negligible* function  $\epsilon$  such that

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] \leq 1/2 + \epsilon(n)$$

Suppose to the **contrary** that there exists an **efficient** attacker  $A$ , s.t.

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] > 1/2 + 1/\text{poly}(n)$$

This means,  $\Pr[A(\text{Enc}_{U_n}(m)) = 1] - \Pr[A(U_{p(n)}) = 1] > 1/\text{poly}(n)$

$$|\Pr[A(G(U_n) \oplus m) = 1] - \Pr[A(U_{p(n)}) = 1]| > 1/\text{poly}(n)$$

# The reduction

## ■ Proof.

**Definition 3.1**  $\Pi$  is *computationally indistinguishable* (aka *EAV-secure*) if for **all PPT** attackers (algorithms)  $A$ , there is a *negligible* function  $\epsilon$  such that

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] \leq 1/2 + \epsilon(n)$$

Suppose to the **contrary** that there exists an **efficient** attacker  $A$ , s.t.

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] > 1/2 + 1/\text{poly}(n)$$

This means,  $\Pr[A(\text{Enc}_{U_n}(m)) = 1] - \Pr[A(U_{p(n)}) = 1] > 1/\text{poly}(n)$

$$|\Pr[A(G(U_n) \oplus m) = 1] - \Pr[A(U_{p(n)}) = 1]| > 1/\text{poly}(n)$$

$\text{Enc}_{U_n}()$  is **not pseudorandom**

# The reduction

## ■ Proof.

**Definition 3.1**  $\Pi$  is *computationally indistinguishable* (aka *EAV-secure*) if for **all PPT** attackers (algorithms)  $A$ , there is a *negligible* function  $\epsilon$  such that

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] \leq 1/2 + \epsilon(n)$$

Suppose to the **contrary** that there exists an **efficient** attacker  $A$ , s.t.

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] > 1/2 + 1/\text{poly}(n)$$

This means,  $\Pr[A(\text{Enc}_{U_n}(m)) = 1] - \Pr[A(U_{p(n)}) = 1] > 1/\text{poly}(n)$

$$|\Pr[A(G(U_n) \oplus m) = 1] - \Pr[A(U_{p(n)}) = 1]| > 1/\text{poly}(n)$$

$\text{Enc}_{U_n}()$  is **not pseudorandom**

Define  $D : \{0, 1\}^{p(n)} \rightarrow \{0, 1\}$  as:  $D(y) = A(y \oplus m)$ , which means  $A(z) = D(z \oplus m)$ . Note that  $D$  is also **efficient**. But we have

$$|\Pr[D(G(U_n)) = 1] - \Pr[D(U_{p(n)} \oplus m) = 1]| \geq 1/\text{poly}(n)$$

# The reduction

## ■ Proof.

**Definition 3.1**  $\Pi$  is *computationally indistinguishable* (aka *EAV-secure*) if for **all PPT** attackers (algorithms)  $A$ , there is a *negligible* function  $\epsilon$  such that

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] \leq 1/2 + \epsilon(n)$$

Suppose to the **contrary** that there exists an **efficient** attacker  $A$ , s.t.

$$\Pr[\text{PrivK}_{A,\Pi}(n) = 1] > 1/2 + 1/\text{poly}(n)$$

This means,  $\Pr[A(\text{Enc}_{U_n}(m)) = 1] - \Pr[A(U_{p(n)}) = 1] > 1/\text{poly}(n)$

$$|\Pr[A(G(U_n) \oplus m) = 1] - \Pr[A(U_{p(n)}) = 1]| > 1/\text{poly}(n)$$

$\text{Enc}_{U_n}()$  is **not pseudorandom**

Define  $D : \{0, 1\}^{p(n)} \rightarrow \{0, 1\}$  as:  $D(y) = A(y \oplus m)$ , which means  $A(z) = D(z \oplus m)$ . Note that  $D$  is also **efficient**. But we have

$$|\Pr[D(G(U_n)) = 1] - \Pr[D(U_{p(n)} \oplus m) = 1]| \geq 1/\text{poly}(n)$$

Since  $U_{p(n)} \oplus m \equiv U_{p(n)}$ , this **contradicts** that  $G$  is a PRG.

# Proof by reduction (alternatively)

- 1. Assume that  $G$  is a *PRG*
- 2. Fix some *arbitrary*, efficient  $A$  attacking the pseudo-OTP scheme
- 3. Use  $A$  as a *subroutine* to build an efficient  $D$  attacking  $G$ 
  - Relate the distinguishing probability of  $D$  to the success probability of  $A$
- 4. By assumption, the distinguishing probability of  $D$  *must be negligible*



# Proof by reduction (alternatively)

- 1. Assume that  $G$  is a *PRG*
- 2. Fix some *arbitrary*, efficient  $A$  attacking the pseudo-OTP scheme
- 3. Use  $A$  as a *subroutine* to build an efficient  $D$  attacking  $G$ 
  - Relate the distinguishing probability of  $D$  to the success probability of  $A$
- 4. By assumption, the distinguishing probability of  $D$  *must be negligible*
  - $\Rightarrow$  *Bound* the success probability of  $A$



# The reduction

- Let  $\mu(n) = \Pr[PrivK_{A,\Pi}(n) = 1]$





# The reduction

- Let  $\mu(n) = \Pr[\text{PrivK}_{A,\Pi}(n) = 1]$

If distribution of  $y$  is **pseudorandom**, then the view of  $A$  is *exactly* the same as in  $\text{PrivK}_{A,\Pi}(n)$

$$\Rightarrow \Pr_{x \leftarrow U_n}[D(G(x)) = 1] = \mu(n)$$

# The reduction

- Let  $\mu(n) = \Pr[\text{PrivK}_{A,\Pi}(n) = 1]$

If distribution of  $y$  is **pseudorandom**, then the view of  $A$  is *exactly* the same as in  $\text{PrivK}_{A,\Pi}(n)$

$$\Rightarrow \Pr_{x \leftarrow U_n}[D(G(x)) = 1] = \mu(n)$$

If distribution of  $y$  is **uniform**, then  $A$  succeeds with probability exactly  $1/2$

$$\Rightarrow \Pr_{y \leftarrow U_{p(n)}}[D(y) = 1] = 1/2$$

# The reduction

- Let  $\mu(n) = \Pr[\text{PrivK}_{A,\Pi}(n) = 1]$

If distribution of  $y$  is **pseudorandom**, then the view of  $A$  is *exactly* the same as in  $\text{PrivK}_{A,\Pi}(n)$

$$\Rightarrow \Pr_{x \leftarrow U_n}[D(G(x)) = 1] = \mu(n)$$

If distribution of  $y$  is **uniform**, then  $A$  succeeds with probability exactly  $1/2$

$$\Rightarrow \Pr_{y \leftarrow U_{p(n)}}[D(y) = 1] = 1/2$$

Since  $G$  is pseudorandom,

$$|\mu(n) - 1/2| \leq \text{negl}(n)$$

# The reduction

- Let  $\mu(n) = \Pr[\text{PrivK}_{A,\Pi}(n) = 1]$

If distribution of  $y$  is **pseudorandom**, then the view of  $A$  is *exactly* the same as in  $\text{PrivK}_{A,\Pi}(n)$

$$\Rightarrow \Pr_{x \leftarrow U_n}[D(G(x)) = 1] = \mu(n)$$

If distribution of  $y$  is **uniform**, then  $A$  succeeds with probability exactly  $1/2$

$$\Rightarrow \Pr_{y \leftarrow U_{p(n)}}[D(y) = 1] = 1/2$$

Since  $G$  is pseudorandom,

$$|\mu(n) - 1/2| \leq \text{negl}(n)$$

$$\Rightarrow \Pr[\text{PrivK}_{A,\Pi}(n) = 1] \leq 1/2 + \text{negl}(n)$$

# Have we gained anything?

- YES: the pseudo-OTP has a key **shorter** than the message
  - $n$  bits vs.  $p(n)$  bits



# Have we gained anything?

- YES: the pseudo-OTP has a key **shorter** than the message
  - $n$  bits vs.  $p(n)$  bits

Recall: Perfect security has two **limitations**

- Key as long as the message
- Key can only be used once



# Have we gained anything?

- YES: the pseudo-OTP has a key **shorter** than the message
  - $n$  bits vs.  $p(n)$  bits

Recall: Perfect security has two **limitations**

- Key as long as the message
- Key can only be used once

The pseudo OTP **still has** the second limitation (for the same reason as the OTP)

# Have we gained anything?

- YES: the pseudo-OTP has a key **shorter** than the message
  - $n$  bits vs.  $p(n)$  bits

Recall: Perfect security has two **limitations**

- Key as long as the message
- Key can only be used once

The pseudo OTP **still has** the second limitation (for the same reason as the OTP)

How can we circumvent the second limitation?





# But first...

- Develop an appropriate security *definition*
  - Security goal
  - Threat model

# But first...


- Develop an appropriate security *definition*
  - Security goal
  - Threat model

We will keep the security goal the same, but **strengthen** the threat model

# But first...

- Develop an appropriate security *definition*
  - Security goal
  - Threat model


We will keep the security goal the same, but **strengthen** the threat model



# But first...

- Develop an appropriate security *definition*
  - Security goal
  - Threat model

We will keep the security goal the same, but **strengthen** the threat model



# A formal definition

- Fix  $\Pi$ ,  $A$

Define a randomized experiment  $\text{PrivK}_{A,\Pi}^{\text{mult}}(n)$ :

1.  $A(1^n)$  outputs two **vectors**  $(m_{0,1}, \dots, m_{0,t})$  and  $(m_{1,1}, \dots, m_{1,t})$   
Required that  $|m_{0,i}| = |m_{1,i}|$  for all  $i$
2.  $k \leftarrow \text{Gen}(1^n)$ ,  $b \leftarrow \{0, 1\}$ , for all  $i$ ,  $c_i \leftarrow \text{Enc}_k(m_{b,i})$
3.  $b' \leftarrow A(c_1, \dots, c_t)$

Adversary  $A$  **succeeds** if  $b = b'$ , and the experiment evaluates to **1** in this case.



# A formal definition

- Fix  $\Pi$ ,  $A$

Define a randomized experiment  $\text{PrivK}_{A,\Pi}^{\text{mult}}(n)$ :

1.  $A(1^n)$  outputs two **vectors**  $(m_{0,1}, \dots, m_{0,t})$  and  $(m_{1,1}, \dots, m_{1,t})$   
Required that  $|m_{0,i}| = |m_{1,i}|$  for all  $i$
2.  $k \leftarrow \text{Gen}(1^n)$ ,  $b \leftarrow \{0, 1\}$ , for all  $i$ ,  $c_i \leftarrow \text{Enc}_k(m_{b,i})$
3.  $b' \leftarrow A(c_1, \dots, c_t)$

Adversary  $A$  **succeeds** if  $b = b'$ , and the experiment evaluates to **1** in this case.

**Definition 3.4**  $\Pi$  is **multiple-message indistinguishable** if for **all PPT** attackers  $A$ , there is a **negligible** function  $\epsilon$  such that

$$\Pr[\text{PrivK}_{A,\Pi}^{\text{mult}}(n) = 1] \leq 1/2 + \epsilon(n)$$



# A formal definition

- Fix  $\Pi$ ,  $A$

Define a randomized experiment  $\text{PrivK}_{A,\Pi}^{\text{mult}}(n)$ :

1.  $A(1^n)$  outputs two **vectors**  $(m_{0,1}, \dots, m_{0,t})$  and  $(m_{1,1}, \dots, m_{1,t})$   
Required that  $|m_{0,i}| = |m_{1,i}|$  for all  $i$
2.  $k \leftarrow \text{Gen}(1^n)$ ,  $b \leftarrow \{0, 1\}$ , for all  $i$ ,  $c_i \leftarrow \text{Enc}_k(m_{b,i})$
3.  $b' \leftarrow A(c_1, \dots, c_t)$

Adversary  $A$  **succeeds** if  $b = b'$ , and the experiment evaluates to 1 in this case.

**Definition 3.4**  $\Pi$  is **multiple-message indistinguishable** if for **all PPT** attackers  $A$ , there is a **negligible** function  $\epsilon$  such that

$$\Pr[\text{PrivK}_{A,\Pi}^{\text{mult}}(n) = 1] \leq 1/2 + \epsilon(n)$$

**Q:** Show that the pseudo OTP is **not** multiple-message indistinguishable



# CPA-security

- We are **not** going to work with *multiple-message secrecy*





# CPA-security

- We are **not** going to work with *multiple-message secrecy*

Instead, define something **stronger**: security against chosen-plaintext attacks (*CPA-security*)

- Nowadays, this is the **minimal** notion of security an encryption scheme should satisfy



# CPA-security

- We are **not** going to work with *multiple-message secrecy*

Instead, define something **stronger**: security against chosen-plaintext attacks (*CPA-security*)


- Nowadays, this is the **minimal** notion of security an encryption scheme should satisfy

In practice, there are many ways an attacker can **influence** what gets encrypted

- Not clear how best to model
- Chosen-plaintext attacks encompasses any such influence




# “Midway” story



# “Midway” story




Will attack AF ..



# “Midway” story



Will attack AF ..




Help! Fresh water needed



# “Midway” story



AF is short of water



Help! Fresh water needed



# CPA-security

## ■ Fix $\Pi$ , $A$

Define a randomized experiment  $\text{PrivKCPA}_{A,\Pi}(n)$ :

1.  $k \leftarrow \text{Gen}(1^n)$
2.  $A(1^n)$  **interacts** with an **encryption oracle**  $\text{Enc}_k(\cdot)$ , and then outputs  $m_0, m_1$  of the same length
3.  $b \leftarrow \{0, 1\}$ ,  $c \leftarrow \text{Enc}_k(m_b)$ , give  $c$  to  $A$
4.  $A$  can **continue** to interact with  $\text{Enc}_k(\cdot)$
5.  $A$  outputs  $b'$ ;  $A$  succeeds if  $b = b'$ , and experiment evaluates to 1 in this case



# CPA-security

## ■ Fix $\Pi$ , $A$

Define a randomized experiment  $\text{PrivKCPA}_{A,\Pi}(n)$ :

1.  $k \leftarrow \text{Gen}(1^n)$
2.  $A(1^n)$  **interacts** with an **encryption oracle**  $\text{Enc}_k(\cdot)$ , and then outputs  $m_0, m_1$  of the same length
3.  $b \leftarrow \{0, 1\}$ ,  $c \leftarrow \text{Enc}_k(m_b)$ , give  $c$  to  $A$
4.  $A$  can **continue** to interact with  $\text{Enc}_k(\cdot)$
5.  $A$  outputs  $b'$ ;  $A$  succeeds if  $b = b'$ , and experiment evaluates to 1 in this case

**Definition 4.1**  $\Pi$  is **secure against chosen-plaintext attacks (CPA-secure)** if for **all PPT** attackers  $A$ , there is a **negligible** function  $\epsilon$  such that

$$\Pr[\text{PrivKCPA}_{A,\Pi}(n) = 1] \leq 1/2 + \epsilon(n)$$





# Impossible?

- Consider the following attacker  $A$ ;
  - Using a **chosen-plaintext attack**, get  $c_0 = \text{Enc}_k(m_0)$  and  $c_1 = \text{Enc}_k(m_1)$
  - Output  $m_0, m_1$ ; get challenge ciphertext  $c$
  - If  $c = c_0$  output '0'; if  $c = c_1$  output '1'
  - $A$  succeeds with probability 1 (?)

# Impossible?

- Consider the following attacker  $A$ ;
  - Using a **chosen-plaintext attack**, get  $c_0 = \text{Enc}_k(m_0)$  and  $c_1 = \text{Enc}_k(m_1)$
  - Output  $m_0, m_1$ ; get challenge ciphertext  $c$
  - If  $c = c_0$  output '0'; if  $c = c_1$  output '1'
  - $A$  succeeds with probability 1 (?)
- This attack **only** works if encryption is deterministic!
  - **randomized** encryption must be used!
  - It really is a problem if an attacker can tell when **the same message is encrypted twice**



# Pseudorandom functions

- Informally, a *pseudorandom function* “looks like” a random (i.e., uniform) function



# Pseudorandom functions

- Informally, a *pseudorandom function* “looks like” a random (i.e., uniform) function

$Func_n =$  all functions mapping  $\{0, 1\}^n$  to  $\{0, 1\}^n$

How big is  $Func_n$ ?



# Pseudorandom functions

- Informally, a *pseudorandom function* “looks like” a random (i.e., uniform) function

$Func_n =$  all functions mapping  $\{0, 1\}^n$  to  $\{0, 1\}^n$

How big is  $Func_n$ ?

- Can represent a function in  $Func_n$  using  $n \cdot 2^n$  bits



# Pseudorandom functions

- Informally, a *pseudorandom function* “looks like” a random (i.e., uniform) function

$Func_n$  = all functions mapping  $\{0, 1\}^n$  to  $\{0, 1\}^n$

How big is  $Func_n$ ?

- Can represent a function in  $Func_n$  using  $n \cdot 2^n$  bits

$$\Rightarrow |Func_n| = 2^{n \cdot 2^n}$$



# Pseudorandom functions

- Informally, a *pseudorandom function* “looks like” a random (i.e., uniform) function

$Func_n$  = all functions mapping  $\{0, 1\}^n$  to  $\{0, 1\}^n$

How big is  $Func_n$ ?

- Can represent a function in  $Func_n$  using  $n \cdot 2^n$  bits

$$\Rightarrow |Func_n| = 2^{n \cdot 2^n}$$

*Q*: how many functions are there mapping from  $\{0, 1\}^n$  to  $\{0, 1\}^m$  ?



# Random functions vs. pseudorandom functions

- Choose uniform  $f \in \text{Func}_n$



# Random functions vs. pseudorandom functions

- Choose uniform  $f \in \text{Func}_n$
- **Equivalent:** for each  $x \in \{0, 1\}^n$ , choose  $f(x)$  **uniformly** in  $\{0, 1\}^n$ 
  - I.e., fill up the function table with uniform values

# Random functions vs. pseudorandom functions

- Choose uniform  $f \in \text{Func}_n$
- **Equivalent:** for each  $x \in \{0, 1\}^n$ , choose  $f(x)$  **uniformly** in  $\{0, 1\}^n$ 
  - I.e., fill up the function table with uniform values
- Informally, a *pseudorandom function* “looks like” a random function
  - It does **not** make sense to talk about any **fixed** function being pseudorandom. We look instead at *keyed* functions

# Keyed functions

- Let  $F : \{0, 1\}^* \times \{0, 1\}^* \rightarrow \{0, 1\}^*$  be an efficient, deterministic algorithm
  - Define  $F_k(x) = F(k, x)$
  - The first input is called the *key*



# Keyed functions

- Let  $F : \{0, 1\}^* \times \{0, 1\}^* \rightarrow \{0, 1\}^*$  be an efficient, deterministic algorithm
  - Define  $F_k(x) = F(k, x)$
  - The first input is called the *key*
- Assume that  $F$  is *length preserving*:  $F(k, x)$  only defined if  $|k| = |x|$ , in which case,  $|F(k, x)| = |k| = |x|$



# Keyed functions

- Let  $F : \{0, 1\}^* \times \{0, 1\}^* \rightarrow \{0, 1\}^*$  be an efficient, deterministic algorithm
  - Define  $F_k(x) = F(k, x)$
  - The first input is called the *key*
- Assume that  $F$  is *length preserving*:  $F(k, x)$  only defined if  $|k| = |x|$ , in which case,  $|F(k, x)| = |k| = |x|$
- Choosing a *uniform*  $k \in \{0, 1\}^n$  is equivalent to choosing the function  $F_k : \{0, 1\}^n \rightarrow \{0, 1\}^n$ 
  - I.e., for fixed key length  $n$ , the algorithm  $F$  defines a *distribution* over functions in  $Func_n$ !

# Keyed functions

- Let  $F : \{0, 1\}^* \times \{0, 1\}^* \rightarrow \{0, 1\}^*$  be an efficient, deterministic algorithm
  - Define  $F_k(x) = F(k, x)$
  - The first input is called the *key*
- Assume that  $F$  is *length preserving*:  $F(k, x)$  only defined if  $|k| = |x|$ , in which case,  $|F(k, x)| = |k| = |x|$
- Choosing a *uniform*  $k \in \{0, 1\}^n$  is equivalent to choosing the function  $F_k : \{0, 1\}^n \rightarrow \{0, 1\}^n$ 
  - I.e., for fixed key length  $n$ , the algorithm  $F$  defines a *distribution* over functions in  $Func_n$ !
  - E.g.,  $F(k, x) = k$ ,  $F(k, x) = k \oplus x$



- The number of functions in  $Func_n$  is  $2^{n \cdot 2^n}$

- The number of functions in  $Func_n$  is  $2^{n \cdot 2^n}$
- $\{F_k\}_{k \in \{0,1\}^n}$  is a subset of  $Func_n$ 
  - The number of functions in  $\{F_k\}_{k \in \{0,1\}^n}$  is **at most  $2^n$**



- The number of functions in  $Func_n$  is  $2^{n \cdot 2^n}$
- $\{F_k\}_{k \in \{0,1\}^n}$  is a subset of  $Func_n$ 
  - The number of functions in  $\{F_k\}_{k \in \{0,1\}^n}$  is **at most  $2^n$**


**Definition 4.2**  $F$  is a *pseudorandom function* if  $F_k$ , for uniform  $k \in \{0,1\}^n$  is **indistinguishable** from a uniform function  $f \in Func_n$ .  
Formally, for **all** poly-time distinguishers  $D$ :

$$|\Pr_{k \leftarrow \{0,1\}^n}[D^{F_k(\cdot)}(1^n) = 1] - \Pr_{f \leftarrow Func_n}[D^{f(\cdot)}(1^n) = 1]| \leq \epsilon(n)$$

# PRFs


$f \in \text{Func}_n$  chosen  
uniformly at random

World 0



World 1

$k \in \{0,1\}^n$  chosen  
uniformly at random



??



(poly-time)

# Pseudorandom permutations (PRPs)

- Let  $f \in \text{Func}_n$



# Pseudorandom permutations (PRPs)

- Let  $f \in \text{Func}_n$   
 $f$  is a *permutation* if it is a bijection
  - This means that the *inverse*  $f^{-1}$  exists



# Pseudorandom permutations (PRPs)

- Let  $f \in \text{Func}_n$   
 $f$  is a *permutation* if it is a bijection
  - This means that the *inverse*  $f^{-1}$  exists
- Let  $\text{Perm}_n \subset \text{Func}_n$  be the set of permutations
  - What is  $|\text{Perm}_n|$ ?



# Pseudorandom permutations

- Let  $F$  be a length-preserving, keyed function



# Pseudorandom permutations

- Let  $F$  be a length-preserving, keyed function
- $F$  is a *keyed permutation* if
  - $F_k$  is a permutation for every  $k$
  - $F_k^{-1}$  is *efficiently computable* (where  $F_k^{-1}(F_k(x)) = x$ )



# Pseudorandom permutations

- Let  $F$  be a length-preserving, keyed function
- $F$  is a *keyed permutation* if
  - $F_k$  is a permutation for every  $k$
  - $F_k^{-1}$  is *efficiently computable* (where  $F_k^{-1}(F_k(x)) = x$ )
- **Definition 4.3**  $F$  is a *pseudorandom permutation* if  $F_k$ , for **uniform** key  $k \in \{0, 1\}^n$ , is **indistinguishable** from a uniform permutation  $f \in \text{Perm}_n$



# Pseudorandom permutations

- Let  $F$  be a length-preserving, keyed function
- $F$  is a *keyed permutation* if
  - $F_k$  is a permutation for every  $k$
  - $F_k^{-1}$  is *efficiently computable* (where  $F_k^{-1}(F_k(x)) = x$ )
- **Definition 4.3**  $F$  is a *pseudorandom permutation* if  $F_k$ , for **uniform** key  $k \in \{0, 1\}^n$ , is **indistinguishable** from a uniform permutation  $f \in \text{Perm}_n$
- For large enough  $n$ , a random permutation is **indistinguishable** from a random function.
  - In practice, PRPs are also good PRFs

# PRFs vs. PRGs

- PRF  $F$  immediately implies a PRG  $G$ :
  - Define  $G(k) = F_k(0 \dots 0) | F_k(0 \dots 1)$
  - I.e.,  $G(k) = F_k(\langle 0 \rangle) | F_k(\langle 1 \rangle) | F_k(\langle 2 \rangle) | \dots$ ,  
where  $\langle i \rangle$  denotes the  $n$ -bit encoding of  $i$



# PRFs vs. PRGs

- PRF  $F$  immediately implies a PRG  $G$ :
  - Define  $G(k) = F_k(0 \dots 0) | F_k(0 \dots 1)$
  - I.e.,  $G(k) = F_k(\langle 0 \rangle) | F_k(\langle 1 \rangle) | F_k(\langle 2 \rangle) | \dots$ ,  
where  $\langle i \rangle$  denotes the  $n$ -bit encoding of  $i$
- PRF can be viewed as a PRG with random access to **exponentially** long output
  - The function  $F_k$  can be viewed as the  $n2^n$ -bit string  $F_k(0 \dots 0) | \dots | F_k(1 \dots 1)$

# Do PRFs/PRPs exist?

- They are a stronger primitive than PRGs
  - though can be built from PRGs



# Do PRFs/PRPs exist?

- They are a stronger primitive than PRGs
  - though can be built from PRGs

**Theorem** (Goldreich, Goldwasser, Micali 1984)

If the PRG Axiom is **true**, then there exist PRFs.

## How to Construct Random Functions

ODED GOLDREICH, SHAFI GOLDWASSER,  
AND SILVIO MICALI

*Massachusetts Institute of Technology, Cambridge, Massachusetts*

**Abstract.** A constructive theory of randomness for functions, based on computational complexity, is developed, and a pseudorandom function generator is presented. This generator is a deterministic polynomial-time algorithm that transforms pairs  $(g, r)$ , where  $g$  is *any* one-way function and  $r$  is a random  $k$ -bit string, to polynomial-time computable functions  $f_r: \{1, \dots, 2^k\} \rightarrow \{1, \dots, 2^k\}$ . These  $f_r$ 's cannot be distinguished from *random* functions by any probabilistic polynomial-time algorithm that asks and receives the value of a function at arguments of its choice. The result has applications in cryptography, random constructions, and complexity theory.

Categories and Subject Descriptors: F.0 [Theory of Computation]: General; F.1.1 [Computation by Abstract Devices]: Models of Computation—*computability theory*; G.0 [Mathematics of Computing]: General; G.3 [Mathematics of Computing]: Probability and Statistics—*probabilistic algorithms; random number generation*

General Terms: Algorithms, Security, Theory

Additional Key Words and Phrases: Cryptography, one-way functions, prediction problems, randomness

*I have set up on a Manchester computer a small programme using only 1000 units of storage, whereby the machine supplied with one sixteen figure number replies with another within two seconds. I would defy anyone to learn from these replies sufficient about the programme to be able to predict any replies to untried values.*

A. TURING

# Do PRFs/PRPs exist?

- They are a stronger primitive than PRGs
  - though can be built from PRGs
- In practice, **block ciphers** are used



# Next Lecture

- block cipher ...

