EUROPEAN ORGANISATION
FOR THE SAFETY OF AIR NAVIGATION



EUROCONTROL EXPERIMENTAL CENTRE

SYNONYM AIRCRAFT REPORT FOR THE BASE OF AIRCRAFT DATA (BADA) REVISION 3.14

EEC Technical/Scientific Report No. 17/05/29-147

Project BADA

Restricted Issued: June 2017

© European Organisation for the Safety of Air Navigation EUROCONTROL 2017

This document is published by EUROCONTROL in the interest of the exchange of information. It may be copied in whole or in part providing that the copyright notice and disclaimer are included. The information contained in this document may not be modified without prior written permission from EUROCONTROL.

EUROCONTROL makes no warranty, either implied or express, for the information contained in this document, neither does it assume any legal liability or responsibility for the accuracy, completeness or usefulness of this information.

REPORT DOCUMENTATION PAGE

Reference EEC Technical/Scientific Report No. 17/05/29-147	**Security Classification** Unclassified
Originator: ATM/RDS/VIF	**Originator (Corporate Author) Name/Location:** EUROCONTROL Experimental Centre Centre de Bois des Bordes B.P.15 F - 91222 Brétigny-sur-Orge CEDEX FRANCE Telephone: +33 (0)1 69 88 75 00 Internet : www.eurocontrol.int
Sponsor EUROCONTROL	**Sponsor (Contract Authority) Name/Location:** EUROCONTROL Agency Rue de la Fusée, 96 B -1130 BRUXELLES Telephone: +32 (0)2 729 9011 Internet : www.eurocontrol.int

TITLE :

SYNONYM AIRCRAFT REPORT FOR THE BASE OF AIRCRAFT DATA (BADA) REVISION 3.14

Author	Date	Pages	Figures	Tables	Annexes	References
V. Mouillet	06/17	viii+315	0	2	1	4

Project	Task no. sponsor	Period
BADA	ATM/RDS/VIF	06/15 to 06/17

Distribution Statement:

(a) Controlled by: Head of section

(b) Distribution: Public ☐ Restricted ☒ Confidential ☐

(c) Copy to NTIS: ~~YES~~ / NO

Descriptors (keywords):

Equivalent aircraft, aircraft performance, synonym, aircraft model.

Abstract:

The BADA data files provide performance and operating procedure data for a set of aircraft known as BADA aircraft original models. A further set of aircraft types have been identified as being 'equivalent' to these original aircraft models. They are referred to as synonym aircraft. In BADA 3.14, 567 new synonym aircraft were added. An overall revision of the BADA 3.14 synonym matches was made. This resulted in a rematch of 112 aircraft. In total BADA 3.14 provides equivalences for 871 aircraft types. An equivalence report for each aircraft is provided.

Page intentionally left blank

SUMMARY

This document presents a revision of the synonym aircraft modifications for the Base of Aircraft Data (BADA) Revision 3.14.

Page intentionally left blank

TABLE OF CONTENTS

SUMMARY V

1. INTRODUCTION 1

1.1. IDENTIFICATION AND SCOPE 1

1.2. ORGANISATION 1

1.3. REFERENCED DOCUMENTS 1

1.4. GLOSSARY OF ACRONYMS 2

2. SYNONYM AIRCRAFT MODEL IDENTIFICATION 3

3. BADA 3.14 SYNONYM REVISION 3

4. CONCLUSION 22

APPENDIX A - BADA 3.14 AIRCRAFT EQUIVALENCE REPORTS 23

Page intentionally left blank

1. INTRODUCTION

1.1. IDENTIFICATION AND SCOPE

This document presents a revision of the synonym aircraft modifications for the Base of Aircraft Data (BADA) Revision 3.14 [RD1].

This revision of the synonym aircraft has been made with the aid of an in-house database called NAVION which contains information on key aircraft performance parameters for synonym models. For the purpose of the BADA Synonym file, a weighting-driven selection process was applied by favouring cruise speed and altitude capabilities.

The BADA users are provided the possibility to select their own BADA reference models matches based on their user preferences by using the BADA Synonym Search Tool. This tool is provided as a function of the BADA Web Calculation Tool and makes use of the NAVION database. The User guide for the BADA Synonym Search Tool is available from the BADA Calculation Tool [RD4].

For the BADA Revision 3.14 release, 567 new synonyms have been added, 1 synonym has been removed, and 20 synonyms have been replaced by new BADA original models. The remaining synonym aircraft have been re-examined for an eventual revision of their BADA model equivalences. BADA 3.14 covers 871 synonym aircraft types.

The acceptance criteria for aircraft equivalences are specified in Section 2.

1.2. ORGANISATION

This document is presented in three sections. The first section includes a list of referenced documents and a glossary of acronyms.

The synonym aircraft model identification is summarised in Section 2.

Section 3 briefly describes the major BADA Revision 3.14 synonym changes since the BADA Revision 3.13 release. A final conclusion is provided.

Appendix A contains an aircraft equivalence report for each of the aircraft under consideration.

1.3. REFERENCED DOCUMENTS

RD1 User Manual for the Base of Aircraft Data (BADA) Revision 3.14; EEC Technical/Scientific Report No. 17/04/29-143, June 2017

RD2 Coverage of 2015 European Air Traffic for the Base of Aircraft Data (BADA) – Versions BADA 3.13.1 & BADA 4.2; EEC Technical Report No. 16/06/22-97, June 2016

RD3 Aircraft Type Designators; ICAO Document No. 8643; Edition 45, April 2017 http://www.icao.int/publications/DOC8643/

RD4 BADA Synonym Search Tool – Brief User Guide; EEC, August 2009 http://bada.eurocontrol.fr/documentation

1.4. GLOSSARY OF ACRONYMS

APM	Aircraft Performance Model
BADA	Base of Aircraft Data
EEC	EUROCONTROL Experimental Centre
ELC	Electric
HMO	Maximum Operational Height
ICAO	International Civil Aviation Organisation
MMO	Max operating Mach number
MTOW	Maximum Take-off Weight
NMOC	Network Manager Operations Center
PST	Piston
RD	Reference Document
TBP	Turbo Prop
VMO	Max Operating Speed
WTC	Wake Turbulence Category

2. SYNONYM AIRCRAFT MODEL IDENTIFICATION

The BADA data files provide performance and operating procedure data for a set of aircraft known as BADA aircraft original models. A further set of aircraft types have been identified as being 'equivalent' to these original aircraft models. They are referred to as synonym aircraft. For all BADA releases, a list of synonym aircraft types is provided.

The following list of search criteria is used for the BADA synonym model identification:

- engine type;
- wake turbulence category (WTC)
- maximum take-off weight (MTOW);
- wingspan;
- maximum operating speed (VMO)
- maximum Mach operating speed (MMO);
- maximum operational altitude (HMO) (or service ceiling)
- Normal Cruise Speed IAS/CAS above 10,000ft (Vhigh_cruise)
- Normal Cruise Speed Mach (Mach_cruise)

The choice of an equivalent aircraft type for a synonym is made by selecting the aircraft type which best matches the search criteria. Because of the increase in the number of both BADA models and synonym aircraft types, the selection and attribution process has been semi-automated based on a weighting function. This process allows a non-biased match. Consideration must be taken however with regard to user preferences and different applications of use. The current weighting prioritisation has been operationally driven by favouring cruise speed and altitude capabilities.

3. BADA 3.14 SYNONYM REVISION

The NMOC air traffic is used as a representative sample to identify the current European traffic mix of aircraft types. The aircraft available as BADA original models are chosen to reflect this traffic make-up. When a BADA original model is not available for a given aircraft type, a synonym equivalent can be proposed. The "Coverage of 2015 European Air Traffic for the Base of Aircraft Data (BADA) - Versions BADA 3.13.1 & BADA 4.2" document [RD2] has been used to select the aircraft types for identification. In addition to this representative sample of aircraft types, new synonym aircraft have been added following specific BADA user requests and additions of designators by ICAO [RD3].

The modifications covered in this chapter are included in BADA Revision 3.14.

A total of 871 synonym aircraft types are proposed for BADA Revision 3.14. Since the release of BADA Revision 3.13, 567 new synonym aircraft have been added, one synonym (F18) has been removed as a result of an ICAO designator name change [RD3], and 20 synonyms have been replaced by BADA original models (see **Table 1**).

All synonym aircraft types were taken into consideration for the revision of aircraft match equivalences. This led to the rematching of 112 synonyms (see **Table 1**).

Two generic fighter models (FGTH and FGTL) and the generic helicopter synonym (HELI) do not hold an official ICAO designator [RD3]. All the helicopters are currently considered in BADA as equivalent to the HELI synonym.

Table 1: BADA 3.14 synonym aircraft modifications

new synonym	modified synonym	synonym replaced by original model	removed synonym

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
A1	DOUGLAS A-1 Skyraider		SW4
A10	FAIRCHILD A-10A	FGTN	A10
A178	ANTONOV An-178		E190
A19N	AIRBUS A319neo		A20N
A210	AQUILA A-210/211		C162
A21N	AIRBUS A321neo		B739
A22	SADLER A-22 Piranha		P28R
A225	ANTONOV An-225 Mriya	B743	A124
A23	AEROPRACT A-23 Dragon		SVNH
A270	IBIS Ae-270 Spirit		F406
A3	DOUGLAS A-3 Skywarrior		A10
A33	AEROPRACT A-33		MAGC
A339	AIRBUS A330-900		A332
A358	AIRBUS A350-800 XWB	B789	A359
A359	AIRBUS A350-941	B789	A359
A35K	AIRBUS A350-1000 XWB	B773	A359
A37	CESSNA A-37 Dragonfly		L39
A4	DOUGLAS A-4 Skyhawk	FGTN	HAWK
A5	ICON A-5		MAGC
A50	BERIEV A-50		IL76
A500	ADAM A-500		B58T
A6	GRUMMAN A-6E Intruder	FGTN	A10
A7	LTV A-7 Corsair 2	FGTN	F16
A743	ANTONOV An-74-300		A158
A748	AVRO 748	ATP	F27
A900	AVIATIKA MAI-900 Acrobat		MAGC
AA1	GRUMMAN AMERICAN AA-1 Yankee		C162
AC50	AERO Commander 500		DA62
AC52	AERO Commander 520		DA62
AC56	AERO Commander 560		C414
AC5A	NANJING AC-500 Aircar		C182
AC6L	ROCKWELL Commander 685		C414
AC72	AERO Commander 720 Alti Cruis		C421
AC80	ROCKWELL Turbo Commander 680		BE99
AE45	LET Aero 45		C82S
AERK	AERONCA K Scout		SVNH
AJ27	COMAC ARJ21-700 Xiangfeng		A148
AJET	DASSAULT-DORNIER Alpha Jet	FGTN	AJET
ALC1	ALTAIR COELHO AC-11		SVNH

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
ALIG	ARION LS-1 Lightning		E300
AMX	AMX A-1	FGTN	AJET
AN2	ANTONOV An-2		C172
AN22	ANTONOV An-22 Antheus	IL86	A332
AN70	ANTONOV An-70		T204
AN72	ANTONOV An-72	F28	F100
ANGL	ANGEL 44 Angel		P28T
AP32	AEROPRAKT A-32 Vixxen		C162
APM2	ISSOIRE APM-20 Lionceau		MAGC
APM3	ISSOIRE APM-30 Lion		C162
APUP	AEROPUP Aeropup		MAGC
AR15	AERONCA 15 Sedan		MAGC
AR50	AERONCA 50 Chief		SVNH
AR5T	AERONCA 50 Tandem		SVNH
AR65	AERONCA 65 Super Chief		SVNH
AR6T	AERONCA 65 Tandem		SVNH
ARVA	IAI Arava		C208
AS02	FFA AS-202-15/18/26 Bravo		C182
AS14	SCHLEICHER ASK-14		SF25
AS22	SCHLEICHER ASW-22BE		SF25
ASTR	IAI 1125 Astra	LJ35	G150
AT2P	AIR TRACTOR AT-250		DA42
AT3	AIDC AT-3 Tzu-Chung		AJET
AT3P	AIR TRACTOR AT-300/301/401		DA40
AT3T	AIR TRACTOR AT-302/400/402		P750
AT5T	AIR TRACTOR AT-502/503/504		P750
AT6T	AIR TRACTOR AT-602		C208
AT8T	AIR TRACTOR AT-802		AN38
ATL	ROBIN ATL		SVNH
ATLA	DASSAULT Atlantique 2	AN12	C160
B103	BERIEV Be-103 Bekas		DA40
B13	AKAFLIEG BERLIN B-13		DIMO
B17	BOEING B-17 Flying Fortress		A10
B2	NORTHROP B-2 Spirit		FGTL
B209	BOLKOW BO-209 Monsun		C182
B23	DOUGLAS B-23 Dragon		E120
B24	CONSOLIDATED B-24 Liberator		C160
B25	NORTH AMERICAN B-25 Mitchell		AT43
B26	DOUGLAS A-26/B-26 Invader		SF34
B37M	BOEING 737 MAX 7		B739
B38M	BOEING 737 MAX 8		B739
B39M	BOEING 737 MAX 9		B739
B60	BOISAVIA B-60 Mercurey		C182

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
B74D	BOEING 747-400 (domestic)	B744	B743
B778	BOEING 777-8		B77W
B779	BOEING 777-9		B77W
B78X	BOEING 787-10 Dreamliner		B789
BCS1	BOMBARDIER CS100		B736
BCS3	BOMBARDIER CS300		A318
BD17	BEDE BD-17 Nuggett		EV97
BE10	BEECH 100 King Air	BE9L	F406
BE12	BERIEV Be-12 Tchaika		C27J
BE17	BEECH 17 Staggerwing		TB21
BE18	BEECH 18 Twin Beech		PA46
BE32	BERIEV Be-30/32		AN38
BE35	BEECH 35 Bonanza	SR22	BE36
BE50	BEECH 50 Twin Bonanza		C402
BE56	BEECH 56 Turbo Baron		PAY3
BE60	BEECH 60 Duke	C421	C414
BE65	BEECH 65 Queen Air	PA31	C414
BE70	BEECH 70 Queen Air		C414
BE77	BEECH 77 Skipper		C162
BE80	BEECH 80 Queen Air		C414
BE88	BEECH 88 Queen Air		C414
BE95	BEECH 95 Travel Air	BE36	P28T
BE9T	BEECH 90 (F90) King Air	PC12	F406
BELF	SHORT SC-5 Belfast		C130
BIRD	TAYLOR TA-2/3 Bird		SVNH
BL8	BELLANCA 8 Scout		C182
BLCF	BOEING 747-400LCF Dreamlifter		B77W
BR60	BRUMBY 600		C162
BR61	BRUMBY 610 Evolution		C162
BRAV	TECNAM P-2004 Bravo		C162
BT36	BEECH Bonanza B36TC	PA46	S22T
BTX1	BOEING BTX-1		L39
BUCA	ADVANCED AVIATION Buccaneer		SVNH
BUSH	RAINBOW SKYREACH BushCat		SVNH
BX2	BRANDLI BX-2 Cherry		C162
C02T	CESSNA 402 (turbine)		E500
C04T	CESSNA 404 (turbine)		F406
C07T	CESSNA 207 (turbine)		E500
C101	CASA Aviojet	C525	L39
C119	FAIRCHILD C-119 Flying Boxcar		F27
C120	CESSNA 120		EV97
C123	FAIRCHILD C-123 Provider		C160
C125	NORTHROP C-125 Raider		AN38

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
C133	DOUGLAS C-133 Cargomaster		C130
C140	CESSNA 140		EV97
C14T	CESSNA 414 (turbine)		E500
C15	MCDONNELL-DOUGLAS YC-15		T154
C150	CESSNA 150		MAGC
C170	CESSNA 170	EV97	C162
C175	CESSNA 175 Skylark		EV97
C180	CESSNA 180		C182
C185	CESSNA 185 Skywagon		C182
C188	CESSNA 188 AgWagon		MAGC
C190	CESSNA 190		M20P
C195	CESSNA 195		C182
C205	CESSNA 205		DA40
C207	CESSNA 207 Stationair 7	PA44	P06T
C21T	CESSNA 421 (turbine)		TBM7
C22J	CAPRONI VIZZOLA C-22J Ventura		EA50
C240	CESSNA T240 Corvalis TTx		S22T
C25M	CESSNA 525 Citation M2		C525
C270	CAUDRON C-275 Luciole		SVNH
C27J	ALENIA C-27J	AN30	C27J
C310	CESSNA 310R	P28U	C310
C320	CESSNA 320 Skyknight		C340
C335	CESSNA 335	PA31	C402
C336	CESSNA 336 Skymaster		PA44
C340	CESSNA 340A	C421	C340
C402	CESSNA 402B	PA31	C402
C404	CESSNA 404 Titan	B58T	PA31
C414	CESSNA 414A	C421	C414
C46	CURTISS C-46 Commando		F27
C68A	CESSNA 680A Citation Latitude		C680
C700	CESSNA Citation Longitude		E550
C82	FAIRCHILD C-82 Packet		F27
C82T	CESSNA TR182 Turbo Skylane RG	TB20	C82S
C97	BOEING C-97 Stratofreighter		A10
CA25	COMMONWEALTH CA-25 Winjeel		C182
CAT	CONSOLIDATED PBY Catalina		DA40
CC19	CUB CRAFTERS CC-19 XCub		C172
CD2	DORNIER CD-2 Seastar		L410
CE22	CHERNOV Che-22 Corvette		SVNH
CE25	CHERNOV Che-25		MAGC
CH10	ZENAIR CH-100 Mono-Zénith		MAGC
CH20	ZENAIR CH-200 Zénith		C162
CH25	ZENAIR CH-250 Zénith		C162

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
CH2T	ZENAIR CH-2000 Zénith		MAGC
CH30	ZENAIR CH-300 Tri-Zénith		MAGC
CH40	CHAMPION 402 Lancer		C172
CH50	ZENAIR CH-50 Mini Zénith		SVNH
CH60	ZENAIR CH-601 Zodiac		EV97
CH7A	BELLANCA Citabria Aurora 7ECA	P28A	MAGC
CH7B	BELLANCA Citabria Adventure 7GCAA	DA40	EV97
CHIN	ASAP Chinook		EV97
CJ6	NANCHANG CJ-6		TB20
CL2P	CANADAIR CL-215		F27
CL30	BOMBARDIER Challenger 300	E550	CL30
CL35	BOMBARDIER Challenger 350	HA4T	G280
CL41	CANADAIR CL-41 Tutor		L39
CL44	CANADAIR CL-44 Forty Four		C130
CN12	CIRCA Nieuport 12-7/8		SVNH
CO50	COBALT Co-50 Valkyrie		M20T
COAR	COBRA Arrow		C162
COL4	CESSNA 400 Corvalis TT	PA34	S22T
CONI	LOCKHEED (Super) Constellation		C160
COUG	NESMITH Cougar		C162
COUR	HELIO H-295 Super Courier		C82S
COZY	CO-Z Cozy		TB20
CP10	CAP AVIATION CAP-10		P28R
CP20	MUDRY CAP-20		E300
CP21	MUDRY CAP-21		C162
CP22	CAP AVIATION CAP-222		E300
CP23	CAP AVIATION CAP-232		E300
CR10	DYN'AERO CR-100/110/120		P28U
CRES	PACIFIC AEROSPACE Cresco		P750
CRUZ	CZAW SportCruiser		EV97
CT4	PACIFIC AEROSPACE CT-4 Airtrainer		P28R
CVLP	CONVAIR CV-240 Convairliner		SH36
CVLT	CANADAIR CL-66	AN32	ATP
CX5	THATCHER CX-5		MAGC
D139	DORNA D-139 Blue Bird		C162
D140	JODEL D-140 Mousquetaire		DA40
D250	CENTRE EST DR-200/250		C162
D28D	DORNIER Do-28D-2 Skyservant		PA46
D28T	DORNIER 128-6 Turbo Skyservant		P46T
D6	AUSTER D-6		C182
D8	FOKKER D-8 Replica		P28U
DA2	DAVIS DA-2		MAGC
DA36	DIAMOND DA-36 E-Star		DIMO

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
DA5	DAVIS DA-5		EV97
DA50	DIAMOND DA-50 Magnum		C182
DC3T	BASLER Turbo 67		F27
DC4	DOUGLAS DC-4		F27
DC6	DOUGLAS DC-6	AT45	C27J
DC7	DOUGLAS DC-7 Seven Seas		C130
DH2T	DEHAVILLAND CANADA DHC-2 Turbo Beaver		C208
DH60	DE HAVILLAND DH-60 Moth		SVNH
DH80	DE HAVILLAND DH-80 Puss Moth		C182
DH82	DE HAVILLAND DH-82 Tiger Moth		SVNH
DH83	DE HAVILLAND DH-83 Fox Moth		SVNH
DH87	DE HAVILLAND DH-87 Hornet Moth		SVNH
DH88	DE HAVILLAND DH-88 Comet Replica		BE58
DH89	DE HAVILLAND DH-89 Dragon Rapide		DA40
DHA3	DEHAVILLAND AUSTRA DHA-3 Drover		MAGC
DHC1	DEHAVILLAND CANADA DHC-1 Chipmunk		EV97
DHC2	DEHAVILLAND CANADA DHC-2 Beaver		C182
DHC3	DEHAVILLAND CANADA DHC-3 Otter		C182
DHC4	DEHAVILLAND CANADA DHC-4 Caribou		F27
DHC5	DEHAVILLAND CANADA DHC-5 Buffalo		SW4
DHC7	DEHAVILLAND CANADA DHC-7 Dash 7	D228	AN30
DLTA	VERHEES Delta		EV97
DO27	DORNIER Do-27		S22T
DO28	DORNIER Do-28A/B		DA62
DOVE	DE HAVILLAND DH-104 Dove		PA31
DR10	CENTRE EST DR-1050 Sicile		MAGC
DR22	CENTRE EST DR-221 Dauphin		P28A
DR40	ROBIN DR-400	P28T	DA40
DT45	DIAMOND Dart-450		E500
DV20	DIAMOND DV-20 Katana		C172
E110	EMBRAER EMB-110 Bandeirante	SW4	D228
E121	EMBRAER EMB-121 Xingu	PAY2	MU2
E2	GRUMMAN E-2 Hawkeye	AN32	C27J
E200	EXTRA EA-200		E300
E230	EXTRA EA-230		E300
E314	EMBRAER EMB-312H/314		TEX2
E350	CESSNA E350		TBM7
E45X	EMBRAER EMB-145XR	E145	E45X
E530	CESSNA E530 Scorpion		AJET
E545	EMBRAER EMB-545 Legacy 450		E550
E6	BOEING E-6 Mercury		DC87
E737	BOEING 737-700 Wedgetail		B738
E767	BOEING E-767		B763

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
EBOY	FMA 20 El Boyero		SVNH
ECHO	TECNAM P-92 Echo		C162
EDGE	ZIVKO Edge 540		E300
EFAN	AIRBUS E-Fan		SVNH
EGRT	GROB G-520 Strato 1		U2
ELIT	EPIC AIRCRAFT Epic Elite		C550
EM10	MARGANSKI EM-10 Bielik		L39
EPIC	EPIC AIRCRAFT Epic LT / E-1000		BE20
EPX1	EPERVIER X-1	C162	EV97
ERCO	ERCO Ercoupe 415-C		C162
ESCA	EPIC AIRCRAFT Epic Escape		TBM7
ETAR	DASSAULT Super Etendard	FGTN	HAWK
EUFI	EUROFIGHTER Typhoon	FGTN	F16
EUPA	EUROPA Europa		C162
EVIC	EPIC AIRCRAFT Epic Victory		EA50
EVOP	LANCAIR Evolution Piston		C340
EVSS	EVEKTOR SportStar		SVNH
EXPR	WHEELER Express		TB20
F1	MITSUBISHI F-1	FGTN	HAWK
F104	LOCKHEED F-104 Starfighter	FGTN	F16
F106	CONVAIR F-106 Delta Dart		F16
F111	GENERAL DYNAMICS F-111 Aardvark		F15
F117	LOCKHEED F-117 Nighthawk	FGTN	A10
F14	GRUMMAN F-14 Tomcat	FGTN	F15
F15	MCDONNELL-DOUGLAS F-15E	FGTN	F15
F16	GENERAL DYNAMICS F-16C	FGTN	F16
F16X	GENERAL DYNAMICS F-16XL Fighting Falcon		F16
F18		FGTN	
F18H	BOEING F/A-18C/D Hornet		F16
F18S	BOEING F/A-18E/F Super Hornet		F16
F2	MITSUBISHI F-2		F16
F22	LOCKHEED-MARTIN F-22 Raptor		F15
F26T	AERMACCHI SF-260TP		E500
F35	LOCKHEED-MARTIN F-35A Lightning II		F16
F4	MCDONNELL F-4 Phantom 2	FGTN	F16
F406	CESSNA 406	PAY3	F406
F5	NORTHROP F-5	FGTN	AJET
F5SA	IRIAF Saeghe	FGTN	AJET
F60	FOKKER 60		F50
F600	SIAI-MARCHETTI SF-600 Canguro		C208
F8	LTV F-8 Crusader		F16
F86	NORTH AMERICAN F-86 Sabre		AJET
F8L	SEQUOIA F-8L Falco		P28T

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
FBA2	FOUND FBA-2 Bush Hawk		P28T
FDCT	FLIGHT DESIGN CT		C162
FFLY	FAIREY Firefly		C421
FLSS	FLYER Flyer SS		MAGC
FU24	FLETCHER FU-24		EV97
FURY	HAWKER Fury		C402
G109	GROB G-109		DIMO
G115	GROB G-115		P28U
G120	GROB G-120A	SR22	BE36
G140	GROB G-140TP		E500
G150	GULFSTREAM G150	C680	G150
G160	GROB G-160 Ranger		P750
G164	GRUMMAN G-164 (Super) Ag-Cat		EV97
G180	GENERAL AIRCRAFT G1-80 Skyfarer		MAGC
G200	GILES G-200		E300
G202	GILES G-202		E300
G21	GRUMMAN G-21A Goose		BE58
G21M	MCKINNON G-21C/D Goose		C414
G21T	MCKINNON G-21E/G Turbo Goose		BE20
G250	GULFSTREAM G250	HA4T	G280
G280	GULFSTREAM G280	HA4T	G280
G2GL	SOKO G-2 Galeb		L39
G2T1	WACO Great Lakes 2T-1A		EV97
G3	REMOS G-3 Mirage		MAGC
G44	GRUMMAN G-44 Widgeon		C172
G4SG	SOKO G-4 Super Galeb		L39
G73	GRUMMAN G-73 Mallard		C421
G73T	GRUMMAN G-73T Turbo Mallard		C208
GA20	GIPPSLAND GA-200 Fatman		C172
GA5C	GULFSTREAM G500 (G-7)	GLF5	FA7X
GA6C	GULFSTREAM G600 (G-7)	GLF5	GL5T
GALX	IAI 1126 Galaxy	HA4T	G280
GC1	GLOBE GC-1 Swift		C182
GENI	IFB E-Genius		P28U
GL7T	BOMBARDIER Global 7000		GLEX
GLSP	NEW GLASTAR Sportsman 2+2		P28U
GM17	INTRACOM GM-17 Viper		E500
GNAT	FOLLAND Fo-144 Gnat		L39
GOLF	TECNAM P-96 Golf		C162
GP1	JIHLAVAN Skyleader GP One		MAGC
GP4	OSPREY GP-4		TB20
GSPN	GROB G-180 SPn Utility Jet		C550
GY80	GARDAN GY-80 Horizon		C162

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
H25C	HAWKER 1000	H25B	G150
H40	HOFFMANN H-40		EV97
HAR	HAWKER SIDDELEY Harrier	FGTN	AJET
HAWK	BRITISH AEROSPACE T-45A Goshawk	FGTN	HAWK
HDJT	HONDA HA-420 HondaJet		C25A
HERN	DE HAVILLAND DH-114 Heron		DA42
HR20	ROBIN HR-200		MAGC
HU1	SHENYANG SAILPLANE HU-1 Seagull		P28A
HU2	SHENYANG SAILPLANE HU-2 Petrel		DIMO
HUNT	HAWKER Hunter	C650	AJET
HURK	TAI Hurkus		BE20
HUSK	AVIAT A-1 Husky		C82S
HYPR	P&M AVIATION HypR		SVNH
IA63	LMAASA IA-63 Pampa		L39
IL38	ILYUSHIN Il-38		B734
IMPU	IMPULSE Impulse		E300
IR23	ICA IAR-823		SR20
IR99	AVIOANE IAR-99 Soim		L39
IS28	ICA IS-28M2		DIMO
J10	CHENGDU J-10		F16
J20	CHENGDU J-20		F15
JAB2	JABIRU Jabiru J160		MAGC
JAB4	JABIRU Jabiru J400		C162
JABI	JABIRU Jabiru ST		EV97
JAGR	SEPECAT Jaguar	FGTN	F16
JPRO	BAC 145 Jet Provost		L39
JS1	HANDLEY PAGE Jetstream 1	BE20	D228
JS20	HANDLEY PAGE Jetstream 200	SW4	D228
JS3	CENTURY Jetstream 3		D228
JU52	JUNKERS Ju-52/3m		SH36
K250	KESTREL K-250		C172
KC39	EMBRAER KC-390		A321
KE3	BOEING KE-3		DC87
KFIR	IAI Kfir		F16
KL07	BOLKOW BO-207		C172
KP2	JIHLAVAN KP-2 Skyleader 200		C162
KP5	JIHLAVAN KP-5 Skyleader 500		C162
KR30	EKOLOT KR-030 Topaz		EV97
KT1	KOREA AEROSPACE KT-1 Woong-Bee		TEX2
L12	LOCKHEED L-12 Electra Junior		B58T
L159	AERO L-159 Albatros 2	FGTN	HAWK
L29	AERO L-29 Delfin		L39
L37	LOCKHEED L-137 Ventura		JS41

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
L39	AERO L-39C	C510	L39
L59	AERO L-59		L39
L6	AEROVOLGA L-6		SVNH
L60	AERO L-60 Brigadyr		C172
L70	VALMET L-70 Vinka		DA40
L90	VALMET L-90TP Redigo		E500
LA25	LAKE LA-250/270		C172
LA4	LAKE LA-4		C172
LA8	AEROVOLGA LA-8 Flagman		DA40
LANC	AVRO 683 Lancaster		F27
LCR	LAIRD LC-R Speedwing		MAGC
LEG2	LANCAIR Legacy		BE36
LESP	LANCAIR Lancair ES-P		M20T
LGEZ	RUTAN Long-EZ		C402
LJ23	LEARJET 23		C25A
LJ28	LEARJET 28/29		LJ45
LJ55	LEARJET 55	LJ45	LJ60
LN3	FLYGFABRIKEN LN-3 Seagull		C162
LNC2	LANCAIR Lancair 200/235		TB20
LNCE	LANCAIR Lancair Super ES		SR22
LW20	HOWARD HUGHES LightWing Speed SP-2000		MAGC
LW40	HOWARD HUGHES LightWing Speed SP-4000		P28A
LWIN	HOWARD HUGHES LightWing Sport 2000		SVNH
M106	LAMBERT M-106 Mission		SVNH
M108	LAMBERT M-108 Mission		MAGC
M10F	MOONEY M-10T		P28A
M10R	MOONEY M-10J		TB20
M15	PZL-MIELEC M-15 Belphegor		P750
M17	MYASISHCHEV M-17 Stratosfera		U2
M18	PZL-MIELEC M-18 Dromader		TB21
M200	MEYERS 200		BE36
M21	PZL-MIELEC M-21 Dromader Mini		C162
M212	LAMBERT M-212 Mission		P28U
M22	MOONEY M-22 Mustang		PA34
M24	PZL-MIELEC M-24 Dromader Super		C172
M26	PZL-MIELEC M-26 Air Wolf		TB20
M339	AERMACCHI MB-339	FGTN	L39
M346	AERMACCHI M-346 Master	FGTN	HAWK
M4	MAULE M-4		P28U
M5	MAULE M-5		TB21
M55	MYASISHCHEV M-55 Geophysica		U2
M6	MAULE M-6 Super Rocket		C82S
M600	PIPER PA-46-600TP M600		TBM7

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
M7	MAULE M-7-235/MT-7/M		TB20
M7T	MAULE M-7-420 Star Craft		E500
M8	MAULE M-8		P28U
MC90	MONOCOUPE 90		EV97
MCR1	DYN'AERO MCR-01 VLA		C162
MCR4	DYN'AERO MCR-4		C162
MG15	MIKOYAN MiG 15		L39
MG21	MIKOYAN MiG 21	FGTN	F16
MG23	MIKOYAN MiG 23	FGTN	F16
MG25	MIKOYAN MiG 25	FGTN	F15
MG29	MIKOYAN MiG 29	FGTN	F16
MG31	MIKOYAN MiG 31		F15
MIR2	DASSAULT Mirage 2000	FGTN	F16
MIR4	DASSAULT Mirage IV	FGTN	F15
MIRA	DASSAULT Mirage 3		F16
MOR2	MORRISEY 2150		TB21
MP20	PLAN MP-205 Busard		EV97
MRF1	DASSAULT Mirage F1	FGTN	F16
MRJ7	MITSUBISHI MRJ-70		A148
MRJ9	MITSUBISHI MRJ-90		A148
MRMD	CZAW Mermaid		MAGC
MS30	SOCATA MS-300 Epsilon 2		TB20
MS76	MORANE-SAULNIER MS-760 Paris		L39
MU23	AKAFLIEG MUNCHEN Mü-23 Saurier		DIMO
MUS2	BUSHBY Mustang 2		TB21
NAVI	RYAN Navion		DA40
NG5	BRM AERO NG-5 Bristell		C162
O1	CESSNA O-1 Bird Dog		C182
OSCR	PARTENAVIA Oscar		C182
P1	KAWASAKI P-1		B738
P100	POTTIER P-100		MAGC
P149	PIAGGIO P-149		C82S
P2	LOCKHEED P-2 Neptune		F27
P210	CESSNA P210 Pressurized	M20T	S22T
P28B	PIPER PA-28-236 Dakota	DA42	C182
P3	LOCKHEED P-3 Orion	C130	AN12
P32R	PIPER PA-32R-301 Saratoga SP	TB20	C82S
P337	CESSNA P337 Pressur. Skymaster		C82S
P38	LOCKHEED P-38 Lightning		C56X
P39	BELL P-39 Airacobra		BE20
P40	CURTISS P-40 Warhawk		BE9L
P50	POTTIER P-50 Bouvreuil		EV97
P51	NORTH AMERICAN P-51 Mustang		P180

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
P60	POTTIER P-60 Minacro		MAGC
P63	BELL P-63 Kingcobra		C551
P66P	PIAGGIO P-166B Portofino		C414
P66T	PIAGGIO P-166DL3	BE99	C208
P70	POTTIER P-70		SVNH
P8	BOEING P-8 Poseidon		B739
P80	POTTIER P-80		SVNH
P82	NORTH AMERICAN F-82 Twin Mustang		A10
PA11	PIPER PA-11 Cub Special		EV97
PA12	PIPER PA-12 Super Cruiser		P28A
PA14	PIPER PA-14 Family Cruiser		MAGC
PA16	PIPER PA-16 Clipper		MAGC
PA18	PIPER PA-18 Super Cub	P28T	C182
PA20	PIPER PA-20 Pacer		EV97
PA22	PIPER PA-22 Tri-Pacer		DA40
PA23	PIPER PA-23-160 Apache	DA42	C182
PA24	PIPER PA-24 Comanche	TB21	M20T
PA25	PIPER PA-25 Pawnee		SVNH
PA30	PIPER PA-30B Turbo Twin Comanc	BE36	C402
PA36	PIPER PA-36 Pawnee Brave		P28A
PA38	PIPER PA-38 Tomahawk		C162
PAT4	PIPER PA-31T-3 T-1040		BE99
PAY1	PIPER PA-31T1-500 Cheyenne 1	PC12	PAY2
PC21	PILATUS PC-21	BE99	TEX2
PC24	PILATUS PC-24		E55P
PC6P	PILATUS PC-6 Porter		DA42
PC7	PILATUS PC-7 Turbo Trainer	E500	TEX2
PC9	PILATUS PC-9	P180	TEX2
PELI	ULTRAVIA Pelican		EV97
PIAE	PIPISTREL Alpha Electro		EV97
PINO	GENERAL AVIA F.22 Pinguino		TB20
PISI	PIPISTREL Sinus		DIMO
PIT4	PIPISTREL Taurus Electro G4		P28A
PITA	PIPISTREL Taurus 503		SF25
PIVI	PIPISTREL Virus		EV97
PL12	TRANSAVIA PL-12 Airtruk		TB21
PL2	PAZMANY PL-2		MAGC
PNR2	ALPI Pioneer 200		EV97
PNR3	ALPI Pioneer 300		P28U
PNR4	ALPI Pioneer 400		C82S
PO60	POTEZ 60 Sauterelle		MAGC
PROT	CZAW Parrot		MAGC
PT70	POTTIER P-170		SVNH

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
PT80	POTTIER P-180		SVNH
PTS1	PITTS S-1 Special		P28R
PTS2	PITTS S-2 Special		EV97
PULR	P&M AVIATION PulsR		SVNH
PUP	BEAGLE B-121 Pup		C162
PZ01	PZL-OKECIE PZL-101 Gawron		SVNH
PZ04	PZL-OKECIE PZL-104 Wilga 35/80		C172
PZ06	PZL-OKECIE PZL-106BR Kruk		EV97
PZ3T	PZL-OKECIE PZL-130TC-1		PAY3
PZ4M	PZL-OKECIE PZL-104M Wilga 2000		P28A
PZ6T	PZL-OKECIE PZL-106BT Turbo Kruk		P750
Q01	REINER STEMME Q-01		C402
R100	ROBIN R-1180T		DA40
R135	BOEING RC-135		B703
R200	ROBIN R-2160 Alpha Sport		C162
R721	BOEING 727-100	B722	MD83
R90F	RUSCHMEYER R-90-230FG		DA40
R90R	RUSCHMEYER R-90-230RG	SR20	DA40
R90T	RUSCHMEYER R-90-420AT		E500
RALL	MORANE-SAULNIER Rallye Commodore		P28A
RANG	NAVION Rangemaster		TB21
RC70	ROCKWELL Commander 700		PA31
RD20	DENIZE RD-20 Raid Driver		E300
RF3	FOURNIER RF-3		C182
RF4	FOURNIER RF-4		C182
RFAL	DASSAULT Rafale	FGTN	F16
RS20	RANS S-20 Raven		SVNH
RV10	VAN'S RV-10		TB20
RV14	VAN'S RV-14	PA31	P28T
RV3	VAN'S RV-3		TB21
RV4	VAN'S RV-4		P28T
RV6	VAN'S RV-6		E300
RV7	VAN'S RV-7		TB21
RV8	VAN'S RV-8		TB21
RV9	VAN'S RV-9		P28T
RYSA	TECHNOAVIA Rysachok		L410
S05F	SIAI-MARCHETTI S-205-20F		DA40
S05R	SIAI-MARCHETTI S-205-20R	P28U	C182
S10	STINSON 105/10 Voyager		MAGC
S108	STINSON 108 Voyager		EV97
S122	SKYLINE SL-122 Pchelka		MAGC
S200	SIPA S-200 Minijet		EA50
S208	SIAI-MARCHETTI S-208		C182

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
S210	SUD SE-210 Caravelle		E190
S211	SIAI-MARCHETTI S-211		L39
S22T	CIRRUS SR22T	TB21	S22T
S2P	GRUMMAN S-2 Tracker		SH36
S2T	GRUMMAN S-2 Turbo Tracker	SW4	JS41
S3	LOCKHEED S-3 Viking		A10
S450	AERO-EAST-EUROPE SILA-450		EV97
S601	AEROSPATIALE SN-601 Corvette	C550	C525
SA02	K&S SA-102.5 Cavalier		C162
SA20	BERIEV SA-20		EV97
SA30	STOLP SA-300 Starduster Too		TB21
SA37	SCHWEIZER SA-2-37 Condor		DIMO
SA50	STOLP SA-500 Starlet		EV97
SAM	SAM AIRCRAFT Sam		C162
SASH	SHARK AIRCRAFT Shark		C182
SATA	HISPANO HA-220 Super Saeta		L39
SAVG	ZLIN AVIATION Savage		EV97
SB05	SAAB 105	C25A	L39
SB29	SAAB 29		AJET
SB32	SAAB 32 Lansen	FGTN	AJET
SB35	SAAB 35 Draken	FGTN	F16
SB37	SAAB 37 Viggen	FGTN	F16
SB39	SAAB 39 Gripen	FGTN	F16
SBR2	ROCKWELL Sabre 75/80		FA10
SC01	GYROFLUG SC-01 Speed Canard		P28R
SF2	VIKING SF-2 Cygnet		SVNH
SF23	SCHEIBE SF-23 Sperling		EV97
SF24	SCHEIBE SF-24 Motorspatz		SF25
SF27	SCHEIBE SF-27M		SF25
SF31	SPORTAVIA-PUTZER SFS-31 Milan		DIMO
SF50	CIRRUS SF-50 Vision		EA50
SG37	SCHWEIZER SGM-2-37		DIMO
SG70	GLASS SG-70 STOLGlass		EV97
SH33	SHORT 330	JS41	SH36
SIRA	TECNAM P-2002 Sierra		C162
SJ30	SINO SWEARINGEN SJ-30		LJ45
SK70	STARKRAFT SK-700		C421
SLG2	AIRPLANE FACTORY Sling 2 Turbo		C162
SLG4	AIRPLANE FACTORY Sling 4		C162
SLK5	SLICK 540	M20P	E300
SM19	SIAI-MARCHETTI SM-1019		E500
SM20	TECHNOAVIA SM-2000		E500
SM92	TECHNOAVIA SM-92 Finist		P28A

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
SOL1	SOLAR IMPULSE 1		EA50
SOL2	SOLAR IMPULSE 2		EA50
SP7	SPARTAN 7 Executive		PA34
SREY	PROGRESSIVE AERODY SeaRey		C182
SS2T	THRUSH S-2R-H80 Turbo Thrush		P750
SSAB	NORTH AMERICAN F-100 Super Sabre		AJET
ST10	SOCATA ST-10 Diplomate		P28R
ST75	STEARMAN 75 Kaydet		SVNH
STAR	BEECH 2000 Starship		P180
STRE	TL ULTRALIGHT Stream		SVNH
STRK	BAC 167 Strikemaster		L39
SU17	SUKHOI Su-17/20/22		F16
SU24	SUKHOI Su-24		F16
SU25	SUKHOI Su-25 Scorpion		HAWK
SU26	SUKHOI Su-26		E300
SU27	SUKHOI Su-27		F15
SU7	SUKHOI Su-7		AJET
SUBA	FUJI FA-200 Aero Subaru		C182
SW18	SKYWOOD SW-18 Teddy	EV97	SVNH
SW2	SWEARINGEN Merlin 2	MU2	BE9L
SW3	SWEARINGEN Merlin 3	PAY2	MU2
SX30	SWEARINGEN SX-300		E300
SYMP	SYMPHONY SA-160 Symphony		DA40
T1	FUJI T-1		L39
T19	THK T-19 Speedfire		EV97
T2	ROCKWELL T-2 Buckeye		L39
T206	CESSNA T206 Turbo Stationair	PA31	C402
T210	CESSNA T210 Turbo Centurion	C421	C340
T211	THORP T-211		MAGC
T22M	TUPOLEV Tu-22M		FGTL
T250	BELLANCA T-250 Aries		C182
T28	NORTH AMERICAN T-28 Trojan		P180
T30	TERZI T-30 Katana		E300
T33	CANADAIR CT-133 Silver Star		AJET
T34P	BEECH T-34B Mentor		TB20
T34T	BEECH T-34C Turbo Mentor		E500
T35	TEMCO T-35 Buckaroo		EV97
T37	CESSNA T-37-B		L39
T38	NORTHROP T-38 Talon	FGTN	L39
T4	KAWASAKI T-4		AJET
T40	TURNER T-40		EV97
T411	KHRUNICHEV T-411 Aist		P28A
T50S	SUKHOI T-50	FGTN	F15

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
T6	NORTH AMERICAN T-6 Texan	TB21	PA46
TARR	PELEGRIN Tarragon		TB21
TB05	AMC Texas Bullet 205		P28R
TB30	SOCATA TB-30 Epsilon	P28U	TB20
TB31	SOCATA TB-31 Omega		P46T
TBEE	UNITED CONSULTANT Twin Bee		C182
TBM9	SOCATA TBM-900	TBM7	TBM8
TEX2	RAYTHEON T-6B	TBM7	TEX2
TFUN	VALENTIN Taifun		DIMO
TJET	MAVERICK TJ-1500 TwinJet		EA50
TL20	TL ULTRALIGHT TL-2000 Sting S3		C162
TL30	TL ULTRALIGHT TL-3000 Sirius		C162
TOR	PANAVIA Tornado	FGTN	F16
TOUR	AESL Airtourer		C162
TR20	TECH AERO TR-200		P28R
TRF1	TEAM ROCKET F-1		E300
TRIM	FORD Tri-Motor		DA42
TS11	PZL-MIELEC TS-11 Iskra	C510	L39
TU22	TUPOLEV Tu-22		FGTL
TU95	TUPOLEV Tu-95		FGTL
TUTR	AVRO 621 Tutor		EV97
TWIR	DYN'AERO Twin-R		P06T
TWST	SILENCE Twister		EV97
U15	PHOENIX AIR U-15 Phoenix		MAGC
U2	LOCKHEED U-2	FGTL	U2
U21	BEECH U-21 Ute		F406
UF10	URBAN UFM-10 Samba		C162
UF13	URBAN UFM-13 Lambada		SF25
UT75	UTVA 75		SVNH
V22	BELL-BOEING V-22 Osprey	DH8D	A140
VAMP	DE HAVILLAND DH-100 Vampire		L39
VELO	VELOCITY Velocity		C340
VF14	VFW VFW-614		YK40
VF35	LOCKHEED-MARTIN F-35B Lightning II		F16
VK3P	CIRRUS VK-30		S22T
VO10	VOLAIRCRAFT Volaire 10/1035/1050		C172
VTOR	PARTENAVIA AP-68TP-600 Viator		E500
VTUR	QUESTAIR M-20 Venture		C340
WA41	WASSMER WA-41 Baladou		DA40
WA42	WASSMER WA-421/235		P28T
WA50	WASSMER WA-54 Atlantic		P06T
WACF	WACO YMF		C172
WB57	MARTIN WB-57		A10

A/C	NAME OR MODEL	BADA 3.13	BADA 3.14
WT9	AEROSPOOL WT-9 Dynamic		C162
WW23	IAI Westwind (1123)		E55P
WW24	IAI 1124 Westwind	C56X	BE40
XA42	XTREMEAIR XA-42		E300
Y12	HARBIN Y-12E Harbinger		C208
Y12F	HARBIN Y-12F Aircar		JS32
Y130	YAKOVLEV Yak-130	FGTN	AJET
Y18T	YAKOVLEV Yak-18T		C172
YK18	YAKOVLEV Yak-18		DA40
YK28	YAKOVLEV Yak-28		F16
YK52	YAKOVLEV Yak-52		P28U
YS11	MITSUBISHI YS-11	AT76	ATP
YURO	SOKO-CNIAR J-22 Orao		AJET
Z42	ZLIN Z-42/142/242		C172
ZERO	MITSUBISHI Zero		PAY3
ZULU	BUL Zulu		SVNH

The summary equivalence report results (see example in Table 2) are provided in Appendix A of this document.

For each parameter, the “Delta” (resp. “% error”) value represents the absolute (resp. relative) difference between the parameter value known for the synonym aircraft (obtained from the NAVION database) and the corresponding value of the reference BADA aircraft original model. The value ‘0’ is used to indicate that engine type and WTC category match for both the BADA synonym and the assigned original model.

Table 2: Example Equivalence Report

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	TOBA	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.15	1.16	0.01	1%
wingspan (m)	9.76	11.00	1.24	13%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	13000	14000	1000	8%
Normal cruise speed IAS (kt)		102		
Normal cruise speed (Mach)		0.20		
Average Error				7%

Most synonym aircraft whose equivalence report presents a high value for the average error belong to one on the following categories:

- Old piston aircraft, often with MTOW greater than 10 tons (e.g. C97, DC3, DC4): no such aircraft is available as a BADA original model;
- Very light piston aircraft, with MTOW lower than 600kg (e.g. CHIN, DLTA, LGEZ, RF3): few such aircraft are available as BADA original models;
- Military aircraft: even though BADA 3.14 introduced new original models for several military aircraft (fighters and trainers), the variety of characteristics among military aircraft makes it difficult to identify equivalences (e.g. B17, C22J, EM10, F104);
- One-of-a-kind aircraft, which cannot be assimilated to any available original model (e.g. EGRT, SOL1, SOL2).

Special attention will be paid to those categories when new original models will be developed for future BADA releases, in order to improve the equivalences proposed for such aircraft types.

4. CONCLUSION

Identifying the best equivalence between a synonym aircraft and the available BADA aircraft original models proves subjective for some aircraft, when several original models can be considered. In such cases, depending on the performance aspects that are of interest to the end-user, certain aircraft behaviours could be favoured over others, e.g. speed vs. altitude capability.

It is worth emphasizing that the proposed synonyms are based on the best information currently available to EUROCONTROL and on the selected matching criteria. The choice of matching criteria and the way priorities are defined may not be the most appropriate for all applications and uses of BADA. For example, the use of BADA in a trajectory prediction tool may place priorities on cruise speed and maximum operational altitudes when it is used in upper airspace, while a WTC may be of greater priority in the TMA. Environmental studies, however, may put greater priority on aircraft engine type and fuel flow. Consequently, it is usually not possible to identify a synonym aircraft which meets all user needs. In some special cases, the choice of available models in BADA has not permitted a synonym match for both engine category and aircraft performance. For this reason, some aircraft have been attributed synonyms of a different engine category when prioritising the performance parameters.

Considering the difficulties described above, it is envisaged that the BADA user can change the choice of synonym aircraft. To facilitate this work, the BADA Synonym Search Tool is provided as a function of the BADA Calculation Tool (Web application), and its use is described in a User Guide [RD4].

APPENDIX A - BADA 3.14 AIRCRAFT EQUIVALENCE REPORTS

These summary reports compare the attributes of the synonyms and BADA reference models.
The reports are presented in alphabetical order of the synonym ICAO designator.
Differences in engine type and/or WTC are highlighted in orange.
Average relative errors are highlighted in:

- Yellow when they exceed 15%,
- Orange when they exceed 30%,
- Red when they exceed 60%.

Page intentionally left blank

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A1	SW4		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	11.34	7.26	-4.08	36%
wingspan (m)	15.25	17.38	2.13	14%
VMO (kt)		248		
MMO (Mach)		0.52		
HMO (ft)	28500	31000	2500	9%
Normal cruise speed IAS (kt)	140	210	70	50%
Normal cruise speed (Mach)		0.42		
Average Error				27%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A178	E190		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	51.90	51.80	-0.10	0%
wingspan (m)	28.84	28.72	-0.12	0%
VMO (kt)		320		
MMO (Mach)		0.82		
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		290		
Normal cruise speed (Mach)	0.75	0.75	0.00	0%
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A19N	A20N		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	75.50	79.00	3.50	5%
wingspan (m)	35.80	35.80	0.00	0%
VMO (kt)	350	350	0	0%
MMO (Mach)	0.82	0.82	0.00	0%
HMO (ft)		41100		
Normal cruise speed IAS (kt)		310		
Normal cruise speed (Mach)	0.78	0.78	0.00	0%
Average Error				1%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	A210	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.60	-0.15	20%
wingspan (m)	10.30	9.26	-1.04	10%
VMO (kt)	165	143	-22	13%
MMO (Mach)		0.29		
HMO (ft)	14500	14625	125	1%
Normal cruise speed IAS (kt)	112	98	-14	12%
Normal cruise speed (Mach)		0.17		
Average Error				11%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	A21N	B739		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	93.50	85.14	-8.36	9%
wingspan (m)	35.80	35.79	-0.01	0%
VMO (kt)	350	340	-10	3%
MMO (Mach)	0.82	0.82	0.00	0%
HMO (ft)		41000		
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.78	0.78	0.00	0%
Average Error				2%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	A22	P28R		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.17	1.25	0.08	7%
wingspan (m)	6.70	10.80	4.10	61%
VMO (kt)		186		
MMO (Mach)		0.40		
HMO (ft)	18000	18400	400	2%
Normal cruise speed IAS (kt)		129		
Normal cruise speed (Mach)		0.21		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A225	A124		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	640.00	392.00	-248.00	39%
wingspan (m)	88.40	73.30	-15.10	17%
VMO (kt)	308	286	-22	7%
MMO (Mach)	0.77	0.77	0.00	0%
HMO (ft)	38060	39370	1310	3%
Normal cruise speed IAS (kt)		281		
Normal cruise speed (Mach)	0.75	0.70	-0.05	7%
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A23	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.45	-0.15	25%
wingspan (m)	9.80	8.98	-0.82	8%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	65	60	-5	8%
Normal cruise speed (Mach)		0.12		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A270	F406		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.80	4.25	0.45	12%
wingspan (m)	14.13	15.09	0.96	7%
VMO (kt)		230		
MMO (Mach)		0.52		
HMO (ft)	26000	30000	4000	15%
Normal cruise speed IAS (kt)	180	180	0	0%
Normal cruise speed (Mach)		0.36		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A3	A10		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	37.20	23.13	-14.07	38%
wingspan (m)	22.10	17.53	-4.57	21%
VMO (kt)	480	450	-30	6%
MMO (Mach)		0.75		
HMO (ft)	41000	45000	4000	10%
Normal cruise speed IAS (kt)		215		
Normal cruise speed (Mach)		0.56		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A33	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.60	-0.15	20%
wingspan (m)	9.58	8.55	-1.03	11%
VMO (kt)	135	108	-27	20%
MMO (Mach)		0.21		
HMO (ft)	11500	12000	500	4%
Normal cruise speed IAS (kt)	81	83	2	2%
Normal cruise speed (Mach)		0.15		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A339	A332		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	242.00	230.00	-12.00	5%
wingspan (m)	64.00	60.30	-3.70	6%
VMO (kt)		330		
MMO (Mach)	0.86	0.86	0.00	0%
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.82		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A358	A359		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	259.00	275.00	16.00	6%
wingspan (m)	64.75	64.75	0.00	0%
VMO (kt)	340	340	0	0%
MMO (Mach)	0.89	0.89	0.00	0%
HMO (ft)	43040	43100	60	0%
Normal cruise speed IAS (kt)		320		
Normal cruise speed (Mach)	0.85	0.84	-0.01	1%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A35K	A359		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	308.00	275.00	-33.00	11%
wingspan (m)	64.75	64.75	0.00	0%
VMO (kt)	340	340	0	0%
MMO (Mach)	0.89	0.89	0.00	0%
HMO (ft)	41340	43100	1760	4%
Normal cruise speed IAS (kt)		320		
Normal cruise speed (Mach)	0.85	0.84	-0.01	1%
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A37	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	6.35	5.22	-1.13	18%
wingspan (m)	10.93	9.46	-1.47	13%
VMO (kt)	400	490	90	22%
MMO (Mach)		0.80		
HMO (ft)	41765	39370	-2395	6%
Normal cruise speed IAS (kt)	280	250	-30	11%
Normal cruise speed (Mach)		0.50		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A4	HAWK		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	11.14	6.58	-4.56	41%
wingspan (m)	8.38	9.40	1.02	12%
VMO (kt)	600	550	-50	8%
MMO (Mach)		1.04		
HMO (ft)	42250	40000	-2250	5%
Normal cruise speed IAS (kt)		375		
Normal cruise speed (Mach)		0.80		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A400	IL76		
Engine type	TBP	JET	TBP / JET	
WTC	H	H	0	
MTOW (t)	136.50	190.00	53.50	39%
wingspan (m)	42.36	50.50	8.14	19%
VMO (kt)		324		
MMO (Mach)	0.72	0.77	0.05	7%
HMO (ft)	40000	39700	-300	1%
Normal cruise speed IAS (kt)		270		
Normal cruise speed (Mach)	0.68	0.70	0.02	3%
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A5	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.69	0.60	-0.09	13%
wingspan (m)	10.61	8.55	-2.06	19%
VMO (kt)	95	108	13	14%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)		83		
Normal cruise speed (Mach)		0.15		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A50	IL76		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	190.00	190.00	0.00	0%
wingspan (m)	50.50	50.50	0.00	0%
VMO (kt)		324		
MMO (Mach)	0.77	0.77	0.00	0%
HMO (ft)	39370	39700	330	1%
Normal cruise speed IAS (kt)		270		
Normal cruise speed (Mach)	0.70	0.70	0.00	0%
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A500	B58T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.17	2.81	-0.36	11%
wingspan (m)	13.41	11.53	-1.88	14%
VMO (kt)	225	235	10	4%
MMO (Mach)		0.43		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	162	160	-2	1%
Normal cruise speed (Mach)		0.35		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A6	A10		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	27.40	23.13	-4.27	16%
wingspan (m)	16.15	17.53	1.38	9%
VMO (kt)		450		
MMO (Mach)		0.75		
HMO (ft)	42400	45000	2600	6%
Normal cruise speed IAS (kt)		215		
Normal cruise speed (Mach)		0.56		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A660	AN28		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	6.42	6.50	0.08	1%
wingspan (m)	16.46	22.06	5.60	34%
VMO (kt)		219		
MMO (Mach)		0.43		
HMO (ft)	14000	13780	-220	2%
Normal cruise speed IAS (kt)	161	173	12	7%
Normal cruise speed (Mach)		0.32		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A7	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	19.05	21.77	2.72	14%
wingspan (m)	11.80	10.01	-1.79	15%
VMO (kt)		800		
MMO (Mach)		2.05		
HMO (ft)		60000		
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A743	A158		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	36.50	43.70	7.20	20%
wingspan (m)	31.89	28.56	-3.33	10%
VMO (kt)		307		
MMO (Mach)		0.80		
HMO (ft)	33140	38060	4920	15%
Normal cruise speed IAS (kt)	230	270	40	17%
Normal cruise speed (Mach)		0.78		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A748	F27		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	21.09	20.00	-1.09	5%
wingspan (m)	30.02	29.00	-1.02	3%
VMO (kt)		223		
MMO (Mach)		0.50		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	180	170	-10	6%
Normal cruise speed (Mach)		0.50		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	A900	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.71	0.60	-0.11	15%
wingspan (m)	7.15	8.55	1.40	20%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)		83		
Normal cruise speed (Mach)		0.15		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AA1	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.68	0.60	-0.08	12%
wingspan (m)	7.46	9.26	1.80	24%
VMO (kt)	125	143	18	14%
MMO (Mach)		0.29		
HMO (ft)	13750	14625	875	6%
Normal cruise speed IAS (kt)	110	98	-12	11%
Normal cruise speed (Mach)		0.17		
Average Error				14%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	AA5	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.00	1.11	0.11	11%
wingspan (m)	9.60	10.67	1.07	11%
VMO (kt)		126		
MMO (Mach)		0.24		
HMO (ft)	12650	12000	-650	5%
Normal cruise speed IAS (kt)	100	110	10	10%
Normal cruise speed (Mach)		0.24		
Average Error				9%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	AC11	M20T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.50	1.53	0.03	2%
wingspan (m)	9.98	11.13	1.15	12%
VMO (kt)		196		
MMO (Mach)		0.48		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	170	180	10	6%
Normal cruise speed (Mach)		0.37		
Average Error				5%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	AC50	DA62		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.06	2.30	-0.76	25%
wingspan (m)	14.95	14.57	-0.38	3%
VMO (kt)		201		
MMO (Mach)		0.45		
HMO (ft)	19400	20000	600	3%
Normal cruise speed IAS (kt)	144	141	-3	2%
Normal cruise speed (Mach)		0.29		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AC52	DA62		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.50	2.30	-0.20	8%
wingspan (m)	14.14	14.57	0.43	3%
VMO (kt)		201		
MMO (Mach)		0.45		
HMO (ft)		20000		
Normal cruise speed IAS (kt)		141		
Normal cruise speed (Mach)		0.29		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AC56	C414		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.72	3.06	0.34	12%
wingspan (m)	14.14	13.45	-0.69	5%
VMO (kt)		232		
MMO (Mach)		0.63		
HMO (ft)		30000		
Normal cruise speed IAS (kt)		147		
Normal cruise speed (Mach)		0.34		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AC5A	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.54	1.41	-0.13	8%
wingspan (m)	10.20	10.97	0.77	8%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	18040	18100	60	0%
Normal cruise speed IAS (kt)	105	115	10	10%
Normal cruise speed (Mach)		0.21		
Average Error				6%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	AC68	C421		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.86	3.38	-0.48	12%
wingspan (m)	13.43	12.53	-0.90	7%
VMO (kt)		238		
MMO (Mach)		0.64		
HMO (ft)	28000	30000	2000	7%
Normal cruise speed IAS (kt)	160	162	2	1%
Normal cruise speed (Mach)		0.36		
Average Error				7%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	AC6L	C414		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	4.08	3.06	-1.02	25%
wingspan (m)	14.19	13.45	-0.74	5%
VMO (kt)	252	232	-20	8%
MMO (Mach)	0.55	0.63	0.08	15%
HMO (ft)	25000	30000	5000	20%
Normal cruise speed IAS (kt)	140	147	7	5%
Normal cruise speed (Mach)		0.34		
Average Error				13%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	AC72	C421		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.40	3.38	-0.02	1%
wingspan (m)	14.24	12.53	-1.71	12%
VMO (kt)	235	238	3	1%
MMO (Mach)		0.64		
HMO (ft)	28600	30000	1400	5%
Normal cruise speed IAS (kt)	155	162	7	5%
Normal cruise speed (Mach)		0.36		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AC80	BE99		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.05	4.72	0.67	17%
wingspan (m)	14.22	14.00	-0.22	2%
VMO (kt)	217	226	9	4%
MMO (Mach)		0.46		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)		210		
Normal cruise speed (Mach)		0.39		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AC90	PAY3		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.68	5.08	0.40	9%
wingspan (m)	14.23	14.53	0.30	2%
VMO (kt)	243	246	3	1%
MMO (Mach)	0.52	0.52	0.00	0%
HMO (ft)	31000	33000	2000	6%
Normal cruise speed IAS (kt)	220	220	0	0%
Normal cruise speed (Mach)		0.46		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AC95	BE20		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.08	5.67	0.59	12%
wingspan (m)	15.89	16.61	0.72	5%
VMO (kt)		260		
MMO (Mach)	0.60	0.52	-0.08	13%
HMO (ft)	35000	35000	0	0%
Normal cruise speed IAS (kt)		225		
Normal cruise speed (Mach)	0.44	0.46	0.02	5%
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AE45	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.60	1.41	-0.19	12%
wingspan (m)	12.25	10.97	-1.28	10%
VMO (kt)		170		
MMO (Mach)		0.38		
HMO (ft)	19360	20000	640	3%
Normal cruise speed IAS (kt)	109	123	14	13%
Normal cruise speed (Mach)		0.25		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AERK	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.45	-0.02	4%
wingspan (m)	10.97	8.98	-1.99	18%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	12000	14000	2000	17%
Normal cruise speed IAS (kt)	60	60	0	0%
Normal cruise speed (Mach)		0.12		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AEST	B58T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.50	2.81	0.31	12%
wingspan (m)	10.43	11.53	1.10	11%
VMO (kt)		235		
MMO (Mach)		0.43		
HMO (ft)	22000	25000	3000	14%
Normal cruise speed IAS (kt)	173	160	-13	8%
Normal cruise speed (Mach)		0.35		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AFOX	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.45	0.60	0.15	33%
wingspan (m)	9.20	8.55	-0.65	7%
VMO (kt)	100	108	8	8%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	80	83	3	4%
Normal cruise speed (Mach)		0.15		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AJ27	A148		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	40.50	42.55	2.05	5%
wingspan (m)	27.29	28.91	1.62	6%
VMO (kt)	269	307	38	14%
MMO (Mach)	0.82	0.80	-0.02	2%
HMO (ft)	39040	40020	980	3%
Normal cruise speed IAS (kt)		270		
Normal cruise speed (Mach)	0.78	0.78	0.00	0%
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ALC1	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.52	0.45	-0.07	13%
wingspan (m)	8.08	8.98	0.90	11%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	66	60	-6	9%
Normal cruise speed (Mach)		0.12		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ALIG	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.65	0.95	0.30	46%
wingspan (m)	8.28	8.00	-0.28	3%
VMO (kt)	180	220	40	22%
MMO (Mach)		0.45		
HMO (ft)	16000	16000	0	0%
Normal cruise speed IAS (kt)	121	150	29	24%
Normal cruise speed (Mach)		0.29		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ALSL	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.45	0.45	0.00	0%
wingspan (m)	8.95	8.10	-0.85	9%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	107	88	-19	18%
Normal cruise speed (Mach)		0.14		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AMX	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	12.40	7.00	-5.40	44%
wingspan (m)	8.88	9.11	0.23	3%
VMO (kt)	440	550	110	25%
MMO (Mach)	0.90	0.95	0.05	6%
HMO (ft)	42650	50000	7350	17%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)		0.73		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AN2	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	5.50	1.16	-4.34	79%
wingspan (m)	18.18	11.00	-7.18	39%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	14270	14000	-270	2%
Normal cruise speed IAS (kt)	88	102	14	16%
Normal cruise speed (Mach)		0.20		
Average Error				34%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AN22	A332		
Engine type	TBP	JET	TBP / JET	
WTC	H	H	0	
MTOW (t)	250.00	230.00	-20.00	8%
wingspan (m)	64.40	60.30	-4.10	6%
VMO (kt)		330		
MMO (Mach)		0.86		
HMO (ft)	32728	41000	8272	25%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.82		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AN26	AN30		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	24.00	24.00	0.00	0%
wingspan (m)	29.20	29.20	0.00	0%
VMO (kt)	290	243	-47	16%
MMO (Mach)		0.65		
HMO (ft)	28500	29528	1028	4%
Normal cruise speed IAS (kt)	200	212	12	6%
Normal cruise speed (Mach)		0.40		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AN70	T204		
Engine type	TBP	JET	TBP / JET	
WTC	M	M	0	
MTOW (t)	145.00	105.00	-40.00	28%
wingspan (m)	44.06	41.84	-2.22	5%
VMO (kt)		313		
MMO (Mach)		0.83		
HMO (ft)	39370	39700	330	1%
Normal cruise speed IAS (kt)		297		
Normal cruise speed (Mach)	0.70	0.78	0.08	11%
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AN72	F100		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	34.50	43.09	8.59	25%
wingspan (m)	31.89	28.08	-3.81	12%
VMO (kt)		320		
MMO (Mach)		0.75		
HMO (ft)	35100	35000	-100	0%
Normal cruise speed IAS (kt)	280	280	0	0%
Normal cruise speed (Mach)		0.70		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ANGL	P28T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.63	1.25	-1.38	52%
wingspan (m)	12.18	10.80	-1.38	11%
VMO (kt)	180	186	6	3%
MMO (Mach)		0.40		
HMO (ft)	19015	18400	-615	3%
Normal cruise speed IAS (kt)	130	130	0	0%
Normal cruise speed (Mach)		0.22		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AP32	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.45	9.26	-0.19	2%
VMO (kt)	125	143	18	14%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	92	98	6	7%
Normal cruise speed (Mach)		0.17		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	APM2	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.66	0.60	-0.06	9%
wingspan (m)	8.66	8.55	-0.11	1%
VMO (kt)	135	108	-27	20%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	85	83	-2	2%
Normal cruise speed (Mach)		0.15		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	APM3	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.73	0.60	-0.13	18%
wingspan (m)	8.66	9.26	0.60	7%
VMO (kt)	143	143	0	0%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	93	98	5	5%
Normal cruise speed (Mach)		0.17		
Average Error				8%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	APM4	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.98	1.11	0.13	13%
wingspan (m)	8.66	10.67	2.01	23%
VMO (kt)	147	126	-21	14%
MMO (Mach)		0.24		
HMO (ft)	11300	12000	700	6%
Normal cruise speed IAS (kt)	105	110	5	5%
Normal cruise speed (Mach)		0.24		
Average Error				12%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	APUP	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.60	-0.15	20%
wingspan (m)	8.20	8.55	0.35	4%
VMO (kt)	108	108	0	0%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)		83		
Normal cruise speed (Mach)		0.15		
Average Error				8%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	AR11	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.57	0.60	0.03	5%
wingspan (m)	11.00	8.55	-2.45	22%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	10800	12000	1200	11%
Normal cruise speed IAS (kt)	72	83	11	15%
Normal cruise speed (Mach)		0.15		
Average Error				13%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	AR15	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.93	0.60	-0.33	35%
wingspan (m)	11.40	8.55	-2.85	25%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	12400	12000	-400	3%
Normal cruise speed IAS (kt)	73	83	10	14%
Normal cruise speed (Mach)		0.15		
Average Error				19%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	AR50	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.52	0.45	-0.07	13%
wingspan (m)	10.90	8.98	-1.92	18%
VMO (kt)	117	109	-8	7%
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)		60		
Normal cruise speed (Mach)		0.12		
Average Error				13%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	AR5T	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.52	0.45	-0.07	13%
wingspan (m)	10.90	8.98	-1.92	18%
VMO (kt)	117	109	-8	7%
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)		60		
Normal cruise speed (Mach)		0.12		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AR65	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.52	0.45	-0.07	13%
wingspan (m)	10.90	8.98	-1.92	18%
VMO (kt)	117	109	-8	7%
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	70	60	-10	14%
Normal cruise speed (Mach)		0.12		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AR6T	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.52	0.45	-0.07	13%
wingspan (m)	10.90	8.98	-1.92	18%
VMO (kt)	117	109	-8	7%
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	70	60	-10	14%
Normal cruise speed (Mach)		0.12		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ARVA	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	6.80	3.97	-2.83	42%
wingspan (m)	20.96	15.88	-5.08	24%
VMO (kt)	215	175	-40	19%
MMO (Mach)		0.43		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	137	150	13	9%
Normal cruise speed (Mach)		0.27		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AS02	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.05	1.41	0.36	34%
wingspan (m)	9.75	10.97	1.22	13%
VMO (kt)	173	171	-2	1%
MMO (Mach)		0.37		
HMO (ft)	18000	18100	100	1%
Normal cruise speed IAS (kt)	91	115	24	26%
Normal cruise speed (Mach)		0.21		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AS14	SF25		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.36	0.54	0.18	50%
wingspan (m)	14.40	15.30	0.90	6%
VMO (kt)		103		
MMO (Mach)		0.21		
HMO (ft)		14800		
Normal cruise speed IAS (kt)		54		
Normal cruise speed (Mach)		0.21		
Average Error				28%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AS22	SF25		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.54	-0.21	28%
wingspan (m)	25.00	15.30	-9.70	39%
VMO (kt)	151	103	-48	32%
MMO (Mach)		0.21		
HMO (ft)		14800		
Normal cruise speed IAS (kt)	42	54	12	29%
Normal cruise speed (Mach)		0.21		
Average Error				32%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ASTO	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	8.65	9.26	0.61	7%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	15000	14625	-375	2%
Normal cruise speed IAS (kt)	108	98	-10	9%
Normal cruise speed (Mach)		0.17		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ASTR	G150		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	10.66	11.84	1.18	11%
wingspan (m)	16.05	16.94	0.89	6%
VMO (kt)	360	330	-30	8%
MMO (Mach)	0.85	0.85	0.00	0%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)	300	300	0	0%
Normal cruise speed (Mach)		0.78		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AT2P	DA42		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.04	1.78	-0.26	13%
wingspan (m)	12.65	13.42	0.77	6%
VMO (kt)	153	155	2	1%
MMO (Mach)		0.29		
HMO (ft)		18000		
Normal cruise speed IAS (kt)		124		
Normal cruise speed (Mach)		0.27		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AT3	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	7.94	7.00	-0.94	12%
wingspan (m)	10.46	9.11	-1.35	13%
VMO (kt)	500	550	50	10%
MMO (Mach)	1.05	0.95	-0.10	10%
HMO (ft)	48000	50000	2000	4%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)		0.73		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AT3P	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.56	1.28	-2.28	64%
wingspan (m)	15.58	11.63	-3.95	25%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)		16400		
Normal cruise speed IAS (kt)	107	110	3	3%
Normal cruise speed (Mach)		0.23		
Average Error				31%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AT3T	P750		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.16	3.40	-0.76	18%
wingspan (m)	15.54	12.80	-2.74	18%
VMO (kt)		171		
MMO (Mach)		0.38		
HMO (ft)		20000		
Normal cruise speed IAS (kt)	115	140	25	22%
Normal cruise speed (Mach)		0.23		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AT44	AT45		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	18.60	18.60	0.00	0%
wingspan (m)	24.57	24.57	0.00	0%
VMO (kt)	250	250	0	0%
MMO (Mach)	0.55	0.55	0.00	0%
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	210	210	0	0%
Normal cruise speed (Mach)		0.45		
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AT46	AT45		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	18.60	18.60	0.00	0%
wingspan (m)	24.57	24.57	0.00	0%
VMO (kt)	250	250	0	0%
MMO (Mach)	0.55	0.55	0.00	0%
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	210	210	0	0%
Normal cruise speed (Mach)	0.45	0.45	0.00	0%
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AT5T	P750		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.40	3.40	-1.00	23%
wingspan (m)	15.85	12.80	-3.05	19%
VMO (kt)	156	171	15	10%
MMO (Mach)		0.38		
HMO (ft)		20000		
Normal cruise speed IAS (kt)	110	140	30	27%
Normal cruise speed (Mach)		0.23		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AT6T	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.67	3.97	-1.70	30%
wingspan (m)	17.07	15.88	-1.19	7%
VMO (kt)	189	175	-14	7%
MMO (Mach)		0.43		
HMO (ft)		25000		
Normal cruise speed IAS (kt)	130	150	20	15%
Normal cruise speed (Mach)		0.27		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	AT8T	AN38		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	7.26	9.50	2.24	31%
wingspan (m)	18.06	22.07	4.01	22%
VMO (kt)	197	195	-2	1%
MMO (Mach)		0.38		
HMO (ft)	13000	13780	780	6%
Normal cruise speed IAS (kt)	150	184	34	23%
Normal cruise speed (Mach)		0.36		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ATL	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.58	0.45	-0.13	22%
wingspan (m)	10.25	8.98	-1.27	12%
VMO (kt)	105	109	4	4%
MMO (Mach)		0.22		
HMO (ft)	13000	14000	1000	8%
Normal cruise speed IAS (kt)	80	60	-20	25%
Normal cruise speed (Mach)		0.12		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ATLA	C160		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	46.20	49.15	2.95	6%
wingspan (m)	36.30	40.00	3.70	10%
VMO (kt)		240		
MMO (Mach)	0.73	0.67	-0.06	8%
HMO (ft)	30000	30000	0	0%
Normal cruise speed IAS (kt)	200	160	-40	20%
Normal cruise speed (Mach)		0.38		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B1	FGTL		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	216.37	214.60	-1.77	1%
wingspan (m)	41.67	41.80	0.13	0%
VMO (kt)		500		
MMO (Mach)	1.25	1.20	-0.05	4%
HMO (ft)		41000		
Normal cruise speed IAS (kt)		350		
Normal cruise speed (Mach)		0.80		
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B103	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.27	1.28	-0.99	44%
wingspan (m)	12.72	11.63	-1.09	9%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)	16460	16400	-60	0%
Normal cruise speed IAS (kt)	93	110	17	18%
Normal cruise speed (Mach)		0.23		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B13	DIMO		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.85	0.77	-0.08	9%
wingspan (m)	23.20	16.33	-6.87	30%
VMO (kt)	151	141	-10	7%
MMO (Mach)		0.25		
HMO (ft)		16400		
Normal cruise speed IAS (kt)		84		
Normal cruise speed (Mach)		0.25		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B17	A10		
Engine type	PST	JET	PST / JET	
WTC	M	M	0	
MTOW (t)	30.78	23.13	-7.65	25%
wingspan (m)	31.62	17.53	-14.09	45%
VMO (kt)		450		
MMO (Mach)		0.75		
HMO (ft)	38000	45000	7000	18%
Normal cruise speed IAS (kt)	123	215	92	75%
Normal cruise speed (Mach)		0.56		
Average Error				41%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B2	FGTL		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	152.63	214.60	61.97	41%
wingspan (m)	52.43	41.80	-10.63	20%
VMO (kt)		500		
MMO (Mach)	0.95	1.20	0.25	26%
HMO (ft)	50000	41000	-9000	18%
Normal cruise speed IAS (kt)		350		
Normal cruise speed (Mach)	0.85	0.80	-0.05	6%
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B209	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.82	1.41	0.59	72%
wingspan (m)	8.40	10.97	2.57	31%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	18100	18100	0	0%
Normal cruise speed IAS (kt)	109	115	6	6%
Normal cruise speed (Mach)		0.21		
Average Error				27%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B23	E120		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	14.70	11.50	-3.20	22%
wingspan (m)	28.04	19.78	-8.26	29%
VMO (kt)		272		
MMO (Mach)		0.52		
HMO (ft)	31600	32000	400	1%
Normal cruise speed IAS (kt)	180	225	45	25%
Normal cruise speed (Mach)		0.47		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B24	C160		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	29.50	49.15	19.65	67%
wingspan (m)	33.50	40.00	6.50	19%
VMO (kt)		240		
MMO (Mach)		0.67		
HMO (ft)	28000	30000	2000	7%
Normal cruise speed IAS (kt)	137	160	23	17%
Normal cruise speed (Mach)		0.38		
Average Error				27%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B25	AT43		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	15.42	16.70	1.28	8%
wingspan (m)	20.60	24.56	3.96	19%
VMO (kt)		250		
MMO (Mach)		0.55		
HMO (ft)	24200	25000	800	3%
Normal cruise speed IAS (kt)	200	210	10	5%
Normal cruise speed (Mach)		0.45		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B26	SF34		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	15.90	13.15	-2.75	17%
wingspan (m)	21.34	21.44	0.10	0%
VMO (kt)		250		
MMO (Mach)		0.50		
HMO (ft)	22000	25000	3000	14%
Normal cruise speed IAS (kt)		245		
Normal cruise speed (Mach)		0.46		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B36T	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.66	2.13	0.47	28%
wingspan (m)	8.40	11.60	3.20	38%
VMO (kt)	180	209	29	16%
MMO (Mach)		0.51		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	170	160	-10	6%
Normal cruise speed (Mach)		0.32		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B37M	B739		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	80.29	85.14	4.85	6%
wingspan (m)	35.90	35.79	-0.11	0%
VMO (kt)	340	340	0	0%
MMO (Mach)	0.82	0.82	0.00	0%
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.79	0.78	-0.01	1%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B38M	B739		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	82.19	85.14	2.95	4%
wingspan (m)	35.90	35.79	-0.11	0%
VMO (kt)	340	340	0	0%
MMO (Mach)	0.82	0.82	0.00	0%
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.79	0.78	-0.01	1%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B39M	B739		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	88.31	85.14	-3.17	4%
wingspan (m)	35.90	35.79	-0.11	0%
VMO (kt)	340	340	0	0%
MMO (Mach)	0.82	0.82	0.00	0%
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.79	0.78	-0.01	1%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B461	B462		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	38.10	42.18	4.08	11%
wingspan (m)	26.21	26.34	0.13	0%
VMO (kt)	300	295	-5	2%
MMO (Mach)	0.73	0.72	-0.01	1%
HMO (ft)	31000	31000	0	0%
Normal cruise speed IAS (kt)		295		
Normal cruise speed (Mach)		0.65		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B52	FGTL		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	221.35	214.60	-6.75	3%
wingspan (m)	56.39	41.80	-14.59	26%
VMO (kt)		500		
MMO (Mach)	0.90	1.20	0.30	33%
HMO (ft)	55000	41000	-14000	25%
Normal cruise speed IAS (kt)		350		
Normal cruise speed (Mach)		0.80		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B60	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.00	1.41	0.41	41%
wingspan (m)	11.38	10.97	-0.41	4%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	18000	18100	100	1%
Normal cruise speed IAS (kt)	81	115	34	42%
Normal cruise speed (Mach)		0.21		
Average Error				22%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	B701	B752		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	116.58	115.90	-0.68	1%
wingspan (m)	39.87	38.05	-1.82	5%
VMO (kt)	350	350	0	0%
MMO (Mach)		0.86		
HMO (ft)	39000	42000	3000	8%
Normal cruise speed IAS (kt)		290		
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				3%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	B720	B752		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	103.87	115.90	12.03	12%
wingspan (m)	39.87	38.05	-1.82	5%
VMO (kt)	360	350	-10	3%
MMO (Mach)		0.86		
HMO (ft)	40000	42000	2000	5%
Normal cruise speed IAS (kt)		290		
Normal cruise speed (Mach)	0.82	0.80	-0.02	2%
Average Error				5%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	B721	B752		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	72.58	115.90	43.32	60%
wingspan (m)	32.92	38.05	5.13	16%
VMO (kt)		350		
MMO (Mach)	0.85	0.86	0.01	1%
HMO (ft)	36500	42000	5500	15%
Normal cruise speed IAS (kt)	320	290	-30	9%
Normal cruise speed (Mach)	0.84	0.80	-0.04	5%
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B731	T134		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	44.00	47.00	3.00	7%
wingspan (m)	28.35	29.01	0.66	2%
VMO (kt)	350	323	-27	8%
MMO (Mach)	0.86	0.82	-0.04	5%
HMO (ft)	35000	39000	4000	11%
Normal cruise speed IAS (kt)	300	297	-3	1%
Normal cruise speed (Mach)	0.78	0.80	0.02	3%
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B741	B743		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	322.05	377.80	55.75	17%
wingspan (m)	59.64	59.64	0.00	0%
VMO (kt)		360		
MMO (Mach)	0.89	0.90	0.01	1%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)	320	340	20	6%
Normal cruise speed (Mach)	0.84	0.85	0.01	1%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B74D	B743		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	378.18	377.80	-0.38	0%
wingspan (m)	59.60	59.64	0.04	0%
VMO (kt)	365	360	-5	1%
MMO (Mach)	0.92	0.90	-0.02	2%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)	340	340	0	0%
Normal cruise speed (Mach)	0.84	0.85	0.01	1%
Average Error				1%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	B74R	B743		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	351.54	377.80	26.26	7%
wingspan (m)	59.64	59.64	0.00	0%
VMO (kt)		360		
MMO (Mach)	0.89	0.90	0.01	1%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)		340		
Normal cruise speed (Mach)	0.85	0.85	0.00	0%
Average Error				2%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	B74S	B742		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	299.37	356.00	56.63	19%
wingspan (m)	59.64	59.64	0.00	0%
VMO (kt)	375	375	0	0%
MMO (Mach)	0.92	0.92	0.00	0%
HMO (ft)	45100	45000	-100	0%
Normal cruise speed IAS (kt)	340	340	0	0%
Normal cruise speed (Mach)	0.84	0.86	0.02	2%
Average Error				3%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	B778	B77W		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	351.50	351.53	0.03	0%
wingspan (m)	71.75	64.80	-6.95	10%
VMO (kt)		330		
MMO (Mach)		0.89		
HMO (ft)	43100	43100	0	0%
Normal cruise speed IAS (kt)		310		
Normal cruise speed (Mach)		0.84		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B779	B77W		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	351.50	351.53	0.03	0%
wingspan (m)	71.75	64.80	-6.95	10%
VMO (kt)		330		
MMO (Mach)		0.89		
HMO (ft)	43100	43100	0	0%
Normal cruise speed IAS (kt)		310		
Normal cruise speed (Mach)		0.84		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	B78X	B789		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	254.01	250.83	-3.18	1%
wingspan (m)	60.12	60.12	0.00	0%
VMO (kt)	350	350	0	0%
MMO (Mach)		0.90		
HMO (ft)	43100	43100	0	0%
Normal cruise speed IAS (kt)		310		
Normal cruise speed (Mach)	0.84	0.84	0.00	0%
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BCS1	B736		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	60.78	65.00	4.22	7%
wingspan (m)	35.10	34.30	-0.80	2%
VMO (kt)		340		
MMO (Mach)		0.82		
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.78	0.78	0.00	0%
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BCS3	A318		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	67.58	68.00	0.42	1%
wingspan (m)	35.10	34.10	-1.00	3%
VMO (kt)		350		
MMO (Mach)		0.82		
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.78	0.78	0.00	0%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BD17	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.43	0.45	0.02	5%
wingspan (m)	6.55	8.10	1.55	24%
VMO (kt)	167	127	-40	24%
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	105	88	-17	16%
Normal cruise speed (Mach)		0.14		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BDOG	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.06	1.41	0.35	33%
wingspan (m)	10.60	10.97	0.37	3%
VMO (kt)	141	170	29	21%
MMO (Mach)		0.38		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	130	123	-7	5%
Normal cruise speed (Mach)		0.25		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE10	F406		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.35	4.25	-1.10	21%
wingspan (m)	13.98	15.09	1.11	8%
VMO (kt)	220	230	10	5%
MMO (Mach)		0.52		
HMO (ft)	29100	30000	900	3%
Normal cruise speed IAS (kt)	180	180	0	0%
Normal cruise speed (Mach)		0.36		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE12	C27J		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	36.00	31.80	-4.20	12%
wingspan (m)	29.84	28.70	-1.14	4%
VMO (kt)		260		
MMO (Mach)		0.55		
HMO (ft)	26247	30000	3753	14%
Normal cruise speed IAS (kt)	170	200	30	18%
Normal cruise speed (Mach)		0.48		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE17	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.93	1.40	-0.53	27%
wingspan (m)	9.75	9.97	0.22	2%
VMO (kt)	180	189	9	5%
MMO (Mach)		0.47		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	140	132	-8	6%
Normal cruise speed (Mach)		0.28		
Average Error				8%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BE18	PA46		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.97	1.97	-2.00	50%
wingspan (m)	14.50	13.11	-1.39	10%
VMO (kt)	199	200	1	1%
MMO (Mach)		0.49		
HMO (ft)	21500	25000	3500	16%
Normal cruise speed IAS (kt)	145	145	0	0%
Normal cruise speed (Mach)		0.33		
Average Error				15%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BE19	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.02	1.11	0.09	9%
wingspan (m)	9.98	10.67	0.69	7%
VMO (kt)		126		
MMO (Mach)		0.24		
HMO (ft)	11100	12000	900	8%
Normal cruise speed IAS (kt)		110		
Normal cruise speed (Mach)		0.24		
Average Error				8%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BE23	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.04	1.16	0.12	12%
wingspan (m)	10.00	11.00	1.00	10%
VMO (kt)	148	160	12	8%
MMO (Mach)		0.32		
HMO (ft)	13650	14000	350	3%
Normal cruise speed IAS (kt)	110	102	-8	7%
Normal cruise speed (Mach)		0.20		
Average Error				8%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BE24	P06T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.25	1.23	-0.02	2%
wingspan (m)	9.98	11.40	1.42	14%
VMO (kt)	172	172	0	0%
MMO (Mach)		0.34		
HMO (ft)	14350	14000	-350	2%
Normal cruise speed IAS (kt)	120	130	10	8%
Normal cruise speed (Mach)		0.21		
Average Error				5%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BE32	AN38		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	7.30	9.50	2.20	30%
wingspan (m)	17.00	22.07	5.07	30%
VMO (kt)	264	195	-69	26%
MMO (Mach)		0.38		
HMO (ft)	13780	13780	0	0%
Normal cruise speed IAS (kt)	180	184	4	2%
Normal cruise speed (Mach)		0.36		
Average Error				18%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BE33	P28T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.54	1.25	-0.29	19%
wingspan (m)	10.21	10.80	0.59	6%
VMO (kt)	182	186	4	2%
MMO (Mach)		0.40		
HMO (ft)	17800	18400	600	3%
Normal cruise speed IAS (kt)	130	130	0	0%
Normal cruise speed (Mach)		0.22		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE35	BE36		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.54	1.66	0.12	8%
wingspan (m)	10.21	10.21	0.00	0%
VMO (kt)	165	203	38	23%
MMO (Mach)		0.44		
HMO (ft)	18000	18500	500	3%
Normal cruise speed IAS (kt)	150	151	1	1%
Normal cruise speed (Mach)		0.26		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE50	C402		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.17	2.86	-0.31	10%
wingspan (m)	13.78	12.15	-1.63	12%
VMO (kt)	178	231	53	30%
MMO (Mach)		0.62		
HMO (ft)	30000	30000	0	0%
Normal cruise speed IAS (kt)	115	142	27	23%
Normal cruise speed (Mach)		0.32		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE55	PA27		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.40	2.36	-0.04	2%
wingspan (m)	11.53	11.37	-0.16	1%
VMO (kt)	208	215	7	3%
MMO (Mach)		0.37		
HMO (ft)	19000	20000	1000	5%
Normal cruise speed IAS (kt)	155	140	-15	10%
Normal cruise speed (Mach)		0.37		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE56	PAY3		
Engine type	PST	TBP	PST / TBP	
WTC	L	L	0	
MTOW (t)	2.72	5.08	2.36	87%
wingspan (m)	11.53	14.53	3.00	26%
VMO (kt)	227	246	19	8%
MMO (Mach)		0.52		
HMO (ft)	32200	33000	800	2%
Normal cruise speed IAS (kt)	156	220	64	41%
Normal cruise speed (Mach)		0.46		
Average Error				33%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE60	C414		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.07	3.06	-0.01	0%
wingspan (m)	11.96	13.45	1.49	12%
VMO (kt)	170	232	62	36%
MMO (Mach)		0.63		
HMO (ft)	30000	30000	0	0%
Normal cruise speed IAS (kt)	150	147	-3	2%
Normal cruise speed (Mach)		0.34		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE65	C414		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.49	3.06	-0.43	12%
wingspan (m)	13.98	13.45	-0.53	4%
VMO (kt)		232		
MMO (Mach)		0.63		
HMO (ft)	27000	30000	3000	11%
Normal cruise speed IAS (kt)	133	147	14	11%
Normal cruise speed (Mach)		0.34		
Average Error				9%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BE70	C414		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.72	3.06	-0.66	18%
wingspan (m)	15.32	13.45	-1.87	12%
VMO (kt)		232		
MMO (Mach)		0.63		
HMO (ft)	26800	30000	3200	12%
Normal cruise speed IAS (kt)	133	147	14	11%
Normal cruise speed (Mach)		0.34		
Average Error				13%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BE76	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.77	1.41	-0.36	20%
wingspan (m)	11.58	10.97	-0.61	5%
VMO (kt)	160	170	10	6%
MMO (Mach)		0.38		
HMO (ft)	19000	20000	1000	5%
Normal cruise speed IAS (kt)	130	123	-7	5%
Normal cruise speed (Mach)		0.25		
Average Error				9%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BE77	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.76	0.60	-0.16	21%
wingspan (m)	9.14	9.26	0.12	1%
VMO (kt)	143	143	0	0%
MMO (Mach)		0.29		
HMO (ft)	15000	14625	-375	2%
Normal cruise speed IAS (kt)	80	98	18	22%
Normal cruise speed (Mach)		0.17		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE80	C414		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.99	3.06	-0.93	23%
wingspan (m)	15.32	13.45	-1.87	12%
VMO (kt)		232		
MMO (Mach)		0.63		
HMO (ft)	26800	30000	3200	12%
Normal cruise speed IAS (kt)	142	147	5	4%
Normal cruise speed (Mach)		0.34		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE88	C414		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.99	3.06	-0.93	23%
wingspan (m)	15.32	13.45	-1.87	12%
VMO (kt)		232		
MMO (Mach)		0.63		
HMO (ft)	26800	30000	3200	12%
Normal cruise speed IAS (kt)	137	147	10	7%
Normal cruise speed (Mach)		0.34		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BE95	P28T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.91	1.25	-0.66	35%
wingspan (m)	11.53	10.80	-0.73	6%
VMO (kt)	182	186	4	2%
MMO (Mach)		0.40		
HMO (ft)	18100	18400	300	2%
Normal cruise speed IAS (kt)	140	130	-10	7%
Normal cruise speed (Mach)		0.22		
Average Error				10%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BE9T	F406		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.97	4.25	-0.72	14%
wingspan (m)	13.99	15.09	1.10	8%
VMO (kt)		230		
MMO (Mach)		0.52		
HMO (ft)	29800	30000	200	1%
Normal cruise speed IAS (kt)		180		
Normal cruise speed (Mach)		0.36		
Average Error				8%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BELF	C130		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	104.30	81.54	-22.76	22%
wingspan (m)	48.42	40.41	-8.01	17%
VMO (kt)	270	310	40	15%
MMO (Mach)	0.65	0.64	-0.01	2%
HMO (ft)	30000	33000	3000	10%
Normal cruise speed IAS (kt)	207	220	13	6%
Normal cruise speed (Mach)		0.61		
Average Error				12%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	BIRD	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.53	0.45	-0.08	15%
wingspan (m)	7.92	8.98	1.06	13%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	14000	14000	0	0%
Normal cruise speed IAS (kt)	63	60	-3	5%
Normal cruise speed (Mach)		0.12		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BL17	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.51	1.40	-0.11	7%
wingspan (m)	10.41	9.97	-0.44	4%
VMO (kt)	196	189	-7	4%
MMO (Mach)		0.47		
HMO (ft)	24000	25000	1000	4%
Normal cruise speed IAS (kt)	130	132	2	2%
Normal cruise speed (Mach)		0.28		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BL8	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.97	1.41	0.44	45%
wingspan (m)	11.02	10.97	-0.05	0%
VMO (kt)	140	171	31	22%
MMO (Mach)		0.37		
HMO (ft)	17500	18100	600	3%
Normal cruise speed IAS (kt)	85	115	30	35%
Normal cruise speed (Mach)		0.21		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BLCF	B77W		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	364.24	351.53	-12.71	3%
wingspan (m)	64.44	64.80	0.36	1%
VMO (kt)		330		
MMO (Mach)		0.89		
HMO (ft)	43100	43100	0	0%
Normal cruise speed IAS (kt)		310		
Normal cruise speed (Mach)	0.82	0.84	0.02	2%
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BMAN	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.85	0.60	-0.25	29%
wingspan (m)	9.80	8.55	-1.25	13%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	12000	12000	0	0%
Normal cruise speed IAS (kt)	75	83	8	11%
Normal cruise speed (Mach)		0.15		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BN2P	DA42		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.73	1.78	-0.95	35%
wingspan (m)	14.94	13.42	-1.52	10%
VMO (kt)	150	155	5	3%
MMO (Mach)		0.29		
HMO (ft)	16200	18000	1800	11%
Normal cruise speed IAS (kt)	120	124	4	3%
Normal cruise speed (Mach)		0.27		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BN2T	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.17	3.97	0.80	25%
wingspan (m)	14.94	15.88	0.94	6%
VMO (kt)	152	175	23	15%
MMO (Mach)		0.43		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	140	150	10	7%
Normal cruise speed (Mach)		0.27		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BR60	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	8.53	9.26	0.73	9%
VMO (kt)	140	143	3	2%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	92	98	6	7%
Normal cruise speed (Mach)		0.17		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BR61	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	8.53	9.26	0.73	9%
VMO (kt)	140	143	3	2%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	87	98	11	13%
Normal cruise speed (Mach)		0.17		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BRAV	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	8.60	9.26	0.66	8%
VMO (kt)	157	143	-14	9%
MMO (Mach)		0.29		
HMO (ft)	14500	14625	125	1%
Normal cruise speed IAS (kt)	93	98	5	5%
Normal cruise speed (Mach)		0.17		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BT36	S22T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.75	1.63	-0.12	7%
wingspan (m)	11.53	11.67	0.14	1%
VMO (kt)	203	208	5	2%
MMO (Mach)		0.44		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	140	135	-5	4%
Normal cruise speed (Mach)		0.30		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BTX1	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.50	5.22	-0.28	5%
wingspan (m)	10.00	9.46	-0.54	5%
VMO (kt)		490		
MMO (Mach)	1.05	0.80	-0.25	24%
HMO (ft)	50000	39370	-10630	21%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BUCA	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.28	0.45	0.17	61%
wingspan (m)	8.43	8.98	0.55	7%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	13000	14000	1000	8%
Normal cruise speed IAS (kt)	43	60	17	40%
Normal cruise speed (Mach)		0.12		
Average Error				29%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BUSH	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.56	0.45	-0.11	20%
wingspan (m)	9.14	8.98	-0.16	2%
VMO (kt)	108	109	1	1%
MMO (Mach)		0.22		
HMO (ft)	14000	14000	0	0%
Normal cruise speed IAS (kt)	75	60	-15	20%
Normal cruise speed (Mach)		0.12		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	BX2	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.55	0.60	0.05	9%
wingspan (m)	7.00	9.26	2.26	32%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	13800	14625	825	6%
Normal cruise speed IAS (kt)	90	98	8	9%
Normal cruise speed (Mach)		0.17		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C02T	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.96	2.13	-0.83	28%
wingspan (m)	12.15	11.60	-0.55	5%
VMO (kt)		209		
MMO (Mach)		0.51		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	170	160	-10	6%
Normal cruise speed (Mach)		0.32		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C04T	F406		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.81	4.25	0.44	12%
wingspan (m)	14.12	15.09	0.97	7%
VMO (kt)		230		
MMO (Mach)		0.52		
HMO (ft)	26000	30000	4000	15%
Normal cruise speed IAS (kt)	193	180	-13	7%
Normal cruise speed (Mach)		0.36		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C06T	P750		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.63	3.40	1.77	109%
wingspan (m)	10.97	12.80	1.83	17%
VMO (kt)		171		
MMO (Mach)		0.38		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	130	140	10	8%
Normal cruise speed (Mach)		0.23		
Average Error				33%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C07T	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.81	2.13	0.32	18%
wingspan (m)	10.92	11.60	0.68	6%
VMO (kt)		209		
MMO (Mach)		0.51		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	130	160	30	23%
Normal cruise speed (Mach)		0.32		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C101	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	4.80	5.22	0.42	9%
wingspan (m)	10.60	9.46	-1.14	11%
VMO (kt)	450	490	40	9%
MMO (Mach)	0.80	0.80	0.00	0%
HMO (ft)	43000	39370	-3630	8%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)	0.69	0.50	-0.19	28%
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C10T	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.81	2.13	0.32	18%
wingspan (m)	12.41	11.60	-0.81	7%
VMO (kt)		209		
MMO (Mach)		0.51		
HMO (ft)	23000	25000	2000	9%
Normal cruise speed IAS (kt)	160	160	0	0%
Normal cruise speed (Mach)		0.32		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C119	F27		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	33.57	20.00	-13.57	40%
wingspan (m)	33.30	29.00	-4.30	13%
VMO (kt)		223		
MMO (Mach)		0.50		
HMO (ft)	23900	25000	1100	5%
Normal cruise speed IAS (kt)	132	170	38	29%
Normal cruise speed (Mach)		0.50		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C120	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.66	0.45	-0.21	32%
wingspan (m)	10.16	8.10	-2.06	20%
VMO (kt)	122	127	5	4%
MMO (Mach)		0.27		
HMO (ft)	15500	16500	1000	6%
Normal cruise speed IAS (kt)	71	88	17	24%
Normal cruise speed (Mach)		0.14		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C123	C160		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	27.22	49.15	21.93	81%
wingspan (m)	33.53	40.00	6.47	19%
VMO (kt)		240		
MMO (Mach)		0.67		
HMO (ft)	28870	30000	1130	4%
Normal cruise speed IAS (kt)	120	160	40	33%
Normal cruise speed (Mach)		0.38		
Average Error				34%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C125	AN38		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	19.01	9.50	-9.51	50%
wingspan (m)	26.37	22.07	-4.30	16%
VMO (kt)		195		
MMO (Mach)		0.38		
HMO (ft)	12200	13780	1580	13%
Normal cruise speed IAS (kt)	120	184	64	53%
Normal cruise speed (Mach)		0.36		
Average Error				33%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C133	C130		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	130.00	81.54	-48.46	37%
wingspan (m)	54.80	40.41	-14.39	26%
VMO (kt)		310		
MMO (Mach)		0.64		
HMO (ft)	32300	33000	700	2%
Normal cruise speed IAS (kt)	185	220	35	19%
Normal cruise speed (Mach)		0.61		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C135	B703		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	146.00	140.00	-6.00	4%
wingspan (m)	39.88	44.10	4.22	11%
VMO (kt)		375		
MMO (Mach)		0.90		
HMO (ft)	50000	42000	-8000	16%
Normal cruise speed IAS (kt)	300	300	0	0%
Normal cruise speed (Mach)	0.79	0.80	0.01	1%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C140	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.66	0.45	-0.21	32%
wingspan (m)	10.16	8.10	-2.06	20%
VMO (kt)	122	127	5	4%
MMO (Mach)		0.27		
HMO (ft)	15500	16500	1000	6%
Normal cruise speed IAS (kt)	71	88	17	24%
Normal cruise speed (Mach)		0.14		
Average Error				17%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	C141	A310		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	155.58	150.00	-5.58	4%
wingspan (m)	48.74	43.90	-4.84	10%
VMO (kt)		360		
MMO (Mach)		0.84		
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		310		
Normal cruise speed (Mach)	0.76	0.80	0.04	5%
Average Error				5%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	C14T	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.96	2.13	-0.83	28%
wingspan (m)	12.17	11.60	-0.57	5%
VMO (kt)		209		
MMO (Mach)		0.51		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	165	160	-5	3%
Normal cruise speed (Mach)		0.32		
Average Error				9%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	C15	T154		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	98.28	100.00	1.72	2%
wingspan (m)	33.63	37.50	3.87	12%
VMO (kt)		320		
MMO (Mach)		0.86		
HMO (ft)		41000		
Normal cruise speed IAS (kt)		297		
Normal cruise speed (Mach)		0.80		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C150	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.73	0.60	-0.13	18%
wingspan (m)	9.97	8.55	-1.42	14%
VMO (kt)	141	108	-33	23%
MMO (Mach)		0.21		
HMO (ft)	12650	12000	-650	5%
Normal cruise speed IAS (kt)	70	83	13	19%
Normal cruise speed (Mach)		0.15		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C152	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.76	0.60	-0.16	21%
wingspan (m)	9.97	9.26	-0.71	7%
VMO (kt)	155	143	-12	8%
MMO (Mach)		0.29		
HMO (ft)	14700	14625	-75	1%
Normal cruise speed IAS (kt)	110	98	-12	11%
Normal cruise speed (Mach)		0.17		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C17	B764		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	263.08	204.10	-58.98	22%
wingspan (m)	50.29	51.92	1.63	3%
VMO (kt)	350	360	10	3%
MMO (Mach)		0.86		
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)		290		
Normal cruise speed (Mach)	0.77	0.80	0.03	4%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C170	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.00	0.60	-0.40	40%
wingspan (m)	10.97	9.26	-1.71	16%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	15500	14625	-875	6%
Normal cruise speed IAS (kt)	84	98	14	17%
Normal cruise speed (Mach)		0.17		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C175	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.07	0.45	-0.62	58%
wingspan (m)	10.97	8.10	-2.87	26%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	15900	16500	600	4%
Normal cruise speed IAS (kt)	90	88	-2	2%
Normal cruise speed (Mach)		0.14		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C177	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.13	1.16	0.03	3%
wingspan (m)	10.82	11.00	0.18	2%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	14600	14000	-600	4%
Normal cruise speed IAS (kt)	101	102	1	1%
Normal cruise speed (Mach)		0.20		
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C180	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.27	1.41	0.14	11%
wingspan (m)	10.92	10.97	0.05	0%
VMO (kt)	167	171	4	2%
MMO (Mach)		0.37		
HMO (ft)	17700	18100	400	2%
Normal cruise speed IAS (kt)	100	115	15	15%
Normal cruise speed (Mach)		0.21		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C185	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.52	1.41	-0.11	7%
wingspan (m)	10.92	10.97	0.05	0%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	17150	18100	950	6%
Normal cruise speed IAS (kt)	120	115	-5	4%
Normal cruise speed (Mach)		0.21		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C188	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.91	0.60	-1.31	69%
wingspan (m)	12.70	8.55	-4.15	33%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	11100	12000	900	8%
Normal cruise speed IAS (kt)	80	83	3	4%
Normal cruise speed (Mach)		0.15		
Average Error				28%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C190	M20P		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.52	1.53	0.01	1%
wingspan (m)	11.02	11.00	-0.02	0%
VMO (kt)		196		
MMO (Mach)		0.44		
HMO (ft)		20000		
Normal cruise speed IAS (kt)		160		
Normal cruise speed (Mach)		0.29		
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C195	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.52	1.41	-0.11	7%
wingspan (m)	11.02	10.97	-0.05	0%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	18300	18100	-200	1%
Normal cruise speed IAS (kt)	120	115	-5	4%
Normal cruise speed (Mach)		0.21		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C2	C160		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	24.66	49.15	24.49	99%
wingspan (m)	24.56	40.00	15.44	63%
VMO (kt)	343	240	-103	30%
MMO (Mach)	0.57	0.67	0.10	18%
HMO (ft)	35000	30000	-5000	14%
Normal cruise speed IAS (kt)	160	160	0	0%
Normal cruise speed (Mach)		0.38		
Average Error				37%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C205	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.50	1.28	-0.22	15%
wingspan (m)	11.15	11.63	0.48	4%
VMO (kt)	182	172	-10	5%
MMO (Mach)		0.35		
HMO (ft)	16100	16400	300	2%
Normal cruise speed IAS (kt)	118	110	-8	7%
Normal cruise speed (Mach)		0.23		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C206	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.63	1.28	-0.35	21%
wingspan (m)	10.97	11.63	0.66	6%
VMO (kt)	180	172	-8	4%
MMO (Mach)		0.35		
HMO (ft)	15700	16400	700	4%
Normal cruise speed IAS (kt)	110	110	0	0%
Normal cruise speed (Mach)		0.23		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C207	P06T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.72	1.23	-0.49	28%
wingspan (m)	10.92	11.40	0.48	4%
VMO (kt)	182	172	-10	5%
MMO (Mach)		0.34		
HMO (ft)	13300	14000	700	5%
Normal cruise speed IAS (kt)	120	130	10	8%
Normal cruise speed (Mach)		0.21		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C210	SR22		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.75	1.54	-0.21	12%
wingspan (m)	11.20	11.67	0.47	4%
VMO (kt)	200	204	4	2%
MMO (Mach)		0.43		
HMO (ft)	16000	17500	1500	9%
Normal cruise speed IAS (kt)	140	150	10	7%
Normal cruise speed (Mach)		0.28		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C212	JS32		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	7.70	7.35	-0.35	5%
wingspan (m)	20.28	15.85	-4.43	22%
VMO (kt)	200	250	50	25%
MMO (Mach)		0.52		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	150	200	50	33%
Normal cruise speed (Mach)		0.41		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C21T	TBM7		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.44	2.98	-0.46	13%
wingspan (m)	12.53	12.68	0.15	1%
VMO (kt)		270		
MMO (Mach)		0.64		
HMO (ft)		31000		
Normal cruise speed IAS (kt)	180	205	25	14%
Normal cruise speed (Mach)		0.49		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C22J	EA50		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	1.25	2.72	1.47	118%
wingspan (m)	9.20	11.60	2.40	26%
VMO (kt)	300	285	-15	5%
MMO (Mach)		0.64		
HMO (ft)	25000	41000	16000	64%
Normal cruise speed IAS (kt)	150	190	40	27%
Normal cruise speed (Mach)		0.63		
Average Error				48%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C240	S22T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.63	1.63	0.00	0%
wingspan (m)	10.92	11.67	0.75	7%
VMO (kt)	230	208	-22	10%
MMO (Mach)		0.44		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	160	135	-25	16%
Normal cruise speed (Mach)		0.30		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C25M	C525		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	4.85	4.85	0.00	0%
wingspan (m)	14.40	14.30	-0.10	1%
VMO (kt)	263	263	0	0%
MMO (Mach)	0.71	0.71	0.00	0%
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		260		
Normal cruise speed (Mach)	0.67	0.66	-0.01	1%
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C270	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.78	0.45	-0.33	42%
wingspan (m)	9.90	8.98	-0.92	9%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	13123	14000	877	7%
Normal cruise speed IAS (kt)	75	60	-15	20%
Normal cruise speed (Mach)		0.12		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C295	F27		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	21.00	20.00	-1.00	5%
wingspan (m)	25.81	29.00	3.19	12%
VMO (kt)	200	223	23	12%
MMO (Mach)		0.50		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	190	170	-20	11%
Normal cruise speed (Mach)		0.50		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C303	PA31		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.34	2.95	0.61	26%
wingspan (m)	11.90	12.40	0.50	4%
VMO (kt)	164	185	21	13%
MMO (Mach)		0.44		
HMO (ft)	25000	26300	1300	5%
Normal cruise speed IAS (kt)	160	160	0	0%
Normal cruise speed (Mach)		0.44		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C30J	C130		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	70.31	81.54	11.23	16%
wingspan (m)	40.41	40.41	0.00	0%
VMO (kt)		310		
MMO (Mach)		0.64		
HMO (ft)	33000	33000	0	0%
Normal cruise speed IAS (kt)	230	220	-10	4%
Normal cruise speed (Mach)	0.60	0.61	0.01	2%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C320	C340		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.30	2.72	0.42	18%
wingspan (m)	11.20	11.62	0.42	4%
VMO (kt)	205	234	29	14%
MMO (Mach)		0.63		
HMO (ft)	29000	30000	1000	3%
Normal cruise speed IAS (kt)	160	153	-7	4%
Normal cruise speed (Mach)		0.34		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C335	C402		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.72	2.86	0.14	5%
wingspan (m)	11.61	12.15	0.54	5%
VMO (kt)		231		
MMO (Mach)		0.62		
HMO (ft)	26800	30000	3200	12%
Normal cruise speed IAS (kt)	140	142	2	1%
Normal cruise speed (Mach)		0.32		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C336	PA44		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.77	1.72	-0.05	3%
wingspan (m)	11.58	11.75	0.17	1%
VMO (kt)	184	194	10	5%
MMO (Mach)		0.39		
HMO (ft)		15000		
Normal cruise speed IAS (kt)		135		
Normal cruise speed (Mach)		0.27		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C337	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.00	1.41	-0.59	30%
wingspan (m)	11.58	10.97	-0.61	5%
VMO (kt)		170		
MMO (Mach)		0.38		
HMO (ft)	19500	20000	500	3%
Normal cruise speed IAS (kt)	120	123	3	2%
Normal cruise speed (Mach)		0.25		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C404	PA31		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.81	2.95	-0.86	23%
wingspan (m)	14.12	12.40	-1.72	12%
VMO (kt)		185		
MMO (Mach)		0.44		
HMO (ft)	26000	26300	300	1%
Normal cruise speed IAS (kt)	160	160	0	0%
Normal cruise speed (Mach)		0.44		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C411	PA31		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.95	2.95	0.00	0%
wingspan (m)	12.15	12.40	0.25	2%
VMO (kt)	231	185	-46	20%
MMO (Mach)		0.44		
HMO (ft)	26000	26300	300	1%
Normal cruise speed IAS (kt)	170	160	-10	6%
Normal cruise speed (Mach)		0.44		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C425	BE20		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.72	5.67	1.95	52%
wingspan (m)	13.45	16.61	3.16	23%
VMO (kt)	220	260	40	18%
MMO (Mach)	0.45	0.52	0.07	16%
HMO (ft)	34700	35000	300	1%
Normal cruise speed IAS (kt)	200	225	25	12%
Normal cruise speed (Mach)		0.46		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C441	BE20		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.47	5.67	1.20	27%
wingspan (m)	15.04	16.61	1.57	10%
VMO (kt)	250	260	10	4%
MMO (Mach)	0.50	0.52	0.02	4%
HMO (ft)	35000	35000	0	0%
Normal cruise speed IAS (kt)	190	225	35	18%
Normal cruise speed (Mach)	0.45	0.46	0.01	2%
Average Error				9%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	C46	F27		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	20.41	20.00	-0.41	2%
wingspan (m)	32.91	29.00	-3.91	12%
VMO (kt)		223		
MMO (Mach)		0.50		
HMO (ft)	24500	25000	500	2%
Normal cruise speed IAS (kt)	120	170	50	42%
Normal cruise speed (Mach)		0.50		
Average Error				14%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	C5	A345		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	379.66	372.00	-7.66	2%
wingspan (m)	67.88	63.45	-4.43	7%
VMO (kt)	350	330	-20	6%
MMO (Mach)	0.83	0.86	0.03	4%
HMO (ft)	35750	41450	5700	16%
Normal cruise speed IAS (kt)	320	310	-10	3%
Normal cruise speed (Mach)		0.83		
Average Error				6%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	C500	C551		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.39	5.67	0.28	5%
wingspan (m)	14.35	15.76	1.41	10%
VMO (kt)	350	277	-73	21%
MMO (Mach)		0.70		
HMO (ft)	41000	43000	2000	5%
Normal cruise speed IAS (kt)	220	220	0	0%
Normal cruise speed (Mach)	0.60	0.63	0.03	5%
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C501	C551		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.38	5.67	0.29	5%
wingspan (m)	14.35	15.76	1.41	10%
VMO (kt)		277		
MMO (Mach)		0.70		
HMO (ft)	41000	43000	2000	5%
Normal cruise speed IAS (kt)	220	220	0	0%
Normal cruise speed (Mach)	0.60	0.63	0.03	5%
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C526	E50P		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	3.36	4.75	1.39	41%
wingspan (m)	11.28	12.30	1.02	9%
VMO (kt)	280	275	-5	2%
MMO (Mach)		0.70		
HMO (ft)	35000	41000	6000	17%
Normal cruise speed IAS (kt)	270	260	-10	4%
Normal cruise speed (Mach)		0.60		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C5M	A345		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	381.02	372.00	-9.02	2%
wingspan (m)	67.91	63.45	-4.46	7%
VMO (kt)	350	330	-20	6%
MMO (Mach)	0.83	0.86	0.03	4%
HMO (ft)	35750	41450	5700	16%
Normal cruise speed IAS (kt)	320	310	-10	3%
Normal cruise speed (Mach)	0.77	0.83	0.06	8%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C68A	C680		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	13.97	13.74	-0.23	2%
wingspan (m)	22.05	19.30	-2.75	12%
VMO (kt)	305	305	0	0%
MMO (Mach)	0.80	0.80	0.00	0%
HMO (ft)	45000	47000	2000	4%
Normal cruise speed IAS (kt)		305		
Normal cruise speed (Mach)	0.76	0.78	0.02	3%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C700	E550		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)		17.20		
wingspan (m)	21.01	20.25	-0.76	4%
VMO (kt)		320		
MMO (Mach)	0.84	0.83	-0.01	1%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)		0.78		
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C72R	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.20	1.28	0.08	7%
wingspan (m)	10.92	11.63	0.71	7%
VMO (kt)	145	172	27	19%
MMO (Mach)		0.35		
HMO (ft)	16800	16400	-400	2%
Normal cruise speed IAS (kt)	110	110	0	0%
Normal cruise speed (Mach)		0.23		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C77R	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.07	1.11	0.04	4%
wingspan (m)	10.86	10.67	-0.19	2%
VMO (kt)	123	126	3	2%
MMO (Mach)		0.24		
HMO (ft)	12700	12000	-700	6%
Normal cruise speed IAS (kt)	90	110	20	22%
Normal cruise speed (Mach)		0.24		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C82	F27		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	24.55	20.00	-4.55	19%
wingspan (m)	32.46	29.00	-3.46	11%
VMO (kt)		223		
MMO (Mach)		0.50		
HMO (ft)	21200	25000	3800	18%
Normal cruise speed IAS (kt)	154	170	16	10%
Normal cruise speed (Mach)		0.50		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C82R	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.41	1.40	-0.01	1%
wingspan (m)	10.97	9.97	-1.00	9%
VMO (kt)	187	189	2	1%
MMO (Mach)		0.42		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	130	125	-5	4%
Normal cruise speed (Mach)		0.23		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C82T	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.41	1.41	0.00	0%
wingspan (m)	10.92	10.97	0.05	0%
VMO (kt)	179	170	-9	5%
MMO (Mach)		0.38		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	136	123	-13	10%
Normal cruise speed (Mach)		0.25		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	C97	A10		
Engine type	PST	JET	PST / JET	
WTC	M	M	0	
MTOW (t)	79.37	23.13	-56.24	71%
wingspan (m)	43.10	17.53	-25.57	59%
VMO (kt)		450		
MMO (Mach)		0.75		
HMO (ft)	35000	45000	10000	29%
Normal cruise speed IAS (kt)	177	215	38	21%
Normal cruise speed (Mach)		0.56		
Average Error				45%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CA25	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.94	1.41	-0.53	27%
wingspan (m)	11.77	10.97	-0.80	7%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	18000	18100	100	1%
Normal cruise speed IAS (kt)	115	115	0	0%
Normal cruise speed (Mach)		0.21		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CA41	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.69	0.95	0.26	38%
wingspan (m)	7.40	8.00	0.60	8%
VMO (kt)		220		
MMO (Mach)		0.45		
HMO (ft)	10000	16000	6000	60%
Normal cruise speed IAS (kt)	180	150	-30	17%
Normal cruise speed (Mach)		0.29		
Average Error				31%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CAT	DA40		
Engine type	PST	PST	0	
WTC	M	L	M / L	
MTOW (t)	16.07	1.28	-14.79	92%
wingspan (m)	31.70	11.63	-20.07	63%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)	15800	16400	600	4%
Normal cruise speed IAS (kt)	87	110	23	26%
Normal cruise speed (Mach)		0.23		
Average Error				46%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CC19	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.04	1.16	0.12	12%
wingspan (m)	10.46	11.00	0.54	5%
VMO (kt)	145	160	15	10%
MMO (Mach)		0.32		
HMO (ft)	14000	14000	0	0%
Normal cruise speed IAS (kt)	102	102	0	0%
Normal cruise speed (Mach)		0.20		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CD2	L410		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.00	6.60	1.60	32%
wingspan (m)	17.74	19.98	2.24	13%
VMO (kt)	180	185	5	3%
MMO (Mach)		0.41		
HMO (ft)	15000	20000	5000	33%
Normal cruise speed IAS (kt)	155	165	10	6%
Normal cruise speed (Mach)		0.31		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CE22	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.65	0.45	-0.20	31%
wingspan (m)	11.70	8.98	-2.72	23%
VMO (kt)	108	109	1	1%
MMO (Mach)		0.22		
HMO (ft)	13120	14000	880	7%
Normal cruise speed IAS (kt)	52	60	8	15%
Normal cruise speed (Mach)		0.12		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CE25	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.15	0.60	-0.55	48%
wingspan (m)	12.60	8.55	-4.05	32%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	70	83	13	19%
Normal cruise speed (Mach)		0.15		
Average Error				33%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CE43	SR22		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.46	1.54	0.08	5%
wingspan (m)	10.00	11.67	1.67	17%
VMO (kt)	189	204	15	8%
MMO (Mach)		0.43		
HMO (ft)	17400	17500	100	1%
Normal cruise speed IAS (kt)	150	150	0	0%
Normal cruise speed (Mach)		0.28		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CH10	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.44	0.60	0.16	36%
wingspan (m)	6.71	8.55	1.84	27%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	12000	12000	0	0%
Normal cruise speed IAS (kt)	74	83	9	12%
Normal cruise speed (Mach)		0.15		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CH20	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.68	0.60	-0.08	12%
wingspan (m)	7.00	9.26	2.26	32%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	15100	14625	-475	3%
Normal cruise speed IAS (kt)	100	98	-2	2%
Normal cruise speed (Mach)		0.17		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CH25	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.73	0.60	-0.13	18%
wingspan (m)	7.00	9.26	2.26	32%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	15100	14625	-475	3%
Normal cruise speed IAS (kt)	120	98	-22	18%
Normal cruise speed (Mach)		0.17		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CH2T	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.73	0.60	-0.13	18%
wingspan (m)	8.79	8.55	-0.24	3%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	12000	12000	0	0%
Normal cruise speed IAS (kt)	79	83	4	5%
Normal cruise speed (Mach)		0.15		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CH30	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.82	0.60	-0.22	27%
wingspan (m)	8.10	8.55	0.45	6%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	12000	12000	0	0%
Normal cruise speed IAS (kt)	87	83	-4	5%
Normal cruise speed (Mach)		0.15		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CH40	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.11	1.16	0.05	5%
wingspan (m)	10.50	11.00	0.50	5%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	14500	14000	-500	3%
Normal cruise speed IAS (kt)	81	102	21	26%
Normal cruise speed (Mach)		0.20		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CH50	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.25	0.45	0.20	80%
wingspan (m)	5.70	8.98	3.28	58%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	60	60	0	0%
Normal cruise speed (Mach)		0.12		
Average Error				46%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CH60	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.54	0.45	-0.09	17%
wingspan (m)	8.23	8.10	-0.13	2%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	15000	16500	1500	10%
Normal cruise speed IAS (kt)	90	88	-2	2%
Normal cruise speed (Mach)		0.14		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CH7A	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.79	0.60	-0.19	24%
wingspan (m)	10.18	8.55	-1.63	16%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	12000	12000	0	0%
Normal cruise speed IAS (kt)	80	83	3	4%
Normal cruise speed (Mach)		0.15		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CH7B	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.79	0.45	-0.34	43%
wingspan (m)	10.18	8.10	-2.08	20%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	17000	16500	-500	3%
Normal cruise speed IAS (kt)	90	88	-2	2%
Normal cruise speed (Mach)		0.14		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CHIN	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.28	0.45	0.17	61%
wingspan (m)	10.67	8.10	-2.57	24%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	15000	16500	1500	10%
Normal cruise speed IAS (kt)	35	88	53	151%
Normal cruise speed (Mach)		0.14		
Average Error				62%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CJ6	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.40	1.40	0.00	0%
wingspan (m)	10.22	9.97	-0.25	2%
VMO (kt)	200	189	-11	6%
MMO (Mach)		0.42		
HMO (ft)	20500	20000	-500	2%
Normal cruise speed IAS (kt)	120	125	5	4%
Normal cruise speed (Mach)		0.23		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CL2P	F27		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	19.73	20.00	0.27	1%
wingspan (m)	28.60	29.00	0.40	1%
VMO (kt)	190	223	33	17%
MMO (Mach)		0.50		
HMO (ft)	20000	25000	5000	25%
Normal cruise speed IAS (kt)	135	170	35	26%
Normal cruise speed (Mach)		0.50		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CL2T	SH36		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	19.89	12.29	-7.60	38%
wingspan (m)	28.63	22.80	-5.83	20%
VMO (kt)	190	200	10	5%
MMO (Mach)		0.44		
HMO (ft)	18000	20000	2000	11%
Normal cruise speed IAS (kt)	180	180	0	0%
Normal cruise speed (Mach)		0.33		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CL35	G280		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	18.42	17.96	-0.46	2%
wingspan (m)	21.00	19.20	-1.80	9%
VMO (kt)		340		
MMO (Mach)	0.83	0.85	0.02	2%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.82	0.82	0.00	0%
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CL41	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.13	5.22	0.09	2%
wingspan (m)	11.13	9.46	-1.67	15%
VMO (kt)	502	490	-12	2%
MMO (Mach)		0.80		
HMO (ft)	42200	39370	-2830	7%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CL44	C130		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	95.00	81.54	-13.46	14%
wingspan (m)	43.37	40.41	-2.96	7%
VMO (kt)		310		
MMO (Mach)		0.64		
HMO (ft)	30000	33000	3000	10%
Normal cruise speed IAS (kt)	244	220	-24	10%
Normal cruise speed (Mach)		0.61		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CN12	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.45	0.45	0.00	0%
wingspan (m)	8.08	8.98	0.90	11%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	35	60	25	71%
Normal cruise speed (Mach)		0.12		
Average Error				28%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CN35	AT43		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	15.10	16.70	1.60	11%
wingspan (m)	25.81	24.56	-1.25	5%
VMO (kt)	240	250	10	4%
MMO (Mach)		0.55		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)		210		
Normal cruise speed (Mach)		0.45		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CNBR	F900		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	26.73	22.23	-4.50	17%
wingspan (m)	19.51	19.33	-0.18	1%
VMO (kt)		370		
MMO (Mach)		0.84		
HMO (ft)	49000	51000	2000	4%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.83	0.80	-0.03	4%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CO50	M20T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.55	1.53	-0.02	1%
wingspan (m)	9.00	11.13	2.13	24%
VMO (kt)	255	196	-59	23%
MMO (Mach)		0.48		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	170	180	10	6%
Normal cruise speed (Mach)		0.37		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	COAR	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.70	0.60	-0.10	14%
wingspan (m)	8.53	9.26	0.73	9%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	106	98	-8	8%
Normal cruise speed (Mach)		0.17		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	COL3	SR22		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.54	1.54	0.00	0%
wingspan (m)	10.90	11.67	0.77	7%
VMO (kt)	235	204	-31	13%
MMO (Mach)		0.43		
HMO (ft)	18000	17500	-500	3%
Normal cruise speed IAS (kt)	150	150	0	0%
Normal cruise speed (Mach)		0.28		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	COL4	S22T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.63	1.63	0.00	0%
wingspan (m)	10.87	11.67	0.80	7%
VMO (kt)	230	208	-22	10%
MMO (Mach)		0.44		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	160	135	-25	16%
Normal cruise speed (Mach)		0.30		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CONI	C160		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	65.00	49.15	-15.85	24%
wingspan (m)	38.45	40.00	1.55	4%
VMO (kt)		240		
MMO (Mach)		0.67		
HMO (ft)	25000	30000	5000	20%
Normal cruise speed IAS (kt)	160	160	0	0%
Normal cruise speed (Mach)		0.38		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CORV	DA42		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.10	1.78	-1.32	43%
wingspan (m)	16.50	13.42	-3.08	19%
VMO (kt)		155		
MMO (Mach)		0.29		
HMO (ft)	16400	18000	1600	10%
Normal cruise speed IAS (kt)	130	124	-6	5%
Normal cruise speed (Mach)		0.27		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	COUG	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.57	0.60	0.03	5%
wingspan (m)	6.25	9.26	3.01	48%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	13000	14625	1625	12%
Normal cruise speed IAS (kt)		98		
Normal cruise speed (Mach)		0.17		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	COUR	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.54	1.41	-0.13	8%
wingspan (m)	11.89	10.97	-0.92	8%
VMO (kt)		170		
MMO (Mach)		0.38		
HMO (ft)	20500	20000	-500	2%
Normal cruise speed IAS (kt)	110	123	13	12%
Normal cruise speed (Mach)		0.25		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	COZY	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.93	1.40	0.47	51%
wingspan (m)	8.56	9.97	1.41	16%
VMO (kt)		189		
MMO (Mach)		0.42		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	150	125	-25	17%
Normal cruise speed (Mach)		0.23		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CP10	P28R		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.83	1.25	0.42	51%
wingspan (m)	8.08	10.80	2.72	34%
VMO (kt)	183	186	3	2%
MMO (Mach)		0.40		
HMO (ft)	16400	18400	2000	12%
Normal cruise speed IAS (kt)	121	129	8	7%
Normal cruise speed (Mach)		0.21		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CP20	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.76	0.95	0.19	25%
wingspan (m)	8.04	8.00	-0.04	0%
VMO (kt)	202	220	18	9%
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)	150	150	0	0%
Normal cruise speed (Mach)		0.29		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CP21	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.62	0.60	-0.02	3%
wingspan (m)	8.08	9.26	1.18	15%
VMO (kt)	205	143	-62	30%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	117	98	-19	16%
Normal cruise speed (Mach)		0.17		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CP22	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.72	0.95	0.23	32%
wingspan (m)	6.71	8.00	1.29	19%
VMO (kt)	219	220	1	0%
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)	130	150	20	15%
Normal cruise speed (Mach)		0.29		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CP23	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.82	0.95	0.13	16%
wingspan (m)	7.39	8.00	0.61	8%
VMO (kt)	218	220	2	1%
MMO (Mach)		0.45		
HMO (ft)	15000	16000	1000	7%
Normal cruise speed IAS (kt)	119	150	31	26%
Normal cruise speed (Mach)		0.29		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CR10	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.85	1.31	0.46	54%
wingspan (m)	8.50	10.80	2.30	27%
VMO (kt)	205	186	-19	9%
MMO (Mach)		0.41		
HMO (ft)		20000		
Normal cruise speed IAS (kt)	114	122	8	7%
Normal cruise speed (Mach)		0.27		
Average Error				24%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CRES	P750		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.92	3.40	0.48	16%
wingspan (m)	12.81	12.80	-0.01	0%
VMO (kt)	173	171	-2	1%
MMO (Mach)		0.38		
HMO (ft)	18000	20000	2000	11%
Normal cruise speed IAS (kt)	120	140	20	17%
Normal cruise speed (Mach)		0.23		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CRJ7	CRJ9		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	33.00	38.00	5.00	15%
wingspan (m)	23.24	24.85	1.61	7%
VMO (kt)	335	335	0	0%
MMO (Mach)	0.85	0.85	0.00	0%
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CRJX	CRJ9		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	40.82	38.00	-2.82	7%
wingspan (m)	26.17	24.85	-1.32	5%
VMO (kt)	335	335	0	0%
MMO (Mach)	0.85	0.85	0.00	0%
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CRUZ	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.45	-0.15	25%
wingspan (m)	8.60	8.10	-0.50	6%
VMO (kt)	138	127	-11	8%
MMO (Mach)		0.27		
HMO (ft)	15000	16500	1500	10%
Normal cruise speed IAS (kt)	73	88	15	21%
Normal cruise speed (Mach)		0.14		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CT4	P28R		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.18	1.25	0.07	6%
wingspan (m)	7.92	10.80	2.88	36%
VMO (kt)	209	186	-23	11%
MMO (Mach)		0.40		
HMO (ft)	18200	18400	200	1%
Normal cruise speed IAS (kt)	124	129	5	4%
Normal cruise speed (Mach)		0.21		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CVLP	SH36		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	18.37	12.29	-6.08	33%
wingspan (m)	27.97	22.80	-5.17	18%
VMO (kt)		200		
MMO (Mach)		0.44		
HMO (ft)	16000	20000	4000	25%
Normal cruise speed IAS (kt)	170	180	10	6%
Normal cruise speed (Mach)		0.33		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CVLT	ATP		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	24.13	22.93	-1.20	5%
wingspan (m)	32.12	30.63	-1.49	5%
VMO (kt)		225		
MMO (Mach)		0.50		
HMO (ft)	25300	25000	-300	1%
Normal cruise speed IAS (kt)	205	205	0	0%
Normal cruise speed (Mach)		0.40		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	CX5	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	8.50	8.55	0.05	1%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	73	83	10	14%
Normal cruise speed (Mach)		0.15		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	D139	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.60	-0.15	20%
wingspan (m)	9.45	9.26	-0.19	2%
VMO (kt)	140	143	3	2%
MMO (Mach)		0.29		
HMO (ft)	14000	14625	625	4%
Normal cruise speed IAS (kt)	92	98	6	7%
Normal cruise speed (Mach)		0.17		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	D140	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.20	1.28	0.08	7%
wingspan (m)	10.27	11.63	1.36	13%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)	16400	16400	0	0%
Normal cruise speed IAS (kt)	95	110	15	16%
Normal cruise speed (Mach)		0.23		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	D250	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.84	0.60	-0.24	29%
wingspan (m)	8.72	9.26	0.54	6%
VMO (kt)	157	143	-14	9%
MMO (Mach)		0.29		
HMO (ft)	12795	14625	1830	14%
Normal cruise speed IAS (kt)	100	98	-2	2%
Normal cruise speed (Mach)		0.17		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	D253	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.10	1.28	0.18	16%
wingspan (m)	8.72	11.63	2.91	33%
VMO (kt)	152	172	20	13%
MMO (Mach)		0.35		
HMO (ft)	16400	16400	0	0%
Normal cruise speed IAS (kt)	105	110	5	5%
Normal cruise speed (Mach)		0.23		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	D28D	PA46		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	4.35	1.97	-2.38	55%
wingspan (m)	15.55	13.11	-2.44	16%
VMO (kt)		200		
MMO (Mach)		0.49		
HMO (ft)	25200	25000	-200	1%
Normal cruise speed IAS (kt)	125	145	20	16%
Normal cruise speed (Mach)		0.33		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	D28T	P46T		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.30	2.31	-1.99	46%
wingspan (m)	15.55	13.11	-2.44	16%
VMO (kt)		187		
MMO (Mach)		0.51		
HMO (ft)	26900	30000	3100	12%
Normal cruise speed IAS (kt)	140	160	20	14%
Normal cruise speed (Mach)		0.36		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	D6	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)		1.41		
wingspan (m)	10.97	10.97	0.00	0%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)		18100		
Normal cruise speed IAS (kt)		115		
Normal cruise speed (Mach)		0.21		
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	D8	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	1.31	0.71	118%
wingspan (m)	8.34	10.80	2.46	29%
VMO (kt)		186		
MMO (Mach)		0.41		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	80	122	42	52%
Normal cruise speed (Mach)		0.27		
Average Error				50%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DA2	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.54	0.60	0.06	11%
wingspan (m)	5.86	8.55	2.69	46%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	85	83	-2	2%
Normal cruise speed (Mach)		0.15		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DA36	DIMO		
Engine type	ELC	PST	ELC / PST	
WTC	L	L	0	
MTOW (t)	0.77	0.77	0.00	0%
wingspan (m)	16.33	16.33	0.00	0%
VMO (kt)		141		
MMO (Mach)		0.25		
HMO (ft)		16400		
Normal cruise speed IAS (kt)		84		
Normal cruise speed (Mach)		0.25		
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DA5	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.35	0.45	0.10	29%
wingspan (m)	4.76	8.10	3.34	70%
VMO (kt)	147	127	-20	14%
MMO (Mach)		0.27		
HMO (ft)	14500	16500	2000	14%
Normal cruise speed IAS (kt)	103	88	-15	15%
Normal cruise speed (Mach)		0.14		
Average Error				28%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DA50	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.48	1.41	-0.07	5%
wingspan (m)	11.68	10.97	-0.71	6%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	18000	18100	100	1%
Normal cruise speed IAS (kt)	120	115	-5	4%
Normal cruise speed (Mach)		0.21		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DC3	F27		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	11.43	20.00	8.57	75%
wingspan (m)	29.00	29.00	0.00	0%
VMO (kt)		223		
MMO (Mach)		0.50		
HMO (ft)	23200	25000	1800	8%
Normal cruise speed IAS (kt)	150	170	20	13%
Normal cruise speed (Mach)		0.50		
Average Error				24%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DC3T	F27		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	13.04	20.00	6.96	53%
wingspan (m)	28.95	29.00	0.05	0%
VMO (kt)		223		
MMO (Mach)		0.50		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	150	170	20	13%
Normal cruise speed (Mach)		0.50		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DC4	F27		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	33.10	20.00	-13.10	40%
wingspan (m)	35.80	29.00	-6.80	19%
VMO (kt)		223		
MMO (Mach)		0.50		
HMO (ft)	22300	25000	2700	12%
Normal cruise speed IAS (kt)	127	170	43	34%
Normal cruise speed (Mach)		0.50		
Average Error				26%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DC6	C27J		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	44.13	31.80	-12.33	28%
wingspan (m)	35.81	28.70	-7.11	20%
VMO (kt)	300	260	-40	13%
MMO (Mach)		0.55		
HMO (ft)	25000	30000	5000	20%
Normal cruise speed IAS (kt)	200	200	0	0%
Normal cruise speed (Mach)		0.48		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DC7	C130		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	65.00	81.54	16.54	25%
wingspan (m)	42.00	40.41	-1.59	4%
VMO (kt)		310		
MMO (Mach)		0.64		
HMO (ft)	28400	33000	4600	16%
Normal cruise speed IAS (kt)	220	220	0	0%
Normal cruise speed (Mach)		0.61		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DC85	DC87		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	147.41	152.00	4.59	3%
wingspan (m)	34.41	45.20	10.79	31%
VMO (kt)		375		
MMO (Mach)		0.90		
HMO (ft)	36000	42000	6000	17%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DC86	DC87		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	158.70	152.00	-6.70	4%
wingspan (m)	43.41	45.20	1.79	4%
VMO (kt)		375		
MMO (Mach)		0.90		
HMO (ft)	41000	42000	1000	2%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.82	0.80	-0.02	2%
Average Error				3%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	DC91	B712		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	35.24	52.60	17.36	49%
wingspan (m)	27.25	28.40	1.15	4%
VMO (kt)	340	340	0	0%
MMO (Mach)	0.81	0.82	0.01	1%
HMO (ft)	35000	37000	2000	6%
Normal cruise speed IAS (kt)	280	275	-5	2%
Normal cruise speed (Mach)	0.77	0.75	-0.02	3%
Average Error				9%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	DC92	DC94		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	44.45	51.70	7.25	16%
wingspan (m)	28.49	28.50	0.01	0%
VMO (kt)		340		
MMO (Mach)		0.80		
HMO (ft)	35000	35000	0	0%
Normal cruise speed IAS (kt)	340	340	0	0%
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				3%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	DC95	DC94		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	54.88	51.70	-3.18	6%
wingspan (m)	28.47	28.50	0.03	0%
VMO (kt)		340		
MMO (Mach)		0.80		
HMO (ft)	35000	35000	0	0%
Normal cruise speed IAS (kt)	340	340	0	0%
Normal cruise speed (Mach)		0.80		
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DH2T	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.44	3.97	1.53	63%
wingspan (m)	14.64	15.88	1.24	8%
VMO (kt)	152	175	23	15%
MMO (Mach)		0.43		
HMO (ft)	23900	25000	1100	5%
Normal cruise speed IAS (kt)	108	150	42	39%
Normal cruise speed (Mach)		0.27		
Average Error				26%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DH60	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.45	-0.30	40%
wingspan (m)	9.14	8.98	-0.16	2%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	14500	14000	-500	3%
Normal cruise speed IAS (kt)	58	60	2	3%
Normal cruise speed (Mach)		0.12		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DH80	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.93	1.41	0.48	52%
wingspan (m)	11.20	10.97	-0.23	2%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	17500	18100	600	3%
Normal cruise speed IAS (kt)	85	115	30	35%
Normal cruise speed (Mach)		0.21		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DH82	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.83	0.45	-0.38	46%
wingspan (m)	8.94	8.98	0.04	0%
VMO (kt)	140	109	-31	22%
MMO (Mach)		0.22		
HMO (ft)	13600	14000	400	3%
Normal cruise speed IAS (kt)	43	60	17	40%
Normal cruise speed (Mach)		0.12		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DH83	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.91	0.45	-0.46	51%
wingspan (m)	9.42	8.98	-0.44	5%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	12700	14000	1300	10%
Normal cruise speed IAS (kt)	62	60	-2	3%
Normal cruise speed (Mach)		0.12		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DH87	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.89	0.45	-0.44	49%
wingspan (m)	9.73	8.98	-0.75	8%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	14800	14000	-800	5%
Normal cruise speed IAS (kt)	73	60	-13	18%
Normal cruise speed (Mach)		0.12		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DH88	BE58		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.52	2.45	-0.07	3%
wingspan (m)	13.41	11.53	-1.88	14%
VMO (kt)		223		
MMO (Mach)		0.50		
HMO (ft)	19000	20688	1688	9%
Normal cruise speed IAS (kt)	160	164	4	2%
Normal cruise speed (Mach)		0.29		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DH89	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.49	1.28	-1.21	49%
wingspan (m)	14.60	11.63	-2.97	20%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)	16700	16400	-300	2%
Normal cruise speed IAS (kt)	110	110	0	0%
Normal cruise speed (Mach)		0.23		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DH8B	DH8C		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	16.47	19.50	3.03	18%
wingspan (m)	25.91	27.43	1.52	6%
VMO (kt)	282	283	1	0%
MMO (Mach)		0.66		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	245	245	0	0%
Normal cruise speed (Mach)		0.45		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DHA3	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.95	0.60	-2.35	80%
wingspan (m)	17.39	8.55	-8.84	51%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	83	83	0	0%
Normal cruise speed (Mach)		0.15		
Average Error				43%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DHC1	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.00	0.45	-0.55	55%
wingspan (m)	10.47	8.10	-2.37	23%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	15800	16500	700	4%
Normal cruise speed IAS (kt)	70	88	18	26%
Normal cruise speed (Mach)		0.14		
Average Error				27%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DHC2	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.31	1.41	-0.90	39%
wingspan (m)	14.63	10.97	-3.66	25%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	18000	18100	100	1%
Normal cruise speed IAS (kt)	100	115	15	15%
Normal cruise speed (Mach)		0.21		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DHC3	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.63	1.41	-2.22	61%
wingspan (m)	17.69	10.97	-6.72	38%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	18800	18100	-700	4%
Normal cruise speed IAS (kt)	95	115	20	21%
Normal cruise speed (Mach)		0.21		
Average Error				31%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DHC4	F27		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	12.93	20.00	7.07	55%
wingspan (m)	29.15	29.00	-0.15	1%
VMO (kt)	208	223	15	7%
MMO (Mach)		0.50		
HMO (ft)	24800	25000	200	1%
Normal cruise speed IAS (kt)	140	170	30	21%
Normal cruise speed (Mach)		0.50		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DHC5	SW4		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	22.32	7.26	-15.06	67%
wingspan (m)	29.26	17.38	-11.88	41%
VMO (kt)		248		
MMO (Mach)		0.52		
HMO (ft)	31000	31000	0	0%
Normal cruise speed IAS (kt)	185	210	25	14%
Normal cruise speed (Mach)		0.42		
Average Error				30%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DHC6	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.67	3.97	-1.70	30%
wingspan (m)	19.81	15.88	-3.93	20%
VMO (kt)		175		
MMO (Mach)		0.43		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	160	150	-10	6%
Normal cruise speed (Mach)		0.27		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DHC7	AN30		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	21.23	24.00	2.77	13%
wingspan (m)	28.40	29.20	0.80	3%
VMO (kt)		243		
MMO (Mach)		0.65		
HMO (ft)	28000	29528	1528	5%
Normal cruise speed IAS (kt)	180	212	32	18%
Normal cruise speed (Mach)		0.40		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DLTA	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.34	0.45	0.11	32%
wingspan (m)	4.50	8.10	3.60	80%
VMO (kt)	146	127	-19	13%
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	99	88	-11	11%
Normal cruise speed (Mach)		0.14		
Average Error				34%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DO27	S22T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.85	1.63	-0.22	12%
wingspan (m)	12.00	11.67	-0.33	3%
VMO (kt)		208		
MMO (Mach)		0.44		
HMO (ft)	22000	25000	3000	14%
Normal cruise speed IAS (kt)	84	135	51	61%
Normal cruise speed (Mach)		0.30		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DO28	DA62		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.72	2.30	-0.42	15%
wingspan (m)	15.55	14.57	-0.98	6%
VMO (kt)	180	201	21	12%
MMO (Mach)		0.45		
HMO (ft)	19400	20000	600	3%
Normal cruise speed IAS (kt)	139	141	2	1%
Normal cruise speed (Mach)		0.29		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DOVE	PA31		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.86	2.95	-0.91	24%
wingspan (m)	17.37	12.40	-4.97	29%
VMO (kt)	180	185	5	3%
MMO (Mach)		0.44		
HMO (ft)	21700	26300	4600	21%
Normal cruise speed IAS (kt)	145	160	15	10%
Normal cruise speed (Mach)		0.44		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DR10	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.78	0.60	-0.18	23%
wingspan (m)	8.72	8.55	-0.17	2%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	90	83	-7	8%
Normal cruise speed (Mach)		0.15		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DR22	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.70	1.11	0.41	59%
wingspan (m)	8.72	10.67	1.95	22%
VMO (kt)	117	126	9	8%
MMO (Mach)		0.24		
HMO (ft)	10000	12000	2000	20%
Normal cruise speed IAS (kt)	110	110	0	0%
Normal cruise speed (Mach)		0.24		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DR30	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.86	0.60	-0.26	30%
wingspan (m)	8.72	9.26	0.54	6%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	15000	14625	-375	2%
Normal cruise speed IAS (kt)	120	98	-22	18%
Normal cruise speed (Mach)		0.17		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DR40	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.10	1.28	0.18	16%
wingspan (m)	8.72	11.63	2.91	33%
VMO (kt)	166	172	6	4%
MMO (Mach)		0.35		
HMO (ft)	15475	16400	925	6%
Normal cruise speed IAS (kt)	120	110	-10	8%
Normal cruise speed (Mach)		0.23		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DT45	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.30	2.13	-0.17	7%
wingspan (m)	11.74	11.60	-0.14	1%
VMO (kt)		209		
MMO (Mach)		0.51		
HMO (ft)	23000	25000	2000	9%
Normal cruise speed IAS (kt)	184	160	-24	13%
Normal cruise speed (Mach)		0.32		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DV2	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	8.17	9.26	1.09	13%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	121	98	-23	19%
Normal cruise speed (Mach)		0.17		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	DV20	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.73	1.16	0.43	59%
wingspan (m)	10.87	11.00	0.13	1%
VMO (kt)	161	160	-1	1%
MMO (Mach)		0.32		
HMO (ft)	13120	14000	880	7%
Normal cruise speed IAS (kt)	115	102	-13	11%
Normal cruise speed (Mach)		0.20		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E110	D228		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.67	6.40	0.73	13%
wingspan (m)	15.33	16.97	1.64	11%
VMO (kt)		220		
MMO (Mach)		0.41		
HMO (ft)	22500	28000	5500	24%
Normal cruise speed IAS (kt)	180	180	0	0%
Normal cruise speed (Mach)		0.34		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E121	MU2		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.60	5.25	-0.35	6%
wingspan (m)	14.05	11.94	-2.11	15%
VMO (kt)		250		
MMO (Mach)		0.57		
HMO (ft)	27000	31000	4000	15%
Normal cruise speed IAS (kt)	250	240	-10	4%
Normal cruise speed (Mach)	0.45	0.48	0.03	7%
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E2	C27J		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	23.56	31.80	8.24	35%
wingspan (m)	24.56	28.70	4.14	17%
VMO (kt)		260		
MMO (Mach)		0.55		
HMO (ft)	30800	30000	-800	3%
Normal cruise speed IAS (kt)	210	200	-10	5%
Normal cruise speed (Mach)	0.55	0.48	-0.07	13%
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E200	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.84	0.95	0.11	13%
wingspan (m)	7.50	8.00	0.50	7%
VMO (kt)	217	220	3	1%
MMO (Mach)		0.45		
HMO (ft)	15000	16000	1000	7%
Normal cruise speed IAS (kt)	130	150	20	15%
Normal cruise speed (Mach)		0.29		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E230	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.56	0.95	0.39	70%
wingspan (m)	7.40	8.00	0.60	8%
VMO (kt)	220	220	0	0%
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)		150		
Normal cruise speed (Mach)		0.29		
Average Error				26%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E314	TEX2		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.19	3.13	-0.06	2%
wingspan (m)	11.14	10.19	-0.95	9%
VMO (kt)	320	316	-4	1%
MMO (Mach)		0.67		
HMO (ft)	35000	31000	-4000	11%
Normal cruise speed IAS (kt)	190	200	10	5%
Normal cruise speed (Mach)		0.47		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E350	TBM7		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)		2.98		
wingspan (m)		12.68		
VMO (kt)		270		
MMO (Mach)		0.64		
HMO (ft)		31000		
Normal cruise speed IAS (kt)		205		
Normal cruise speed (Mach)		0.49		
Average Error				

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E3CF	B762		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	150.82	160.00	9.18	6%
wingspan (m)	44.42	47.57	3.15	7%
VMO (kt)		350		
MMO (Mach)	0.82	0.86	0.04	5%
HMO (ft)	43000	43000	0	0%
Normal cruise speed IAS (kt)	300	310	10	3%
Normal cruise speed (Mach)	0.76	0.80	0.04	5%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E3TF	B762		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	150.82	160.00	9.18	6%
wingspan (m)	44.42	47.57	3.15	7%
VMO (kt)		350		
MMO (Mach)	0.82	0.86	0.04	5%
HMO (ft)	43000	43000	0	0%
Normal cruise speed IAS (kt)		310		
Normal cruise speed (Mach)	0.76	0.80	0.04	5%
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E400	PA34		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.00	2.00	0.00	0%
wingspan (m)	11.50	11.85	0.35	3%
VMO (kt)		203		
MMO (Mach)		0.50		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	150	150	0	0%
Normal cruise speed (Mach)		0.31		
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E530	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.64	7.00	-2.64	27%
wingspan (m)	14.58	9.11	-5.47	38%
VMO (kt)	450	550	100	22%
MMO (Mach)		0.95		
HMO (ft)	45000	50000	5000	11%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)		0.73		
Average Error				25%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E545	E550		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	16.00	17.20	1.20	8%
wingspan (m)	20.25	20.25	0.00	0%
VMO (kt)	320	320	0	0%
MMO (Mach)	0.83	0.83	0.00	0%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)	300	300	0	0%
Normal cruise speed (Mach)	0.78	0.78	0.00	0%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E6	DC87		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	155.13	152.00	-3.13	2%
wingspan (m)	45.16	45.20	0.04	0%
VMO (kt)		375		
MMO (Mach)		0.90		
HMO (ft)	42000	42000	0	0%
Normal cruise speed IAS (kt)	240	300	60	25%
Normal cruise speed (Mach)	0.79	0.80	0.01	1%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E737	B738		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	77.56	78.30	0.74	1%
wingspan (m)	34.30	34.30	0.00	0%
VMO (kt)		340		
MMO (Mach)		0.82		
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.71	0.78	0.07	10%
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	E767	B763		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	175.00	186.88	11.88	7%
wingspan (m)	47.60	47.57	-0.03	0%
VMO (kt)		360		
MMO (Mach)	0.86	0.86	0.00	0%
HMO (ft)	40100	43100	3000	7%
Normal cruise speed IAS (kt)		310		
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EBOY	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.55	0.45	-0.10	18%
wingspan (m)	11.50	8.98	-2.52	22%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	13100	14000	900	7%
Normal cruise speed IAS (kt)	62	60	-2	3%
Normal cruise speed (Mach)		0.12		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ECHO	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.54	0.60	0.06	11%
wingspan (m)	9.60	9.26	-0.34	4%
VMO (kt)	140	143	3	2%
MMO (Mach)		0.29		
HMO (ft)	13200	14625	1425	11%
Normal cruise speed IAS (kt)	80	98	18	22%
Normal cruise speed (Mach)		0.17		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EDGE	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.70	0.95	0.25	36%
wingspan (m)	7.42	8.00	0.58	8%
VMO (kt)	230	220	-10	4%
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)		150		
Normal cruise speed (Mach)		0.29		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EFAN	SVNH		
Engine type	ELC	PST	ELC / PST	
WTC	L	L	0	
MTOW (t)	0.58	0.45	-0.13	22%
wingspan (m)	9.50	8.98	-0.52	5%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	66	60	-6	9%
Normal cruise speed (Mach)		0.12		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EGRT	U2		
Engine type	TBP	JET	TBP / JET	
WTC	L	M	L / M	
MTOW (t)	4.70	11.01	6.31	134%
wingspan (m)	33.00	24.39	-8.61	26%
VMO (kt)		240		
MMO (Mach)		0.80		
HMO (ft)	50000	76000	26000	52%
Normal cruise speed IAS (kt)	140	220	80	57%
Normal cruise speed (Mach)	0.44	0.72	0.28	64%
Average Error				67%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ELIT	C550		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)		6.40		
wingspan (m)		15.90		
VMO (kt)		277		
MMO (Mach)		0.70		
HMO (ft)	41000	43000	2000	5%
Normal cruise speed IAS (kt)	220	220	0	0%
Normal cruise speed (Mach)	0.70	0.63	-0.07	10%
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EM10	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	2.50	5.22	2.72	109%
wingspan (m)	6.60	9.46	2.86	43%
VMO (kt)	600	490	-110	18%
MMO (Mach)	0.90	0.80	-0.10	11%
HMO (ft)		39370		
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				45%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EPIC	BE20		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.40	5.67	2.27	67%
wingspan (m)	13.11	16.61	3.50	27%
VMO (kt)		260		
MMO (Mach)		0.52		
HMO (ft)	34000	35000	1000	3%
Normal cruise speed IAS (kt)	200	225	25	12%
Normal cruise speed (Mach)		0.46		
Average Error				27%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EPX1	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.35	0.45	0.10	29%
wingspan (m)	6.00	8.10	2.10	35%
VMO (kt)	140	127	-13	9%
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	130	88	-42	32%
Normal cruise speed (Mach)		0.14		
Average Error				26%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ERCO	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.57	0.60	0.03	5%
wingspan (m)	9.14	9.26	0.12	1%
VMO (kt)	125	143	18	14%
MMO (Mach)		0.29		
HMO (ft)	13000	14625	1625	12%
Normal cruise speed IAS (kt)	96	98	2	2%
Normal cruise speed (Mach)		0.17		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ESCA	TBM7		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.65	2.98	0.33	12%
wingspan (m)	12.06	12.68	0.62	5%
VMO (kt)		270		
MMO (Mach)		0.64		
HMO (ft)	28000	31000	3000	11%
Normal cruise speed IAS (kt)	210	205	-5	2%
Normal cruise speed (Mach)		0.49		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ETAR	HAWK		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	11.50	6.58	-4.92	43%
wingspan (m)	9.60	9.40	-0.20	2%
VMO (kt)	651	550	-101	16%
MMO (Mach)	1.00	1.04	0.04	4%
HMO (ft)		40000		
Normal cruise speed IAS (kt)		375		
Normal cruise speed (Mach)		0.80		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EUFI	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	21.00	21.77	0.77	4%
wingspan (m)	10.95	10.01	-0.94	9%
VMO (kt)		800		
MMO (Mach)	2.00	2.05	0.05	2%
HMO (ft)	55000	60000	5000	9%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EUPA	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.59	0.60	0.01	2%
wingspan (m)	7.92	9.26	1.34	17%
VMO (kt)	160	143	-17	11%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	101	98	-3	3%
Normal cruise speed (Mach)		0.17		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EVIC	EA50		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	2.50	2.72	0.22	9%
wingspan (m)	11.08	11.60	0.52	5%
VMO (kt)		285		
MMO (Mach)		0.64		
HMO (ft)	28000	41000	13000	46%
Normal cruise speed IAS (kt)	200	190	-10	5%
Normal cruise speed (Mach)		0.63		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EVOP	C340		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.06	2.72	0.66	32%
wingspan (m)	11.28	11.62	0.34	3%
VMO (kt)	255	234	-21	8%
MMO (Mach)	0.64	0.63	-0.01	2%
HMO (ft)	28000	30000	2000	7%
Normal cruise speed IAS (kt)	170	153	-17	10%
Normal cruise speed (Mach)		0.34		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EVOT	TBM7		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.06	2.98	0.92	45%
wingspan (m)	11.28	12.68	1.40	12%
VMO (kt)	256	270	14	5%
MMO (Mach)	0.62	0.64	0.02	3%
HMO (ft)	28000	31000	3000	11%
Normal cruise speed IAS (kt)	195	205	10	5%
Normal cruise speed (Mach)		0.49		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EVSS	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.45	-0.15	25%
wingspan (m)	8.65	8.98	0.33	4%
VMO (kt)	146	109	-37	25%
MMO (Mach)		0.22		
HMO (ft)	13000	14000	1000	8%
Normal cruise speed IAS (kt)	73	60	-13	18%
Normal cruise speed (Mach)		0.12		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	EXPR	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.31	1.40	0.09	7%
wingspan (m)	9.45	9.97	0.52	6%
VMO (kt)		189		
MMO (Mach)		0.42		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)		125		
Normal cruise speed (Mach)		0.23		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F1	HAWK		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	13.70	6.58	-7.12	52%
wingspan (m)	7.88	9.40	1.52	19%
VMO (kt)		550		
MMO (Mach)	1.60	1.04	-0.56	35%
HMO (ft)		40000		
Normal cruise speed IAS (kt)		375		
Normal cruise speed (Mach)		0.80		
Average Error				35%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F104	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	14.06	21.77	7.71	55%
wingspan (m)	6.68	10.01	3.33	50%
VMO (kt)		800		
MMO (Mach)		2.05		
HMO (ft)	58000	60000	2000	3%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				36%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F106	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	15.67	21.77	6.10	39%
wingspan (m)	11.67	10.01	-1.66	14%
VMO (kt)		800		
MMO (Mach)	2.30	2.05	-0.25	11%
HMO (ft)	57000	60000	3000	5%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F111	F15		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	41.50	36.74	-4.76	11%
wingspan (m)	19.20	13.06	-6.14	32%
VMO (kt)	795	800	5	1%
MMO (Mach)	2.20	2.50	0.30	14%
HMO (ft)	51000	65000	14000	27%
Normal cruise speed IAS (kt)		360		
Normal cruise speed (Mach)		0.90		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F117	A10		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	23.81	23.13	-0.68	3%
wingspan (m)	13.20	17.53	4.33	33%
VMO (kt)	525	450	-75	14%
MMO (Mach)	0.90	0.75	-0.15	17%
HMO (ft)		45000		
Normal cruise speed IAS (kt)		215		
Normal cruise speed (Mach)		0.56		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F14	F15		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	33.72	36.74	3.02	9%
wingspan (m)	19.45	13.06	-6.39	33%
VMO (kt)		800		
MMO (Mach)	2.40	2.50	0.10	4%
HMO (ft)		65000		
Normal cruise speed IAS (kt)		360		
Normal cruise speed (Mach)		0.90		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F16X	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	21.80	21.77	-0.03	0%
wingspan (m)	10.44	10.01	-0.43	4%
VMO (kt)		800		
MMO (Mach)	2.05	2.05	0.00	0%
HMO (ft)	50000	60000	10000	20%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F18H	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	23.54	21.77	-1.77	8%
wingspan (m)	12.31	10.01	-2.30	19%
VMO (kt)	800	800	0	0%
MMO (Mach)	2.00	2.05	0.05	2%
HMO (ft)	50000	60000	10000	20%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F18S	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	30.21	21.77	-8.44	28%
wingspan (m)	13.68	10.01	-3.67	27%
VMO (kt)	800	800	0	0%
MMO (Mach)	2.00	2.05	0.05	2%
HMO (ft)	50000	60000	10000	20%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F1FV	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.04	0.95	-0.09	9%
wingspan (m)	7.40	8.00	0.60	8%
VMO (kt)		220		
MMO (Mach)		0.45		
HMO (ft)	12000	16000	4000	33%
Normal cruise speed IAS (kt)	205	150	-55	27%
Normal cruise speed (Mach)		0.29		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F2	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	22.10	21.77	-0.33	1%
wingspan (m)	11.13	10.01	-1.12	10%
VMO (kt)		800		
MMO (Mach)		2.05		
HMO (ft)	59000	60000	1000	2%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)	2.00	0.84	-1.16	58%
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F22	F15		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	27.22	36.74	9.52	35%
wingspan (m)	13.56	13.06	-0.50	4%
VMO (kt)		800		
MMO (Mach)	2.25	2.50	0.25	11%
HMO (ft)	65000	65000	0	0%
Normal cruise speed IAS (kt)		360		
Normal cruise speed (Mach)	1.58	0.90	-0.68	43%
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F260	M20P		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.35	1.53	0.18	13%
wingspan (m)	8.35	11.00	2.65	32%
VMO (kt)	236	196	-40	17%
MMO (Mach)		0.44		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	160	160	0	0%
Normal cruise speed (Mach)		0.29		
Average Error				12%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	F26T	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.35	2.13	0.78	58%
wingspan (m)	8.35	11.60	3.25	39%
VMO (kt)	236	209	-27	11%
MMO (Mach)		0.51		
HMO (ft)	24600	25000	400	2%
Normal cruise speed IAS (kt)	180	160	-20	11%
Normal cruise speed (Mach)		0.32		
Average Error				24%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	F35	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	31.75	21.77	-9.98	31%
wingspan (m)	10.67	10.01	-0.66	6%
VMO (kt)		800		
MMO (Mach)	1.60	2.05	0.45	28%
HMO (ft)		60000		
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				22%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	F4	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	24.77	21.77	-3.00	12%
wingspan (m)	11.70	10.01	-1.69	14%
VMO (kt)		800		
MMO (Mach)		2.05		
HMO (ft)		60000		
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F5	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.38	7.00	-2.38	25%
wingspan (m)	7.70	9.11	1.41	18%
VMO (kt)		550		
MMO (Mach)	1.60	0.95	-0.65	41%
HMO (ft)	50500	50000	-500	1%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)		0.73		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F5SA	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.00	7.00	-2.00	22%
wingspan (m)	8.13	9.11	0.98	12%
VMO (kt)		550		
MMO (Mach)	1.60	0.95	-0.65	41%
HMO (ft)	52500	50000	-2500	5%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)		0.73		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F60	F50		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	22.95	20.82	-2.13	9%
wingspan (m)	29.00	29.00	0.00	0%
VMO (kt)		227		
MMO (Mach)	0.50	0.50	0.00	0%
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	220	224	4	2%
Normal cruise speed (Mach)	0.46	0.46	0.00	0%
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F600	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.40	3.97	0.57	17%
wingspan (m)	15.00	15.88	0.88	6%
VMO (kt)		175		
MMO (Mach)		0.43		
HMO (ft)	24000	25000	1000	4%
Normal cruise speed IAS (kt)	130	150	20	15%
Normal cruise speed (Mach)		0.27		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F8	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	15.00	21.77	6.77	45%
wingspan (m)	10.87	10.01	-0.86	8%
VMO (kt)		800		
MMO (Mach)	1.86	2.05	0.19	10%
HMO (ft)	58000	60000	2000	3%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F86	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	8.23	7.00	-1.23	15%
wingspan (m)	11.30	9.11	-2.19	19%
VMO (kt)	597	550	-47	8%
MMO (Mach)		0.95		
HMO (ft)	49600	50000	400	1%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)		0.73		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	F8L	P28T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.85	1.25	0.40	47%
wingspan (m)	8.00	10.80	2.80	35%
VMO (kt)	208	186	-22	11%
MMO (Mach)		0.40		
HMO (ft)	19000	18400	-600	3%
Normal cruise speed IAS (kt)	130	130	0	0%
Normal cruise speed (Mach)		0.22		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	FA04	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.60	9.26	-0.34	4%
VMO (kt)	119	143	24	20%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	97	98	1	1%
Normal cruise speed (Mach)		0.17		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	FA5X	FA7X		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	31.57	31.75	0.18	1%
wingspan (m)	25.94	26.21	0.27	1%
VMO (kt)		370		
MMO (Mach)	0.90	0.90	0.00	0%
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	FA8X	FA7X		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	33.11	31.75	-1.36	4%
wingspan (m)	26.29	26.21	-0.08	0%
VMO (kt)		370		
MMO (Mach)	0.90	0.90	0.00	0%
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	FBA2	P28T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.59	1.25	-0.34	21%
wingspan (m)	10.97	10.80	-0.17	2%
VMO (kt)		186		
MMO (Mach)		0.40		
HMO (ft)	18000	18400	400	2%
Normal cruise speed IAS (kt)	130	130	0	0%
Normal cruise speed (Mach)		0.22		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	FDCT	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	8.59	9.26	0.67	8%
VMO (kt)	135	143	8	6%
MMO (Mach)		0.29		
HMO (ft)	15000	14625	-375	2%
Normal cruise speed IAS (kt)	95	98	3	3%
Normal cruise speed (Mach)		0.17		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	FFLY	C421		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	6.37	3.38	-2.99	47%
wingspan (m)	13.57	12.53	-1.04	8%
VMO (kt)		238		
MMO (Mach)		0.64		
HMO (ft)	28000	30000	2000	7%
Normal cruise speed IAS (kt)	180	162	-18	10%
Normal cruise speed (Mach)		0.36		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	FLSS	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.75	8.55	-1.20	12%
VMO (kt)	134	108	-26	19%
MMO (Mach)		0.21		
HMO (ft)	12000	12000	0	0%
Normal cruise speed IAS (kt)	85	83	-2	2%
Normal cruise speed (Mach)		0.15		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	FU24	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.59	0.45	-1.14	72%
wingspan (m)	12.81	8.10	-4.71	37%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	17000	16500	-500	3%
Normal cruise speed IAS (kt)	85	88	3	4%
Normal cruise speed (Mach)		0.14		
Average Error				29%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	FURY	C402		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.64	2.86	1.22	74%
wingspan (m)	9.14	12.15	3.01	33%
VMO (kt)		231		
MMO (Mach)		0.62		
HMO (ft)	29500	30000	500	2%
Normal cruise speed IAS (kt)	130	142	12	9%
Normal cruise speed (Mach)		0.32		
Average Error				30%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G109	DIMO		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.85	0.77	-0.08	9%
wingspan (m)	17.37	16.33	-1.04	6%
VMO (kt)	130	141	11	8%
MMO (Mach)		0.25		
HMO (ft)	16500	16400	-100	1%
Normal cruise speed IAS (kt)	85	84	-1	1%
Normal cruise speed (Mach)		0.25		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G115	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.99	1.31	0.32	32%
wingspan (m)	10.00	10.80	0.80	8%
VMO (kt)	184	186	2	1%
MMO (Mach)		0.41		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	115	122	7	6%
Normal cruise speed (Mach)		0.27		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G120	BE36		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.44	1.66	0.22	15%
wingspan (m)	10.18	10.21	0.03	0%
VMO (kt)	220	203	-17	8%
MMO (Mach)		0.44		
HMO (ft)	18000	18500	500	3%
Normal cruise speed IAS (kt)	140	151	11	8%
Normal cruise speed (Mach)		0.26		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G12T	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.51	2.13	0.62	41%
wingspan (m)	10.31	11.60	1.29	13%
VMO (kt)	238	209	-29	12%
MMO (Mach)	0.45	0.51	0.06	13%
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	190	160	-30	16%
Normal cruise speed (Mach)		0.32		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G140	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.80	2.13	0.33	18%
wingspan (m)	10.60	11.60	1.00	9%
VMO (kt)		209		
MMO (Mach)		0.51		
HMO (ft)		25000		
Normal cruise speed IAS (kt)	170	160	-10	6%
Normal cruise speed (Mach)		0.32		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G159	D328		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	15.24	13.64	-1.60	10%
wingspan (m)	23.92	20.98	-2.94	12%
VMO (kt)		270		
MMO (Mach)		0.59		
HMO (ft)	33600	32800	-800	2%
Normal cruise speed IAS (kt)	200	270	70	35%
Normal cruise speed (Mach)	0.50	0.59	0.09	18%
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G160	P750		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.30	3.40	0.10	3%
wingspan (m)	13.00	12.80	-0.20	2%
VMO (kt)		171		
MMO (Mach)		0.38		
HMO (ft)		20000		
Normal cruise speed IAS (kt)	170	140	-30	18%
Normal cruise speed (Mach)		0.23		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G164	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.77	0.45	-2.32	84%
wingspan (m)	10.95	8.10	-2.85	26%
VMO (kt)	128	127	-1	1%
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	90	88	-2	2%
Normal cruise speed (Mach)		0.14		
Average Error				28%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G180	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.61	0.60	-0.01	2%
wingspan (m)	9.58	8.55	-1.03	11%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	10000	12000	2000	20%
Normal cruise speed IAS (kt)	70	83	13	19%
Normal cruise speed (Mach)		0.15		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G200	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.59	0.95	0.36	61%
wingspan (m)	6.10	8.00	1.90	31%
VMO (kt)	219	220	1	0%
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)	150	150	0	0%
Normal cruise speed (Mach)		0.29		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G202	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.72	0.95	0.23	32%
wingspan (m)	6.71	8.00	1.29	19%
VMO (kt)	219	220	1	0%
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)	130	150	20	15%
Normal cruise speed (Mach)		0.29		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G21	BE58		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.64	2.45	-1.19	33%
wingspan (m)	14.94	11.53	-3.41	23%
VMO (kt)		223		
MMO (Mach)		0.50		
HMO (ft)	21300	20688	-612	3%
Normal cruise speed IAS (kt)	144	164	20	14%
Normal cruise speed (Mach)		0.29		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G21M	C414		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	5.67	3.06	-2.61	46%
wingspan (m)	14.94	13.45	-1.49	10%
VMO (kt)		232		
MMO (Mach)		0.63		
HMO (ft)		30000		
Normal cruise speed IAS (kt)		147		
Normal cruise speed (Mach)		0.34		
Average Error				28%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G21T	BE20		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.54	5.67	0.13	2%
wingspan (m)	15.49	16.61	1.12	7%
VMO (kt)		260		
MMO (Mach)		0.52		
HMO (ft)		35000		
Normal cruise speed IAS (kt)		225		
Normal cruise speed (Mach)		0.46		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G222	F27		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	28.00	20.00	-8.00	29%
wingspan (m)	28.70	29.00	0.30	1%
VMO (kt)	210	223	13	6%
MMO (Mach)		0.50		
HMO (ft)	25700	25000	-700	3%
Normal cruise speed IAS (kt)	180	170	-10	6%
Normal cruise speed (Mach)		0.50		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G250	G280		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	17.96	17.96	0.00	0%
wingspan (m)	19.20	19.20	0.00	0%
VMO (kt)	340	340	0	0%
MMO (Mach)	0.85	0.85	0.00	0%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.82	0.82	0.00	0%
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G2GL	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	4.30	5.22	0.92	21%
wingspan (m)	10.47	9.46	-1.01	10%
VMO (kt)	450	490	40	9%
MMO (Mach)		0.80		
HMO (ft)	39375	39370	-5	0%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G2T1	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.82	0.45	-0.37	45%
wingspan (m)	8.13	8.10	-0.03	0%
VMO (kt)	133	127	-6	5%
MMO (Mach)		0.27		
HMO (ft)	17000	16500	-500	3%
Normal cruise speed IAS (kt)	65	88	23	35%
Normal cruise speed (Mach)		0.14		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G3	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.80	8.55	-1.25	13%
VMO (kt)	118	108	-10	8%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	90	83	-7	8%
Normal cruise speed (Mach)		0.15		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G44	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.05	1.16	-0.89	43%
wingspan (m)	12.19	11.00	-1.19	10%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	14600	14000	-600	4%
Normal cruise speed IAS (kt)	100	102	2	2%
Normal cruise speed (Mach)		0.20		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G4SG	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	6.33	5.22	-1.11	18%
wingspan (m)	9.88	9.46	-0.42	4%
VMO (kt)	400	490	90	22%
MMO (Mach)	0.87	0.80	-0.07	8%
HMO (ft)	49200	39370	-9830	20%
Normal cruise speed IAS (kt)	350	250	-100	29%
Normal cruise speed (Mach)		0.50		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G73	C421		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	5.78	3.38	-2.40	42%
wingspan (m)	20.30	12.53	-7.77	38%
VMO (kt)		238		
MMO (Mach)		0.64		
HMO (ft)		30000		
Normal cruise speed IAS (kt)		162		
Normal cruise speed (Mach)		0.36		
Average Error				40%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	G73T	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	6.35	3.97	-2.38	37%
wingspan (m)	20.30	15.88	-4.42	22%
VMO (kt)	187	175	-12	6%
MMO (Mach)		0.43		
HMO (ft)	24500	25000	500	2%
Normal cruise speed IAS (kt)	127	150	23	18%
Normal cruise speed (Mach)		0.27		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GA10	P750		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.15	3.40	1.25	58%
wingspan (m)	12.37	12.80	0.43	3%
VMO (kt)	185	171	-14	8%
MMO (Mach)		0.38		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	130	140	10	8%
Normal cruise speed (Mach)		0.23		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GA20	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.52	1.16	-0.36	24%
wingspan (m)	11.99	11.00	-0.99	8%
VMO (kt)	144	160	16	11%
MMO (Mach)		0.32		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	88	102	14	16%
Normal cruise speed (Mach)		0.20		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GA5C	FA7X		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	34.86	31.75	-3.11	9%
wingspan (m)	26.54	26.21	-0.33	1%
VMO (kt)		370		
MMO (Mach)	0.93	0.90	-0.03	3%
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.85	0.80	-0.05	6%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GA6C	GL5T		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	41.55	41.96	0.41	1%
wingspan (m)	28.96	28.65	-0.31	1%
VMO (kt)		340		
MMO (Mach)	0.93	0.89	-0.04	4%
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		320		
Normal cruise speed (Mach)	0.85	0.85	0.00	0%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GA7	SR22		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.72	1.54	-0.18	10%
wingspan (m)	11.23	11.67	0.44	4%
VMO (kt)	180	204	24	13%
MMO (Mach)		0.43		
HMO (ft)	17500	17500	0	0%
Normal cruise speed IAS (kt)	165	150	-15	9%
Normal cruise speed (Mach)		0.28		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GA8	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.91	1.31	-0.60	31%
wingspan (m)	12.41	10.80	-1.61	13%
VMO (kt)	185	186	1	1%
MMO (Mach)		0.41		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	120	122	2	2%
Normal cruise speed (Mach)		0.27		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GALX	G280		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	15.81	17.96	2.15	14%
wingspan (m)	17.70	19.20	1.50	8%
VMO (kt)	360	340	-20	6%
MMO (Mach)	0.85	0.85	0.00	0%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)	300	300	0	0%
Normal cruise speed (Mach)	0.82	0.82	0.00	0%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GC1	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.78	1.41	0.63	81%
wingspan (m)	8.94	10.97	2.03	23%
VMO (kt)	150	171	21	14%
MMO (Mach)		0.37		
HMO (ft)	18000	18100	100	1%
Normal cruise speed IAS (kt)	100	115	15	15%
Normal cruise speed (Mach)		0.21		
Average Error				27%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GENI	P28U		
Engine type	ELC	PST	ELC / PST	
WTC	L	L	0	
MTOW (t)	0.95	1.31	0.36	38%
wingspan (m)	16.90	10.80	-6.10	36%
VMO (kt)		186		
MMO (Mach)		0.41		
HMO (ft)	19685	20000	315	2%
Normal cruise speed IAS (kt)	70	122	52	74%
Normal cruise speed (Mach)		0.27		
Average Error				37%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GL7T	GLEX		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	48.19	45.13	-3.06	6%
wingspan (m)	31.70	28.65	-3.05	10%
VMO (kt)		340		
MMO (Mach)		0.89		
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		320		
Normal cruise speed (Mach)	0.90	0.85	-0.05	6%
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GLAS	M20P		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.95	1.53	0.58	61%
wingspan (m)	6.81	11.00	4.19	62%
VMO (kt)	207	196	-11	5%
MMO (Mach)		0.44		
HMO (ft)	19000	20000	1000	5%
Normal cruise speed IAS (kt)	160	160	0	0%
Normal cruise speed (Mach)		0.29		
Average Error				27%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GLF2	FA7X		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	31.61	31.75	0.14	0%
wingspan (m)	23.72	26.21	2.49	10%
VMO (kt)		370		
MMO (Mach)	0.85	0.90	0.05	6%
HMO (ft)	45000	51000	6000	13%
Normal cruise speed IAS (kt)	300	300	0	0%
Normal cruise speed (Mach)	0.77	0.80	0.03	4%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GLF3	FA7X		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	31.61	31.75	0.14	0%
wingspan (m)	23.72	26.21	2.49	10%
VMO (kt)		370		
MMO (Mach)	0.85	0.90	0.05	6%
HMO (ft)	45000	51000	6000	13%
Normal cruise speed IAS (kt)	300	300	0	0%
Normal cruise speed (Mach)	0.77	0.80	0.03	4%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GLF4	FA7X		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	33.84	31.75	-2.09	6%
wingspan (m)	23.72	26.21	2.49	10%
VMO (kt)	340	370	30	9%
MMO (Mach)	0.88	0.90	0.02	2%
HMO (ft)	45000	51000	6000	13%
Normal cruise speed IAS (kt)	300	300	0	0%
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GLF6	GLEX		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	45.18	45.13	-0.05	0%
wingspan (m)	30.35	28.65	-1.70	6%
VMO (kt)		340		
MMO (Mach)	0.93	0.89	-0.04	4%
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		320		
Normal cruise speed (Mach)	0.85	0.85	0.00	0%
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GLSP	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.07	1.31	0.24	22%
wingspan (m)	10.67	10.80	0.13	1%
VMO (kt)		186		
MMO (Mach)		0.41		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	114	122	8	7%
Normal cruise speed (Mach)		0.27		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GLST	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.89	1.31	0.42	47%
wingspan (m)	10.67	10.80	0.13	1%
VMO (kt)		186		
MMO (Mach)		0.41		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	140	122	-18	13%
Normal cruise speed (Mach)		0.27		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GM17	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.30	2.13	-1.17	35%
wingspan (m)	12.40	11.60	-0.80	6%
VMO (kt)		209		
MMO (Mach)		0.51		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	159	160	1	1%
Normal cruise speed (Mach)		0.32		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GNAT	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	4.10	5.22	1.12	27%
wingspan (m)	6.73	9.46	2.73	41%
VMO (kt)	480	490	10	2%
MMO (Mach)	0.95	0.80	-0.15	16%
HMO (ft)	48000	39370	-8630	18%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GOLF	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.54	0.60	0.06	11%
wingspan (m)	8.70	9.26	0.56	6%
VMO (kt)	145	143	-2	1%
MMO (Mach)		0.29		
HMO (ft)	13200	14625	1425	11%
Normal cruise speed IAS (kt)	79	98	19	24%
Normal cruise speed (Mach)		0.17		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GP1	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	10.20	8.55	-1.65	16%
VMO (kt)	135	108	-27	20%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	75	83	8	11%
Normal cruise speed (Mach)		0.15		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GP4	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.91	1.40	0.49	54%
wingspan (m)	7.30	9.97	2.67	37%
VMO (kt)	222	189	-33	15%
MMO (Mach)		0.42		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)		125		
Normal cruise speed (Mach)		0.23		
Average Error				26%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GRIZ	P750		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.50	3.40	0.90	36%
wingspan (m)	14.17	12.80	-1.37	10%
VMO (kt)	165	171	6	4%
MMO (Mach)		0.38		
HMO (ft)		20000		
Normal cruise speed IAS (kt)	125	140	15	12%
Normal cruise speed (Mach)		0.23		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GSPN	C550		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	6.30	6.40	0.10	2%
wingspan (m)	14.86	15.90	1.04	7%
VMO (kt)	272	277	5	2%
MMO (Mach)	0.70	0.70	0.00	0%
HMO (ft)	41000	43000	2000	5%
Normal cruise speed IAS (kt)	240	220	-20	8%
Normal cruise speed (Mach)		0.63		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	GY80	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.15	0.60	-0.55	48%
wingspan (m)	9.70	9.26	-0.44	5%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	15400	14625	-775	5%
Normal cruise speed IAS (kt)	95	98	3	3%
Normal cruise speed (Mach)		0.17		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	H25C	G150		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	14.06	11.84	-2.22	16%
wingspan (m)	15.66	16.94	1.28	8%
VMO (kt)		330		
MMO (Mach)	0.87	0.85	-0.02	2%
HMO (ft)	43000	45000	2000	5%
Normal cruise speed IAS (kt)	300	300	0	0%
Normal cruise speed (Mach)		0.78		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	H40	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.85	0.45	-0.40	47%
wingspan (m)	10.76	8.10	-2.66	25%
VMO (kt)	134	127	-7	5%
MMO (Mach)		0.27		
HMO (ft)	14800	16500	1700	11%
Normal cruise speed IAS (kt)	76	88	12	16%
Normal cruise speed (Mach)		0.14		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HAR	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	11.43	7.00	-4.43	39%
wingspan (m)	9.04	9.11	0.07	1%
VMO (kt)	635	550	-85	13%
MMO (Mach)	1.30	0.95	-0.35	27%
HMO (ft)	51200	50000	-1200	2%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)		0.73		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HDJT	C25A		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	4.81	5.67	0.86	18%
wingspan (m)	12.12	15.19	3.07	25%
VMO (kt)	270	278	8	3%
MMO (Mach)	0.72	0.74	0.02	3%
HMO (ft)	43000	45000	2000	5%
Normal cruise speed IAS (kt)	265	275	10	4%
Normal cruise speed (Mach)	0.71	0.71	0.00	0%
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HERN	DA42		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	6.14	1.78	-4.36	71%
wingspan (m)	21.80	13.42	-8.38	38%
VMO (kt)		155		
MMO (Mach)		0.29		
HMO (ft)	18500	18000	-500	3%
Normal cruise speed IAS (kt)	129	124	-5	4%
Normal cruise speed (Mach)		0.27		
Average Error				29%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HF20	H25A		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.20	9.85	0.65	7%
wingspan (m)	14.49	15.66	1.17	8%
VMO (kt)		285		
MMO (Mach)		0.76		
HMO (ft)	37500	41000	3500	9%
Normal cruise speed IAS (kt)		270		
Normal cruise speed (Mach)		0.75		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HR10	M20P		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.40	1.53	0.13	9%
wingspan (m)	9.08	11.00	1.92	21%
VMO (kt)	185	196	11	6%
MMO (Mach)		0.44		
HMO (ft)	18700	20000	1300	7%
Normal cruise speed IAS (kt)	160	160	0	0%
Normal cruise speed (Mach)		0.29		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HR20	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.78	0.60	-0.18	23%
wingspan (m)	8.33	8.55	0.22	3%
VMO (kt)	160	108	-52	32%
MMO (Mach)		0.21		
HMO (ft)	12800	12000	-800	6%
Normal cruise speed IAS (kt)	85	83	-2	2%
Normal cruise speed (Mach)		0.15		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HRNT	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.00	8.55	-0.45	5%
VMO (kt)	90	108	18	20%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	90	83	-7	8%
Normal cruise speed (Mach)		0.15		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HU1	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.05	1.11	0.06	6%
wingspan (m)	17.00	10.67	-6.33	37%
VMO (kt)		126		
MMO (Mach)		0.24		
HMO (ft)		12000		
Normal cruise speed IAS (kt)		110		
Normal cruise speed (Mach)		0.24		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HU2	DIMO		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.77	0.02	3%
wingspan (m)	14.92	16.33	1.41	9%
VMO (kt)		141		
MMO (Mach)		0.25		
HMO (ft)		16400		
Normal cruise speed IAS (kt)		84		
Normal cruise speed (Mach)		0.25		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HUNT	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	11.16	7.00	-4.16	37%
wingspan (m)	10.26	9.11	-1.15	11%
VMO (kt)	620	550	-70	11%
MMO (Mach)		0.95		
HMO (ft)	50000	50000	0	0%
Normal cruise speed IAS (kt)	260	280	20	8%
Normal cruise speed (Mach)		0.73		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HURK	BE20		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.20	5.67	2.47	77%
wingspan (m)	9.97	16.61	6.64	67%
VMO (kt)		260		
MMO (Mach)		0.52		
HMO (ft)	34700	35000	300	1%
Normal cruise speed IAS (kt)		225		
Normal cruise speed (Mach)		0.46		
Average Error				48%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HUSK	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.82	1.41	0.59	72%
wingspan (m)	10.73	10.97	0.24	2%
VMO (kt)	132	170	38	29%
MMO (Mach)		0.38		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	105	123	18	17%
Normal cruise speed (Mach)		0.25		
Average Error				24%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	HYPR	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.45	-0.02	4%
wingspan (m)	9.26	8.98	-0.28	3%
VMO (kt)	104	109	5	5%
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	65	60	-5	8%
Normal cruise speed (Mach)		0.12		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	IA63	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.00	5.22	0.22	4%
wingspan (m)	9.69	9.46	-0.23	2%
VMO (kt)	405	490	85	21%
MMO (Mach)	0.81	0.80	-0.01	1%
HMO (ft)	42320	39370	-2950	7%
Normal cruise speed IAS (kt)	335	250	-85	25%
Normal cruise speed (Mach)		0.50		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	IL18	C130		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	61.20	81.54	20.34	33%
wingspan (m)	37.40	40.41	3.01	8%
VMO (kt)		310		
MMO (Mach)		0.64		
HMO (ft)	32800	33000	200	1%
Normal cruise speed IAS (kt)	220	220	0	0%
Normal cruise speed (Mach)	0.75	0.61	-0.14	19%
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	IL38	B734		
Engine type	TBP	JET	TBP / JET	
WTC	M	M	0	
MTOW (t)	66.00	68.00	2.00	3%
wingspan (m)	37.42	28.90	-8.52	23%
VMO (kt)		340		
MMO (Mach)	0.65	0.82	0.17	26%
HMO (ft)	36100	37000	900	2%
Normal cruise speed IAS (kt)	210	280	70	33%
Normal cruise speed (Mach)		0.74		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	IL62	A30B		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	162.00	165.00	3.00	2%
wingspan (m)	43.20	44.84	1.64	4%
VMO (kt)		345		
MMO (Mach)	0.86	0.82	-0.04	5%
HMO (ft)	39000	39000	0	0%
Normal cruise speed IAS (kt)	280	300	20	7%
Normal cruise speed (Mach)	0.78	0.78	0.00	0%
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	IMPU	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.95	0.20	27%
wingspan (m)	8.74	8.00	-0.74	8%
VMO (kt)		220		
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)	150	150	0	0%
Normal cruise speed (Mach)		0.29		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	IR23	SR20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.38	1.38	0.00	0%
wingspan (m)	10.00	11.68	1.68	17%
VMO (kt)	215	204	-11	5%
MMO (Mach)		0.43		
HMO (ft)	18375	17500	-875	5%
Normal cruise speed IAS (kt)	135	127	-8	6%
Normal cruise speed (Mach)		0.24		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	IR99	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.56	5.22	-0.34	6%
wingspan (m)	9.85	9.46	-0.39	4%
VMO (kt)	467	490	23	5%
MMO (Mach)	0.76	0.80	0.04	5%
HMO (ft)	42325	39370	-2955	7%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	IS28	DIMO		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.77	0.02	3%
wingspan (m)	17.00	16.33	-0.67	4%
VMO (kt)	114	141	27	24%
MMO (Mach)		0.25		
HMO (ft)	16400	16400	0	0%
Normal cruise speed IAS (kt)	70	84	14	20%
Normal cruise speed (Mach)		0.25		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	J10	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	18.60	21.77	3.17	17%
wingspan (m)	9.75	10.01	0.26	3%
VMO (kt)	795	800	5	1%
MMO (Mach)	1.80	2.05	0.25	14%
HMO (ft)	55780	60000	4220	8%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	J20	F15		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	36.29	36.74	0.45	1%
wingspan (m)	13.00	13.06	0.06	0%
VMO (kt)		800		
MMO (Mach)	1.80	2.50	0.70	39%
HMO (ft)		65000		
Normal cruise speed IAS (kt)		360		
Normal cruise speed (Mach)		0.90		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	J328	E135		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	15.20	19.99	4.79	32%
wingspan (m)	20.98	20.04	-0.94	4%
VMO (kt)		320		
MMO (Mach)		0.78		
HMO (ft)	35000	37000	2000	6%
Normal cruise speed IAS (kt)	260	270	10	4%
Normal cruise speed (Mach)	0.66	0.60	-0.06	9%
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	JAB2	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.54	0.60	0.06	11%
wingspan (m)	8.12	8.55	0.43	5%
VMO (kt)	140	108	-32	23%
MMO (Mach)		0.21		
HMO (ft)	10000	12000	2000	20%
Normal cruise speed IAS (kt)	80	83	3	4%
Normal cruise speed (Mach)		0.15		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	JAB4	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.70	0.60	-0.10	14%
wingspan (m)	8.10	9.26	1.16	14%
VMO (kt)	138	143	5	4%
MMO (Mach)		0.29		
HMO (ft)	10000	14625	4625	46%
Normal cruise speed IAS (kt)	98	98	0	0%
Normal cruise speed (Mach)		0.17		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	JABI	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.45	0.45	0.00	0%
wingspan (m)	8.03	8.10	0.07	1%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	85	88	3	4%
Normal cruise speed (Mach)		0.14		
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	JAGR	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	15.70	21.77	6.07	39%
wingspan (m)	8.69	10.01	1.32	15%
VMO (kt)	729	800	71	10%
MMO (Mach)	1.60	2.05	0.45	28%
HMO (ft)		60000		
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	JPRO	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	4.17	5.22	1.05	25%
wingspan (m)	10.77	9.46	-1.31	12%
VMO (kt)	400	490	90	22%
MMO (Mach)	0.70	0.80	0.10	14%
HMO (ft)	36750	39370	2620	7%
Normal cruise speed IAS (kt)	200	250	50	25%
Normal cruise speed (Mach)		0.50		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	JS1	D228		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.67	6.40	0.73	13%
wingspan (m)	15.85	16.97	1.12	7%
VMO (kt)	215	220	5	2%
MMO (Mach)		0.41		
HMO (ft)	25000	28000	3000	12%
Normal cruise speed IAS (kt)	180	180	0	0%
Normal cruise speed (Mach)		0.34		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	JS20	D228		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.67	6.40	0.73	13%
wingspan (m)	15.85	16.97	1.12	7%
VMO (kt)	215	220	5	2%
MMO (Mach)		0.41		
HMO (ft)	25000	28000	3000	12%
Normal cruise speed IAS (kt)	180	180	0	0%
Normal cruise speed (Mach)		0.34		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	JS3	D228		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.67	6.40	0.73	13%
wingspan (m)	15.85	16.97	1.12	7%
VMO (kt)	215	220	5	2%
MMO (Mach)		0.41		
HMO (ft)	25000	28000	3000	12%
Normal cruise speed IAS (kt)	190	180	-10	5%
Normal cruise speed (Mach)		0.34		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	JS31	JS32		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	6.95	7.35	0.40	6%
wingspan (m)	15.85	15.85	0.00	0%
VMO (kt)	230	250	20	9%
MMO (Mach)		0.52		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	180	200	20	11%
Normal cruise speed (Mach)		0.41		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	JU52	SH36		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	9.21	12.29	3.08	33%
wingspan (m)	29.25	22.80	-6.45	22%
VMO (kt)		200		
MMO (Mach)		0.44		
HMO (ft)	17000	20000	3000	18%
Normal cruise speed IAS (kt)	100	180	80	80%
Normal cruise speed (Mach)		0.33		
Average Error				38%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	K250	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.13	1.16	0.03	3%
wingspan (m)	11.20	11.00	-0.20	2%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	13000	14000	1000	8%
Normal cruise speed IAS (kt)	100	102	2	2%
Normal cruise speed (Mach)		0.20		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	K35A	B703		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	134.69	140.00	5.31	4%
wingspan (m)	39.88	44.10	4.22	11%
VMO (kt)		375		
MMO (Mach)	0.93	0.90	-0.03	3%
HMO (ft)	40000	42000	2000	5%
Normal cruise speed IAS (kt)	300	300	0	0%
Normal cruise speed (Mach)		0.80		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	K35E	B703		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	143.34	140.00	-3.34	2%
wingspan (m)	39.88	44.10	4.22	11%
VMO (kt)		375		
MMO (Mach)		0.90		
HMO (ft)	45000	42000	-3000	7%
Normal cruise speed IAS (kt)	270	300	30	11%
Normal cruise speed (Mach)		0.80		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	K35R	B703		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	146.30	140.00	-6.30	4%
wingspan (m)	39.88	44.10	4.22	11%
VMO (kt)		375		
MMO (Mach)	0.93	0.90	-0.03	3%
HMO (ft)	50000	42000	-8000	16%
Normal cruise speed IAS (kt)	300	300	0	0%
Normal cruise speed (Mach)		0.80		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	KAT3	P46T		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.00	2.31	-0.69	23%
wingspan (m)	13.40	13.11	-0.29	2%
VMO (kt)		187		
MMO (Mach)		0.51		
HMO (ft)		30000		
Normal cruise speed IAS (kt)	162	160	-2	1%
Normal cruise speed (Mach)		0.36		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	KC39	A321		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	80.98	83.00	2.02	2%
wingspan (m)	35.05	34.10	-0.95	3%
VMO (kt)	300	350	50	17%
MMO (Mach)	0.80	0.82	0.02	2%
HMO (ft)	36000	39100	3100	9%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.79	0.78	-0.01	1%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	KE3	DC87		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	151.32	152.00	0.68	0%
wingspan (m)	44.42	45.20	0.78	2%
VMO (kt)		375		
MMO (Mach)	0.95	0.90	-0.05	5%
HMO (ft)	39000	42000	3000	8%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.83	0.80	-0.03	4%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	KEST	TBM8		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.63	3.35	-0.28	8%
wingspan (m)	13.11	12.68	-0.43	3%
VMO (kt)		270		
MMO (Mach)		0.64		
HMO (ft)	31000	31000	0	0%
Normal cruise speed IAS (kt)	230	220	-10	4%
Normal cruise speed (Mach)		0.53		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	KFIR	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	16.20	21.77	5.57	34%
wingspan (m)	8.22	10.01	1.79	22%
VMO (kt)	750	800	50	7%
MMO (Mach)	2.30	2.05	-0.25	11%
HMO (ft)	58000	60000	2000	3%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	KL07	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.20	1.16	-0.04	3%
wingspan (m)	10.81	11.00	0.19	2%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	14000	14000	0	0%
Normal cruise speed IAS (kt)	90	102	12	13%
Normal cruise speed (Mach)		0.20		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	KODI	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.29	3.97	0.68	21%
wingspan (m)	13.72	15.88	2.16	16%
VMO (kt)	180	175	-5	3%
MMO (Mach)		0.43		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	140	150	10	7%
Normal cruise speed (Mach)		0.27		
Average Error				9%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	KP2	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.60	0.13	28%
wingspan (m)	9.90	9.26	-0.64	6%
VMO (kt)	140	143	3	2%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	95	98	3	3%
Normal cruise speed (Mach)		0.17		
Average Error				10%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	KP5	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.58	0.60	0.02	3%
wingspan (m)	9.90	9.26	-0.64	6%
VMO (kt)	140	143	3	2%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	95	98	3	3%
Normal cruise speed (Mach)		0.17		
Average Error				4%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	KR30	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.45	-0.02	4%
wingspan (m)	10.76	8.10	-2.66	25%
VMO (kt)	124	127	3	2%
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	85	88	3	4%
Normal cruise speed (Mach)		0.14		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	KT1	TEX2		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.31	3.13	-0.18	5%
wingspan (m)	10.59	10.19	-0.40	4%
VMO (kt)	310	316	6	2%
MMO (Mach)		0.67		
HMO (ft)	37000	31000	-6000	16%
Normal cruise speed IAS (kt)	180	200	20	11%
Normal cruise speed (Mach)		0.47		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L12	B58T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	4.17	2.81	-1.36	33%
wingspan (m)	15.09	11.53	-3.56	24%
VMO (kt)		235		
MMO (Mach)		0.43		
HMO (ft)	22900	25000	2100	9%
Normal cruise speed IAS (kt)	150	160	10	7%
Normal cruise speed (Mach)		0.35		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L159	HAWK		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	8.00	6.58	-1.42	18%
wingspan (m)	9.54	9.40	-0.14	1%
VMO (kt)	518	550	32	6%
MMO (Mach)		1.04		
HMO (ft)	43300	40000	-3300	8%
Normal cruise speed IAS (kt)		375		
Normal cruise speed (Mach)		0.80		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L188	C160		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	52.67	49.15	-3.52	7%
wingspan (m)	30.17	40.00	9.83	33%
VMO (kt)		240		
MMO (Mach)		0.67		
HMO (ft)	28400	30000	1600	6%
Normal cruise speed IAS (kt)		160		
Normal cruise speed (Mach)		0.38		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L200	BE36		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.95	1.66	-0.29	15%
wingspan (m)	12.31	10.21	-2.10	17%
VMO (kt)		203		
MMO (Mach)		0.44		
HMO (ft)	18700	18500	-200	1%
Normal cruise speed IAS (kt)	152	151	-1	1%
Normal cruise speed (Mach)		0.26		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L29	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	3.55	5.22	1.67	47%
wingspan (m)	10.30	9.46	-0.84	8%
VMO (kt)	443	490	47	11%
MMO (Mach)	0.75	0.80	0.05	7%
HMO (ft)	36100	39370	3270	9%
Normal cruise speed IAS (kt)	170	250	80	47%
Normal cruise speed (Mach)		0.50		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L29A	CL60		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	19.05	20.23	1.18	6%
wingspan (m)	16.60	19.61	3.01	18%
VMO (kt)		365		
MMO (Mach)		0.85		
HMO (ft)	39400	41000	1600	4%
Normal cruise speed IAS (kt)	280	280	0	0%
Normal cruise speed (Mach)		0.77		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L29B	CL60		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	19.84	20.23	0.39	2%
wingspan (m)	16.60	19.61	3.01	18%
VMO (kt)		365		
MMO (Mach)	0.87	0.85	-0.02	2%
HMO (ft)	36000	41000	5000	14%
Normal cruise speed IAS (kt)	280	280	0	0%
Normal cruise speed (Mach)	0.77	0.77	0.00	0%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L37	JS41		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	15.00	10.43	-4.57	30%
wingspan (m)	20.00	18.29	-1.71	9%
VMO (kt)		250		
MMO (Mach)		0.52		
HMO (ft)	26300	26000	-300	1%
Normal cruise speed IAS (kt)	147	200	53	36%
Normal cruise speed (Mach)		0.42		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L59	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	7.00	5.22	-1.78	25%
wingspan (m)	9.54	9.46	-0.08	1%
VMO (kt)	496	490	-6	1%
MMO (Mach)	0.82	0.80	-0.02	2%
HMO (ft)	38480	39370	890	2%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L6	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.00	0.45	-1.55	78%
wingspan (m)	14.20	8.98	-5.22	37%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	13120	14000	880	7%
Normal cruise speed IAS (kt)	70	60	-10	14%
Normal cruise speed (Mach)		0.12		
Average Error				34%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L60	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.42	1.16	-0.26	18%
wingspan (m)	13.96	11.00	-2.96	21%
VMO (kt)	104	160	56	54%
MMO (Mach)		0.32		
HMO (ft)	14764	14000	-764	5%
Normal cruise speed IAS (kt)	95	102	7	7%
Normal cruise speed (Mach)		0.20		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L70	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.25	1.28	0.03	2%
wingspan (m)	9.85	11.63	1.78	18%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)	16400	16400	0	0%
Normal cruise speed IAS (kt)	112	110	-2	2%
Normal cruise speed (Mach)		0.23		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	L90	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.60	2.13	0.53	33%
wingspan (m)	10.34	11.60	1.26	12%
VMO (kt)	251	209	-42	17%
MMO (Mach)		0.51		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	132	160	28	21%
Normal cruise speed (Mach)		0.32		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LA25	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.42	1.16	-0.26	18%
wingspan (m)	11.68	11.00	-0.68	6%
VMO (kt)	148	160	12	8%
MMO (Mach)		0.32		
HMO (ft)	14700	14000	-700	5%
Normal cruise speed IAS (kt)	110	102	-8	7%
Normal cruise speed (Mach)		0.20		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LA4	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.09	1.16	0.07	6%
wingspan (m)	11.58	11.00	-0.58	5%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	14000	14000	0	0%
Normal cruise speed IAS (kt)	88	102	14	16%
Normal cruise speed (Mach)		0.20		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LA8	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.72	1.28	-1.44	53%
wingspan (m)	14.40	11.63	-2.77	19%
VMO (kt)	160	172	12	8%
MMO (Mach)		0.35		
HMO (ft)	17000	16400	-600	4%
Normal cruise speed IAS (kt)	100	110	10	10%
Normal cruise speed (Mach)		0.23		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LANC	F27		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	31.75	20.00	-11.75	37%
wingspan (m)	31.10	29.00	-2.10	7%
VMO (kt)		223		
MMO (Mach)		0.50		
HMO (ft)	24500	25000	500	2%
Normal cruise speed IAS (kt)	137	170	33	24%
Normal cruise speed (Mach)		0.50		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LCR	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)		0.60		
wingspan (m)	8.53	8.55	0.02	0%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	83	83	0	0%
Normal cruise speed (Mach)		0.15		
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LEG2	BE36		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.00	1.66	0.66	66%
wingspan (m)	7.77	10.21	2.44	31%
VMO (kt)		203		
MMO (Mach)		0.44		
HMO (ft)	18000	18500	500	3%
Normal cruise speed IAS (kt)	180	151	-29	16%
Normal cruise speed (Mach)		0.26		
Average Error				29%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LESP	M20T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.59	1.53	-0.06	4%
wingspan (m)	10.82	11.13	0.31	3%
VMO (kt)	220	196	-24	11%
MMO (Mach)		0.48		
HMO (ft)	24000	25000	1000	4%
Normal cruise speed IAS (kt)	176	180	4	2%
Normal cruise speed (Mach)		0.37		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LGEZ	C402		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	2.86	2.26	377%
wingspan (m)	7.96	12.15	4.19	53%
VMO (kt)	190	231	41	22%
MMO (Mach)		0.62		
HMO (ft)	27000	30000	3000	11%
Normal cruise speed IAS (kt)	105	142	37	35%
Normal cruise speed (Mach)		0.32		
Average Error				99%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LJ23	C25A		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.67	5.67	0.00	0%
wingspan (m)	10.84	15.19	4.35	40%
VMO (kt)		278		
MMO (Mach)		0.74		
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)		275		
Normal cruise speed (Mach)	0.78	0.71	-0.07	9%
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LJ24	C25A		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.90	5.67	-0.23	4%
wingspan (m)	10.84	15.19	4.35	40%
VMO (kt)		278		
MMO (Mach)		0.74		
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)		275		
Normal cruise speed (Mach)	0.78	0.71	-0.07	9%
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LJ25	LJ45		
Engine type	JET	JET	0	
WTC	L	M	L / M	
MTOW (t)	6.80	9.30	2.50	37%
wingspan (m)	10.84	14.56	3.72	34%
VMO (kt)		330		
MMO (Mach)	0.81	0.81	0.00	0%
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.77	0.76	-0.01	1%
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LJ28	LJ45		
Engine type	JET	JET	0	
WTC	L	M	L / M	
MTOW (t)	6.80	9.30	2.50	37%
wingspan (m)	13.35	14.56	1.21	9%
VMO (kt)		330		
MMO (Mach)	0.81	0.81	0.00	0%
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.78	0.76	-0.02	3%
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LJ31	LJ45		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	7.71	9.30	1.59	21%
wingspan (m)	13.36	14.56	1.20	9%
VMO (kt)		330		
MMO (Mach)	0.81	0.81	0.00	0%
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.77	0.76	-0.01	1%
Average Error				6%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	LJ40	LJ45		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.23	9.30	0.07	1%
wingspan (m)	14.56	14.56	0.00	0%
VMO (kt)	330	330	0	0%
MMO (Mach)	0.81	0.81	0.00	0%
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.79	0.76	-0.03	4%
Average Error				1%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	LJ55	LJ60		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.53	10.66	1.13	12%
wingspan (m)	13.34	13.35	0.01	0%
VMO (kt)	350	340	-10	3%
MMO (Mach)	0.81	0.81	0.00	0%
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.78	0.79	0.01	1%
Average Error				3%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	LJ70	C650		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.75	10.43	0.68	7%
wingspan (m)	15.51	16.31	0.80	5%
VMO (kt)		336		
MMO (Mach)		0.83		
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LJ75	C650		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.75	10.43	0.68	7%
wingspan (m)	15.51	16.31	0.80	5%
VMO (kt)		336		
MMO (Mach)		0.83		
HMO (ft)	51000	51000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LJ85	FA50		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	16.13	18.01	1.88	12%
wingspan (m)	18.75	18.85	0.10	1%
VMO (kt)		370		
MMO (Mach)		0.86		
HMO (ft)	49000	49000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.80	0.80	0.00	0%
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LN3	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	10.83	9.26	-1.57	14%
VMO (kt)	152	143	-9	6%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	85	98	13	15%
Normal cruise speed (Mach)		0.17		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LNC2	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.64	1.40	0.76	119%
wingspan (m)	7.16	9.97	2.81	39%
VMO (kt)		189		
MMO (Mach)		0.42		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	140	125	-15	11%
Normal cruise speed (Mach)		0.23		
Average Error				42%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LNC4	TBM7		
Engine type	PST	TBP	PST / TBP	
WTC	L	L	0	
MTOW (t)	1.61	2.98	1.37	85%
wingspan (m)	9.19	12.68	3.49	38%
VMO (kt)	274	270	-4	1%
MMO (Mach)		0.64		
HMO (ft)	29000	31000	2000	7%
Normal cruise speed IAS (kt)	200	205	5	2%
Normal cruise speed (Mach)		0.49		
Average Error				27%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LNCE	SR22		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.45	1.54	0.09	6%
wingspan (m)	10.82	11.67	0.85	8%
VMO (kt)	220	204	-16	7%
MMO (Mach)		0.43		
HMO (ft)	18000	17500	-500	3%
Normal cruise speed IAS (kt)	159	150	-9	6%
Normal cruise speed (Mach)		0.28		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LNP4	TBM7		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.72	2.98	1.26	73%
wingspan (m)	9.93	12.68	2.75	28%
VMO (kt)	270	270	0	0%
MMO (Mach)		0.64		
HMO (ft)	29000	31000	2000	7%
Normal cruise speed IAS (kt)	220	205	-15	7%
Normal cruise speed (Mach)		0.49		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LW20	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	8.70	8.55	-0.15	2%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	10000	12000	2000	20%
Normal cruise speed IAS (kt)	100	83	-17	17%
Normal cruise speed (Mach)		0.15		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LW40	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.10	1.11	0.01	1%
wingspan (m)	8.70	10.67	1.97	23%
VMO (kt)		126		
MMO (Mach)		0.24		
HMO (ft)	10000	12000	2000	20%
Normal cruise speed IAS (kt)	130	110	-20	15%
Normal cruise speed (Mach)		0.24		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	LWIN	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.45	-0.15	25%
wingspan (m)	9.50	8.98	-0.52	5%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	60	60	0	0%
Normal cruise speed (Mach)		0.12		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M106	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.45	0.45	0.00	0%
wingspan (m)	9.32	8.98	-0.34	4%
VMO (kt)	113	109	-4	4%
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	70	60	-10	14%
Normal cruise speed (Mach)		0.12		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M108	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.32	8.55	-0.77	8%
VMO (kt)	112	108	-4	4%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	70	83	13	19%
Normal cruise speed (Mach)		0.15		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M10F	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)		1.11		
wingspan (m)	9.10	10.67	1.57	17%
VMO (kt)		126		
MMO (Mach)		0.24		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	111	110	-1	1%
Normal cruise speed (Mach)		0.24		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M10R	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)		1.40		
wingspan (m)	9.10	9.97	0.87	10%
VMO (kt)		189		
MMO (Mach)		0.42		
HMO (ft)		20000		
Normal cruise speed IAS (kt)	127	125	-2	2%
Normal cruise speed (Mach)		0.23		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M15	P750		
Engine type	JET	TBP	JET / TBP	
WTC	L	L	0	
MTOW (t)	5.65	3.40	-2.25	40%
wingspan (m)	22.40	12.80	-9.60	43%
VMO (kt)		171		
MMO (Mach)		0.38		
HMO (ft)		20000		
Normal cruise speed IAS (kt)	76	140	64	84%
Normal cruise speed (Mach)		0.23		
Average Error				56%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M17	U2		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	19.95	11.01	-8.94	45%
wingspan (m)	40.32	24.39	-15.93	40%
VMO (kt)	179	240	61	34%
MMO (Mach)	0.70	0.80	0.10	14%
HMO (ft)	70500	76000	5500	8%
Normal cruise speed IAS (kt)		220		
Normal cruise speed (Mach)		0.72		
Average Error				28%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M18	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	4.70	1.40	-3.30	70%
wingspan (m)	17.70	9.97	-7.73	44%
VMO (kt)	151	189	38	25%
MMO (Mach)		0.47		
HMO (ft)	21400	25000	3600	17%
Normal cruise speed IAS (kt)	100	132	32	32%
Normal cruise speed (Mach)		0.28		
Average Error				38%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M2	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.40	9.26	-0.14	1%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	120	98	-22	18%
Normal cruise speed (Mach)		0.17		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M200	BE36		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.36	1.66	0.30	22%
wingspan (m)	9.30	10.21	0.91	10%
VMO (kt)		203		
MMO (Mach)		0.44		
HMO (ft)	18500	18500	0	0%
Normal cruise speed IAS (kt)	150	151	1	1%
Normal cruise speed (Mach)		0.26		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M21	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.60	0.60	-3.00	83%
wingspan (m)	14.51	9.26	-5.25	36%
VMO (kt)	145	143	-2	1%
MMO (Mach)		0.29		
HMO (ft)	13200	14625	1425	11%
Normal cruise speed IAS (kt)	80	98	18	22%
Normal cruise speed (Mach)		0.17		
Average Error				31%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M212	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.15	1.31	0.16	14%
wingspan (m)	9.80	10.80	1.00	10%
VMO (kt)	183	186	3	2%
MMO (Mach)		0.41		
HMO (ft)		20000		
Normal cruise speed IAS (kt)	112	122	10	9%
Normal cruise speed (Mach)		0.27		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M22	PA34		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.67	2.00	0.33	20%
wingspan (m)	10.67	11.85	1.18	11%
VMO (kt)		203		
MMO (Mach)		0.50		
HMO (ft)	24000	25000	1000	4%
Normal cruise speed IAS (kt)	155	150	-5	3%
Normal cruise speed (Mach)		0.31		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M24	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	5.00	1.16	-3.84	77%
wingspan (m)	19.90	11.00	-8.90	45%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	13200	14000	800	6%
Normal cruise speed IAS (kt)	100	102	2	2%
Normal cruise speed (Mach)		0.20		
Average Error				32%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M26	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.40	1.40	0.00	0%
wingspan (m)	8.60	9.97	1.37	16%
VMO (kt)	215	189	-26	12%
MMO (Mach)		0.42		
HMO (ft)		20000		
Normal cruise speed IAS (kt)		125		
Normal cruise speed (Mach)		0.23		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M28	JS32		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	7.50	7.35	-0.15	2%
wingspan (m)	22.07	15.85	-6.22	28%
VMO (kt)	186	250	64	34%
MMO (Mach)		0.52		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	160	200	40	25%
Normal cruise speed (Mach)		0.41		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M339	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	6.35	5.22	-1.13	18%
wingspan (m)	11.22	9.46	-1.76	16%
VMO (kt)	500	490	-10	2%
MMO (Mach)	0.82	0.80	-0.02	2%
HMO (ft)	46700	39370	-7330	16%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)	0.80	0.50	-0.30	38%
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M346	HAWK		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.50	6.58	-2.92	31%
wingspan (m)	9.72	9.40	-0.32	3%
VMO (kt)	572	550	-22	4%
MMO (Mach)	1.20	1.04	-0.16	13%
HMO (ft)	45000	40000	-5000	11%
Normal cruise speed IAS (kt)		375		
Normal cruise speed (Mach)	1.15	0.80	-0.35	30%
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M4	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.04	1.31	0.27	26%
wingspan (m)	9.40	10.80	1.40	15%
VMO (kt)		186		
MMO (Mach)		0.41		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	117	122	5	4%
Normal cruise speed (Mach)		0.27		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M5	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.04	1.40	0.36	35%
wingspan (m)	9.40	9.97	0.57	6%
VMO (kt)	156	189	33	21%
MMO (Mach)		0.47		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	116	132	16	14%
Normal cruise speed (Mach)		0.28		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M55	U2		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	23.80	11.01	-12.79	54%
wingspan (m)	37.46	24.39	-13.07	35%
VMO (kt)	179	240	61	34%
MMO (Mach)	0.70	0.80	0.10	14%
HMO (ft)	70500	76000	5500	8%
Normal cruise speed IAS (kt)		220		
Normal cruise speed (Mach)		0.72		
Average Error				29%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M6	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.13	1.41	0.28	25%
wingspan (m)	9.75	10.97	1.22	13%
VMO (kt)	156	170	14	9%
MMO (Mach)		0.38		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	115	123	8	7%
Normal cruise speed (Mach)		0.25		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M600	TBM7		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.72	2.98	0.26	10%
wingspan (m)	9.10	12.68	3.58	39%
VMO (kt)	250	270	20	8%
MMO (Mach)		0.64		
HMO (ft)	30000	31000	1000	3%
Normal cruise speed IAS (kt)	175	205	30	17%
Normal cruise speed (Mach)		0.49		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M7	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.13	1.40	0.27	24%
wingspan (m)	10.03	9.97	-0.06	1%
VMO (kt)		189		
MMO (Mach)		0.42		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	139	125	-14	10%
Normal cruise speed (Mach)		0.23		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M7T	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.13	2.13	1.00	88%
wingspan (m)	10.03	11.60	1.57	16%
VMO (kt)		209		
MMO (Mach)		0.51		
HMO (ft)	20000	25000	5000	25%
Normal cruise speed IAS (kt)	131	160	29	22%
Normal cruise speed (Mach)		0.32		
Average Error				38%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	M8	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.13	1.31	0.18	16%
wingspan (m)	10.03	10.80	0.77	8%
VMO (kt)		186		
MMO (Mach)		0.41		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	120	122	2	2%
Normal cruise speed (Mach)		0.27		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MC90	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.68	0.45	-0.23	34%
wingspan (m)	9.76	8.10	-1.66	17%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	15000	16500	1500	10%
Normal cruise speed IAS (kt)	70	88	18	26%
Normal cruise speed (Mach)		0.14		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MCR1	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.49	0.60	0.11	22%
wingspan (m)	6.63	9.26	2.63	40%
VMO (kt)	172	143	-29	17%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	134	98	-36	27%
Normal cruise speed (Mach)		0.17		
Average Error				26%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MCR4	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.60	-0.15	20%
wingspan (m)	8.72	9.26	0.54	6%
VMO (kt)	145	143	-2	1%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	116	98	-18	16%
Normal cruise speed (Mach)		0.17		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MD81	MD82		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	63.51	67.81	4.30	7%
wingspan (m)	32.87	32.87	0.00	0%
VMO (kt)	340	340	0	0%
MMO (Mach)		0.84		
HMO (ft)	37000	37000	0	0%
Normal cruise speed IAS (kt)		290		
Normal cruise speed (Mach)	0.76	0.76	0.00	0%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MD87	MD82		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	63.51	67.81	4.30	7%
wingspan (m)	32.87	32.87	0.00	0%
VMO (kt)	340	340	0	0%
MMO (Mach)		0.84		
HMO (ft)	37000	37000	0	0%
Normal cruise speed IAS (kt)		290		
Normal cruise speed (Mach)	0.76	0.76	0.00	0%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MD88	MD82		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	67.81	67.81	0.00	0%
wingspan (m)	32.87	32.87	0.00	0%
VMO (kt)		340		
MMO (Mach)		0.84		
HMO (ft)	37000	37000	0	0%
Normal cruise speed IAS (kt)		290		
Normal cruise speed (Mach)	0.76	0.76	0.00	0%
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MD90	MD83		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	70.76	72.58	1.82	3%
wingspan (m)	32.87	32.87	0.00	0%
VMO (kt)		340		
MMO (Mach)	0.84	0.84	0.00	0%
HMO (ft)	37000	37000	0	0%
Normal cruise speed IAS (kt)		290		
Normal cruise speed (Mach)	0.76	0.76	0.00	0%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MF17	P06T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.20	1.23	0.03	2%
wingspan (m)	8.85	11.40	2.55	29%
VMO (kt)		172		
MMO (Mach)		0.34		
HMO (ft)	13450	14000	550	4%
Normal cruise speed IAS (kt)	126	130	4	3%
Normal cruise speed (Mach)		0.21		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MG15	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	6.11	5.22	-0.89	15%
wingspan (m)	10.08	9.46	-0.62	6%
VMO (kt)	572	490	-82	14%
MMO (Mach)		0.80		
HMO (ft)	50900	39370	-11530	23%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MG21	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.80	21.77	11.97	122%
wingspan (m)	7.15	10.01	2.86	40%
VMO (kt)	701	800	99	14%
MMO (Mach)	2.05	2.05	0.00	0%
HMO (ft)	58400	60000	1600	3%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				36%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MG23	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	17.80	21.77	3.97	22%
wingspan (m)	13.97	10.01	-3.96	28%
VMO (kt)	728	800	72	10%
MMO (Mach)	2.35	2.05	-0.30	13%
HMO (ft)	60700	60000	-700	1%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MG25	F15		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	41.20	36.74	-4.46	11%
wingspan (m)	14.01	13.06	-0.95	7%
VMO (kt)	647	800	153	24%
MMO (Mach)	3.20	2.50	-0.70	22%
HMO (ft)	80000	65000	-15000	19%
Normal cruise speed IAS (kt)		360		
Normal cruise speed (Mach)		0.90		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MG29	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	18.50	21.77	3.27	18%
wingspan (m)	11.36	10.01	-1.35	12%
VMO (kt)	810	800	-10	1%
MMO (Mach)	2.30	2.05	-0.25	11%
HMO (ft)	59060	60000	940	2%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MG31	F15		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	46.20	36.74	-9.46	20%
wingspan (m)	13.46	13.06	-0.40	3%
VMO (kt)	810	800	-10	1%
MMO (Mach)	2.83	2.50	-0.33	12%
HMO (ft)	67600	65000	-2600	4%
Normal cruise speed IAS (kt)		360		
Normal cruise speed (Mach)		0.90		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MIR2	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	17.00	21.77	4.77	28%
wingspan (m)	9.13	10.01	0.88	10%
VMO (kt)		800		
MMO (Mach)	2.20	2.05	-0.15	7%
HMO (ft)	59000	60000	1000	2%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MIR4	F15		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	33.80	36.74	2.94	9%
wingspan (m)	11.85	13.06	1.21	10%
VMO (kt)		800		
MMO (Mach)	2.20	2.50	0.30	14%
HMO (ft)	65600	65000	-600	1%
Normal cruise speed IAS (kt)		360		
Normal cruise speed (Mach)		0.90		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MIRA	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	13.50	21.77	8.27	61%
wingspan (m)	8.22	10.01	1.79	22%
VMO (kt)	739	800	61	8%
MMO (Mach)	2.20	2.05	-0.15	7%
HMO (ft)	56000	60000	4000	7%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)	0.90	0.84	-0.06	7%
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MOR2	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.82	1.40	0.58	71%
wingspan (m)	9.14	9.97	0.83	9%
VMO (kt)		189		
MMO (Mach)		0.47		
HMO (ft)	22000	25000	3000	14%
Normal cruise speed IAS (kt)	86	132	46	53%
Normal cruise speed (Mach)		0.28		
Average Error				37%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MP20	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.34	0.45	0.11	32%
wingspan (m)	6.00	8.10	2.10	35%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	100	88	-12	12%
Normal cruise speed (Mach)		0.14		
Average Error				26%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MRF1	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	16.20	21.77	5.57	34%
wingspan (m)	8.40	10.01	1.61	19%
VMO (kt)		800		
MMO (Mach)	2.20	2.05	-0.15	7%
HMO (ft)	65600	60000	-5600	9%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MRJ7	A148		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	40.20	42.55	2.35	6%
wingspan (m)	29.20	28.91	-0.29	1%
VMO (kt)		307		
MMO (Mach)	0.82	0.80	-0.02	2%
HMO (ft)	39000	40020	1020	3%
Normal cruise speed IAS (kt)		270		
Normal cruise speed (Mach)	0.78	0.78	0.00	0%
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MRJ9	A148		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	42.80	42.55	-0.25	1%
wingspan (m)	29.20	28.91	-0.29	1%
VMO (kt)		307		
MMO (Mach)	0.82	0.80	-0.02	2%
HMO (ft)	39000	40020	1020	3%
Normal cruise speed IAS (kt)		270		
Normal cruise speed (Mach)	0.78	0.78	0.00	0%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MRMD	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.65	0.60	-0.05	8%
wingspan (m)	10.16	8.55	-1.61	16%
VMO (kt)	135	108	-27	20%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	78	83	5	6%
Normal cruise speed (Mach)		0.15		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MS30	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.15	1.40	0.25	22%
wingspan (m)	7.35	9.97	2.62	36%
VMO (kt)	281	189	-92	33%
MMO (Mach)		0.42		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)		125		
Normal cruise speed (Mach)		0.23		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MS76	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	3.47	5.22	1.75	50%
wingspan (m)	10.15	9.46	-0.69	7%
VMO (kt)		490		
MMO (Mach)		0.80		
HMO (ft)	32800	39370	6570	20%
Normal cruise speed IAS (kt)	240	250	10	4%
Normal cruise speed (Mach)		0.50		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MU23	DIMO		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.70	0.77	0.07	10%
wingspan (m)	20.00	16.33	-3.67	18%
VMO (kt)		141		
MMO (Mach)		0.25		
HMO (ft)		16400		
Normal cruise speed IAS (kt)		84		
Normal cruise speed (Mach)		0.25		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MU30	BE40		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	7.36	7.39	0.03	0%
wingspan (m)	13.25	13.26	0.01	0%
VMO (kt)	320	320	0	0%
MMO (Mach)	0.78	0.78	0.00	0%
HMO (ft)	41000	45000	4000	10%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.73	0.76	0.03	4%
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	MUS2	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.73	1.40	0.67	92%
wingspan (m)	7.37	9.97	2.60	35%
VMO (kt)		189		
MMO (Mach)		0.47		
HMO (ft)	21000	25000	4000	19%
Normal cruise speed IAS (kt)	145	132	-13	9%
Normal cruise speed (Mach)		0.28		
Average Error				39%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	N262	JS41		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	10.80	10.43	-0.37	3%
wingspan (m)	22.60	18.29	-4.31	19%
VMO (kt)		250		
MMO (Mach)		0.52		
HMO (ft)	28500	26000	-2500	9%
Normal cruise speed IAS (kt)	180	200	20	11%
Normal cruise speed (Mach)		0.42		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	NAVI	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.25	1.28	0.03	2%
wingspan (m)	10.17	11.63	1.46	14%
VMO (kt)	165	172	7	4%
MMO (Mach)		0.35		
HMO (ft)	15000	16400	1400	9%
Normal cruise speed IAS (kt)	115	110	-5	4%
Normal cruise speed (Mach)		0.23		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	NG5	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.13	9.26	0.13	1%
VMO (kt)	156	143	-13	8%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	110	98	-12	11%
Normal cruise speed (Mach)		0.17		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	NIM	B738		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	80.51	78.30	-2.21	3%
wingspan (m)	35.00	34.30	-0.70	2%
VMO (kt)		340		
MMO (Mach)		0.82		
HMO (ft)	42000	41000	-1000	2%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.72	0.78	0.06	8%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	NM5	M20P		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.52	1.53	0.01	1%
wingspan (m)	10.90	11.00	0.10	1%
VMO (kt)		196		
MMO (Mach)		0.44		
HMO (ft)		20000		
Normal cruise speed IAS (kt)	160	160	0	0%
Normal cruise speed (Mach)		0.29		
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	NNJA	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.60	0.13	28%
wingspan (m)	8.70	8.55	-0.15	2%
VMO (kt)	100	108	8	8%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	90	83	-7	8%
Normal cruise speed (Mach)		0.15		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	NOMA	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.86	3.97	0.11	3%
wingspan (m)	16.46	15.88	-0.58	4%
VMO (kt)		175		
MMO (Mach)		0.43		
HMO (ft)	22500	25000	2500	11%
Normal cruise speed IAS (kt)		150		
Normal cruise speed (Mach)		0.27		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	O1	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.11	1.41	0.30	27%
wingspan (m)	10.97	10.97	0.00	0%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	18500	18100	-400	2%
Normal cruise speed IAS (kt)	67	115	48	72%
Normal cruise speed (Mach)		0.21		
Average Error				25%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ONE	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.60	-0.15	20%
wingspan (m)	9.67	9.26	-0.41	4%
VMO (kt)	148	143	-5	3%
MMO (Mach)		0.29		
HMO (ft)	14760	14625	-135	1%
Normal cruise speed IAS (kt)	110	98	-12	11%
Normal cruise speed (Mach)		0.17		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ONEX	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.43	0.45	0.02	5%
wingspan (m)	6.10	8.10	2.00	33%
VMO (kt)	187	127	-60	32%
MMO (Mach)		0.27		
HMO (ft)	16000	16500	500	3%
Normal cruise speed IAS (kt)	110	88	-22	20%
Normal cruise speed (Mach)		0.14		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	OSCR	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.16	1.41	0.25	22%
wingspan (m)	9.99	10.97	0.98	10%
VMO (kt)	178	171	-7	4%
MMO (Mach)		0.37		
HMO (ft)	17400	18100	700	4%
Normal cruise speed IAS (kt)	100	115	15	15%
Normal cruise speed (Mach)		0.21		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P1	B738		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	79.70	78.30	-1.40	2%
wingspan (m)	35.40	34.30	-1.10	3%
VMO (kt)		340		
MMO (Mach)		0.82		
HMO (ft)		41000		
Normal cruise speed IAS (kt)	290	280	-10	3%
Normal cruise speed (Mach)		0.78		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P100	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.68	0.60	-0.08	12%
wingspan (m)	6.85	8.55	1.70	25%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	86	83	-3	3%
Normal cruise speed (Mach)		0.15		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P149	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.68	1.41	-0.27	16%
wingspan (m)	11.12	10.97	-0.15	1%
VMO (kt)		170		
MMO (Mach)		0.38		
HMO (ft)	19849	20000	151	1%
Normal cruise speed IAS (kt)	125	123	-2	2%
Normal cruise speed (Mach)		0.25		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P2	F27		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	35.24	20.00	-15.24	43%
wingspan (m)	31.65	29.00	-2.65	8%
VMO (kt)		223		
MMO (Mach)		0.50		
HMO (ft)	22400	25000	2600	12%
Normal cruise speed IAS (kt)	150	170	20	13%
Normal cruise speed (Mach)		0.50		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P208	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	8.80	9.26	0.46	5%
VMO (kt)	141	143	2	1%
MMO (Mach)		0.29		
HMO (ft)	14000	14625	625	4%
Normal cruise speed IAS (kt)	100	98	-2	2%
Normal cruise speed (Mach)		0.17		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P210	S22T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.81	1.63	-0.18	10%
wingspan (m)	11.20	11.67	0.47	4%
VMO (kt)		208		
MMO (Mach)		0.44		
HMO (ft)	23000	25000	2000	9%
Normal cruise speed IAS (kt)	140	135	-5	4%
Normal cruise speed (Mach)		0.30		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P212	C421		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.29	3.38	0.09	3%
wingspan (m)	14.00	12.53	-1.47	10%
VMO (kt)		238		
MMO (Mach)		0.64		
HMO (ft)		30000		
Normal cruise speed IAS (kt)	160	162	2	1%
Normal cruise speed (Mach)		0.36		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P28B	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.36	1.41	0.05	4%
wingspan (m)	10.67	10.97	0.30	3%
VMO (kt)	148	171	23	16%
MMO (Mach)		0.37		
HMO (ft)	17900	18100	200	1%
Normal cruise speed IAS (kt)	123	115	-8	7%
Normal cruise speed (Mach)		0.21		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P28S	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.31	1.31	0.00	0%
wingspan (m)	10.80	10.80	0.00	0%
VMO (kt)	183	186	3	2%
MMO (Mach)		0.41		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	120	122	2	2%
Normal cruise speed (Mach)		0.27		
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P3	AN12		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	64.41	61.00	-3.41	5%
wingspan (m)	30.37	38.01	7.64	25%
VMO (kt)	330	319	-11	3%
MMO (Mach)		0.70		
HMO (ft)	28300	33465	5165	18%
Normal cruise speed IAS (kt)	225	260	35	16%
Normal cruise speed (Mach)		0.56		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P32R	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.63	1.41	-0.22	13%
wingspan (m)	11.02	10.97	-0.05	0%
VMO (kt)		170		
MMO (Mach)		0.38		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	135	123	-12	9%
Normal cruise speed (Mach)		0.25		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P32T	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.63	1.41	-0.22	13%
wingspan (m)	9.99	10.97	0.98	10%
VMO (kt)	170	170	0	0%
MMO (Mach)		0.38		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	150	123	-27	18%
Normal cruise speed (Mach)		0.25		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P337	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.13	1.41	-0.72	34%
wingspan (m)	11.63	10.97	-0.66	6%
VMO (kt)	169	170	1	1%
MMO (Mach)		0.38		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	150	123	-27	18%
Normal cruise speed (Mach)		0.25		
Average Error				12%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	P38	C56X		
Engine type	PST	JET	PST / JET	
WTC	M	M	0	
MTOW (t)	9.79	9.16	-0.63	6%
wingspan (m)	15.85	17.17	1.32	8%
VMO (kt)		305		
MMO (Mach)		0.75		
HMO (ft)	44000	45000	1000	2%
Normal cruise speed IAS (kt)	210	280	70	33%
Normal cruise speed (Mach)		0.70		
Average Error				13%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	P39	BE20		
Engine type	PST	TBP	PST / TBP	
WTC	L	L	0	
MTOW (t)	3.80	5.67	1.87	49%
wingspan (m)	10.40	16.61	6.21	60%
VMO (kt)		260		
MMO (Mach)		0.52		
HMO (ft)	35000	35000	0	0%
Normal cruise speed IAS (kt)	220	225	5	2%
Normal cruise speed (Mach)		0.46		
Average Error				28%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	P40	BE9L		
Engine type	PST	TBP	PST / TBP	
WTC	L	L	0	
MTOW (t)	4.02	4.58	0.56	14%
wingspan (m)	11.38	15.32	3.94	35%
VMO (kt)		226		
MMO (Mach)		0.68		
HMO (ft)	31000	31000	0	0%
Normal cruise speed IAS (kt)	150	194	44	29%
Normal cruise speed (Mach)		0.40		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P50	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.40	0.45	0.05	12%
wingspan (m)	6.20	8.10	1.90	31%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	120	88	-32	27%
Normal cruise speed (Mach)		0.14		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P51	P180		
Engine type	PST	TBP	PST / TBP	
WTC	L	L	0	
MTOW (t)	5.49	5.49	0.00	0%
wingspan (m)	11.28	14.03	2.75	24%
VMO (kt)		260		
MMO (Mach)		0.70		
HMO (ft)	41900	41000	-900	2%
Normal cruise speed IAS (kt)	215	260	45	21%
Normal cruise speed (Mach)		0.63		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P60	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.42	0.60	0.18	43%
wingspan (m)	5.00	8.55	3.55	71%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	10000	12000	2000	20%
Normal cruise speed IAS (kt)	100	83	-17	17%
Normal cruise speed (Mach)		0.15		
Average Error				38%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P63	C551		
Engine type	PST	JET	PST / JET	
WTC	L	L	0	
MTOW (t)	4.90	5.67	0.77	16%
wingspan (m)	11.70	15.76	4.06	35%
VMO (kt)		277		
MMO (Mach)		0.70		
HMO (ft)	43000	43000	0	0%
Normal cruise speed IAS (kt)	200	220	20	10%
Normal cruise speed (Mach)		0.63		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P66P	C414		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.80	3.06	-0.74	19%
wingspan (m)	14.25	13.45	-0.80	6%
VMO (kt)	231	232	1	0%
MMO (Mach)		0.63		
HMO (ft)	29100	30000	900	3%
Normal cruise speed IAS (kt)	139	147	8	6%
Normal cruise speed (Mach)		0.34		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P66T	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.30	3.97	-0.33	8%
wingspan (m)	14.69	15.88	1.19	8%
VMO (kt)	220	175	-45	20%
MMO (Mach)		0.43		
HMO (ft)	24000	25000	1000	4%
Normal cruise speed IAS (kt)	154	150	-4	3%
Normal cruise speed (Mach)		0.27		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P68	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.99	1.41	-0.58	29%
wingspan (m)	12.00	10.97	-1.03	9%
VMO (kt)	174	170	-4	2%
MMO (Mach)		0.38		
HMO (ft)	19200	20000	800	4%
Normal cruise speed IAS (kt)	140	123	-17	12%
Normal cruise speed (Mach)		0.25		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P68T	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.60	2.13	-0.47	18%
wingspan (m)	12.00	11.60	-0.40	3%
VMO (kt)	193	209	16	8%
MMO (Mach)		0.51		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	150	160	10	7%
Normal cruise speed (Mach)		0.32		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P70	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.33	0.45	0.12	36%
wingspan (m)	5.85	8.98	3.13	54%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	14775	14000	-775	5%
Normal cruise speed IAS (kt)	60	60	0	0%
Normal cruise speed (Mach)		0.12		
Average Error				24%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P8	B739		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	85.14	85.14	0.00	0%
wingspan (m)	37.67	35.79	-1.88	5%
VMO (kt)		340		
MMO (Mach)		0.82		
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)	280	280	0	0%
Normal cruise speed (Mach)	0.78	0.78	0.00	0%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P80	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.33	0.45	0.12	36%
wingspan (m)	6.50	8.98	2.48	38%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	14775	14000	-775	5%
Normal cruise speed IAS (kt)	60	60	0	0%
Normal cruise speed (Mach)		0.12		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	P82	A10		
Engine type	PST	JET	PST / JET	
WTC	M	M	0	
MTOW (t)	11.61	23.13	11.52	99%
wingspan (m)	15.62	17.53	1.91	12%
VMO (kt)		450		
MMO (Mach)		0.75		
HMO (ft)	38900	45000	6100	16%
Normal cruise speed IAS (kt)	169	215	46	27%
Normal cruise speed (Mach)		0.56		
Average Error				39%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	PA11	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.45	-0.15	25%
wingspan (m)	10.82	8.10	-2.72	25%
VMO (kt)	94	127	33	35%
MMO (Mach)		0.27		
HMO (ft)	15000	16500	1500	10%
Normal cruise speed IAS (kt)	84	88	4	5%
Normal cruise speed (Mach)		0.14		
Average Error				20%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	PA12	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.79	1.11	0.32	41%
wingspan (m)	10.80	10.67	-0.13	1%
VMO (kt)	130	126	-4	3%
MMO (Mach)		0.24		
HMO (ft)	12600	12000	-600	5%
Normal cruise speed IAS (kt)	96	110	14	15%
Normal cruise speed (Mach)		0.24		
Average Error				13%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	PA14	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.84	0.60	-0.24	29%
wingspan (m)	10.82	8.55	-2.27	21%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	12500	12000	-500	4%
Normal cruise speed IAS (kt)	75	83	8	11%
Normal cruise speed (Mach)		0.15		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA16	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.60	-0.15	20%
wingspan (m)	8.92	8.55	-0.37	4%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	11000	12000	1000	9%
Normal cruise speed IAS (kt)	83	83	0	0%
Normal cruise speed (Mach)		0.15		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA18	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.79	1.41	0.62	78%
wingspan (m)	10.73	10.97	0.24	2%
VMO (kt)	112	171	59	53%
MMO (Mach)		0.37		
HMO (ft)	19000	18100	-900	5%
Normal cruise speed IAS (kt)	80	115	35	44%
Normal cruise speed (Mach)		0.21		
Average Error				36%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA20	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.46	0.45	-0.01	2%
wingspan (m)	8.92	8.10	-0.82	9%
VMO (kt)	110	127	17	15%
MMO (Mach)		0.27		
HMO (ft)	15500	16500	1000	6%
Normal cruise speed IAS (kt)	100	88	-12	12%
Normal cruise speed (Mach)		0.14		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA22	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.91	1.28	0.37	41%
wingspan (m)	8.92	11.63	2.71	30%
VMO (kt)	155	172	17	11%
MMO (Mach)		0.35		
HMO (ft)	16500	16400	-100	1%
Normal cruise speed IAS (kt)	105	110	5	5%
Normal cruise speed (Mach)		0.23		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA23	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.59	1.41	-0.18	11%
wingspan (m)	11.28	10.97	-0.31	3%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	18500	18100	-400	2%
Normal cruise speed IAS (kt)	120	115	-5	4%
Normal cruise speed (Mach)		0.21		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA24	M20T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.45	1.53	0.08	6%
wingspan (m)	10.97	11.13	0.16	1%
VMO (kt)		196		
MMO (Mach)		0.48		
HMO (ft)	21000	25000	4000	19%
Normal cruise speed IAS (kt)	155	180	25	16%
Normal cruise speed (Mach)		0.37		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA25	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.32	0.45	-0.87	66%
wingspan (m)	11.02	8.98	-2.04	19%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	13000	14000	1000	8%
Normal cruise speed IAS (kt)	73	60	-13	18%
Normal cruise speed (Mach)		0.12		
Average Error				27%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA30	C402		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.69	2.86	1.17	69%
wingspan (m)	10.96	12.15	1.19	11%
VMO (kt)	200	231	31	16%
MMO (Mach)		0.62		
HMO (ft)	30000	30000	0	0%
Normal cruise speed IAS (kt)	120	142	22	18%
Normal cruise speed (Mach)		0.32		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA32	PA44		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.63	1.72	0.09	6%
wingspan (m)	11.02	11.75	0.73	7%
VMO (kt)		194		
MMO (Mach)		0.39		
HMO (ft)	14100	15000	900	6%
Normal cruise speed IAS (kt)	140	135	-5	4%
Normal cruise speed (Mach)		0.27		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA36	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.00	1.11	-0.89	44%
wingspan (m)	11.89	10.67	-1.22	10%
VMO (kt)	145	126	-19	13%
MMO (Mach)		0.24		
HMO (ft)	6400	12000	5600	88%
Normal cruise speed IAS (kt)	110	110	0	0%
Normal cruise speed (Mach)		0.24		
Average Error				31%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA38	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.76	0.60	-0.16	21%
wingspan (m)	10.36	9.26	-1.10	11%
VMO (kt)	138	143	5	4%
MMO (Mach)		0.29		
HMO (ft)	14000	14625	625	4%
Normal cruise speed IAS (kt)	86	98	12	14%
Normal cruise speed (Mach)		0.17		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PA47	C510		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	3.65	3.92	0.27	7%
wingspan (m)	13.56	13.16	-0.40	3%
VMO (kt)		250		
MMO (Mach)		0.63		
HMO (ft)	35000	41000	6000	17%
Normal cruise speed IAS (kt)	215	200	-15	7%
Normal cruise speed (Mach)		0.56		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PAT4	BE99		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.08	4.72	0.64	16%
wingspan (m)	12.52	14.00	1.48	12%
VMO (kt)	243	226	-17	7%
MMO (Mach)		0.46		
HMO (ft)	24000	25000	1000	4%
Normal cruise speed IAS (kt)	185	210	25	14%
Normal cruise speed (Mach)		0.39		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PAY1	PAY2		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.95	4.08	0.13	3%
wingspan (m)	12.40	12.40	0.00	0%
VMO (kt)	230	246	16	7%
MMO (Mach)		0.47		
HMO (ft)	28200	29000	800	3%
Normal cruise speed IAS (kt)	200	220	20	10%
Normal cruise speed (Mach)	0.40	0.44	0.04	10%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PAY4	P180		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.47	5.49	0.02	0%
wingspan (m)	14.53	14.03	-0.50	3%
VMO (kt)	246	260	14	6%
MMO (Mach)	0.62	0.70	0.08	13%
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)	220	260	40	18%
Normal cruise speed (Mach)	0.58	0.63	0.05	9%
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PC21	TEX2		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.25	3.13	-1.12	26%
wingspan (m)	9.11	10.19	1.08	12%
VMO (kt)	370	316	-54	15%
MMO (Mach)		0.67		
HMO (ft)	25000	31000	6000	24%
Normal cruise speed IAS (kt)	227	200	-27	12%
Normal cruise speed (Mach)		0.47		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PC24	E55P		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	8.01	8.15	0.14	2%
wingspan (m)	17.00	15.91	-1.09	6%
VMO (kt)		320		
MMO (Mach)		0.78		
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)	270	280	10	4%
Normal cruise speed (Mach)	0.72	0.70	-0.02	3%
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PC6P	DA42		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.20	1.78	-0.42	19%
wingspan (m)	15.20	13.42	-1.78	12%
VMO (kt)	151	155	4	3%
MMO (Mach)		0.29		
HMO (ft)	17400	18000	600	3%
Normal cruise speed IAS (kt)	95	124	29	31%
Normal cruise speed (Mach)		0.27		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PC6T	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.20	3.97	1.77	80%
wingspan (m)	15.90	15.88	-0.02	0%
VMO (kt)	140	175	35	25%
MMO (Mach)		0.43		
HMO (ft)	25500	25000	-500	2%
Normal cruise speed IAS (kt)	110	150	40	36%
Normal cruise speed (Mach)		0.27		
Average Error				29%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PC7	TEX2		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.25	3.13	0.88	39%
wingspan (m)	10.18	10.19	0.01	0%
VMO (kt)	300	316	16	5%
MMO (Mach)		0.67		
HMO (ft)	25000	31000	6000	24%
Normal cruise speed IAS (kt)	150	200	50	33%
Normal cruise speed (Mach)		0.47		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PC9	TEX2		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.35	3.13	0.78	33%
wingspan (m)	10.13	10.19	0.06	1%
VMO (kt)	320	316	-4	1%
MMO (Mach)	0.65	0.67	0.02	3%
HMO (ft)	25000	31000	6000	24%
Normal cruise speed IAS (kt)	200	200	0	0%
Normal cruise speed (Mach)		0.47		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PELI	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.64	0.45	-0.19	30%
wingspan (m)	8.99	8.10	-0.89	10%
VMO (kt)	142	127	-15	11%
MMO (Mach)		0.27		
HMO (ft)	16000	16500	500	3%
Normal cruise speed IAS (kt)	90	88	-2	2%
Normal cruise speed (Mach)		0.14		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PETL	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.56	0.45	-0.11	20%
wingspan (m)	9.60	8.10	-1.50	16%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	16000	16500	500	3%
Normal cruise speed IAS (kt)	90	88	-2	2%
Normal cruise speed (Mach)		0.14		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PIAE	EV97		
Engine type	ELC	PST	ELC / PST	
WTC	L	L	0	
MTOW (t)	0.55	0.45	-0.10	18%
wingspan (m)	10.52	8.10	-2.42	23%
VMO (kt)	135	127	-8	6%
MMO (Mach)		0.27		
HMO (ft)	16000	16500	500	3%
Normal cruise speed IAS (kt)	65	88	23	35%
Normal cruise speed (Mach)		0.14		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PIAT	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.55	1.41	0.86	156%
wingspan (m)	10.52	10.97	0.45	4%
VMO (kt)	135	171	36	27%
MMO (Mach)		0.37		
HMO (ft)	18000	18100	100	1%
Normal cruise speed IAS (kt)	85	115	30	35%
Normal cruise speed (Mach)		0.21		
Average Error				45%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PINO	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.90	1.40	0.50	56%
wingspan (m)	8.50	9.97	1.47	17%
VMO (kt)		189		
MMO (Mach)		0.42		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	135	125	-10	7%
Normal cruise speed (Mach)		0.23		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PIPA	M20T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.31	1.53	0.22	17%
wingspan (m)	10.86	11.13	0.27	2%
VMO (kt)	220	196	-24	11%
MMO (Mach)		0.48		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	165	180	15	9%
Normal cruise speed (Mach)		0.37		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PISI	DIMO		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.77	0.30	64%
wingspan (m)	14.97	16.33	1.36	9%
VMO (kt)	121	141	20	17%
MMO (Mach)		0.25		
HMO (ft)		16400		
Normal cruise speed IAS (kt)	85	84	-1	1%
Normal cruise speed (Mach)		0.25		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PIT4	P28A		
Engine type	ELC	PST	ELC / PST	
WTC	L	L	0	
MTOW (t)	1.48	1.11	-0.37	25%
wingspan (m)	21.36	10.67	-10.69	50%
VMO (kt)	122	126	4	3%
MMO (Mach)		0.24		
HMO (ft)		12000		
Normal cruise speed IAS (kt)		110		
Normal cruise speed (Mach)		0.24		
Average Error				26%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PITA	SF25		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.54	0.07	15%
wingspan (m)	14.97	15.30	0.33	2%
VMO (kt)	121	103	-18	15%
MMO (Mach)		0.21		
HMO (ft)		14800		
Normal cruise speed IAS (kt)		54		
Normal cruise speed (Mach)		0.21		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PITE	SF25		
Engine type	ELC	PST	ELC / PST	
WTC	L	L	0	
MTOW (t)	0.55	0.54	-0.01	2%
wingspan (m)	14.97	15.30	0.33	2%
VMO (kt)	121	103	-18	15%
MMO (Mach)		0.21		
HMO (ft)	12795	14800	2005	16%
Normal cruise speed IAS (kt)	64	54	-10	16%
Normal cruise speed (Mach)		0.21		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PIVI	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.45	-0.02	4%
wingspan (m)	12.46	8.10	-4.36	35%
VMO (kt)	134	127	-7	5%
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	95	88	-7	7%
Normal cruise speed (Mach)		0.14		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PL12	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.93	1.40	-0.53	27%
wingspan (m)	11.98	9.97	-2.01	17%
VMO (kt)	148	189	41	28%
MMO (Mach)		0.47		
HMO (ft)	22600	25000	2400	11%
Normal cruise speed IAS (kt)	75	132	57	76%
Normal cruise speed (Mach)		0.28		
Average Error				32%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PL2	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.66	0.60	-0.06	9%
wingspan (m)	8.53	8.55	0.02	0%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	89	83	-6	7%
Normal cruise speed (Mach)		0.15		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PNR2	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.52	0.45	-0.07	13%
wingspan (m)	7.55	8.10	0.55	7%
VMO (kt)	129	127	-2	2%
MMO (Mach)		0.27		
HMO (ft)	16400	16500	100	1%
Normal cruise speed IAS (kt)	79	88	9	11%
Normal cruise speed (Mach)		0.14		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PNR3	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.56	1.31	0.75	134%
wingspan (m)	7.55	10.80	3.25	43%
VMO (kt)	151	186	35	23%
MMO (Mach)		0.41		
HMO (ft)	19700	20000	300	2%
Normal cruise speed IAS (kt)	110	122	12	11%
Normal cruise speed (Mach)		0.27		
Average Error				43%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	PNR4	C82S		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.80	1.41	0.61	76%
wingspan (m)	8.80	10.97	2.17	25%
VMO (kt)	160	170	10	6%
MMO (Mach)		0.38		
HMO (ft)	19700	20000	300	2%
Normal cruise speed IAS (kt)	95	123	28	29%
Normal cruise speed (Mach)		0.25		
Average Error				28%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	PO60	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.57	0.60	0.03	5%
wingspan (m)	10.00	8.55	-1.45	14%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	11483	12000	517	5%
Normal cruise speed IAS (kt)	80	83	3	4%
Normal cruise speed (Mach)		0.15		
Average Error				7%

Parameter	*Synonym Aircraft*	*Reference Aircraft Model*	*Delta*	*% error*
ICAO	PROT	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.50	8.55	-0.95	10%
VMO (kt)	135	108	-27	20%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	78	83	5	6%
Normal cruise speed (Mach)		0.15		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PRXT	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.99	3.97	0.98	33%
wingspan (m)	14.43	15.88	1.45	10%
VMO (kt)		175		
MMO (Mach)		0.43		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	130	150	20	15%
Normal cruise speed (Mach)		0.27		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PT70	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.45	0.45	0.00	0%
wingspan (m)	5.95	8.98	3.03	51%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	65	60	-5	8%
Normal cruise speed (Mach)		0.12		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PT80	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.45	-0.02	4%
wingspan (m)	6.50	8.98	2.48	38%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	70	60	-10	14%
Normal cruise speed (Mach)		0.12		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PTS1	P28R		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.48	1.25	0.77	160%
wingspan (m)	5.28	10.80	5.52	105%
VMO (kt)		186		
MMO (Mach)		0.40		
HMO (ft)	18000	18400	400	2%
Normal cruise speed IAS (kt)	97	129	32	33%
Normal cruise speed (Mach)		0.21		
Average Error				75%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PTS2	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.64	0.45	-0.19	30%
wingspan (m)	6.10	8.10	2.00	33%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	16000	16500	500	3%
Normal cruise speed IAS (kt)	90	88	-2	2%
Normal cruise speed (Mach)		0.14		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PULR	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.45	-0.02	4%
wingspan (m)	9.26	8.98	-0.28	3%
VMO (kt)	104	109	5	5%
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	65	60	-5	8%
Normal cruise speed (Mach)		0.12		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PUP	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.87	0.60	-0.27	31%
wingspan (m)	9.45	9.26	-0.19	2%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	14700	14625	-75	1%
Normal cruise speed IAS (kt)		98		
Normal cruise speed (Mach)		0.17		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PZ01	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.66	0.45	-1.21	73%
wingspan (m)	12.68	8.98	-3.70	29%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	11800	14000	2200	19%
Normal cruise speed IAS (kt)	62	60	-2	3%
Normal cruise speed (Mach)		0.12		
Average Error				31%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PZ04	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.30	1.16	-0.14	11%
wingspan (m)	11.12	11.00	-0.12	1%
VMO (kt)	150	160	10	7%
MMO (Mach)		0.32		
HMO (ft)	13250	14000	750	6%
Normal cruise speed IAS (kt)	73	102	29	40%
Normal cruise speed (Mach)		0.20		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PZ06	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.45	0.45	-3.00	87%
wingspan (m)	14.90	8.10	-6.80	46%
VMO (kt)	145	127	-18	12%
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	75	88	13	17%
Normal cruise speed (Mach)		0.14		
Average Error				41%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PZ3T	PAY3		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.70	5.08	2.38	88%
wingspan (m)	9.00	14.53	5.53	61%
VMO (kt)		246		
MMO (Mach)		0.52		
HMO (ft)	33000	33000	0	0%
Normal cruise speed IAS (kt)	190	220	30	16%
Normal cruise speed (Mach)		0.46		
Average Error				41%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PZ4M	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.50	1.11	-0.39	26%
wingspan (m)	11.28	10.67	-0.61	5%
VMO (kt)	131	126	-5	4%
MMO (Mach)		0.24		
HMO (ft)	11610	12000	390	3%
Normal cruise speed IAS (kt)	93	110	17	18%
Normal cruise speed (Mach)		0.24		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	PZ6T	P750		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.50	3.40	-0.10	3%
wingspan (m)	15.00	12.80	-2.20	15%
VMO (kt)	145	171	26	18%
MMO (Mach)		0.38		
HMO (ft)		20000		
Normal cruise speed IAS (kt)	75	140	65	87%
Normal cruise speed (Mach)		0.23		
Average Error				31%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	Q01	C402		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.75	2.86	0.11	4%
wingspan (m)	20.00	12.15	-7.85	39%
VMO (kt)		231		
MMO (Mach)		0.62		
HMO (ft)	30000	30000	0	0%
Normal cruise speed IAS (kt)	132	142	10	8%
Normal cruise speed (Mach)		0.32		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	R100	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.13	1.28	0.15	13%
wingspan (m)	9.08	11.63	2.55	28%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)	16500	16400	-100	1%
Normal cruise speed IAS (kt)	115	110	-5	4%
Normal cruise speed (Mach)		0.23		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	R135	B703		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	146.00	140.00	-6.00	4%
wingspan (m)	39.88	44.10	4.22	11%
VMO (kt)		375		
MMO (Mach)		0.90		
HMO (ft)	49869	42000	-7869	16%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.84	0.80	-0.04	5%
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	R200	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.80	0.60	-0.20	25%
wingspan (m)	8.33	9.26	0.93	11%
VMO (kt)	180	143	-37	21%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	107	98	-9	8%
Normal cruise speed (Mach)		0.17		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	R300	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.05	1.16	0.11	10%
wingspan (m)	9.81	11.00	1.19	12%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	14000	14000	0	0%
Normal cruise speed IAS (kt)		102		
Normal cruise speed (Mach)		0.20		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	R721	MD83		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	72.58	72.58	0.00	0%
wingspan (m)	32.92	32.87	-0.05	0%
VMO (kt)	390	340	-50	13%
MMO (Mach)	0.90	0.84	-0.06	7%
HMO (ft)	37400	37000	-400	1%
Normal cruise speed IAS (kt)		290		
Normal cruise speed (Mach)	0.82	0.76	-0.06	7%
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	R722	B722		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	95.03	86.40	-8.63	9%
wingspan (m)	32.92	32.92	0.00	0%
VMO (kt)		360		
MMO (Mach)	0.90	0.90	0.00	0%
HMO (ft)	37000	42000	5000	14%
Normal cruise speed IAS (kt)	350	350	0	0%
Normal cruise speed (Mach)	0.82	0.82	0.00	0%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	R90F	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.35	1.28	-0.07	5%
wingspan (m)	9.50	11.63	2.13	22%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)	16000	16400	400	2%
Normal cruise speed IAS (kt)	110	110	0	0%
Normal cruise speed (Mach)		0.23		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	R90R	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.35	1.28	-0.07	5%
wingspan (m)	9.50	11.63	2.13	22%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)	16000	16400	400	2%
Normal cruise speed IAS (kt)	120	110	-10	8%
Normal cruise speed (Mach)		0.23		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	R90T	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.35	2.13	0.78	58%
wingspan (m)	9.50	11.60	2.10	22%
VMO (kt)		209		
MMO (Mach)		0.51		
HMO (ft)		25000		
Normal cruise speed IAS (kt)		160		
Normal cruise speed (Mach)		0.32		
Average Error				40%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RALL	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.05	1.11	0.06	6%
wingspan (m)	9.74	10.67	0.93	10%
VMO (kt)	135	126	-9	7%
MMO (Mach)		0.24		
HMO (ft)	11800	12000	200	2%
Normal cruise speed IAS (kt)	112	110	-2	2%
Normal cruise speed (Mach)		0.24		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RANG	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.50	1.40	-0.10	7%
wingspan (m)	10.59	9.97	-0.62	6%
VMO (kt)		189		
MMO (Mach)		0.47		
HMO (ft)		25000		
Normal cruise speed IAS (kt)	130	132	2	2%
Normal cruise speed (Mach)		0.28		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RC70	PA31		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.15	2.95	-0.20	6%
wingspan (m)	12.94	12.40	-0.54	4%
VMO (kt)		185		
MMO (Mach)		0.44		
HMO (ft)	25000	26300	1300	5%
Normal cruise speed IAS (kt)	152	160	8	5%
Normal cruise speed (Mach)		0.44		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RD20	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.83	0.95	0.12	14%
wingspan (m)	8.08	8.00	-0.08	1%
VMO (kt)		220		
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)		150		
Normal cruise speed (Mach)		0.29		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RF3	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.35	1.41	1.06	303%
wingspan (m)	11.20	10.97	-0.23	2%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	19000	18100	-900	5%
Normal cruise speed IAS (kt)	72	115	43	60%
Normal cruise speed (Mach)		0.21		
Average Error				92%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RF4	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.39	1.41	1.02	262%
wingspan (m)	11.26	10.97	-0.29	3%
VMO (kt)	134	171	37	28%
MMO (Mach)		0.37		
HMO (ft)	18000	18100	100	1%
Normal cruise speed IAS (kt)	65	115	50	77%
Normal cruise speed (Mach)		0.21		
Average Error				74%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RF6	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.60	-0.15	20%
wingspan (m)	10.50	9.26	-1.24	12%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	13125	14625	1500	11%
Normal cruise speed IAS (kt)	100	98	-2	2%
Normal cruise speed (Mach)		0.17		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RFAL	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	24.50	21.77	-2.73	11%
wingspan (m)	10.90	10.01	-0.89	8%
VMO (kt)		800		
MMO (Mach)		2.05		
HMO (ft)	55000	60000	5000	9%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RJ70	RJ85		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	43.09	44.00	0.91	2%
wingspan (m)	26.21	26.34	0.13	0%
VMO (kt)	300	300	0	0%
MMO (Mach)	0.73	0.72	-0.01	1%
HMO (ft)	35000	35000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.70	0.70	0.00	0%
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RS20	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.45	-0.15	25%
wingspan (m)	9.22	8.98	-0.24	3%
VMO (kt)	113	109	-4	4%
MMO (Mach)		0.22		
HMO (ft)	14500	14000	-500	3%
Normal cruise speed IAS (kt)	75	60	-15	20%
Normal cruise speed (Mach)		0.12		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RV10	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.23	1.40	0.17	14%
wingspan (m)	9.68	9.97	0.29	3%
VMO (kt)	180	189	9	5%
MMO (Mach)		0.42		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	142	125	-17	12%
Normal cruise speed (Mach)		0.23		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RV12	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	8.15	9.26	1.11	14%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	13800	14625	825	6%
Normal cruise speed IAS (kt)	91	98	7	8%
Normal cruise speed (Mach)		0.17		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RV14	P28T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.93	1.25	0.32	34%
wingspan (m)	8.23	10.80	2.57	31%
VMO (kt)		186		
MMO (Mach)		0.40		
HMO (ft)	18000	18400	400	2%
Normal cruise speed IAS (kt)	140	130	-10	7%
Normal cruise speed (Mach)		0.22		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RV3	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.48	1.40	0.92	192%
wingspan (m)	6.07	9.97	3.90	64%
VMO (kt)		189		
MMO (Mach)		0.47		
HMO (ft)	21000	25000	4000	19%
Normal cruise speed IAS (kt)	110	132	22	20%
Normal cruise speed (Mach)		0.28		
Average Error				74%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RV4	P28T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.68	1.25	0.57	84%
wingspan (m)	7.01	10.80	3.79	54%
VMO (kt)		186		
MMO (Mach)		0.40		
HMO (ft)	18000	18400	400	2%
Normal cruise speed IAS (kt)	135	130	-5	4%
Normal cruise speed (Mach)		0.22		
Average Error				36%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RV6	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.95	0.20	27%
wingspan (m)	7.01	8.00	0.99	14%
VMO (kt)		220		
MMO (Mach)		0.45		
HMO (ft)	15800	16000	200	1%
Normal cruise speed IAS (kt)	134	150	16	12%
Normal cruise speed (Mach)		0.29		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RV7	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.82	1.40	0.58	71%
wingspan (m)	7.62	9.97	2.35	31%
VMO (kt)	188	189	1	1%
MMO (Mach)		0.47		
HMO (ft)	22500	25000	2500	11%
Normal cruise speed IAS (kt)	150	132	-18	12%
Normal cruise speed (Mach)		0.28		
Average Error				25%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RV8	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.82	1.40	0.58	71%
wingspan (m)	7.32	9.97	2.65	36%
VMO (kt)	191	189	-2	1%
MMO (Mach)		0.47		
HMO (ft)	22500	25000	2500	11%
Normal cruise speed IAS (kt)	150	132	-18	12%
Normal cruise speed (Mach)		0.28		
Average Error				26%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RV9	P28T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.79	1.25	0.46	58%
wingspan (m)	8.53	10.80	2.27	27%
VMO (kt)	170	186	16	9%
MMO (Mach)		0.40		
HMO (ft)	19000	18400	-600	3%
Normal cruise speed IAS (kt)	135	130	-5	4%
Normal cruise speed (Mach)		0.22		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	RYSA	L410		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	6.00	6.60	0.60	10%
wingspan (m)	18.00	19.98	1.98	11%
VMO (kt)		185		
MMO (Mach)		0.41		
HMO (ft)	19680	20000	320	2%
Normal cruise speed IAS (kt)	140	165	25	18%
Normal cruise speed (Mach)		0.31		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S05F	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.30	1.28	-0.02	2%
wingspan (m)	10.86	11.63	0.77	7%
VMO (kt)	174	172	-2	1%
MMO (Mach)		0.35		
HMO (ft)	16000	16400	400	2%
Normal cruise speed IAS (kt)	100	110	10	10%
Normal cruise speed (Mach)		0.23		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S05R	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.30	1.41	0.11	8%
wingspan (m)	10.86	10.97	0.11	1%
VMO (kt)	174	171	-3	2%
MMO (Mach)		0.37		
HMO (ft)	17500	18100	600	3%
Normal cruise speed IAS (kt)	110	115	5	5%
Normal cruise speed (Mach)		0.21		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S10	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.72	0.60	-0.12	17%
wingspan (m)	10.36	8.55	-1.81	17%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	10500	12000	1500	14%
Normal cruise speed IAS (kt)	70	83	13	19%
Normal cruise speed (Mach)		0.15		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S108	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.09	0.45	-0.64	59%
wingspan (m)	10.34	8.10	-2.24	22%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	16500	16500	0	0%
Normal cruise speed IAS (kt)	83	88	5	6%
Normal cruise speed (Mach)		0.14		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S122	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.95	0.60	-0.35	37%
wingspan (m)	11.76	8.55	-3.21	27%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	72	83	11	15%
Normal cruise speed (Mach)		0.15		
Average Error				26%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S200	EA50		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	0.88	2.72	1.84	209%
wingspan (m)	8.00	11.60	3.60	45%
VMO (kt)		285		
MMO (Mach)		0.64		
HMO (ft)	26000	41000	15000	58%
Normal cruise speed IAS (kt)	140	190	50	36%
Normal cruise speed (Mach)		0.63		
Average Error				87%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S208	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.50	1.41	-0.09	6%
wingspan (m)	10.86	10.97	0.11	1%
VMO (kt)	175	171	-4	2%
MMO (Mach)		0.37		
HMO (ft)	17725	18100	375	2%
Normal cruise speed IAS (kt)	125	115	-10	8%
Normal cruise speed (Mach)		0.21		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S210	E190		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	50.00	51.80	1.80	4%
wingspan (m)	34.30	28.72	-5.58	16%
VMO (kt)	350	320	-30	9%
MMO (Mach)	0.81	0.82	0.01	1%
HMO (ft)	39370	41000	1630	4%
Normal cruise speed IAS (kt)		290		
Normal cruise speed (Mach)	0.74	0.75	0.01	1%
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S211	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	3.15	5.22	2.07	66%
wingspan (m)	8.46	9.46	1.00	12%
VMO (kt)	400	490	90	22%
MMO (Mach)	0.80	0.80	0.00	0%
HMO (ft)	40000	39370	-630	2%
Normal cruise speed IAS (kt)	230	250	20	9%
Normal cruise speed (Mach)		0.50		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S2P	SH36		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	11.79	12.29	0.50	4%
wingspan (m)	22.12	22.80	0.68	3%
VMO (kt)		200		
MMO (Mach)		0.44		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	145	180	35	24%
Normal cruise speed (Mach)		0.33		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S2T	JS41		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	12.47	10.43	-2.04	16%
wingspan (m)	22.12	18.29	-3.83	17%
VMO (kt)		250		
MMO (Mach)		0.52		
HMO (ft)	24000	26000	2000	8%
Normal cruise speed IAS (kt)	175	200	25	14%
Normal cruise speed (Mach)		0.42		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S3	A10		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	23.83	23.13	-0.70	3%
wingspan (m)	20.93	17.53	-3.40	16%
VMO (kt)	450	450	0	0%
MMO (Mach)	0.79	0.75	-0.04	5%
HMO (ft)	40000	45000	5000	12%
Normal cruise speed IAS (kt)	220	215	-5	2%
Normal cruise speed (Mach)		0.56		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S450	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.45	-0.02	4%
wingspan (m)	9.40	8.10	-1.30	14%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	85	88	3	4%
Normal cruise speed (Mach)		0.14		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	S601	C525		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	6.60	4.85	-1.75	27%
wingspan (m)	12.87	14.30	1.43	11%
VMO (kt)		263		
MMO (Mach)		0.71		
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)	240	260	20	8%
Normal cruise speed (Mach)	0.65	0.66	0.01	2%
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SA02	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.82	0.60	-0.22	27%
wingspan (m)	8.18	9.26	1.08	13%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	117	98	-19	16%
Normal cruise speed (Mach)		0.17		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SA20	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.27	0.45	-1.82	80%
wingspan (m)	12.72	8.10	-4.62	36%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	15420	16500	1080	7%
Normal cruise speed IAS (kt)	76	88	12	16%
Normal cruise speed (Mach)		0.14		
Average Error				35%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SA30	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.77	1.40	0.63	82%
wingspan (m)	7.30	9.97	2.67	37%
VMO (kt)		189		
MMO (Mach)		0.47		
HMO (ft)	23000	25000	2000	9%
Normal cruise speed IAS (kt)		132		
Normal cruise speed (Mach)		0.28		
Average Error				42%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SA37	DIMO		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.84	0.77	-0.07	8%
wingspan (m)	18.14	16.33	-1.81	10%
VMO (kt)		141		
MMO (Mach)		0.25		
HMO (ft)	14000	16400	2400	17%
Normal cruise speed IAS (kt)	77	84	7	9%
Normal cruise speed (Mach)		0.25		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SA50	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.45	0.45	0.00	0%
wingspan (m)	7.60	8.10	0.50	7%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	75	88	13	17%
Normal cruise speed (Mach)		0.14		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SAM	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	8.69	9.26	0.57	7%
VMO (kt)	130	143	13	10%
MMO (Mach)		0.29		
HMO (ft)	13000	14625	1625	12%
Normal cruise speed IAS (kt)	95	98	3	3%
Normal cruise speed (Mach)		0.17		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SASH	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.70	1.41	-0.29	17%
wingspan (m)	11.70	10.97	-0.73	6%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)		18100		
Normal cruise speed IAS (kt)	117	115	-2	2%
Normal cruise speed (Mach)		0.21		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SATA	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	3.70	5.22	1.52	41%
wingspan (m)	10.93	9.46	-1.47	13%
VMO (kt)	431	490	59	14%
MMO (Mach)	0.72	0.80	0.08	11%
HMO (ft)	42650	39370	-3280	8%
Normal cruise speed IAS (kt)	230	250	20	9%
Normal cruise speed (Mach)		0.50		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SAVG	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.45	-0.15	25%
wingspan (m)	9.39	8.10	-1.29	14%
VMO (kt)	110	127	17	15%
MMO (Mach)		0.27		
HMO (ft)	16400	16500	100	1%
Normal cruise speed IAS (kt)	80	88	8	10%
Normal cruise speed (Mach)		0.14		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SB05	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	4.05	5.22	1.17	29%
wingspan (m)	9.50	9.46	-0.04	0%
VMO (kt)	524	490	-34	6%
MMO (Mach)		0.80		
HMO (ft)	44300	39370	-4930	11%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)	0.64	0.50	-0.14	22%
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SB29	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	8.38	7.00	-1.38	16%
wingspan (m)	11.00	9.11	-1.89	17%
VMO (kt)	540	550	10	2%
MMO (Mach)		0.95		
HMO (ft)	50850	50000	-850	2%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.75	0.73	-0.02	3%
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SB32	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	13.60	7.00	-6.60	49%
wingspan (m)	13.00	9.11	-3.89	30%
VMO (kt)	648	550	-98	15%
MMO (Mach)		0.95		
HMO (ft)	49000	50000	1000	2%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)		0.73		
Average Error				24%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SB35	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	15.00	21.77	6.77	45%
wingspan (m)	9.40	10.01	0.61	6%
VMO (kt)		800		
MMO (Mach)	2.20	2.05	-0.15	7%
HMO (ft)		60000		
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SB37	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	20.00	21.77	1.77	9%
wingspan (m)	10.60	10.01	-0.59	6%
VMO (kt)		800		
MMO (Mach)	2.10	2.05	-0.05	2%
HMO (ft)		60000		
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SB39	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	13.00	21.77	8.77	67%
wingspan (m)	8.40	10.01	1.61	19%
VMO (kt)		800		
MMO (Mach)	2.00	2.05	0.05	2%
HMO (ft)		60000		
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				30%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SB91	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.21	1.31	0.10	8%
wingspan (m)	10.60	10.80	0.20	2%
VMO (kt)		186		
MMO (Mach)		0.41		
HMO (ft)	20341	20000	-341	2%
Normal cruise speed IAS (kt)	120	122	2	2%
Normal cruise speed (Mach)		0.27		
Average Error				3%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SBR1	FA10		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.15	8.76	-0.39	4%
wingspan (m)	13.61	13.08	-0.53	4%
VMO (kt)	370	370	0	0%
MMO (Mach)	0.81	0.87	0.06	7%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)	260	300	40	15%
Normal cruise speed (Mach)	0.75	0.75	0.00	0%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SBR2	FA10		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	10.43	8.76	-1.67	16%
wingspan (m)	13.61	13.08	-0.53	4%
VMO (kt)		370		
MMO (Mach)		0.87		
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.74	0.75	0.01	1%
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SC01	P28R		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.71	1.25	0.54	76%
wingspan (m)	7.77	10.80	3.03	39%
VMO (kt)	154	186	32	21%
MMO (Mach)		0.40		
HMO (ft)	18504	18400	-104	1%
Normal cruise speed IAS (kt)	127	129	2	2%
Normal cruise speed (Mach)		0.21		
Average Error				28%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SC7	D228		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.67	6.40	0.73	13%
wingspan (m)	19.79	16.97	-2.82	14%
VMO (kt)	217	220	3	1%
MMO (Mach)		0.41		
HMO (ft)	22500	28000	5500	24%
Normal cruise speed IAS (kt)	175	180	5	3%
Normal cruise speed (Mach)		0.34		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SD4	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.45	-0.02	4%
wingspan (m)	8.50	8.10	-0.40	5%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	108	88	-20	19%
Normal cruise speed (Mach)		0.14		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SF2	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.50	0.45	-0.05	10%
wingspan (m)	9.10	8.98	-0.12	1%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	70	60	-10	14%
Normal cruise speed (Mach)		0.12		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SF23	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.73	0.45	-0.28	38%
wingspan (m)	9.87	8.10	-1.77	18%
VMO (kt)	135	127	-8	6%
MMO (Mach)		0.27		
HMO (ft)	17000	16500	-500	3%
Normal cruise speed IAS (kt)		88		
Normal cruise speed (Mach)		0.14		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SF24	SF25		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.33	0.54	0.21	64%
wingspan (m)	14.00	15.30	1.30	9%
VMO (kt)	90	103	13	14%
MMO (Mach)		0.21		
HMO (ft)	8000	14800	6800	85%
Normal cruise speed IAS (kt)	60	54	-6	10%
Normal cruise speed (Mach)		0.21		
Average Error				36%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SF27	SF25		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.39	0.54	0.15	38%
wingspan (m)	15.00	15.30	0.30	2%
VMO (kt)		103		
MMO (Mach)		0.21		
HMO (ft)		14800		
Normal cruise speed IAS (kt)		54		
Normal cruise speed (Mach)		0.21		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SF31	DIMO		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.44	0.77	0.33	75%
wingspan (m)	15.00	16.33	1.33	9%
VMO (kt)		141		
MMO (Mach)		0.25		
HMO (ft)		16400		
Normal cruise speed IAS (kt)	79	84	5	6%
Normal cruise speed (Mach)		0.25		
Average Error				30%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SF50	EA50		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	2.73	2.72	-0.01	0%
wingspan (m)	11.79	11.60	-0.19	2%
VMO (kt)		285		
MMO (Mach)		0.64		
HMO (ft)	28000	41000	13000	46%
Normal cruise speed IAS (kt)	200	190	-10	5%
Normal cruise speed (Mach)		0.63		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SG37	DIMO		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.84	0.77	-0.07	8%
wingspan (m)	18.14	16.33	-1.81	10%
VMO (kt)		141		
MMO (Mach)		0.25		
HMO (ft)	14000	16400	2400	17%
Normal cruise speed IAS (kt)	77	84	7	9%
Normal cruise speed (Mach)		0.25		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SG70	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.45	-0.15	25%
wingspan (m)	9.15	8.10	-1.05	11%
VMO (kt)	121	127	6	5%
MMO (Mach)		0.27		
HMO (ft)	14000	16500	2500	18%
Normal cruise speed IAS (kt)	79	88	9	11%
Normal cruise speed (Mach)		0.14		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SH33	SH36		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	10.39	12.29	1.90	18%
wingspan (m)	22.76	22.80	0.04	0%
VMO (kt)	198	200	2	1%
MMO (Mach)		0.44		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	150	180	30	20%
Normal cruise speed (Mach)		0.33		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SHRK	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.48	0.60	0.12	25%
wingspan (m)	7.90	9.26	1.36	17%
VMO (kt)	179	143	-36	20%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	110	98	-12	11%
Normal cruise speed (Mach)		0.17		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SIRA	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.62	0.60	-0.02	3%
wingspan (m)	8.60	9.26	0.66	8%
VMO (kt)	135	143	8	6%
MMO (Mach)		0.29		
HMO (ft)	14760	14625	-135	1%
Normal cruise speed IAS (kt)	110	98	-12	11%
Normal cruise speed (Mach)		0.17		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SJ30	LJ45		
Engine type	JET	JET	0	
WTC	L	M	L / M	
MTOW (t)	6.33	9.30	2.97	47%
wingspan (m)	12.90	14.56	1.66	13%
VMO (kt)	320	330	10	3%
MMO (Mach)	0.83	0.81	-0.02	2%
HMO (ft)	49000	51000	2000	4%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.80	0.76	-0.04	5%
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SK70	C421		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	3.31	3.38	0.07	2%
wingspan (m)	12.89	12.53	-0.36	3%
VMO (kt)		238		
MMO (Mach)		0.64		
HMO (ft)		30000		
Normal cruise speed IAS (kt)	160	162	2	1%
Normal cruise speed (Mach)		0.36		
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SLG2	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.70	0.60	-0.10	14%
wingspan (m)	9.17	9.26	0.09	1%
VMO (kt)	135	143	8	6%
MMO (Mach)		0.29		
HMO (ft)	15000	14625	-375	2%
Normal cruise speed IAS (kt)	108	98	-10	9%
Normal cruise speed (Mach)		0.17		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SLG4	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.92	0.60	-0.32	35%
wingspan (m)	9.97	9.26	-0.71	7%
VMO (kt)	140	143	3	2%
MMO (Mach)		0.29		
HMO (ft)	15000	14625	-375	2%
Normal cruise speed IAS (kt)	110	98	-12	11%
Normal cruise speed (Mach)		0.17		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SLK3	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.58	0.95	0.37	64%
wingspan (m)	7.31	8.00	0.69	9%
VMO (kt)	216	220	4	2%
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)	130	150	20	15%
Normal cruise speed (Mach)		0.29		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SLK5	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.72	0.95	0.23	32%
wingspan (m)	7.31	8.00	0.69	9%
VMO (kt)	216	220	4	2%
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)	140	150	10	7%
Normal cruise speed (Mach)		0.29		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SM19	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.45	2.13	0.68	47%
wingspan (m)	10.97	11.60	0.63	6%
VMO (kt)	169	209	40	24%
MMO (Mach)		0.51		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	115	160	45	39%
Normal cruise speed (Mach)		0.32		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SM20	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.10	2.13	0.03	1%
wingspan (m)	11.60	11.60	0.00	0%
VMO (kt)		209		
MMO (Mach)		0.51		
HMO (ft)	20000	25000	5000	25%
Normal cruise speed IAS (kt)	176	160	-16	9%
Normal cruise speed (Mach)		0.32		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SM92	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.35	1.11	-1.24	53%
wingspan (m)	14.60	10.67	-3.93	27%
VMO (kt)	140	126	-14	10%
MMO (Mach)		0.24		
HMO (ft)	9840	12000	2160	22%
Normal cruise speed IAS (kt)	106	110	4	4%
Normal cruise speed (Mach)		0.24		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SNAP	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.42	0.60	0.18	43%
wingspan (m)	7.20	9.26	2.06	29%
VMO (kt)	171	143	-28	16%
MMO (Mach)		0.29		
HMO (ft)	15000	14625	-375	2%
Normal cruise speed IAS (kt)	118	98	-20	17%
Normal cruise speed (Mach)		0.17		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SNTA	SF25		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.54	0.07	15%
wingspan (m)	15.04	15.30	0.26	2%
VMO (kt)	90	103	13	14%
MMO (Mach)		0.21		
HMO (ft)		14800		
Normal cruise speed IAS (kt)	49	54	5	10%
Normal cruise speed (Mach)		0.21		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SOL1	EA50		
Engine type	ELC	JET	ELC / JET	
WTC	L	L	0	
MTOW (t)	2.00	2.72	0.72	36%
wingspan (m)	63.40	11.60	-51.80	82%
VMO (kt)		285		
MMO (Mach)		0.64		
HMO (ft)	39000	41000	2000	5%
Normal cruise speed IAS (kt)	25	190	165	660%
Normal cruise speed (Mach)		0.63		
Average Error				196%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SOL2	EA50		
Engine type	ELC	JET	ELC / JET	
WTC	L	L	0	
MTOW (t)	2.30	2.72	0.42	18%
wingspan (m)	71.90	11.60	-60.30	84%
VMO (kt)		285		
MMO (Mach)		0.64		
HMO (ft)	39000	41000	2000	5%
Normal cruise speed IAS (kt)	36	190	154	428%
Normal cruise speed (Mach)		0.63		
Average Error				134%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SORA	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	7.70	9.26	1.56	20%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	115	98	-17	15%
Normal cruise speed (Mach)		0.17		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SP7	PA34		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.00	2.00	0.00	0%
wingspan (m)	11.89	11.85	-0.04	0%
VMO (kt)		203		
MMO (Mach)		0.50		
HMO (ft)	24000	25000	1000	4%
Normal cruise speed IAS (kt)	148	150	2	1%
Normal cruise speed (Mach)		0.31		
Average Error				1%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SR01	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.45	9.26	-0.19	2%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	119	98	-21	18%
Normal cruise speed (Mach)		0.17		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SREY	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.65	1.41	0.76	117%
wingspan (m)	9.14	10.97	1.83	20%
VMO (kt)	104	171	67	64%
MMO (Mach)		0.37		
HMO (ft)	18000	18100	100	1%
Normal cruise speed IAS (kt)	65	115	50	77%
Normal cruise speed (Mach)		0.21		
Average Error				56%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SS2T	P750		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.76	3.40	-1.36	29%
wingspan (m)	14.48	12.80	-1.68	12%
VMO (kt)	162	171	9	6%
MMO (Mach)		0.38		
HMO (ft)	12000	20000	8000	67%
Normal cruise speed IAS (kt)	110	140	30	27%
Normal cruise speed (Mach)		0.23		
Average Error				28%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SSAB	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	15.80	7.00	-8.80	56%
wingspan (m)	11.81	9.11	-2.70	23%
VMO (kt)	750	550	-200	27%
MMO (Mach)	1.30	0.95	-0.35	27%
HMO (ft)	50000	50000	0	0%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)		0.73		
Average Error				26%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ST10	P28R		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.22	1.25	0.03	2%
wingspan (m)	9.70	10.80	1.10	11%
VMO (kt)		186		
MMO (Mach)		0.40		
HMO (ft)	16400	18400	2000	12%
Normal cruise speed IAS (kt)	125	129	4	3%
Normal cruise speed (Mach)		0.21		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ST75	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.20	0.45	-0.75	62%
wingspan (m)	9.81	8.98	-0.83	8%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	13200	14000	800	6%
Normal cruise speed IAS (kt)	66	60	-6	9%
Normal cruise speed (Mach)		0.12		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	STAR	P180		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	6.76	5.49	-1.27	19%
wingspan (m)	16.60	14.03	-2.57	15%
VMO (kt)	261	260	-1	0%
MMO (Mach)	0.60	0.70	0.10	17%
HMO (ft)	41000	41000	0	0%
Normal cruise speed IAS (kt)	170	260	90	53%
Normal cruise speed (Mach)		0.63		
Average Error				17%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	STRE	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)		0.45		
wingspan (m)	9.00	8.98	-0.02	0%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)		60		
Normal cruise speed (Mach)		0.12		
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	STRK	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.21	5.22	0.01	0%
wingspan (m)	11.23	9.46	-1.77	16%
VMO (kt)	450	490	40	9%
MMO (Mach)		0.80		
HMO (ft)	40000	39370	-630	2%
Normal cruise speed IAS (kt)	280	250	-30	11%
Normal cruise speed (Mach)		0.50		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SU17	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	17.70	21.77	4.07	23%
wingspan (m)	13.80	10.01	-3.79	27%
VMO (kt)	755	800	45	6%
MMO (Mach)	1.70	2.05	0.35	21%
HMO (ft)	59000	60000	1000	2%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SU24	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	39.70	21.77	-17.93	45%
wingspan (m)	17.64	10.01	-7.63	43%
VMO (kt)	712	800	88	12%
MMO (Mach)	1.35	2.05	0.70	52%
HMO (ft)	57400	60000	2600	5%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				31%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SU25	HAWK		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	17.60	6.58	-11.02	63%
wingspan (m)	14.36	9.40	-4.96	35%
VMO (kt)	526	550	24	5%
MMO (Mach)		1.04		
HMO (ft)	22960	40000	17040	74%
Normal cruise speed IAS (kt)		375		
Normal cruise speed (Mach)		0.80		
Average Error				44%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SU26	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.00	0.95	-0.05	5%
wingspan (m)	7.80	8.00	0.20	3%
VMO (kt)	243	220	-23	9%
MMO (Mach)		0.45		
HMO (ft)	13125	16000	2875	22%
Normal cruise speed IAS (kt)	118	150	32	27%
Normal cruise speed (Mach)		0.29		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SU27	F15		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	33.00	36.74	3.74	11%
wingspan (m)	14.70	13.06	-1.64	11%
VMO (kt)	756	800	44	6%
MMO (Mach)	2.30	2.50	0.20	9%
HMO (ft)	60000	65000	5000	8%
Normal cruise speed IAS (kt)		360		
Normal cruise speed (Mach)		0.90		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SU7	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	14.50	7.00	-7.50	52%
wingspan (m)	8.93	9.11	0.18	2%
VMO (kt)		550		
MMO (Mach)	1.70	0.95	-0.75	44%
HMO (ft)	49700	50000	300	1%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)		0.73		
Average Error				25%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SUBA	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.15	1.41	0.26	23%
wingspan (m)	9.42	10.97	1.55	16%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	19000	18100	-900	5%
Normal cruise speed IAS (kt)	83	115	32	39%
Normal cruise speed (Mach)		0.21		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SW18	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.45	-0.15	25%
wingspan (m)	10.73	8.98	-1.75	16%
VMO (kt)	115	109	-6	5%
MMO (Mach)		0.22		
HMO (ft)	14000	14000	0	0%
Normal cruise speed IAS (kt)	65	60	-5	8%
Normal cruise speed (Mach)		0.12		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SW2	BE9L		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.54	4.58	0.04	1%
wingspan (m)	13.98	15.32	1.34	10%
VMO (kt)	208	226	18	9%
MMO (Mach)		0.68		
HMO (ft)	31000	31000	0	0%
Normal cruise speed IAS (kt)	205	194	-11	5%
Normal cruise speed (Mach)		0.40		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SW3	MU2		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.67	5.25	-0.42	7%
wingspan (m)	14.10	11.94	-2.16	15%
VMO (kt)	265	250	-15	6%
MMO (Mach)		0.57		
HMO (ft)	31000	31000	0	0%
Normal cruise speed IAS (kt)	240	240	0	0%
Normal cruise speed (Mach)		0.48		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SX30	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.09	0.95	-0.14	13%
wingspan (m)	7.43	8.00	0.57	8%
VMO (kt)	274	220	-54	20%
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)	190	150	-40	21%
Normal cruise speed (Mach)		0.29		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	SYMP	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.97	1.28	0.31	32%
wingspan (m)	10.67	11.63	0.96	9%
VMO (kt)	162	172	10	6%
MMO (Mach)		0.35		
HMO (ft)	16400	16400	0	0%
Normal cruise speed IAS (kt)		110		
Normal cruise speed (Mach)		0.23		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T1	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.00	5.22	0.22	4%
wingspan (m)	10.50	9.46	-1.04	10%
VMO (kt)	400	490	90	22%
MMO (Mach)		0.80		
HMO (ft)	47250	39370	-7880	17%
Normal cruise speed IAS (kt)	210	250	40	19%
Normal cruise speed (Mach)		0.50		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T10	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.55	0.60	0.05	9%
wingspan (m)	9.13	8.55	-0.58	6%
VMO (kt)	125	108	-17	14%
MMO (Mach)		0.21		
HMO (ft)	9840	12000	2160	22%
Normal cruise speed IAS (kt)	103	83	-20	19%
Normal cruise speed (Mach)		0.15		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T160	FGTL		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	275.00	214.60	-60.40	22%
wingspan (m)	55.70	41.80	-13.90	25%
VMO (kt)		500		
MMO (Mach)	2.05	1.20	-0.85	41%
HMO (ft)	49200	41000	-8200	17%
Normal cruise speed IAS (kt)		350		
Normal cruise speed (Mach)	0.90	0.80	-0.10	11%
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T19	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.45	-0.02	4%
wingspan (m)		8.10		
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	110	88	-22	20%
Normal cruise speed (Mach)		0.14		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T2	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.98	5.22	-0.76	13%
wingspan (m)	11.62	9.46	-2.16	19%
VMO (kt)	485	490	5	1%
MMO (Mach)	0.85	0.80	-0.05	6%
HMO (ft)	50000	39370	-10630	21%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T206	C402		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.63	2.86	1.23	75%
wingspan (m)	10.97	12.15	1.18	11%
VMO (kt)	179	231	52	29%
MMO (Mach)		0.62		
HMO (ft)	27000	30000	3000	11%
Normal cruise speed IAS (kt)	120	142	22	18%
Normal cruise speed (Mach)		0.32		
Average Error				29%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T210	C340		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.86	2.72	0.86	46%
wingspan (m)	11.20	11.62	0.42	4%
VMO (kt)	203	234	31	15%
MMO (Mach)		0.63		
HMO (ft)	30000	30000	0	0%
Normal cruise speed IAS (kt)	150	153	3	2%
Normal cruise speed (Mach)		0.34		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T211	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.57	0.60	0.03	5%
wingspan (m)	7.62	8.55	0.93	12%
VMO (kt)		108		
MMO (Mach)		0.21		
HMO (ft)	12500	12000	-500	4%
Normal cruise speed IAS (kt)		83		
Normal cruise speed (Mach)		0.15		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T22M	FGTL		
Engine type	JET	JET	0	
WTC	M	H	M / H	
MTOW (t)	124.00	214.60	90.60	73%
wingspan (m)	34.28	41.80	7.52	22%
VMO (kt)		500		
MMO (Mach)	1.88	1.20	-0.68	36%
HMO (ft)	43640	41000	-2640	6%
Normal cruise speed IAS (kt)		350		
Normal cruise speed (Mach)		0.80		
Average Error				34%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T250	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.43	1.41	-0.02	1%
wingspan (m)	9.55	10.97	1.42	15%
VMO (kt)		171		
MMO (Mach)		0.37		
HMO (ft)	18100	18100	0	0%
Normal cruise speed IAS (kt)		115		
Normal cruise speed (Mach)		0.21		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T28	P180		
Engine type	PST	TBP	PST / TBP	
WTC	L	L	0	
MTOW (t)	3.86	5.49	1.63	42%
wingspan (m)	12.22	14.03	1.81	15%
VMO (kt)		260		
MMO (Mach)		0.70		
HMO (ft)	39000	41000	2000	5%
Normal cruise speed IAS (kt)		260		
Normal cruise speed (Mach)		0.63		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T30	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.88	0.95	0.07	8%
wingspan (m)	7.77	8.00	0.23	3%
VMO (kt)		220		
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)		150		
Normal cruise speed (Mach)		0.29		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T33	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	7.63	7.00	-0.63	8%
wingspan (m)	12.93	9.11	-3.82	30%
VMO (kt)	500	550	50	10%
MMO (Mach)		0.95		
HMO (ft)	47000	50000	3000	6%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)		0.73		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T34P	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.38	1.40	0.02	1%
wingspan (m)	10.00	9.97	-0.03	0%
VMO (kt)	240	189	-51	21%
MMO (Mach)		0.42		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	120	125	5	4%
Normal cruise speed (Mach)		0.23		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T34T	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	2.00	2.13	0.13	6%
wingspan (m)	10.16	11.60	1.44	14%
VMO (kt)	280	209	-71	25%
MMO (Mach)		0.51		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	150	160	10	7%
Normal cruise speed (Mach)		0.32		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T35	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.87	0.45	-0.42	48%
wingspan (m)	8.94	8.10	-0.84	9%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	17000	16500	-500	3%
Normal cruise speed IAS (kt)		88		
Normal cruise speed (Mach)		0.14		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T37	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	2.99	5.22	2.23	75%
wingspan (m)	10.30	9.46	-0.84	8%
VMO (kt)	400	490	90	22%
MMO (Mach)		0.80		
HMO (ft)	39200	39370	170	0%
Normal cruise speed IAS (kt)	180	250	70	39%
Normal cruise speed (Mach)	0.54	0.50	-0.04	7%
Average Error				25%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T38	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.44	5.22	-0.22	4%
wingspan (m)	7.70	9.46	1.76	23%
VMO (kt)		490		
MMO (Mach)	1.30	0.80	-0.50	38%
HMO (ft)	53500	39370	-14130	26%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				23%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T4	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	7.50	7.00	-0.50	7%
wingspan (m)	9.94	9.11	-0.83	8%
VMO (kt)	560	550	-10	2%
MMO (Mach)	0.91	0.95	0.04	4%
HMO (ft)	50000	50000	0	0%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.75	0.73	-0.02	3%
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T40	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.39	0.45	0.06	15%
wingspan (m)	6.78	8.10	1.32	19%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	93	88	-5	5%
Normal cruise speed (Mach)		0.14		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T411	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.65	1.11	-0.54	33%
wingspan (m)	13.02	10.67	-2.35	18%
VMO (kt)		126		
MMO (Mach)		0.24		
HMO (ft)	9800	12000	2200	22%
Normal cruise speed IAS (kt)	90	110	20	22%
Normal cruise speed (Mach)		0.24		
Average Error				24%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T50S	F15		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	37.00	36.74	-0.26	1%
wingspan (m)	15.00	13.06	-1.94	13%
VMO (kt)		800		
MMO (Mach)		2.50		
HMO (ft)	65000	65000	0	0%
Normal cruise speed IAS (kt)		360		
Normal cruise speed (Mach)	1.60	0.90	-0.70	44%
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	T6	PA46		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.50	1.97	-0.53	21%
wingspan (m)	12.81	13.11	0.30	2%
VMO (kt)	180	200	20	11%
MMO (Mach)		0.49		
HMO (ft)	24200	25000	800	3%
Normal cruise speed IAS (kt)	125	145	20	16%
Normal cruise speed (Mach)		0.33		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TAMP	P28A		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.06	1.11	0.05	5%
wingspan (m)	10.04	10.67	0.63	6%
VMO (kt)	170	126	-44	26%
MMO (Mach)		0.24		
HMO (ft)	11000	12000	1000	9%
Normal cruise speed IAS (kt)	115	110	-5	4%
Normal cruise speed (Mach)		0.24		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TARR	TB21		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)		1.40		
wingspan (m)	7.94	9.97	2.03	26%
VMO (kt)	200	189	-11	6%
MMO (Mach)		0.47		
HMO (ft)		25000		
Normal cruise speed IAS (kt)	130	132	2	2%
Normal cruise speed (Mach)		0.28		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TB05	P28R		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.04	1.25	0.21	20%
wingspan (m)	8.53	10.80	2.27	27%
VMO (kt)		186		
MMO (Mach)		0.40		
HMO (ft)	17800	18400	600	3%
Normal cruise speed IAS (kt)	129	129	0	0%
Normal cruise speed (Mach)		0.21		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TB30	TB20		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.15	1.40	0.25	22%
wingspan (m)	7.35	9.97	2.62	36%
VMO (kt)	281	189	-92	33%
MMO (Mach)		0.42		
HMO (ft)	20000	20000	0	0%
Normal cruise speed IAS (kt)	140	125	-15	11%
Normal cruise speed (Mach)		0.23		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TB31	P46T		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	1.40	2.31	0.91	65%
wingspan (m)	7.92	13.11	5.19	66%
VMO (kt)		187		
MMO (Mach)		0.51		
HMO (ft)	30000	30000	0	0%
Normal cruise speed IAS (kt)	150	160	10	7%
Normal cruise speed (Mach)		0.36		
Average Error				34%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TBEE	C182		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.72	1.41	-0.31	18%
wingspan (m)	13.21	10.97	-2.24	17%
VMO (kt)	144	171	27	19%
MMO (Mach)		0.37		
HMO (ft)	19000	18100	-900	5%
Normal cruise speed IAS (kt)	95	115	20	21%
Normal cruise speed (Mach)		0.21		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TBM	JS32		
Engine type	PST	TBP	PST / TBP	
WTC	M	M	0	
MTOW (t)	7.88	7.35	-0.53	7%
wingspan (m)	16.51	15.85	-0.66	4%
VMO (kt)	218	250	32	15%
MMO (Mach)		0.52		
HMO (ft)	22400	25000	2600	12%
Normal cruise speed IAS (kt)	180	200	20	11%
Normal cruise speed (Mach)		0.41		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TBM9	TBM8		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.35	3.35	0.00	0%
wingspan (m)	12.83	12.68	-0.15	1%
VMO (kt)	271	270	-1	0%
MMO (Mach)		0.64		
HMO (ft)	31000	31000	0	0%
Normal cruise speed IAS (kt)	220	220	0	0%
Normal cruise speed (Mach)		0.53		
Average Error				0%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TFUN	DIMO		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.85	0.77	-0.08	9%
wingspan (m)	17.00	16.33	-0.67	4%
VMO (kt)	120	141	21	18%
MMO (Mach)		0.25		
HMO (ft)	16000	16400	400	2%
Normal cruise speed IAS (kt)	100	84	-16	16%
Normal cruise speed (Mach)		0.25		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TJET	EA50		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	2.36	2.72	0.36	15%
wingspan (m)	10.52	11.60	1.08	10%
VMO (kt)	391	285	-106	27%
MMO (Mach)		0.64		
HMO (ft)	30000	41000	11000	37%
Normal cruise speed IAS (kt)	210	190	-20	10%
Normal cruise speed (Mach)	0.56	0.63	0.07	12%
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TL20	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.12	9.26	0.14	2%
VMO (kt)	164	143	-21	13%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	95	98	3	3%
Normal cruise speed (Mach)		0.17		
Average Error				4%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TL30	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.40	9.26	-0.14	1%
VMO (kt)	136	143	7	5%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	95	98	3	3%
Normal cruise speed (Mach)		0.17		
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TOBA	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.15	1.16	0.01	1%
wingspan (m)	9.76	11.00	1.24	13%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	13000	14000	1000	8%
Normal cruise speed IAS (kt)		102		
Normal cruise speed (Mach)		0.20		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TOR	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	27.22	21.77	-5.45	20%
wingspan (m)	13.91	10.01	-3.90	28%
VMO (kt)	800	800	0	0%
MMO (Mach)	2.20	2.05	-0.15	7%
HMO (ft)		60000		
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TOUR	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.60	-0.15	20%
wingspan (m)	7.92	9.26	1.34	17%
VMO (kt)		143		
MMO (Mach)		0.29		
HMO (ft)	14000	14625	625	4%
Normal cruise speed IAS (kt)	87	98	11	13%
Normal cruise speed (Mach)		0.17		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TR20	P28R		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.87	1.25	0.38	44%
wingspan (m)	7.42	10.80	3.38	46%
VMO (kt)		186		
MMO (Mach)		0.40		
HMO (ft)	18000	18400	400	2%
Normal cruise speed IAS (kt)	120	129	9	8%
Normal cruise speed (Mach)		0.21		
Average Error				25%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TRF1	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.91	0.95	0.04	4%
wingspan (m)	6.56	8.00	1.44	22%
VMO (kt)		220		
MMO (Mach)		0.45		
HMO (ft)		16000		
Normal cruise speed IAS (kt)	162	150	-12	7%
Normal cruise speed (Mach)		0.29		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TRIM	DA42		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	6.12	1.78	-4.34	71%
wingspan (m)	23.72	13.42	-10.30	43%
VMO (kt)		155		
MMO (Mach)		0.29		
HMO (ft)	17500	18000	500	3%
Normal cruise speed IAS (kt)	106	124	18	17%
Normal cruise speed (Mach)		0.27		
Average Error				34%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TRIS	DA42		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	2.86	1.78	-1.08	38%
wingspan (m)	14.94	13.42	-1.52	10%
VMO (kt)	152	155	3	2%
MMO (Mach)		0.29		
HMO (ft)	16200	18000	1800	11%
Normal cruise speed IAS (kt)	140	124	-16	11%
Normal cruise speed (Mach)		0.27		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TS11	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	3.80	5.22	1.42	37%
wingspan (m)	10.70	9.46	-1.24	12%
VMO (kt)	405	490	85	21%
MMO (Mach)	0.80	0.80	0.00	0%
HMO (ft)	41000	39370	-1630	4%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TU22	FGTL		
Engine type	JET	JET	0	
WTC	M	H	M / H	
MTOW (t)	92.00	214.60	122.60	133%
wingspan (m)	23.50	41.80	18.30	78%
VMO (kt)		500		
MMO (Mach)	1.52	1.20	-0.32	21%
HMO (ft)	43635	41000	-2635	6%
Normal cruise speed IAS (kt)		350		
Normal cruise speed (Mach)		0.80		
Average Error				60%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TU95	FGTL		
Engine type	TBP	JET	TBP / JET	
WTC	H	H	0	
MTOW (t)	185.00	214.60	29.60	16%
wingspan (m)	50.04	41.80	-8.24	16%
VMO (kt)		500		
MMO (Mach)		1.20		
HMO (ft)	39370	41000	1630	4%
Normal cruise speed IAS (kt)		350		
Normal cruise speed (Mach)	0.87	0.80	-0.07	8%
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TUCA	TBM7		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.17	2.98	-0.19	6%
wingspan (m)	11.14	12.68	1.54	14%
VMO (kt)	280	270	-10	4%
MMO (Mach)		0.64		
HMO (ft)	30000	31000	1000	3%
Normal cruise speed IAS (kt)	180	205	25	14%
Normal cruise speed (Mach)		0.49		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TUTR	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.13	0.45	-0.68	60%
wingspan (m)	10.36	8.10	-2.26	22%
VMO (kt)		127		
MMO (Mach)		0.27		
HMO (ft)	16000	16500	500	3%
Normal cruise speed IAS (kt)	70	88	18	26%
Normal cruise speed (Mach)		0.14		
Average Error				28%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TWEN	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.16	1.28	0.12	10%
wingspan (m)	10.30	11.63	1.33	13%
VMO (kt)	164	172	8	5%
MMO (Mach)		0.35		
HMO (ft)	15000	16400	1400	9%
Normal cruise speed IAS (kt)	130	110	-20	15%
Normal cruise speed (Mach)		0.23		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TWIR	P06T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.95	1.23	0.28	29%
wingspan (m)	9.24	11.40	2.16	23%
VMO (kt)		172		
MMO (Mach)		0.34		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	140	130	-10	7%
Normal cruise speed (Mach)		0.21		
Average Error				20%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	TWST	EV97		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.41	0.45	0.04	10%
wingspan (m)	7.50	8.10	0.60	8%
VMO (kt)	162	127	-35	22%
MMO (Mach)		0.27		
HMO (ft)		16500		
Normal cruise speed IAS (kt)	105	88	-17	16%
Normal cruise speed (Mach)		0.14		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	U15	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	11.00	8.55	-2.45	22%
VMO (kt)	120	108	-12	10%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	80	83	3	4%
Normal cruise speed (Mach)		0.15		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	U21	F406		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	4.38	4.25	-0.13	3%
wingspan (m)	13.98	15.09	1.11	8%
VMO (kt)	208	230	22	11%
MMO (Mach)		0.52		
HMO (ft)	26150	30000	3850	15%
Normal cruise speed IAS (kt)	150	180	30	20%
Normal cruise speed (Mach)		0.36		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	UF10	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.52	0.60	0.08	15%
wingspan (m)	10.00	9.26	-0.74	7%
VMO (kt)	136	143	7	5%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	95	98	3	3%
Normal cruise speed (Mach)		0.17		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	UF13	SF25		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.54	-0.06	10%
wingspan (m)	13.00	15.30	2.30	18%
VMO (kt)	115	103	-12	10%
MMO (Mach)		0.21		
HMO (ft)		14800		
Normal cruise speed IAS (kt)	60	54	-6	10%
Normal cruise speed (Mach)		0.21		
Average Error				12%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	UT75	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.96	0.45	-0.51	53%
wingspan (m)	9.73	8.98	-0.75	8%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)	13125	14000	875	7%
Normal cruise speed IAS (kt)	74	60	-14	19%
Normal cruise speed (Mach)		0.12		
Average Error				22%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	V22	A140		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	27.44	21.00	-6.44	23%
wingspan (m)	15.52	24.50	8.98	58%
VMO (kt)		227		
MMO (Mach)		0.50		
HMO (ft)	25000	24934	-66	0%
Normal cruise speed IAS (kt)	230	221	-9	4%
Normal cruise speed (Mach)		0.42		
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	VAMP	L39		
Engine type	JET	JET	0	
WTC	L	L	0	
MTOW (t)	5.62	5.22	-0.40	7%
wingspan (m)	11.58	9.46	-2.12	18%
VMO (kt)	476	490	14	3%
MMO (Mach)		0.80		
HMO (ft)	42800	39370	-3430	8%
Normal cruise speed IAS (kt)		250		
Normal cruise speed (Mach)		0.50		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	VC10	B703		
Engine type	JET	JET	0	
WTC	H	H	0	
MTOW (t)	141.52	140.00	-1.52	1%
wingspan (m)	44.55	44.10	-0.45	1%
VMO (kt)		375		
MMO (Mach)	0.86	0.90	0.04	5%
HMO (ft)	42000	42000	0	0%
Normal cruise speed IAS (kt)		300		
Normal cruise speed (Mach)	0.82	0.80	-0.02	2%
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	VELO	C340		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.02	2.72	1.70	167%
wingspan (m)	8.71	11.62	2.91	33%
VMO (kt)	200	234	34	17%
MMO (Mach)		0.63		
HMO (ft)	30000	30000	0	0%
Normal cruise speed IAS (kt)	160	153	-7	4%
Normal cruise speed (Mach)		0.34		
Average Error				44%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	VF14	YK40		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	19.95	17.20	-2.75	14%
wingspan (m)	21.50	25.00	3.50	16%
VMO (kt)		243		
MMO (Mach)		0.54		
HMO (ft)	25000	26575	1575	6%
Normal cruise speed IAS (kt)	250	210	-40	16%
Normal cruise speed (Mach)		0.46		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	VF35	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	27.22	21.77	-5.45	20%
wingspan (m)	10.67	10.01	-0.66	6%
VMO (kt)		800		
MMO (Mach)	1.60	2.05	0.45	28%
HMO (ft)		60000		
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				18%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	VK3P	S22T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.61	1.63	0.02	1%
wingspan (m)	12.09	11.67	-0.42	3%
VMO (kt)		208		
MMO (Mach)		0.44		
HMO (ft)		25000		
Normal cruise speed IAS (kt)		135		
Normal cruise speed (Mach)		0.30		
Average Error				2%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	VO10	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.02	1.16	0.14	14%
wingspan (m)	10.67	11.00	0.33	3%
VMO (kt)		160		
MMO (Mach)		0.32		
HMO (ft)	13000	14000	1000	8%
Normal cruise speed IAS (kt)	89	102	13	15%
Normal cruise speed (Mach)		0.20		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	VTOR	E500		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	3.00	2.13	-0.87	29%
wingspan (m)	12.00	11.60	-0.40	3%
VMO (kt)		209		
MMO (Mach)		0.51		
HMO (ft)	25000	25000	0	0%
Normal cruise speed IAS (kt)	170	160	-10	6%
Normal cruise speed (Mach)		0.32		
Average Error				10%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	VTUR	C340		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.91	2.72	1.81	199%
wingspan (m)	8.38	11.62	3.24	39%
VMO (kt)		234		
MMO (Mach)		0.63		
HMO (ft)	29000	30000	1000	3%
Normal cruise speed IAS (kt)	200	153	-47	24%
Normal cruise speed (Mach)		0.34		
Average Error				66%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	WA40	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.20	1.28	0.08	7%
wingspan (m)	10.00	11.63	1.63	16%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)	16400	16400	0	0%
Normal cruise speed IAS (kt)	110	110	0	0%
Normal cruise speed (Mach)		0.23		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	WA41	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.20	1.28	0.08	7%
wingspan (m)	10.00	11.63	1.63	16%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)	16400	16400	0	0%
Normal cruise speed IAS (kt)	100	110	10	10%
Normal cruise speed (Mach)		0.23		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	WA42	P28T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.41	1.25	-0.16	11%
wingspan (m)	10.00	10.80	0.80	8%
VMO (kt)	178	186	8	4%
MMO (Mach)		0.40		
HMO (ft)	16400	18400	2000	12%
Normal cruise speed IAS (kt)	135	130	-5	4%
Normal cruise speed (Mach)		0.22		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	WA50	P06T		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.13	1.23	0.10	9%
wingspan (m)	9.40	11.40	2.00	21%
VMO (kt)		172		
MMO (Mach)		0.34		
HMO (ft)	14760	14000	-760	5%
Normal cruise speed IAS (kt)	129	130	1	1%
Normal cruise speed (Mach)		0.21		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	WACF	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.34	1.16	-0.18	13%
wingspan (m)	9.14	11.00	1.86	20%
VMO (kt)	186	160	-26	14%
MMO (Mach)		0.32		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	80	102	22	28%
Normal cruise speed (Mach)		0.20		
Average Error				19%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	WB57	A10		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	24.36	23.13	-1.23	5%
wingspan (m)	19.50	17.53	-1.97	10%
VMO (kt)	502	450	-52	10%
MMO (Mach)	0.79	0.75	-0.04	5%
HMO (ft)	45100	45000	-100	0%
Normal cruise speed IAS (kt)		215		
Normal cruise speed (Mach)	0.70	0.56	-0.14	20%
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	WSP	MAGC		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.54	0.60	0.06	11%
wingspan (m)	8.90	8.55	-0.35	4%
VMO (kt)	105	108	3	3%
MMO (Mach)		0.21		
HMO (ft)		12000		
Normal cruise speed IAS (kt)	95	83	-12	13%
Normal cruise speed (Mach)		0.15		
Average Error				8%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	WT9	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.60	0.60	0.00	0%
wingspan (m)	9.00	9.26	0.26	3%
VMO (kt)	151	143	-8	5%
MMO (Mach)		0.29		
HMO (ft)		14625		
Normal cruise speed IAS (kt)	115	98	-17	15%
Normal cruise speed (Mach)		0.17		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	WW23	E55P		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	9.39	8.15	-1.24	13%
wingspan (m)	13.65	15.91	2.26	17%
VMO (kt)	360	320	-40	11%
MMO (Mach)	0.77	0.78	0.01	1%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.64	0.70	0.06	9%
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	WW24	BE40		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	10.36	7.39	-2.97	29%
wingspan (m)	13.16	13.26	0.10	1%
VMO (kt)		320		
MMO (Mach)	0.76	0.78	0.02	3%
HMO (ft)	45000	45000	0	0%
Normal cruise speed IAS (kt)		280		
Normal cruise speed (Mach)	0.75	0.76	0.01	1%
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	XA41	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.85	0.95	0.10	12%
wingspan (m)	7.50	8.00	0.50	7%
VMO (kt)	225	220	-5	2%
MMO (Mach)		0.45		
HMO (ft)	15000	16000	1000	7%
Normal cruise speed IAS (kt)	167	150	-17	10%
Normal cruise speed (Mach)		0.29		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	XA42	E300		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.85	0.95	0.10	12%
wingspan (m)	7.50	8.00	0.50	7%
VMO (kt)	225	220	-5	2%
MMO (Mach)		0.45		
HMO (ft)	15000	16000	1000	7%
Normal cruise speed IAS (kt)	167	150	-17	10%
Normal cruise speed (Mach)		0.29		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	XL2	C162		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.75	0.60	-0.15	20%
wingspan (m)	8.72	9.26	0.54	6%
VMO (kt)	157	143	-14	9%
MMO (Mach)		0.29		
HMO (ft)	12500	14625	2125	17%
Normal cruise speed IAS (kt)	110	98	-12	11%
Normal cruise speed (Mach)		0.17		
Average Error				13%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	Y12	C208		
Engine type	TBP	TBP	0	
WTC	L	L	0	
MTOW (t)	5.67	3.97	-1.70	30%
wingspan (m)	19.20	15.88	-3.32	17%
VMO (kt)	162	175	13	8%
MMO (Mach)		0.43		
HMO (ft)	23000	25000	2000	9%
Normal cruise speed IAS (kt)	140	150	10	7%
Normal cruise speed (Mach)		0.27		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	Y12F	JS32		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	8.40	7.35	-1.05	12%
wingspan (m)	19.89	15.85	-4.04	20%
VMO (kt)	209	250	41	20%
MMO (Mach)		0.52		
HMO (ft)	23000	25000	2000	9%
Normal cruise speed IAS (kt)	170	200	30	18%
Normal cruise speed (Mach)		0.41		
Average Error				16%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	Y130	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	10.29	7.00	-3.29	32%
wingspan (m)	9.84	9.11	-0.73	7%
VMO (kt)	572	550	-22	4%
MMO (Mach)	0.93	0.95	0.02	2%
HMO (ft)	41020	50000	8980	22%
Normal cruise speed IAS (kt)	280	280	0	0%
Normal cruise speed (Mach)		0.73		
Average Error				11%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	Y18T	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.65	1.16	-0.49	30%
wingspan (m)	11.16	11.00	-0.16	1%
VMO (kt)	161	160	-1	1%
MMO (Mach)		0.32		
HMO (ft)	13000	14000	1000	8%
Normal cruise speed IAS (kt)	110	102	-8	7%
Normal cruise speed (Mach)		0.20		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	YK18	DA40		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.32	1.28	-0.04	3%
wingspan (m)	10.60	11.63	1.03	10%
VMO (kt)		172		
MMO (Mach)		0.35		
HMO (ft)	16600	16400	-200	1%
Normal cruise speed IAS (kt)		110		
Normal cruise speed (Mach)		0.23		
Average Error				5%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	YK28	F16		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	20.00	21.77	1.77	9%
wingspan (m)	12.50	10.01	-2.49	20%
VMO (kt)		800		
MMO (Mach)	1.73	2.05	0.32	18%
HMO (ft)	55000	60000	5000	9%
Normal cruise speed IAS (kt)		330		
Normal cruise speed (Mach)		0.84		
Average Error				14%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	YK52	P28U		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.29	1.31	0.02	2%
wingspan (m)	9.30	10.80	1.50	16%
VMO (kt)	194	186	-8	4%
MMO (Mach)		0.41		
HMO (ft)	19685	20000	315	2%
Normal cruise speed IAS (kt)	108	122	14	13%
Normal cruise speed (Mach)		0.27		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	YS11	ATP		
Engine type	TBP	TBP	0	
WTC	M	M	0	
MTOW (t)	24.50	22.93	-1.57	6%
wingspan (m)	32.00	30.63	-1.37	4%
VMO (kt)		225		
MMO (Mach)		0.50		
HMO (ft)	22900	25000	2100	9%
Normal cruise speed IAS (kt)		205		
Normal cruise speed (Mach)		0.40		
Average Error				7%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	YURO	AJET		
Engine type	JET	JET	0	
WTC	M	M	0	
MTOW (t)	10.10	7.00	-3.10	31%
wingspan (m)	9.62	9.11	-0.51	5%
VMO (kt)	626	550	-76	12%
MMO (Mach)		0.95		
HMO (ft)	41010	50000	8990	22%
Normal cruise speed IAS (kt)	270	280	10	4%
Normal cruise speed (Mach)		0.73		
Average Error				15%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	Z42	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.09	1.16	0.07	6%
wingspan (m)	9.34	11.00	1.66	18%
VMO (kt)	170	160	-10	6%
MMO (Mach)		0.32		
HMO (ft)	14760	14000	-760	5%
Normal cruise speed IAS (kt)	95	102	7	7%
Normal cruise speed (Mach)		0.20		
Average Error				9%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	Z43	C172		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	1.25	1.16	-0.09	7%
wingspan (m)	9.76	11.00	1.24	13%
VMO (kt)	155	160	5	3%
MMO (Mach)		0.32		
HMO (ft)	14775	14000	-775	5%
Normal cruise speed IAS (kt)	100	102	2	2%
Normal cruise speed (Mach)		0.20		
Average Error				6%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ZERO	PAY3		
Engine type	PST	TBP	PST / TBP	
WTC	L	L	0	
MTOW (t)	3.15	5.08	1.93	61%
wingspan (m)	12.00	14.53	2.53	21%
VMO (kt)		246		
MMO (Mach)		0.52		
HMO (ft)	33000	33000	0	0%
Normal cruise speed IAS (kt)		220		
Normal cruise speed (Mach)	0.45	0.46	0.01	2%
Average Error				21%

Parameter	Synonym Aircraft	Reference Aircraft Model	Delta	% error
ICAO	ZULU	SVNH		
Engine type	PST	PST	0	
WTC	L	L	0	
MTOW (t)	0.47	0.45	-0.02	4%
wingspan (m)	10.00	8.98	-1.02	10%
VMO (kt)		109		
MMO (Mach)		0.22		
HMO (ft)		14000		
Normal cruise speed IAS (kt)	69	60	-9	13%
Normal cruise speed (Mach)		0.12		
Average Error				9%

Page intentionally left blank