THE UNIVERSITY OF BRITISH COLUMBIA
Electrical and Computer Engineering Department

CPEN 442 **Introduction to Cybersecurity** **Winter Term 1, 2026**

Assignment 3: Authentication and Hashing

Name	Student number
Chongkai (Lucas) Lyu	30349559
Leyang Gao	58256207

Questions 3, 6, and 9 are answered in `a3.py`; this PDF covers Questions 1, 2, 4, 5, 7, and 8.

1 Offline Dictionary Attacks

[10 pts] **Question 1** Which hash function generated each of the three digests, how did you deduce it, and what are the passwords?

Digest 1: hash function `SHA-256`, password `annette`
Digest 2: hash function `SHA3-224`, password `spurs`
Digest 3: hash function `SHA-1`, password `loki`
How I deduced the hash functions: One hexadecimal character is 4 bits, so the bit length of a digest is four times its character length. The three digests have lengths 64, 56, and 40, which are 256, 224, and 160 bits. That narrows the SHA family, but it does not name a single function: SHA-256, SHA3-256, and SHA-512/256 all produce 64 hex characters, and SHA-224, SHA3-224, and SHA-512/224 all produce 56. Only SHA-1 is a common SHA function with a 40-character digest.
The passwords cannot be recovered by inverting the hash. The assignment says every password comes from the dictionary, so I hashed each dictionary word with every candidate of the matching length and compared the result with the digest. Each digest matched exactly once: SHA-256(`annette`), SHA3-224(`spurs`), and SHA-1(`loki`). The same-length alternatives matched no dictionary word, so the dictionary search both identifies the algorithm and recovers the password.

[10 pts] **Question 2** Answer the three questions about the bcrypt digests, briefly explaining each answer (one sentence is enough).

Hash function used: bcrypt. All three digests use bcrypt, as indicated by the `$2b$` prefix in their Modular Crypt Format representations.
Same salt or different salts: different salts. The 22-character salt fields following the cost factors are `AS2K2H8nSwdvs2yNoDgtbu`, `Shq4mPuANPJbdqozQkB1NO`, and `dHO22WXdr4/w6PiDHhVYA.`
Digest that took longer to compute, and why: digest 2. Its cost factor is 8, while digests 1 and 3 have cost factor 6. bcrypt's work scales as 2^{cost}, so digest 2 takes about $2^8/2^6 = 4$ times as much work.

[15 pts] Question 4 Which of `q3_sample1.txt`, `q3_sample2.txt`, and `q3_sample3.txt` is the easiest to break, and which is the hardest? Why?

Easiest: `q3_sample?.txt`
Explanation:

Hardest: `q3_sample?.txt`
Explanation:

2 Offline Brute-Force Attacks

[10 pts] Question 5 What is the maximum password length that your computer can brute-force in under one day, for bcrypt (4 rounds) and for SHA-256? Explain how you got each number.

My computer's hashing speed: bcrypt (4 rounds): ? hashes per second; SHA-256: ? hashes per second
Maximum length with bcrypt: ?
Maximum length with SHA-256: ?
How I got these numbers:

3 Two-Factor Authentication

[10 pts] Question 7 Which service did you pick, which forms of two-factor authentication does it support, and how could an attacker circumvent it?

Service: ?
Forms of two-factor authentication it supports: ?

How an attacker could circumvent it (a realistic example):

4 Authentication in UBC

[15 pts] **Question 8** Comment on the two answers from the UBC website, and quote the NIST recommendation that applies to each one.

"Why do I have to change my CWL password?"
My comment:
NIST recommendation (quote and section number):

"What are the CWL password requirements?"
My comment:
NIST recommendation (quote and section number):

Generative AI Disclosure