

A Comparison of Static, Dynamic, and Hybrid Analysis for Malware Detection

LyuJiuyang, Dec 23, 2021

Info

- **Title:** A Comparison of Static, Dynamic, and Hybrid Analysis for Malware Detection.
- **Author:** Anusha Damodaran, Fabio Di Troia, Corrado Aaron Visaggio, Thomas H. Austin & Mark Stamp.
- **Journal:** J. Comput. Virol. Hacking Tech. 2017.

Introduction

Difference between Static and Dynamic detection methods: if needed to execute the software.

Signature Based Detection

Core: A database of signatures of malware.

Pros: simple, relatively fast and effective

Cons: need an up-to-date database, can be simply evade.

Behavior Based Detection

Classify a software while focusing on the actions performed by the malware during execution.

Statistical Based Detection

based on statistical properties derived from program features.

Hidden Markov Models




Figure 1: Generic Hidden Markov Model

- T = length of the observation sequence
- N = number of states in the model
- M = number of observation symbols
- $Q = \{q_0, q_1, \dots, q_{N-1}\}$ = distinct states of the Markov process
- $V = \{0, 1, \dots, M-1\}$ = set of possible observations
- A = state transition probabilities
- B = observation probability matrix
- π = initial state distribution
- $\mathcal{O} = (\mathcal{O}_0, \mathcal{O}_1, \dots, \mathcal{O}_{T-1})$ = observation sequence.

Unnecessary to write much about this part, this article simply applies HMM to malware detection. The **Problems** to solve are also classic.

Related Work

Static Analysis

Based on opcode sequences, control flow graphs, function call graph, etc. Using some techniques or ML such as SVM+PCA.

Dynamic Analysis

Based on API calls, system calls, instruction traces, registry changes, memory writes, and so on.

Hybrid Approaches

Seems can be obtain more features.

Experiments

- Tools: IDA Pro, Buster Sandbox Analyzer, Ether.
- Datasets: Harebot, Security Shield, Smart HDD, Winwebsec, Zbot, ZeroAccess
- Metrics: AUC

Training/Scoring with specified analysis.




Figure 4: ROC Results for API Call Sequence




Figure 7: ROC Results for Opcode Sequences

A straightforward hybrid approach is unlikely to be superior to fully dynamic detection. Use hybrid with caution.

Other

- Imbalance Problem: In Recommender System, negative sampling is a good way to solve it. But the scale of these datasets are too small.
- It's very likely that using LSTM will achieve better performance.
- As authors mentioned, more scoring techniques can be used.
- Shijie Key uses CNN in her Graduation Project to detect malware, which is also a good idea.