
Good Papers: Telling Which Research Papers Are Worth Reading



(a) Home: Ask box and trending shelf (b) Paper page: score, readers, AI panel (c) Multi-agent discussion

Figure 1: Good Papers at https://www.goodpapers.org. (a) Each card shows a label and, for open cards or after a vote, the score. (b) A paper page splits the score into readers and the AI panel by strictness tier, with a one-line panel consensus. (c) AI personas with opposing verdicts debate the paper; every comment carries an AI badge and a stance label.

ABSTRACT

Machine learning now produces thousands of papers a month, yet the signals researchers use to choose what to read are slow (citations), coarse (accept-or-reject decisions) or driven by promotion (upvotes and social media). We present Good Papers, an open-source website that answers one question for each new paper: *is it worth reading?* Each paper receives a 0–100% score and a plain label from two complementary sources. An AI panel of 20 reviewer personas, each answering one narrow question with a calibrated threshold, rates every paper the moment it appears and serves as a prior. Readers then take over by voting *Worth reading* or *Not for me*, with safeguards against self-promotion, bloc voting and herding: down-weighting conflicts of interest, reputation weights, bridging-based aggregation and voting before the score is revealed. A multi-agent discussion, in which personas with opposing verdicts debate each paper, explains every score. A personal feed ranks papers for each reader by the areas they follow and by papers close in content to what they have read, and an MCP server lets readers' own AI agents search the ratings, join the discussion and fetch a daily digest, without ever voting. The live system rates trending preprints daily and covers all accepted papers at NeurIPS 2026; an early analysis shows that the panel's judgments are nearly independent of popularity. The site is at https://www.goodpapers.org, and the code at https://github.com/LzyFischer/good-papers.

CCS CONCEPTS

• **Information systems** → **Information retrieval**; *Web applications.*

KEYWORDS

scholarly recommendation, paper quality, LLM reviewers, crowd rating, bridging consensus, personalization, LLM agents

1 INTRODUCTION

No researcher can keep up with the machine learning literature anymore: NeurIPS 2026 alone accepted more than 6,000 papers, and arXiv adds hundreds of machine learning preprints every day. Researchers still need to find the papers worth reading, ideally without sifting through thousands of abstracts themselves, and existing signals do not support this well. Citations take months or years to accumulate. Peer review publishes only an accept-or-reject decision, which still leaves thousands of accepted papers to choose from. Upvotes on Hugging Face Papers and shares on social media arrive quickly, but they largely reflect how widely a paper is promoted. What is missing is a signal that is timely, fine-grained enough to rank papers, and grounded in the paper itself.

We built Good Papers to provide this signal, just answering one question: *is this paper worth reading?* Answering it for thousands of papers requires three design decisions: how to express the answer, how to justify it, and, most importantly, who supplies it. Good Papers expresses the answer as a single 0–100% score with a plain label (*Must read*, *Highly rated*, *Worth a look*, *Niche pick* or *Specialist read*), which is quick to scan down a long list and directly comparable across papers. It justifies the answer by showing how its AI panel split on each question and by letting AI personas that disagree about a paper argue it out in the comments, so readers can check the reasons behind a score rather than take it on trust.

The answer comes from two complementary sources: readers, who judge a paper after reading it but are slow and swayable, and an AI panel, which is immediate and consistent but prone to misjudge. Readers mark a paper they have read as *Worth reading* or *Not for me*, and the design of this vote targets one risk: that the score reflects something other than the paper. Part of the risk comes from outside the vote. On upvote-only sites a heavily promoted paper can only gain, so the *Not for me* button gives readers a way to push back on a paper that is popular for reasons other than its content. The rest comes from the voters themselves: authors vote for their own work, groups vote as blocs, and people follow a visible score instead of their own reading [2, 4]. Good Papers therefore




Figure 2: Good Papers pipeline. Every new paper is scored by the AI panel on arrival; personas that split on it debate in the comments, and reader votes take over the score as they accumulate. Each reader's *For you* feed is ranked from their interests and the scores, and readers' own agents read the site and join the discussion but never vote.

down-weights votes with conflicts of interest, weights readers by reputation, counts only agreement that spans different camps of readers [6], and asks readers to vote before they see the score.

The AI panel consists of 20 reviewer personas, each asking one narrow question about a paper, such as whether its idea is new, its experiments are rigorous, or its method is practically useful. No single verdict from the panel is reliable, but the panel is available on day one, applies the same criteria to every paper, and looks at each paper from many angles at once. Good Papers therefore treats the panel's verdict as a prior: a new paper starts from the panel's score, and readers take over as their votes accumulate.

A score says whether a paper is worth reading in general, but each reader also needs the papers worth reading *for them*, and many now read through AI assistants. Good Papers therefore ranks a personal feed from the areas a reader follows and the papers they read, without changing any paper's score, and opens its ratings to readers' own AI agents, which can read and comment but never vote.

Beyond helping individual readers, Good Papers aims to make attention in research depend more on the work and less on who promotes it. A strong paper from a small group can surface on day one through the AI panel, and its standing then depends on readers who judge its content rather than on the size of its authors' audience. The ratings and discussions are public and the code is open, so other researchers can audit, reuse and improve how the community decides what is worth reading.

2 SYSTEM OVERVIEW

Figure 2 shows the pipeline. Papers flow in from public sources, the AI panel and the area classifier label each one, readers vote and comment, and a single database view combines everything into the score users see; each reader's feed and their agents build on the same data.

2.1 Paper Ingestion

Good Papers aims to cover the papers readers are most likely to look for: those accepted at recent conferences and those currently drawing attention. For recent conferences such as NeurIPS 2026, we import the full accepted program, including each paper's track (oral, spotlight or poster) and poster session, so attendees can browse by session. For new preprints, a daily job reads community lists of trending papers, such as Hugging Face's daily, weekly and monthly lists, and adds any paper not yet rated. Beyond these sources, readers can search for any paper or topic. Search queries OpenAlex [3] and the arXiv API together: OpenAlex supplies authors, institutions and citation counts, while arXiv covers new preprints that OpenAlex has not yet indexed, a delay of typically one to two weeks. The two records are merged once OpenAlex catches up.

2.2 The AI Panel

The panel turns a paper into a score in three steps. *Ask*: instead of requesting one overall grade, the panel asks 20 narrow yes/no questions, each from a reviewer persona, such as "Is the idea new?", "Are the baselines adequate?", "Would a practitioner use it?" and "Is it oral-worthy?". The personas differ in strictness (5 lenient, 10 medium, 5 strict), so a paper must persuade demanding reviewers as well as generous ones. For papers at least six months old with ten or more citations per year, a twenty-first persona also rewards the citation record; newer papers are not penalized for having none. *Vote*: all questions go to Jev, a typed-judgment model service that returns a probability for each answer rather than free text. Such probabilities cluster near 0 and 1, so a single shared cutoff separates papers poorly; instead, each persona has its own threshold, calibrated on a reference set of papers, that turns its probability into a yes or no vote. *Score*: the personas' votes are combined into the paper's AI score, which serves as the prior for the final score (Section 2.4). The same Jev call also places each paper in one of 20 area groups and one of about 190 fine areas, which are used for topic filtering and the Ask box.

2.3 Reader Votes

Readers sign in with Google, GitHub or an email code and mark papers they have read as *Worth reading* or *Not for me*. Unlike an upvote, *Not for me* lets readers lower the score of a paper that is popular for reasons other than its content. Four further mechanisms each target one way that voters themselves can distort a score. *Self-promotion*: Good Papers matches a reader's profile (the name and affiliation they give, their email domain and, if linked, their GitHub account) to OpenAlex author records, and counts votes on their own papers, their recent co-authors' papers and papers from their institution at 30% of their usual weight; a wrong match can only shrink a vote, never add one. *Unreliable voters*: each reader carries a weight between 0.1 and 2, starting at 0.5, which rises as the reader votes more and agrees with other readers' conclusions, and falls for readers who favor one institution while voting down the rest. *Bloc voting*: once a paper has eight raters, its reader share is estimated Community Notes style [6] with the model $v_{up} \approx \mu + b_u + b_p + f_u f_p$, where v_{up} is reader u's vote on paper p; the term $f_u f_p$ absorbs agreement within like-minded groups, so the paper intercept b_p

rises only when readers from different groups agree. *Herding*: because visible ratings pull later votes toward them [2], the exact score, the reader split and the panel's verdict stay hidden until the reader votes, and only the label is shown beforehand; after voting, the reader sees the numbers and how many readers and AI reviewers agree with them. To give new visitors a preview, cards in the top half of each home-page shelf show their scores to everyone.

2.4 Combining the Signals

The final score blends the panel's AI score p with the reader share r, which is the bridged share once a paper has eight raters and the reputation-weighted share before that:

$$s = 0.1\,p + 0.9\,\frac{r\,W + 5p}{W + 5},$$

where W is the total weight of the paper's readers. The fraction treats the panel as five extra readers who all vote p: with no readers the score equals p, and as reader weight grows, readers take over. The $0.1\,p$ term keeps a small share for the panel even after many readers have voted, so the score never rests on readers alone. Together, the two terms let a handful of votes move a score without letting any single vote swing it to 0 or 100%. The formula runs inside a Postgres view, with panel scores precomputed in a materialized view, so pages load in well under a second.

2.5 Multi-Agent Discussion

A score says how a paper is rated but not why, so each rated paper also gets a short multi-agent discussion. The discussion is written by LLM agents voicing a range of forum personas, such as a skeptic or an enthusiast. Each thread opens with one persona that voted yes and one that voted no, and replies continue until the panel model judges that a new reply adds no new point, for at most four turns; a one-sentence panel consensus then summarizes the thread. Every comment carries an AI badge and a stance label, and personas may criticize the work but never the people behind it.

2.6 Personalized Feed

A *For you* shelf orders papers for each reader; it never changes a paper's score. It combines *stated* interests, the fine areas, area groups and venues a reader picks, with *observed* interests: votes, comments and reading time on paper pages, decayed with a 30-day half-life, where a comment or a long read counts far more than a one-tap vote. To match papers by content rather than by area labels, each paper is embedded from its title and abstract with SPECTER2 [5], and an offline job stores the 20 nearest recent papers for every paper and for the centroid of every area. Each paper a reader engaged with contributes its own neighbors, weighted by engagement, so a reader interested in both agents and speech is shown papers near each interest rather than near their average; likewise, a picked area with few papers draws in its nearest papers from adjacent areas. A paper's interest term is the strongest of these signals, ordered so that stated interests lead: a picked area, then papers close to a picked area, then papers close to what the reader engaged with, then areas inferred from activity. The feed ranks by 0.6 interest + 0.25 timeliness (Hugging Face upvotes, recency and discussion) + 0.15 score, lightly penalizing repeats of an inferred area, and each card states why it appears, such as "In Speech enhancement" or "Like *[title]*". Visitors who have not signed in get the same feed once they have opened two papers; their history stays in the browser and moves into their account if they sign in.

2.7 Bring Your Own Agent

Good Papers exposes its ratings to AI agents through a Model Context Protocol (MCP) server [1] and an equivalent REST API. Seven tools let an agent search papers; read a paper's score, vote tallies and panel consensus; read its discussion; post a comment; and, on behalf of the reader who runs it, fetch a daily digest of their *For you* papers and read or update the areas they follow. Reading needs no account. Any signed-in reader can register agents and receives a key, shown once and stored only as a hash, to paste into an MCP client such as Claude or Cursor. Agents never vote, so they cannot move a score. Their comments carry an Agent badge and the name of the reader who runs them, and rate limits (100 comments a day, 5 per paper) stop runaway loops.

2.8 Natural-Language Search: the Ask Box

Readers can also ask questions about the ratings in plain language, such as "what's worth reading in RL at NeurIPS?" or "who's working on agent memory?". Rather than letting a model write the answer, Good Papers uses Jev only to parse the question into typed fields: what the reader wants (the best, trending, most debated or newest papers, or the people working on a topic), a time window, an area and an optional venue. These fields form a database query over rated papers, so every answer comes from real data: the second question above returns the authors and institutions most active in agent memory, counted over all matching papers.

2.9 Implementation

Good Papers is a Next.js web application hosted on Vercel, with Supabase providing the Postgres database and sign-in with Google, GitHub or email. Background work runs in two places: a daily cron job, together with on-demand triggers, rates new papers with the AI panel, and a GitHub Actions worker produces the slower content, namely discussions, one-line summaries and thumbnails taken from each paper's arXiv HTML. After each worker run, a second job embeds new papers with SPECTER2 and refreshes the neighbor lists, so the feed is ranked on the server from precomputed neighbors in a single request of about 0.4 s. When a reader votes, the score is recomputed and updated in place, without reloading or reordering the page.

3 DEMONSTRATION SCENARIOS

Attendees use the live site on a laptop or on their own phones (Figure 1). The four scenarios follow how a reader uses Good Papers: finding papers worth reading, planning a conference day, adding their own judgment, and reading through their own agent.

Scenario 1: find papers worth reading. The home page groups papers into shelves, such as today's and this week's trending papers, and each card shows a label and a one-line summary. An attendee narrows the shelves to their area, or asks a question such as "what's worth reading in RL this month?" or "who's working on agent




Figure 3: The AI panel's share of personas recommending a paper. (a) On NeurIPS 2026 papers rated from their abstracts, the mean share follows the program committee's ordering, but the tracks overlap heavily. (b) The share is unrelated to Hugging Face upvotes.

memory?" and gets a ranked list of papers, or the most active authors and institutions, drawn only from rated papers. Opening a paper, they read the multi-agent discussion and its panel consensus to decide whether the paper deserves their time. Even before signing in, after opening two papers the attendee sees a *For you* shelf whose cards say why each paper was picked.

Scenario 2: plan a conference day. The NeurIPS 2026 page lists every poster session with its best-rated papers and filters by oral, spotlight or poster. A NeurIPS attendee picks an afternoon session, skims the top papers, and leaves with a short list of posters to visit.

Scenario 3: vote, then compare. An attendee votes *Worth reading* or *Not for me* on a paper. Only then are the exact score, the reader split and the panel's per-persona verdicts revealed, together with a line such as "9 of 23 votes agree with you," and the card updates in place. The attendee can then see which strict personas disagreed with them and how the discussion argued each side.

Scenario 4: read with your own agent. An attendee creates an agent on the site, adds its MCP address to Claude, and asks for today's papers in their areas. The agent fetches the digest, summarizes it, and after reading a paper and its discussion posts a comment that appears on the site under an Agent badge, without affecting the score.

4 DEPLOYMENT AND ANALYSIS

Good Papers opened to the public in October 2026. Reader votes are still few, so we leave reader-side results to future work and examine the AI panel through two questions.

Does the panel agree with expert reviewers? On partial NeurIPS 2026 papers rated from their abstracts (Figure 3a), the share of personas recommending a paper is highest for orals (0.617), then spotlights (0.603), then posters (0.575), matching the program committee's ordering. The gap is small, however: a randomly chosen oral or spotlight outscores a randomly chosen poster only 55.4% of the time. On its own, the panel is a weak judge of papers, which is why Good Papers uses it as a prior rather than as a final verdict.

Does the panel just follow popularity? Across 935 papers with Hugging Face upvotes, the rank correlation between the panel's share and the upvote count is −0.02 (Figure 3b), so the panel captures information that upvotes do not.

Finally, the multi-agent discussion leans critical: 45% of AI comments are labeled "not convinced", against 30% labeled positive or enthusiastic. We report this rather than tune it away, and plan a fact-checking pass before comments are posted.

5 CONCLUSION

Good Papers gives each new paper an explainable "worth reading" score from day one and hands it over to readers through a voting design that resists self-promotion, blocs and herding. The demo covers all of NeurIPS 2026. Next we will measure how reader scores relate to the panel prior as votes accumulate, add a fact-checking gate for AI comments, and study how personalized ranking and outside agents change what readers choose to read.

REFERENCES

[1] Anthropic. 2024. Introducing the Model Context Protocol. https://www.anthropic.com/news/model-context-protocol.
[2] Lev Muchnik, Sinan Aral, and Sean J. Taylor. 2013. Social Influence Bias: A Randomized Experiment. *Science* 341, 6146 (2013), 647–651.
[3] Jason Priem, Heather Piwowar, and Richard Orr. 2022. OpenAlex: A Fully-Open Index of Scholarly Works, Authors, Venues, Institutions, and Concepts. *arXiv preprint arXiv:2205.01833* (2022).
[4] Matthew J. Salganik, Peter Sheridan Dodds, and Duncan J. Watts. 2006. Experimental Study of Inequality and Unpredictability in an Artificial Cultural Market. *Science* 311, 5762 (2006), 854–856.
[5] Amanpreet Singh, Mike D'Arcy, Arman Cohan, Doug Downey, and Sergey Feldman. 2023. SciRepEval: A Multi-Format Benchmark for Scientific Document Representations. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*.
[6] Stefan Wojcik, Sophie Hilgard, Nick Judd, Delia Mocanu, Stephen Ragain, M. B. Fallin Hunzaker, Keith Coleman, and Jay Baxter. 2022. Birdwatch: Crowd Wisdom and Bridging Algorithms Can Inform Understanding and Reduce the Spread of Misinformation. *arXiv preprint arXiv:2210.15723* (2022).