



COMP 125 Programming with Python

Dictionaries



```
py_dict = { 1: 'Apple', 2: 'OnePlus' }
```

Diagram illustrating the structure of a Python dictionary. The keys (1 and 2) are labeled 'key' and the values ('Apple' and 'OnePlus') are labeled 'value'. The pairs are grouped into 'Item 1' and 'Item 2'.

Mehmet Sayar
Koç University

How can we store and organize data?

- **Collection:** A data structure used to store values as a single unit
- So far, we have seen lists and tuples for general data storage
- The items were accessed by their indices
- What if we want to use more generic indices, such as a string?
- Or if we have mappings such as key -> value

Organizing Data

- Dictionaries

`Turkish2English['bir'] = 'one'`

- Using name and surname to get the student identification numbers

`StudentIDs['John Doe'] = '00123456'`

- Storing the measurements of a furniture

`table['width'] = 1.2, table['length'] = 2.0`

- Sparse arrays (where a lot entries are non-existent)

`array[1] = 1.48, array[141] = -7.92, array[186219] = 0.3`

- And many more!


Dictionaries

- A collection (sometimes called container) data type that maps “**keys**” to their associated “**values**”
- Defined using curly brackets: {key1:value1, key2:value2, ...}
- Called maps in most languages, associative arrays in some others
- Values can be any Python object
- Keys can be any “hashable” Python object (more on this in a little bit)
 - Strings, integers, floats work
 - Booleans and functions work too
 - Tuples work but not lists

Anatomy of a Dictionary


- Let's define a dictionary of pet's and the number of times they were fed
`d = {'hansa': 4, 'kandula': 3, 'lumpy': 2, 'surus': 6}`

- Let's visualize:



Anatomy of a Dictionary

- Can “get” (retrieve) the value
`a = d['hansa']`
`a → 4`
- Can “set” the values
`d['hansa'] = 5`
- Error if key not in the dictionary for get
`b = d['karzo']`



Keys are unique, each key stores a single value
(this value can be a list, tuple or another collection)

Anatomy of a Dictionary

- Can create a new key-value pair

```
d['karzo'] = 4
```

- Can check if a key exists

```
'hansa' in d
```

→ **True**


```
'pasa' in d
```

→ **False**

```
'pasa' not in d
```

→ **True**

- Common pattern: Check if key is present. If it is, do something. If it isn't, do something else.



More Dictionary Examples

```
# Create an empty dictionary:
```

```
d = {}
```

```
# Add the key-value pair
```

```
d['hansa'] = 1
```

```
# Update the key-value pair (note that get and set done at the same line)
```

```
d['hansa'] += 2
```

```
d['hansa'] → 3
```

```
# Keys and values do not have to be of the same type
```

```
d[1.34] = 'Random Float'
```

```
d → {'hansa': 3, 1.34: 'Random Float'}
```

string key
integer value

float key
string value

Built-in Methods for Dictionaries

- `len`: Returns the number of key-value pairs inside the dictionary
- `del` statement: removes key-value pair
 - General format: `del dictionary[key]`
- `min` and `max`: They work on keys, but the keys must be comparable (e.g. if you have both string and integer type keys it won't work)

Dictionary Methods: Reference Slide

Method	Description
<code>clear()</code>	Removes all the elements from the dictionary
<code>copy()</code>	Returns a copy of the dictionary
<code>fromkeys(keys)</code>	Returns a dictionary with the specified keys and value
<code>get(key, default_value)</code>	Returns the value of the specified key
<code>items()</code>	Returns a list containing a tuple for each key value pair
<code>keys()</code>	Returns a list containing the dictionary's keys
<code>pop(key, default_value)</code>	Removes the element with the specified key
<code>popitem()</code>	Removes the last inserted key-value pair
<code>update(pair_iterable)</code>	Updates the dictionary with the specified key-value pairs
<code>values()</code>	Returns a list of all the values in the dictionary

Some Useful Dictionary Methods

- `keys()`: Returns an iterable data type that holds the **keys**
- `values()`: Returns an iterable data type that holds the **values**
- `items()`: Returns an iterable data type that holds the **key-value pairs** as tuples

Accessing Keys

```
d = {'Koc': 27, 'Bogazici': 157, 'METU': 64}
```

```
d.keys() → dict_keys(['Koc', 'Bogazici', 'METU'])
```



iterable collection of all the keys.

iterable means it can be used in foreach

```
list(d.keys()) → ['Koc', 'Bogazici', 'METU']
```



*You can use list() to convert d.keys()
into a list*

Iterating over the Keys

```
d = {'Koc': 27, 'Bogazici': 157, 'METU': 64}
```

```
for university in d.keys():  
    print(university)
```

Output:

Koc

Bogazici

METU

Accessing Values and the Key-Value Pairs

```
d = {'Koc': 27, 'Bogazici': 157, 'METU': 64}
```

```
d.values() → dict_values([27, 157, 64])
```

```
list(d.values()) → [27, 157, 64]
```

```
d.items()
```

```
→ dict_items([('Koc', 27), ('Bogazici', 157), ('METU', 64)])
```

Iterating over the Values

```
d = {'Koc': 27, 'Bogazici': 157, 'METU': 64}
```

```
for age in d.values():  
    print(age)
```

Output:

27

157


64

Iterating over the Items

```
d = {'Koc': 27, 'Bogazici': 157, 'METU': 64}
```

Iterating over tuples and unpacking

```
for university, age in d.items():  
    print(university, 'is', age, 'years old')
```



Output:

Koc is 27 years old

Bogazici is 157 years old

METU is 64 years old

Side note: Print automatically concatenates, with a single space in between, the inputs separated by commas

Sorting Keys and Values

```
d = {'Koc': 27, 'Bogazici': 157, 'METU': 64}
```

```
sorted(d.keys()) → ['Bogazici', 'Koc', 'METU']
```

```
sorted(d.values()) → [27, 64, 157]
```