

Error handling and testing

Victor Eijkhout, Susan Lindsey

Fall 2022

last formatted: March 27, 2023

1. Programming and correctness

Find your favorite example of costly programming mistakes ...

What to do about it?

- Never make mistakes.
- Prove that your program is correct.
- Test your program before deploying it.
- Handle errors as they occur.

Error handling

2. Assertions to catch logic errors

Sanity check on things 'that you just know are true':

```
#include <cassert>
...
assert( bool expression )
```

Example:

```
x = sin(2.81);
y = x*x;
z = y * (1-y);
assert( z>=0. and z<=1. );
```

3. Using assertions

Check on valid input parameters:

```
#include <cassert>

// this function requires x<y
// it computes something positive
float f(x,y) {
    assert( x<y );
    return /* some result */;
}
```

Check on valid results:

```
float positive_outcome = f(x,y);
assert( positive_outcome>0 );
```

4. Example

```
int collatz_next( int current ) {  
    assert( current>0 );  
    int next{-1};  
    if (current%2==0) {  
        next = current/2;  
        assert(next<current);  
    } else {  
        next = 3*current+1;  
        assert(next>current);  
    }  
    return next;  
}
```

5. Use assertions during development

Assertions are disabled by

```
#define NDEBUG
```

before the include.

You can pass this as compiler flag:

```
icpc -DNDEBUG yourprog.cxx
```

6. Exceptions

Not every error is fatal:

$$\text{Exception} \equiv \left\{ \begin{array}{l} \text{'this should not happen'} \\ \text{but we can handle it} \end{array} \right.$$

1. recover from the problem
2. graceful exit

7. Exceptions

Have you seen the following?

Code:

```
1 vector<float> x(5);  
2 x.at(5) = 3.14;
```

Output:

```
libc++abi.dylib: terminating with  
uncaught exception of type  
std::out_of_range: vector
```

The Standard Template Library (STL) can generate many exceptions.

- You can let your program crash, and start debugging
- You can try to catch and handle them yourself.

8. Exception structure

Code with problem:

```
if ( /* some problem */ )  
    throw(5);  
/* or: throw("error"); */
```

```
try {  
    /* code that can go wrong */  
} catch (...) { // literally  
    three dots!  
    /* code to deal with the  
       problem */  
}
```

9. Exceptions

Assume a routine only works for certain values, and you want to generate an error if called with an inappropriate value.

```
double compute_root(double x) {  
    if (x<0) throw(1);  
    return sqrt(x);  
}  
  
int main() {  
    try {  
        y = compute_root(x);  
    } catch (...) {  
        /* handle error */  
        cout << "Root failed, using default\n";  
        y = 0;  
    }  
}
```

See book for more details.