

Derived Types and Modules in Fortran

Victor Eijkhout, Susan Lindsey

Fall 2022

last formatted: March 27, 2023

Types

1. Structures: type

- Fortran has structures similar to C:
bundle variables – of different types.
- Structures are a derived type: you can create variables of that type, but it's not a built-in type.
- Fortran keyword for derived types is (confusingly) `Type`

2. Type declaration

Type name / End Type name block.

Member declarations inside the block:

```
type mytype
  integer :: number
  character :: name
  real(4) :: value
end type mytype
```

Type definitions go before executable statements.

3. Creating / initializing type variables

Declare type variables in the main program:

```
Type(mytype) :: struct1, struct2
```

Initialize with type name:

```
struct1 = mytype( 1, 'my_name', 3.7 )
```

Copying:

```
struct2 = struct1
```

4. Member access

Access structure members with %
(compare C++ dot-notation)

```
Type(mytype) :: typed_struct  
typed_struct%member = ....
```

5. Example

```
type point
  real :: x,y
end type point
```

```
type(point) :: p1,p2
p1 = point(2.5, 3.7)
```

```
p2 = p1
print *,p1
print *,p2%x,p2%y
```

6. Structures as procedure argument

Structures can be passed as procedure argument, just like any other datatype. In this example the function *length*:

- Takes a structure of `type(point)` as argument; and
- returns a `real(4)` result.
- The structure is declared as `intent(in)`.

Function with structure
argument:


```
real(4) function length(p)
  implicit none
  type(point), intent(in) :: p
  length = sqrt( &
    p%x**2 + p%y**2 )
end function length
```

Function call

```
print *, "Length:", length(p2)
```


Exercise 1

Add a function `angle` that takes a `Point` argument and returns the angle of the x -axis and the line from the origin to that point.



Your program should read in the x, y values of the point and print out the angle in radians.

Bonus: can you print the angle as a fraction of π ? So

$$(1, 1) \Rightarrow 0.25$$

You can base this off the file `point.F90` in the repository

Exercise 2

Write a program that has the following:

- A type *Point* that contains real numbers x, y ;
- a type *Rectangle* that contains two *Points*, corresponding to the lower left and upper right point;
- a function *area* that has one argument: a *Rectangle*.

Your program should

- Accept two real numbers on one line, for the bottom left point;
- similarly, again on one line, the coordinates of the top right point; then
- print out the area of the (axi-parallel) rectangle defined by these two points.

7. Definitions

Type definition:

```
type namedvar  
  character(len=20) :: expression = ""  
  integer :: value  
end type namedvar
```

Exercise 3

The following main program should give the corresponding output:

Code:

```
1 print *,x
2 print *,y
3 z = varadd(x,y)
4 print *,z
5 a = varmult(x,z)
6 print *,a
```

Output:

x	1
y	2
(x)+(y)	3
((x)+(y)) * (x)	3

You can base this off the file named var.F90 in the repository

Turn it in!

- If you have compiled your program, do:
`coe_varf yourprogram.F90`
where 'yourprogram.F90' stands for the name of your source file.
- Is it reporting that your program is correct? If so, do:
`coe_varf -s yourprogram.F90`
where the `-s` flag stands for 'submit'.
- If you don't manage to get your code working correctly, you can submit as incomplete with
`coe_varf -i yourprogram.F90`
- Use the `-d` debug flag for more information.

For bonus points, use a module.

Modules

8. What are modules

Programming is about introducing abstractions.

- Functions are good.
- ... but in a **Contains** section they can only be used in one program.
- \Rightarrow Put useful functions in a module and use that module anywhere.
- 'Software library'

9. Module definition

Modules look like a program, but without main (only 'stuff to be used elsewhere'):

```
Module geometry
  type point
    real :: x,y
  end type point
  real(8),parameter :: pi = 3.14159265359
contains
  real(4) function length(p)
    implicit none
    type(point),intent(in) :: p
    length = sqrt( p%x**2 + p%y**2 )
  end function length
end Module geometry
```

Note also the numeric constant.

10. Example use

Module imported through use statement;
placed before implicit none

Code:

```
1 Program size
2   use geometry
3   implicit none
4
5   type(point) :: p1,p2
6   p1 = point(2.5, 3.7)
7
8   p2 = p1
9   print *,p2%x,p2%y
10  print *,"length:",length(p2)
11  print *,2*pi
12
13 end Program size
```

Output:

```
2.50000000
3.70000005
length:  4.46542263
6.2831854820251465
```

Exercise 4

Create a module (suggested name: *VarHandling*) and move the *namedvar* type definition and the routines *varadd*, *varmult* into it.

Exercise 5

Also create a module (suggested name: *InputHandling*) that contains the routines *islower*, *isdigit* from the character exercises in chapter ?? . You will also need an *isop* routine to recognize arithmetic operations.

Exercise 6

Write a loop that accepts character input, and only prints out what kind of character was encountered: a lowercase character, a digit, or a character denoting an arithmetic operation $+ - * /$.

Code:

```
1 do
2   read *,input
3   if (input .eq. '0') then
4     exit
5   else if ( isdigit(input) ) then
```

Output:

```
Inputs: 4 x 3 + 0
4 is a digit
x is a lowercase
3 is a digit
+ is an operator
```

Use the *InputHandling* module introduced above.

11. Stack definition

```
type(namedvar),dimension(10) :: stack  
integer :: stackpointer=0
```

Exercise 7

Make your event loop accept digits, creating a new entry:

Code:

```
1 else if ( isdigit(input) ) then
2     call stack_push(input)
```

Output:

Inputs: 4 5 6 0

expr=4 val=4;

expr=4 val=4; expr=5 val=5;

expr=4 val=4; expr=5 val=5; expr=6 val=6;

Exercise 8

Add a clause to your event loop to handle characters that stand for arithmetic operations:

Code:

```
1 else if ( isop(input) ) then
2     call stack_op(input)
```

Output:

Inputs: 4 5 6 + + 0

expr=4 val=4;

expr=4 val=4; expr=5 val=5;

expr=4 val=4; expr=5 val=5; expr=6 val=6;

expr=4 val=4; expr=(5)+(6) val=11;

expr=(4)+((5)+(6)) val=15;

Advanced module topics

12. Module use syntax

Use statement placed before `Implicit`

```
Program ModProgram
  use FunctionsAndValues
  implicit none
```

```
  print *, "Pi is:", pi
  call SayHi()
```

```
End Program ModProgram
```

Also possible:

```
Use mymodule, Only: func1, func2
Use mymodule, func1 => new_name1
```

13. Separate compilation of modules

Suppose program is split over two files:

`theprogram.F90` and `themodule.F90`.

- Compile the module: `ifort -c themodule.F90`; this gives
- an object file (extension: `.o`) that will be linked later, and
- a module file `modulename.mod`.
- Compile the main program:
`ifort -c theprogram.F90` will read the `.mod` file; and finally
- Link the object files into an executable:
`ifort -o myprogram theprogram.o themodule.o`
The compiler is used as linker: there is no compiling in this step.

Important: the module needs to be compiled before any (sub)program that uses it.