

Objects and classes

Victor Eijkhout, Susan Lindsey

Fall 2022

last formatted: March 27, 2023

Classes

1. Definition of object/class

An object is an entity that you can request to do certain things. These actions are the *methods*, and to make these possible the object probably stores data, the *members*.

When designing a class, first ask yourself:
'what functionality should the objects support'.

A class is a user-defined type; an object is an instance of that type.

2. Running example

We are going to build classes for points/lines/shapes in the plane.

```
1 class Point {  
2     /* stuff */  
3 };  
4 int main () {  
5     Point p; /* stuff */  
6 }
```

Exercise 1

Thought exercise: what are some of the actions that a point object should be capable of?

3. Object functionality

Small illustration: point objects.

Code:

```
1 Point p(1.,2.); // make point (1,2)
2 cout << "distance to origin "
3     << p.distance_to_origin()
4     << '\n';
5 p.scaleby(2.);
6 cout << "distance to origin "
7     << p.distance_to_origin()
8     << '\n'
9     << "and angle " << p.angle()
10    << '\n';
```

Output:

```
distance to origin
    2.23607
distance to origin
    4.47214
and angle 1.10715
```

Note the 'dot' notation.

Exercise 2

Thought exercise:

What data does the object need to store to be able to calculate angle and distance to the origin?

Is there more than one possibility?

4. The object workflow

- First define the class, with data and function members:

```
class MyObject {  
    // define class members  
    // define class methods  
};
```

(details later) typically before the *main*.

- You create specific objects with a declaration

```
MyObject  
    object1( /* .. */ ),  
    object2( /* .. */ );
```

- You let the objects do things:

```
object1.do_this();  
x = object2.do_that( /* ... */ );
```


5. Construct an object

The declaration of an object *x* of class *Point*; the coordinates of the point are initially set to 1.5,2.5.

```
Point x(1.5, 2.5);
```

```
1 class Point {  
2 private: // data members  
3     double x,y;  
4 public: // function members  
5     Point  
6         ( double x_in,double y_in  
7             ) {  
8             x = x_in; y = y_in;  
9         };  
10    /* ... */  
11 };
```

Use the constructor to create an object of a class:
function with same name as the class.
(but no return type!)

6. Private and public

Best practice we will use:

```
class MyClass {  
private:  
    // data members  
public:  
    // methods  
}
```

- Data is private: not visible outside of the objects.
- Methods are public: can be used in the code that uses objects.
- You can have multiple private/public sections, in any order.

Methods

7. Class methods

Let's define method *distance*.

Definition in the class:

```
class Point {  
    /* stuff */  
    double distance_to_origin() {  
        return sqrt(x*x + y*y); }  
}
```


Use in the program:

```
Point pt(5,12);  
double  
    s = pt.distance_to_origin();
```

- Methods look like ordinary functions,
- except that they can use the data members of the class, for instance *x,y*;
- Methods can only be used on an object with the 'dot' notation. They are not independently defined.

Exercise 3

Add a method *angle* to the *Point* class. How many parameters does it need?



Hint: use the function *atan* or *atan2*.

You can base this off the file `pointclass.cxx` in the repository

Exercise 4

Make a class *GridPoint* which can have only integer coordinates. Implement a function *manhattan_distance* which gives the distance to the origin counting how many steps horizontal plus vertical it takes to reach that point.

8. Food for thought: constructor vs data

The arguments of the constructor imply nothing about what data members are stored!

Example: create a point in x,y Cartesian coordinates, but store r, θ polar coordinates:

```
1 #include <cmath>
2 class Point {
3 private: // members
4     double r, theta;
5 public: // methods
6     Point( double x, double y ) {
7         r = sqrt(x*x+y*y);
8         theta = atan2(y/x);
9     }
```

Note: no change to outward API.

Exercise 5

Discuss the pros and cons of this design:

```
1 class Point {  
2 private:  
3     double x,y,r,theta;  
4 public:  
5     Point(double xx,double yy) {  
6         x = xx; y = yy;  
7         r = // sqrt something  
8         theta = // something trig  
9     };  
10    double angle() { return alpha; };  
11 };
```


9. Data access in methods

You can access data members of other objects of the same type:

```
1 class Point {  
2     private:  
3         double x,y;  
4     public:  
5         void flip() {  
6             Point flipped;  
7             flipped.x = y; flipped.y = x;  
8             // more  
9         };  
10 };
```

(Normally, data members should not be accessed directly from outside an object)

Exercise 6

Extend the `Point` class of the previous exercise with a method: `distance` that computes the distance between this point and another: if `p,q` are `Point` objects,

`p.distance(q)`

computes the distance between them.

Review quiz 1

T/F?

- A class is primarily determined by the data it stores.
`/poll "Class determined by its data" "T" "F"`
- A class is primarily determined by its methods.
`/poll "Class determined by its methods" "T" "F"`
- If you change the design of the class data, you need to change the constructor call.
`/poll "Change data, change constructor proto too" "T" "F"`

10. Methods that alter the object

For instance, you may want to scale a vector by some amount:

Code:

```
1 class Point {
2     /* ... */
3     void scaleby( double a ) {
4         x *= a; y *= a; };
5     /* ... */
6 };
7     /* ... */
8     Point p1(1.,2.);
9     cout << "p1 to origin "
10         << p1.length() << '\n';
11     p1.scaleby(2.);
12     cout << "p1 to origin "
13         << p1.length() << '\n';
```

Output:

```
p1 to origin 2.23607
p1 to origin 4.47214
```

Data initialization

11. Member default values

Class members can have default values, just like ordinary variables:

```
class Point {  
private:  
    float x=3., y=.14;  
public:  
    // et cetera  
}
```

Each object will have its members initialized to these values.

12. Data initialization

The naive way:

```
1 class Point {  
2 private:  
3     double x,y;  
4 public:  
5     Point( double in_x,  
6           double in_y ) {  
7         x = in_x; y = in_y;  
8     };
```

The preferred way:

```
1 class Point {  
2 private:  
3     double x,y;  
4 public:  
5     Point( double userx,  
6           double usery )  
7         : x(userx),y(usery) {  
8     }
```

Interaction between objects

13. Methods that create a new object

Code:

```
1 class Point {  
2     /* ... */  
3     Point scale( double a ) {  
4         auto scaledpoint =  
5             Point( x*a, y*a );  
6         return scaledpoint;  
7     };  
8     /* ... */  
9     cout << "p1 to origin "  
10         << p1.dist_to_origin()  
11         << '\n';  
12     Point p2 = p1.scale(2.);  
13     cout << "p2 to origin "  
14         << p2.dist_to_origin()  
15         << '\n';
```

Output:

```
p1 to origin 2.23607  
p2 to origin 4.47214
```

Note the 'anonymous object' in the assignment

14. Anonymous objects

Create a point by scaling another point:

```
new_point = old_point.scale(2.81);
```

Two ways of handling the `return` statement:

Naive:

```
1 Point Point::scale( double a )  
  {  
2   Point scaledpoint =  
3   Point( x*a, y*a );  
4   return scaledpoint;  
5 };
```

Creates point, copies it to *new_point*

Better:

```
1 Point Point::scale( double a )  
  {  
2   return Point( x*a, y*a );  
3 };
```

Creates point, moves it directly to
new_point

'move semantics' and 'copy elision':
compiler is pretty good at avoiding copies

Optional exercise 7

Write a method *halfway* that, given two *Point* objects *p*, *q*, construct the *Point* halfway, that is, $(p + q)/2$:

```
Point p(1,2.2), q(3.4,5.6);  
Point h = p.halfway(q);
```

You can write this function directly, or you could write functions *Add* and *Scale* and combine these.

(Later you will learn about operator overloading.)

How would you print out a *Point* to make sure you compute the halfway point correctly?

15. Using the default constructor

No constructor explicitly defined;

You recognize the default constructor in the main by the fact that an object is defined without any parameters.

Code:

```
1 class IamOne {  
2 private:  
3   int i=1;  
4 public:  
5   void print() {  
6     cout << i << '\n';  
7   };  
8 };  
9 /* ... */  
10 IamOne one;  
11 one.print();
```

Output:

1

16. Default constructor

Refer to point definition: 9

Consider this code that looks like variable declaration, but for objects:

```
Point p1(1.5, 2.3);  
Point p2;  
p2 = p1.scaleby(3.1);
```

Compiling gives (g++; different for intel):

```
pointdefault.cxx: In function 'int main()':  
pointdefault.cxx:32:21: error: no matching function for call to  
                        'Point::Point()'
```

17. Default constructor

The problem is with *p2*:

```
Point p1(1.5, 2.3);
```

```
Point p2;
```

- *p1* is created with the constructor;
- *p2* uses the default constructor:

```
Point() {};
```

- as soon as you define a constructor, the default constructor goes away;
- you need to redefine the default constructor:

```
Point() {};
```

```
Point( double x, double y )  
    : x(x), y(y) {};
```

(but only if you really need it.)

18. Other way

```
Point() = default;  
Point( double x,double y )  
    : x(x),y(y) {};
```

Also:

```
Point() = delete;
```

to disable.

Exercise 8

Make a class `LinearFunction` with a constructor:

```
LinearFunction( Point input_p1,Point input_p2 );
```

and a member function

```
float evaluate_at( float x );
```

which you can use as:

```
LinearFunction line(p1,p2);  
cout << "Value at 4.0: " << line.evaluate_at(4.0) << endl;
```


19. Classes for abstract objects

Objects can model fairly abstract things:

Code:

```
1 class Stream {
2 private:
3     int last_result{0};
4 public:
5     int next() {
6         return last_result++; };
7 };
8
9 int main() {
10     Stream ints;
11     cout << "Next: "
12         << ints.next() << '\n';
13     cout << "Next: "
14         << ints.next() << '\n';
15     cout << "Next: "
16         << ints.next() << '\n';
```

Output:

```
Next: 0
Next: 1
Next: 2
```

20. Preliminary to the following exercise

A prime number generator has:
an API of just one function: `nextprime`

To support this it needs to store:
an integer `last_prime_found`

Project Exercise 9

Write a class `primegenerator` that contains:

- Methods `number_of_primes_found` and `nextprime`;
- Also write a function `isprime` that does not need to be in the class.

Your main program should look as follows:

```
cin >> nprimes;
primegenerator sequence;
while (sequence.number_of_primes_found()<nprimes) {
    int number = sequence.nextprime();
    cout << "Number " << number << " is prime" << '\n';
}
```

Turn it in!

- If you have compiled your program, do:
`coe_primes yourprogram.cc`
where 'yourprogram.cc' stands for the name of your source file.
- Is it reporting that your program is correct? If so, do:
`coe_primes -s yourprogram.cc`
where the -s flag stands for 'submit'.
- If you don't manage to get your code working correctly, you can submit as incomplete with
`coe_primes -i yourprogram.cc`
- If you don't understand what the script is telling you, try the debug flag:
`coe_primes -d yourprogram.cc`

Project Exercise 10

The Goldbach conjecture says that every even number, from 4 on, is the sum of two primes $p + q$. Write a program to test this for the even numbers up to a bound that you read in. Use the `primegenerator` class you developed in exercise 35.

This is a great exercise for a top-down approach!

1. Make an outer loop over the even numbers e .
2. For each e , generate all primes p .
3. From $p + q = e$, it follows that $q = e - p$ is prime: test if that q is prime.

For each even number e then print e, p, q , for instance:

The number 10 is 3+7

If multiple possibilities exist, only print the first one you find.

Turn it in!

- If you have compiled your program, do:
`coe_goldbach yourprogram.cc`
where 'yourprogram.cc' stands for the name of your source file.
- Is it reporting that your program is correct? If so, do:
`coe_goldbach -s yourprogram.cc`
where the -s flag stands for 'submit'.
- If you don't manage to get your code working correctly, you can submit as incomplete with
`coe_goldbach -i yourprogram.cc`

21. A Goldbach corollary

The Goldbach conjecture says that every even number $2n$ (starting at 4), is the sum of two primes $p + q$:

$$2n = p + q.$$

Equivalently, every number n is equidistant from two primes:

$$n = \frac{p + q}{2} \quad \text{or} \quad q - n = n - p.$$

In particular this holds for each prime number:

$$\forall_{r \text{ prime}} \exists_{p, q \text{ prime}} : r = (p + q)/2 \text{ is prime.}$$

Project Exercise 11

Write a program that tests this. You need at least one loop that tests all primes r ; for each r you then need to find the primes p, q that are equidistant to it. Do you use two generators for this, or is one enough? Do you need three, for p, q, r ?

For each r value, when the program finds the p, q values, print the p, q, r triple and move on to the next r .

Turn it in!

- If you have compiled your program, do:

```
coe_pqr yourprogram.cc
```

where 'yourprogram.cc' stands for the name of your source file.

- Is it reporting that your program is correct? If so, do:

```
coe_pqr -s yourprogram.cc
```

where the -s flag stands for 'submit'.

- If you don't manage to get your code working correctly, you can submit as incomplete with

```
coe_pqr -i yourprogram.cc
```

Advanced stuff

22. Direct alteration of internals

Return a reference to a private member:

```
1 class Point {  
2 private:  
3     double x,y;  
4 public:  
5     double &x_component() { return x; };  
6 };  
7 int main() {  
8     Point v;  
9     v.x_component() = 3.1;  
10 }
```

Only define this if you need to be able to alter the internal entity.

23. Reference to internals

Returning a reference saves you on copying.

Prevent unwanted changes by using a 'const reference'.

```
1 class Grid {
2 private:
3     vector<Point> thepoints;
4 public:
5     const vector<Point> &points() const {
6         return thepoints; };
7 };
8 int main() {
9     Grid grid;
10    cout << grid.points()[0];
11    // grid.points()[0] = whatever ILLEGAL
12 }
```

24. Access gone wrong

We make a class for points on the unit circle

```
1 class UnitCirclePoint {  
2     private:  
3         float x,y;  
4     public:  
5         UnitCirclePoint(float x) {  
6             setx(x); };  
7     void setx(float newx) {  
8         x = newx; y = sqrt(1-x*x);  
9     };
```

You don't want to be able to change just one of x,y !
In general: enforce invariants on the members.

25. Const functions

A function can be marked as const:
it does not alter class data,
only changes are through return and parameters

26. 'this' pointer to the current object

Inside an object, a pointer to the object is available as this:

```
1 class MyClass {  
2     private:  
3         int myint;  
4     public:  
5         MyClass(int myint) {  
6             this->myint = myint; // `this' redundant!  
7         };  
8 };
```

27. 'this' use

You don't often need the `this` pointer. Example: you need to call a function inside a method that needs the object as argument)

```
1 /* forward definition: */ class someclass;
2 void somefunction(const someclass &c) {
3     /* ... */ }
4 class someclass {
5     // method:
6     void somemethod() {
7         somefunction(*this);
8     };
```

(Rare use of dereference star)

Operator overloading

28. Operator overloading

Syntax:

<returntype> **operator**<op>(<argument>) { <definition> }

For instance:

Code:

```
1 Point Point::operator*(double f) {  
2     return Point(f*x,f*y);  
3 };  
4 /* ... */  
5 cout << "p1 to origin "  
6     << p1.dist_to_origin() <<  
7     '\n';  
7 Point scale2r = p1*2.;  
8 cout << "scaled right: "  
9     << scale2r.dist_to_origin()  
10    << '\n';  
10 // ILLEGAL Point scale2l = 2.*p1;
```

Output:

```
p1 to origin 2.23607  
scaled right: 4.47214
```

Can also:



`Point::operator*=(double factor);`

Exercise 12

Revisit exercise 7 and replace the *add* and *scale* functions by overloaded operators.

Hint: for the *add* function you may need `'this'`.

29. Constructors and contained classes

Finally, if a class contains objects of another class,

```
1 class Inner {  
2 public:  
3     Inner(int i) { /* ... */ }  
4 };  
5 class Outer {  
6 private:  
7     Inner contained;  
8 public:  
9 };
```

30. When are contained objects created?

```
Outer( int n ) {  
    contained = Inner(n);  
};
```

1. This first calls the default constructor
2. then calls the *Inner(n)* constructor,
3. then copies the result over the *contained* member.

```
Outer( int n )  
    : contained(Inner(n)) {  
    /* ... */  
};
```

1. This creates the *Inner(n)* object,
2. placed it in the *contained* member,
3. does the rest of the constructor, if any.

31. Copy constructor

- Default defined copy and 'copy assignment' constructors:

```
some_object x(data);  
some_object y = x;  
some_object z(x);
```

- They copy an object:
 - simple data, including pointers
 - included objects recursively.
- You can redefine them as needed.

```
1 class has_int {  
2 private:  
3     int mine{1};  
4 public:  
5     has_int(int v) {  
6         cout << "set: " << v  
7         << '\n';  
8         mine = v; };  
9     has_int( has_int &h ) {  
10        auto v = h.mine;  
11        cout << "copy: " << v  
12        << '\n';  
13        mine = v; };  
14    void printme() {  
15        cout << "I have: " << mine  
16        << '\n'; };  
17 };
```

32. Copy constructor in action

Code:

```
1 has_int an_int(5);  
2 has_int other_int(an_int);  
3 an_int.printme();  
4 other_int.printme();  
5 has_int yet_other = other_int;  
6 yet_other.printme();
```

Output:

```
set: 5  
copy: 5  
I have: 5  
I have: 5  
copy: 5  
I have: 5
```

33. Copying is recursive

Class with a vector:

```
1 class has_vector {  
2 private:  
3     vector<int> myvector;  
4 public:  
5     has_vector(int v) { myvector.push_back(v); };  
6     void set(int v) { myvector.at(0) = v; };  
7     void printme() { cout  
8         << "I have: " << myvector.at(0) << '\n'; };  
9 };
```

Copying is recursive, so the copy has its own vector:

Code:

```
1 has_vector a_vector(5);  
2 has_vector other_vector(a_vector);  
3 a_vector.set(3);  
4 a_vector.printme();  
5 other_vector.printme();
```

Output:

```
I have: 3  
I have: 5
```


34. Destructor

- Every class *myclass* has a *destructor* *~myclass* defined by default.

- The default destructor does nothing:

```
~myclass() {};
```

- A destructor is called when the object goes out of scope.
Great way to prevent memory leaks: dynamic data can be released in the destructor. Also: closing files.

35. Destructor example

Just for tracing, constructor and destructor do `cout`:

```
1 class SomeObject {  
2 public:  
3     SomeObject() {  
4         cout << "calling the constructor"  
5             << '\n';  
6     };  
7     ~SomeObject() {  
8         cout << "calling the destructor"  
9             << '\n';  
10    };  
11};
```

36. Destructor example

Destructor called implicitly:

Code:

```
1 cout << "Before the nested scope"
2   << '\n';
3 {
4   SomeObject obj;
5   cout << "Inside the nested scope"
6       << '\n';
7 }
8 cout << "After the nested scope"
9   << '\n';
```

Output:

*Before the nested scope
calling the constructor
Inside the nested scope
calling the destructor
After the nested scope*

Headers

37. C headers plusplus

You know how to use `.h` files in C.

Classes in C++ need some extra syntax.

38. Data members in proto

Data members, even private ones, need to be in the header file:

```
1 class something {  
2 private:  
3   int localvar;  
4 public:  
5   // declaration:  
6   double somedo(vector);  
7 };
```

Implementation file:

```
1 // definition  
2 double something::somedo(vector v) {  
3   .... something with v ....  
4   .... something with localvar ....  
5 };
```

39. Static class members

A static member acts as if it's shared between all objects.

(Note: C++17 syntax)

Code:

```
1 class myclass {  
2 private:  
3     static inline int count=0;  
4 public:  
5     myclass() { count++; };  
6     int create_count() {  
7         return count; };  
8 };  
9  /* ... */  
10 myclass obj1,obj2;  
11 cout << "I have defined "  
12      << obj1.create_count()  
13      << " objects" << '\n';
```

Output:

I have defined 2 objects

40. Static class members, C++11 syntax

```
1 class myclass {  
2 private:  
3     static int count;  
4 public:  
5     myclass() { count++; };  
6     int create_count() { return count; };  
7 };  
8 /* ... */  
9 // in main program  
10 int myclass::count=0;
```