Sistemi Operativi I

Corso di Laurea in Informatica 2024-2025



Gabriele Tolomei

Dipartimento di Informatica Sapienza Università di Roma

tolomei@di.uniroma1.it

• So far, we have assumed each process is allocated into a contiguous space of physical memory

- So far, we have assumed each process is allocated into a contiguous space of physical memory
- One simple method is to divide upfront all available memory dedicated to user processes into equally-sized segments/partitions


- So far, we have assumed each process is allocated into a contiguous space of physical memory
- One simple method is to divide upfront all available memory dedicated to user processes into equally-sized segments/partitions
 - Assign each process to a segment

- So far, we have assumed each process is allocated into a contiguous space of physical memory
- One simple method is to divide upfront all available memory dedicated to user processes into equally-sized segments/partitions
 - Assign each process to a segment
 - Implicitly restricts the grade of multiprogramming (i.e., the number of simultaneous processes) and their size


- So far, we have assumed each process is allocated into a contiguous space of physical memory
- One simple method is to divide upfront all available memory dedicated to user processes into equally-sized segments/partitions
 - Assign each process to a segment
 - Implicitly restricts the grade of multiprogramming (i.e., the number of simultaneous processes) and their size
 - No longer used!

An alternative approach is for the OS to keep track of **free** (unused) memory segments, as processes enter the system, grow, and terminate


An alternative approach is for the OS to keep track of **free** (unused) memory segments, as processes enter the system, grow, and terminate




An alternative approach is for the OS to keep track of **free** (unused) memory segments, as processes enter the system, grow, and terminate





An alternative approach is for the OS to keep track of **free** (unused) memory segments, as processes enter the system, grow, and terminate





An alternative approach is for the OS to keep track of **free** (unused) memory segments, as processes enter the system, grow, and terminate












• Linearly scan the list of holes until one is found that is big enough to satisfy the request

- Linearly scan the list of holes until one is found that is big enough to satisfy the request
- Subsequent requests may either start from the beginning of the list or from the end of previous search

- Linearly scan the list of holes until one is found that is big enough to satisfy the request
- Subsequent requests may either start from the beginning of the list or from the end of previous search
- Complexity: O(n), where n is the number of holes

20/11/2024

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using first-fit?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:




Which segment will be picked by the OS using first-fit?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:




Which segment will be picked by the OS using first-fit?



Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using first-fit?




What if afterwards process Y requires 350B?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using first-fit?



What if afterwards process Y requires 350B?

We will not be able to satisfy this request even if theoretically we could

 Allocate the smallest hole that is big enough to satisfy the request

- Allocate the smallest hole that is big enough to satisfy the request
- This saves large holes for other process requests that may need them

- Allocate the smallest hole that is big enough to satisfy the request
- This saves large holes for other process requests that may need them
- However, the resulting unused portions of holes may be too small to be of any use, and will therefore be wasted

- Allocate the smallest hole that is big enough to satisfy the request
- This saves large holes for other process requests that may need them
- However, the resulting unused portions of holes may be too small to be of any use, and will therefore be wasted
- Complexity: still O(n) but can be O(log n) if the list of holes is kept sorted

- Allocate the smallest hole that is big enough to satisfy the request
- This saves large holes for other process requests that may need them
- However, the resulting unused portions of holes may be too small to be of any use, and will therefore be wasted
- Complexity: still O(n) but can be O(log n) if the list of holes is kept sorted

Do you know how which data structure can be used to achieve this?

- Allocate the smallest hole that is big enough to satisfy the request
- This saves large holes for other process requests that may need them
- However, the resulting unused portions of holes may be too small to be of any use, and will therefore be wasted
- Complexity: still O(n) but can be O(log n) if the list of holes is kept sorted

Do you know how which data structure can be used to achieve this?

Binary Search Tree (BST)

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using best-fit?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:




Which segment will be picked by the OS using best-fit?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using best-fit?



Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using best-fit?



What if afterwards process Y requires 350B?

Suppose process X needs 100B of memory to be loaded, and the list of holes is as follows:



Which segment will be picked by the OS using best-fit?



What if afterwards process Y requires 350B?

We can now assign it the second available hole segment (400B)

• Allocate the largest hole available

- Allocate the largest hole available
- Might sound counterintuitive but this increases the likelihood that the remaining portion will be usable for satisfying future requests

- Allocate the largest hole available
- Might sound counterintuitive but this increases the likelihood that the remaining portion will be usable for satisfying future requests
- Simulations show that First-Fit and Best-Fit usually work best

- Allocate the largest hole available
- Might sound counterintuitive but this increases the likelihood that the remaining portion will be usable for satisfying future requests
- Simulations show that First-Fit and Best-Fit usually work best
- First-Fit is also generally faster than Best-Fit

Fragmentation

Problem

Individual holes may be too small to serve a process request but they can be large enough if combined together

20/11/2024 41

Fragmentation

Problem

Individual holes may be too small to serve a process request but they can be large enough if combined together

External Fragmentation

Fragmentation

Problem

Individual holes may be too small to serve a process request but they can be large enough if combined together

External Fragmentation


Internal Fragmentation

• Frequent loading and unloading processes causes holes to be broken into small (i.e., unusable) chunks

- Frequent loading and unloading processes causes holes to be broken into small (i.e., unusable) chunks
- It happens when there is enough memory to load a process in memory but space is not contiguous

20/11/2024 45


- Frequent loading and unloading processes causes holes to be broken into small (i.e., unusable) chunks
- It happens when there is enough memory to load a process in memory but space is not contiguous 3999




- Frequent loading and unloading processes causes holes to be broken into small (i.e., unusable) chunks
- It happens when there is enough memory to load a process in memory but space is not contiguous 3999

Simulations show that for every 2N allocated blocks, N are lost due to external fragmentation

1/3 of memory space is wasted on average



- Frequent loading and unloading processes causes holes to be broken into small (i.e., unusable) chunks
- It happens when there is enough memory to load a process in memory but space is not contiguous 3999





48


• It happens when memory internal to a segment is wasted


- It happens when memory internal to a segment is wasted
- For example, consider a process whose size is 8,846B
 and a hole of size 8,848B


- It happens when memory internal to a segment is wasted
- For example, consider a process whose size is 8,846B and a hole of size 8,848B
- It may be much more efficient to allocate the process the whole block (and waste 2B) rather than keep track of a tiny 2B hole






















Only one hole is left but two processes need to be moved (C and D)















20/11/2024

58



Still some holes left but only one process is moved (D) rather than two

• So far, we have assumed all processes are entirely loaded in memory (of course, when loaded!)

- So far, we have assumed all processes are entirely loaded in memory (of course, when loaded!)
- Remember: A process needs to sit physically in main memory only if the CPU executes its instructions and accesses its data

- So far, we have assumed all processes are entirely loaded in memory (of course, when loaded!)
- Remember: A process needs to sit physically in main memory only if the CPU executes its instructions and accesses its data
- If a process blocks (e.g., due to an I/O call) it doesn't need to be in memory while I/O is running

- So far, we have assumed all processes are entirely loaded in memory (of course, when loaded!)
- Remember: A process needs to sit physically in main memory only if the CPU executes its instructions and accesses its data
- If a process blocks (e.g., due to an I/O call) it doesn't need to be in memory while I/O is running
- That process can be "swapped out" from memory to disk to make room for other processes

• Once process becomes ready again, the OS must reload it in memory

- Once process becomes ready again, the OS must reload it in memory
- Swap in depends on the address binding used:
 - compile- or load-time: must be swapped back into the same memory location from which they were swapped out

- Once process becomes ready again, the OS must reload it in memory
- Swap in depends on the address binding used:
 - compile- or load-time: must be swapped back into the same memory location from which they were swapped out
 - execution-time: can be swapped back into any available location (updating base and limit registers)


- Once process becomes ready again, the OS must reload it in memory
- Swap in depends on the address binding used:
 - compile- or load-time: must be swapped back into the same memory location from which they were swapped out
 - execution-time: can be swapped back into any available location (updating base and limit registers)
- Using swapping, fragmentation can be tackled easily
 - Just run compaction before swapping-in a process

• Swapping is a very slow process compared to other operations due to the interaction with hard disk

- Swapping is a very slow process compared to other operations due to the interaction with hard disk
- Example:
 - 10 MB user process
 - disk transfer rate = 40 MB/sec (250 msec just to do the data transfer)

- Swapping is a very slow process compared to other operations due to the interaction with hard disk
- Example:
 - 10 MB user process
 - disk transfer rate = 40 MB/sec (250 msec just to do the data transfer)
- Since swap-in may involve swapping-out another process, the overall time required will be ~500 msec

- Swapping is a very slow process compared to other operations due to the interaction with hard disk
- Example:
 - 10 MB user process
 - disk transfer rate = 40 MB/sec (250 msec just to do the data transfer)
- Since swap-in may involve swapping-out another process, the overall time required will be ~500 msec
- Time slice is usually way smaller than that!



Most modern OSs no longer use swapping, because it is too slow and there are faster alternatives available (e.g., paging)

Problems Seen So Far

- Contiguous allocation
 - Hard to grow or shrink process memory

Problems Seen So Far

- Contiguous allocation
 - Hard to grow or shrink process memory
- Fragmentation
 - Frequent compaction needed

Problems Seen So Far

- Contiguous allocation
 - Hard to grow or shrink process memory
- Fragmentation
 - Frequent compaction needed
- Process entirely loaded
 - Swapping helps but it may be too inefficient

• A memory management scheme that addresses the problems above

- A memory management scheme that addresses the problems above
- The logical address space of a process is still **contiguous** but it is divided into **fixed-size blocks**, called **pages**

- A memory management scheme that addresses the problems above
- The logical address space of a process is still contiguous but it is divided into fixed-size blocks, called pages
- Contiguous allocation is no longer required as logical pages can be mapped to non-contiguous physical frames


- A memory management scheme that addresses the problems above
- The logical address space of a process is still contiguous but it is divided into fixed-size blocks, called pages
- Contiguous allocation is no longer required as logical pages can be mapped to non-contiguous physical frames
- External fragmentation is eliminated because pages have fixed size
 - Internal fragmentation may still occur though

- A memory management scheme that addresses the problems above
- The logical address space of a process is still contiguous but it is divided into fixed-size blocks, called pages
- Contiguous allocation is no longer required as logical pages can be mapped to non-contiguous physical frames
- External fragmentation is eliminated because pages have fixed size
 - Internal fragmentation may still occur though

90/10 Rule

Processes spend 90% of their time accessing only 10% of their allocated memory space

Paging: The Big Picture



Logical/Virtual Address Space of process A

Physical Memory Paging: The Big Picture frame O OS OS frame 1 page 0 A_0 frame 2 A_4 page 1 A_1 frame 3 page 2 A_2 frame 4 page 3 A_3 A_1 frame 5 page 4 A_4 frame 6 page 5 A_5 frame 7 A_2 Logical/Virtual Address Space frame 8 A_{O} of process A frame 9 A_3 frame 10 A_5 20/11/2024

82

Basic OS Responsibilities for Paging

- The OS has 2 main responsibilities:
 - mapping between logical pages and physical frames
 - translating logical addresses to physical addresses


Basic OS Responsibilities for Paging


- The OS has 2 main responsibilities:
 - mapping between logical pages and physical frames
 - translating logical addresses to physical addresses
- All of this must be done efficiently!
 - Remember, memory addresses are referenced all the time

Basic OS Responsibilities for Paging

- The OS has 2 main responsibilities:
 - mapping between logical pages and physical frames
 - translating logical addresses to physical addresses
- All of this must be done efficiently!
 - Remember, memory addresses are referenced all the time
- OS needs dedicated support for doing it → Page
 Table

Page Table: Mapping Pages to Frames





Page Table: Mapping Pages to Frames

Lookup table to retrieve what frame a page is stored in

Page	Frame
0	8
1	5
2	7
3	9
4	2
5	10

OS	0
OS	1
A ₄	2
	3
	4
A_1	5
	6
A ₂	7
A _O	8
A_3	9
A ₅	10

87

Page Table: Mapping Pages to Frames

Lookup table to retrieve what frame a page is stored in

Ο	Ao
1	A_1
2	A ₂
3	A ₃
4	A ₄
5	A ₅

Page	Frame
0	8
1	5
2	7
3	9
4	2
5	10

OS	0
OS	1
A ₄	2
	3
	4
A_1	5
	6
A ₂	7
A _O	8
A_3	9
A_5	10

We have assumed all pages of a process are mapped to physical frames, but this is not always the case

- Contiguous memory allocation may cause fragmentation
 - External vs. Internal Fragmentation

- Contiguous memory allocation may cause fragmentation
 - External vs. Internal Fragmentation
- Existing countermeasures (compaction) exist but they are costly

- Contiguous memory allocation may cause fragmentation
 - External vs. Internal Fragmentation
- Existing countermeasures (compaction) exist but they are costly
- We may want to relax the constraint on having an entire process loaded in main memory

- Contiguous memory allocation may cause fragmentation
 - External vs. Internal Fragmentation
- Existing countermeasures (compaction) exist but they are costly
- We may want to relax the constraint on having an entire process loaded in main memory
- Paging solves all these issues!