



LECTURE ASSIGNMENT



NAME: MAHER ESMAT SOHSAH

JUNE 8, 2021


AVL TREE Insertion and Deletion

TYPES OF ROTATION: LL, RR, LR, RL


EX ON: 10, 20, 30

ROTATIONS:


1. Right rotation.




2. Left rotation



3. Left Right



4. Right Left



Insertion Code

- Class TreeNode{
 Int value; TreeNode *left, *right;
 TreeNode()
 { value = 0; left = right = NULL;}
 TreeNode(int v)
 {value = v; Left = right = NULL;}
}
- Int getBalance(TreeNode *n)
 {
 1. If (n == NULL)
 1.1. Return -1;
 2. Else
 2.1. Return (height(n-> left) – height(n-> right));
 }
- Int height(TreeNode *r)
 {
 1. If (r == NULL)
 1.1. Return -1;
 2. Else
 2.1. Lheight = height(r -> left);
 2.2. Rheight = height(r -> right);
 2.3. If (Lheight > Rheight)
 2.3.1. Return (Lheight + 1);
 2.4. Else
 2.4.1. Return (Rheight + 1);
 }

- `TreeNode* rightRotate(TreeNode *y)`

```
{
    1. TreeNode *x = y -> left;
    2. TreeNode *temp = x -> right;
    3. X -> right = y;
    4. Y -> left = temp;
    5. Return x;
}
```

- `TreeNode* leftRotate(TreeNode *x)`

```
{
    1. TreeNode *y = x -> right;
    2. TreeNode *temp = y -> left;
    3. Y -> left = x;
    4. X -> right = temp;
    5. Return y;
}
```

- `TreeNode* insert (TreeNode *r, TreeNode *newnode)`

```
{
    1. If (r == NULL)
        a. r = newnode;
        b. return r;
    2. if (newnode -> value smaller r -> value)
        a. r -> left = insert(r -> left, newnode)
    3. Elseif(newnode -> value greater r -> value)
        a. r -> right = insert(r -> right, newnode)
    4. Else
        a. Print ("no duplicate values!! ")
        b. Return r;
    5. Num = getBalance(r);
    6. If (num > 1 && newnode -> value ≤ r -> left -> value)// LL-rotation
        a. Return rightRotate(r);
}
```

```

7. If (num < -1 && newnode -> value ≤ r-> left -> value)//RR-rotation
    a. Return leftRotate(r)
8. If (num > 1 && newnode -> value ≤ r->left -> value) //LR-rotation
    a. r -> left = leftRotation(r -> left)
    b. return rightRotation(r)
9. if (num < -1 && newnode -> value ≤ r ->right ->value)//RL-rotation
    a. r ->right = rightRotation(r ->right);
    b. return leftRotation(r);
10.    return r;
}

```


Insert 15:




Insert 20:



Insert 24:



Need right rotation:





Insert 10:




Insert 13:




Need rotation:




Insert 7:




Need rotation:




Insert 30:




Insert 36:




Need rotation:








Insert 25:



Need rotation:



Deletion Code

```
- TreeNode* deleteNode(TreeNode* r, int v)
{
    1. IF (r == NULL)
        1.1. Return r;
    2. Else IF ( $v \leq r \rightarrow \text{value}$ ) // if value smaller go left
        2.1. r -> left = deleteNode(r->left, v)
    3. Else IF ( $v \geq r \rightarrow \text{value}$ ) // value larger go right
        3.1. r -> right = (deleteNode(r -> right, v))
    4. Else
        4.1. if (r -> left == NULL) // node with right child only
            4.1.1. temp = r -> right
            4.1.2. delete r
            4.1.3. return temp
        4.2. Else IF (r -> right == NULL) // node with only left child
            4.2.1 temp = r -> left
            4.2.2. delete r
            4.2.3. return temp
        4.3. Else // node has 2 children
            4.3.1 temp = minval(r -> right)
            4.3.2. r-> value = temp -> value
            4.3.3. r-> right = deleteNode(r -> right, temp ->value)
    5. num = getbalance (r)
    6. IF num == 2 and getbalance (r -> left ) >= 0 // LL - imbalance
        6.1. return rightRotate(r)
    7. Else IF (num == 2 && getbalance (r -> left) == -1) // LR - imbalance
```

No. 6, 7, 8, 9 are condition on which we perform single or double rotation.

7.1. r -> left = leftRotate(r -> left)

7.2. return rightRotate(r)

8. Else IF(num == -2 && getbalance (r -> right) <= 0) // RR imbalance

8.1. return leftRotate(r)

9. Else IF(num == -2 && getbalance (r-> right) == 1) // RL imbalance

9.1. r -> right = rightRotate(r -> right)


9.2. return leftRotate(r)

10. return r


}

Deletion:

Delete 24:





Need Rotation:





Delete 25:





Need Rotation:



Delete 20:



Delete 13:



Deleting nodes: 10, 30 like deleting node 20.
Deleting node: 15 like deleting node 13.