
Connection Oriented Transport: TCP
Transmission Control Protcol

agenda

- The **TCP** Connection
- TCP Segment **Structure**
- Round-Trip Time **Estimation** and **Timeout**
- Reliable **Data** Transfer
- **Flow** Control



Transmission Control Protocol (TCP)

Fundamental communication protocol in computer networking. It operates at the transport layer of the **OSI** model and plays a crucial role in ensuring reliable and orderly data transmission over the internet and other interconnected networks. It works hand in hand with the **Internet Protocol (IP)** to form the basis of the widely used **TCP/IP** protocol suite

Connection Oriented Protocol

(TCP)

Connection Oriented Protocol

- Connection Oriented Protocol is one that establishes and maintains a **logical** connection b/w two devices.
- This connection ensures that data is transmitted **reliably** and in the correct **order** b/w sender and receiver.

The TCP Connection

TCP IS CONNECTION-ORIENTED

APPLICATION PROCESS **"HANDSHAKE"** WITH EACH OTHER.

MUST SEND SOME **PRE-LIMINARY SEGMENTS** TO EACH OTHER

Connection Oriented Transport: TCP

- Full-Duplex Service
  - Data can flow from one process to another and vice versa simultaneously.
- Point to Point
  - The transfer of data from one sender to many receivers in a single send operation is not possible.

Establishment of connection

- Client/Server Process
  - clientSocket.connect((serverName, serverPort)) > *port identifies process on the server*
- Three Way Hand-Shake
- Connection Establishment
- Maximum Segment Size (MSS) - Largest Link Layer frame



Figure 3.28 ♦ TCP send and receive buffers

TCP Segment Structure

TCP Segment Structure

- Header field
- Data field
- Source & Destination Ports
- Checksum field(integrity)
- Sequence number field
- Acknowledgment number field



TCP Segment Structure

- Receive window field
- Header length field(32bit)
- Options field (MSS)
- Flag field(6 bits)
  - ACK, RST, SYN, FIN, PSH,URG



Establishment of connection

- Sequence number for a segment
- Acknowledgement Number



Figure 3.30 ♦ Dividing file data into TCP segments

TCP Implementation

There are basically two choices:

(1) the receiver immediately discards out-of-order segments

(2) the receiver keeps the out-of-order bytes and waits for the missing bytes to fill in the gaps

Telnet: A Case Study

- **Telnet**, popular application-layer protocol used for remote login.
- Unlike the bulk data transfer, Telnet is an interactive application.
- **Piggybacked**



Figure 3.31 ♦ Sequence and acknowledgment numbers for a simple Telnet application over TCP

Round Trip Time(RTT) and Timeout

Round Trip Time

- Amount of time between sent time and ack message time



How to set TCP timeout value.

- Longer than RTT
  - Issue: RTT varies
- Too short than RTT:
  - Unnecessary timeout,
- Too long than RTT:
  - Slow reaction to segment loss



How to measure RTT.

- **Sample RTT:** measured time from segment transmission until Ack message received
  - Ignore retransmissions
- **Estimated RTT:** average several sample RTTs, not just single RTT



Estimated RTT.

- Exponential weighted moving average(**EWMA**)
- Influence of past sample decreases exponentially fast



Figure 3.32 ♦ RTT samples and RTT estimates

Estimated RTT - cont

$$\text{EstimatedRTT} = (1 - \alpha) \cdot \text{EstimatedRTT} + \alpha \cdot \text{SampleRTT}$$

- Typical value for α is : 0.125

$$\text{EstimatedRTT} = 0.875 \cdot \text{EstimatedRTT} + 0.125 \cdot \text{SampleRTT}$$

Deviation RTT.

- Deviation of SampleRTT from EstimatedRTT



Figure 3.32 ♦ RTT samples and RTT estimates

Deviation RTT. - cont

$$DevRTT = (1 - \beta) \cdot DevRTT + \beta \cdot |SampleRTT - EstimatedRTT|$$

- The recommended value of β is 0.25.

Timeout Interval

$$TimeoutInterval = EstimatedRTT + 4 \cdot DevRTT$$

- An initial T*imeoutInterval* value of 1 second is recommended.
- When timeout occurs, value of T*imeoutInterval* is doubled to avoid premature timeout and is again updated through the formula when the acknowledge message is received



Reliable Data Transfer

- What is **Reliable Data Transfer** in TCP?
- Reason to use this?
- Three **Events** and **Actions** on it
- Three **Scenarios**

What is Reliable Data Transfer

- A Service which ensures that data received on the receiver side via TCP is...

1. Uncorrupted
2. In Sequence
3. Without Duplications
4. Without Gaps

Reason to use this

- Sending Data only To IP is Un-reliable
  - Sender is not confirmed that receiver received the data or not
  - Data that is send can be lost or Corrupted
- Acknowledges
  - A Verification from receiver side to sender side when data is received
- Re-Transmissions
  - When data is send to receiver. That data is marked as **Not-Acknowledge**
  - If the Timer out … then the **Not-Acknowledge** data is re-send to receiver

Re-Transmissions Triggered

- Sending Data only To IP is Un-reliable
  - Sender is not confirmed that receiver received the data or not
  - Data that is send can be lost or Corrupted
- Acknowledges
  - A Verification from receiver side to sender side when data is received
- Re-Transmissions
  - When data is send to receiver. That data is marked as **Not-Acknowledge**
  - If the Timer out … then the **Not-Acknowledge** data is re-send to receiver

Three Events

1

Data Received

When Sender received Data from Application

2

data received on the receiver side via TCP is...

Timer Timeout

Data send but not acknowledge

3

Acknowledge Received

Receiver send Acknowledge message to Sender

Actions on Three Events

- Data Received
  - Create Segment with Sequence Number (= NextSeqNum)
  - Send Segment (to receiver)
  - Increment NextSeqNum with data-length
  - Start Time if not running
- Timer Timeout
  - Re-transmit a Not-Yet-Acknowledge Segment
  - Start Timer
- Acknowledge Received

```
If( y > Send Base ) {
    Send Base = y
    if(Not-Yet-Acknowledge Segment Present){
       Start Timmer
    }
}
```

Three Scenarios

Retransmission due to a lost acknowledgement

- Host A send data to Host B
- Data is Send , But acknowledge is not Received in terminal
- Data again send
- Acknowledgement Received



Segment 100 not retransmitted

- Two Data Segment sends 92 and 100
- Acknowledge not received in time interval
- Smallest Not-Yet acknowledge send
- Segment 100 not send



A cumulative acknowledgement avoid retransmission of the first segment

- Segment 92 is send and Timer start
- Acknowledge not received
- Segment 100 is send within Timer
- Acknowledge 120 received
- segment 92 will not be resend



Flow Control

Flow Control

- Receiver controls sender, so sender won't overflow receiver's buffer by transmitting too much, too fast.



Flow Control

- Receiver informs free buffer space by including rwnd value in TCP header of receiver-to-sender segments
  - RcvBuffer size set via socket options(default 4096 bytes)
  - Many operating systems auto adjust RcvBuffer



receiver-side buffering

Flow Control

- Sender limits amount of unacknowledged data to receiver's rwnd value.

  LastByteSent – LastByteAck <= rwnd

- Gaurantees receive buffer will not overflow



Flow Control – handling issue

- As the sender gets blocked if the rnwd is full when, it will unblock?
- Sender keeps on sending 1 byte for acknowledgement untill it is acknowledged.



receiver-side buffering

Thank you

- Presentation by Group 6
  - **S**alman Naeem
  - **N**uman Ahmad
  - **F**arjad Waseem