

OUR COMPANY PAGE OF CONTANT

LED GOBO PROJECTOR

NEW LIGHT FOR ADVERTISING SIGNAGE AND DECORATION.

CATALOG

2P	COMPANY PROFILE
4P	LED PROJECTOR SERIES
4P	10W 20W CEILING RECESSED GOBO PROJECTOR
6P	20W STATIC / ROTATING IMAGE GOBO PROJECTOR
8P	40W 80W STATIC IMAGE GOBO PROJECTOR
10P	40W 80W TWO GOBOS PROJECTOR
12P	40W 80W ROTATING LOGO GOBO PROJECTOR
14P	WATER WAVE PROJECTOR LIGHT
16P	80W 4/6/8 IMAGES GOBO PROJECTOR
18P	200W 300W GOBO PROJECTOR
20P	200W 300W 4/6 IMAGES GOBO PROJECTOR
22P	300W SNOWFALL PROJECTOR
24P	GLASS GOBO



COMPANY PROFILE

Establised since 2012, Zhengzhou ledy optical-electrical technology Co.,Ltd is a science and technology oriented enterprise, dedicated to researching and developing, manufacturing and selling gobo projector, which is widely used in advertising, signage and decoration.

Our factory located in High-Tech zone of Zhengzhou, China. Complete production system with print, assemble, package and testing, with 6 assembly lines, 60+ employees, 20+ engineers, 10+ sales personnel, 3 quality control personnel, 3 aftersales service personnel, our annual production reach 5000+ projectors, annual sales reach USD2,000,000.

Exported to more than 72 countries all over the world, mainly North America and Europe, We got CE, RoHS, REACH and SGS for our projectors to facilitate our clients' business.

Rich experiences to provide OEM and ODM service, offer one-stop shopping and comprehensive package solutions to our clients, professional team can meet all your requirements.

Committed to high quality, Ledy is your reliable and competent partner, provide variety choices and affordable custom services for image projection solutions.

Sincerely hope to cooperate with you!

10W 20W

MAIN APPLICATION

Suitable for floor image or signage projection in exit passageway, staircase, elevator, hotel, corridor, gallery, coffee shop, private club, warehouse etc, where doesn't need to change the image.



FEATURES

- Indoor use only(Reach CE RoHs SGS Certified)
- · Ceiling recessed model, embedded mounted.
- · Compact structure with aluminium alloy shell.
- · Adjustable focus allows for crisp image projection.



















TECHNICAL PARAMETERS

10W Single image static

Model	Projector Power	Light Scurce	Luminous Flux	Projector Weight
LD-10Q	12W	CREE LED	900 - 1200LM	0.8KG
Suggested Projection Distance	Lamp Bead Power	Gobo Size OD	Color Temperature	Projector Size
0.6 - 2.2M	10W	37MM	6500K	190*90*125MM

20W Single image static/ external power supply

Model	Projector Power	Light Scurce	Luminous Flux	Projector Weight
LD-20Q	22W	CREE LED	1800 – 2000LM	0.9KG
Suggested Projection Distance	Lamp Bead Power	Gobo Size OD	Color Temperature	Projector Size
1.5 – 7.5M	20W	37MM	6500K	190*90*125MM



MAIN APPLICATION

Suitable for logo advertising and sign light, like supermarket, shop, street, coffee shop, factory, private club park, restaurant, event, exhibition, bar, square etc.

FEATURES

- Advanced Thermal Management
- · Compact structure with aluminium alloy shell
- Adjustable focus allows for crisp image projection
- 270 degree adjustable bracket for convenient projection angle
- Indoor and outdoor available (Reach CE RoHs SGS Certified)

FEATURES



TECHNICAL PARAMETERS

1				
W	A	7	١.	
4	4	u	ш	
V.		r	4	



Model	LD-40S-IP	LD-80S-IP
Projection Distance	14M	21M
Projector Power	45W	85W
Lamp Bead Power	40W	80W
Gobo Size OD	. 54MM	54MM
Light Source	. CREE LED	CREE LED
Luminous Flux	. 4200–4500LM	9000-10000LM
Color Temperature	6500K	6500K
Projector Weight	2.3KG	2.4KG
Projector Size	260*195*130MM	260*195*130MM







FEATURES

- Advanced Thermal Management
- Big glass gobo 54mm outer diameter
- Aluminum sandblasted oxidation outer shell
- Magnet gobo install system make it easier to replace
- Indoor and outdoor available (Reach CE RoHs SGS Certified)

MAIN APPLICATION

Suitable for logo advertising and sign light, like supermarket, street, coffee shop, factory, private club, park, restaurant, shop, event, exhibition, bar, square etc.

40&80W STATIC IMAGE GOBO PROJECTOR

40W 80W

FEATURES

- Advanced Thermal Management
- Magnet gobo install system make it easier to replace
- Adjustable focus allows for crisp image projection
- Indoor and outdoor available (Reach CE RoHs SGS Certified)

Model
Projection Distance
Projector Power
Lamp Bead Power
Gobo Size OD

LD-40W 14M

45W

40W

54&66MM

Luminous Flux

4200-4500LM

CREE LED

6500K

2.3KG

Projector Weight

Color Temperature

260*130*240MM WITH POWER SUPPLY BOX Projector Size

Lamp Bead Power

LD-80W 21M 85W 80W

30000H

Light Source CREE LED 9000-10000LM Luminous Flux 6500K Color Temperature 2.3KG Projector Weight 260*130*175MM



TECHNICAL PARAMETERS 4











Projector Size



EXTERNAL POWER SUPPLY







Projector Weight

Projector Size



2.3KG

260*195*130MM EXTERNAL POWER SUPPLY

40W&80W ROTATING LOGO GOBO PROJECTOR

FEATURES

12

- Big glass gobo 54mm outer diameter
- · Adjustable rotating speed: slow, normal and fast
- · Magnet gobo install system make it easier to replace
- · Indoor and outdoor available (Reach CE RoHs SGS Certified)
- Strong cooling system: internal circulating fan & external waterproof fan, make low temperature rise low light decay

TECHNICAL PARAMETERS

	40	80
Model	LD-40R-IP	LD-80R-IP
Projection Distance	14M	21M
Projector Power	45W	85W
Lamp Bead Power	40W	80W
Gobo Size OD	54MM	54MM
Light Source	CREE LED	CREE LED
Luminous Flux	4200-4500LM	9000-10000LM
Color Temperature	6500K	6500K

2.3KG

260*195*130MM EXTERNAL POWER SUPPLY

TECHNICAL PARAMETERS

40

80

Model	LD-40B	Model	LD-80B
Projection Distance	7M	Projection Distance	10M
Projector Power	45W	Projector Power	85W
Lamp Bead Power	40W	Lamp Bead Power	80W
Gobo Size OD	68MM	Gobo Size OD	68MM
Light Source	· CREE LED	Light Source	. CREE LED
Luminous Flux	4200-4500LM	Luminous Flux	9000-10000LM
Color Temperature	6500K	Color Temperature	6500K
Projector Weight	2.3KG	Projector Weight	2.4KG
Projector Size	. 260*175*130MM	Projector Size	260*175*130MN

FEATURES

- 50mm short lens
- · Glass water wave gobo color customizing
- · Water wave speed adjustable: slow, normal and fast
- Strong cooling system: internal circulating fan & external waterproof fan, make low temperature rise, low light decay



WATER WAVE PROJECTION LIGHT









TEC	Model	LD-80X4/X8	Light Source	CREE LED
ECHNICAL PARAMETERS 4	Projection Distance	30M	Luminous Flux	9000-10000LM
PAR	Projector Power	85W	Color Temperature	6500K
AMETE	Lamp Bead Power	80W	· Projector Weight	4.6KG
RS 40	Gobo Size OD	30MM	Projector Size	360*220*250MM
TEC	Model	LD-80T4/T6	Light Source	CREE LED
HNICAI	Projection Distance	32M	Luminous Flux	9000-10000LM
_ PAR/	Projector Power	85W	Color Temperature .	6500K
TECHNICAL PARAMETERS 8	Lamp Bead Power	80W	Projector Weight	6KG
RS 80	Gobo Size OD	55MM	Projector Size	360*220*250MM

FEATURES

- · Light utilization up to 90%
- 4 or 6 or 8 image gobos project in one projector
- · Hinged front cover easy to open and install gobos
- · Image project time interval can be adjusted inside projector

200W / 300W GOBO PROJECTOR

			2008		200R
-1	Model		LD-200S-IP		LD-200R-IP
m 0	Projection Effect	į	Static		Rotate
I Z	Projector Power		220W		220W
O A	Light Scurce		Osram LED	6 • 0	Osram LED
Г	Luminous Flux		14000 – 16000LM		14000 – 16000LM
P A	Voltage		110 – 240V	0.00	110 – 240V
R A	Max Projection Distance	•	Within 47M	•	Within 47M
M I	Max Image Diameter	•	28M	'n	28M
T E D	Projector Weight		6KG		6KG
S	Projector Size		374*278*194MM		374*278*194MM

Model LD-300S-IP LD-300R-IP \circ I Projection Effect Static Rotate Z Projector Power 310W 310W 0 Light Scurce Osram LED Osram LED Power Supply Meanwell Meanwell Luminoius Flux 22000 - 24000V 22000 - 24000V IJ Voltage 110 - 240V 110 - 240V Max Projection Distance Within 55M \leq Within 55M Max Image Diameter 33M 33M Projector Weight 6.5KG 6.5KG \mathbb{Z} Projector Size 395*164*263MM 395*164*263MM

FEATURES

- F70 lens
- 54mm OD glass gobo
- Large size projection image effect
- Magnet gobo install
- Easy to replace and adjust the image direction

FEATURES

- Advanced Thermal Management
- CE RoHs SGS REACH Certified
- Compact structure aluminium alloy shell IP65
- Project 4 or 6 images exchanging by turn, set time interval manually or remote control

MAIN APPLICATION

Suitable for building wall, like part, large square, exhibition hall, stadium, museum etc.

200W 300W 4/6 IMAGES GOBO PROJECTOR

TECHNICAL PARAMETERS

200


Model	LD-200X4/X6-IP
Projection Distance	37M
Projector Power	240W
Lamp Bead Power	200W
Gobo Size OD	54MM
	•
Light Source	OSRAM LED
Luminous Flux	14000–16000LM
Color Temperature	8000-9000K
Projector Weight	8.4KG
Projector Size	370*215*215MM

Model	LD-300X4/X6-IP
Projection Distance	44M
Projector Power	340W
Lamp Bead Power	300W
Gobo Size OD	. 54MM
Light Source	. OSRAM LED
Luminous Flux	22000-24000LM
Color Temperature	8000-9000K
Projector Weight	8.4KG

370*215*215MM




Projector Size



GLASS GOBO


ONE COLOR IMAGE


















TWO COLOR IMAGE

Three-Color Gobo









THREE COLOR IMAGE





FOUR OR MORE THAN FOUR COLOR IMAGE, OR NEED PRINT COLOR IMAGE



PATTERN CHIP SPECIFICATIONS

25

Model	Gobo Diameter	Max.lmage Diameter in Gobo	Application
L30	30mm	26mm	X Model
L37	30mm	26mm	10Q,20Q,20S,20R
L45	37mm	33mm	40&80S/R/W
L54	53mm	42.5mm	40&80S/R/W
L55	53mm	44mm	T Model
L62	53mm	48mm	Old ledy model
L66	53mm	42.5mm	40&80W

PATTERN COLOR

Red	Orange	Brown	Yellow	Dark green
■ Grass green	Young	Purple	Rose red	■ Black

Attention

Environment brightness and reflective level of projected object has impact on projection effect, please use our products under dark and favorable condition.