

[Dashboard](#) / [My courses](#) / [CS23333-OOPJ-2023](#) / [Lab-01-Java Architecture, Language Basics](#) / [Lab-01-Logic Building](#)

**Status** Finished

**Started** Saturday, 21 September 2024, 10:41 PM

**Completed** Saturday, 21 September 2024, 10:52 PM

**Duration** 11 mins 2 secs

Question **1**

Correct

Marked out of 5.00

Write a program to find whether the given input number is Odd.

If the given number is odd, the program should return 2 else It should return 1.

Note: The number passed to the program can either be negative, positive or zero. Zero should NOT be treated as Odd.

**For example:**

Input	Result
123	2
456	1

**Answer:** (penalty regime: 0 %)

```

1 import java.util.*;
2 class prog
3 {
4     public static void main(String args[])
5     {
6         int x;
7         Scanner inp=new Scanner(System.in);
8         x=inp.nextInt();
9         if(x%2==0)
10            System.out.println(1);
11        else
12            System.out.println(2);
13    }
14 }
```

	Input	Expected	Got	
✓	123	2	2	✓
✓	456	1	1	✓

Passed all tests! ✓

## Question 2

Correct

Marked out of 5.00

Write a program that returns the last digit of the given number. Last digit is being referred to the least significant digit i.e. the digit in the ones (units) place in the given number.

The last digit should be returned as a positive number.

For example,

if the given number is 197, the last digit is 7

if the given number is -197, the last digit is 7

**For example:**

Input	Result
197	7
-197	7

**Answer:** (penalty regime: 0 %)

```
1 import java.util.*;
2
3 class prog {
4
5     public static void main(String[] args) {
6         Scanner inp=new Scanner(System.in);
7         int x;
8         x=inp.nextInt();
9         System.out.println(Math.abs(x%10));
10    }
11 }
```

	Input	Expected	Got	
✓	197	7	7	✓
✓	-197	7	7	✓

Passed all tests! ✓

## Question 3

Correct

Marked out of 5.00

Rohit wants to add the last digits of two given numbers.

For example,

If the given numbers are 267 and 154, the output should be 11.

Below is the explanation:

Last digit of the 267 is 7

Last digit of the 154 is 4

Sum of 7 and 4 = 11

Write a program to help Rohit achieve this for any given two numbers.

Note: Tile sign of the input numbers should be ignored.

i.e.

if the input numbers are 267 and 154, the sum of last two digits should be 11

if the input numbers are 267 and -154, the sum of last two digits should be 11

if the input numbers are -267 and 154, the sum of last two digits should be 11

if the input numbers are -267 and -154, the sum of last two digits should be 11

**For example:**

Input	Result
267 154	11
267 -154	11
-267 154	11
-267 -154	11

**Answer:** (penalty regime: 0 %)

```
1 import java.util.*;
2
3 class prog {
4
5     public static void main(String[] args) {
6         Scanner inp=new Scanner(System.in);
7         int x,y;
8         x=inp.nextInt();
9         y=inp.nextInt();
10        System.out.println(Math.abs((x%10))+Math.abs((y%10)));
11    }
12 }
```

	Input	Expected	Got	
✓	267 154	11	11	✓
✓	267 -154	11	11	✓
✓	-267 154	11	11	✓
✓	-267 -154	11	11	✓

Passed all tests! ✓

◀ Lab-01-MCQ

Jump to...

Is Even? ▶

[Dashboard](#) / [My courses](#) / [CS23333-OOPUI-2023](#) / [Lab-02-Flow Control Statements](#) / [Lab-02-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Saturday, 21 September 2024, 11:05 PM
<b>Completed</b>	Saturday, 21 September 2024, 11:57 PM
<b>Duration</b>	52 mins 21 secs

## Question 1

Correct

Marked out of 5.00

Consider a sequence of the form 0, 1, 1, 2, 4, 7, 13, 24, 44, 81, 149...

Write a method program which takes as parameter an integer n and prints the nth term of the above sequence. The nth term will fit in an integer value.

Example Input:

5

Output:

4

Example Input:

8

Output:

24

Example Input:

11

Output:

149

**For example:**

Input	Result
5	4
8	24
11	149

**Answer:** (penalty regime: 0 %)

```

1 import java.util.Scanner;
2
3 public class CustomSeries {
4
5     public static int logic(int n) {
6         if (n == 1) return 0;
7         else if (n == 2 || n == 3) return 1;
8         else
9             return logic(n-1)+logic(n-2)+logic(n-3);
10    }
11
12    public static void main(String[] args) {
13        Scanner scanner = new Scanner(System.in);
14
15
16        int input = scanner.nextInt();
17
18        int result = logic(input);
19        System.out.println(result);
20    }
21 }
22

```

	Input	Expected	Got	
✓	5	4	4	✓
✓	8	24	24	✓

	Input	Expected	Got	
✓	11	149	149	✓

Passed all tests! ✓

## Question 2

Correct

Marked out of 5.00

Consider the following sequence:

1st term: 1

2nd term: 1 2 1

3rd term: 1 2 1 3 1 2 1

4th term: 1 2 1 3 1 2 1 4 1 2 1 3 1 2 1

And so on. Write a program that takes as parameter an integer n and prints the nth terms of this sequence.

Example Input:

1

Output:

1

Example Input:

4

Output:

1 2 1 3 1 2 1 4 1 2 1 3 1 2 1

For example:

Input	Result
1	1
2	1 2 1
3	1 2 1 3 1 2 1
4	1 2 1 3 1 2 1 4 1 2 1 3 1 2 1

Answer: (penalty regime: 0 %)

```

1 import java.util.*;
2
3 class prog {
4
5     public static void logic(int a)
6     {
7         if (a==0)
8             return ;
9         logic(a-1);
10        System.out.print(a+" ");
11        logic(a-1);
12    }
13    public static void main(String[] args) {
14        Scanner inp=new Scanner(System.in);
15        int n;
16        n=inp.nextInt();
17        logic(n);
18    }
19 }
```

	Input	Expected	Got	
✓	1	1	1	✓
✓	2	1 2 1	1 2 1	✓



	Input	Expected	Got	
✓	3	1 2 1 3 1 2 1	1 2 1 3 1 2 1	✓
✓	4	1 2 1 3 1 2 1 4 1 2 1 3 1 2 1	1 2 1 3 1 2 1 4 1 2 1 3 1 2 1	✓

Passed all tests! ✓

## Question 3

Correct

Marked out of 5.00

You and your friend are movie fans and want to predict if the movie is going to be a hit!

The movie's success formula depends on 2 parameters:

the acting power of the actor (range 0 to 10)

the critic's rating of the movie (range 0 to 10)

The movie is a hit if the acting power is excellent (more than 8) or the rating is excellent (more than 8). This holds true except if either the acting power is poor (less than 2) or rating is poor (less than 2), then the movie is a flop. Otherwise the movie is average.

Write a program that takes 2 integers:

the first integer is the acting power

second integer is the critic's rating.

You have to print Yes if the movie is a hit, Maybe if the movie is average and No if the movie is flop.

Example input:

9 5

Output:

Yes

Example input:

1 9

Output:

No

Example input:

6 4

Output:

Maybe

**For example:**

Input	Result
9 5	Yes
1 9	No
6 4	Maybe

**Answer:** (penalty regime: 0 %)

```
1 import java.util.*;
2
3 class prog {
4
5     public static void main(String[] args) {
6         Scanner inp=new Scanner(System.in);
7         int x,y;
8         x=inp.nextInt();
9         y=inp.nextInt();
10        if((x>=8 || y>=8)&(x>=2 && y>=2))
11            System.out.println("Yes");
12        else if(x<=2 || y<=2)
13            System.out.println("No");
14        else
15            System.out.println("Maybe");
16    }
17 }
```

	Input	Expected	Got	
✓	9 5	Yes	Yes	✓
✓	1 9	No	No	✓
✓	6 4	Maybe	Maybe	✓

Passed all tests! ✓

[◀ Lab-02-MCQ](#)

Jump to...

[Lab-03-MCQ ▶](#)

[Dashboard](#) / [My courses](#) / [CS23333-OOPUI-2023](#) / [Lab-03-Arrays](#) / [Lab-03-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Sunday, 22 September 2024, 9:34 PM
<b>Completed</b>	Sunday, 22 September 2024, 10:47 PM
<b>Duration</b>	1 hour 12 mins

## Question 1

Correct

Marked out of 5.00

Given an integer array as input, perform the following operations on the array, in the below specified sequence.

1. Find the maximum number in the array.
2. Subtract the maximum number from each element of the array.
3. Multiply the maximum number (found in step 1) to each element of the resultant array.

After the operations are done, return the resultant array.

Example 1:

input1 = 4 (represents the number of elements in the input1 array)

input2 = {1, 5, 6, 9}

Expected Output = {-72, -36, 27, 0}

Explanation:

Step 1: The maximum number in the given array is 9.

Step 2: Subtracting the maximum number 9 from each element of the array:

$\{(1 - 9), (5 - 9), (6 - 9), (9 - 9)\} = \{-8, -4, -3, 0\}$

Step 3: Multiplying the maximum number 9 to each of the resultant array:

$\{(-8 \times 9), (-4 \times 9), (3 \times 9), (0 \times 9)\} = \{-72, -36, -27, 0\}$

So, the expected output is the resultant array {-72, -36, -27, 0}.

Example 2:

input1 = 5 (represents the number of elements in the input1 array)

input2 = {10, 87, 63, 42, 2}

Expected Output = {-6699, 0, -2088, -3915, -7395}

Explanation:

Step 1: The maximum number in the given array is 87.

Step 2: Subtracting the maximum number 87 from each element of the array:

$\{(10 - 87), (87 - 87), (63 - 87), (42 - 87), (2 - 87)\} = \{-77, 0, -24, -45, -85\}$

Step 3: Multiplying the maximum number 87 to each of the resultant array:

$\{(-77 \times 87), (0 \times 87), (-24 \times 87), (-45 \times 87), (-85 \times 87)\} = \{-6699, 0, -2088, -3915, -7395\}$

So, the expected output is the resultant array {-6699, 0, -2088, -3915, -7395}.

Example 3:

input1 = 2 (represents the number of elements in the input1 array)

input2 = {-9, 9}

Expected Output = {-162, 0}

Explanation:

Step 1: The maximum number in the given array is 9.

Step 2: Subtracting the maximum number 9 from each element of the array:

$\{(-9 - 9), (9 - 9)\} = \{-18, 0\}$

Step 3: Multiplying the maximum number 9 to each of the resultant array:

$\{(-18 \times 9), (0 \times 9)\} = \{-162, 0\}$

So, the expected output is the resultant array {-162, 0}.

Note: The input array will contain not more than 100 elements

**For example:**

Input	Result
4 1 5 6 9	-72 -36 -27 0

Input	Result
5 10 87 63 42 2	-6699 0 -2088 -3915 -7395
2 -9 9	-162 0

**Answer:** (penalty regime: 0 %)

```

1 import java.util.*;
2 class prog
3 {
4     public static void main(String args[])
5     {
6         Scanner inp=new Scanner(System.in);
7         int x;
8         x=inp.nextInt();
9         int a[]=new int[x];
10        int a2[]=new int[x];
11        for(int i=0;i<x;i++)
12        {
13            a[i]=inp.nextInt();
14            a2[i]=a[i];
15        }
16        int max=-9999999;
17        for(int i: a)
18        {
19            if(i>max)
20                max=i;
21        }
22        for(int i=0;i<a2.length;i++)
23        {
24            a2[i]=(a2[i]-max)*max;
25        }
26        for(int i=0;i<a2.length;i++)
27            System.out.print(a2[i]+" ");
28    }
29 }
```

	Input	Expected	Got	
✓	4 1 5 6 9	-72 -36 -27 0	-72 -36 -27 0	✓
✓	5 10 87 63 42 2	-6699 0 -2088 -3915 -7395	-6699 0 -2088 -3915 -7395	✓
✓	2 -9 9	-162 0	-162 0	✓

Passed all tests! ✓

## Question 2

Correct

Marked out of 5.00

You are provided with a set of numbers (array of numbers).

You have to generate the sum of specific numbers based on its position in the array set provided to you.

This is explained below:

Example 1:

Let us assume the encoded set of numbers given to you is:

input1:5 and input2: {1, 51, 436, 7860, 41236}

Step 1:

Starting from the 0<sup>th</sup> index of the array pick up digits as per below:

0<sup>th</sup> index – pick up the units value of the number (in this case is 1).

1<sup>st</sup> index – pick up the tens value of the number (in this case it is 5).

2<sup>nd</sup> index – pick up the hundreds value of the number (in this case it is 4).

3<sup>rd</sup> index – pick up the thousands value of the number (in this case it is 7).

4<sup>th</sup> index – pick up the ten thousands value of the number (in this case it is 4).

(Continue this for all the elements of the input array).

The array generated from Step 1 will then be – {1, 5, 4, 7, 4}.

Step 2:

Square each number present in the array generated in Step 1.

{1, 25, 16, 49, 16}

Step 3:

Calculate the sum of all elements of the array generated in Step 2 to get the final result. The result will be = 107.

Note:

- 1) While picking up a number in Step1, if you observe that the number is smaller than the required position then use 0.
- 2) In the given function, input1[] is the array of numbers and input2 represents the number of elements in input1.

Example 2:

input1: 5 and input2: {1, 5, 423, 310, 61540}

Step 1:

Generating the new array based on position, we get the below array:

{1, 0, 4, 0, 6}

In this case, the value in input1 at index 1 and 3 is less than the value required to be picked up based on position, so we use a 0.

Step 2:

{1, 0, 16, 0, 36}

Step 3:

The final result = 53.

**For example:**

Input	Result
5 1 51 436 7860 41236	107
5 1 5 423 310 61540	53

**Answer:** (penalty regime: 0 %)

```
1 import java.util.*;
2 class prog
3 {
4     public static void main(String args[])
5     {
```

```
6      int x;
7      Scanner inp=new Scanner(System.in);
8      x=inp.nextInt();
9      int a1=0;
10     int a[]=new int[x];
11     for(int i=0;i<x;i++)
12     {
13         a[i]=inp.nextInt();
14     }
15     int aa=10;
16     for(int i=0;i<x;i++)
17     {
18         a1=a1+((a[i]%aa)/(aa/10)*((a[i]%aa)/(aa/10)));
19         aa=aa*10;
20     }
21     System.out.print(a1);
22 }
23 }
```

	Input	Expected	Got	
✓	5 1 51 436 7860 41236	107	107	✓
✓	5 1 5 423 310 61540	53	53	✓

Passed all tests! ✓



## Question 3

Correct

Marked out of 5.00

Given an array of numbers, you are expected to return the sum of the longest sequence of POSITIVE numbers in the array.

If there are NO positive numbers in the array, you are expected to return -1.

In this question's scope, the number 0 should be considered as positive.

Note: If there are more than one group of elements in the array having the longest sequence of POSITIVE numbers, you are expected to return the total sum of all those POSITIVE numbers (see example 3 below).

input1 represents the number of elements in the array.

input2 represents the array of integers.

Example 1:

input1 = 16

input2 = {-12, -16, 12, 18, 18, 14, -4, -12, -13, 32, 34, -5, 66, 78, 78, -79}

Expected output = 62

Explanation:

The input array contains four sequences of POSITIVE numbers, i.e. "12, 18, 18, 14", "12", "32, 34", and "66, 78, 78". The first sequence "12, 18, 18, 14" is the longest of the four as it contains 4 elements. Therefore, the expected output = sum of the longest sequence of POSITIVE numbers = 12 + 18 + 18 + 14 = 63.

Example 2:

input1 = 11

input2 = {-22, -24, 16, -1, -17, -19, -37, -25, -19, -93, -61}

Expected output = -1

Explanation:

There are NO positive numbers in the input array. Therefore, the expected output for such cases = -1.

Example 3:

input1 = 16

input2 = {-58, 32, 26, 92, -10, -4, 12, 0, 12, -2, 4, 32, -9, -7, 78, -79}

Expected output = 174

Explanation:

The input array contains four sequences of POSITIVE numbers, i.e. "32, 26, 92", "12, 0, 12", "4, 32", and "78". The first and second sequences "32, 26, 92" and "12, 0, 12" are the longest of the four as they contain 4 elements each. Therefore, the expected output = sum of the longest sequence of POSITIVE numbers = (32 + 26 + 92) + (12 + 0 + 12) = 174.

**For example:**

Input	Result
16 -12 -16 12 18 18 14 -4 -12 -13 32 34 -5 66 78 78 -79	62
11 -22 -24 -16 -1 -17 -19 -37 -25 -19 -93 -61	-1
16 -58 32 26 92 -10 -4 12 0 12 -2 4 32 -9 -7 78 -79	174

**Answer:** (penalty regime: 0 %)

```

1 import java.util.*;
2 public class prog {
3
4     public static int logic(int[] inputArray) {
5         int maxSum = -1;
6         int currentSum = 0;
7         int maxLength = 0;
8         int currentLength = 0;
9

```

```

10  ▼   for (int num : inputArray) {
11  ▼       if (num >= 0) {
12  ▼           currentSum += num;
13  ▼           currentLength++;
14  ▼       } else {
15  ▼
16  ▼           if (currentLength > maxLength) {
17  ▼               maxLength = currentLength;
18  ▼               maxSum = currentSum;
19  ▼           } else if (currentLength == maxLength) {
20  ▼               maxSum += currentSum;
21  ▼           }
22  ▼           currentSum = 0;
23  ▼           currentLength = 0;
24  ▼       }
25  ▼   }
26  ▼
27  ▼   if (currentLength > maxLength) {
28  ▼       maxSum = currentSum;
29  ▼   } else if (currentLength == maxLength && currentLength > 0) {
30  ▼       maxSum += currentSum;
31  ▼   }
32  ▼
33  ▼   return maxLength > 0 ? maxSum : -1;
34  ▼ }
35  ▼
36  ▼ public static void main(String[] args) {
37  ▼
38  ▼     Scanner inp=new Scanner(System.in);
39  ▼     int x;
40  ▼     x=inp.nextInt();
41  ▼     int a[]=new int[x];
42  ▼     for(int i=0;i<x;i++)
43  ▼     {
44  ▼         a[i]=inp.nextInt();
45  ▼     }
46  ▼     System.out.println(logic(a));
47  ▼ }
48  ▼ }
49  ▼

```

	Input	Expected	Got	
✓	16 -12 -16 12 18 18 14 -4 -12 -13 32 34 -5 66 78 78 -79	62	62	✓
✓	11 -22 -24 -16 -1 -17 -19 -37 -25 -19 -93 -61	-1	-1	✓
✓	16 -58 32 26 92 -10 -4 12 0 12 -2 4 32 -9 -7 78 -79	174	174	✓

Passed all tests! ✓

◀ Lab-03-MCQ

Jump to...

[Simple Encoded Array ▶](#)

[Dashboard](#) / [My courses](#) / [CS23333-OOPUI-2023](#) / [Lab-04-Classes and Objects](#) / [Lab-04-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Saturday, 21 September 2024, 11:58 PM
<b>Completed</b>	Sunday, 22 September 2024, 12:47 AM
<b>Duration</b>	48 mins 57 secs

## Question 1

Correct

Marked out of 5.00

Create a Class Mobile with the attributes listed below,

```
private String manufacturer;
private String operating_system;
public String color;
private int cost;
```

Define a Parameterized constructor to initialize the above instance variables.

Define getter and setter methods for the attributes above.

for example : setter method for manufacturer is

```
void setManufacturer(String manufacturer){
    this.manufacturer= manufacturer;
}
```

```
String getManufacturer(){
    return manufacturer;}

```

Display the object details by overriding the toString() method.

**For example:**

Test	Result
1	manufacturer = Redmi operating_system = Andriod color = Blue cost = 34000

**Answer:** (penalty regime: 0 %)

```

1  class mobile
2  {
3      int c;
4      String manu,Os,Col;
5      mobile(String mn,String os,String color,int cost)
6      {
7          manu=mn;
8          Os=os;
9          Col=color;
10         c=cost;
11     }
12     public String toString()
13     {
14         return "manufacturer = "+manu+"\noperating_system = "+Os+"\ncolor = "+Col+"\ncost = "+c;
15     }
16 }
17 class prog{
18     public static void main(String arg[])
19     {
20         mobile m=new mobile("Redmi","Andriod","Blue",34000);
21         System.out.println(m.toString());
22     }
23 }
```

	Test	Expected	Got	
✓	1	manufacturer = Redmi operating_system = Andriod color = Blue cost = 34000	manufacturer = Redmi operating_system = Andriod color = Blue cost = 34000	✓

Passed all tests! ✓

## Question 2

Correct

Marked out of 5.00

Create a class called "Circle" with a radius attribute. You can access and modify this attribute using getter and setter methods. Calculate the area and circumference of the circle.

**Area of Circle =  $\pi r^2$**

**Circumference =  $2\pi r$**

**Input:**

2

**Output:**

**Area = 12.57**

**Circumference = 12.57**

**For example:**

Test	Input	Result
1	4	Area = 50.27 Circumference = 25.13

**Answer:** (penalty regime: 0 %)

Reset answer

```

1 import java.util.*;
2 class Circle
3 {
4     private double radius;
5     public Circle(double r){
6         radius=r;
7
8
9     }
10    public void setRadius(double r){
11
12    }
13    public double getRadius()    {
14        return radius;
15
16    }
17    public double calculateArea() { // complete the below statement
18        return Math.PI*radius*radius;
19
20    }
21    public double calculateCircumference()    {
22        return Math.PI*2*radius;
23    }
24 }
25 class prog{
26     public static void main(String[] args) {
27         int r;
28         Scanner sc= new Scanner(System.in);
29         r=sc.nextInt();
30         Circle c= new Circle(r);
31         System.out.println("Area = "+String.format("%.2f", c.calculateArea()));
32         System.out.println("Circumference = "+String.format("%.2f",c.calculateCircumference()));
33     }
34 }
35

```

	Test	Input	Expected	Got	
✓	1	4	Area = 50.27 Circumference = 25.13	Area = 50.27 Circumference = 25.13	✓

	Test	Input	Expected	Got	
✓	2	6	Area = 113.10 Circumference = 37.70	Area = 113.10 Circumference = 37.70	✓
✓	3	2	Area = 12.57 Circumference = 12.57	Area = 12.57 Circumference = 12.57	✓

Passed all tests! ✓

## Question 3

Correct

Marked out of 5.00

Create a class Student with two private attributes, name and roll number. Create three objects by invoking different constructors available in the class Student.

Student()

Student(String name)

Student(String name, int rollno)

**Input:**

No input

**Output:**

No-arg constructor is invoked

1 arg constructor is invoked

2 arg constructor is invoked

Name =null , Roll no = 0

Name =Rajalakshmi , Roll no = 0

Name =Lakshmi , Roll no = 101

For example:

Test	Result
1	No-arg constructor is invoked 1 arg constructor is invoked 2 arg constructor is invoked Name =null , Roll no = 0 Name =Rajalakshmi , Roll no = 0 Name =Lakshmi , Roll no = 101

**Answer:** (penalty regime: 0 %)

```

1 class stu
2 {
3     String name;
4     int roll;
5     stu()
6     {
7         System.out.println("No-arg constructor is invoked");
8         name="null";
9         roll=0;
10    }
11    stu(String n)
12    {
13        name=n;
14        roll=0;
15        System.out.println("1 arg constructor is invoked");
16    }
17    stu(String n,int r)
18    {
19        name=n;
20        roll=r;
21        System.out.println("2 arg constructor is invoked");
22    }
23    void display()
24    {
25        System.out.println("Name =" +name+ " , "+" Roll no = "+roll);
26    }
27 }
28 class prog {
29
30     public static void main(String[] args) {
31         stu s1=new stu();
32         stu s2=new stu("Rajalakshmi");
33         stu s3=new stu("Lakshmi",101);
34         s1.display();
35         s2.display();
36         s3.display();
37     }
38 }

```

	Test	Expected	Got	
✓	1	No-arg constructor is invoked 1 arg constructor is invoked 2 arg constructor is invoked Name =null , Roll no = 0 Name =Rajalakshmi , Roll no = 0 Name =Lakshmi , Roll no = 101	No-arg constructor is invoked 1 arg constructor is invoked 2 arg constructor is invoked Name =null , Roll no = 0 Name =Rajalakshmi , Roll no = 0 Name =Lakshmi , Roll no = 101	✓

Passed all tests! ✓

◀ Lab-04-MCQ

Jump to...

Number of Primes in a specified range ▶

⚡



[Dashboard](#) / [My courses](#) / [CS23333-OOPUI-2023](#) / [Lab-05-Inheritance](#) / [Lab-05-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Monday, 30 September 2024, 9:19 PM
<b>Completed</b>	Monday, 30 September 2024, 10:15 PM
<b>Duration</b>	55 mins 42 secs

## Question 1

Correct

Marked out of 5.00

Create a class known as "BankAccount" with methods called deposit() and withdraw().

Create a subclass called SavingsAccount that overrides the withdraw() method to prevent withdrawals if the account balance falls below one hundred.

**For example:**

**Result**

```
Create a Bank Account object (A/c No. BA1234) with initial balance of $500:
Deposit $1000 into account BA1234:
New balance after depositing $1000: $1500.0
Withdraw $600 from account BA1234:
New balance after withdrawing $600: $900.0
Create a SavingsAccount object (A/c No. SA1000) with initial balance of $300:
Try to withdraw $250 from SA1000!
Minimum balance of $100 required!
Balance after trying to withdraw $250: $300.0
```

**Answer:** (penalty regime: 0 %)

Reset answer

```
1 class BankAccount {
2     private String accountNumber;
3
4     private double balance;
5
6     BankAccount(String acno, double bal)
7     {
8         accountNumber=acno;
9         balance=bal;
10    }
11    public void deposit(double amount) {
12        balance=balance+amount;
13    }
14
15    public void withdraw(double amount) {
16        if (balance >= amount) {
17            balance -= amount;
18        } else {
19            System.out.println("Insufficient balance");
20        }
21    }
22
23    public double getBalance() {
24        return balance;
25    }
26 }
27
28
29 class SavingsAccount extends BankAccount {
30     // Constructor to initialize account number and balance
31     public SavingsAccount(String accountNumber, double balance) {
32         super(accountNumber, balance);
33     }
34
35
36
37     @Override
38     public void withdraw(double amount) {
39         if (getBalance() - amount < 100) {
40             System.out.println("Minimum balance of $100 required!");
41         } else {
42             super.withdraw(amount);
43         }
44     }
45 }
46
47 class prog {
48
49     public static void main(String[] args) {
50         System.out.println("Create a Bank Account object (A/c No. BA1234) with initial balance of $500:");
51         BankAccount BA1234 = new BankAccount("BA1234", 500);
52         System.out.println("Deposit $1000 into account BA1234:");
```

	Expected	Got	
✓	<p>Create a Bank Account object (A/c No. BA1234) with initial balance of \$500:</p> <p>Deposit \$1000 into account BA1234:</p> <p>New balance after depositing \$1000: \$1500.0</p> <p>Withdraw \$600 from account BA1234:</p> <p>New balance after withdrawing \$600: \$900.0</p> <p>Create a SavingsAccount object (A/c No. SA1000) with initial balance of \$300:</p> <p>Try to withdraw \$250 from SA1000!</p> <p>Minimum balance of \$100 required!</p> <p>Balance after trying to withdraw \$250: \$300.0</p>	<p>Create a Bank Account object (A/c No. BA1234) with initial balance of \$500:</p> <p>Deposit \$1000 into account BA1234:</p> <p>New balance after depositing \$1000: \$1500.0</p> <p>Withdraw \$600 from account BA1234:</p> <p>New balance after withdrawing \$600: \$900.0</p> <p>Create a SavingsAccount object (A/c No. SA1000) with initial balance of \$300:</p> <p>Try to withdraw \$250 from SA1000!</p> <p>Minimum balance of \$100 required!</p> <p>Balance after trying to withdraw \$250: \$300.0</p>	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of 5.00

Create a class `Mobile` with constructor and a method `basicMobile()`.

Create a subclass `CameraMobile` which extends `Mobile` class, with constructor and a method `newFeature()`.

Create a subclass `AndroidMobile` which extends `CameraMobile`, with constructor and a method `androidMobile()`.

display the details of the Android Mobile class by creating the instance.

```
class Mobile{  
  
}  
class CameraMobile extends Mobile {  
  
}  
class AndroidMobile extends CameraMobile {  
  
}
```

expected output:

```
Basic Mobile is Manufactured  
Camera Mobile is Manufactured  
Android Mobile is Manufactured  
Camera Mobile with 5MG px  
Touch Screen Mobile is Manufactured
```

**For example:**

**Result**

```
Basic Mobile is Manufactured  
Camera Mobile is Manufactured  
Android Mobile is Manufactured  
Camera Mobile with 5MG px  
Touch Screen Mobile is Manufactured
```

**Answer:** (penalty regime: 0 %)

```
1 class Mobile  
2 {  
3     void feat()  
4     {  
5         System.out.println("Basic Mobile is Manufactured");  
6     }  
7 }  
8 class cmob extends Mobile  
9 {  
10    void feat()  
11    {  
12        System.out.println("Camera Mobile is Manufactured");  
13    }  
14 }  
15 class amob extends cmob  
16 {  
17    void feat()  
18    {  
19        System.out.println("Android Mobile is Manufactured");  
20        System.out.println("Camera Mobile with 5MG px");  
21        System.out.println("Touch Screen Mobile is Manufactured");  
22    }  
23 }  
24 public class prog  
25 {  
26     public static void main(String args[])  
27     {  
28         Mobile a=new Mobile();  
29         cmob b=new cmob();  
30         amob c=new amob();  
31         a.feat();  
32         b.feat();  
33         c.feat();  
34     }  
35 }
```

	Expected	Got	
✓	Basic Mobile is Manufactured Camera Mobile is Manufactured Android Mobile is Manufactured Camera Mobile with 5MG px Touch Screen Mobile is Manufactured	Basic Mobile is Manufactured Camera Mobile is Manufactured Android Mobile is Manufactured Camera Mobile with 5MG px Touch Screen Mobile is Manufactured	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of 5.00

create a class called College with attribute String name, constructor to initialize the name attribute , a method called Admitted(). Create a subclass called CSE that extends Student class, with department attribute , Course() method to sub class. Print the details of the Student.

College:

String collegeName;

public College() {}

public admitted() {}

Student:

String studentName;

String department;

public Student(String collegeName, String studentName,String depart) {}

public toString()

Expected Output:

A student admitted in REC

CollegeName : REC

StudentName : Venkatesh

Department : CSE

**For example:**

Result
A student admitted in REC CollegeName : REC StudentName : Venkatesh Department : CSE

**Answer:** (penalty regime: 0 %)

Reset answer

```
1 class College
2 {
3     protected String collegeName;
4
5     public College(String collegeName) {
6         this.collegeName=collegeName;
7     }
8
9
10    public void admitted() {
11        System.out.println("A student admitted in "+collegeName);
12    }
13 }
14 class Student extends College{
15
16     String studentName;
17     String department;
18
19     public Student(String collegeName, String studentName,String depart) {
20         super(collegeName);
21         this.studentName=studentName;
22         this.department=depart;
23     }
24
25     public String toString(){
26         admitted();
27         return "CollegeName : "+collegeName+"\nStudentName : "+studentName+"\nDepartment : "+department;
28     };
29 }
30 class prog {
31     public static void main (String[] args) {
32         Student s1 = new Student("REC","Venkatesh","CSE");
33         // invoke the admitted() method
34         System.out.println(s1.toString());
35     }
36 }
```

	Expected	Got	
✓	A student admitted in REC CollegeName : REC StudentName : Venkatesh Department : CSE	A student admitted in REC CollegeName : REC StudentName : Venkatesh Department : CSE	✓

Passed all tests! ✓

[◀ Lab-05-MCQ](#)

Jump to...

[Is Palindrome Number? ▶](#)

[Dashboard](#) / [My courses](#) / [CS23333-OOPUI-2023](#) / [Lab-06-String,StringBuffer](#) / [Lab-06-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Sunday, 6 October 2024, 9:09 PM
<b>Completed</b>	Sunday, 6 October 2024, 9:29 PM
<b>Duration</b>	20 mins 3 secs



## Question 1

Correct

Marked out of 5.00

Given a String input1, which contains many number of words separated by : and each word contains exactly two lower case alphabets, generate an output based upon the below 2 cases.

Note:

1. All the characters in input 1 are lowercase alphabets.
2. input 1 will always contain more than one word separated by :
3. Output should be returned in uppercase.

Case 1:

Check whether the two alphabets are same.

If yes, then take one alphabet from it and add it to the output.

Example 1:

input1 = ww:ii:pp:rr:oo

output = WIPRO

Explanation:

word1 is ww, both are same hence take w

word2 is ii, both are same hence take i

word3 is pp, both are same hence take p

word4 is rr, both are same hence take r

word5 is oo, both are same hence take o

Hence the output is WIPRO

Case 2:

If the two alphabets are not same, then find the position value of them and find maximum value – minimum value.

Take the alphabet which comes at this (maximum value - minimum value) position in the alphabet series.

Example 2"

input1 = zx:za:ee

output = BYE

Explanation

word1 is zx, both are not same alphabets

position value of z is 26

position value of x is 24

max – min will be  $26 - 24 = 2$

Alphabet which comes in 2<sup>nd</sup> position is b

Word2 is za, both are not same alphabets

position value of z is 26

position value of a is 1

max – min will be  $26 - 1 = 25$

Alphabet which comes in 25<sup>th</sup> position is y

word3 is ee, both are same hence take e

Hence the output is BYE

**For example:**

Input	Result
ww:ii:pp:rr:oo	WIPRO
zx:za:ee	BYE

**Answer:** (penalty regime: 0 %)

```

1 import java.util.Scanner;
2
3 public class prog {
4     public static char findChar(char ch1, char ch2) {
5         if (ch1 == ch2) {
6             return ch1;
7         } else {
8             int max = Math.max(ch1 - 'a' + 1, ch2 - 'a' + 1);
9             int min = Math.min(ch1 - 'a' + 1, ch2 - 'a' + 1);
10            int pos = max - min;
11            return (char) ('a' + pos - 1);
12        }
13    }
14
15    public static String processString(String str) {
16        String[] pairs = str.split(":");
17        StringBuilder result = new StringBuilder();
18
19        for (String pair : pairs) {
20            char ch1 = pair.charAt(0);
21            char ch2 = pair.charAt(1);
22            result.append(findChar(ch1, ch2));
23        }
24
25        return result.toString().toUpperCase();
26    }
27
28    public static void main(String[] args) {
29        Scanner scanner = new Scanner(System.in);
30        String input = scanner.nextLine();
31
32        String result = processString(input);
33        System.out.println( result);
34    }
35 }
36

```

	Input	Expected	Got	
✓	ww:ii:pp:rr:oo	WIPRO	WIPRO	✓
✓	zx:za:ee	BYE	BYE	✓

Passed all tests! ✓

## Question 2

Correct

Marked out of 5.00

Given 2 strings input1 & input2.

- Concatenate both the strings.
- Remove duplicate alphabets & white spaces.
- Arrange the alphabets in descending order.

Assumption 1:

There will either be alphabets, white spaces or null in both the inputs.

Assumption 2:

Both inputs will be in lower case.

Example 1:

Input 1: apple

Input 2: orange

Output: rponlgea

Example 2:

Input 1: fruits

Input 2: are good

Output: utsroigfeda

Example 3:

Input 1: ""

Input 2: ""

Output: null

**For example:**

Test	Input	Result
1	apple orange	rponlgea
2	fruits are good	utsroigfeda

**Answer:** (penalty regime: 0 %)

```

1
2 import java.util.*;
3 class prog {
4
5     public static String logic(String input1, String input2) {
6         String concatenated = input1 + input2;
7
8         char[] chars = concatenated.toCharArray();
9         StringBuilder uniqueChars = new StringBuilder();
10
11         for (char ch : chars) {
12             if (ch != ' ' && uniqueChars.indexOf(String.valueOf(ch)) == -1) {
13                 uniqueChars.append(ch);
14             }
15         }
16
17         char[] sortedChars = uniqueChars.toString().toCharArray();
18         Arrays.sort(sortedChars);
19
20         StringBuilder result = new StringBuilder(new String(sortedChars)).reverse();
21
22         return result.length() > 0 ? result.toString() : "null";
23     }
24
25     public static void main(String[] args) {
26         Scanner scanner = new Scanner(System.in);
27

```

```

28     String input1 = scanner.nextLine();
29
30     String input2 = scanner.nextLine();
31
32     String result = logic(input1, input2);
33     System.out.println( result);
34
35     scanner.close();
36 }
37 }
38

```

	Test	Input	Expected	Got	
✓	1	apple orange	rponlgea	rponlgea	✓
✓	2	fruits are good	utsroigfeda	utsroigfeda	✓
✓	3		null	null	✓

Passed all tests! ✓

16

## Question 3

Correct

Marked out of 5.00

You are provided a string of words and a 2-digit number. The two digits of the number represent the two words that are to be processed.

For example:

If the string is "Today is a Nice Day" and the 2-digit number is 41, then you are expected to process the 4th word ("Nice") and the 1st word ("Today").

The processing of each word is to be done as follows:

Extract the Middle-to-Begin part: Starting from the middle of the word, extract the characters till the beginning of the word.

Extract the Middle-to-End part: Starting from the middle of the word, extract the characters till the end of the word.

If the word to be processed is "Nice":

Its Middle-to-Begin part will be "iN".

Its Middle-to-End part will be "ce".

So, merged together these two parts would form "iNce".

Similarly, if the word to be processed is "Today":

Its Middle-to-Begin part will be "doT".

Its Middle-to-End part will be "day".

So, merged together these two parts would form "doTday".

Note: Note that the middle letter 'd' is part of both the extracted parts. So, for words whose length is odd, the middle letter should be included in both the extracted parts.

Expected output:

The expected output is a string containing both the processed words separated by a space "iNce doTday"

Example 1:

input1 = "Today is a Nice Day"

input2 = 41

output = "iNce doTday"

Example 2:

input1 = "Fruits like Mango and Apple are common but Grapes are rare"

input2 = 39

output = "naMngo arGpes"

Note: The input string input1 will contain only alphabets and a single space character separating each word in the string.

Note: The input string input1 will NOT contain any other special characters.

Note: The input number input2 will always be a 2-digit number ( $\geq 11$  and  $\leq 99$ ). One of its digits will never be 0. Both the digits of the number will always point to a valid word in the input1 string.

**For example:**

Input	Result
Today is a Nice Day 41	iNce doTday
Fruits like Mango and Apple are common but Grapes are rare 39	naMngo arGpes

**Answer:** (penalty regime: 0 %)

```
1 import java.util.Scanner;
2
3 public class WordProcessor {
4     public static void main(String[] args) {
5         Scanner sc = new Scanner(System.in);
6
7         String input = sc.nextLine();
8
9         int number = sc.nextInt();
10    }
```

```

11     String[] words = input.split(" ");
12
13     int pos1 = number / 10;
14     int pos2 = number % 10;
15     pos1--;
16     pos2--;
17
18     String result1 = processWord(words[pos1]);
19     String result2 = processWord(words[pos2]);
20
21     String result = result1 + " " + result2;
22     System.out.println(result);
23 }
24
25 public static String processWord(String word) {
26     int len = word.length();
27     int mid = len / 2;
28
29     String middleToBegin;
30     String middleToEnd;
31
32     if (len % 2 == 0) {
33         middleToBegin = new StringBuilder(word.substring(0, mid)).reverse().toString();
34         middleToEnd = word.substring(mid);
35     } else {
36         middleToBegin = new StringBuilder(word.substring(0, mid + 1)).reverse().toString();
37         middleToEnd = word.substring(mid);
38     }
39     return middleToBegin + middleToEnd;
40 }
41 }
42

```

	Input	Expected	Got	
✓	Today is a Nice Day 41	iNce doTday	iNce doTday	✓
✓	Fruits like Mango and Apple are common but Grapes are rare 39	naMngo arGpes	naMngo arGpes	✓

Passed all tests! ✓

◀ Lab-06-MCQ

Jump to...

[Return second word in Uppercase ▶](#)

[Dashboard](#) / [My courses](#) / [CS23333-OOPJ-2023](#) / [Lab-07-Interfaces](#) / [Lab-07-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Sunday, 6 October 2024, 9:30 PM
<b>Completed</b>	Sunday, 6 October 2024, 9:56 PM
<b>Duration</b>	26 mins 6 secs

## Question 1

Correct

Marked out of 5.00

RBI issues all national banks to collect interest on all customer loans.

Create an RBI interface with a variable String parentBank="RBI" and abstract method rateOfInterest().

RBI interface has two more methods default and static method.

default void policyNote() {

System.out.println("RBI has a new Policy issued in 2023.");

}

static void regulations(){

System.out.println("RBI has updated new regulations on 2024.");

}

Create two subclasses SBI and Karur which implements the RBI interface.

Provide the necessary code for the abstract method in two sub-classes.

### Sample Input/Output:

**RBI has a new Policy issued in 2023**

**RBI has updated new regulations in 2024.**

**SBI rate of interest: 7.6 per annum.**

**Karur rate of interest: 7.4 per annum.**

For example:

Test	Result
1	RBI has a new Policy issued in 2023 RBI has updated new regulations in 2024. SBI rate of interest: 7.6 per annum. Karur rate of interest: 7.4 per annum.

Answer: (penalty regime: 0 %)

```

1 interface RBI {
2     String parentBank = "RBI";
3     double rateOfInterest();
4     default void policyNote() {
5         System.out.println("RBI has a new Policy issued in 2023");
6     }
7
8     static void regulations() {
9         System.out.println("RBI has updated new regulations in 2024.");
10    }
11 }
12
13 class SBI implements RBI {
14     public double rateOfInterest() {
15         return 7.6;
16     }
17 }
18
19 class Karur implements RBI {
20     public double rateOfInterest() {
21         return 7.4;
22     }
23 }
24
25 public class Main {
26     public static void main(String[] args) {
27         RBI rbi = new SBI();
28         rbi.policyNote();
29         RBI.regulations();
30
31         SBI sbi = new SBI();
32         System.out.println("SBI rate of interest: " + sbi.rateOfInterest() + " per annum.");
33
34         Karur karur = new Karur();
35         System.out.println("Karur rate of interest: " + karur.rateOfInterest() + " per annum.");
36     }
37 }
38

```



	Test	Expected	Got	
✓	1	RBI has a new Policy issued in 2023 RBI has updated new regulations in 2024. SBI rate of interest: 7.6 per annum. Karur rate of interest: 7.4 per annum.	RBI has a new Policy issued in 2023 RBI has updated new regulations in 2024. SBI rate of interest: 7.6 per annum. Karur rate of interest: 7.4 per annum.	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of 5.00

Create interfaces shown below.

```
interface Sports {
    public void setHomeTeam(String name);
    public void setVisitingTeam(String name);
}
```

```
interface Football extends Sports {
    public void homeTeamScored(int points);
    public void visitingTeamScored(int points);
}
```

create a class College that implements the Football interface and provides the necessary functionality to the abstract methods.

sample Input:

Rajalakshmi  
Saveetha  
22  
21

Output:

Rajalakshmi 22 scored  
Saveetha 21 scored  
Rajalakshmi is the Winner!

**For example:**

Test	Input	Result
1	Rajalakshmi Saveetha 22 21	Rajalakshmi 22 scored Saveetha 21 scored Rajalakshmi is the winner!

**Answer:** (penalty regime: 0 %)

Reset answer

```
1 import java.util.Scanner;
2 interface Sports {
3     public void setHomeTeam(String name);
4     public void setVisitingTeam(String name);
5 }
6
7 interface Football extends Sports {
8     public void homeTeamScored(int points);
9     public void visitingTeamScored(int points);
10 }
11
12 class College implements Football {
13     String homeTeam;
14     String visitingTeam;
15
16     public void setHomeTeam(String name){
17         this.homeTeam=name;
18     }
19
20     public void setVisitingTeam(String name){
21         this.visitingTeam=name;
22     }
23
24     public void homeTeamScored(int points){
25         System.out.println(homeTeam+" "+points+" scored");
26     }
27     public void visitingTeamScored(int points){
28         System.out.println(visitingTeam+" "+points+" scored");
29     }
30     public void winningTeam(int p1, int p2){
31         if(p1>p2)
32             System.out.println(homeTeam+" is the winner!");
33         else if(p1<p2)
34             System.out.println(visitingTeam+" is the winner!");
35         else
36             System.out.println("It's a tie match.");
37     }
38 }
39
40 class prog{
41     public static void main(String[] args){
```

```

42     Scanner sc= new Scanner(System.in);
43     String hname=sc.next();
44     String vteam=sc.next();
45     int htpoints=sc.nextInt();
46     int vtpoints=sc.nextInt();
47     College s= new College();
48     s.setHomeTeam(hname);
49     s.setVisitingTeam(vteam);
50     s.homeTeamScored(htpoints);
51     s.visitingTeamScored(vtpoints);
52     s.winningTeam(htpoints,vtpoints);

```

	Test	Input	Expected	Got	
✓	1	Rajalakshmi Saveetha 22 21	Rajalakshmi 22 scored Saveetha 21 scored Rajalakshmi is the winner!	Rajalakshmi 22 scored Saveetha 21 scored Rajalakshmi is the winner!	✓
✓	2	Anna Balaji 21 21	Anna 21 scored Balaji 21 scored It's a tie match.	Anna 21 scored Balaji 21 scored It's a tie match.	✓
✓	3	SRM VIT 20 21	SRM 20 scored VIT 21 scored VIT is the winner!	SRM 20 scored VIT 21 scored VIT is the winner!	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of 5.00

create an interface Playable with a method play() that takes no arguments and returns void. Create three classes Football, Volleyball, and Basketball that implement the Playable interface and override the play() method to play the respective sports.

```
interface Playable {
    void play();
}

class Football implements Playable {
    String name;
    public Football(String name){
        this.name=name;
    }
    public void play() {
        System.out.println(name+" is Playing football");
    }
}
```

Similarly, create Volleyball and Basketball classes.

**Sample output:**

```
Sadhvin is Playing football
Sanjay is Playing volleyball
Sruthi is Playing basketball
```

**For example:**

Test	Input	Result
1	Sadhvin Sanjay Sruthi	Sadhvin is Playing football Sanjay is Playing volleyball Sruthi is Playing basketball
2	Vijay Arun Balaji	Vijay is Playing football Arun is Playing volleyball Balaji is Playing basketball

**Answer:** (penalty regime: 0 %)

```
1 import java.util.*;
2 interface playable
3 {
4     void play();
5 }
6 class foot implements playable
7 {
8     String name;
9     public foot(String n)
10    {
11        this.name=n;
12    }
13    public void play()
14    {
15        System.out.println(name+" is Playing football");
16    }
17 }
18 class volley implements playable
19 {
20     String name;
21     public volley(String n)
22    {
23        this.name=n;
24    }
25    public void play()
26    {
27        System.out.println(name+" is Playing volleyball");
28    }
29 }
30 class bas implements playable
31 {
32     String name;
33     bas(String n)
34    {
35        this.name=n;
36    }
37    public void play()
38    {
39        System.out.println(name+" is Playing basketball");
```

```

40     }
41 }
42 public class prog
43 {
44     public static void main(String args[])
45     {
46         Scanner inp=new Scanner(System.in);
47         foot f=new foot(inp.next());
48         volley v=new volley(inp.next());
49         bas b=new bas(inp.next());
50         f.play();
51         v.play();
52         b.play();

```

	Test	Input	Expected	Got	
✓	1	Sadhvin Sanjay Sruthi	Sadhvin is Playing football Sanjay is Playing volleyball Sruthi is Playing basketball	Sadhvin is Playing football Sanjay is Playing volleyball Sruthi is Playing basketball	✓
✓	2	Vijay Arun Balaji	Vijay is Playing football Arun is Playing volleyball Balaji is Playing basketball	Vijay is Playing football Arun is Playing volleyball Balaji is Playing basketball	✓

Passed all tests! ✓

[◀ Lab-07-MCQ](#)

Jump to...

[Generate series and find Nth element ▶](#)

[Dashboard](#) / [My courses](#) / [CS23333-OOPJ-2023](#) / [Lab-08 - Polymorphism, Abstract Classes, final Keyword](#) / [Lab-08-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Wednesday, 23 October 2024, 12:00 PM
<b>Completed</b>	Wednesday, 23 October 2024, 12:17 PM
<b>Duration</b>	17 mins 13 secs

## Question 1

Correct

Marked out of 5.00

As a logic building learner you are given the task to extract the string which has vowel as the first and last characters from the given array of Strings.

Step1: Scan through the array of Strings, extract the Strings with first and last characters as vowels; these strings should be concatenated.

Step2: Convert the concatenated string to lowercase and return it.

If none of the strings in the array has first and last character as vowel, then return no matches found

input1: an integer representing the number of elements in the array.

input2: String array.

Example 1:

input1: 3

input2: {"oreo", "sirish", "apple"}

output: oreoapple

Example 2:

input1: 2

input2: {"Mango", "banana"}

output: no matches found

Explanation:

None of the strings has first and last character as vowel.

Hence the output is no matches found.

Example 3:

input1: 3

input2: {"Ate", "Ace", "Girl"}

output: ateace

**For example:**

Input	Result
3 oreo sirish apple	oreoapple
2 Mango banana	no matches found
3 Ate Ace Girl	ateace

**Answer:** (penalty regime: 0 %)

```

1 import java.util.* ;
2 final class vowel
3 {
4     public final String evs(String[] arr)
5     {
6         StringBuilder r = new StringBuilder();
7         for(String s:arr)
8         {
9             if(s.length()>0 && isvowel(s.charAt(0))&&isvowel(s.charAt(s.length()-1)))
10                r.append(s);
11         }
12         return r.length()>0?r.toString().toLowerCase():"no matches found";
13     }
14     public final boolean isvowel(char c){
15         c=Character.toLowerCase(c);
16         return c=='a' || c=='e' || c=='i' || c=='o' || c=='u';
17     }
18 }
19
20 public class Sample
21 {
22     public static void main(String args[])
23     {
24         Scanner scn = new Scanner(System.in);
25         int n=scn.nextInt();
26         scn.nextLine();

```

```

27     String s=scn.nextLine();
28     String[] arr = s.split(" ");
29     vowel v = new vowel();
30     String r = v.evs(arr);
31     System.out.print(r);
32     scn.close();
33 }
34 }

```

	Input	Expected	Got	
✓	3 oreo sirish apple	oreoapple	oreoapple	✓
✓	2 Mango banana	no matches found	no matches found	✓
✓	3 Ate Ace Girl	ateace	ateace	✓

Passed all tests! ✓






## Question 2

Correct

Marked out of 5.00

Create a base class Shape with a method called calculateArea(). Create three subclasses: Circle, Rectangle, and Triangle. Override the calculateArea() method in each subclass to calculate and return the shape's area.

In the given exercise, here is a simple diagram illustrating polymorphism implementation:



```

abstract class Shape {
    public abstract double calculateArea() ;
}

```

```
System.out.printf("Area of a Triangle :%.2f\n",((0.5)*base*height)); // use this statement
```

sample Input :

```

4 // radius of the circle to calculate area PI*r*r
5 // length of the rectangle
6 // breadth of the rectangle to calculate the area of a rectangle
4 // base of the triangle
3 // height of the triangle

```

**OUTPUT:**

**Area of a circle :50.27**

**Area of a Rectangle :30.00**

**Area of a Triangle :6.00**

**For example:**

Test	Input	Result
1	4 5 6 4 3	Area of a circle: 50.27 Area of a Rectangle: 30.00 Area of a Triangle: 6.00
2	7 4.5 6.5 2.4 3.6	Area of a circle: 153.94 Area of a Rectangle: 29.25 Area of a Triangle: 4.32

**Answer:** (penalty regime: 0 %)

```

1 import java.util.*;
2 abstract class Shape
3 {
4     public abstract double calArea();
5 }
6 class Circle extends Shape
7 {
8     private double radius ;
9     public Circle(double r)
10    {
11        radius = r;
12    }
13     public double calArea()
14    {
15        return Math.PI*radius*radius;
16    }
17 }
18 class Rectangle extends Shape

```

```

19 {
20     private double l,b;
21     public Rectangle(double l,double r)
22     {
23         this.l = l ;
24         this.b = r;
25     }
26     public double calArea()
27     {
28         return l*b;
29     }
30 }
31 class Triangle extends Shape
32 {
33     private double b,h ;
34     public Triangle (double b , double h)
35     {
36         this.b=b;
37         this.h=h;
38     }
39     public double calArea()
40     {
41         return 0.5*b*h;
42     }
43 }
44 }
45 public class Sample
46 {
47     public static void main(String args[])
48     {
49         Scanner scn = new Scanner(System.in);
50         double r = scn.nextDouble();
51         double l =scn.nextDouble();
52         double b =scn.nextDouble();

```

	Test	Input	Expected	Got	
✓	1	4 5 6 4 3	Area of a circle: 50.27 Area of a Rectangle: 30.00 Area of a Triangle: 6.00	Area of a circle: 50.27 Area of a Rectangle: 30.00 Area of a Triangle: 6.00	✓
✓	2	7 4.5 6.5 2.4 3.6	Area of a circle: 153.94 Area of a Rectangle: 29.25 Area of a Triangle: 4.32	Area of a circle: 153.94 Area of a Rectangle: 29.25 Area of a Triangle: 4.32	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of 5.00

## 1. Final Variable:

- Once a variable is declared **final**, its value cannot be changed after it is initialized.
- It must be initialized when it is declared or in the constructor if it's not initialized at declaration.
- It can be used to define constants

```
final int MAX_SPEED = 120; // Constant value, cannot be changed
```

## 2. Final Method:

- A method declared **final** cannot be overridden by subclasses.
- It is used to prevent modification of the method's behavior in derived classes.

```
public final void display() {  
    System.out.println("This is a final method.");  
}
```

## 3. Final Class:

- A class declared as **final** cannot be subclassed (i.e., no other class can inherit from it).
- It is used to prevent a class from being extended and modified.
- public final class Vehicle {  
 // class code  
}

**Given a Java Program that contains the bug in it, your task is to clear the bug to the output.**  
**you should delete any piece of code.**

**For example:**

Test	Result
1	The maximum speed is: 120 km/h This is a subclass of FinalExample.

**Answer:** (penalty regime: 0 %)

Reset answer

```
1 class FinalExample {  
2  
3     // Final variable  
4     final int maxSpeed = 120;  
5  
6     // Final method  
7     public final void displayMaxSpeed() {  
8         System.out.println("The maximum speed is: " + maxSpeed + " km/h");  
9     }  
10 }  
11  
12 class SubClass extends FinalExample {  
13  
14  
15  
16     // You can create new methods here  
17     public void showDetails() {  
18         System.out.println("This is a subclass of FinalExample.");  
19     }  
20 }  
21  
22 class prog {  
23     public static void main(String[] args) {  
24         FinalExample obj = new FinalExample();  
25         obj.displayMaxSpeed();  
26  
27         SubClass subObj = new SubClass();  
28         subObj.showDetails();  
29     }  
30 }
```

	Test	Expected	Got	
✓	1	The maximum speed is: 120 km/h This is a subclass of FinalExample.	The maximum speed is: 120 km/h This is a subclass of FinalExample.	✓

Passed all tests! ✓

[◀ Lab-08-MCQ](#)

Jump to...

[FindStringCode ▶](#)

[Dashboard](#) / [My courses](#) / [CS23333-OOPUI-2023](#) / [Lab-09-Exception Handling](#) / [Lab-09-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Wednesday, 23 October 2024, 12:18 PM
<b>Completed</b>	Wednesday, 23 October 2024, 12:24 PM
<b>Duration</b>	6 mins 21 secs

## Question 1

Correct

Marked out of 5.00

In the following program, an array of integer data is to be initialized.

During the initialization, if a user enters a value other than an integer, it will throw an InputMismatchException exception.

On the occurrence of such an exception, your program should print "You entered bad data."

If there is no such exception it will print the total sum of the array.

/\* Define try-catch block to save user input in the array "name"

If there is an exception then catch the exception otherwise print the total sum of the array. \*/

**Sample Input:**

3  
5 2 1

**Sample Output:**

8

**Sample Input:**

2  
1 g

**Sample Output:**

You entered bad data.

**For example:**

Input	Result
3 5 2 1	8
2 1 g	You entered bad data.

**Answer:** (penalty regime: 0 %)

Reset answer

```

1 import java.util.Scanner;
2 import java.util.InputMismatchException;
3 class prog {
4     public static void main(String[] args) {
5         Scanner sc = new Scanner(System.in);
6         int length = sc.nextInt();
7         // create an array to save user input
8         int[] name = new int[length];
9         int sum=0;//save the total sum of the array.
10
11         /* Define try-catch block to save user input in the array "name"
12         If there is an exception then catch the exception otherwise print
13         the total sum of the array. */
14         try
15         {
16             for(int i=0;i<length;i++)
17             {
18                 name[i] =sc.nextInt();
19                 sum+=name[i];
20             }
21             System.out.println(sum);
22         }
23         catch(InputMismatchException e )
24         {
25             System.out.println("You entered bad data.");
26         }
27     }
28
29
30
31
32
33

```

```
34 | }
35 | }
```

	Input	Expected	Got	
✓	3 5 2 1	8	8	✓
✓	2 1 g	You entered bad data.	You entered bad data.	✓

Passed all tests! ✓



## Question 2

Correct

Marked out of 5.00

Write a Java program to handle `ArithmeticException` and `ArrayIndexOutOfBoundsException`.

Create an array, read the input from the user, and store it in the array.

Divide the 0th index element by the 1st index element and store it.

if the 1st element is zero, it will throw an exception.

if you try to access an element beyond the array limit throws an exception.

**Input:**

5

10 0 20 30 40

**Output:**

`java.lang.ArithmeticException: / by zero`

I am always executed

Input:

3

10 20 30

**Output**

`java.lang.ArrayIndexOutOfBoundsException: Index 3 out of bounds for length 3`

I am always executed

**For example:**

Test	Input	Result
1	6 1 0 4 1 2 8	<code>java.lang.ArithmeticException: / by zero</code> I am always executed

**Answer:** (penalty regime: 0 %)

```

1 import java.util.*;
2 public class Sample
3 {
4     public static void main(String args[])
5     {
6         Scanner scn = new Scanner(System.in);
7         int n=scn.nextInt();
8         int[] arr = new int[n];
9         try
10        {
11            for(int i=0;i<n;i++)
12            {
13                arr[i]=scn.nextInt();
14            }
15            int res=arr[0]/arr[1];
16            int a = arr[n];
17        }
18        catch(ArithmeticException e)
19        {
20            System.out.println("java.lang.ArithmeticException: "+e.getMessage());
21        }
22        catch(ArrayIndexOutOfBoundsException e)
23        {
24            System.out.println("java.lang.ArrayIndexOutOfBoundsException: "+e.getMessage());
25        }
26        finally
27        {
28            System.out.println("I am always executed");
29        }
30    }
31 }
```



	Test	Input	Expected	Got	
✓	1	6 1 0 4 1 2 8	java.lang.ArithmeticException: / by zero I am always executed	java.lang.ArithmeticException: / by zero I am always executed	✓
✓	2	3 10 20 30	java.lang.ArrayIndexOutOfBoundsException: Index 3 out of bounds for length 3 I am always executed	java.lang.ArrayIndexOutOfBoundsException: Index 3 out of bounds for length 3 I am always executed	✓

Passed all tests! ✓

## Question 3

Correct

Marked out of 5.00

Write a Java program to create a method that takes an integer as a parameter and throws an exception if the number is odd.

**Sample input and Output:**

82 is even.  
Error: 37 is odd.

Fill the preloaded answer to get the expected output.

**For example:****Result**

82 is even.  
Error: 37 is odd.

**Answer:** (penalty regime: 0 %)

Reset answer

```

1 class prog {
2     public static void main(String[] args) {
3         int n = 82;
4         trynumber(n);
5         n = 37;
6         trynumber(n);
7     }
8 }
9
10 public static void trynumber(int n) {
11     try {
12
13         checkEvenNumber(n);
14         System.out.println(n + " is even.");
15     }
16     catch (Exception e) {
17         System.out.println("Error: " + e.getMessage());
18     }
19 }
20
21 public static void checkEvenNumber(int number) throws Exception{
22     if (number % 2 != 0) {
23         throw new Exception(number + " is odd.");
24     }
25 }
26 }
```

	Expected	Got	
✓	82 is even. Error: 37 is odd.	82 is even. Error: 37 is odd.	✓

Passed all tests! ✓

◀ Lab-09-MCQ

Jump to...

The "Nambiar Number" Generator ▶

[Dashboard](#) / [My courses](#) / [CS23333-OOPUI-2023](#) / [Lab-10- Collection- List](#) / [Lab-10-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Monday, 18 November 2024, 6:03 PM
<b>Completed</b>	Monday, 18 November 2024, 6:15 PM
<b>Duration</b>	12 mins 18 secs

## Question 1

Correct

Marked out of 1.00

Given an ArrayList, the task is to get the first and last element of the ArrayList in Java.

Input: ArrayList = [1, 2, 3, 4]

Output: First = 1, Last = 4

Input: ArrayList = [12, 23, 34, 45, 57, 67, 89]

Output: First = 12, Last = 89

**Approach:**

1. Get the ArrayList with elements.
2. Get the first element of ArrayList using the get(index) method by passing index = 0.
3. Get the last element of ArrayList using the get(index) method by passing index = size – 1.

**Answer:** (penalty regime: 0 %)

```

1 import java.util.*;
2 public class Array
3 {
4     public static void main(String[] args)
5     {
6         Scanner in=new Scanner(System.in);
7         int n=in.nextInt();
8         ArrayList<Integer> l=new ArrayList<>(n);
9         for(int i=0;i<n;i++)
10            l.add(in.nextInt());
11         System.out.print("ArrayList: "+l+"\n"+"First : "+l.get(0)+" , Last : "+l.get(n-1));
12     }
13 }
```

	Test	Input	Expected	Got	
✓	1	6 30 20 40 50 10 80	ArrayList: [30, 20, 40, 50, 10, 80] First : 30, Last : 80	ArrayList: [30, 20, 40, 50, 10, 80] First : 30, Last : 80	✓
✓	2	4 5 15 25 35	ArrayList: [5, 15, 25, 35] First : 5, Last : 35	ArrayList: [5, 15, 25, 35] First : 5, Last : 35	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of 1.00

The given Java program is based on the ArrayList methods and its usage. The Java program is partially filled. Your task is to fill in the incomplete statements to get the desired output.

```
list.set();
list.indexOf();
list.lastIndexOf()
list.contains()
list.size();
list.add();
list.remove();
```

The above methods are used for the below Java program.

**Answer:** (penalty regime: 0 %)

Reset answer

```
1 import java.util.ArrayList;
2 import java.util.Scanner;
3 public class Prog {
4     public static void main(String[] args) {
5         Scanner sc= new Scanner(System.in);
6         int n = sc.nextInt();
7         ArrayList<Integer> list = new ArrayList<Integer>();
8         for(int i = 0; i<n;i++)
9             list.add(sc.nextInt());
10        System.out.println("ArrayList: " + list);
11        list.set(1, 100);
12        System.out.println("Index of 100 = "+ list.indexOf(100));
13        System.out.println("LastIndex of 100 = "+ list.lastIndexOf(100));
14        System.out.println(list.contains(200));
15        System.out.println("Size Of ArrayList = "+ list.size());
16        list.add(1,500);
17        list.remove(3);
18        System.out.print("ArrayList: " + list);
19    }
20 }
```

	Test	Input	Expected	Got	
✓	1	5 1 2 3 100 5	ArrayList: [1, 2, 3, 100, 5] Index of 100 = 1 LastIndex of 100 = 3 false Size Of ArrayList = 5 ArrayList: [1, 500, 100, 100, 5]	ArrayList: [1, 2, 3, 100, 5] Index of 100 = 1 LastIndex of 100 = 3 false Size Of ArrayList = 5 ArrayList: [1, 500, 100, 100, 5]	✓


Passed all tests! ✓

## Question 3

Correct

Marked out of 1.00

Write a Java program to reverse elements in an array list.



Sample input and Output:

Red

Green

Orange

White

Black

**Sample output**

List before reversing :

[Red, Green, Orange, White, Black]

List after reversing :

[Black, White, Orange, Green, Red]

**Answer:** (penalty regime: 0 %)

```

1 import java.util.*;
2 public class Rev
3 {
4     public static void main(String[] args)
5     {
6         Scanner in=new Scanner(System.in);
7         int n=in.nextInt();
8         in.nextLine();
9         ArrayList<String> l=new ArrayList<>(n);
10        for(int i=0;i<n;i++)
11            l.add(in.nextLine());
12        System.out.println("List before reversing : \n"+l);
13        Collections.reverse(l);
14        System.out.println("List after reversing : \n"+l);
15    }
16 }

```

	Test	Input	Expected	Got	
✓	1	5 Red Green Orange White Black	List before reversing : [Red, Green, Orange, White, Black] List after reversing : [Black, White, Orange, Green, Red]	List before reversing : [Red, Green, Orange, White, Black] List after reversing : [Black, White, Orange, Green, Red]	✓
✓	2	4 CSE AIML AIDS CYBER	List before reversing : [CSE, AIML, AIDS, CYBER] List after reversing : [CYBER, AIDS, AIML, CSE]	List before reversing : [CSE, AIML, AIDS, CYBER] List after reversing : [CYBER, AIDS, AIML, CSE]	✓

Passed all tests! ✓

◀ [Lab-10-MCQ](#)

Jump to...

[Lab-11-MCQ](#) ▶

[Dashboard](#) / [My courses](#) / [CS23333-OOPUI-2023](#) / [Lab-11-Set, Map](#) / [Lab-11-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Monday, 18 November 2024, 6:06 PM
<b>Completed</b>	Monday, 18 November 2024, 6:16 PM
<b>Duration</b>	10 mins 3 secs



## Question 1

Correct

Marked out of 1.00

**Java HashSet** class implements the Set interface, backed by a hash table which is actually a [HashMap](#) instance.

No guarantee is made as to the iteration order of the hash sets which means that the class does not guarantee the constant order of elements over time.

This class permits the null element.

The class also offers constant time performance for the basic operations like add, remove, contains, and size assuming the hash function disperses the elements properly among the buckets.

## Java HashSet Features

A few important features of HashSet are mentioned below:

- Implements [Set Interface](#).
- The underlying data structure for HashSet is [Hashtable](#).
- As it implements the Set Interface, duplicate values are not allowed.
- Objects that you insert in HashSet are not guaranteed to be inserted in the same order. Objects are inserted based on their hash code.
- NULL elements are allowed in HashSet.
- HashSet also implements **Serializable** and **Cloneable** interfaces.

```
public class HashSet<E> extends AbstractSet<E> implements Set<E>, Cloneable, Serializable
```

Sample Input and Output:

```
5
```

```
90
```

```
56
```

```
45
```

```
78
```

```
25
```

```
78
```

Sample Output:

```
78 was found in the set.
```

Sample Input and output:

```
3
```

```
2
```

```
7
```

```
9
```

```
5
```

Sample Input and output:

```
5 was not found in the set.
```

**Answer:** (penalty regime: 0 %)

Reset answer

```
1 import java.util.HashSet;
2 import java.util.Scanner;
3 class prog {
4     public static void main(String[] args) {
5         Scanner sc= new Scanner(System.in);
6         int n = sc.nextInt();
7         // Create a HashSet object called numbers
8         HashSet<Integer> numbers = new HashSet<>();
9
10        // Add values to the set
11        for(int i=0;i<n;i++)
12            numbers.add(sc.nextInt());
13
14        int skey=sc.nextInt();
15
16        // Show which numbers between 1 and 10 are in the set
17        if(numbers.contains(skey))
18        {
19            System.out.println(skey + " was found in the set.");
20        }
21        else
22        {
23            System.out.println(skey + " was not found in the set.");
24        }
25    }
26 }
```

```

26 |
27 |
28 | }
29 | }

```

	Test	Input	Expected	Got	
✓	1	5 90 56 45 78 25 78	78 was found in the set.	78 was found in the set.	✓
✓	2	3 -1 2 4 5	5 was not found in the set.	5 was not found in the set.	✓

Passed all tests! ✓



## Question 2

Correct

Marked out of 1.00

Write a Java program to compare two sets and retain elements that are the same.

**Sample Input and Output:**

5

Football

Hockey

Cricket

Volleyball

Basketball

7 // **HashSet 2:**

Golf

Cricket

Badminton

Football

Hockey

Volleyball

Handball

**SAMPLE OUTPUT:**

Football

Hockey

Cricket

Volleyball

Basketball

**Answer:** (penalty regime: 0 %)

```
1 import java.util.*;
2 public class prog {
3     public static void main(String args[]) {
4         Scanner scan=new Scanner(System.in);
5         int n1=scan.nextInt(); scan.nextLine();
6         HashSet<String> set1 = new HashSet<>();
7         for(int i=0;i<n1;i++){
8             set1.add(scan.nextLine());
9         }
10        int n2 = scan.nextInt(); scan.nextLine(); HashSet<String> set2 = new HashSet<>();
11        for(int i=0;i<n2;i++){
12            set2.add(scan.nextLine());
13        }
14        set1.retainAll(set2);
15        set1.stream().forEach(System.out::println);
16    }
17 }
```

	Test	Input	Expected	Got	
✓	1	5 Football Hockey Cricket Volleyball Basketball 7 Golf Cricket Badminton Football Hockey Volleyball Throwball	Cricket Hockey Volleyball Football	Cricket Hockey Volleyball Football	✓
✓	2	4 Toy Bus Car Auto 3 Car Bus Lorry	Bus Car	Bus Car	✓

Passed all tests! ✓

Question 3

Correct

Marked out of 1.00

## Java HashMap Methods

[containsKey\(\)](#) Indicate if an entry with the specified key exists in the map[containsValue\(\)](#) Indicate if an entry with the specified value exists in the map[putIfAbsent\(\)](#) Write an entry into the map but only if an entry with the same key does not already exist[remove\(\)](#) Remove an entry from the map[replace\(\)](#) Write to an entry in the map only if it exists[size\(\)](#) Return the number of entries in the map

Your task is to fill the incomplete code to get desired output

**Answer:** (penalty regime: 0 %)

Reset answer

```
1 import java.util.HashMap;
2 import java.util.Map.Entry;
3 import java.util.Set;
4 import java.util.Scanner;
5
6 public class Prog {
7     public static void main(String[] args) {
8         HashMap<String, Integer> map = new HashMap<String, Integer>();
9         String name;
10        int num;
11        Scanner sc = new Scanner(System.in);
12        int n = sc.nextInt();
13
14        for (int i = 0; i < n; i++) {
15            name = sc.next();
16            num = sc.nextInt();
17            map.put(name, num);
18        }
19
20        Set<Entry<String, Integer>> entrySet = map.entrySet();
21        for (Entry<String, Integer> entry : entrySet) {
22            System.out.println(entry.getKey() + " : " + entry.getValue());
23        }
24
25        System.out.println("-----");
26
27        HashMap<String, Integer> anotherMap = new HashMap<String, Integer>();
28        anotherMap.put("SIX", 6);
29        anotherMap.put("SEVEN", 7);
30        anotherMap.putAll(map);
31
32        entrySet = anotherMap.entrySet();
33        for (Entry<String, Integer> entry : entrySet) {
34            System.out.println(entry.getKey() + " : " + entry.getValue());
35        }
36
37        map.putIfAbsent("FIVE", 5);
38
39        int value = map.get("TWO");
40        System.out.println(value);
41
42        System.out.println(map.containsKey("ONE"));
43
44        System.out.println(map.containsValue(3));
45
46        System.out.println(map.size());
47    }
48 }
49
```

	Test	Input	Expected	Got	
✓	1	3 ONE 1 TWO 2 THREE 3	ONE : 1 TWO : 2 THREE : 3 ----- SIX : 6 ONE : 1 TWO : 2 SEVEN : 7 THREE : 3 2 true true 4	ONE : 1 TWO : 2 THREE : 3 ----- SIX : 6 ONE : 1 TWO : 2 SEVEN : 7 THREE : 3 2 true true 4	✓

Passed all tests! ✓

◀ Lab-11-MCQ

Jump to...

[TreeSet example ▶](#)

[Dashboard](#) / [My courses](#) / [CS23333-OOPUI-2023](#) / [Lab-12-Introduction to I/O, I/O Operations, Object Serialization](#) / [Lab-12-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Monday, 18 November 2024, 6:12 PM
<b>Completed</b>	Monday, 18 November 2024, 6:21 PM
<b>Duration</b>	8 mins 55 secs

## Question 1

Correct

Marked out of 5.00

Given two char arrays input1[] and input2[] containing only lower case alphabets, extracts the alphabets which are present in both arrays (common alphabets).

Get the ASCII values of all the extracted alphabets.

Calculate sum of those ASCII values. Lets call it sum1 and calculate single digit sum of sum1, i.e., keep adding the digits of sum1 until you arrive at a single digit.

Return that single digit as output.

Note:

1. Array size ranges from 1 to 10.
2. All the array elements are lower case alphabets.
3. Atleast one common alphabet will be found in the arrays.

Example 1:

input1: {'a', 'b', 'c'}

input2: {'b', 'c'}

output: 8

Explanation:

'b' and 'c' are present in both the arrays.

ASCII value of 'b' is 98 and 'c' is 99.

$98 + 99 = 197$

$1 + 9 + 7 = 17$

$1 + 7 = 8$

For example:

Input	Result
a b c b c	8

Answer: (penalty regime: 0 %)

```

1 public class CommonAlphabetSum {
2
3     public static int getSingleDigitSum(int sum) {
4         while (sum >= 10) {
5             int tempSum = 0;
6             while (sum > 0) {
7                 tempSum += sum % 10;
8                 sum /= 10;
9             }
10            sum = tempSum;
11        }
12        return sum;
13    }
14
15    public static int calculateSingleDigitSum(char[] input1, char[] input2) {
16        StringBuilder commonChars = new StringBuilder();
17
18        for (char c1 : input1) {
19            for (char c2 : input2) {
20                if (c1 == c2) {
21                    commonChars.append(c1);
22                    break;
23                }
24            }
25        }
26
27        int sum1 = 0;
28        for (char c : commonChars.toString().toCharArray()) {
29            sum1 += (int) c;
```



```
30     }
31
32     return getSingleDigitSum(sum1);
33 }
34
35 public static void main(String[] args) {
36     char[] input1 = {'a', 'b', 'c'};
37     char[] input2 = {'b', 'c'};
38
39     int result = calculateSingleDigitSum(input1, input2);
40     System.out.println(result);
41 }
42 }
43 }
```

	Input	Expected	Got	
✓	a b c b c	8	8	✓

Passed all tests! ✓



## Question 2

Correct

Marked out of 5.00

You are provided with a string which has a sequence of 1's and 0's.

This sequence is the encoded version of an English word. You are supposed to write a program to decode the provided string and find the original word.

Each alphabet is represented by a sequence of 0s.

This is as mentioned below:

Z : 0

Y : 00

X : 000

W : 0000

V : 00000

U : 000000

T : 0000000

and so on upto A having 26 0's (000000000000000000000000).

The sequence of 0's in the encoded form are separated by a single 1 which helps to distinguish between 2 letters.

Example 1:

input1: 010010001

The decoded string (original word) will be: ZYX

Example 2:

input1: 0000100000000000000000001000000000001000000000010000000000001

The decoded string (original word) will be: WIPRO

Note: The decoded string must always be in UPPER case.

**For example:**

Input	Result
010010001	ZYX
0000100000000000000000001000000000001000000000010000000000001	WIPRO

**Answer:** (penalty regime: 0 %)

```

1 import java.util.Scanner;
2
3 public class Decoder {
4     public static void main(String[] args) {
5         Scanner sc = new Scanner(System.in);
6         String encoded = sc.nextLine();
7         String[] segments = encoded.split("1");
8         StringBuilder decodedWord = new StringBuilder();
9
10        for (String segment : segments) {
11            int length = segment.length();
12            char letter = (char) ('A' + (26 - length));
13            decodedWord.append(letter);
14        }
15
16        System.out.println(decodedWord.toString());
17    }
18 }
19

```

Passed all tests! ✓

## Question 3

Correct

Marked out of 5.00

Write a function that takes an input String (sentence) and generates a new String (modified sentence) by reversing the words in the original String, maintaining the words position.

In addition, the function should be able to control the reversing of the case (upper or lowercase) based on a case\_option parameter, as follows:

If case\_option = 0, normal reversal of words i.e., if the original sentence is "Wipro TechNologies BangaLore", the new reversed sentence should be "orpiW seigolonhceT erolagnaB".

If case\_option = 1, reversal of words with retaining position's case i.e., if the original sentence is "Wipro TechNologies BangaLore", the new reversed sentence should be "Orpiw SeigOlonhceT ErolaGnab".

Note that positions 1, 7, 11, 20 and 25 in the original string are uppercase W, T, N, B and L.

Similarly, positions 1, 7, 11, 20 and 25 in the new string are uppercase O, S, O, E and G.

NOTE:

- Only space character should be treated as the word separator i.e., "Hello World" should be treated as two separate words, "Hello" and "World". However, "Hello,World", "Hello;World", "Hello-World" or "Hello/World" should be considered as a single word.
- Non-alphabetic characters in the String should not be subjected to case changes. For example, if case option = 1 and the original sentence is "Wipro TechNologies, Bangalore" the new reversed sentence should be "Orpiw ,seigolonhceT Erolagnab". Note that comma has been treated as part of the word "Technologies," and when comma had to take the position of uppercase T it remained as a comma and uppercase T took the position of comma. However, the words "Wipro and Bangalore" have changed to "Orpiw" and "Erolagnab".
- Kindly ensure that no extra (additional) space characters are embedded within the resultant reversed String.

Examples:

S. No.	input1	input2	output
1	Wipro Technologies Bangalore	0	orpiW seigolonhceT erolagnaB
2	Wipro Technologies, Bangalore	0	orpiW ,seigolonhceT erolagnaB
3	Wipro Technologies Bangalore	1	Orpiw SeigolonhceT Erolagnab
4	Wipro Technologies, Bangalore	1	Orpiw ,seigolonhceT Erolagnab

For example:

Input	Result
Wipro Technologies Bangalore 0	orpiW seigolonhceT erolagnaB
Wipro Technologies, Bangalore 0	orpiW ,seigolonhceT erolagnaB
Wipro Technologies Bangalore 1	Orpiw SeigolonhceT Erolagnab
Wipro Technologies, Bangalore 1	Orpiw ,seigolonhceT Erolagnab

Answer: (penalty regime: 0 %)

```

1 import java.util.*;
2
3 public class prog {
4
5     public static String reverseWords(String sentence, int caseOption) {
6         String[] words = sentence.split(" "); // Split sentence into words based on spaces
7         StringBuilder result = new StringBuilder();
8
9         for (String word : words) {
10             if (caseOption == 0) {
11                 // Normal reversal without retaining case
12                 result.append(new StringBuilder(word).reverse()).append(" ");
13             } else if (caseOption == 1) {
14                 // Reverse while retaining the case
15                 result.append(reverseWithCaseRetention(word)).append(" ");
16             }
17         }
18     }
19 }

```

```

17     }
18
19     return result.toString().trim(); // Remove trailing space
20 }
21
22 private static String reverseWithCaseRetention(String word) {
23     char[] original = word.toCharArray();
24     char[] reversed = new char[original.length];
25
26     // Reverse the word
27     for (int i = 0, j = original.length - 1; i < original.length; i++, j--) {
28         reversed[i] = original[j];
29     }
30
31     // Retain the case of the original word
32     for (int i = 0; i < original.length; i++) {
33         if (Character.isUpperCase(original[i])) {
34             reversed[i] = Character.toUpperCase(reversed[i]);
35         } else if (Character.isLowerCase(original[i])) {
36             reversed[i] = Character.toLowerCase(reversed[i]);
37         }
38     }
39
40     return new String(reversed);
41 }
42
43 public static void main(String[] args) {
44     Scanner scan = new Scanner(System.in);
45     System.out.println(reverseWords(scan.nextLine(), scan.nextInt()));
46 }
47 }

```

	Input	Expected	Got	
✓	Wipro Technologies Bangalore 0	orpiW seigolonhceT erolagnaB	orpiW seigolonhceT erolagnaB	✓
✓	Wipro Technologies, Bangalore 0	orpiW ,seigolonhceT erolagnaB	orpiW ,seigolonhceT erolagnaB	✓
✓	Wipro Technologies Bangalore 1	Orpiw Seigolonhcet Erolagnab	Orpiw Seigolonhcet Erolagnab	✓
✓	Wipro Technologies, Bangalore 1	Orpiw ,seigolonhceT Erolagnab	Orpiw ,seigolonhceT Erolagnab	✓

Passed all tests! ✓

◀ Lab-12-MCQ

Jump to...

Identify possible words ►