

# Data Classes

## *Introduction to R for Public Health Researchers*

### Data Classes:

- One dimensional classes ('vectors'):
  - Character: strings or individual characters, quoted
  - Numeric: any real number(s)
  - Integer: any integer(s)/whole numbers
  - Factor: categorical/qualitative variables
  - Logical: variables composed of TRUE or FALSE
  - Date/POSIXct: represents calendar dates and times

### Character and numeric

We have already covered `character` and `numeric` classes.

```
class(c("Andrew", "Jaffe"))
```

```
## [1] "character"
```

```
class(c(1, 4, 7))
```

```
## [1] "numeric"
```

### Integer

`Integer` is a special subset of `numeric` that contains only whole numbers

A sequence of numbers is an example of the integer class

```
x = seq(from = 1, to = 5) # seq() is a function
x
```

```
## [1] 1 2 3 4 5
```

```
class(x)
```

```
## [1] "integer"
```

### Integer

The colon `:` is a shortcut for making sequences of numbers

It makes consecutive integer sequence from `[num1]` to `[num2]` by 1

```
1:5
```

```
## [1] 1 2 3 4 5
```

## Logical

`logical` is a class that only has two possible elements: `TRUE` and `FALSE`

```
x = c(TRUE, FALSE, TRUE, TRUE, FALSE)
class(x)
```

```
## [1] "logical"
```

```
is.numeric(c("Andrew", "Jaffe"))
```

```
## [1] FALSE
```

```
is.character(c("Andrew", "Jaffe"))
```

```
## [1] TRUE
```

## Logical

Note that `logical` elements are NOT in quotes.

```
z = c("TRUE", "FALSE", "TRUE", "FALSE")
class(z)
```

```
## [1] "character"
```

```
as.logical(z)
```

```
## [1] TRUE FALSE TRUE FALSE
```

Bonus: `sum()` and `mean()` work on `logical` vectors - they return the total and proportion of `TRUE` elements, respectively.

```
sum(as.logical(z))
```

```
## [1] 2
```

## General Class Information

There are two useful functions associated with practically all R classes, which relate to logically checking the underlying class (`is.CLASS_()`) and coercing between classes (`as.CLASS_()`).

```
is.numeric(c("Andrew", "Jaffe"))
```

```
## [1] FALSE
```

```
is.character(c("Andrew", "Jaffe"))
```

```
## [1] TRUE
```

## General Class Information

There are two useful functions associated with practically all R classes, which relate to logically checking the underlying class (`is.CLASS_()`) and coercing between classes (`as.CLASS_()`).

```
as.character(c(1, 4, 7))
```

```
## [1] "1" "4" "7"
```

```
as.numeric(c("Andrew", "Jaffe"))
```

```
## Warning: NAs introduced by coercion
```

```
## [1] NA NA
```

## Factors

A **factor** is a special **character** vector where the elements have pre-defined groups or ‘levels’. You can think of these as qualitative or categorical variables:

```
x = factor(c("boy", "girl", "girl", "boy", "girl"))
x
```

```
## [1] boy  girl girl boy  girl
```

```
## Levels: boy girl
```

```
class(x)
```

```
## [1] "factor"
```

Note that levels are, by default, in alphanumerical order.

## Factors

Factors are used to represent categorical data, and can also be used for ordinal data (ie categories have an intrinsic ordering)

Note that R reads in character strings as factors by default in functions like `read.table()`

‘The function `factor` is used to encode a vector as a factor (the terms ‘category’ and ‘enumerated type’ are also used for factors). If argument `ordered` is `TRUE`, the factor levels are assumed to be ordered.’

```
factor(x = character(), levels, labels = levels,
       exclude = NA, ordered = is.ordered(x))
```

## Factors

Suppose we have a vector of case-control status

```
cc = factor(c("case", "case", "case",
             "control", "control", "control"))
cc
```

```
## [1] case  case  case  control control control
```

```
## Levels: case control
```

```
levels(cc) = c("control", "case")
cc
```

```
## [1] control control control case  case  case
```

```
## Levels: control case
```

## Factors

Note that the levels are alphabetically ordered by default. We can also specify the levels within the factor call

```

casecontrol = c("case","case","case","control",
               "control","control")
factor(casecontrol, levels = c("control","case") )

## [1] case    case    case    control control control
## Levels: control case

factor(casecontrol, levels = c("control","case"),
       ordered=TRUE)

## [1] case    case    case    control control control
## Levels: control < case

```

## Factors

Factors can be converted to numeric or character very easily

```

x = factor(casecontrol,
           levels = c("control","case") )
as.character(x)

## [1] "case"    "case"    "case"    "control" "control" "control"
as.numeric(x)

## [1] 2 2 2 1 1 1

```

## Factors

However, you need to be careful modifying the labels of existing factors, as its quite easy to alter the meaning of the underlying data.

```

xCopy = x
levels(xCopy) = c("case", "control") # wrong way
xCopy

## [1] control control control case    case    case
## Levels: case control
as.character(xCopy) # labels switched

## [1] "control" "control" "control" "case"    "case"    "case"
as.numeric(xCopy)

## [1] 2 2 2 1 1 1

```

## Creating categorical variables

The `rep()` ["repeat"] function is useful for creating new variables

```

bg = rep(c("boy","girl"),each=50)
head(bg)

## [1] "boy" "boy" "boy" "boy" "boy" "boy"

```

```
bg2 = rep(c("boy", "girl"), times=50)
head(bg2)

## [1] "boy" "girl" "boy" "girl" "boy" "girl"
length(bg) == length(bg2)

## [1] TRUE
```

## Creating categorical variables

One frequently-used tool is creating categorical variables out of continuous variables, like generating quantiles of a specific continuously measured variable.

A general function for creating new variables based on existing variables is the `ifelse()` function, which “returns a value with the same shape as test which is filled with elements selected from either yes or no depending on whether the element of test is TRUE or FALSE.”

```
ifelse(test, yes, no)

# test: an object which can be coerced
#       to logical mode.
# yes: return values for true elements of test.
# no: return values for false elements of test.
```

## Charm City Circulator data

Please download the Charm City Circulator data:

[http://www.aejaffe.com/summerR\\_2016/data/Charm\\_City\\_Circulator\\_Ridership.csv](http://www.aejaffe.com/summerR_2016/data/Charm_City_Circulator_Ridership.csv)

```
# paste/paste0 will be covered later
circ = read.csv(
  paste0("http://www.aejaffe.com/summerR_2016/data",
        "/Charm_City_Circulator_Ridership.csv"),
  header = TRUE, as.is = TRUE)
```

## Creating categorical variables

For example, we can create a new variable that records whether daily ridership on the Circulator was above 10,000.

```
hi_rider = ifelse(circ$daily > 10000, "high", "low")
hi_rider = factor(hi_rider, levels = c("low", "high"))
head(hi_rider)

## [1] low low low low low low
## Levels: low high
table(hi_rider)

## hi_rider
## low high
## 740 282
```

## Creating categorical variables

You can also nest `ifelse()` within itself to create 3 levels of a variable.

```
riderLevels = ifelse(circ$daily < 10000, "low",
                    ifelse(circ$daily > 20000,
                          "high", "med"))
riderLevels = factor(riderLevels,
                    levels = c("low", "med", "high"))
head(riderLevels)
```

```
## [1] low low low low low low
## Levels: low med high
```

```
table(riderLevels)
```

```
## riderLevels
##  low  med high
##  740  280   2
```

## Creating categorical variables

However, it's much easier to use `cut()` to create categorical variables from continuous variables.

'cut divides the range of x into intervals and codes the values in x according to which interval they fall. The leftmost interval corresponds to level one, the next leftmost to level two and so on.'

```
cut(x, breaks, labels = NULL, include.lowest = FALSE,
    right = TRUE, dig.lab = 3,
    ordered_result = FALSE, ...)
```

## Creating categorical variables

**x:** a numeric vector which is to be converted to a factor by cutting.

**breaks:** either a numeric vector of two or more unique cut points or a single number (greater than or equal to 2) giving the number of intervals into which x is to be cut.

**labels:** labels for the levels of the resulting category. By default, labels are constructed using "(a,b]" interval notation. If `labels = FALSE`, simple integer codes are returned instead of a factor.

## Cut

Now that we know more about factors, `cut()` will make more sense:

```
x = 1:100
cx = cut(x, breaks=c(0,10,25,50,100))
head(cx)
```

```
## [1] (0,10] (0,10] (0,10] (0,10] (0,10] (0,10]
## Levels: (0,10] (10,25] (25,50] (50,100]
```

```
table(cx)
```

```
## cx
##  (0,10] (10,25] (25,50] (50,100]
##      10      15      25      50
```

## Cut

We can also leave off the labels

```
cx = cut(x, breaks=c(0,10,25,50,100), labels=FALSE)
head(cx)
```

```
## [1] 1 1 1 1 1 1
```

```
table(cx)
```

```
## cx
##  1  2  3  4
## 10 15 25 50
```

## Cut

Note that you have to specify the endpoints of the data, otherwise some of the categories will not be created

```
cx = cut(x, breaks=c(10,25,50), labels=FALSE)
head(cx)
```

```
## [1] NA NA NA NA NA NA
```

```
table(cx)
```

```
## cx
##  1  2
## 15 25
```

```
table(cx,useNA="ifany")
```

```
## cx
##    1    2 <NA>
##   15   25   60
```

## Date

You can convert date-like strings in the `Date` class (<http://www.statmethods.net/input/dates.html> for more info)

```
head(sort(circ$date))
```

```
## [1] "01/01/2011" "01/01/2012" "01/01/2013" "01/02/2011" "01/02/2012"
## [6] "01/02/2013"
```

```
# creating a date for sorting
```

```
circ$newDate <- as.Date(circ$date, "%m/%d/%Y")
head(circ$newDate)
```

```
## [1] "2010-01-11" "2010-01-12" "2010-01-13" "2010-01-14" "2010-01-15"
## [6] "2010-01-16"
```

```
range(circ$newDate)
```

```
## [1] "2010-01-11" "2013-03-01"
```

## Date

However, the `lubridate` package is much easier for generating explicit dates:

```
library(lubridate) # great for dates!
circ = mutate(circ, newDate2 = mdy(date))
head(circ$newDate2)

## [1] "2010-01-11" "2010-01-12" "2010-01-13" "2010-01-14" "2010-01-15"
## [6] "2010-01-16"

range(circ$newDate2) # gives you the range of the data

## [1] "2010-01-11" "2013-03-01"
```

## POSIXct

The `POSIXct` class is like a more general date format (with hours, minutes, seconds).

```
theTime = Sys.time()
theTime

## [1] "2017-01-04 21:33:52 EST"

class(theTime)

## [1] "POSIXct" "POSIXt"

theTime + as.period(20, unit = "minutes") # the future

## [1] "2017-01-04 21:53:52 EST"
```

## Data Classes:

- Two dimensional classes:
  - `data.frame`: traditional ‘Excel’ spreadsheets
    - \* Each column can have a different class, from above
  - `Matrix`: two-dimensional data, composed of rows and columns. Unlike data frames, the entire matrix is composed of one R class, e.g. all numeric or all characters.

## Matrices

```
n = 1:9
n

## [1] 1 2 3 4 5 6 7 8 9

mat = matrix(n, nrow = 3)
mat

##      [,1] [,2] [,3]
## [1,]    1    4    7
## [2,]    2    5    8
## [3,]    3    6    9
```



## Matrix (and Data frame) Functions

These are in addition to the previous useful vector functions:

- `nrow()` displays the number of rows of a matrix or data frame
- `ncol()` displays the number of columns
- `dim()` displays a vector of length 2: # rows, # columns
- `colnames()` displays the column names (if any) and `rownames()` displays the row names (if any)

## Data Selection

Matrices have two “slots” you can use to select data, which represent rows and columns, that are separated by a comma, so the syntax is `matrix[row,column]`. Note you cannot use `dplyr` functions on matrices.

```
mat[1, 1] # individual entry: row 1, column 1
```

```
## [1] 1
```

```
mat[1, ] # first row
```

```
## [1] 1 4 7
```

```
mat[, 1] # first columns
```

```
## [1] 1 2 3
```

## Data Selection

Note that the class of the returned object is no longer a matrix

```
class(mat[1, ])
```

```
## [1] "integer"
```

```
class(mat[, 1])
```

```
## [1] "integer"
```

## Data Frames

To review, the `data.frame` is the other two dimensional variable class.

Again, data frames are like matrices, but each column is a vector that can have its own class. So some columns might be `character` and others might be `numeric`, while others maybe a `factor`.

## Lists

- One other data type that is the most generic are `lists`.
- Can be created using `list()`
- Can hold vectors, strings, matrices, models, list of other list, lists upon lists!
- Can reference data using `$` (if the elements are named), or using `[[`, or `[[[]]`

```
> mylist <- list(letters=c("A", "b", "c"),  
+             numbers=1:3, matrix(1:25, ncol=5))
```

## List Structure

```
> head(mylist)
```

```
$letters
```

```
[1] "A" "b" "c"
```

```
$numbers
```

```
[1] 1 2 3
```

```
[[3]]
```

	[,1]	[,2]	[,3]	[,4]	[,5]
[1,]	1	6	11	16	21
[2,]	2	7	12	17	22
[3,]	3	8	13	18	23
[4,]	4	9	14	19	24
[5,]	5	10	15	20	25

## List referencing

```
> mylist[1] # returns a list
```

```
$letters
```

```
[1] "A" "b" "c"
```

```
> mylist["letters"] # returns a list
```

```
$letters
```

```
[1] "A" "b" "c"
```

## List referencing

```
> mylist[[1]] # returns the vector 'letters'
```

```
[1] "A" "b" "c"
```

```
> mylist$letters # returns vector
```

```
[1] "A" "b" "c"
```

```
> mylist[["letters"]] # returns the vector 'letters'
```

```
[1] "A" "b" "c"
```

## List referencing

You can also select multiple lists with the single brackets.

```
> mylist[1:2] # returns a list
```

```
$letters
```

```
[1] "A" "b" "c"
```

```
$numbers  
[1] 1 2 3
```

## List referencing

You can also select down several levels of a list at once

```
> mylist$letters[1]
```

```
[1] "A"
```

```
> mylist[[2]][1]
```

```
[1] 1
```

```
> mylist[[3]][1:2,1:2]
```

```
      [,1] [,2]  
[1,]    1    6  
[2,]    2    7
```