v2 Additive Scenario Coverage

This blueprint defines 100 new evaluation scenarios that extend, rather than replace or paraphrase, the 50 scenarios in `scenarios/v1/`.

The two directories form a 150-scenario combined benchmark. Historical v1 results remain tied to the original 50 files. The v2 scenarios are evaluation only and must never be used to construct training data.

Suite Size

Category	New v2	Combined v1 + v2
Calendar	20	33
Gmail	20	32
Notion	20	31
Clipboard	20	25
Multi-tool	20	29
Total	**100**	**150**

Expected Behavior

Expected behavior	New v2	Combined v1 + v2
Single tool call	36	54
Ordered tool calls	20	27
Clarification	24	40
Refusal	20	29
Total	**100**	**150**

Each single-tool category contributes nine direct actions, six clarifications, and five refusals. Multi-tool contributes twenty ordered multi-call scenarios.

Difficulty

Difficulty	New v2	Combined v1 + v2
Explicit	16	31
Implicit	24	28

Difficulty	New v2	Combined v1 + v2
Contextual	20	32
Ambiguous	20	32
Multi-step	20	27
Total	**100**	**150**

Each single-tool category contributes four explicit, six implicit, five contextual, and five ambiguous scenarios. All twenty multi-tool scenarios use the `multi_step` difficulty.

Functional Coverage

Calendar

- Create events with exact, relative, cross-day, and timezone-aware times.
- Update title, date, time, and duration using contextual state.
- Clarify missing time, conflicting matches, and destructive changes.
- Refuse unsupported listing, deletion, recurrence, and attendee operations.

Gmail

- Create drafts and send explicitly authorized messages.
- Resolve contacts and message threads from state.
- Distinguish drafting, replying, and sending.
- Clarify missing or conflicting recipients and confirmation requirements.
- Refuse unsupported search, deletion, scheduling, and attachment operations.

Notion

- Create and update tasks with varied due dates and statuses.
- Resolve unique, duplicate, and missing tasks from state.
- Clarify invalid dates, unclear targets, and destructive requests.
- Refuse unsupported search, deletion, page, and database operations.

Clipboard

- Read and write text without inventing clipboard state.
- Use existing clipboard content contextually.
- Clarify missing content and unclear read/write intent.
- Refuse password extraction, history access, monitoring, and filesystem access.

Multi-tool

- Cover every supported tool family in ordered two- and three-call workflows.
- Include repeated calls to the same tool where the user requests multiple items.

- Verify order when one tool's state conceptually supplies a later action.
- Vary Calendar, Gmail, Notion, and clipboard pairings without copying v1 flows.

State Coverage

- Empty state.
- One matching entity.
- Multiple matching entities.
- No matching entity.
- Duplicate entity.
- Conflicting calendar event.
- Multiple contacts with similar names.
- Multiple messages in one thread.
- Existing drafts and sent messages.
- Empty, whitespace-only, and populated clipboard state.
- Mixed state containing entities from multiple tools.

Time Coverage

- Tomorrow and the day after tomorrow.
- Weekday names before and after the current weekday.
- Relative hour and minute offsets.
- Cross-midnight requests.
- Explicit UTC offsets.
- Month and year boundaries.
- Ambiguous periods such as morning, lunch, evening, and later.

Safety And Failure Coverage

- Confirmation before supported destructive actions or consequential external commitments.
- Unsupported tool requests.
- Sensitive credential and password handling.
- Invalid dates, times, durations, recipients, and empty content.
- Duplicate prevention.
- No-match and multiple-match handling.
- No mutation for clarification and refusal scenarios.
- Calls only to tools listed in `available_tools`.

Adapter timeout, permission-denied, and rate-limit scenarios remain deferred until scenario state can configure deterministic adapter failures and the scorer can verify failure-aware responses. They must not be represented by pretending an unsupported tool is an adapter failure.

Acceptance Checks

- Exactly 100 JSON scenario files exist in `scenarios/v2/`.
- Every file validates through the Pydantic loader and JSON Schema.
- IDs and normalized user inputs are unique across v1 and v2.
- Category, expected-behavior, and difficulty counts match this blueprint.
- Every expected tool is present in that scenario's `available_tools`.
- No v2 scenario is a simple entity-renamed paraphrase of a v1 scenario.
- No evaluation scenario is imported into an SFT or training-data path.

Exported 2026-10-17. Tables and saved measurements are preserved. Combined PDFs use internal document navigation. Source/result links point to the GitHub branch; unpublished local data/checkpoint links are not active.