Early Balanced BAYMAX Data at Two Epochs

Experiment index

Question and Context

Would longer training help the early 100/100/100 BAYMAX mixture learn its policy?

Change

An early two-epoch SFT run used the same general ACR mixture family. This is not the later cleaned, anchored two-epoch reference.

Results

Evaluation	Cases	Task success	Tool accuracy	Argument accuracy	Clarification wording	Refusal wording
100/100/100 BAYMAX / two epochs	150	46/150 (0.307)	0.570	0.791	0.075	0.138
100/100/100 BAYMAX / two epochs	30	5/30 (0.167)	0.467	0.728	0.250	0.400

Values are ratios from 0 to 1, rounded to three decimals. Clarification/refusal columns measure wording criteria, not routing alone. Different suite sizes remain separate evaluations.

Result Provenance

- 100/100/100 BAYMAX / two epochs: 2026-09-27 UTC, 150 cases.
- 100/100/100 BAYMAX / two epochs: 2026-09-27 UTC, 30 cases.

Interpretation

The historical full-suite count increased from 43 to 46 successes relative to the one-epoch ACR artifact. The template-shift count fell from six to five.

That result did not establish robust generalization from the extra epoch.

Limits

These runs predate later strict-parser and data-integrity corrections. No strict-rescore artifact for this two-epoch candidate is present in the catalog. The current two-epoch config is not sufficient evidence of an immutable historical data identity.

Supporting Files

- qwen2_5_1_5b_lora_baymax_mix_2epoch_v1.json

Notes assembled on 2026-10-10 from saved artifacts and repository records. No training, inference or result modification was performed to write this note.

PDF exported 2026-10-12. Original Markdown and benchmark evidence are preserved. Local artifact links require the project files.