Target-Contract Cleaning With Resampled External Rows

Experiment index

Question and Context

The new strict training gate found target/schema failures in xLAM. Would excluding incompatible examples help?

Change

Build a target-compatible external source: 57,611 accepted rows after 618 credential exclusions and 1,771 additional target/credential exclusions, for 2,389 total skipped rows.

Retain the generator14 ACT200 recipe, but rebuild the mixed sampler. Removing rows changes which xLAM examples survive the cap; this is the cleaned-resampled candidate.

Actual Artifact

Raw cap 1,000; usable train 977: direct 447, multi 330, refusal 100, clarification 100. BAYMAX 400, xLAM 577, zero exact duplicates.

Usable validation 196: direct 72, multi 64, refusal 30, clarification 30.

Results

Evaluation	Cases	Task success	Tool accuracy	Argument accuracy	Clarification wording	Refusal wording
Cleaned / resampled	150	47/150 (0.313)	0.493	0.761	0.013	0.086

Values are ratios from 0 to 1, rounded to three decimals. Clarification/refusal columns measure wording criteria, not routing alone. Different suite sizes remain separate evaluations.

Routing and Output Validity

Evaluation	Macro-F1	Invalid-output rate
Cleaned / resampled (150 cases)	0.354	0.073

Routing values use the existing comparison helper on recorded per-scenario decisions; missing historical aggregate fields are derived without rewriting source files. Invalid output and unknown decision are not identical categories.

Decision Matrix: Cleaned / resampled (150 Cases)

Rows are expected decisions; columns are recorded predictions. The diagonal is correct routing, not necessarily full task success.

Expected	ACT	CLARIFY	REFUSE	Invalid/unknown
ACT	59	15	2	5
CLARIFY	28	3	5	4
REFUSE	17	2	7	3

Result Provenance

- Cleaned / resampled: 2026-10-06 UTC, 150 cases.

Interpretation

Success reached 47/150, versus 38/150 for original ACT200. Invalid outputs fell from 20 to 11, but routing macro-F1 fell from 0.396 to 0.354.

The model completed more tasks while handling abstention worse. "Cleaning improved reasoning" would overstate the evidence.

Limits

A recorded content-hash comparison found only 7/600 shared xLAM rows and 301/400 shared BAYMAX rows versus the original raw cap. Even the unchanged BAYMAX source yielded different selected examples. This does not isolate removal of faulty examples. A full-pool exclusion rate of about three percent can still change a small capped artifact substantially. The anchored comparison was created to address that confound.

Supporting Files

- qwen2_5_1_5b_lora_target_compatible_v14_act200_val200.json
- TRAINING_DATA_AUDIT.md

Notes assembled on 2026-10-10 from saved artifacts and repository records. No training, inference or result modification was performed to write this note.