



Tajamul Khan

Pandas **Cheat** **Sheet**



@Tajamulkhann



Import Export Data

- **`pd.read_csv(filename)`**: Read data from a CSV file.
- **`pd.read_table(filename)`**: Read data from a delimited text file.
- **`pd.read_excel(filename)`**: Read data from an Excel file.
- **`pd.read_sql(query, connection_object)`**: Read data from a SQL table/database.
- **`pd.read_json(json_string)`**: Read data from a JSON formatted string, URL, or file.
- **`pd.read_html(url)`**: Parse an HTML URL, string, or file to extract tables to a list of DataFrames.
- **`pd.DataFrame(dict)`**: Create a DataFrame from a dictionary (keys as column names, values as lists).
- **`df.to_csv(filename)`**: Write to a CSV file.
- **`df.to_excel(filename)`**: Write to an Excel file.
- **`df.to_sql(table_nm, connection_object)`**: Write to a SQL table.
- **`df.to_json(filename)`**: Write to a file in JSON format.



@Tajamulkhann



@Tajamul.datascientist



Inspect Data

- **df.head():** View the first 5 rows of the DataFrame.
- **df.tail():** View the last 5 rows of the DataFrame.
- **df.sample():** View the random 5 rows of the DataFrame.
- **df.shape:** Get the dimensions of the DataFrame.
- **df.info():** Get a concise summary of the DataFrame.
- **df.describe():** Summary statistics for numerical columns.
- **df.dtypes:** Check data types of columns.
- **df.columns:** List column names.
- **df.index:** Display the index range.



@Tajamulkhann



@Tajamul.datascientist



Select Index Data

- **`df['column']`**: Select a single column.
- **`df[['col1', 'col2']]`**: Select multiple columns.
- **`df.iloc[0]`**: Select the first row by position.
- **`df.loc[0]`**: Select the first row by index label.
- **`df.iloc[0, 0]`**: Select a specific element by position.
- **`df.loc[0, 'column']`**: Select a specific element by label.
- **`df[df['col'] > 5]`**: Filter rows where column > 5.
- **`df.iloc[0:5, 0:2]`**: Slice rows and columns.
- **`df.set_index('column')`**: Set a column as the index.



@Tajamulkhann



@Tajamul.datascientist



Cleaning Data

- **`df.isnull()`**: Check for null values.
- **`df.notnull()`**: Check for non-null values.
- **`df.dropna()`**: Drop rows with null values.
- **`df.fillna(value)`**: Replace null values with a specific value.
- **`df.replace(1, 'one')`**: Replace specific values.
- **`df.rename(columns={'old': 'new'})`**: Rename columns.
- **`df.astype('int')`**: Change data type of a column.
- **`df.drop_duplicates()`**: Remove duplicate rows.
- **`df.reset_index()`**: Reset the index.



@Tajamulkhann



@Tajamul.datascientist



Sort Filter Data

- **`df.sort_values('col')`**: Sort by column in ascending order.
- **`df.sort_values('col', ascending=False)`**: Sort by column in descending order.
- **`df.sort_values(['col1', 'col2'], ascending=[True, False])`**: Sort by multiple columns.
- **`df[df['col'] > 5]`**: Filter rows based on condition.
- **`df.query('col > 5')`**: Filter using a query string.
- **`df.sample(5)`**: Randomly select 5 rows.
- **`df.nlargest(3, 'col')`**: Get top 3 rows by column.
- **`df.nsmallest(3, 'col')`**: Get bottom 3 rows by column.
- **`df.filter(like='part')`**: Filter columns by substring.



@Tajamulkhann



@Tajamul.datascientist



Group Data

- **`df.groupby('col')`**: Group by a column.
- **`df.groupby('col').mean()`**: Mean of groups.
- **`df.groupby('col').sum()`**: Sum of groups.
- **`df.groupby('col').count()`**: Count non-null values in groups.
- **`df.groupby('col')['other_col'].max()`**: Max value in another column for groups.
- **`df.pivot_table(values='col', index='group', aggfunc='mean')`**: Create a pivot table.
- **`df.agg({'col1': 'mean', 'col2': 'sum'})`**: Aggregate multiple columns.
- **`df.apply(np.mean)`**: Apply a function to columns.
- **`df.transform(lambda x: x + 10)`**: Transform data column-wise.



@Tajamulkhann



@Tajamul.datascientist



Merge Join Data

- **`pd.concat([df1, df2])`:** Concatenate DataFrames vertically.
- **`pd.concat([df1, df2], axis=1)`:** Concatenate DataFrames horizontally.
- **`df1.merge(df2, on='key')`:** Merge two DataFrames on a key.
- **`df1.join(df2)`:** SQL-style join.
- **`df1.append(df2)`:** Append rows of one DataFrame to another.
- **`pd.merge(df1, df2, how='outer', on='key')`:** Outer join.
- **`pd.merge(df1, df2, how='inner', on='key')`:** Inner join.
- **`pd.merge(df1, df2, how='left', on='key')`:** Left join.
- **`pd.merge(df1, df2, how='right', on='key')`:** Right join.



@Tajamulkhann



@Tajamul.datascientist



Statistical Operations

- **df.mean()**: Column-wise mean.
- **df.median()**: Column-wise median.
- **df.std()**: Column-wise standard deviation.
- **df.var()**: Column-wise variance.
- **df.sum()**: Column-wise sum.
- **df.min()**: Column-wise minimum.
- **df.max()**: Column-wise maximum.
- **df.count()**: Count of non-null values per column.
- **df.corr()**: Correlation matrix.



@Tajamulkhann



@Tajamul.datascientist



Data Visualization

- **`df.plot(kind='line')`**: Line plot.
- **`df.plot(kind='bar')`**: Vertical bar plot.
- **`df.plot(kind='barh')`**: Horizontal bar plot.
- **`df.plot(kind='hist')`**: Histogram.
- **`df.plot(kind='box')`**: Box plot.
- **`df.plot(kind='kde')`**: Kernel density estimation plot.
- **`df.plot(kind='pie', y='col')`**: Pie chart.
- **`df.plot.scatter(x='c1', y='c2')`**: Scatter plot.
- **`df.plot(kind='area')`**: Area plot.



@Tajamulkhann



@Tajamul.datascientist



Found Helpful ?

Repost



@Tajamulkhann



@Tajamul.datascientist

Follow for more!