`terraform/` · state `terraform/terraform.tfstate`
created by `just infra` (second half), deleted by `just destroy`

master
e2-standard-2, 30 GB boot disk

worker1 (tag edge)
e2-standard-4, 30 GB boot disk

VPC g17-cluster
subnet 10.10.0.0/24, europe-west4

Firewall rules
g17-internal: all, inside the subnet
g17-admin: 22, 6443, ICMP
g17-web: 80, 443, to edge

worker2
e2-standard-4, 30 GB boot disk

Ubuntu 24.04 LTS, zone europe-west4-b

`attached_disk`, device `data`

`nat_ip`

`attached_disk`, device `data`

`terraform/persistent/`

g17-data-worker1
pd-balanced, 40 GB

g17-edge
static external IP

`terraform/` only looks these up by name (data sources): its destroy can't delete them.

g17-data-worker2
pd-balanced, 40 GB

Its own state, `terraform/persistent/terraform.tfstate`. Created, or adopted if they already exist, by `just persistent` (the first half of `just infra`). Deleted only by `just destroy-data`.

mounted at `/mnt/data` by 01-nodes.yml

mounted at `/mnt/data` by 01-nodes.yml

inside worker1: `/mnt/data`
ext4, formatted only if blank

`movies/data-movies-db-0`	10 Gi	movies-db
`movies/data-profiles-db-0`	2 Gi	profiles-db
`movies/data-recommendations-db-0`	2 Gi	recommendations-db
`movies/data-keycloak-db-0`	2 Gi	keycloak-db
`kafka/data-0-movies-kafka-dual-0`	5 Gi	Kafka broker 0
`kafka/data-0-movies-kafka-dual-2`	5 Gi	Kafka broker 2

Sizes are what each claim requests: a local volume doesn't enforce them.

inside worker2: `/mnt/data`
ext4, formatted only if blank

`movies/ollama-models`	15 Gi	Ollama's models
`kafka/data-0-movies-kafka-dual-1`	5 Gi	Kafka broker 1
`monitoring/data-prometheus-monitoring-kube-prometheus-prometheus-0`	10 Gi	Prometheus (7 days)
`monitoring/monitoring-grafana`	2 Gi	Grafana's database

kubelet starts only once `/mnt/data` is mounted (`RequiresMountsFor`).

How a claim finds its folder: no provisioner, one PersistentVolume per claim (03-platform.yml, `persistent_volumes`)

StatefulSet movies-db
volumeClaimTemplate data

→ **PVC data-movies-db-0**
StorageClass persistent

→ **PV movies-data-movies-db-0**
local, Retain, claimRef movies/data-movies-db-0, node worker1

→ **`/mnt/data/movies/data-movies-db-0`**
on worker1's data disk