



Microsoft Sentinel Use-Case Implementation Part 2

Phase 2: Case 1 — Unwanted Mail

Objective and Safety Boundary

This phase implements the workbook's second use case: phishing, spam, and user-reported phishing. The response must distinguish ordinary spam from credential phishing. Do not reset an account, block a sender, or create a tenant-wide mail rule from a single low-confidence spam event.

The production flow is:



```
Defender for Office 365 detects, or a user reports, a message
-> Sentinel analytic rule creates an alert and incident
    ✓ "Phishing email delivered and URL clicked" (High, groups by Account)
    ✓ "User-reported phishing email" (Medium, groups by Mail message)
-> ✓ Automation rule (incident created) starts PB-UnwantedMail-Response
    (currently conditioned on the "Phishing email delivered and URL clicked" rule only)
-> ✓ Entities - Get_Accounts, build UserUpn (Name + UPNSuffix)
-> ✓ Filter mail entities that carry a networkMessageId
-> ✓ Build the delete list { networkMessageId, recipientEmailAddress }
-> ✓ Soft-delete the messages (Graph analyzedEmails/remediate, managed identity)
```

1 - Prerequisites

Complete these checks before creating the rule or playbook:



1. Confirm Microsoft Defender for Office 365 is licensed and mailboxes are protected by Exchange Online Protection/Defender for Office 365.
2. In **Microsoft Sentinel > Content hub**, install or update the Microsoft Defender XDR and Microsoft Defender for Office 365 solutions.
 - a. Done in phase 0.
3. In **Microsoft Sentinel > Data connectors**, connect Microsoft Defender XDR and verify that alerts and incidents are arriving.
 - a. Done in phase 0.



4. Enable the **Report Message** or **Report Phishing** add-in and configure user-reported message settings in Defender for Office 365.



1. Creating a Safe Links Policy in Microsoft Defender for Office 365

- a. Check Microsoft documentation in this link → <https://learn.microsoft.com/en-us/defender-office-365/safe-links-policies-configure>





Microsoft Defender

Policies & rules > Threat policies > Create safe links policy

☒ Name your policy
☒ **Users and domains**
☐ URL & click protection settings
☐ Notification & Url
☐ Review

Users and domains

Add users, groups and domains to include or exclude in this policy.

Include these users, groups and domains

Users

muAyman

And

Groups

And

Domains

☐ Exclude these users, groups and domains

Back Next Cancel

Apply the policy to targeted users, groups or domains

Microsoft Defender

Policies & rules > Threat policies > Create safe links policy

☒ Name your policy
☒ Users and domains
☒ **URL & click protection settings**
☐ Notification & Url
☐ Review

URL & click protection settings

Configure your Safe Links URL and click protection settings for this policy. For more information, see [Safe Links in Microsoft Defender for Office 365](#).

Email

☒ On: Safe Links checks a list of known, malicious links when users click links in email. URLs are rewritten by default.
☒ Apply Safe Links to email messages sent within the organization
☒ Apply real-time URL scanning for suspicious links and links that point to files
☒ Wait for URL scanning to complete before delivering the message
☐ Do not rewrite URLs, do checks via Safe Links API only.

Do not rewrite the following URLs in email (0)
[Manage 0 URLs](#)

Teams

☒ On: Safe Links checks a list of known, malicious links when users click links in Microsoft Teams. URLs are not rewritten.



Office 365 Apps

☒ On: Safe Links checks a list of known, malicious links when users click links in Microsoft Office apps. URLs are not rewritten.

Click protection settings

☒ Track user clicks
☐ Let users click through to the original URL.
☐ Display the organization branding on notification and warning pages

Back Next Cancel



2 - Detection: Phishing

MDO's anti-phish impersonation protection should be the primary control.

Step 1 - Validate the source telemetry

Run the following query in **Sentinel > Logs** after a Defender alert or test message is available. Column availability differs by connector and tenant, so first run `EmailEvents | take 5` and adjust only column names that are absent.


This query to detect mails from `EmailEvents` table:

```
let clicks = UrlClickEvents
    | where ingestion_time() > ago(10m)
    | where ActionType in ("ClickAllowed", "ClickAllowedByTenantPolicy")
    | project ClickTime = TimeGenerated, NetworkMessageId, AccountUpn =
tolower(AccountUpn), Url, ClickAction = ActionType, ClickIP = IPAdres
s, IsClickedThrough;
EmailEvents
    | where TimeGenerated > ago(1d)
    | where UrlCount > 0 and DeliveryAction == "Delivered"
    | extend Auth = parse_json(AuthenticationDetails)
    | extend AuthFail = tostring(Auth.SPF) !~ "pass" or tostring(Auth.DKIM)
!~ "pass" or tostring(Auth.DMARC) !~ "pass"
    | extend LegitMs = SenderFromDomain matches regex @"(?i)(^|\.)?(microsof
t|office365|microsoftonline|azure|windows|outlook|live|sharepoint|offic
e)\.(com|net)$"
    | extend Impersonation = not(LegitMs) and SenderFromDomain matches rege
x @"(?i)(microsoft|office365|azure|outlook|sharepoint|onedrive)"
    | extend BadTld = SenderFromDomain matches regex @"(?i)\.(xyz|top|click
|online|tech|site|info)$"
    | extend Lure = Subject has_any ("verify", "suspended", "deactivated", "ex
pired", "compromised", "password", "action required", "credential")
    | where Impersonation or (AuthFail and BadTld) or (AuthFail and Lure) o
r (BadTld and Lure)
    | extend Recipient = tolower(RecipientEmailAddress)
    | join kind=inner clicks on NetworkMessageId, $left.Recipient == $righ
t.AccountUpn
    | project TimeGenerated = ClickTime, DeliveredTime = TimeGenerated, Rec
ipientEmailAddress, SenderFromAddress, SenderFromDomain, Subject, Url,
ClickAction, ClickIP, IsClickedThrough, AuthFail, Impersonation, BadTld,
Lure, NetworkMessageId, InternetMessageId
```

This KQL queries Microsoft 365 Defender's EmailEvents table to detect delivered phishing emails by identifying typosquatted domains impersonating Microsoft, suspicious subject lines containing urgency or verification keywords, authentication failures (SPF/DKIM/DMARC), and malicious TLDs (.xyz, .top, .info, .click, .online, .tech, .site). The

query projects key email metadata, calculates severity based on authentication failures and threat intelligence flags, then returns the 100 most recent suspicious emails for security analyst investigation.

Note that to detect onClick links you must enable **Safe Links** policy.




This query to detect user-reported phishing mails:

```
let ReportedPhishAlerts = AlertInfo
| where ingestion_time() > ago(10m)
| where ServiceSource == "Microsoft Defender for Office 365"
| where Title has_any ("Email reported by user as malware or phish", "User reported", "reported message")
| summarize arg_max(TimeGenerated, *) by AlertId
| project AlertId, AlertTitle = Title, AlertSeverity = Severity, DetectionSource, AlertTime = TimeGenerated;
let AlertIds = ReportedPhishAlerts
| project AlertId;
let Evidence = AlertEvidence
| where TimeGenerated > ago(1d)
| where AlertId in (AlertIds);
let ReporterInfo = Evidence
| where EntityType == "User" and isnotempty(AccountUpn)
```

```

    | summarize ReporterUpn = make_set(tolower(AccountUpn), 5) by Alert
Id;
let MessageIds = Evidence
    | where isnotempty(NetworkMessageId)
    | summarize NetworkMessageId = take_any(NetworkMessageId) by AlertI
d;
let UrlInfo = Evidence
    | where isnotempty(RemoteUrl)
    | summarize Urls = tostring(make_set(RemoteUrl, 20)) by AlertId;
let MailContext = EmailEvents
    | where TimeGenerated > ago(47h)
    | summarize arg_max(TimeGenerated, SenderFromAddress, Subject, Deli
veryAction, ThreatTypes, InternetMessageId)
        by NetworkMessageId, Recipient = tolower(RecipientEmailAddres
s);
ReportedPhishAlerts
| join kind=inner ReporterInfo on AlertId
| join kind=inner MessageIds on AlertId
| join kind=leftouter UrlInfo on AlertId
| mv-expand ReporterUpn to typeof(string)
| join kind=leftouter MailContext on NetworkMessageId, $left.ReporterUp
n == $right.Recipient
| project TimeGenerated = AlertTime, AlertId, AlertTitle, AlertSeverit
y, ReporterUpn,
        SenderFromAddress, Subject, DeliveryAction, ThreatTypes, Url
s, NetworkMessageId, InternetMessageId

```



Mail example:

Subject: **URGENT: Your account will be suspended in 24 hours**

Body:

Dear Valued User,

Our security system detected unusual activity on your account.

To avoid permanent suspension, you must verify your identity immediately.

Action Required Within 24 Hours:

Click the link below to confirm your account ownership:

<https://passwordreset.rnicrosoftonline.com>

Failure to verify within the specified time will result in:

Account suspension

Loss of mailbox access

Data deletion

This is an automated security alert. Do not reply to this email.

Microsoft 365 Security Team

Step 2 - Create the detection phishing rule

In **Microsoft Sentinel > Analytics > Create > Scheduled query rule:**

- **Name:** Phishing email delivered and URL clicked
- **Description:** Delivered email with Microsoft impersonation or lure characteristics, and the recipient clicked an allowed link.

- **Tactics:** Initial Access, Credential Access
- **Techniques:** T1566
- **Severity:** High
- **Status:** Enabled
- Set rule logic

Entity Mapping

Entity	Identifier	Column
Account	FullName	RecipientEmailAddress
IP	Address	ClickIP
URL	Url	Url
Mail message	NetworkMessageId	NetworkMessageId
Mail message	Recipient	RecipientEmailAddress

Custom details (optional but useful for the playbook):

SenderDomain → SenderFromDomain , MailSubject → Subject , InternetMessageId → InternetMessageId ,
ClickedThrough → IsClickedThrough

Alert details override:

- Name format: Phishing link clicked by {{RecipientEmailAddress}} from {{SenderFromDomain}}
- Description format: Subject: {{Subject}} | Click IP: {{ClickIP}}

Query scheduling:

- Run every: **5 minutes**
- Lookup data from the last: **1 days**

Create incidents from alerts: Enabled

Alert grouping: Enabled

- Group by matching entities: **Account** only
- Time frame: **5 hours**
- Re-open closed incidents: **off**

Deployment notes

- Use the portal-generated ARM template to deploy the rule after it has been tested.
- Keep the query in source control or the runbook so future changes are reviewable.

Microsoft Defender

Search

Home

Find Defender solutions

Home

Cases

Exposure management

Investigation & response

Threat intelligence

Assets

Microsoft Sentinel

Search

Threat management

Content management

Configuration

Tables

Data connectors

Analytics

Summary rules

Watchlist

Automation

Identities

Endpoints

Email & collaboration

Cloud apps

Cloud security

SOC optimization

Reports

Learning hub

Trials

More resources

Analytics

Manage all your rules in one place

Now you can manage all your rules on one page, providing a centralized and streamlined approach to rule management. This enhancement not only simplifies your workflow but also ensures that you can easily access, modify, and oversee all your rules in one convenient location.

Go to unified rules page

Refresh Guides & Feedback Workspace: intern-ws

Rules by severity

High (1) Medium (0) Low (0) Informational (0)

Active rules Rule templates Anomalies

+ Create Analytics workbooks Rule runs (Preview) Enable Disable Delete Import Export

Search by ID, name, tactic or technique Add filter

Severity	Name	Rule type	Status	Tactics	Techniques	Sub techniques	Source
----------	------	-----------	--------	---------	------------	----------------	--------

No analytics rules selected

Select an analytics rule to view more details

Showing 1 to 1 of 1 results.

Microsoft Defender

Search

Home

Find Defender solutions

Home

Cases

Exposure management

Investigation & response

Threat intelligence

Assets

Microsoft Sentinel

Search

Threat management

Content management

Configuration

Tables

Data connectors

Analytics

Summary rules

Watchlist

Automation

Identities

Endpoints

Email & collaboration

Cloud apps

Cloud security

SOC optimization

Reports

Learning hub

Trials

More resources

Analytics

Manage all your rules in one place

Now you can manage all your rules on one page, providing a centralized and streamlined approach to rule management. This enhancement not only simplifies your workflow but also ensures that you can easily access, modify, and oversee all your rules in one convenient location.

Go to unified rules page

Refresh Guides & Feedback Workspace: intern-ws

Rules by severity

High (1) Medium (0) Low (0) Informational (0)

Active rules Rule templates Anomalies

+ Create Analytics workbooks Rule runs (Preview) Enable Disable Delete Import Export

Search by ID, name, tactic or technique Add filter

Severity	Name	Rule type	Status	Tactics	Techniques	Sub techniques	Source
High	Phishing email delivered and URL clicked	S...	Enabled	Initial Access			Custom

Phishing email delivered and URL clicked

Severity: High

Custom Content Source

Enabled Status

Info Insights

Shb17789-263e-431e-a033-f3470ad539

Description

Delivered email with Microsoft impersonation or lure characteristics, and the recipient clicked an allowed link.

MITRE ATT&CK

Initial Access

Credential Access



Rule query



```
let clicks = UnClickEvents
| where IngestionTime() > ago(10m)
| where ActionType in ("ClickAllowed", "ClickAllowed")
| project ClickTime = TimeGenerated, Network
EmailEvents
```



Rule frequency



Run query every 5 minutes


Edit











Analytic rule ARM template:

```
{
  "$schema": "https://schema.management.azure.com/schemas/2019-04-01/deploymentTemplate.json#",
  "contentVersion": "1.0.0.0",
  "parameters": {
    "workspace": {
      "type": "String"
    }
  },
  "resources": [
    {
      "id": "[concat(resourceId('Microsoft.OperationalInsights/workspaces/providers', parameters('workspace'), 'Microsoft.SecurityInsights'), '/alertRules/5be17789-263e-431e-a033-ff3470adf539')]",
      "name": "[concat(parameters('workspace'), '/Microsoft.SecurityInsights/5be17789-263e-431e-a033-ff3470adf539')]",
      "type": "Microsoft.OperationalInsights/workspaces/providers/alertRules",
      "kind": "Scheduled",
      "apiVersion": "2023-12-01-preview",
      "properties": {
```

```

        "displayName": "Phishing email delivered and URL clicked",
        "description": "Delivered email with Microsoft impersonation or lure characteristics, and the recipient clicked an allowed link.",
        "severity": "High",
        "enabled": true,
        "query": "let clicks = UrlClickEvents\n    | where ingestion_time() > ago(10m)\n    | where ActionType in (\"ClickAllowed\", \"ClickAllowedByTenantPolicy\")\n    | project ClickTime = TimeGenerated, NetworkMessageId, AccountUpn = tolower(AccountUpn), Url, ClickAction = ActionType, ClickIP = IPAddress, IsClickedThrough;\nEmailEvents\n| where TimeGenerated > ago(1d)\n| where UrlCount > 0 and DeliveryAction == \"Delivered\"\n| extend Auth = parse_json(AuthenticationDetails)\n| extend AuthFail = tostring(Auth.SPF) !~ \"pass\" or tostring(Auth.DKIM) !~ \"pass\" or tostring(Auth.DMARC) !~ \"pass\"\n| extend LegitMs = SenderFromDomain matches regex @\"(?:)(^|\\.)(microsoft|office365|microsoftonline|azure|windows|outlook|live|sharepoint|office)\\.?(com|net)$\"\n| extend Impersonation = not(LegitMs) and SenderFromDomain matches regex @\"(?:)(microsoft|office365|azure|outlook|sharepoint|onedrive)\\.?\"\n| extend BadTld = SenderFromDomain matches regex @\"(?:)\\.?(xyz|top|click|online|tech|site|info)$\"\n| extend Lure = Subject has_any (\"verify\", \"suspended\", \"deactivated\", \"expired\", \"compromised\", \"password\", \"action required\", \"credential\")\n| where Impersonation or (AuthFail and BadTld) or (AuthFail and Lure) or (BadTld and Lure)\n| extend Recipient = tolower(RecipientEmailAddress)\n| join kind=inner clicks on NetworkMessageId, $left.Recipient == $right.AccountUpn\n| project TimeGenerated = ClickTime, DeliveredTime = TimeGenerated, RecipientEmailAddress, SenderFromAddress, SenderFromDomain, Subject, Url, ClickAction, ClickIP, IsClickedThrough, AuthFail, Impersonation, BadTld, Lure, NetworkMessageId, InternetMessageId",
        "queryFrequency": "PT5M",
        "queryPeriod": "P1D",
        "triggerOperator": "GreaterThan",
        "triggerThreshold": 0,
        "suppressionDuration": "PT5H",
        "suppressionEnabled": false,
        "startTimeUtc": null,
        "tactics": [
            "InitialAccess",
            "CredentialAccess"
        ]
    }

```

```

],
"techniques": [],
"subTechniques": [],
"alertRuleTemplateName": null,
"incidentConfiguration": {
  "createIncident": true,
  "groupingConfiguration": {
    "enabled": true,
    "reopenClosedIncident": false,
    "lookbackDuration": "PT5H",
    "matchingMethod": "Selected",
    "groupByEntities": [
      "Account"
    ],
    "groupByAlertDetails": [],
    "groupByCustomDetails": []
  }
},
"eventGroupingSettings": {
  "aggregationKind": "AlertPerResult"
},
"alertDetailsOverride": {
  "alertDisplayNameFormat": "Phishing link clicked by {{RecipientEmailAddress}} from {{SenderFromDomain}}",
  "alertDescriptionFormat": "Subject: {{Subject}} | Clicked IP: {{ClickIP}}",
  "alertDynamicProperties": []
},
"customDetails": {
  "SenderDomain": "SenderFromDomain",
  "MailSubject": "Subject",
  "InternetMessageId": "InternetMessageId",
  "ClickedThrough": "IsClickedThrough"
},
"entityMappings": [
  {
    "entityType": "Account",
    "fieldMappings": [
      {
        "identifier": "FullName",
        "columnName": "RecipientEmailAddress"
      }
    ]
  }
]

```

```

    }
  ]
},
{
  "entityType": "IP",
  "fieldMappings": [
    {
      "identifier": "Address",
      "columnName": "ClickIP"
    }
  ]
},
{
  "entityType": "URL",
  "fieldMappings": [
    {
      "identifier": "Url",
      "columnName": "Url"
    }
  ]
},
{
  "entityType": "MailMessage",
  "fieldMappings": [
    {
      "identifier": "NetworkMessageId",
      "columnName": "NetworkMessageId"
    }
  ]
},
{
  "entityType": "MailMessage",
  "fieldMappings": [
    {
      "identifier": "Recipient",
      "columnName": "RecipientEmailAddress"
    }
  ]
}
],
"sentinelEntitiesMappings": null,

```

```

    "templateVersion": null
  }
}
]
}

```

Step 3 - Create the user-reported phishing rule

In **Microsoft Sentinel > Analytics > Create > Scheduled query rule**:

- **Name:** `User-reported phishing email`
- **Description:** A user reported an email as phishing or malware through Defender for Office 365. Enriched with sender, subject, delivery action and URLs.
- **Tactics:** Initial Access
- **Techniques:** T1566
- **Severity:** Medium
- **Status:** Enabled
- Set rule logic

Entity Mapping

Entity	Identifier	Column
Account	FullName	<code>ReporterUpn</code>
Mail message	NetworkMessageId	<code>NetworkMessageId</code>
Mail message	Recipient	<code>ReporterUpn</code>

Custom details

Key	Column
SenderAddress	<code>SenderFromAddress</code>
MailSubject	<code>Subject</code>
DeliveryAction	<code>DeliveryAction</code>
ThreatTypes	<code>ThreatTypes</code>
Urls	<code>Urls</code>
InternetMessageId	<code>InternetMessageId</code>
AlertSeverity	<code>AlertSeverity</code>

Alert details override

- Name format: `User-reported phish: {{Subject}} (reported by {{ReporterUpn}})`

- Description format: `Sender: {{SenderFromAddress}} | Delivery: {{DeliveryAction}}`

Query scheduling

- Run every: **5 minutes**
- Lookup data from the last: **1 day**

Alert threshold: generate an alert when the number of results is **greater than 0**.

Event grouping: *Trigger an alert for each event.*

Suppression: off.


Create incidents from alerts: Enabled



Alert grouping: Enabled

- Group by matching entities: **Mail message** only
- Time frame: **5 hours**
- Re-open closed incidents: **off**

Deployment notes

- Use the portal-generated ARM template to deploy the rule after it has been tested.
- Keep the query in source control or the runbook so future changes are reviewable.





Microsoft Defender

Search

Find Defender solutions

Home

Cases 4 New

Exposure management

Investigation & response

Threat intelligence

Assets

Microsoft Sentinel

Search

Threat management

Content management

Configuration

Tables

Data connectors

Analytics

Summary rules

Watchlist

Automation

Identities

Endpoints

Email & collaboration

Cloud apps

Cloud security

SOC optimization

Reports

Learning hub

Trials

More resources

Analytics > Analytics rule wizard

Analytics rule wizard - Create a new Scheduled rule

General

Set rule logic

Incident settings

Automated response

Review + create

Alert Name Format

User-reported phish: {Subject} (reported by {ReporterUpn})

Alert Description Format

Sender: {SenderFromAddress} | Delivery: {DeliveryAction}

+ Add new property override

Query scheduling

Run query every *

5 Minutes

Lookup data from the last *

1 Days

Start running

☒ Automatically

☐ At specific time (Preview)

9/30/2026 12:00 PM

Starting automatically, the rule will run every 5 minutes, looking up data from last 1 days.

Alert threshold

Generate alert when number of query results *

Is greater than 0

Event grouping

< Previous

Next : Incident settings >

Cancel

Microsoft Defender

Search

Find Defender solutions

Home

Cases 4 New

Exposure management

Investigation & response

Threat intelligence

Assets

Microsoft Sentinel

Search

Threat management

Content management

Configuration

Tables

Data connectors

Analytics

Summary rules

Watchlist

Automation

Identities

Endpoints

Email & collaboration

Cloud apps

Cloud security

SOC optimization

Reports

Learning hub

Trials

More resources

Analytics > Analytics rule wizard

Analytics rule wizard - Create a new Scheduled rule

General

Set rule logic

Incident settings

Automated response

Review + create

Event grouping

Configure how rule query results are grouped into alerts

☐ Group all events into a single alert

☒ Trigger an alert for each event

A single analytics rule can generate up to 150 alerts. If you choose "trigger an alert for each event" and the rule query returns more than 150 events, the rule will generate 150 alerts, and the last alert will include a summary of all the events.

Suppression

Stop running query after alert is generated

☐ Off

Results simulation

This chart shows the results of the last 50 evaluations of the defined analytics rule. Click a point on the chart to display the raw events for that point in time.



Test with current data



Define a valid analytics rule configuration and click "Test with current data" to test your rule with current data in your workspace

< Previous

Next : Incident settings >

Cancel





Analytic rule ARM template:

```
{
  "$schema": "https://schema.management.azure.com/schemas/2019-04-01/deploymentTemplate.json#",
```

```

"contentVersion": "1.0.0.0",
"parameters": {
  "workspace": {
    "type": "String"
  }
},
"resources": [
  {
    "id": "[concat(resourceId('Microsoft.OperationalInsights/workspaces/providers', parameters('workspace'), 'Microsoft.SecurityInsights'), '/alertRules/6ab741fc-e30e-4f77-9a93-27a7e777120f')]",
    "name": "[concat(parameters('workspace'), '/Microsoft.SecurityInsights/6ab741fc-e30e-4f77-9a93-27a7e777120f')]",
    "type": "Microsoft.OperationalInsights/workspaces/providers/alertRules",
    "kind": "Scheduled",
    "apiVersion": "2023-12-01-preview",
    "properties": {
      "displayName": "User-reported phishing email",
      "description": "A user reported an email as phishing or malware through Defender for Office 365. Enriched with sender, subject, delivery action and URLs.",
      "severity": "Medium",
      "enabled": true,
      "query": "let ReportedPhishAlerts = AlertInfo\n    | where ingestion_time() > ago(10m)\n    | where ServiceSource == \"Microsoft Defender for Office 365\"\n    | where Title has_any (\"Email reported by user as malware or phish\", \"User reported\", \"reported message\")\n    | summarize arg_max(TimeGenerated, *) by AlertId\n    | project AlertId, AlertTitle = Title, AlertSeverity = Severity, DetectionSource, AlertTime = TimeGenerated;\n    let AlertIds = ReportedPhishAlerts | project AlertId;\n    let Evidence = AlertEvidence\n    | where TimeGenerated > ago(47h)\n    | where AlertId in (AlertIds);\n    let ReporterInfo = Evidence\n    | where EntityType == \"User\" and isnotempty(AccountUpn)\n    | summarize ReporterUpn = make_set(tolower(AccountUpn), 5) by AlertId;\n    let MessageIds = Evidence\n    | where isnotempty(NetworkMessageId)\n    | summarize NetworkMessageId = take_any(NetworkMessageId) by AlertId;\n    let UrlInfo = Evidence\n    | where isnotempty(RemoteUrl)\n    | summarize Urls = tostring(make_set(RemoteUrl, 20)) by AlertId;\n    let MailContext = EmailEvents\n    | where TimeGenerated > ago(1d)\n    | summarize arg_max(TimeGenerated, SenderFromAddress, Subject, DeliveryAction) by AlertId;
    }
  }
]

```

```

n, ThreatTypes, InternetMessageId)\n          by NetworkMessageId, Recipient = tolower(RecipientEmailAddress);\nReportedPhishAlerts\n| join kind=inner ReporterInfo on AlertId\n| join kind=inner MessageIds on AlertId\n| join kind=leftouter UrlInfo on AlertId\n| mv-expand ReporterUpn to typeof(string)\n| join kind=leftouter MailContext on NetworkMessageId, $left.ReporterUpn == $right.Recipient\n| project TimeGenerated = AlertTime, AlertId, AlertTitle, AlertSeverity, ReporterUpn,\nSenderFromAddress, Subject, DeliveryAction, ThreatTypes, Urls, NetworkMessageId, InternetMessageId",
    "queryFrequency": "PT5M",
    "queryPeriod": "P1D",
    "triggerOperator": "GreaterThan",
    "triggerThreshold": 0,
    "suppressionDuration": "PT5H",
    "suppressionEnabled": false,
    "startTimeUtc": null,
    "tactics": [
        "InitialAccess"
    ],
    "techniques": [],
    "subTechniques": [],
    "alertRuleTemplateName": null,
    "incidentConfiguration": {
        "createIncident": true,
        "groupingConfiguration": {
            "enabled": true,
            "reopenClosedIncident": false,
            "lookbackDuration": "PT5H",
            "matchingMethod": "Selected",
            "groupByEntities": [
                "MailMessage"
            ],
            "groupByAlertDetails": [],
            "groupByCustomDetails": []
        }
    },
    "eventGroupingSettings": {
        "aggregationKind": "AlertPerResult"
    },
    "alertDetailsOverride": {
        "alertDisplayNameFormat": "User-reported phish: {{S

```

```

    subject}} (reported by {{ReporterUpn}})",
    "alertDescriptionFormat": "Sender: {{SenderFromAddress}} | Delivery: {{DeliveryAction}}",
    "alertDynamicProperties": [],
  },
  "customDetails": {
    "SenderAddress": "SenderFromAddress",
    "MailSubject": "Subject",
    "DeliveryAction": "DeliveryAction",
    "ThreatTypes": "ThreatTypes",
    "Urls": "Urls",
    "InternetMessageId": "InternetMessageId",
    "AlertSeverity": "AlertSeverity"
  },
  "entityMappings": [
    {
      "entityType": "Account",
      "fieldMappings": [
        {
          "identifier": "FullName",
          "columnName": "ReporterUpn"
        }
      ]
    },
    {
      "entityType": "MailMessage",
      "fieldMappings": [
        {
          "identifier": "NetworkMessageId",
          "columnName": "NetworkMessageId"
        }
      ]
    },
    {
      "entityType": "MailMessage",
      "fieldMappings": [
        {
          "identifier": "Recipient",
          "columnName": "ReporterUpn"
        }
      ]
    }
  ]
}

```

```

    },
    "sentinelEntitiesMappings": null,
    "templateVersion": null
  }
}
]
}

```

3 - Response: Delete the phishing email from the user's mailbox

This section builds the playbook `PB-UnwantedMail-Response`. In this version it implements **one response action: soft delete the phishing email from the user's mailbox**. Other actions from the workbook (password reset, MFA check, full scan, location block, sender block, ticket) are added later and documented when they are built.

3.1 What the playbook does

```

Sentinel creates an incident from the phishing rule
-> Automation rule starts the playbook
-> Get the user (account entity) and build the UPN
-> Keep only the mail-message entities that have a NetworkMessageId
-> Build a list of { NetworkMessageId, recipient }
-> Soft delete every message in the list through the Defender remediation API

```

Soft delete moves the message to the user's **Deleted Items** (recoverable). The remediation is asynchronous, so the result is confirmed in the Defender **Action center**.

3.2 Design

Node	Type	Purpose
Microsoft Sentinel incident	Trigger	Starts on incident creation and passes in the incident, including <code>relatedEntities</code> .
Entities - Get_Accounts	Sentinel action	Extracts the user account from the incident.
Initialize variables (UserUpn)	Variable	Builds the UPN, for example <code>aymantestuser@gbgss.life</code> .
Filter Mail Entities	Filter array	Keeps only mail entities that carry a <code>networkMessageId</code> .
Build Delete List	Select	Turns each mail entity into <code>{ networkMessageId, recipientEmailAddress }</code> .

Node	Type	Purpose
Soft Delete Mail	HTTP	Sends the list to the Graph <code>analyzedEmails/remediate</code> API with <code>softDelete</code> .

Why the recipient comes from `UserUpn`. The analytic rule maps `NetworkMessageId` and `Recipient` as two separate Mail message entities, so the entities that carry a message ID have no recipient. The incident's account is the recipient, so the playbook uses `UserUpn`.

Why a list. The incident groups by Account, so one incident can hold several phishing emails for the same user. The remediation API accepts an array, so all of them are deleted in one call.

3.3 Who can do what

Task	Permission needed by the implementer
Create the Logic App	Contributor on the resource group
Assign Azure roles (Step 2A)	Role Based Access Control Administrator , User Access Administrator , or Owner on the resource group. Contributor is not enough .
Automation → Configure permissions button	Owner on the playbook resource group. If unavailable, use the CLI command in Step 2A.
Grant the Graph app role (Step 2B)	Privileged Role Administrator or Global Administrator

3.4 Step 1 - Create the Logic App

1. In the Azure portal, go to **Logic apps** → **Create** → **Consumption**.
2. Choose the resource group, name it `PB-UnwantedMail-Response`, and create it.
3. Open it and go to **Settings** → **Identity** → **System assigned**. Set **Status** to **On** and save.
4. Copy the **Object (principal) ID**. You need it in Step 2.

Microsoft Azure

Search resources, services, and docs (G+/)

Copilot

muhammad.fathy@gbg... (gbgss security (gbgss-lbf))

Home > Logic apps

Create Logic App

Select a hosting option

These hosting plans determine the resource allocation, scaling and pricing for your app. [Learn more about Logic App hosting options](#)

	Consumption	Standard			Automation Project (preview)
Hosting plans	Multi-tenant ☒ Fully managed and easy to get started.	Workflow Service Plan ☐ Single tenant runtime with in-app connectors and scaling features.	App Service Environment V3 ☐ Single tenant runtime with full isolation and scale out feature across App Service plans.	Hybrid ☐ Local processing and multi-cloud support with Kubernetes Event-Driven Autoscaling.	Managed ☐ Fully managed and easy to get started.
Compute	Shared	Dedicated	Dedicated	Customer managed	Dedicated
Networking	Public cloud	VNET Integration	VNET Integration	Local network access	VNET Integration
Pricing	Pay-per-operation	Per workflow service plan instance	Per App Service for App Service Environment instance	Per vCPU hour of Kubernetes cluster	Base + per vCPU second with scale to zero

Select

Microsoft Azure

Search resources, services, and docs (G+/)

Copilot

muhammad.fathy@gbg... (gbgss security (gbgss-lbf))

Home > Logic apps > Create Logic App

Create Logic App (Multi-tenant)

Basics Tags Review + create

Create a logic app, which lets you group workflows as a logical unit for easier management, deployment and sharing of resources. Workflows let you connect your business-critical apps and services with Azure Logic Apps, automating your workflows without writing a single line of code.

Project Details

Select a subscription to manage deployed resources and costs. Use resource groups like folders to organize and manage all your resources.

Subscription ☐ **Microsoft Azure Sponsorship - 13 - GbgSS Security**

Resource Group ☐ **muhammad-RG** [Create new](#)

Instance Details

Logic App name ☐ **ayman-PB-UnwantedMail-Response**

Region ☐ **Sweden Central**

Enable log analytics ☒ Yes ☐ No

Log Analytics workspace ☐ **intern-WS**

Workflow Type

☒ **Stateful**


☐ **Conversational Agents (Preview)**: Stateful workflows that use AI agents to complete tasks through chat interactions or other agents. Not supported in the selected region.

☐ **Autonomous Agents (Preview)**: Stateful workflows that use AI agents to complete tasks and can start from any trigger, such as an event, schedule, or API call. Not supported in the selected region.

Review + create

< Previous

Next: Tags >



3.5 Step 2 - Permissions

2A. Azure roles (Azure portal or CLI)

Open the resource, then **Access control (IAM)** → **Add** → **Add role assignment**. Pick the role, then choose the assignee on the **Members** tab.


Role	Add it on	Assign to	Members tab
Microsoft Sentinel Responder	Sentinel workspace	Logic App identity	<i>Managed identity</i> → <i>Logic app</i> → your Logic App
Microsoft Sentinel Automation Contributor	The playbook's resource group	Azure Security Insights (the Sentinel service)	<i>User, group, or service principal</i> → search "Azure Security Insights"

The Automation Contributor assignment fixes the **Missing permissions** label on the incident's Run playbook pane. CLI equivalent:

```
SP=$(az ad sp list --display-name "Azure Security Insights" --query "[0].id" -o tsv)
az role assignment create --assignee-object-id $SP --assignee-principal \
  -type ServicePrincipal \
  --role "Microsoft Sentinel Automation Contributor" \
```

```
--scope /subscriptions/<subscription-id>/resourceGroups/<playbook-resource-group>
```

New assignments can take a few minutes to take effect.



2B. Graph permission (PowerShell only)

The portal has no button for granting app roles to a managed identity. Run this in **Cloud Shell** → **PowerShell**. It runs as your signed-in identity, so it needs **Privileged Role Administrator** or **Global Administrator**.

Identity	API	Permission	Used for
Logic App	Microsoft Graph	<code>SecurityAnalyzedMessage.ReadWrite.All</code>	Soft delete the mail


```
Connect-MgGraph -Scopes "AppRoleAssignment.ReadWrite.All","Application.Read.All"
```

```
$mi = "<Logic App managed identity object ID>"
$graph = Get-MgServicePrincipal -Filter "appId eq '00000003-0000-0000-c000-000000000000'"
$role = $graph.AppRoles | Where-Object { $_.Value -eq "SecurityAnalyzedMessage.ReadWrite.All" }
New-MgServicePrincipalAppRoleAssignment -ServicePrincipalId $mi -Princi
```

```
palId $mi `
-ResourceId $graph.Id -AppRoleId $role.Id
```

To verify: **Entra ID** → **Enterprise applications**, filter **Application type: Managed identities**, open the identity, and check **Permissions**. No **Mail.ReadWrite** permission is needed.

```
Microsoft Azure
Switch to Bash Restart Manage files New session Editor Open in VS Code for the Web Web preview Settings Help
Requesting a Cloud Shell.Succeeded.
Connecting terminal...
Welcome to Azure Cloud Shell
Type "az" to use Azure CLI
Type "help" to learn about Cloud Shell
Your Cloud Shell session will be ephemeral so no files or system changes will persist beyond your current session.
MOTD: You can now copy & paste in Cloud Shell using Ctrl+C/Ctrl+V (Linux/Windows) or Cmd+C/Cmd+V (Mac)! Learn more: https://aka.ms/cloudshell/copy-paste
VERBOSE: Authenticating to Azure ...
PS /home/muhammad> Connect-MgGraph -Scopes "AppRoleAssignment.ReadWrite.All","Application.Read.All"
To sign in, use a web browser to open the page https://login.microsoft.com/device and enter the code DMWP524R6 to authenticate.
Welcome to Microsoft Graph!
Connected via delegated access using 14d82eec-204b-4c2f-b7e8-296a70dab67e
Readme: https://aka.ms/graph/sdk/powershell
SDK Docs: https://aka.ms/graph/sdk/powershell/docs
API Docs: https://aka.ms/graph/docs
NOTE: You can use the -NoWelcome parameter to suppress this message.
NOTE: Sign in by Web Account Manager (WAM) is enabled by default on Windows systems and cannot be disabled when using the default ClientId.
To disable WAM run Set-MgGraphOption -DisableLoginByWAM $true and then use a custom ClientId.
PS /home/muhammad>
PS /home/muhammad> $mi = " "
PS /home/muhammad> $graph = Get-MgServicePrincipal -Filter "appId eq '00000003-0000-0000-c000-000000000000'"
PS /home/muhammad> $role = $graph.AppRoles | Where-Object { $_.Value -eq "SecurityAnalyzedMessage.ReadWrite.All" }
PS /home/muhammad> New-MgServicePrincipalAppRoleAssignment -ServicePrincipalId $mi -PrincipalId $mi `
>> -ResourceId $graph.Id -AppRoleId $role.Id
DeletedDateTime Id AppRoleId CreatedDateTime PrincipalDisplayName PrincipalId PrincipalType Res
our
ceID
isp
lay
Nam
e
-----
9MDav8uw-0mK8f5e-Squ6ZSMLFKL1etFpCX9n6lgZ4o 04c55753-2244-4c25-87fc-704ab82a4f69 9/30/2026 9:08:26 AM ayman-PB-UnwantedMail-Response ServicePrincipal Mi...
PS /home/muhammad>
```



3.6 Step 3 - Build the workflow

Open the Logic App and go to **Development Tools** → **Logic app designer**.


Entering values and expressions in the designer

Most values below are **expressions**, not dynamic content tokens.

1. Click the field. A popup opens with **Dynamic content** and **Expression** tabs (in the newer designer, click **fx**).
2. Open the **Expression** tab, type the formula, and click **Add**. It appears as an **fx** chip.
3. **Do not type a leading @ or @{ }** in the **Expression** tab. Those are how the value looks in **Code view**. The only exception is the Filter array's **Edit in advanced mode** box, which expects the leading **@**.
4. In a longer field (a URI or JSON body), type the text, then add a token or an expression where the value goes.

3.6.1 Trigger

1. **Add a trigger**, search **Microsoft Sentinel**, choose **Microsoft Sentinel incident**.
2. Connect with **managed identity**.



3.6.2 Entities: the user


1. **+ → Add an action → Microsoft Sentinel → Entities - Get Accounts.** In **Entities list**, choose the **Entities** dynamic content from the trigger.
2. Add **Initialize variable**. **Name:** `UserUpn`. **Type:** String.
3. Click **Value**, open the **Expression** tab, enter this, and click **Add**:


```
concat(first(body('Entities_-_Get_Accounts')?['Accounts'])?['Name'], '@', first(body('Entities_-_Get_Accounts')?['Accounts'])?['UPNSuffix'])
```

Sentinel splits a UPN into `Name` and `UPNSuffix`, so the expression joins them. `first()` is safe because the rule groups incidents by Account, so there is one account per incident.

To confirm, run the playbook once and open **Run history** → **Initialize variable**. The variable shows the real UPN, for example:

```
[
  { "name": "UserUpn", "type": "String", "value": "aymantestuser@gbgss.life" }
]
```





3.6.3 Entities: the mail messages


There is no "Entities - Get Mail Messages" action, so the mail entities are read from the trigger. The trigger output confirms the entity list at `triggerBody()?['object']?['properties']?['relatedEntities']`, with entity `kind` values `MailMessage`, `Ip`, `Account`, and `Url`.

1. Add **Data Operations** → **Filter array** and rename it `Filter_Mail_Entities`.

- **From:** open the **Expression** tab, enter `triggerBody()?['object']?['properties']?['relatedEntities']`, and click **Add**.
- **Condition:** click **Edit in advanced mode** and enter:

```
@and(equals(toLower(item()?['kind']), 'mailmessage'), not(empty(item()?['properties']?['networkMessageId'])))
```

This keeps entities that are mail messages **and** carry a message ID, and drops the recipient-only entity. In the test incident it returns 3 items.




2. Add **Data Operations** → **Select** and rename it **Build_Delete_List**.

- **From:** open **Dynamic content** and pick the Filter array's **Body**.
- **Map:** add two key/value rows, entering each value in the **Expression** tab:

Key	Value
networkMessageId	item()?['properties']['networkMessageId']
recipientEmailAddress	variables('UserUpn')

Save and re-run. The Select output should look like this:

```
[
  { "networkMessageId": "bfa7227b-83e5-487a-1d09-08df1e0509db", "recipientEmailAddress": "aymantestuser@gbgss.life" },
  { "networkMessageId": "8642fa99-dcc2-474e-4c17-08df1e01438b", "recipientEmailAddress": "aymantestuser@gbgss.life" },
  { "networkMessageId": "8cc282b1-9b64-4406-1715-08df1e0b9d9c", "recipientEmailAddress": "aymantestuser@gbgss.life" }
]
```



3.6.4 Soft delete the mail

Add an **HTTP** action and rename it **Soft Delete Mail**.

Field	Value
Method	POST
URI	https://graph.microsoft.com/v1.0/security/collaboration/analyzedEmails/remediate
Headers	Content-Type = application/json
Authentication type	Managed identity
Managed identity	System-assigned managed identity
Audience	https://graph.microsoft.com

Body. Paste the JSON, then delete `@{body('Build_Delete_List')}` and insert the Select action's **Output** from **Dynamic content** in its place. Keep it **outside any quotes**, so the array is sent as JSON:

```
{
  "displayName": "PB-UnwantedMail",
  "description": "Soft delete phishing mail",
  "severity": "high",
  "action": "softDelete",
}
```

```

    "remediateSendersCopy": false,
    "analyzedEmails": @{body('Build_Delete_List')}
  }

```

A **2xx** response means the request was accepted. Remediation is asynchronous, so confirm the result in **Defender** → **Actions & submissions** → **Action center**.

Click **Save**.

The screenshot displays the Microsoft Azure Logic App Designer interface for a workflow named "ayman-PB-UnwantedMail-Response". The workflow is in the "Workflow" view and consists of the following steps:

- Microsoft Sentinel Incident
- Entities - Get Accounts
- Initialize variables (UserUpn)
- Filter Mail Entities
- Build Delete List
- Soft Delete Mail



The "Soft Delete Mail" step is expanded, showing its configuration:

- URI:** `https://graph.microsoft.com/v1.0/security/collaboration/analyze/dEmails/remediate`
- Method:** POST
- Headers:** Content-Type: application/json
- Body:**

```

{
  "displayName": "ayman-PB-UnwantedMail-Response",
  "description": "Soft delete phishing mail",
  "severity": "high",
  "action": "softDelete",
  "remediateSendersCopy": false,
  "analyzedEmails": Output
}

```
- Authentication:** Managed identity



3.6.5 Code view reference

The same workflow as JSON, for checking against the designer. In **Logic app code view**, `"analyzedEmails": "@body('Build_Delete_List')"` in quotes is correct, because a whole-string expression returns the array itself.

```

{
  "definition": {
    "metadata": {
      "notes": {}
    },
    "$schema": "https://schema.management.azure.com/providers/Microsoft.Logic/schemas/2016-06-01/workflowdefinition.json#",
    "contentVersion": "1.0.0.0",
    "triggers": {
      "Microsoft_Sentinel_incident": {
        "type": "ApiConnectionWebhook",
        "inputs": {
          "host": {
            "connection": {
              "name": "@parameters('$connections')['azure sentinel']['connectionId']"
            }
          },
          "body": {
            "callback_url": "@listCallbackUrl()"
          },
          "path": "/incident-creation"
        }
      }
    },
    "actions": {
      "Entities_-_Get_Accounts": {
        "runAfter": {},
        "type": "ApiConnection",
        "inputs": {
          "host": {
            "connection": {
              "name": "@parameters('$connections')['azure sentinel']['connectionId']"
            }
          },
          "method": "post",
          "body": "@triggerBody()?['object']?['properties']?['relatedEntities']",
          "path": "/entities/account"
        }
      }
    }
  }
}

```

```

    },
    "Initialize_variables_(UserUpn)": {
      "runAfter": {
        "Entities_-_Get_Accounts": [
          "Succeeded"
        ]
      },
      "type": "InitializeVariable",
      "inputs": {
        "variables": [
          {
            "name": "UserUpn",
            "type": "string",
            "value": "@{concat(first(body('Entities_-_Get_Accounts'))?['Accounts'])?['Name'],'@',first(body('Entities_-_Get_Accounts'))?['Accounts'])?['UPNSuffix']}"
          }
        ]
      }
    },
    "Filter_Mail_Entities": {
      "runAfter": {
        "Initialize_variables_(UserUpn)": [
          "Succeeded"
        ]
      },
      "type": "Query",
      "inputs": {
        "from": "@triggerBody()?['object']?['properties']?['relatedEntities']",
        "where": "@and(equals(toLower(item()?['kind']),'mailmessage'),not(empty(item()?['properties']?['networkMessageId'])))"
      }
    },
    "Build_Delete_List": {
      "runAfter": {
        "Filter_Mail_Entities": [
          "Succeeded"
        ]
      },
    },

```

```

        "type": "Select",
        "inputs": {
            "from": "@body('Filter_Mail_Entities')",
            "select": {
                "networkMessageId": "@item()?['properties']['networkMessageId']",
                "recipientEmailAddress": "@variables('UserUp
n')"
            }
        },
        "Soft_Delete_Mail": {
            "runAfter": {
                "Build_Delete_List": [
                    "Succeeded"
                ]
            },
            "type": "Http",
            "inputs": {
                "uri": "https://graph.microsoft.com/v1.0/security/collaboration/analyzedEmails/remediate",
                "method": "POST",
                "headers": {
                    "Content-Type": "application/json"
                },
                "body": {
                    "displayName": "ayman-PB-UnwantedMail-Response",
                    "description": "Soft delete phishing mail",
                    "severity": "high",
                    "action": "softDelete",
                    "remediateSendersCopy": false,
                    "analyzedEmails": "@body('Build_Delete_List')"
                },
                "authentication": {
                    "type": "ManagedServiceIdentity",
                    "audience": "https://graph.microsoft.com"
                }
            },
            "operationOptions": "DisableAsyncPattern",
            "runtimeConfiguration": {

```

```

        "contentTransfer": {
            "transferMode": "Chunked"
        }
    },
    "outputs": {},
    "parameters": {
        "$connections": {
            "type": "Object",
            "defaultValue": {}
        }
    },
    "parameters": {
        "$connections": {
            "type": "Object",
            "value": {
                "azuresentinel": {
                    "id": "/subscriptions/a5412fa2-4452-4fdb-b6fe-efbfa4f4df81/providers/Microsoft.Web/locations/swedencentral/managedApis/azuresentinel",
                    "connectionId": "/subscriptions/a5412fa2-4452-4fdb-b6fe-efbfa4f4df81/resourceGroups/muhammad-RG/providers/Microsoft.Web/connections/azuresentinel",
                    "connectionName": "azuresentinel",
                    "connectionProperties": {
                        "authentication": {
                            "type": "ManagedServiceIdentity"
                        }
                    }
                }
            }
        }
    }
}

```

3.7 Step 4 - Create the automation rule


Under **Sentinel** → **Automation** → **Create** → **Automation rule**:


1. **Trigger**: When incident is created.

2. **Condition:** Analytic rule name **Contains** `Phishing email delivered and URL clicked`.
3. **Actions:** Run playbook → `PB-UnwantedMail-Response`.
4. Save.

If the playbook shows "**Missing permissions**" in the Run playbook pane, Sentinel has no role on the playbook's resource group. Either open **Automation** → **Settings** → **Configure permissions**, tick the resource group and **Apply** (needs Owner), or assign **Microsoft Sentinel Automation Contributor** to **Azure Security Insights** with the CLI in Step 2A.



To run it manually, open an incident and click **Actions** → **Run playbook**. Manual runs require Logic App Contributor or the Sentinel Playbook Operator role on the resource group.





3.8 Step 5 - Test

1. Use a **lab user** and a **lab mailbox**. The delete is real, although soft delete is recoverable from Deleted Items.
2. Open an incident created by the phishing rule (it needs mail entities). Click **Actions** → **Run playbook** and choose **PB-UnwantedMail-Response**.
3. Open the Logic App **Run history** → **latest run** and check:
 - **Initialize_variables_(UserUpn)** shows the real UPN.
 - **Filter_Mail_Entities** returns the mail entities that have a message ID.
 - **Build_Delete_List** returns one object per message.
 - **Soft_Delete_Mail** **Inputs** shows the full **analyzedEmails** array, and **Outputs** shows a **2xx** status.
4. After a minute or two, confirm the messages appear in **Defender** → **Actions & submissions** → **Action center** and in the user's **Deleted Items**.



3.9 Troubleshooting

Symptom	Likely cause and fix
Missing permissions on the Run playbook pane	Sentinel Automation Contributor is missing on the playbook resource group. See Step 4.

Symptom	Likely cause and fix
Add role assignment button is greyed out	You have Contributor only. Ask for Role Based Access Control Administrator on the resource group.
Sentinel actions return 403	Sentinel Responder is missing for the Logic App identity on the workspace.
<code>Soft_Delete_Mail</code> returns 403	<code>SecurityAnalyzedMessage.ReadWrite.All</code> is not granted to the Logic App identity, or has not propagated yet. Check the identity's Permissions in Enterprise applications.
<code>Soft_Delete_Mail</code> returns 401	The audience is not <code>https://graph.microsoft.com</code> .
<code>Soft_Delete_Mail</code> returns 400	<code>analyzedEmails</code> was sent as text instead of an array. Check the action's Inputs , and use the Select Output chip outside quotes.
<code>Filter_Mail_Entities</code> returns no items	The incident has no mail entities, or <code>kind</code> differs. Check <code>relatedEntities</code> in the trigger output.
<code>body('Entities_-_Get_Accounts')</code> errors	Action name mismatch. Use the exact action name, with spaces replaced by underscores.
"The template language expression is not valid"	A leading <code>@</code> was typed in the Expression tab. Remove it.
A field shows literal <code>@{...}</code> text	The value was pasted as text. Delete it and re-enter it with the Expression tab or a Dynamic content token.

3.10 Current limits

- **No approval step.** The playbook deletes automatically when the automation rule fires. Test on a lab user before enabling it on real incidents.
- **Runs once, at incident creation.** Emails that join the incident later (grouping window is 5 hours) are not deleted unless the automation rule also triggers on incident updates.
- **Recipient is the incident's account.** For the phishing click rule this is the recipient who clicked. For the user-reported rule it is the reporter, so only the reporter's copy is deleted.
- `recipientEmailAddress` **uses the UPN.** This works when the UPN equals the mailbox address.