```
# -*- coding: utf-8 -*-
111111
Created on Tue May 10 18:05:25 2022
@author: Asus
import cv2 as cv
import numpy as np
import matplotlib.pyplot as plt
import math
def clip(img):
  m = img.shape[0]
  n = img.shape[1]
  for i in range(m):
    for j in range(n):
      if img[i][j] > 255:
        img[i][j] = 255
      if img[i][j] < 0:
        img[i][j] = 0
  return img.astype(np.float32)
path = "C:/Users/Asus/imagelab/Image-Processing-and-Computer-Vision-Lab/Lab 2/Prewitt/input.jpg"
img = cv.imread(path)
img = cv.cvtColor(img,cv.COLOR_BGR2GRAY)
```

```
plt.imshow(img,'gray')
plt.title("Input for Robert: ")
plt.show()
kernel_v = np.array(([1,0],[0,-1]),np.float32)
kernel_h = np.array(([0,1],[-1,0]),np.float32)
k_s = kernel_h.shape[0]
a = kernel_h.shape[0] // 2
b = kernel_h.shape[1] // 2
m = img.shape[0]
n = img.shape[1]
op_v = np.zeros((m,n),np.float32)
op_h = np.zeros((m,n),np.float32)
for i in range(m):
  for j in range(n):
    for x in range(-a,a+1):
      for y in range(-b,b+1):
         if i-x>=0 and i-x<m and j-y>=0 and j-y<n and x+a>=0 and x+a<k_s and y+b>=0 and y+b<k_s:
           op_v[i][j]+=kernel_v[x+a][y+b]*img[i-x][j-y]
```

```
else:
           op_v[i][j]+=0
plt.imshow(op_v,'gray')
plt.title("Vertical raw output:")
plt.show()
op_v = clip(op_v)
plt.imshow(op_v,'gray')
plt.title("Vertical clipped output:")
plt.show()
for i in range(m):
  for j in range(n):
    for x in range(-a,a+1):
      for y in range(-b,b+1):
         if i-x>=0 and i-x<m and j-y>=0 and j-y<n and x+a>=0 and x+a<k_s and y+b>=0 and y+b<k_s:
           op_h[i][j]+=kernel_h[x+a][y+b]*img[i-x][j-y]
         else:
           op_v[i][j]+=0
plt.imshow(op_h,'gray')
plt.title("Horizontal raw output:")
plt.show()
op_h = clip(op_h)
plt.imshow(op_h,'gray')
```

```
plt.title("Horizontal clipped output:")
plt.show()
op_v = op_v + op_h
op_v = clip(op_v)
plt.imshow(op_v,'gray')
plt.title("Added clipped output:")
plt.show()
img = img+op_v
img = clip(img)
plt.imshow(img,'gray')
plt.title("Enhanced output:")
plt.show()
```