L2: C for High Performance

M. Jam, P. de Oliveira Castro
October 2, 2025

Master Calcul Haute Performance et Simulation - GLHPC | UVSQ

1. C for High Performance

2. Managing Memory

3. Compilation & Assembly

4. Parallelism Basics

C for High Performance

Programming occurs at several abstraction levels from the hardware

Figure 1: Hardware to Software layers
(https://www.startertutorials.com/blog/basic-software-concepts.html)

- Layers close to metal are harder to program...
  - But they offer maximum control and performance
- High-level abstraction maximize productivity...
  - But have significant overhead, less control over performance

In practice; we often combine multiple languages

- C for performance critical sections, python for higher level APIs

Figure 2: Hardware to Software layers (Shershakov, Sergey. (2018). Enhancing Efficiency of Process Mining Algorithms with a Tailored Library: Design Principles and Performance Assessment Technical Report. 10.13140/RG.2.2.18320.46084.)

C is a strongly typed imperative language:

```c
int main() {
  int a = 5;
  int b = 10;

  int c = a + b;
  float d = c / a;
  float e = (float)c / a;

  int f = a * a * a * a;

  return 0;
}
```

`main` is the program entry point.

```c
#include <stdio.h> // For printf(...)

int sum_and_square(int a, int n) {
  int tmp = a + n;
  return tmp * tmp;
}

int main() {
  int a = 5;
  int b = 4;
  int c = sum_and_square(a, b);
  int d = sum_and_square(3, 9);

  // Print the result to the console
  printf("(5+4)**2: %d\n", c);
  printf("(3+9)**2: %d\n", d);
  return 0;
}
```

Implementation C de $\sum_{i=1}^{100} i$

```c
#include <stdio.h> // For printf(...)

int sum_range(const int start, const int end) {
  int sum = 0;
  // Consider start = 0; end = 100
  // For i starting at 0; while i <= 100; increment i by one
  for (int i = start; i <= end; i = i + 1) {
    sum += i;
  }
  return sum;
}

int main() {
  printf("Result: %d\n", sum_range(1, 100));
  return 0;
}
```

const qualified variable cannot be modified. This may enable optimizations during compilation.

Numbers of multiple of 3 inside $[0, 99]$ (i.e. $i \mod 3 = 0$)

```c
void count_multiples_of_three() {
  unsigned int count = 0;
  // For i starting at 0; while i < 100; increment i by one
  for (unsigned int i = 0; i < 100; i++) {
    // if i % 3 (Remainder of the integer division) is equal to 0
    if (i % 3 == 0) {
      count++;
    }
  }
  printf("Result: %d\n", count);
}
```

Note

Here we could also do for (unsigned int i = 0; i < 100; i += 3)

```c
int a = 0;
int b = 5;

int* c = &a;
*c = *c + b;
printf("a: %d; b: %d; c: %d\n", a, b , *c);
```

c contains the address of a; so *c = *c + b write in a the sum of a and b.

Adress	Value	Variable
0x004	0	a
0x008	5	b
0x00c	0x004	c
...	...	...

```c
int main() {
  char morpion[9] = {'X', 'O',  '\0',
                     'O', 'X',  '\0',
                     'O', '\0', '\0'};
  morpion[8] = 'X'; // The player clicked on the bottom-right
    cell !
}
```


Figure 3: Morpion layout in memory

Structures are user-defined composite types:

```c
typedef struct {
  char* first_name;
  char* last_name;
  int age;
  float mean_grade;
  char gender;
} Student;
```

```c
Student e1 = {"Dupont", "Pierre", 22, 13, 'm'};
Student e2 = {"Major", "Major", 22, 13.5, 'a'};
Student e3 = {"Martin", "Evelynne", 24, 14, 'f'};

if (e1.mean_grade > 10) {
  printf("(%s %s) is a pretty good student !\n",
         e1.first_name, e1.last_name);
}
```

C has no concept of `class`, `object`, or `method` !

```c
void display_student(Student* s) {
  // s->age is equivalent to (*s).age
  printf("%s %s (%i): %f\n", s->first_name,
                            s->last_name, s->age,
                            s->mean_grade);
}

// We can have arrays of any types !
Student students[3] = {{"Dupont", "Pierre", 22, 13, 'm'}, ...};
for (int i = 0; i < 3; i++)
  display_student(&students[i]);
```


Figure 4: Array of Structure (AoS) layout

In C, we must manually take care of very low level concepts

- We care about data layout, memory addresses, pointers, etc.
- The language doesn't provide linked lists, dynamic arrays, dictionaries, etc.
- No basic algorithms like sorting

On the flip side, we can

- Manually lay out data to maximize efficiency
- Remove any abstractions and overhead to maximize performance
- Generate code that runs as close to the metal as possible
- Optimize our program for the hardware

Consider the following python and C code:

```python
sum = 0
for i in range(ub):
  sum += i
print(sum)
```

```c
unsigned long long sum = 0;
for (unsigned int i = 0; i < ub; i++){
    sum += i;
}
printf("Sum of first %llu integers is: %llu\n", ub, sum);
```

Where ub is a very large number (100 Millions in this example).
Which one is faster, and by how much ?

Results:

- `C` version: 0.024s
- `Python` version: 5.650s

That's a speedup of $\times 235$.

We will see later in this course how this is possible.

Numpy and other libraries

Note that we could use `numpy` or the `sum` python function: but those are actually implemented in `C`!

Managing Memory

In High-level languages

- We operate on abstracted data structures (lists, dictionaries, etc.)
- Memory is managed automatically (allocation, resizing, deallocation)
- We don't care about memory alignment, stack vs. heap, page size, Numa effects, etc.

In C

- We perform directly with primitive data and raw memory
- We are responsible for allocation, layout, and cleanup
- We can only request chunks of raw memory, and fill it however we choose
- This is critical for performance

This low level control is critical for performance; hence we must understand how memory works under the hood !

We can distinguish two types of memory

- Memory automatically allocated by the compiler on **the stack**.
    - Stores variables, functions arguments, etc.
    - Fast but limited in size
- Memory that is (manually) dynamically allocated on **the heap**
    - Must be allocated and freed by the developer !

The kernel (Linux / Windows) allocates **memory pages** and operates at a coarse grain level.
The standard library (`libc`) manipulates pages on a finer scale and provides memory to the user.

```c
#include <time.h> // for time
#include <stdlib.h> // For malloc,  srand, rand

int do_the_thing(int n) {
  // We allocate n numbers
  float* numbers = malloc(sizeof(float) * n);

  // We seed the random number generator
  srand(time(NULL));

  // We generate nsamples random numbers
  for (int i = 0; i < n; i++) {
    numbers[i] = (float) rand() / RAND_MAX; // Generate a number
    in [0, 1]
  }
  ... // Do something complicated here
  free(numbers); // Release memory back to the kernel
  return 0;
}
```

Figure 5: Results of memory allocation

`malloc` returns a pointer to the beginning of the allocated memory range

Managing Memory - Deallocation

Memory is not infinite !

In Python (and Java, C#, etc.); memory is managed by the garbage collector (GC):

- The runtime tracks all memory allocations; and all reference(s)
- When a memory block is not referenced by the program; the GC will release the memory back to the kernel.

In C/C++, **the user must deallocate memory** using `free(ptr)`.

Memory leak

If memory is not freed (memory leak) the computer can run out:

- The kernel can kill the program
- The OS can crash
- Other applications requesting memory can crash or fail

- How can the kernel guarantee that memory is always contiguous?
- Can I acess memory from another program and steal their data?
- How can multiple applications share the same memory?
  - Some variables have hard-coded addresses!
- How to handle (Internal/External) fragmentation (Empty slot)?

We separate **Physical Addresses** (locations in memory) from
Virtual Addresses (Logic locations) seen by each program !

- Physical memory is divided into small **fixed-size blocks** called
  pages (typically ~4KB).
- The CPU includes a **Memory Management Unit** (MMU) that
  translates virtual addresses into physical addresses.
- Each program is given its own isolated virtual address space.
- The kernel maintains a **page table** for each program that tells
  the MMU how to translate addresses.

Each process believes it has acces to a large, contiguous block of memory; while it can be physically fragmented or shared.

Figure 6: Virtual And Physical Memory

*Note that this is a simplified representation.

Which memory are we talking about ?

Figure 7: Memory Hierarchy (https://www.geeksforgeeks.org/memory-hierarchy-design-and-its-characteristics/)

Note that GPU(s) also have their own separate memory !

- CPU computations are extremely fast, and memory access can be a bottleneck
  - Registers have the lowest latency
  - CPU caches (L1, L2, L3) act as fast buffers for memory
- DRAM (main memory) is much slower, but cheaper and larger
  - Accessing DRAM causes significant delays compared to cache

To achieve high performance, we must maximize data reuse in registers or caches, and minimize DRAM access.

CPU Caches

Most CPU have 3 levels of cache

- L1d - First Level Cache (Very fast)
- L2 - Second Level Cache (Fast)
- L3 (Last Level Cache - LLC) (Larger but slower than L1/L2)

Some cache level are per-core (L1, often L2) whereas others are shared between multiple cores (L3).

Instruction Cache

The assembly instructions are stored in a separate (L1i) instruction cache

Figure 8: CPU Latency and Cache

We speak of **Heterogeneous Memory Hierarchy**: the same memory accesses can have different latency depending on where the data resides !

[Live example: LSTOPO]

```
for (int i = 0; i < n; i++) {
  T[i] = A[i] * B[i];
}
```

1. The cache controller looks-up the data inside the CPU cache
   (L1 -> L2 -> L3)
2. If available, data is sent to register for the ALU
3. Else, a memory request is emitted

- This introduces latency and a bubble in the CPU pipeline

4. When the memory request is resolved; execution resumes
5. The results of $a * b$ is written to cache, and eventually back to
   main memory later on.

CPU Caches - In practice

In practice:

- The CPU fetches entire **cache line** (Often 64 Bytes) at once (If float: $64B/4B = 16$ values at once)
- The CPU can **prefetch** data: it learns data access patterns and anticipates future memory access.
- The CPU can execute **out-of-order**; independent instructions are executed while the memory request is in flight.

Consider two NBody 3D implementations:

Array Of Structure (AoS)

```
// We allocate N tuples of (x, y, z) positions
float* positions = malloc(sizeof(float) * N * 3);
```

Structure Of Array (SoA)

```
// We allocate separate arrays for each components
float* x = malloc(sizeof(float) * N);
float* y = malloc(sizeof(float) * N);
float* z = malloc(sizeof(float) * N);
```

We want to record the number of particles with $x \leq 0.5$

Array Of Structure (AoS)

```
for (int i = 0; i < N; i += 3)
  if (positions[i] < 0.5)
    count++;
```

Structure Of Array (SoA)

```
for (int i = 0; i < N; i++)
  if (x[i] < 0.5)
    count++;
```

Which one is faster; and why ?

Which access pattern makes better use of cache lines ?

Caches CPU - Strided Access

`Perf` results summed across 100 runs:

	Time	# Instr	# L1 Loads	# L1 Miss	# LLC Loads	# LLC Miss
AoS	~1.93s	~14 Billion	~3.5 Billion	~1 Million	~400k	~382k
SoA	~1.75s	~14 Billion	~3.5 Billion	~300k	~24k	~15k

	# Cache references (LLC)	# Cache miss
AoS	~158 Million	~151 Million
SoA	~52 Million	~35 Million

With AoS more load fail in the L1, leading to LLC accesses.

Most LLC loads still results in misses, leading to DRAM access.

Compilation & Assembly

C is a compiled language: we must translate the source code to assembly for the CPU

```
gcc ./main.c -o main (<flags>)
```

- Python is interpreted
    - More flexible but **significantly slower**
- C# and Java are compiled to intermediary bytecode and then executed via a virtual machine (or JIT-ed)
    - Balances performance and productivity
- C/C++/Rust are compiled to assembly code
    - Poor portability, but no intermediary.

Compilation & Assembly - Simple Loop

```
int sum = 0;
for (int i = 0; i < 100000; i++){
  sum += i;
}
```

```
main:
.LFB6:
    pushq   %rbp                // We record the stack pointer
    movq    %rsp, %rbp
    movl    $0, -4(%rbp)        // Initialize sum
    movl    $0, -8(%rbp)        // Initialize i
    jmp .L2
.L3:
    movl    -8(%rbp), %eax      // Load sum to a register
    addl    %eax, -4(%rbp)      // Add i and sum (from memory)
    addl    $1, -8(%rbp)        // Add 1 to i (from memory)
.L2:
    cmpl    $99999, -8(%rbp)    // Check if i < 100 000
    jle .L3                     // Jump Less Equal
    movl    $0, %eax            // Set the return value of main
    popq    %rbp
    ret                         // Return from main
```

gcc ./main.c -o main -O0

Assembly is as close to the metal we usually get, and is architecture dependant:

- Intel and AMD use the x86 Instruction Set
- x86 has multiple extensions (FMA, sse, avx, avx512, etc.)
- To maximize performance, we should compile our applications on each platform
  - Our binaries are not portable
  - But we can use dedicated instructions
- Other instructions set exists (ARM, Risc V, etc.)

The compiler is not just a translator:

- The compiler can generate optimized instructions from our program
- Constant values can be propagated, unused values/code removed
- Operations can be reordered, inlined, vectorized using SIMD, etc.
- Many, many more optimizations

Those optimizations are enable through flags such as -O1, -O2, -O3 which are predefined sets of optimization passes.

The flag -march=native allows the compiler to target the current machine for compilation and use all the available ASM extensions.

Figure 9: C Compiler Workflow

There are several compilers with varying performance and features:

- GCC and Clang-LLVM (The classics)
- MSVC (Microsoft), mingw-LLVM, arm-clang (For ARM) and many, many others.

Make is a scripting tool to automate complex compilation workflows. It works by defining rules inside **Makefiles**.

```
CC := gcc
CFLAGS := -g

main: main.c my_library.c my_library.h
  $(CC) -o $@ $^ $(CFLAGS)
```

- `main` is the target (What we want to build)
- `main.c my_library.c my_library.h` are the dependencies: rule reruns if any change
- `$(CC) -o $@ $< $(CFLAGS)` is the recipe
- `$@` expands to the target name
- `$^` expands to all dependency

Makefiles expects that a rule `main` produces a file called `main`.
However, not all rules produce files:

```
.PHONY: all clean

all: main mylibrary

...

clean:
  rm -rf *.o
  rm -rf ./main
```

Here, `make all` will be an alias to build everything, while `make clean`
is a custom rule to clean all build artifacts. Makefile has many,
many other functionalities, outside the scope of this course.

The typical projects looks something like:

```
Project/
  src/
    main.c
    my_library.c
  include/
    my_library.h
  Makefile # We define the Make rules here
```

`make` will look for a file in the `cwd` named `Makefile` or `makefile`. You can directly call `make all`, `make clean`, etc.

Parallelism Basics

Compiler optimization is only one side of high peformance computing.

If you remember; we saw in `LSTOPO` that our CPU has many cores:

- Every core can perform computations independently of the other
- Multiple process (Google, vscode, firefox, excel) can run **simultaneously** on different cores.
- The kernel manages execution through thread scheduling and time-slicing

Main Thread

Every process has at least one "thread of execution", which is an ordered sequence of instructions executed by the CPU.

What if we could split our programs into multiple threads ?

- If we have 1 thread only one computation happens at a time
- If we have 2 threads, we can potentially double throughput !

In practice, there is some overhead, we must handle dependencies between instructions, etc.

We consider three main types of parallelism

- Single Instruction Multiple Data (SIMD): also called Vectorization
    - single instruction operates simultaneously on multiple data elements.
- Shared Memory: Multiple threads inside the same memory space
    - Threads share a memory space, enabling fast communication and synchronization.
- Distributed Memory: Multiple processes
    - Communications are slower, but this model enables scaling across multiple machines.

For this course, we will only focus on SIMD and Shared Memory parallelism.

Consider the following loop:

```
int sum = 0;
for (int i = 0; i < 100; i++)
  sum += i;
```

We can slice the iteration space in multiple chunks:

Figure 10: Iteration slicing with 4 threads

We split the program into multiple instruction sequences running in parallel.

- Every thread operates a sum on a subset of the data
- We synchronize every thread and combine the partial sums via a global reduction.

`OpenMP` is an HPC tool designed for scenarios like this !

It's a simple to use library/compiler pass to parallelize trivial loops.

```
int sum = 0;

#pragma omp parallel for reduction(sum: +)
for (int i = 0; i < 100; i++)
  sum += i;
```

```
gcc ./main.c -fopenmp -O3 -march=native
```

This directive automatically distributes the loop iterations across all available CPU cores, performing a thread-safe reduction on sum.

`OpenMP` defines a set of `clause` which are operations followed by a set of modifiers.

- `#pragma omp`: is the start of all OpenMP clauses
- `parallel`: enable the creations of multiple threads
- `for`: toggle the automatic slicing of following loop
- `reduction(sum: +)`: toggles a reductions clause for sum using the + operation.

This code will be enough for most cases; but `OpenMP` allows for significantly more complex operations.

```
float global_min = FLT_MAX;
int global_min_index = -1;
#pragma omp parallel
{
  float min_value = FLT_MAX;
  int min_index = -1;
#pragma omp for nowait schedule(dynamic)
  for (int i = 0; i < N; i++) {
    if (T[i] < min_value) {
      min_value = T[i];
      min_index = i;
    }
  }
#pragma omp critical
  {
    if (min_value < global_min) {
      global_min = min_value;
      global_min_index = min_index;
    }
  }
}
```

We increase the number of threads while keeping the work size constant.

```
OMP_PLACES={0,2,4,6,8,10,12,14} OMP_PROC_BIND=True
OMP_NUM_THREADS=8 ./nbody 10000
sudo cpupower frequency-set -g performance
```

5 Meta repetitions per run, 13th Gen Intel(R) Core(TM) i7-13850HX @5.30 GHz, 32KB/2MB/30MB:L1/L2/L3 15GB DDR5.

Figure 11: Speedup of Naive Gravitationnal NBody 3D

Speedup is limited by runtime overhead, concurrency, memory bandwidth, data size, etc.