Combined_Asset_Vulnerability_Assessment

Report generated by Tenable Nessus™

Tue, 17 Mar 2026 15:09:59 EDT

TABLE OF CONTENTS

Vulnerabilities by Host

- 10.0.2.3 4
- 10.0.2.5 7

Vulnerabilities by Host

10.0.2.3

0	0	0	0	2
CRITICAL	HIGH	MEDIUM	LOW	INFO

Scan Information

Start time:	Tue Mar 17 14:57:41 2026
End time:	Tue Mar 17 15:09:59 2026

Host Information

IP:	10.0.2.3

Vulnerabilities

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/03/04

Plugin Output

tcp/0

```
Information about this scan :

Nessus version : 10.11.3
Nessus build : 20047
Plugin feed version : 202603160414
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : Combined_Asset_Vulnerability_Assessment
Scan policy used : Basic Network Scan
Scanner IP : 10.0.2.15
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 71.590 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/3/17 14:57 EDT (UTC -04:00)
Scan duration : 730 sec
Scan for malware : no
Fully Scan Operational Technology devices : yes
Safely Scan Operational Technology devices with OT Discovery : no
```

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2023/12/04

Plugin Output

udp/0

```
For your information, here is the traceroute from 10.0.2.15 to 10.0.2.3 :
10.0.2.15

ttl was greater than 50 - Completing Traceroute.

?
10.0.2.1
?

Hop Count: 4

An error was detected along the way.
```

10.0.2.5

0	0	1	1	23
CRITICAL	HIGH	MEDIUM	LOW	INFO

Scan Information

Start time:	Tue Mar 17 14:57:41 2026
End time:	Tue Mar 17 15:00:00 2026

Host Information

IP:	10.0.2.5
MAC Address:	08:00:27:74:4B:B1
OS:	Linux Kernel 2.6

Vulnerabilities

187315 - SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795)

Synopsis

The remote SSH server is vulnerable to a mitm prefix truncation attack.

Description

The remote SSH server is vulnerable to a man-in-the-middle prefix truncation weakness known as Terrapin. This can allow a remote, man-in-the-middle attacker to bypass integrity checks and downgrade the connection's security.

Note that this plugin only checks for remote SSH servers that support either ChaCha20-Poly1305 or CBC with Encrypt-then-MAC and do not support the strict key exchange countermeasures. It does not check for vulnerable software versions.

See Also

https://terrapin-attack.com/

Solution

Contact the vendor for an update with the strict key exchange countermeasures or disable the affected algorithms.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

5.3 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.1

EPSS Score

0.5786

CVSS v2.0 Base Score

5.4 (CVSS2#AV:N/AC:H/Au:N/C:N/I:C/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:POC/RL:OF/RC:C)

References

CVE	CVE-2023-48795

Plugin Information

Published: 2023/12/27, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Supports following ChaCha20-Poly1305 Client to Server algorithm : chacha20-
poly1305@openssh.com,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openssh.com,aes256-gcm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm  : umac-64-etm@openssh.com,umac-128-
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-
etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1
Supports following ChaCha20-Poly1305 Server to Client algorithm : chacha20-
poly1305@openssh.com,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openssh.com,aes256-gcm@openssh.com
Supports following Encrypt-then-MAC Server to Client algorithm  : umac-64-etm@openssh.com,umac-128-
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-
etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

VPR Score

2.2

EPSS Score

0.0037

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The difference between the local and remote clocks is -1 seconds.
```

39520 - Backported Security Patch Detection (SSH)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/22/ssh

```
Give Nessus credentials to perform local checks.
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

http://cpe.mitre.org/

https://nvd.nist.gov/products/cpe

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/01/05

Plugin Output

tcp/0

```
The remote operating system matched the following CPE :

  cpe:/o:linux:linux_kernel -> Linux Kernel

Following application CPE's matched on the remote system :

  cpe:/a:openbsd:openssh:8.9 -> OpenBSD OpenSSH
  cpe:/a:openbsd:openssh:8.9p1 -> OpenBSD OpenSSH
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose
Confidence level : 65
```

35716 - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

https://standards.ieee.org/faqs/regauth.html

http://www.nessus.org/u?794673b4

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

```
The following card manufacturers were identified :

08:00:27:74:4B:B1 : PCS Systemtechnik GmbH
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:
  - 08:00:27:74:4B:B1
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/22/ssh

```
Port 22/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/03/04

Plugin Output

tcp/0

```
Information about this scan :

Nessus version : 10.11.3
Nessus build : 20047
Plugin feed version : 202603160414
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : Combined_Asset_Vulnerability_Assessment
```

```
Scan policy used : Basic Network Scan
Scanner IP : 10.0.2.15
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 70.938 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/3/17 14:57 EDT (UTC -04:00)
Scan duration : 100 sec
Scan for malware : no
Fully Scan Operational Technology devices : yes
Safely Scan Operational Technology devices with OT Discovery : no
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, “OS Identification”, the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

```
Following OS Fingerprints were found

Remote operating system : Linux Kernel 6.x
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.6
Confidence level : 65
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
   P1:B10113:F0x12:W64240:O0204ffff:M1460:
   P2:B10113:F0x12:W65160:O0204ffff0402080affffffff4445414401030307:M1460:
   P3:B00000:F0x00:W0:O0:M0
   P4:191603_7_p=22

Following fingerprints could not be used to determine OS :
 SSH:!:SSH-2.0-OpenSSH_8.9p1 Ubuntu-3ubuntu0.1
```

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 2.6
Confidence level : 65
Method : SinFP


The remote host is running Linux Kernel 2.6
```

117886 - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF	IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

```
The following issues were reported :

  - Plugin      : no_local_checks_credentials.nasl
    Plugin ID   : 110723
    Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
    Message     :
Credentials were not provided for detected SSH service.
```

181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

https://www.openssh.com/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2026/02/03

Plugin Output

tcp/22/ssh

```
Service    : ssh
Version    : 8.9p1
Banner     : SSH-2.0-OpenSSH_8.9p1 Ubuntu-3ubuntu0.1
backported : 1
```

66334 - Patch Report

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2026/03/10

Plugin Output

tcp/0

```
. You need to take the following action :

[ SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795) (187315) ]

+ Action to take : Contact the vendor for an update with the strict key exchange countermeasures or
 disable the affected algorithms.
```

277653 - Remote Services Using Post-Quantum Ciphers

Synopsis

Reports remote services that offer post-quantum ciphers.

Description

This plugin reports network services that offer post-quantum ciphers and enumerates the post-quantum ciphers that they offer. Tenable makes no attempt to determine whether the remote service is actually hardened against a post-quantum attack.

See Also

http://www.nessus.org/u?7a390f87

http://www.nessus.org/u?ad7d6b3b

http://www.nessus.org/u?1c0c61e0

http://www.nessus.org/u?5eec4b28

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/22/ssh

```
The target SSH server offers the following post-quantum ciphers:

KEX
sntrup761x25519-sha512@openssh.com
```

70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Nessus negotiated the following encryption algorithm(s) with the server :

  Client to Server: aes256-ctr
  Server to Client: aes256-ctr

The server supports the following options for compression_algorithms_server_to_client :

  none
  zlib@openssh.com

The server supports the following options for mac_algorithms_client_to_server :

  hmac-sha1
  hmac-sha1-etm@openssh.com
  hmac-sha2-256
  hmac-sha2-256-etm@openssh.com
  hmac-sha2-512
  hmac-sha2-512-etm@openssh.com
  umac-128-etm@openssh.com
  umac-128@openssh.com
  umac-64-etm@openssh.com
  umac-64@openssh.com

The server supports the following options for server_host_key_algorithms :

  ecdsa-sha2-nistp256
  rsa-sha2-256
  rsa-sha2-512
  ssh-ed25519
```

```
The server supports the following options for encryption_algorithms_client_to_server :

  aes128-ctr
  aes128-gcm@openssh.com
  aes192-ctr
  aes256-ctr
  aes256-gcm@openssh.com
  chacha20-poly1305@openssh.com

The server supports the following options for mac_algorithms_server_to_client :

  hmac-sha1
  hmac-sha1-etm@openssh.com
  hmac-sha2-256
  hmac-sha2-256-etm@openssh.com
  hmac-sha2-512
  hmac-sha2-512-etm@openssh.com
  umac-128-etm@openssh.com
  umac-128@openssh.com
  umac-64-etm@openssh.com
  umac-64@openssh.com

The server supports the following options for kex_algorithms :

  curve25519-sha256
  curve25519-sha256@libssh.org
  diffie-hellman-group-exchange-sha256
  diffie-hellman-group14-sha256
  diffie-hellman-group16-sha512
  diffie-hellman-group18-sha512
  ecdh-sha2-nistp256
  ecdh-sha2-nistp384
  ecdh-sha2-nistp521
  sntrup761x25519-sha512@openssh.com

The server supports the following options for compression_algorithms_client_to_server :

  none
  zlib@openssh.com

The server supports the following options for encryption_algorithms_server_to_client :

  aes128-ctr
  aes128-gcm@openssh.com
  aes192-ctr
  aes256-ctr
  aes256-gcm@openssh.com
  chacha20-poly1305@openssh.com
```

149334 - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

https://tools.ietf.org/html/rfc4252#section-8

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The remote SSH daemon supports the following versions of the
SSH protocol :

  - 1.99
  - 2.0
```

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

```
The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are
 supported :

  umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-
etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-
sha2-256,hmac-sha2-512,hmac-sha1

The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are
 supported :

  umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-
etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-
sha2-256,hmac-sha2-512,hmac-sha1
```

10267 - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_8.9p1 Ubuntu-3ubuntu0.1
SSH supported authentication : publickey,password
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/02/02

Plugin Output

tcp/22/ssh

```
An SSH server is running on this port.
```

298387 - Shor's Harvest Now Decrypt Later

Synopsis

Reports remote services potentially vulnerable to Shor's Algorithm.

Description

This plugin reports network services that may be vulnerable now to a future attack by adversaries using a cryptographically relevant quantum computer (CRQC). Shor's is a theoretical algorithm that leverages the unique ability of quantum computation to do massively parallel calculations developed by Peter Shor in 1994.

This algorithm easily computes two classically difficult mathematical problems used in modern cryptography; discrete logarithms, and factoring numbers formed by multiplying large primes. Shor's reduces both of these problems from taking exponential time in chosen cases to being solvable in polynomial time.

Asymmetric encryption algorithms such as RSA, Diffie-Hellman and Elliptic Curve Diffie-Hellman are impacted by Shor's Algorithm. The most common uses of these algorithms are in symmetric key establishment and authentication. These uses render Shor's Algorithm particularly dangerous because it may give an adversary the ability to harvest network communications now, and in the future, when a CRQC becomes available, extract the symmetric key and decrypt the communication.

See Also

http://www.nessus.org/u?54fba2c1

Solution

Replace affected ciphers with algorithms chosen to resist CRQC attack.

Risk Factor

None

Plugin Information

Published: 2026/02/09, Modified: 2026/02/09

Plugin Output

tcp/0

```
The SSH service on port 22 offers these ciphers vulnerable to Shor's:
diffie-hellman-group-exchange-sha256
curve25519-sha256
ecdh-sha2-nistp256
ecdh-sha2-nistp521
curve25519-sha256@libssh.org
ecdh-sha2-nistp384
diffie-hellman-group18-sha512
```

```
diffie-hellman-group14-sha256
diffie-hellman-group16-sha512
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

http://www.ietf.org/rfc/rfc1323.txt

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.

- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF	IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

tcp/0

```
SSH was detected on port 22 but no credentials were provided.
SSH local checks were not enabled.
```

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2023/12/04

Plugin Output

udp/0

```
For your information, here is the traceroute from 10.0.2.15 to 10.0.2.5 :
10.0.2.15
10.0.2.5

Hop Count: 1
```