Swagger & Swagger UI

🔥 **Hot Tips**

- Visit `/swagger` to see the interactive Swagger UI
- Visit `/swagger.json` for the raw OpenAPI 3.0.3 spec
- Add metadata via `swagger_meta:` on any route

Tina4 Ruby auto-generates OpenAPI 3.0.3 documentation from your registered routes.

Configuration

Set environment variables in `.env` :

```env
SWAGGER_TITLE=My API
SWAGGER_DESCRIPTION=Auto-generated API documentation
SWAGGER_VERSION=1.0.0
SWAGGER_CONTACT=Tina4 Team
SWAGGER_CONTACT_URL=https://tina4.com
SWAGGER_CONTACT_EMAIL=support@tina4.com
```

Usage

Simply define routes — they appear in Swagger automatically:

ruby

```ruby
Tina4.get "/api/users" do |request, response|
  response.json({ users: [] })
end
```

Adding Metadata

Use the `swagger_meta:` keyword to enrich your API docs:

ruby

```ruby
Tina4.get "/api/users", swagger_meta: {
  description: "Retrieve all users",
  summary: "List users",
  tags: ["Users"],
  params: { page: "Page number", limit: "Items per page" },
  example_response: { users: [{ id: 1, name: "Alice" }] }
} do |request, response|
  response.json({ users: [] })
end
```

POST/PUT with Request Body

ruby

```ruby
Tina4.post "/api/users", swagger_meta: {
  description: "Create a new user",
  tags: ["Users"],
  secure: true,
  example: { name: "Alice", email: "alice@example.com" },
  example_response: { id: 1, name: "Alice", status: "active" }
} do |request, response|
  user = User.create(request.json_body)
  response.json(user.to_hash, 201)
end
```

Metadata Options

Key	Type	Description
`description`	`String`	Detailed description of the endpoint
`summary`	`String`	Short one-line summary
`tags`	`Array`	Grouping tags for Swagger UI
`params`	`Hash`	Query parameter descriptions
`example`	`Hash`	Request body example (POST/PUT/PATCH)
`example_response`	`Hash`	Response body example
`secure`	`Boolean`	Marks route as requiring auth

Secured Routes in Swagger

Secured routes automatically show a lock icon and 401 response:

ruby

```ruby
Tina4.secure_get "/api/profile", swagger_meta: {
  description: "Get current user profile",
  secure: true
} do |request, response|
  response.json({ user: "authenticated" })
end
```

Previous page
AJAX - tina4helper.js

Next page
Database