Consuming REST APIs

🔥 **Hot Tips**

- `Tina4::API` is a thin HTTP client for calling external APIs
- Supports GET, POST, PUT, PATCH, DELETE
- Auto-parses JSON responses
- Pass custom auth headers easily

Basic Usage

ruby

```ruby
require "tina4"

api = Tina4::API.new("https://api.example.com")

# GET
result = api.get("/users")
puts result.body          # Parsed response body
puts result.status_code   # HTTP status code
puts result.headers       # Response headers

# POST with JSON body
result = api.post("/users", body: { name: "Alice", email: "alice@example.com" }

# PUT
result = api.put("/users/1", body: { name: "Alice Updated" })
```

```ruby
# DELETE
result = api.delete("/users/1")
```

Authentication

```ruby
# Bearer token
api = Tina4::API.new("https://api.example.com", auth_header: "Bearer my-token")

# Custom headers
api = Tina4::API.new("https://api.example.com", headers: {
  "X-API-Key" => "secret123",
  "Accept" => "application/json"
})
```

APIResponse Object

Every API call returns a `Tina4::APIResponse` :

Property	Type	Description
`body`	`String/Hash`	Response body (auto-parsed if JSON)
`status_code`	`Integer`	HTTP status code
`headers`	`Hash`	Response headers
`success?`	`Boolean`	`true` if status 2xx

```ruby
result = api.get("/users/42")

if result.success?
  user = result.body
```

```
    puts user["name"]
  else
    puts "Error: #{result.status_code}"
  end
```

Using in Routes

ruby

```ruby
Tina4.get "/api/weather/{city}" do |request, response|
  api = Tina4::API.new("https://wttr.in")
  result = api.get("/#{request.params['city']}?format=j1")

  if result.success?
    response.json(result.body)
  else
    response.json({ error: "Weather service unavailable" }, 502)
  end
end
```

Previous page
CRUD

Next page
Development Mode