Connect to CCH Tagetik MCP

1 / Authenticate with the DemoHub identity provider

Use this guide to obtain an access token, connect your MCP client and validate a first database read. Replace every placeholder with the value for your environment.

1. Have your access details ready

Locate the **Client ID, Client secret and Tenant ID** supplied in your dedicated credentials email. CCH Tagetik registers your client with the DemoHub IdP and enables its access to the tenant. You do not need to edit the server configuration.

2. Request an access token

Send the following request to the DemoHub identity provider. Use the same Tenant ID throughout this guide.

Method	POST
Token endpoint	https://idp-demohub.demohub.saastagetik.com/oauth2/token
Authentication	HTTP Basic Auth: username = your Client ID; password = your Client secret
Tenant header	cchtagetik-tenant-id: <tenant_id>
Content-Type	application/x-www-form-urlencoded
Form body	grant_type=client_credentials

Example token request

```
curl --request POST \
  "https://idp-demohub.demohub.saastagetik.com/oauth2/token" \
  --user "<client_id>:<client_secret>" \
  --header "cchtagetik-tenant-id: <tenant_id>" \
  --header "Content-Type: application/x-www-form-urlencoded" \
  --data "grant_type=client_credentials"
```

3. Keep the returned access token for the next step

Use the returned JWT access token as the bearer token for your MCP connection. Request a new token when it expires.

Need Okta authentication? Contact DL-TGK-Aiecosystem@wolterskluwer.com. We will work with your team to arrange the required configuration.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.

Connect your MCP client

2 / Configure the server connection

1. Enter your tenant-specific server URL

Replace **<tenant_id>** with the Tenant ID supplied by CCH Tagetik. Use the MCP URL below, rather than the token endpoint used on the previous page.

```
https://www.demohub.saastagetik.com/server/<tenant_id>/mcp/v0
```

2. Provide the bearer token

Configure your MCP client with the server URL and the access token obtained from the DemoHub IdP. Client settings may use different field names.

Server URL	https://www.demohub.saastagetik.com/server/<tenant_id>/mcp/v0
Authorization header	Bearer <mcp_jwt>

3. Let the MCP client initialize the session

The MCP client normally handles initialization and session management automatically. Once connected, continue to the first-read instructions on the next page. Replace the bearer token when it expires.

For custom clients: initialization request

If you implement the protocol yourself, send a **POST** request to the MCP Server URL with the headers and example JSON body below. Standard MCP clients normally handle this exchange for you.

```
Authorization: Bearer <mcp_jwt>
Content-Type: application/json
Accept: application/json, text/event-stream

{
  "jsonrpc": "2.0",
  "id": 1,
  "method": "initialize",
  "params": {
    "protocolVersion": "2025-06-18",
    "capabilities": {},
    "clientInfo": { "name": "user-client", "version": "1.0.0" }
  }
}
```

After initialization, a custom client must send the initialized notification and use the **negotiated protocol version** and any returned **session ID** on subsequent requests. The JSON above is only the initialization request.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.

Run your first database read

3 / Supply tool parameters and validate the result

Connecting to MCP and discovering tools do not by themselves confirm access to your Tagetik database. Complete a read and inspect its result.

1. Provide the database tool parameters

Supply **api_key** and **db_id** through your agent configuration, or provide them to the agent in chat. Your integration can inject them as fixed tool argument values.

api_key	Identifies the Tagetik user whose permissions apply to the database operation.
db_id	Identifies the Tagetik database to use.

These are **tool parameters**, not MCP connection settings. Include them in **every Tagetik operation invoked through call_tool**. The discovery tool **search_tools** does not require them.

2. Ask the agent to list existing workspaces

Example request: **“Show me existing workspaces in the database.”** Ensure the agent has the api_key and db_id before it calls the operation.

The agent should first discover the workspace operation, then execute it:

```
search_tools: {"query": "list AIH workspaces"}

call_tool: {
  "name": "workspace_find",
  "arguments": {"api_key": "<your_api_key>",
                "db_id": "<your_db_id>", "take": 100}
}
```

Illustrative tool inputs. Follow the tool definitions returned by your MCP client.

3. Check the actual tool result

A successful read returns **workspace data or a valid empty list**, without a tool error. Inspect the result, including **isError** where available. An HTTP success status or a confident final answer alone does not prove the read succeeded.

If the results exceed the requested page size, retrieve additional pages using **skip** and **take**.

Two separate identities apply

The **IdP access token** authorizes the MCP client for the tenant in the server URL. The **API key** identifies the Tagetik user whose permissions govern the database operation.

Keep API keys, client secrets and bearer tokens out of shared traces. For assistance, contact DL-TGK-Aiecosystem@wolterskluwer.com.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.