Wolters Kluwer

PARTNER REFERENCE

CCH Tagetik

MCP operation catalog

WOLTERS KLUWER
INTELLECTUAL PROPERTY

TGK all folders MCP Server — 222 tools registered

Listed to clients: 2 (call_tool, search_tools)

222 operations. Five functional areas.

Full operation definitions, parameters and example arguments.

Source: tools_descriptions 2(1).txt

CCH® Tagetik
by Wolters Kluwer

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Contents

Navigate by functional area, object group or operation using the linked contents and PDF bookmarks. An alphabetical operation index appears at the end.

The sections are an editorial grouping of the original definitions. Operation identifiers, descriptions, parameter text and examples retain the source wording.

AIH data and foundation 4

- Workspaces . . . 5
- Analytical data extraction . . . 10
- Datasets . . . 12
- Dataset fields . . . 19
- Dataset partitions . . . 24
- Dataset availability . . . 27
- Dataset typologies . . . 29
- Datasources . . . 31
- Datasource fields . . . 37
- Virtual datasets . . . 42
- Virtual dataset fields . . . 48
- AIH dictionaries . . . 53

Data Model and master data 59

- Accounts . . . 60
- Account hierarchies . . . 81
- Account hierarchy relationships . . . 84
- Account hierarchy structure . . . 88
- Entities . . . 94
- Entity hierarchies . . . 107
- Entity hierarchy structure . . . 112
- Analytical dimensions . . . 118
- Custom dimensions . . . 123
- Categories . . . 125
- Currencies . . . 133
- Scenarios . . . 138
- Scenario periods . . . 144

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Periods . . . 149
Shared dictionary items . . . 150

Financial Reporting configuration 156
Report definitions . . . 157
Report filters . . . 168
Report formulas . . . 171
Report parameters . . . 172
Report queries . . . 172
Report style sheets . . . 177

DTP and process configuration 184
DTPs . . . 185
Activities . . . 186
Operations . . . 188
Allocation details . . . 190
Calculation rule attributes . . . 191
Calculation rule scripts . . . 193
Checking rules . . . 195
Parameters . . . 196
Special methods . . . 198

User Provisioning 200
Users . . . 201

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

01

AIH data and foundation

70 operations

Workspaces 7

Analytical data extraction 2

Datasets 7

Dataset fields 7

Dataset partitions 4

Dataset availability 4

Dataset typologies 4

Datasources 7

Datasource fields 7

Virtual datasets 7

Virtual dataset fields 7

AIH dictionaries 7

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Workspaces

AIH data and foundation · 7 operations

[workspace_addWorkspace]

Creates a new AIH Workspace with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "W01",
  "oid": "VAFAANCMTHWEZRQ",
  "descriptions": {
    "en": "Example workspace",
    "it": "Workspace di esempio"
  },
  "dimensions": [
    "$ACCOUNT",
    "ANDIM_01"
  ],
  "online": true,
  "database": "DB_01",
  "distributedExecution": false
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

id (string): Workspace code, immutable

oid (string): Workspace table oid , immutable, not required

*** descriptions (object):** Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

dimensions (array): Dimension filter for the workspace.

* `$SCENARIO` - Scenario
* `$PERIOD` - Period
* `$ENTITY` - Entity
* `$CURRENCY` - Currency
* `$ACCOUNT` - Account
* `$VARDET` - Variation & Detail
* `$CATEGORY` - Category
* `$CUSTOM_DIM1` - Custom Dimension 1
* `$CUSTOM_DIM2` - Custom Dimension 2

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

* $CUSTOM_DIM3 - Custom Dimension 3
* $CUSTOM_DIM4 - Custom Dimension 4
* $CUSTOM_DIM5 - Custom Dimension 5
* <ANALYTICAL DIMENSION NAME> - Analytical Dimension name

*** online (boolean):** Whether the workspace is online and available for use.

database (string): reference database on which the data tables will be created, immutable

distributedExecution (boolean): enable distributed execution

[workspace_count]

Returns the number of AIH Workspaces matching the optional FIQL filter. Use this when only the count is needed, not the AIH Workspace data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable fields:
- id
- descriptions
- online
- version
- updateInfo.origin
- updateInfo.user
- updateInfo.date

[workspace_deleteWorkspace]

Deletes an AIH Workspace

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Id of Workspace.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[workspace_find]

Returns AIH Workspaces matching the optional FIQL filter. Use this to search or list AIH Workspaces. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL') Omit this parameter when no filter is needed; do not send an empty string.

- Filterable fields:
- id
- descriptions
- online
- version
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting. Omit this parameter when no sorting is needed; do not send an empty string.

[workspace_getById]

Returns one AIH Workspace identified by its ID. Use this when the AIH Workspace ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Id of the Workspace to be retrieved

[workspace_updateWorkspace]

Updates an existing AIH Workspace only for properties passed as input

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "string",
  "descriptions": {
    "en": "Example workspace",
    "it": "Workspace di esempio"
  },
  "dimensions": [
    "$ACCOUNT",
    "ANDIM_01"
  ],
  "online": true,
  "distributedExecution": false
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Id of Workspace.

descriptions (object): Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it").

dimensions (array): Dimension filter for the workspace.

* `$SCENARIO` - Scenario
* `$PERIOD` - Period
* `$ENTITY` - Entity
* `$CURRENCY` - Currency
* `$ACCOUNT` - Account
* `$VARDET` - Variation & Detail
* `$CATEGORY` - Category
* `$CUSTOM_DIM1` - Custom Dimension 1
* `$CUSTOM_DIM2` - Custom Dimension 2
* `$CUSTOM_DIM3` - Custom Dimension 3
* `$CUSTOM_DIM4` - Custom Dimension 4
* `$CUSTOM_DIM5` - Custom Dimension 5
* `<ANALYTICAL DIMENSION NAME>` - Analytical Dimension name

online (boolean): Whether the workspace is online and available for use.

distributedExecution (boolean): enable distributed execution

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[workspace_workspaceBulk]

Performs bulk create, replace, and partial update operations on AIH Workspaces. Use this tool when multiple AIH Workspaces must be changed in a single request.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "saveMode": "LOOSE",
  "post": [
    {
      "id": "W01",
      "oid": "VAFAANCMTHWEZRQ",
      "descriptions": {
        "en": "Example workspace",
        "it": "Workspace di esempio"
      },
      "dimensions": [
        "$ACCOUNT",
        "ANDIM_01"
      ],
      "online": true,
      "database": "DB_01",
      "distributedExecution": false
    }
  ],
  "put": [
    {
      "id": "W01",
      "oid": "VAFAANCMTHWEZRQ",
      "descriptions": {
        "en": "Example workspace",
        "it": "Workspace di esempio"
      },
      "dimensions": [
        "$ACCOUNT",
        "ANDIM_01"
      ],
      "online": true,
      "database": "DB_01",
      "distributedExecution": false
    }
  ],
  "patch": [
    {
      "key": {
        "id": "A00"
      },
      "data": {
        "descriptions": {
          "en": "Example workspace",
          "it": "Workspace di esempio"
        },
        "dimensions": [
          "SCENARIO",
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
          "ANDIM_02"
        ],
        "online": false
      }
    }
  ],
  "delete": [
    {
      "id": "W01"
    }
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Workspaces to partially update. Each item contains a key identifying the Workspace to update and a data object containing only the properties to modify.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

==========

Analytical data extraction

AIH data and foundation · 2 operations

`[analytical_workspace_data_extraction_get_analytical_data]`

Reads data from an AIH Analytical Workspace physical dataset, virtual dataset, or datasource. The `dataObjectId` path parameter is built by concatenating `Dataset_`, `VirtualDataset_`, or `Datasource_` with the ID of that dataset/datasource/virtual dataset as it appears in the metadata; this ID is not necessarily numeric.

The caller can scope the data by Process, Scenario, Period, and Entity. Which of these parameters are mandatory for this object is not guessed: it must be retrieved beforehand by calling `analytical_workspace_data_extraction_get_analytical_data_requirements` (`GET .../Parameters`) for the same data object. That operation only returns which parameters are required, not their valid values/codes; the actual codes to pass (e.g. the Scenario, Period, or Entity codes) must be obtained from the relevant Data Model tools. Use OData options to select columns, filter rows, sort, and page.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Field names used in `$select`, `$filter`, and `$orderby` must be copied character-for-character from the matching field discovery tool for the object type (dataset, virtual dataset, or datasource fields). Never use a business-language name, an abbreviation, or a prefix/guess of the real ID: e.g. if the field discovery tool returns `MARGIN_LEV4`, use `MARGIN_LEV4` — not `margin`, `MARGIN`, or `logisticsChain`.

Start with `$select` and `$top`; do not use `$ALL` or omit `$top` unless the requested result is known to be small. The platform timeout is 10 minutes and cannot be changed.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Analytical Workspace code.

*** dataObjectId (string):** Object to read. Build it by concatenating `Dataset_`, `VirtualDataset_`, or `Datasource_` with the ID of the dataset/datasource/virtual dataset as it appears in the metadata (e.g. the ID returned by the dataset, datasource, or virtual dataset discovery/metadata operations). This ID is not necessarily numeric: it can be alphanumeric, so do not assume a fixed numeric format.

Process (string): Required for objects partitioned by business cycle. Whether it is required comes from `analytical_workspace_data_extraction_get_analytical_data_requirements`; the valid codes must be looked up separately (not returned by that operation).

Scenario (string): A code, comma-separated codes, or `$ALL` when allowed. Whether it is required comes from `analytical_workspace_data_extraction_get_analytical_data_requirements`; the valid codes must be looked up separately (not returned by that operation).

Period (string): A code, comma-separated codes, or `$ALL` when allowed. Whether it is required comes from `analytical_workspace_data_extraction_get_analytical_data_requirements`; the valid codes must be looked up separately (not returned by that operation).

Entity (string): A code, comma-separated codes, or `$ALL`. Virtual datasets accept one entity only. Whether it is required comes from `analytical_workspace_data_extraction_get_analytical_data_requirements`; the valid codes must be looked up separately (not returned by that operation).

$select (string): Comma-separated fields to return. Use this to reduce payload size. Each name must be an exact technical field ID from this data object's field discovery tool, not a guessed or business-language name.

$filter (string): OData predicate. Quote text values with single quotes; leave numbers and UTC timestamps unquoted. Supported operators: eq, in, ne, gt, ge, lt, le, and, or, not. Field names must be exact technical field IDs, not guessed or business-language names.

$orderby (string): Sort expression. Use a stable order when paging. Separate multiple fields with a comma and no surrounding space, e.g. `Account desc,Entity asc` — not `Account desc, Entity asc`.

$top (integer): Maximum rows to return. Required when `$skip` is used.

$skip (integer): Number of rows to skip. May only be used with `$top`.

$count (boolean): When true, returns `@odata.count`; it may be used without row values.

numberFormat (string): Numeric serialization format for returned values.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[analytical_workspace_data_extraction_get_analytical_data_requirements]

Returns which extraction parameters are mandatory for an AIH Analytical Workspace physical dataset, virtual dataset, or datasource. Call this before `analytical_workspace_data_extraction_get_analytical_data` when the object partitioning is not known: the response only tells the agent which of Process, Scenario, Period, and Entity must be supplied for this object — it does NOT return the valid values/codes to use for those parameters. The values must be obtained separately (e.g. from the relevant Data Model tools such as process, scenario, period, or entity lookups). For this operation, provide only the data object ID as it appears in the metadata, without the `Dataset_`, `VirtualDataset_`, or `Datasource_` prefix. This ID is an identifier assigned by CCH Tagetik and is not necessarily numeric (it can be alphanumeric).

Parameters:

* **api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

* **db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

* **workspaceId (string):** Analytical Workspace code.

* **dataObjectId (string):** ID of the data object as it appears in the metadata, without the `Dataset_`, `VirtualDataset_`, or `Datasource_` prefix. This ID is not necessarily numeric: it can be alphanumeric.

Datasets

AIH data and foundation · 7 operations

[dataset_addDataset]

Creates a new AIH Dataset with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "id": "100001",
  "oid": "XYH6HHyi999HHG1234",
  "descriptions": {
    "en": "Example dataset",
    "it": "dataset di esempio"
  },
  "index": [
    {
      "field": "LABEL",
      "indexPosition": "0"
    }
  ],
  "sort": [
    {
      "field": "LABEL",
      "sortPosition": "0",
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "sortType": "DESC"
    }
  ],
  "dtpProperties": {
    "datasetType": "REFERENCE_TABLE"
  },
  "userDataOnly": true,
  "disableUserRightReadonlyCheck": false,
  "disableSubmissionChecks": false,
  "disableProcessConsistencyChecks": false,
  "disableScenarioPeriodLockingChecks": true,
  "dataUpdateMode": "CREATE_NEW_RECORD",
  "partitionPolicy": "NOT_PARTITIONED"
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Dataset code, Immutable

oid (string): Dataset table oid, Immutable, not required

*** descriptions (object):** Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

index (array):

sort (array):

dtpProperties (any):

*** userDataOnly (boolean):** data is shown filtered by user

*** disableUserRightReadonlyCheck (boolean):** disable checking of the read only option

disableSubmissionChecks (boolean): disable submission checks when saving data

*** disableProcessConsistencyChecks (boolean):** disable consistency checks when saving data

*** disableScenarioPeriodLockingChecks (boolean):** disable scenario period locking checks when saving data

*** dataUpdateMode (string):** How changes are stored after editing data .

  * `CREATE_NEW_RECORD`
  * `UPDATE_EXISTING_RECORD`

Immutable if at least one partition exist

*** partitionPolicy (any):**

`[dataset_count]`

Returns the number of AIH Datasets matching the optional FIQL filter. Use this when only the count is needed, not the AIH Dataset data.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

dataset_count

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable fields:
- workspace.id
- id
- descriptions
- dtpProperties.datasetType
- userDataOnly
- disableUserRightReadonlyCheck
- disableSubmissionChecks
- disableProcessConsistencyChecks
- disableScenarioPeriodLockingChecks
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** workspaceId (string):** Workspace code.

[dataset_datasetBulk]

Performs bulk create, replace, and partial update operations on AIH Datasets. Use this tool when multiple AIH Datasets in the same AIH Workspace must be changed in a single request.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "saveMode": "LOOSE",
  "post": [
    {
      "id": "100001",
      "oid": "XYH6HHyi999HHG1234",
      "descriptions": {
        "en": "Example dataset",
        "it": "dataset di esempio"
      },
      "index": [
        {
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
        "field": "LABEL",
        "indexPosition": "0"
      }
    ],
    "sort": [
      {
        "field": "LABEL",
        "sortPosition": "0",
        "sortType": "DESC"
      }
    ],
    "dtpProperties": {
      "datasetType": "REFERENCE_TABLE"
    },
    "userDataOnly": true,
    "disableUserRightReadonlyCheck": false,
    "disableSubmissionChecks": false,
    "disableProcessConsistencyChecks": false,
    "disableScenarioPeriodLockingChecks": true,
    "dataUpdateMode": "CREATE_NEW_RECORD",
    "partitionPolicy": "NOT_PARTITIONED"
  }
],
"put": [
  {
    "id": "100001",
    "oid": "XYH6HHyi999HHG1234",
    "descriptions": {
      "en": "Example dataset",
      "it": "dataset di esempio"
    },
    "index": [
      {
        "field": "LABEL",
        "indexPosition": "0"
      }
    ],
    "sort": [
      {
        "field": "LABEL",
        "sortPosition": "0",
        "sortType": "DESC"
      }
    ],
    "dtpProperties": {
      "datasetType": "REFERENCE_TABLE"
    },
    "userDataOnly": true,
    "disableUserRightReadonlyCheck": false,
    "disableSubmissionChecks": false,
    "disableProcessConsistencyChecks": false,
    "disableScenarioPeriodLockingChecks": true,
    "dataUpdateMode": "CREATE_NEW_RECORD",
    "partitionPolicy": "NOT_PARTITIONED"
  }
],
"patch": [
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
    {
      "key": {
        "id": "100001"
      },
      "data": {
        "descriptions": {
          "en": "dataset english description to be modified"
        },
        "partitionPolicy": "BY_BUSINESS_CYCLE",
        "index": [
          {
            "field": "LABEL1",
            "indexPosition": "1"
          }
        ],
        "disableScenarioPeriodLockingChecks": false
      }
    }
  ],
  "delete": [
    {
      "id": 46
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Datasets to partially update. Each item contains a key identifying the Dataset to update and a data object containing only the properties to modify.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

[dataset_deleteDataset]

Deletes an AIH Dataset

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Dataset code.

[dataset_find]

Returns AIH Datasets matching the optional FIQL filter within the specified AIH Workspace. Use this to search or list AIH Datasets. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable fields:
- workspace.id
- id
- descriptions
- dtpProperties.datasetType
- userDataOnly
- disableUserRightReadonlyCheck
- disableSubmissionChecks
- disableProcessConsistencyChecks
- disableScenarioPeriodLockingChecks
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

expand (string): Determine if description of nested referenced elements should be retrieved (disabled by default)

*** workspaceId (string):** Workspace code.

[dataset_getById]

Returns one AIH Dataset identified by its ID within the specified AIH Workspace. Use this when the AIH Dataset ID is already known.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Dataset code.

[dataset_updateDataset]

Updates an existing AIH Dataset only for properties passed as input

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "string",
  "id": "string",
  "descriptions": {
    "en": "Example dataset",
    "it": "dataset di esempio"
  },
  "index": [
    {
      "field": "LABEL",
      "indexPosition": "0"
    }
  ],
  "sort": [
    {
      "field": "LABEL",
      "sortPosition": "0",
      "sortType": "DESC"
    }
  ],
  "userDataOnly": true,
  "disableSubmissionChecks": false,
  "disableProcessConsistencyChecks": false,
  "disableScenarioPeriodLockingChecks": true
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Dataset code.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

descriptions (object): Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

index (array):

sort (array):

userDataOnly (boolean): data is shown filtered by user

disableSubmissionChecks (boolean): disable submission checks when saving data

disableProcessConsistencyChecks (boolean): disable consistency checks when saving data

disableScenarioPeriodLockingChecks (boolean): disable scenario period locking checks when saving data

Dataset fields

AIH data and foundation · 7 operations

[dataset_field_addDataset]

Creates a new AIH Dataset Field with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "datasetId": 3,
  "body": {
    "formatType": "PLAIN",
    "personalDataProtection": true,
    "encoded": false,
    "length": 2000,
    "defaultValue": "default value for field"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

*** body (object):** Field definition to create. The body must match one of these schemas: TextMeasurePost, NumericMeasurePost, DateMeasurePost, CommentsAndAttachmentsMeasurePost, LeafDimensionPost, HierarchyDimensionPost, or HierarchyLevelDimensionPost. All field types use the common field properties such as id, descriptions, fieldType, length, mandatory, editability, and key. Numeric fields may additionally define decimalDigits, defaultValue, timeDimensionRollup, and conversionType. Dimension fields define dimensionType and may define hierarchyId or dictionary.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[dataset_field_count]

Returns the number of AIH Dataset Fields matching the optional FIQL filter. Use this when only the count is needed, not the AIH Dataset Field data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL') Filterable properties:

- id
- descriptions
- fieldType
- formatType
- personalDataProtection
- encoded
- timeDimensionRollup
- conversionType
- dimensionType
- hierarchyId
- values.dictionary.id
- mandatory
- key
- editability
- referenceType
- updateInfo.user
- updateInfo.date
- updateInfo.origin

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

[dataset_field_datasetBulk]

Performs bulk create, replace, and partial update operations on AIH Dataset Fields. Use this tool when multiple AIH Dataset Fields in the same AIH Dataset must be changed in a single request.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "datasetId": 2,
  "saveMode": "LOOSE",
  "post": [
    {
      "formatType": "PLAIN",
      "personalDataProtection": true,
      "encoded": false,
      "length": 2000,
      "defaultValue": "default value for field"
    }
  ],
  "put": [
    {
      "formatType": "PLAIN",
      "personalDataProtection": true,
      "encoded": false,
      "length": 2000,
      "defaultValue": "default value for field"
    }
  ],
  "patch": [
    {
      "key": {
        "id": "FIELD_COLUMN"
      },
      "data": {
        "descriptions": {
          "en": "field description modified"
        },
        "editability": true,
        "mandatory": false,
        "dictionary": {
          "id": 27
        }
      }
    }
  ],
  "delete": [
    {
      "id": 46
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.

INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Dataset Fields to partially update. Each item contains a key identifying the Dataset Field to update and a data object containing only the properties to modify.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

[dataset_field_deleteDatasetField]

Deletes an AIH Dataset Field

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

*** id (string):** Field code.

[dataset_field_find]

Returns AIH Dataset Fields matching the optional FIQL filter within the specified AIH Dataset. Use this to search or list AIH Dataset Fields. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL') String values must be enclosed in double quotes. For example, use `fieldType=="MEASURE"` or `dimensionType=="ENTITY"`; do not use unquoted values such as `fieldType=MEASURE`. Exact `fieldType` and `dimensionType` filters are applied locally after retrieving the dataset fields, due to an upstream API filter defect.

- Filterable properties:

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- id
- descriptions
- fieldType
- formatType
- personalDataProtection
- encoded
- timeDimensionRollup
- conversionType
- dimensionType
- hierarchyId
- values.dictionary.id
- mandatory
- key
- editability
- referenceType
- updateInfo.user
- updateInfo.date
- updateInfo.origin

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

[dataset_field_getById]

Returns one AIH Dataset Field identified by its ID within the specified AIH Dataset. Use this when the AIH Dataset Field ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

*** id (string):** Field code.

[dataset_field_updateDatasetField]

Updates an existing AIH Dataset Field only for properties passed as input

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "string",
  "datasetId": "string",
  "id": "string",
  "body": {
    "descriptions": {
      "en": "field description modified"
    },
    "editability": true,
    "mandatory": false,
    "dictionary": {
      "id": 27
    }
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

*** id (string):** Field code.

*** body (object):** Partial update object -- include only the properties you want to change for this resource. Immutable properties are ignored if passed.

Dataset partitions

AIH data and foundation · 4 operations

[dataset_partitions_addDatasetPartition]

Creates a new AIH Dataset Partition with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "datasetId": "ABCDEF",
  "process": {
    "id": "ACT"
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  },
  "scenario": {
    "id": "2019ACT"
  },
  "period": {
    "id": 12
  },
  "entity": {
    "id": "$"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

process (any):

scenario (any):

period (any):

entity (any):

[dataset_partitions_count]

Returns the number of AIH Dataset Partitions matching the optional FIQL filter. Use this when only the count is needed, not the AIH Dataset Partition data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable fields:
- id
- process.id
- process.description
- scenario.id
- scenario.description

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- period.id
- period.description
- entity.id
- entity.description
- typology.id
- typology.description
- status

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

[dataset_partitions_find]

Returns AIH Dataset Partitions matching the optional FIQL filter within the specified AIH Dataset. Use this to search or list AIH Dataset Partitions. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable fields:
- id
- process.id
- process.description
- scenario.id
- scenario.description
- period.id
- period.description
- entity.id
- entity.description
- typology.id
- typology.description
- status

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[dataset_partitions_getById]

Returns one AIH Dataset Partition identified by its ID within the specified AIH Dataset. Use this when the AIH Dataset Partition ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

*** id (string):** dataset partition id.

Dataset availability

AIH data and foundation · 4 operations

[dataset_set_offline_setOffline]

Sets the AIH Datasets specified in the body offline

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "datasets": [
    "ABC",
    "BBB"
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

datasets (array): Datasets to be set offline.

[dataset_set_offline_setOffline_2]

Sets the AIH Datasets specified in the body offline

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "datasets": [
    "ABC",
    "BBB"
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

datasets (array): Datasets to be set offline.

[dataset_set_online_setOnline]

Sets the AIH Datasets specified in the body online

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "datasets": [
    "ABC",
    "BBB"
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

datasets (array): Datasets to be set online.

[dataset_set_online_setOnline_2]

Sets the AIH Datasets specified in the body online

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.

INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "datasets": [
    "ABC",
    "BBB"
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

datasets (array): Datasets to be set online.

Dataset typologies

AIH data and foundation · 4 operations

[typology_count]

Returns the number of Typologies matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[typology_elementsFetch]

Returns only selected properties of Typologies matching the optional FIQL filter. Use this tool instead of find when only specific properties are needed. Specify the properties as a comma-separated list.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** properties (string):** Comma-separated properties to fetch. **Please note that description property is set with user default language**

sort (string): Sort parameter for sorting

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

*** workspaceId (string):** Workspace code

*** datasetId (string):** Dataset code.

[typology_find]

Returns Typologies matching the optional FIQL filter. Use this tool to search or list Typologies. Supports filtering, sorting, and pagination. Resource hierarchy: Workspace > Dataset

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

*** datasetId (string):** Dataset code.

[typology_getById]

Returns one Typology identified by its ID. Use this tool when the resource ID is already known. Resource hierarchy: Workspace > Dataset

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Typology code.

*** datasetId (string):** Dataset code.

Datasources

AIH data and foundation · 7 operations

[datasource_addDatasource]

Creates a new AIH Datasource with LOOSE save mode (validation ignoring warnings). Send SQL query text in customQuery using secured-oracle, secured-sqlServer, secured-hana, secured-postgres, or secured-others. The secured- prefix applies to the properties containing SQL text, not to customQuery.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "id": "100001",
  "oid": "XYH6HHyi999HHG1234",
  "descriptions": {
    "en": "Example Datasource",
    "it": "Datasource di esempio"
  },
  "sort": [
    {
      "field": "LABEL",
      "sortPosition": "0",
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "sortType": "DESC"
    }
  ],
  "customQuery": {
    "secured-oracle": "SELECT A,B,C FROM TABLE",
    "secured-sqlServer": "SELECT A,B,C FROM TABLE",
    "secured-hana": "SELECT A,B,C FROM TABLE",
    "secured-postgres": "SELECT A,B,C FROM TABLE",
    "secured-others": "SELECT A,B,C FROM TABLE"
  },
  "connection": "DB_SCHEMA_1"
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Datasource code, Immutable

oid (string): Workspace table oid , immutable, not required

*** descriptions (object):** Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

sort (array):

customQuery (any):

connection (string): Datasource connection. Available options are

* `Current` means current connection
* `DB SCHEMA` the schema name for the connection

`[datasource_count]`

Returns the number of AIH Datasources matching the optional FIQL filter. Use this when only the count is needed, not the AIH Datasource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable fields:

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** workspaceId (string):** Workspace code.

[datasource_datasourceBulk]

Performs bulk create, replace, and partial update operations on AIH Datasources. Use this tool when multiple AIH Datasources in the same AIH Workspace must be changed in a single request. In post/put items or patch data, send SQL query text in customQuery using secured-oracle, secured-sqlServer, secured-hana, secured-postgres, or secured-others. The secured- prefix applies to the properties containing SQL text, not to customQuery.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "saveMode": "LOOSE",
  "post": [
    {
      "id": "100001",
      "oid": "XYH6HHyi999HHG1234",
      "descriptions": {
        "en": "Example Datasource",
        "it": "Datasource di esempio"
      },
      "sort": [
        {
          "field": "LABEL",
          "sortPosition": "0",
          "sortType": "DESC"
        }
      ],
      "customQuery": {
        "secured-oracle": "SELECT A,B,C FROM TABLE",
        "secured-sqlServer": "SELECT A,B,C FROM TABLE",
        "secured-hana": "SELECT A,B,C FROM TABLE",
        "secured-postgres": "SELECT A,B,C FROM TABLE",
        "secured-others": "SELECT A,B,C FROM TABLE"
      },
      "connection": "DB_SCHEMA_1"
    }
  ],
  "put": [
    {
      "id": "100001",
      "oid": "XYH6HHyi999HHG1234",
      "descriptions": {
        "en": "Example Datasource",
        "it": "Datasource di esempio"
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      },
      "sort": [
        {
          "field": "LABEL",
          "sortPosition": "0",
          "sortType": "DESC"
        }
      ],
      "customQuery": {
        "secured-oracle": "SELECT A,B,C FROM TABLE",
        "secured-sqlServer": "SELECT A,B,C FROM TABLE",
        "secured-hana": "SELECT A,B,C FROM TABLE",
        "secured-postgres": "SELECT A,B,C FROM TABLE",
        "secured-others": "SELECT A,B,C FROM TABLE"
      },
      "connection": "DB_SCHEMA_1"
    }
  ],
  "patch": [
    {
      "key": {
        "id": "100001"
      },
      "data": {
        "descriptions": {
          "en": "dataset english description to be modified"
        },
        "customQuery": {
          "secured-oracle": "SELECT 1 FROM DUAL"
        }
      }
    }
  ],
  "delete": [
    {
      "id": 46
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

patch (array): Datasources to partially update. Each item contains a key identifying the Datasource to update and a data object containing only the properties to modify.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

[datasource_deleteDatasource]

Deletes an AIH Datasource

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Datasource code.

[datasource_find]

Returns AIH Datasources matching the optional FIQL filter within the specified AIH Workspace. Use this to search or list AIH Datasources. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[datasource_getById]

Returns one AIH Datasource identified by its ID within the specified AIH Workspace. Use this when the AIH Datasource ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Datasource code.

[datasource_updateDatasource]

Updates an existing AIH Datasource only for properties passed as input. Send SQL query text in customQuery using secured-oracle, secured-sqlServer, secured-hana, secured-postgres, or secured-others. The secured- prefix applies to the properties containing SQL text, not to customQuery.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "string",
  "id": "string",
  "descriptions": {
    "en": "Example Datasource",
    "it": "Datasource di esempio"
  },
  "sort": [
    {
      "field": "LABEL",
      "sortPosition": "0",
      "sortType": "DESC"
    }
  ],
  "customQuery": {
    "secured-oracle": "SELECT A,B,C FROM TABLE",
    "secured-sqlServer": "SELECT A,B,C FROM TABLE",
    "secured-hana": "SELECT A,B,C FROM TABLE",
    "secured-postgres": "SELECT A,B,C FROM TABLE",
    "secured-others": "SELECT A,B,C FROM TABLE"
  },
  "connection": "DB_SCHEMA_1"
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Datasource code.

descriptions (object): Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

sort (array):

customQuery (any):

connection (string): Datasource connection. Available options are * `Current` means current connection * `DB SCHEMA` the schema name for the connection

Datasource fields

AIH data and foundation · 7 operations

`[datasource_field_addDatasource]`

Creates a new AIH Datasource Field with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "datasourceId": 3,
  "body": {
    "encoded": false
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** datasourceId (string):** Datasource code.

*** body (object):** Field definition to create. The body must match one of these schemas: TextMeasurePost, NumericMeasurePost, DateMeasurePost, or LeafDimensionPost. All field types use the common field properties such as id, descriptions, fieldType, length, mandatory, editability, and key. Numeric fields may additionally define timeDimensionRollup and conversionType. Dimension fields define dimensionType and may define hierarchyId or dictionary.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[datasource_field_count]

Returns the number of AIH Datasource Fields matching the optional FIQL filter. Use this when only the count is needed, not the AIH Datasource Field data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL') Filterable properties:

- id
- descriptions
- fieldType
- values.dictionary.id
- updateInfo.user
- updateInfo.date
- updateInfo.origin

*** workspaceId (string):** Workspace code.

*** datasourcesId (string):** Datasource code.

[datasource_field_datasourceBulk]

Performs bulk create, replace, and partial update operations on AIH Datasource Fields. Use this tool when multiple AIH Datasource Fields in the same AIH Datasource must be changed in a single request.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "datasourceId": 2,
  "saveMode": "LOOSE",
  "post": [
    {
      "encoded": false
    }
  ],
  "put": [
    {
      "encoded": false
    }
  ],
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  "patch": [
    {
      "key": {
        "id": "FIELD_COLUMN"
      },
      "data": {
        "descriptions": {
          "en": "field description modified"
        },
        "mandatory": false,
        "values": {
          "dictionary": {
            "id": 27
          }
        }
      }
    }
  ],
  "delete": [
    {
      "id": 46
    }
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** datasourceId (string):** datasource code.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Datasource Fields to partially update. Each item contains a key identifying the Datasource Field to update and a data object containing only the properties to modify.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

[datasource_field_deleteDatasourceField]

Deletes an AIH Datasource Field

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** datasourceId (string):** datasource code.

*** id (string):** Field code.

[datasource_field_find]

Returns AIH Datasource Fields matching the optional FIQL filter within the specified AIH Datasource. Use this to search or list AIH Datasource Fields. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable properties:
- id
- descriptions
- fieldType
- values.dictionary.id
- updateInfo.user
- updateInfo.date
- updateInfo.origin

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

*** datasourceId (string):** Datasource code.

[datasource_field_getById]

Returns one AIH Datasource Field identified by its ID within the specified AIH Datasource. Use this when the AIH Datasource Field ID is already known.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** datasourceId (string):** datasource code.

*** id (string):** Field code.

[datasource_field_updateDatasourceField]

Updates an existing AIH Datasource Field only for properties passed as input

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "string",
  "datasourceId": "string",
  "id": "string",
  "body": {
    "descriptions": {
      "en": "field description modified"
    },
    "mandatory": false,
    "values": {
      "dictionary": {
        "id": 27
      }
    }
  }
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** datasourceId (string):** datasource code.

*** id (string):** Field code.

*** body (object):** Partial update object -- include only the properties you want to change for this resource. Immutable properties are ignored if passed.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Virtual datasets

AIH data and foundation · 7 operations

[virtual_dataset_addVirtualDataset]

Creates a new AIH Virtual Dataset with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "id": "000001",
  "oid": "XYH6HHyi999HHG1234",
  "descriptions": {
    "en": "Example Virtual dataset",
    "it": "Virtual dataset di esempio"
  },
  "relationships": [
    {
      "order": 1,
      "leftDataset": {
        "id": "000001",
        "includeAllFields": false
      },
      "rightDataset": {
        "id": "000001",
        "includeAllFields": false
      },
      "joinFields": [
        {
          "leftField": "FIELD01",
          "rightField": "FIELD02"
        }
      ]
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Virtual Dataset code, Immutable

oid (string): Virtual Dataset oid, Immutable, not required

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** descriptions (object):** Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

relationships (array): Relationships between the datasets used to build the virtual dataset. Each relationship defines the order, the left and right datasets, and the fields used to join them.

[virtual_dataset_count]

Returns the number of AIH Virtual Datasets matching the optional FIQL filter. Use this when only the count is needed, not the AIH Virtual Dataset data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable properties:
- id
- descriptions

*** workspaceId (string):** Workspace code.

[virtual_dataset_deleteVirtualDataset]

Deletes an AIH Virtual Dataset

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Virtual Dataset code.

[virtual_dataset_find]

Returns AIH Virtual Datasets matching the optional FIQL filter within the specified AIH Workspace. Use this to search or list AIH Virtual Datasets. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable properties:
- id
- descriptions
- updateInfo.user
- updateInfo.date
- updateInfo.origin

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

[virtual_dataset_getById]

Returns one AIH Virtual Dataset identified by its ID within the specified AIH Workspace. Use this when the AIH Virtual Dataset ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Virtual Dataset code.

[virtual_dataset_updateVirtualDataset]

Updates an existing AIH Virtual Dataset only for properties passed as input

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "string",
  "id": "string",
  "descriptions": {
    "en": "Example Virtual dataset",
    "it": "Virtual dataset di esempio"
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  },
  "sort": [
    {
      "field": "LABEL",
      "sortPosition": "0",
      "sortType": "DESC"
    }
  ],
  "relationships": [
    {
      "order": 1,
      "leftDataset": {
        "id": "000001",
        "includeAllFields": false
      },
      "rightDataset": {
        "id": "000001",
        "includeAllFields": false
      },
      "joinFields": [
        {
          "leftField": "FIELD01",
          "rightField": "FIELD02"
        }
      ]
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Virtual Dataset code.

descriptions (object): Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

sort (array):

relationships (array): Relationships between the datasets used to build the virtual dataset. Each relationship defines the order, the left and right datasets, and the fields used to join them.

[virtual_dataset_virtualDatasetBulk]

Performs bulk create, replace, and partial update operations on AIH Virtual Datasets. Use this tool when multiple AIH Virtual Datasets in the same AIH Workspace must be changed in a single request.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "saveMode": "LOOSE",
  "post": [
    {
      "id": "000001",
      "oid": "XYH6HHyi999HHG1234",
      "descriptions": {
        "en": "Example Virtual dataset",
        "it": "Virtual dataset di esempio"
      },
      "relationships": [
        {
          "order": 1,
          "leftDataset": {
            "id": "000001",
            "includeAllFields": false
          },
          "rightDataset": {
            "id": "000001",
            "includeAllFields": false
          },
          "joinFields": [
            {
              "leftField": "FIELD01",
              "rightField": "FIELD02"
            }
          ]
        }
      ]
    }
  ],
  "put": [
    {
      "id": "000001",
      "oid": "XYH6HHyi999HHG1234",
      "descriptions": {
        "en": "Example Virtual dataset",
        "it": "Virtual dataset di esempio"
      },
      "sort": [
        {
          "field": "LABEL",
          "sortPosition": "0",
          "sortType": "DESC"
        }
      ],
      "relationships": [
        {
          "order": 1,
          "leftDataset": {
            "id": "000001",
            "includeAllFields": false
          },
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.

INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
          "rightDataset": {
            "id": "000001",
            "includeAllFields": false
          },
          "joinFields": [
            {
              "leftField": "FIELD01",
              "rightField": "FIELD02"
            }
          ]
        }
      ]
    }
  ],
  "patch": [
    {
      "key": {
        "id": "000001"
      },
      "data": {
        "descriptions": {
          "en": "virtual dataset english description to be modified"
        },
        "sort": [
          {
            "field": "LABEL1",
            "sortPosition": "0",
            "sortType": "DESC"
          }
        ],
        "relationships": [
          {
            "leftDataset": {
              "id": "000001",
              "includeAllFields": false
            },
            "rightDataset": {
              "id": "000001",
              "includeAllFields": false
            },
            "joinFields": [
              {
                "leftField": "FIELD1",
                "rightField": "FIELD2"
              }
            ]
          }
        ]
      }
    }
  ],
  "delete": [
    {
      "id": "000056"
    }
  ]
}
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.

INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Virtual Datasets to partially update. Each item contains a key identifying the Virtual Dataset to update and a data object containing only the properties to modify.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

Virtual dataset fields

AIH data and foundation · 7 operations

`[virtual_dataset_field_addDataset]`

Creates a new AIH Virtual Dataset Field with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "virtualDatasetId": "A00003",
  "body": {
    "id": "MARGIN",
    "descriptions": {
      "en": "Margin formula",
      "it": "Formula margine"
    },
    "fieldType": "FORMULA",
    "formula": "${REVENUE}-${COSTS}",
    "timeDimensionRollup": "SUM",
    "conversionType": "NONE"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** virtualDatasetId (string):** Virtual Dataset code.

*** body (object):** Field definition to create. The body must match one of these schemas: FormulaPost or DatasetFieldPost. A DatasetFieldPost contains the common field properties such as id, descriptions, fieldType, length, mandatory, editability, and key. A FormulaPost additionally defines the formula expression and related formula settings.

[virtual_dataset_field_count]

Returns the number of AIH Virtual Dataset Fields matching the optional FIQL filter. Use this when only the count is needed, not the AIH Virtual Dataset Field data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

*** workspaceId (string):** Workspace code.

*** virtualDatasetId (string):** Virtual Dataset code.

[virtual_dataset_field_datasetBulk]

Performs bulk create, replace, and partial update operations on AIH Virtual Dataset Fields. Use this tool when multiple AIH Virtual Dataset Fields in the same AIH Virtual Dataset must be changed in a single request.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "virtualDatasetId": "A00003",
  "saveMode": "LOOSE",
  "post": [
    {
      "id": "MARGIN",
      "descriptions": {
        "en": "Margin formula",
        "it": "Formula margine"
      },
      "fieldType": "FORMULA",
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "formula": "${REVENUE}-${COSTS}",
      "timeDimensionRollup": "SUM",
      "conversionType": "NONE"
    }
  ],
  "put": [
    {
      "formula": "${FIELD01}",
      "timeDimensionRollup": "SUM",
      "conversionType": "NONE"
    }
  ],
  "patch": [
    {
      "formula": "${FIELD01}",
      "timeDimensionRollup": "SUM",
      "conversionType": "NONE"
    }
  ],
  "delete": [
    {
      "id": "000056"
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** virtualDatasetId (string):** Virtual Dataset code.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Virtual Dataset Fields to partially update. Each item contains the properties to modify directly; this schema does not use a key/data wrapper.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

[virtual_dataset_field_deleteDatasetField]

Deletes an AIH Virtual Dataset Field

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** virtualDatasetId (string):** Virtual Dataset code.

*** id (string):** Field code.

[virtual_dataset_field_find]

Returns AIH Virtual Dataset Fields matching the optional FIQL filter within the specified AIH Virtual Dataset. Use this to search or list AIH Virtual Dataset Fields. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable properties:
- id
- descriptions
- updateInfo.user
- updateInfo.date
- updateInfo.origin

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

*** virtualDatasetId (string):** Virtual Dataset code.

[virtual_dataset_field_getById]

Returns one AIH Virtual Dataset Field identified by its ID within the specified AIH Virtual Dataset. Use this when the AIH Virtual Dataset Field ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** virtualDatasetId (string):** Virtual Dataset code.

*** id (string):** Field code.

[virtual_dataset_field_updateDatasetField]

Updates an existing AIH Virtual Dataset Field only for properties passed as input

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "string",
  "virtualDatasetId": "A00003",
  "id": "string",
  "body": {
    "id": "MARGIN",
    "descriptions": {
      "en": "Margin formula",
      "it": "Formula margine"
    },
    "fieldType": "FORMULA",
    "formula": "${REVENUE}-${COSTS}",
    "timeDimensionRollup": "SUM",
    "conversionType": "NONE"
  }
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** virtualDatasetId (string):** Virtual Dataset code.

*** id (string):** Field code.

*** body (object):** Partial field update. The body must contain only the properties to modify and match the DatasetFieldPatchData structure, such as descriptions, editability, mandatory, or other mutable field properties. Immutable properties are ignored.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

AIH dictionaries

AIH data and foundation · 7 operations

[dictionary_addDictionary]

Creates a new AIH Dictionary with LOOSE save mode (validation ignoring warnings). Send SQL query text in queryBody using secured-oracle, secured-sqlServer, secured-hana, secured-postgres, or secured-others. The secured- prefix applies to the properties containing SQL text, not to queryBody.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "id": "123456",
  "oid": "XYH6HHyi999HHG1234",
  "descriptions": {
    "en": "Example Dictionary",
    "it": "Dictionary di esempio"
  },
  "queryBody": {
    "secured-oracle": "SELECT ABC FROM TABLE",
    "secured-sqlServer": "SELECT ABC FROM TABLE",
    "secured-hana": "SELECT ABC FROM TABLE",
    "secured-postgres": "SELECT ABC FROM TABLE",
    "secured-others": "SELECT ABC FROM TABLE"
  },
  "personalDataManagement": [
    "ABC",
    "DEF"
  ],
  "connection": "DB_SCHEMA_1"
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Dictionary code, Immutable

oid (string): Dictionary oid, not required

*** descriptions (object):** Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

queryBody (any):

personalDataManagement (array): List of Query Fields name that contains personal data

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

connection (string): Datasource connection. Available options are

* `Current` means current connection
* `DB SCHEMA` the schema name for the connection

[dictionary_count]

Returns the number of AIH Dictionaries matching the optional FIQL filter. Use this when only the count is needed, not the AIH Dictionary data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** workspaceId (string):** Workspace code.

[dictionary_deleteDictionary]

Deletes an AIH Dictionary

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** dictionary code.

[dictionary_dictionaryBulk]

Performs bulk create, replace, and partial update operations on AIH Dictionaries. Use this tool when multiple AIH Dictionaries in the same AIH Workspace must be changed in a single request. Send SQL query text in queryBody in post/put items or patch data, using secured-oracle, secured-sqlServer, secured-hana, secured-postgres, or secured-others as property names. The secured- prefix applies to the properties containing SQL text, not to queryBody.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "XYZ",
  "saveMode": "LOOSE",
  "post": [
    {
      "id": "123456",
      "oid": "XYH6HHyi999HHG1234",
      "descriptions": {
        "en": "Example Dictionary",
        "it": "Dictionary di esempio"
      },
      "queryBody": {
        "secured-oracle": "SELECT ABC FROM TABLE",
        "secured-sqlServer": "SELECT ABC FROM TABLE",
        "secured-hana": "SELECT ABC FROM TABLE",
        "secured-postgres": "SELECT ABC FROM TABLE",
        "secured-others": "SELECT ABC FROM TABLE"
      },
      "personalDataManagement": [
        "ABC",
        "DEF"
      ],
      "connection": "DB_SCHEMA_1"
    }
  ],
  "put": [
    {
      "id": "123456",
      "oid": "XYH6HHyi999HHG1234",
      "descriptions": {
        "en": "Example Dictionary",
        "it": "Dictionary di esempio"
      },
      "queryBody": {
        "secured-oracle": "SELECT ABC FROM TABLE",
        "secured-sqlServer": "SELECT ABC FROM TABLE",
        "secured-hana": "SELECT ABC FROM TABLE",
        "secured-postgres": "SELECT ABC FROM TABLE",
        "secured-others": "SELECT ABC FROM TABLE"
      },
      "personalDataManagement": [
        "ABC",
        "DEF"
      ],
      "connection": "DB_SCHEMA_1"
    }
  ],
  "patch": [
    {
      "key": {
        "id": "100001"
      },
      "data": {
        "descriptions": {
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
          "en": "dataset english description to be modified"
        },
        "queryBody": {
          "secured-oracle": "SELECT 1 FROM DUAL"
        }
      }
    }
  ],
  "delete": [
    {
      "id": 46
    }
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Dictionaries to partially update. Each item contains a key identifying the Dictionary to update and a data object containing only the properties to modify.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

[dictionary_find]

Returns AIH Dictionaries matching the optional FIQL filter within the specified AIH Workspace. Use this to search or list AIH Dictionaries. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL. All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

[dictionary_getById]

Returns one AIH Dictionary identified by its ID within the specified AIH Workspace. Use this when the AIH Dictionary ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** dictionary code.

[dictionary_updateDictionary]

Updates an existing AIH Dictionary only for properties passed as input. Send SQL query text in queryBody, using secured-oracle, secured-sqlServer, secured-hana, secured-postgres, or secured-others as property names. The secured- prefix applies to the properties containing SQL text, not to queryBody.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "workspaceId": "string",
  "id": "string",
  "oid": "XYH6HHyi999HHG1234",
  "descriptions": {
    "en": "Example Dictionary",
    "it": "Dictionary di esempio"
  },
  "queryBody": {
    "secured-oracle": "SELECT ABC FROM TABLE",
    "secured-sqlServer": "SELECT ABC FROM TABLE",
    "secured-hana": "SELECT ABC FROM TABLE",
    "secured-postgres": "SELECT ABC FROM TABLE",
    "secured-others": "SELECT ABC FROM TABLE"
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  },
  "personalDataManagement": [
    "ABC",
    "DEF"
  ],
  "connection": "DB_SCHEMA_1"
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** dictionary code.

oid (string): Dictionary oid, not required

descriptions (object): Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

queryBody (any):

personalDataManagement (array): List of Query Fields name that contains personal data

connection (string): Datasource connection. Available options are * `Current` means current connection * `DB SCHEMA` the schema name for the connection

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

02

Data Model and master data

88 operations

Accounts 5

Account hierarchies 6

Account hierarchy relationships 7

Account hierarchy structure 6

Entities 6

Entity hierarchies 7

Entity hierarchy structure 7

Analytical dimensions 6

Custom dimensions 3

Categories 6

Currencies 6

Scenarios 6

Scenario periods 7

Periods 3

Shared dictionary items 7

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Accounts

Data Model and master data · 5 operations

[account_addAccount]

Creates a new Account with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "10010",
  "descriptions": {
    "en": "Cash in Bank Accounts",
    "it": "Cash in Bank Accounts",
    "es": "Cash in Bank Accounts"
  },
  "alternativeDescriptions": {
    "en": "Cash in Bank Accounts",
    "it": "Cash in Bank Accounts",
    "es": "Cash in Bank Accounts"
  },
  "customAttributes": {
    "Country": "Italy",
    "Entering group": "1090",
    "Leaving group": "1088",
    "Other custom attribute": "Other"
  },
  "nature": "BALANCE_SHEET",
  "type": "NORMAL",
  "conversion": {
    "conversionType": "FINAL",
    "referenceAccountForInitialBalance": 10015
  },
  "consolidation": {
    "rules": {
      "useAccountForSetup": false,
      "excludeFromProportionalCalculation": true
    },
    "bankingData": {
      "bankitReportingMItem": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "bankitReportingMItemICGroup": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "bankitReporting1Item": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      },
      "bankitReportingEPItem": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "ebaSignalingSubAccount": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "bankitReportingMItemOld": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "icIitemOld": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      }
    }
  },
  "dataEntryAndReporting": {
    "validity": {
      "startDate": "2017-07-21",
      "endDate": "2034-07-21"
    },
    "class": "NONE",
    "manageTransactionCurrency": true,
    "icManagement": false,
    "manageMaximumNumberDecimals": true
  },
  "documentationLink": "string",
  "rules": {
    "grossAmountEqualICSum": true,
    "accrual": {
      "debitAccrual": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "creditAccrual": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "validationChecks": {
      "standardSignCheck": "ANY",
      "icCapacityCheck": "DO_NOT_CHECK",
      "fxRatesCheck": "DO_NOT_CHECK",
      "icSignCheck": "DO_NOT_CHECK",
      "notesCheck": "DO_NOT_CHECK"
    }
  },
  "restrictions": {
    "customDimension1": {
      "dimensionName": "Cost center",
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "restriction": "RESTRICTED"
    },
    "customDimension2": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension3": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension4": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension5": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "ctpRestriction": {
      "id": 1,
      "description": "CTP Dynamic group"
    }
  },
  "cashFlowPlanning": {
    "variation": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "receivablePayable": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "liquidity": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "other": {
      "debit": {
        "id": "10010",
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "additionalCreditAccrualAccount": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "additionalDebitAccrualAccount": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "revaluationDevaluation": {
      "enable": true,
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    }
  },
  "monthlySplittingRules": {
    "monthlySplittingType": false,
    "reference": {
      "referenceAccount": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "referenceAccountHierarchy": {
        "hierarchyId": "$",
        "nodeId": 8,
        "description": "Income statement"
      },
      "referenceSenario": "string",
      "customDimension1Filter": "LOWEST_LEVEL",
      "customDimension2Filter": "LOWEST_LEVEL",
      "customDimension3Filter": "LOWEST_LEVEL",
      "customDimension4Filter": "LOWEST_LEVEL",
      "customDimension5Filter": "LOWEST_LEVEL",
      "categoryFilter": "NONE",
      "entityCtpFilter": "LOWEST_LEVEL",
      "customDimension2CtpFilter": "LOWEST_LEVEL"
    }
  },
  "updateInfo": {
    "user": "anUser",
    "date": "2017-07-21T17:32:28.581+0000",
    "origin": "INPUT_WEB"
  }
}
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Unique ID of the Account, Immutable

*** descriptions (object):** Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

alternativeDescriptions (object): Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

customAttributes (any):

*** nature (string):** Nature of the account. Mandatory Field. Possible values are: - Profit&Loss - Balance Sheet - Guaranties&Commitments - Other Variations - Other Stocks

*** type (string):** Type of the account. Mandatory Field. Possible values are:

- Normal
- Detail
- Variation An account of Variation type can't be of Profit&Loss nature or of Other Variations type.

conversion (any):

consolidation (any):

dataEntryAndReporting (any):

documentationLink (string): Allows to create a hypertextual link to a web page (world wide web) or to a web page inside an intranet so that additional information for the current element can be inserted.

rules (any):

restrictions (any):

cashFlowPlanning (any):

monthlySplittingRules (any):

updateInfo (any):

[account_count]

Returns the number of Accounts matching the optional FIQL filter. Use this when only the count is needed, not the Account data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL - Filterable properties:

- id

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- descriptions
- alternativeDescriptions
- customAttributes
- nature
- type
- conversion-conversionType
- conversion.referenceAccountForInitialBalance
- restrictions.customDimension1.restricted
- restrictions.customDimension2.restricted
- restrictions.customDimension3.restricted
- restrictions.customDimension4.restricted
- restrictions.customDimension5.restricted
- dataEntryAndReporting.validity.startDate
- dataEntryAndReporting.validity.endDate
- dataEntryAndReporting.class
- dataEntryAndReporting.manageTransactionCurrency
- dataEntryAndReporting.icManagement
- dataEntryAndReporting.manageMaximumNumberDecimals
- rules.grossAmountEqualICSum
- rules.accrual.debit.id
- rules.accrual.credit.id
- rules.consolidaton.useAccountForSetup
- rules.consolidaton.excludeFromProportionalCalculation
- rules.validationChecks.standardSignCheck
- rules.validationChecks.icCapacityCheck
- rules.validationChecks.fxRatesCheck
- rules.validationChecks.icSignCheck
- rules.validationChecks.notesCheck
- updateInfo.origin
- updateInfo.user
- updateInfo.date

[account_find]

Returns Accounts matching the optional FIQL filter. Use this to search or list Accounts. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

filter (string): Filter string which is compliant to FIQL

- Filterable properties:
- id
- descriptions
- alternativeDescriptions
- customAttributes
- nature
- type
- conversion-conversionType
- conversion.referenceAccountForInitialBalance
- restrictions.customDimension1.dimensionName
- restrictions.customDimension1.restriction
- restrictions.customDimension2.dimensionName
- restrictions.customDimension2.restriction
- restrictions.customDimension3.dimensionName
- restrictions.customDimension3.restriction
- restrictions.customDimension4.dimensionName
- restrictions.customDimension4.restriction
- restrictions.customDimension5.dimensionName
- restrictions.customDimension5.restriction
- restrictions.ctpRestriction.id
- consolidation.rules.useAccountForSetup
- consolidation.rules.excludeFromProportionalCalculation
- consolidation.bankingData.bankitReportingMItem.id
- consolidation.bankingData.bankitReportingMItem.changeSign
- consolidation.bankingData.bankitReportingMItemICGroup.id
- consolidation.bankingData.bankitReportingMItemICGroup.changeSign
- consolidation.bankingData.bankitReporting1Item.id
- consolidation.bankingData.bankitReporting1Item.changeSign
- consolidation.bankingData.bankitReportingEPItem.id
- consolidation.bankingData.bankitReportingEPItem.changeSign
- consolidation.bankingData.ebaSignalingSubAccount.id
- consolidation.bankingData.ebaSignalingSubAccount.changeSign
- consolidation.bankingData.bankitReportingMItemOld.id
- consolidation.bankingData.bankitReportingMItemOld.changeSign
- consolidation.bankingData.icItemOld.id
- consolidation.bankingData.icItemOld.changeSign
- dataEntryAndReporting.validity.startDate
- dataEntryAndReporting.validity.endDate
- dataEntryAndReporting.class
- dataEntryAndReporting.manageTransactionCurrency
- dataEntryAndReporting.icManagement

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- dataEntryAndReporting.manageMaximumNumberDecimals
- rules.grossAmountEqualICSum
- rules.accrual.debitAccrual.id
- rules.accrual.creditAccrual.id
- rules.validationChecks.standardSignCheck
- rules.validationChecks.icCapacityCheck
- rules.validationChecks.fxRatesCheck
- rules.validationChecks.icSignCheck
- rules.validationChecks.notesCheck
- cashFlowPlanning.variation.debit.id
- cashFlowPlanning.variation.credit.id
- cashFlowPlanning.receivablePayable.debit.id
- cashFlowPlanning.receivablePayable.credit.id
- cashFlowPlanning.liquidity.debit.id
- cashFlowPlanning.liquidity.credit.id
- cashFlowPlanning.other.debit.id
- cashFlowPlanning.other.credit.id
- cashFlowPlanning.revaluationDevaluation.debit.id
- cashFlowPlanning.revaluationDevaluation.credit.id
- monthlySplittingRules.monthlySplittingType
- monthlySplittingRules.reference.referenceAccount.id
- monthlySplittingRules.reference.referenceAccountHierarchy.hierarchyId
- monthlySplittingRules.reference.referenceAccountHierarchy.nodeId
- monthlySplittingRules.reference.referenceSenario
- monthlySplittingRules.reference.categoryFilter
- updateInfo.origin
- updateInfo.user
- updateInfo.date example: id=like="dd";descriptions=like="ddd";customAttributes.Country="XXXX; restrictionCustomDimension1.restricted="RESTRICTED"

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

[account_originalAccountBulk]

Performs bulk create, replace, and partial update operations on Accounts. Use this tool when multiple Accounts must be changed in a single request.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "saveMode": "LOOSE",
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
"post": [
  {
    "id": "10010",
    "descriptions": {
      "en": "Cash in Bank Accounts",
      "it": "Cash in Bank Accounts",
      "es": "Cash in Bank Accounts"
    },
    "alternativeDescriptions": {
      "en": "Cash in Bank Accounts",
      "it": "Cash in Bank Accounts",
      "es": "Cash in Bank Accounts"
    },
    "customAttributes": {
      "Country": "Italy",
      "Entering group": "1090",
      "Leaving group": "1088",
      "Other custom attribute": "Other"
    },
    "nature": "BALANCE_SHEET",
    "type": "NORMAL",
    "conversion": {
      "conversionType": "FINAL",
      "referenceAccountForInitialBalance": 10015
    },
    "consolidation": {
      "rules": {
        "useAccountForSetup": false,
        "excludeFromProportionalCalculation": true
      },
      "bankingData": {
        "bankitReportingMItem": {
          "id": "ITEM_ID",
          "description": "Bankit item description",
          "changeSign": true
        },
        "bankitReportingMItemICGroup": {
          "id": "ITEM_ID",
          "description": "Bankit item description",
          "changeSign": true
        },
        "bankitReporting1Item": {
          "id": "ITEM_ID",
          "description": "Bankit item description",
          "changeSign": true
        },
        "bankitReportingEPItem": {
          "id": "ITEM_ID",
          "description": "Bankit item description",
          "changeSign": true
        },
        "ebaSignalingSubAccount": {
          "id": "ITEM_ID",
          "description": "Bankit item description",
          "changeSign": true
        },
        "bankitReportingMItemOld": {
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "icIitemOld": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      }
    }
  },
  "dataEntryAndReporting": {
    "validity": {
      "startDate": "2017-07-21",
      "endDate": "2034-07-21"
    },
    "class": "NONE",
    "manageTransactionCurrency": true,
    "icManagement": false,
    "manageMaximumNumberDecimals": true
  },
  "documentationLink": "string",
  "rules": {
    "grossAmountEqualICSum": true,
    "accrual": {
      "debitAccrual": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "creditAccrual": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "validationChecks": {
      "standardSignCheck": "ANY",
      "icCapacityCheck": "DO_NOT_CHECK",
      "fxRatesCheck": "DO_NOT_CHECK",
      "icSignCheck": "DO_NOT_CHECK",
      "notesCheck": "DO_NOT_CHECK"
    }
  },
  "restrictions": {
    "customDimension1": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension2": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension3": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension4": {
      "dimensionName": "Cost center",
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "restriction": "RESTRICTED"
    },
    "customDimension5": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "ctpRestriction": {
      "id": 1,
      "description": "CTP Dynamic group"
    }
  },
  "cashFlowPlanning": {
    "variation": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "receivablePayable": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "liquidity": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "other": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "additionalCreditAccrualAccount": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "additionalDebitAccrualAccount": {
        "id": "10010",
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.

INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
            "description": "Cash in Bank Accounts"
          }
        },
        "revaluationDevaluation": {
          "enable": true,
          "debit": {
            "id": "10010",
            "description": "Cash in Bank Accounts"
          },
          "credit": {
            "id": "10010",
            "description": "Cash in Bank Accounts"
          }
        }
      },
      "monthlySplittingRules": {
        "monthlySplittingType": false,
        "reference": {
          "referenceAccount": {
            "id": "10010",
            "description": "Cash in Bank Accounts"
          },
          "referenceAccountHierarchy": {
            "hierarchyId": "$",
            "nodeId": 8,
            "description": "Income statement"
          },
          "referenceSenario": "string",
          "customDimension1Filter": "LOWEST_LEVEL",
          "customDimension2Filter": "LOWEST_LEVEL",
          "customDimension3Filter": "LOWEST_LEVEL",
          "customDimension4Filter": "LOWEST_LEVEL",
          "customDimension5Filter": "LOWEST_LEVEL",
          "categoryFilter": "NONE",
          "entityCtpFilter": "LOWEST_LEVEL",
          "customDimension2CtpFilter": "LOWEST_LEVEL"
        }
      },
      "updateInfo": {
        "user": "anUser",
        "date": "2017-07-21T17:32:28.581+0000",
        "origin": "INPUT_WEB"
      }
    }
  ],
  "put": [
    {
      "id": "10010",
      "descriptions": {
        "en": "Cash in Bank Accounts",
        "it": "Cash in Bank Accounts",
        "es": "Cash in Bank Accounts"
      },
      "alternativeDescriptions": {
        "en": "Cash in Bank Accounts",
        "it": "Cash in Bank Accounts",
        "es": "Cash in Bank Accounts"
```


© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  },
  "customAttributes": {
    "Country": "Italy",
    "Entering group": "1090",
    "Leaving group": "1088",
    "Other custom attribute": "Other"
  },
  "nature": "BALANCE_SHEET",
  "type": "NORMAL",
  "conversion": {
    "conversionType": "FINAL",
    "referenceAccountForInitialBalance": 10015
  },
  "consolidation": {
    "rules": {
      "useAccountForSetup": false,
      "excludeFromProportionalCalculation": true
    },
    "bankingData": {
      "bankitReportingMItem": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "bankitReportingMItemICGroup": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "bankitReporting1Item": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "bankitReportingEPItem": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "ebaSignalingSubAccount": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "bankitReportingMItemOld": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "icIitemOld": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      }
    }
  },
  "dataEntryAndReporting": {
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
    "validity": {
      "startDate": "2017-07-21",
      "endDate": "2034-07-21"
    },
    "class": "NONE",
    "manageTransactionCurrency": true,
    "icManagement": false,
    "manageMaximumNumberDecimals": true
  },
  "documentationLink": "string",
  "rules": {
    "grossAmountEqualICSum": true,
    "accrual": {
      "debitAccrual": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "creditAccrual": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "validationChecks": {
      "standardSignCheck": "ANY",
      "icCapacityCheck": "DO_NOT_CHECK",
      "fxRatesCheck": "DO_NOT_CHECK",
      "icSignCheck": "DO_NOT_CHECK",
      "notesCheck": "DO_NOT_CHECK"
    }
  },
  "restrictions": {
    "customDimension1": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension2": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension3": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension4": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension5": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "ctpRestriction": {
      "id": 1,
      "description": "CTP Dynamic group"
    }
  },
  "cashFlowPlanning": {
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
    "variation": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "receivablePayable": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "liquidity": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "other": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "additionalCreditAccrualAccount": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "additionalDebitAccrualAccount": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "revaluationDevaluation": {
      "enable": true,
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
        }
      }
    },
    "monthlySplittingRules": {
      "monthlySplittingType": false,
      "reference": {
        "referenceAccount": {
          "id": "10010",
          "description": "Cash in Bank Accounts"
        },
        "referenceAccountHierarchy": {
          "hierarchyId": "$",
          "nodeId": 8,
          "description": "Income statement"
        },
        "referenceSenario": "string",
        "customDimension1Filter": "LOWEST_LEVEL",
        "customDimension2Filter": "LOWEST_LEVEL",
        "customDimension3Filter": "LOWEST_LEVEL",
        "customDimension4Filter": "LOWEST_LEVEL",
        "customDimension5Filter": "LOWEST_LEVEL",
        "categoryFilter": "NONE",
        "entityCtpFilter": "LOWEST_LEVEL",
        "customDimension2CtpFilter": "LOWEST_LEVEL"
      }
    },
    "updateInfo": {
      "user": "anUser",
      "date": "2017-07-21T17:32:28.581+0000",
      "origin": "INPUT_WEB"
    }
  }
],
"patch": [
  {
    "key": {
      "id": 50010
    },
    "data": {
      "descriptions": {
        "en": "New York"
      },
      "defaultDimensions": [
        {
          "dimension": "$CUSTOM_DIM1",
          "id": "CC_500"
        }
      ],
      "restrictions": [
        {
          "dimension": "$CUSTOM_DIM2",
          "restriction": "RESTRICTED"
        },
        {
          "dimension": "$CUSTOM_DIM3",
          "restriction": "NONE"
        }
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
        ],
        "customAttributes": {
          "Country": "Italia",
          "Unit group": "1098"
        }
      }
    }
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Accounts to partially update. Each item contains a key identifying the Account and a data object containing only the properties to modify.

[account_updateAccount]

Updates an existing Account only for properties passed as input

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "string",
  "descriptions": {
    "en": "Cash in Bank Accounts",
    "it": "Cash in Bank Accounts",
    "es": "Cash in Bank Accounts"
  },
  "alternativeDescriptions": {
    "en": "Cash in Bank Accounts",
    "it": "Cash in Bank Accounts",
    "es": "Cash in Bank Accounts"
  },
  "customAttributes": {
    "Country": "Italy",
    "Entering group": "1090",
    "Leaving group": "1088",
    "Other custom attribute": "Other"
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  },
  "nature": "BALANCE_SHEET",
  "type": "NORMAL",
  "conversion": {
    "conversionType": "FINAL",
    "referenceAccountForInitialBalance": 10015
  },
  "consolidation": {
    "rules": {
      "useAccountForSetup": false,
      "excludeFromProportionalCalculation": true
    },
    "bankingData": {
      "bankitReportingMItem": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "bankitReportingMItemICGroup": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "bankitReporting1Item": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "bankitReportingEPItem": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "ebaSignalingSubAccount": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "bankitReportingMItemOld": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      },
      "icIitemOld": {
        "id": "ITEM_ID",
        "description": "Bankit item description",
        "changeSign": true
      }
    }
  },
  "dataEntryAndReporting": {
    "validity": {
      "startDate": "2017-07-21",
      "endDate": "2034-07-21"
    },
    "class": "NONE",
    "manageTransactionCurrency": true,
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
    "icManagement": false,
    "manageMaximumNumberDecimals": true
  },
  "documentationLink": "string",
  "rules": {
    "grossAmountEqualICSum": true,
    "accrual": {
      "debitAccrual": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "creditAccrual": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "validationChecks": {
      "standardSignCheck": "ANY",
      "icCapacityCheck": "DO_NOT_CHECK",
      "fxRatesCheck": "DO_NOT_CHECK",
      "icSignCheck": "DO_NOT_CHECK",
      "notesCheck": "DO_NOT_CHECK"
    }
  },
  "restrictions": {
    "customDimension1": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension2": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension3": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension4": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "customDimension5": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "ctpRestriction": {
      "id": 1,
      "description": "CTP Dynamic group"
    }
  },
  "cashFlowPlanning": {
    "variation": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "receivablePayable": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "liquidity": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "other": {
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "additionalCreditAccrualAccount": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "additionalDebitAccrualAccount": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    },
    "revaluationDevaluation": {
      "enable": true,
      "debit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "credit": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      }
    }
  },
  "monthlySplittingRules": {
    "monthlySplittingType": false,
    "reference": {
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "referenceAccount": {
        "id": "10010",
        "description": "Cash in Bank Accounts"
      },
      "referenceAccountHierarchy": {
        "hierarchyId": "$",
        "nodeId": 8,
        "description": "Income statement"
      },
      "referenceSenario": "string",
      "customDimension1Filter": "LOWEST_LEVEL",
      "customDimension2Filter": "LOWEST_LEVEL",
      "customDimension3Filter": "LOWEST_LEVEL",
      "customDimension4Filter": "LOWEST_LEVEL",
      "customDimension5Filter": "LOWEST_LEVEL",
      "categoryFilter": "NONE",
      "entityCtpFilter": "LOWEST_LEVEL",
      "customDimension2CtpFilter": "LOWEST_LEVEL"
    }
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Account code.

descriptions (object): Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

alternativeDescriptions (object): Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

customAttributes (any):

nature (string): Nature of the account. Mandatory Field. Possible values are: - Profit&Loss - Balance Sheet - Guaranties&Commitments - Other Variations - Other Stocks

type (string): Type of the account. Mandatory Field. Possible values are: - Normal - Detail - Variation An account of Variation type can't be of Profit&Loss nature or of Other Variations type.

conversion (any):

consolidation (any):

dataEntryAndReporting (any):

documentationLink (string): Allows to create a hypertextual link to a web page (world wide web) or to a web page inside an intranet so that additional information for the current element can be inserted.

rules (any):

restrictions (any):

cashFlowPlanning (any):

monthlySplittingRules (any):

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Account hierarchies

Data Model and master data · 6 operations

[account_hierarchy_countAccountHierarchy]

Returns the number of Account Hierarchies matching the optional FIQL filter. Use this when only the count is needed, not the Account Hierarchy data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): FIQL filter string.

[account_hierarchy_createAccountHierarchy]

Create a new AccountHierarchy element

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "id": "02",
  "nodeCode": "ND_02",
  "descriptions": {
    "it": "Gerarchia conto 02",
    "en": "Account hierarchy 02"
  },
  "noReport": false,
  "generaFlat": false,
  "updateInfo": {}
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin override for update metadata.

id (string): Hierarchy element identifier.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

nodeCode (string): Immutable node code (set at creation, cannot be changed via PUT/PATCH).

descriptions (object): Multi-language description map.

noReport (boolean):

generaFlat (boolean):

updateInfo (object):

[account_hierarchy_fetchAccountHierarchy]

Returns only selected properties of matching Account Hierarchies. Use this instead of listAccountHierarchy when only specific properties are needed.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): FIQL filter string.

skip (integer): Paging offset.

take (integer): Paging size (max 10000).

sort (string): Sort expression.

*** properties (string):** Comma-separated properties to fetch.

[account_hierarchy_getAccountHierarchyById]

Returns one Account Hierarchy identified by its ID. Use this when the Account Hierarchy ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** AccountHierarchy element identifier.

[account_hierarchy_listAccountHierarchy]

Returns Account Hierarchies matching the optional FIQL filter. Use this to search or list Account Hierarchies. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): FIQL filter string.

skip (integer): Paging offset.

take (integer): Paging size (max 10000).

sort (string): Sort expression.

[account_hierarchy_updateAccountHierarchy]

Update AccountHierarchy element by id

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "id__path": "02",
  "id": "02",
  "descriptions": {
    "it": "Gerarchia conto 02",
    "en": "Account hierarchy 02"
  },
  "noReport": false,
  "generaFlat": false,
  "updateInfo": {}
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin override for update metadata.

*** id__path (string):** AccountHierarchy element identifier. (Path parameter)

id (string): Hierarchy element identifier.

descriptions (object): Multi-language description map.

noReport (boolean):

generaFlat (boolean):

updateInfo (object):

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Account hierarchy relationships

Data Model and master data · 7 operations

[account_hierarchy_relationships_addContoGerarchiaAbbiLowest]

Creates a new account-to-hierarchy-node assignment. The hierarchy is identified exclusively by {hId} in the URL path; there is no writable "hierarchy" field in the request body.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "hId": "02",
  "account": {
    "id": "50010",
    "description": "Ricavi totali netti"
  },
  "nodeCode": {
    "id": "50010",
    "description": "Ricavi totali netti"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Origin of the operation. If not provided, defaults to INPUT_WEB. Accepted values: INPUT_WEB, MDM, REST_API.

*** hId (string):** Hierarchy code (codGerarchia). Example values: "01", "02", "$". Note: this is NOT a numeric surrogate key.

account (any): WRITE_ONLY. Account reference; alternative to a top-level "id". At least one of "id" or "account.id" must be provided.

*** nodeCode (any):** Hierarchy node reference (mutable, required).

[account_hierarchy_relationships_contoGerarchiaAbbiLowestBulk]

Perform multiple create (post), replace (put), patch, and delete operations in a single request. Accepts both "id" and account-object addressing: when "id" is null but "account.id" (post/put/delete), or the patch key is absent while "data.account.id" is present, the controller normalizes the identifier server-side before delegating to the shared bulk pipeline.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "hId": "02",
  "saveMode": "LOOSE",
  "post": [
    {
      "account": {
        "id": "50010",
        "description": "Ricavi totali netti"
      },
      "nodeCode": {
        "id": "50010",
        "description": "Ricavi totali netti"
      }
    }
  ],
  "put": [
    {
      "id": "50010",
      "account": {
        "id": "50010",
        "description": "Ricavi totali netti"
      },
      "nodeCode": {
        "id": "50010",
        "description": "Ricavi totali netti"
      },
      "updateInfo": {
        "user": "RAFFAELLA",
        "date": "2011-03-03T16:30:52.780+0000",
        "origin": "INPUT_WEB"
      }
    }
  ],
  "patch": [
    {
      "key": {
        "id": "50010"
      },
      "data": {
        "nodeCode": {
          "id": "50030"
        }
      }
    }
  ],
  "delete": [
    {
      "id": "50010",
      "account": {
        "id": "50010",
        "description": "Ricavi totali netti"
      },
      "nodeCode": {
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
        "id": "50010",
        "description": "Ricavi totali netti"
      },
      "updateInfo": {
        "user": "RAFFAELLA",
        "date": "2011-03-03T16:30:52.780+0000",
        "origin": "INPUT_WEB"
      }
    }
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Origin of the operation. If not provided, defaults to INPUT_WEB. Accepted values: INPUT_WEB, MDM, REST_API.

*** hId (string):** Hierarchy code (codGerarchia).

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Items to create (POST)

put (array): Items to replace (PUT)

patch (array): Items to partially update (PATCH)

delete (array): Items to delete (DELETE). Only the id field is required.

[account_hierarchy_relationships_count]

Returns the number of Account-to-Node Relationships matching the optional FIQL filter. Use this when only the count is needed, not the relationship data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string compliant with FIQL.

*** hId (string):** Hierarchy code (codGerarchia).

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[account_hierarchy_relationships_deleteContoGerarchiaAbbiLowest]

Deletes the relationship and returns the deleted entity.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** hId (string):** Hierarchy code (codGerarchia). Example values: "01", "02", "$".

*** id (string):** Relationship ID (account/Conto code). Plain code - not composite.

[account_hierarchy_relationships_find]

Returns Account-to-Node Relationships matching the optional FIQL filter within the specified Account Hierarchy. Use this to search or list relationships. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string compliant with FIQL. Filterable properties:

- id
- nodeCode.id
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Offset for paging

take (integer): Page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter

*** hId (string):** Hierarchy code (codGerarchia). Example values: "01", "02", "$". Note: this is NOT a numeric surrogate key.

[account_hierarchy_relationships_getById]

Returns one Account-to-Node Relationship identified by its ID within the specified Account Hierarchy. Use this when the relationship ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** hId (string):** Hierarchy code (codGerarchia). Example values: "01", "02", "$".

*** id (string):** Relationship ID (account/Conto code). Plain code - not composite.

`[account_hierarchy_relationships_updateContoGerarchiaAbbiLowest]`

Partial update - only provided properties are updated. Immutable properties are ignored.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "hId": "02",
  "id": "50010",
  "nodeCode": {
    "id": "50010",
    "description": "Ricavi totali netti"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Origin of the operation. If not provided, defaults to INPUT_WEB. Accepted values: INPUT_WEB, MDM, REST_API.

*** hId (string):** Hierarchy code (codGerarchia). Example values: "01", "02", "$".

*** id (string):** Relationship ID (account/Conto code). Plain code - not composite.

nodeCode (any): Hierarchy node reference (mutable, required).

Account hierarchy structure

Data Model and master data · 6 operations

`[account_hierarchy_structure_bulkAccountHierarchyStructureNodes]`

Delete list is ignored by controller (cleared server-side).

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "hierarchiesID": "$",
  "saveMode": "SAVE_ONLY_VALID_ROWS",
  "post": [
    {
      "id": "AHS_NODE_001",
      "nodeType": "NORMAL",
      "defaultNode": false,
      "signClass": "ASSETS",
      "sortOrder": 10,
      "descriptions": {
        "en": "Node description",
        "it": "Descrizione nodo"
      },
      "parentNode": {
        "id": "$",
        "description": "Root"
      },
      "updateInfo": {
        "user": "API_AI",
        "date": "2026-06-16T12:10:25.380+0000",
        "origin": "INPUT_WEB"
      }
    }
  ],
  "put": [
    {
      "id": "AHS_NODE_001",
      "nodeType": "NORMAL",
      "defaultNode": false,
      "signClass": "ASSETS",
      "sortOrder": 10,
      "descriptions": {
        "en": "Node description",
        "it": "Descrizione nodo"
      },
      "parentNode": {
        "id": "$",
        "description": "Root"
      },
      "updateInfo": {
        "user": "API_AI",
        "date": "2026-06-16T12:10:25.380+0000",
        "origin": "INPUT_WEB"
      }
    }
  ],
  "patch": [
    {
      "key": {
        "id": "string"
      },
      "data": {
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
        "nodeType": "NORMAL",
        "defaultNode": false,
        "signClass": "ASSETS",
        "sortOrder": 10,
        "descriptions": {
          "en": "English description",
          "it": "Descrizione italiana"
        },
        "parentNode": {
          "id": 8,
          "description": "Parent node"
        },
        "referenceAccount": {
          "id": 8,
          "description": "Parent node"
        },
        "updateInfo": {
          "user": "string",
          "date": "2024-01-01T12:00:00Z",
          "origin": "string"
        }
      }
    }
  ],
  "delete": [
    {
      "id": "$|AHS_NODE_001"
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** hierarchiesID (string):** Account hierarchy ID.

saveMode (string): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Resources to partially update. Each item contains only the properties to modify for one resource.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[account_hierarchy_structure_countAccountHierarchyStructureNodes]

Returns the number of Account Hierarchy Structure Nodes matching the optional FIQL filter. Use this when only the count is needed, not the node data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string):

*** hierarchiesID (string):** Account hierarchy ID.

[account_hierarchy_structure_createAccountHierarchyStructureNode]

Create account hierarchy structure node

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "hierarchiesID": "$",
  "id": "AHS_NODE_001",
  "hierarchyId": "$",
  "nodeType": "NORMAL",
  "defaultNode": false,
  "signClass": "ASSETS",
  "sortOrder": 10,
  "descriptions": {
    "en": "English description",
    "it": "Descrizione italiana"
  },
  "parentNode": {
    "id": 8,
    "description": "Parent node"
  },
  "referenceAccount": {
    "id": 8,
    "description": "Parent node"
  },
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  }
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** hierarchiesID (string):** Account hierarchy ID.

id (string): Node identifier (read-only in payload).

hierarchyId (string): Hierarchy identifier (write-only).

nodeType (string): Node type.

defaultNode (boolean): Default node flag.

signClass (string): Sign class of node.

sortOrder (integer): Sort order.

descriptions (any):

parentNode (any):

referenceAccount (any):

updateInfo (any):

[account_hierarchy_structure_findAccountHierarchyStructureNodeById]

Returns one Account Hierarchy Structure Node identified by its ID. Use this when the node ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** hierarchiesID (string):** Account hierarchy ID.

*** id (string):** Account hierarchy structure node ID.

[account_hierarchy_structure_findAccountHierarchyStructureNodes]

Returns Account Hierarchy Structure Nodes matching the optional FIQL filter within the specified Account Hierarchy. Use this to search or list nodes. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string):

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

skip (integer):

take (integer):

sort (string):

*** hierarchiesID (string):** Account hierarchy ID.

[account_hierarchy_structure_patchAccountHierarchyStructureNode]

Patch account hierarchy structure node

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "hierarchiesID": "$",
  "id": "AHS_NODE_001",
  "nodeType": "NORMAL",
  "defaultNode": false,
  "signClass": "ASSETS",
  "sortOrder": 10,
  "descriptions": {
    "en": "English description",
    "it": "Descrizione italiana"
  },
  "parentNode": {
    "id": 8,
    "description": "Parent node"
  },
  "referenceAccount": {
    "id": 8,
    "description": "Parent node"
  },
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** hierarchiesID (string):** Account hierarchy ID.

*** id (string):** Account hierarchy structure node ID.

nodeType (string): Node type.

defaultNode (boolean): Default node flag.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

signClass (string): Sign class of node.

sortOrder (integer): Sort order.

descriptions (any):

parentNode (any):

referenceAccount (any):

updateInfo (any):

Entities

Data Model and master data · 6 operations

[entity_addEntity]

Creates a new Entity with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "EN_00",
  "descriptions": {
    "en": "New York",
    "it": "New York",
    "es": "New York"
  },
  "validity": {
    "startDate": "2017-07-21",
    "endDate": "2034-07-21"
  },
  "sorting": "string",
  "documentationLink": "string",
  "additionalInfo": {
    "businessName": "business name value",
    "legalHQLocation": "Legal HQ Location value",
    "legalHQ": "Legal HQ  value",
    "administrativeHQLocation": "administrative HQ Location value",
    "administrativeHQ": "Legal administrative HQ value",
    "mainOffice": "main office value",
    "manager": "manager value",
    "icMatchingManagers": "ic matching managers value",
    "email": "email value",
    "phone": "phone value"
  },
  "customAttributes": {
    "Country": "Italy",
    "Entering group": "1090",
    "Leaving group": "1088",
    "Other custom attribute": "Other"
  },
  "currency": {
    "id": "EUR"
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  },
  "defaultCustomDimension1": {
    "id": "CC_500"
  },
  "defaultCustomDimension2": {
    "id": "CC_500"
  },
  "defaultCustomDimension3": {
    "id": "CC_500"
  },
  "defaultCustomDimension4": {
    "id": "CC_500"
  },
  "defaultCustomDimension5": {
    "id": "CC_500"
  },
  "restrictionCustomDimension1": {
    "restriction": "RESTRICTED"
  },
  "restrictionCustomDimension2": {
    "restriction": "RESTRICTED"
  },
  "restrictionCustomDimension3": {
    "restriction": "RESTRICTED"
  },
  "restrictionCustomDimension4": {
    "restriction": "RESTRICTED"
  },
  "restrictionCustomDimension5": {
    "restriction": "RESTRICTED"
  },
  "rules": {
    "fiscalPolicy": {
      "id": "USA",
      "description": "USA Corporate Tax"
    },
    "consolidation": {
      "consolidationMethod": "COST",
      "deconsolidationMethod": "NOTTODECONSOLIDATE",
      "percConsolidation": 100.0,
      "generateCtpElimination": "ALLELIMINATIONLOGICS",
      "onlyCtp": false,
      "onlyConsolidatorData": false,
      "icMatching": "AUTOMATIC",
      "excludeAndUseReferenceEntity": true,
      "referenceEntity": {
        "id": "EN_01",
        "description": "Entity 01"
      }
    },
    "taxAndCashManagement": {
      "runAsEntity": true,
      "runAsSubentity": true
    }
  },
  "taxAndCashManagement": {
    "runAsEntity": true,
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
    "runAsSubentity": true
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Unique ID of the Entity, Immutable

*** descriptions (object):** Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

validity (any):

sorting (string): Allows to implement custom sortings on the Entity dimension in system reports. Currently, no system report utilizes this information.

documentationLink (string): Allows to create a hypertextual link to a web page (world wide web) or to a web page inside an intranet so that additional information for the current element can be inserted.

additionalInfo (any):

customAttributes (any):

*** currency (any):**

defaultCustomDimension1 (any):

defaultCustomDimension2 (any):

defaultCustomDimension3 (any):

defaultCustomDimension4 (any):

defaultCustomDimension5 (any):

restrictionCustomDimension1 (any):

restrictionCustomDimension2 (any):

restrictionCustomDimension3 (any):

restrictionCustomDimension4 (any):

restrictionCustomDimension5 (any):

rules (any):

taxAndCashManagement (any):

[entity_count]

Returns the number of Entities matching the optional FIQL filter. Use this when only the count is needed, not the Entity data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

entity_count

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL - Filterable properties:

- id
- descriptions
- currency
- customAttributes
- additionalInfo.businessName
- additionalInfo.legalHQLocation
- additionalInfo.legalHQ
- additionalInfo.administrativeHQLocation
- additionalInfo.administrativeHQ
- additionalInfo.mainOffice
- additionalInfo.manager
- additionalInfo.icMatchingManagers
- additionalInfo.email
- additionalInfo.phone
- defaultCustomDimension1.id
- defaultCustomDimension2.id
- defaultCustomDimension3.id
- defaultCustomDimension4.id
- defaultCustomDimension5.id
- restrictionCustomDimension1.restricted
- restrictionCustomDimension2.restricted
- restrictionCustomDimension3.restricted
- restrictionCustomDimension4.restricted
- restrictionCustomDimension5.restricted
- rules.fiscalPolicy.id
- rules.fiscalPolicy.description
- rules.consolidation.consolidationMethod
- rules.consolidation.deconsolidationMethod
- rules.consolidation.percConsolidation
- rules.consolidation.generateCtpElimination
- rules.consolidation.onlyCtp
- rules.consolidation.onlyConsolidatorData
- rules.consolidation.listed
- rules.consolidation.icMatching
- rules.consolidation.excludeAndUseReferenceEntity
- rules.consolidation.referenceEntity.id

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

entity_count

- rules.consolidation.referenceEntity.description
- rules.taxAndCashManagement.runAsEntity
- rules.taxAndCashManagement.runAsSubentity
- validity.startDate
- validity.endDate
- updateInfo.origin
- updateInfo.user
- updateInfo.date

[entity_find]

Returns Entities matching the optional FIQL filter. Use this to search or list Entities. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL

- Filterable properties:
- id
- descriptions
- currency
- customAttributes
- additionalInfo.businessName
- additionalInfo.legalHQLocation
- additionalInfo.legalHQ
- additionalInfo.administrativeHQLocation
- additionalInfo.administrativeHQ
- additionalInfo.mainOffice
- additionalInfo.manager
- additionalInfo.icMatchingManagers
- additionalInfo.email
- additionalInfo.phone
- defaultCustomDimension1.id
- defaultCustomDimension2.id
- defaultCustomDimension3.id
- defaultCustomDimension4.id
- defaultCustomDimension5.id
- restrictionCustomDimension1.restricted

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- restrictionCustomDimension2.restricted
- restrictionCustomDimension3.restricted
- restrictionCustomDimension4.restricted
- restrictionCustomDimension5.restricted
- validity.startDate
- validity.endDate
- sorting
- documentationLink
- rules.fiscalPolicy.id
- rules.consolidation.consolidationMethod
- rules.consolidation.deconsolidationMethod
- rules.consolidation.percConsolidation
- rules.consolidation.generateCtpElimination
- rules.consolidation.onlyCtp
- rules.consolidation.onlyConsolidatorData
- rules.consolidation.listed
- rules.consolidation.icMatching
- rules.consolidation.excludeAndUseReferenceEntity
- rules.consolidation.referenceEntity.id
- rules.taxAndCashManagement.runAsEntity
- rules.taxAndCashManagement.runAsSubentity
- bankingData.costitutionDate
- bankingData.abiCode
- bankingData.bankGroupRegistrationDate
- bankingData.bankitReportingCode
- bankingData.assignmentDate
- bankingData.centralCreditRiskCode
- bankingData.iso
- bankingData.individualDataSignaling
- bankingData.intragroupSignaling
- bankingData.excludeFinInvAutomaticInput
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

[entity_getById]

Returns one Entity identified by its ID. Use this when the Entity ID is already known.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Id of the Entity to be retrieved

[entity_originalEntityBulk]

Performs bulk create, replace, and partial update operations on Entities. Use this tool when multiple Entities must be changed in a single request.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "saveMode": "LOOSE",
  "post": [
    {
      "customAttributes": {
        "Country": "Italy",
        "Entering group": "1090",
        "Leaving group": "1088",
        "Other custom attribute": "Other"
      },
      "currency": {
        "id": "EUR",
        "description": "Euro"
      },
      "defaultCustomDimension1": {
        "dimensionName": "Cost center",
        "id": "CC_500",
        "description": "Generic Cost center"
      },
      "defaultCustomDimension2": {
        "dimensionName": "Cost center",
        "id": "CC_500",
        "description": "Generic Cost center"
      },
      "defaultCustomDimension3": {
        "dimensionName": "Cost center",
        "id": "CC_500",
        "description": "Generic Cost center"
      },
      "defaultCustomDimension4": {
        "dimensionName": "Cost center",
        "id": "CC_500",
        "description": "Generic Cost center"
      },
      "defaultCustomDimension5": {
        "dimensionName": "Cost center",
        "id": "CC_500",
        "description": "Generic Cost center"
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
    },
    "restrictionCustomDimension1": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "restrictionCustomDimension2": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "restrictionCustomDimension3": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "restrictionCustomDimension4": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "restrictionCustomDimension5": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "rules": {
      "fiscalPolicy": {
        "id": "USA",
        "description": "USA Corporate Tax"
      },
      "consolidation": {
        "consolidationMethod": "COST",
        "deconsolidationMethod": "NOTTODECONSOLIDATE",
        "percConsolidation": 100.0,
        "generateCtpElimination": "ALLELIMINATIONLOGICS",
        "onlyCtp": false,
        "onlyConsolidatorData": false,
        "icMatching": "AUTOMATIC",
        "excludeAndUseReferenceEntity": true,
        "referenceEntity": {
          "id": "EN_01",
          "description": "Entity 01"
        }
      },
      "taxAndCashManagement": {
        "runAsEntity": true,
        "runAsSubentity": true
      }
    },
    "bankingData": {
      "constitutionDate": "2000-01-01",
      "abiCode": "12345",
      "bankGroupRegistrationDate": "2010-05-20",
      "bankitReportingCode": "BT123",
      "assignmentDate": "2018-02-01",
      "centralCreditRiskCode": "CCR001",
      "iso": "IT",
      "individualDataSignaling": false,
      "intragroupSignaling": false,
      "excludeFinInvAutomaticInput": false
    },
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "taxAndCashManagement": {
        "runAsEntity": true,
        "runAsSubentity": true
      },
      "updateInfo": {
        "user": "anUser",
        "date": "2017-07-21T17:32:28.581+0000",
        "origin": "INPUT_WEB"
      }
    }
  ],
  "put": [
    {
      "customAttributes": {
        "Country": "Italy",
        "Entering group": "1090",
        "Leaving group": "1088",
        "Other custom attribute": "Other"
      },
      "currency": {
        "id": "EUR",
        "description": "Euro"
      },
      "defaultCustomDimension1": {
        "dimensionName": "Cost center",
        "id": "CC_500",
        "description": "Generic Cost center"
      },
      "defaultCustomDimension2": {
        "dimensionName": "Cost center",
        "id": "CC_500",
        "description": "Generic Cost center"
      },
      "defaultCustomDimension3": {
        "dimensionName": "Cost center",
        "id": "CC_500",
        "description": "Generic Cost center"
      },
      "defaultCustomDimension4": {
        "dimensionName": "Cost center",
        "id": "CC_500",
        "description": "Generic Cost center"
      },
      "defaultCustomDimension5": {
        "dimensionName": "Cost center",
        "id": "CC_500",
        "description": "Generic Cost center"
      },
      "restrictionCustomDimension1": {
        "dimensionName": "Cost center",
        "restriction": "RESTRICTED"
      },
      "restrictionCustomDimension2": {
        "dimensionName": "Cost center",
        "restriction": "RESTRICTED"
      },
      "restrictionCustomDimension3": {
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "restrictionCustomDimension4": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "restrictionCustomDimension5": {
      "dimensionName": "Cost center",
      "restriction": "RESTRICTED"
    },
    "rules": {
      "fiscalPolicy": {
        "id": "USA",
        "description": "USA Corporate Tax"
      },
      "consolidation": {
        "consolidationMethod": "COST",
        "deconsolidationMethod": "NOTTODECONSOLIDATE",
        "percConsolidation": 100.0,
        "generateCtpElimination": "ALLELIMINATIONLOGICS",
        "onlyCtp": false,
        "onlyConsolidatorData": false,
        "icMatching": "AUTOMATIC",
        "excludeAndUseReferenceEntity": true,
        "referenceEntity": {
          "id": "EN_01",
          "description": "Entity 01"
        }
      },
      "taxAndCashManagement": {
        "runAsEntity": true,
        "runAsSubentity": true
      }
    },
    "bankingData": {
      "constitutionDate": "2000-01-01",
      "abiCode": "12345",
      "bankGroupRegistrationDate": "2010-05-20",
      "bankitReportingCode": "BT123",
      "assignmentDate": "2018-02-01",
      "centralCreditRiskCode": "CCR001",
      "iso": "IT",
      "individualDataSignaling": false,
      "intragroupSignaling": false,
      "excludeFinInvAutomaticInput": false
    },
    "taxAndCashManagement": {
      "runAsEntity": true,
      "runAsSubentity": true
    },
    "updateInfo": {
      "user": "anUser",
      "date": "2017-07-21T17:32:28.581+0000",
      "origin": "INPUT_WEB"
    }
  }
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  ],
  "patch": [
    {
      "key": {
        "id": "EN_00"
      },
      "data": {
        "descriptions": {
          "en": "New York"
        },
        "defaultDimensions": [
          {
            "dimension": "$CUSTOM_DIM1",
            "id": "CC_500"
          }
        ],
        "restrictions": [
          {
            "dimension": "$CUSTOM_DIM2",
            "restriction": "RESTRICTED"
          },
          {
            "dimension": "$CUSTOM_DIM3",
            "restriction": "NONE"
          }
        ],
        "customAttributes": {
          "Country": "Italia",
          "Unit group": "1098"
        }
      }
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Entities to partially update. Each item contains a key identifying the Entity and a data object containing only the properties to modify.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[entity_updateEntity]

Updates an existing Entity only for properties passed as input

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "string",
  "customAttributes": {
    "Country": "Italy",
    "Entering group": "1090",
    "Leaving group": "1088",
    "Other custom attribute": "Other"
  },
  "currency": {
    "id": "EUR"
  },
  "defaultCustomDimension1": {
    "id": "CC_500"
  },
  "defaultCustomDimension2": {
    "id": "CC_500"
  },
  "defaultCustomDimension3": {
    "id": "CC_500"
  },
  "defaultCustomDimension4": {
    "id": "CC_500"
  },
  "defaultCustomDimension5": {
    "id": "CC_500"
  },
  "restrictionCustomDimension1": {
    "restriction": "RESTRICTED"
  },
  "restrictionCustomDimension2": {
    "restriction": "RESTRICTED"
  },
  "restrictionCustomDimension3": {
    "restriction": "RESTRICTED"
  },
  "restrictionCustomDimension4": {
    "restriction": "RESTRICTED"
  },
  "restrictionCustomDimension5": {
    "restriction": "RESTRICTED"
  },
  "rules": {
    "fiscalPolicy": {
      "id": "USA",
      "description": "USA Corporate Tax"
    },
    "consolidation": {
      "consolidationMethod": "COST",
      "deconsolidationMethod": "NOTTODECONSOLIDATE",
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "percConsolidation": 100.0,
      "generateCtpElimination": "ALLELIMINATIONLOGICS",
      "onlyCtp": false,
      "onlyConsolidatorData": false,
      "icMatching": "AUTOMATIC",
      "excludeAndUseReferenceEntity": true,
      "referenceEntity": {
        "id": "EN_01",
        "description": "Entity 01"
      }
    },
    "taxAndCashManagement": {
      "runAsEntity": true,
      "runAsSubentity": true
    }
  },
  "taxAndCashManagement": {
    "runAsEntity": true,
    "runAsSubentity": true
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Entity code.

customAttributes (any):

currency (any):

defaultCustomDimension1 (any):

defaultCustomDimension2 (any):

defaultCustomDimension3 (any):

defaultCustomDimension4 (any):

defaultCustomDimension5 (any):

restrictionCustomDimension1 (any):

restrictionCustomDimension2 (any):

restrictionCustomDimension3 (any):

restrictionCustomDimension4 (any):

restrictionCustomDimension5 (any):

rules (any):

taxAndCashManagement (any):

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Entity hierarchies

Data Model and master data · 7 operations

[entity_hierarchy_v2_bulkEntityHierarchiesV2]

Delete list is ignored by controller (cleared server-side).

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "organization": true,
  "saveMode": "SAVE_ONLY_VALID_ROWS",
  "post": [
    {
      "id": "EFA01",
      "descriptions": {
        "it": "Descrizione gerarchia",
        "en": "Hierarchy description"
      },
      "nodeCode": "EFA01",
      "organization": true,
      "timeDependent": false,
      "geographical": false,
      "convertToFlatStructure": false,
      "excludeFromReporting": false,
      "updateInfo": {
        "user": "API_AI",
        "date": "2026-06-16T14:45:00.216+0000",
        "origin": "INPUT_WEB"
      }
    }
  ],
  "put": [
    {
      "id": "EFA01",
      "descriptions": {
        "it": "Descrizione gerarchia",
        "en": "Hierarchy description"
      },
      "nodeCode": "EFA01",
      "organization": true,
      "timeDependent": false,
      "geographical": false,
      "convertToFlatStructure": false,
      "excludeFromReporting": false,
      "updateInfo": {
        "user": "API_AI",
        "date": "2026-06-16T14:45:00.216+0000",
        "origin": "INPUT_WEB"
      }
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
    }
  ],
  "patch": [
    {
      "key": {
        "id": "string"
      },
      "data": {
        "id": "EFA01",
        "descriptions": {
          "it": "Descrizione",
          "en": "Description"
        },
        "nodeCode": "EFA01",
        "organization": true,
        "timeDependent": false,
        "geographical": false,
        "convertToFlatStructure": false,
        "excludeFromReporting": false,
        "updateInfo": {
          "user": "string",
          "date": "2024-01-01T12:00:00Z",
          "origin": "string"
        }
      }
    }
  ],
  "delete": [
    {
      "id": "EDL01",
      "nodeCode": "ROOT_1"
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

organization (boolean): Optional organization mode filter (bound to request parameters).

saveMode (string): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Resources to partially update. Each item contains only the properties to modify for one resource.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[entity_hierarchy_v2_countEntityHierarchiesV2]

Count entity hierarchies (V2)

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string):

organization (boolean): Optional organization mode filter (bound to request parameters).

[entity_hierarchy_v2_createEntityHierarchyV2]

Create entity hierarchy (V2)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "organization__query": true,
  "id": "EFA01",
  "descriptions": {
    "it": "Descrizione",
    "en": "Description"
  },
  "nodeCode": "EFA01",
  "organization": true,
  "timeDependent": false,
  "geographical": false,
  "convertToFlatStructure": false,
  "excludeFromReporting": false,
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

organization__query (boolean): Optional organization mode filter (bound to request parameters). (Query parameter)

id (string): Unique hierarchy id.

descriptions (any):

nodeCode (string): Root node code.

organization (boolean):

timeDependent (boolean):

geographical (boolean):

convertToFlatStructure (boolean):

excludeFromReporting (boolean):

updateInfo (any):

[entity_hierarchy_v2_fetchEntityHierarchiesV2]

Fetch entity hierarchy projected properties (V2)

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

properties (string): Comma-separated list of properties to fetch.

filter (string):

skip (integer):

take (integer):

sort (string):

organization (boolean): Optional organization mode filter (bound to request parameters).

[entity_hierarchy_v2_findEntityHierarchiesV2]

List entity hierarchies (V2)

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string):

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

skip (integer):

take (integer):

sort (string):

organization (boolean): Optional organization mode filter (bound to request parameters).

[entity_hierarchy_v2_findEntityHierarchyV2ById]

Get entity hierarchy by id (V2)

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Entity hierarchy identifier.

organization (boolean): Optional organization mode filter (bound to request parameters).

[entity_hierarchy_v2_patchEntityHierarchyV2]

Patch entity hierarchy (V2)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "id__path": "HIERARCHY_001",
  "organization__query": true,
  "id": "EFA01",
  "descriptions": {
    "it": "Descrizione",
    "en": "Description"
  },
  "nodeCode": "EFA01",
  "organization": true,
  "timeDependent": false,
  "geographical": false,
  "convertToFlatStructure": false,
  "excludeFromReporting": false,
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** id__path (string):** Entity hierarchy identifier. (Path parameter)

organization__query (boolean): Optional organization mode filter (bound to request parameters). (Query parameter)

id (string): Unique hierarchy id.

descriptions (any):

nodeCode (string): Root node code.

organization (boolean):

timeDependent (boolean):

geographical (boolean):

convertToFlatStructure (boolean):

excludeFromReporting (boolean):

updateInfo (any):

Entity hierarchy structure

Data Model and master data · 7 operations

`[entity_hierarchy_structure_v2_bulkEntityHierarchyStructureNodesV2]`

Delete list is ignored by controller (cleared server-side).

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "hierarchyId": "EPPFA",
  "saveMode": "SAVE_ONLY_VALID_ROWS",
  "post": [
    {
      "id": "EHS_FA_01",
      "descriptions": {
        "it": "Nodo FA 01",
        "en": "Node FA 01"
      },
      "nodeType": "NORMAL",
      "parent": {
        "id": "EPPFA",
        "desc": "Parent fixture"
      },
      "referenceEntity": {
        "id": "ENT_001",
        "desc": "Reference entity"
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      },
      "default": false,
      "sortOrder": 5,
      "entityType": "ENTITY",
      "contributorCertificationType": "TO_SUBMIT",
      "consolidatorCertificationType": "TO_CONSOLIDATE",
      "updateInfo": {
        "user": "API_AI",
        "date": "2026-06-18T14:18:22.327+0200",
        "origin": "INPUT_WEB"
      }
    }
  ],
  "put": [
    {
      "id": "EHS_FA_01",
      "descriptions": {
        "it": "Nodo FA 01",
        "en": "Node FA 01"
      },
      "nodeType": "NORMAL",
      "parent": {
        "id": "EPPFA",
        "desc": "Parent fixture"
      },
      "referenceEntity": {
        "id": "ENT_001",
        "desc": "Reference entity"
      },
      "default": false,
      "sortOrder": 5,
      "entityType": "ENTITY",
      "contributorCertificationType": "TO_SUBMIT",
      "consolidatorCertificationType": "TO_CONSOLIDATE",
      "updateInfo": {
        "user": "API_AI",
        "date": "2026-06-18T14:18:22.327+0200",
        "origin": "INPUT_WEB"
      }
    }
  ],
  "patch": [
    {
      "key": {
        "id": "string"
      },
      "data": {
        "hierarchyId": "EPPFA",
        "descriptions": {
          "it": "Descrizione",
          "en": "Description"
        },
        "nodeType": "ROOT",
        "parent": {
          "id": "string",
          "desc": "string"
        },
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
        "referenceEntity": {
          "id": "string",
          "desc": "string"
        },
        "default": false,
        "sortOrder": 5,
        "entityType": "DO_NOT_RUN",
        "contributorCertificationType": "NONE",
        "consolidatorCertificationType": "NONE",
        "updateInfo": {
          "user": "string",
          "date": "2024-01-01T12:00:00Z",
          "origin": "string"
        }
      }
    }
  ],
  "delete": [
    {
      "id": "EHS_DEL_01"
    }
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** hierarchyId (string):** Entity hierarchy identifier.

saveMode (string): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Resources to partially update. Each item contains only the properties to modify for one resource.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

[entity_hierarchy_structure_v2_countEntityHierarchyStructureNodesV2]

Count entity hierarchy nodes (V2)

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string):

*** hierarchyId (string):** Entity hierarchy identifier.

[entity_hierarchy_structure_v2_createEntityHierarchyStructureNodeV2]

Create entity hierarchy node (V2)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "hierarchyId__path": "EPPFA",
  "id": "EHS_FA_01",
  "hierarchyId": "EPPFA",
  "descriptions": {
    "it": "Descrizione",
    "en": "Description"
  },
  "nodeType": "ROOT",
  "parent": {
    "id": "string",
    "desc": "string"
  },
  "referenceEntity": {
    "id": "string",
    "desc": "string"
  },
  "default": false,
  "sortOrder": 5,
  "entityType": "DO_NOT_RUN",
  "contributorCertificationType": "NONE",
  "consolidatorCertificationType": "NONE",
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** hierarchyId__path (string):** Entity hierarchy identifier. (Path parameter)

*** id (string):** Unique node id. Immutable.

hierarchyId (string): Hierarchy id context (normally derived from path variable).

*** descriptions (any):**

nodeType (string):

parent (any):

referenceEntity (any):

default (boolean): Default node flag.

sortOrder (integer):

entityType (['string', 'null']):

contributorCertificationType (['string', 'null']):

consolidatorCertificationType (['string', 'null']):

updateInfo (any):

[entity_hierarchy_structure_v2_fetchEntityHierarchyStructureNodesV2]

Fetch entity hierarchy node projected properties (V2)

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

properties (string): Comma-separated list of properties to fetch.

filter (string):

skip (integer):

take (integer):

sort (string):

*** hierarchyId (string):** Entity hierarchy identifier.

[entity_hierarchy_structure_v2_findEntityHierarchyStructureNodeV2ById]

Get entity hierarchy node by id (V2)

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** hierarchyId (string):** Entity hierarchy identifier.

*** id (string):** Entity hierarchy structure node identifier.

[entity_hierarchy_structure_v2_findEntityHierarchyStructureNodesV2]

List entity hierarchy nodes (V2)

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string):

skip (integer):

take (integer):

sort (string):

*** hierarchyId (string):** Entity hierarchy identifier.

[entity_hierarchy_structure_v2_patchEntityHierarchyStructureNodeV2]

Patch entity hierarchy node (V2)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "hierarchyId__path": "EPPFA",
  "id": "EHS_FA_01",
  "hierarchyId": "EPPFA",
  "descriptions": {
    "it": "Descrizione",
    "en": "Description"
  },
  "nodeType": "ROOT",
  "parent": {
    "id": "string",
    "desc": "string"
  },
  "referenceEntity": {
    "id": "string",
    "desc": "string"
  },
  "default": false,
  "sortOrder": 5,
  "entityType": "DO_NOT_RUN",
  "contributorCertificationType": "NONE",
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  "consolidatorCertificationType": "NONE",
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** hierarchyId__path (string):** Entity hierarchy identifier. (Path parameter)

*** id (string):** Entity hierarchy structure node identifier.

hierarchyId (string): Hierarchy id context (normally derived from path variable).

descriptions (any):

nodeType (string):

parent (any):

referenceEntity (any):

default (boolean): Default node flag.

sortOrder (integer):

entityType (['string', 'null']):

contributorCertificationType (['string', 'null']):

consolidatorCertificationType (['string', 'null']):

updateInfo (any):

Analytical dimensions

Data Model and master data · 6 operations

[analyticalDimension_addAnalytical_Dimension]

Creates a new Analytical Dimension with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "ANALYTICAL_DIM_ID": "AR_AGING",
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  "id": "CC_050",
  "descriptions": {
    "en": "Accounting",
    "it": "Accounting",
    "es": "Accounting"
  },
  "validity": {
    "startDate": "2017-07-21",
    "endDate": "2034-07-21"
  },
  "updateInfo": {
    "user": "anUser",
    "date": "2017-07-21T17:32:28.581+0000",
    "origin": "INPUT_WEB"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** ANALYTICAL_DIM_ID (string):** Analytical dimension label

*** id (string):** Unique ID of the Analytical dimension, Immutable

*** descriptions (object):** Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

validity (any):

updateInfo (any):

[analyticalDimension_count]

Returns the number of Analytical Dimensions matching the optional FIQL filter. Use this when only the count is needed, not the Analytical Dimension data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL - Filterable properties:

- id
- descriptions
- validity.startDate
- validity.endDate

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** ANALYTICAL_DIM_ID (string):** Analytical dimension label

[analyticalDimension_find]

Returns Analytical Dimensions matching the optional FIQL filter. Use this to search or list Analytical Dimensions. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL

- Filterable properties:
- id
- descriptions
- validity.startDate
- validity.endDate
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** ANALYTICAL_DIM_ID (string):** Analytical dimension label

[analyticalDimension_getById]

Returns one Analytical Dimension identified by its ID. Use this when the Analytical Dimension ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Id of the Analytical Dimension to be retrieved

*** ANALYTICAL_DIM_ID (string):** Analytical dimension label

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[analyticalDimension_originalAnalyticalDimensionBulk]

Performs bulk create, replace, and partial update operations on Analytical Dimensions. Use this tool when multiple Analytical Dimensions must be changed in a single request.

Example arguments:


```
{
  "api_key": "string",
  "db_id": "string",
  "ANALYTICAL_DIM_ID": "AR_AGING",
  "saveMode": "LOOSE",
  "post": [
    {
      "id": "CC_050",
      "descriptions": {
        "en": "Accounting",
        "it": "Accounting",
        "es": "Accounting"
      },
      "validity": {
        "startDate": "2017-07-21",
        "endDate": "2034-07-21"
      },
      "updateInfo": {
        "user": "anUser",
        "date": "2017-07-21T17:32:28.581+0000",
        "origin": "INPUT_WEB"
      }
    }
  ],
  "put": [
    {
      "id": "CC_050",
      "descriptions": {
        "en": "Accounting",
        "it": "Accounting",
        "es": "Accounting"
      },
      "validity": {
        "startDate": "2017-07-21",
        "endDate": "2034-07-21"
      },
      "updateInfo": {
        "user": "anUser",
        "date": "2017-07-21T17:32:28.581+0000",
        "origin": "INPUT_WEB"
      }
    }
  ],
  "patch": [
    {
      "key": {
        "id": "CC_050"
      },
      "data": {
        "descriptions": {
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
          "en": "Accounting in english"
        },
        "AnalyticalAttriubutes": {
          "Country": "Italia",
          "Unit group": "1098"
        }
      }
    }
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** ANALYTICAL_DIM_ID (string):** Analytical dimension label

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Analytical Dimensions to partially update. Each item contains a key identifying the Analytical Dimension and a data object containing only the properties to modify.

[analyticalDimension_updateAnalyticalDimension]

Updates an existing Analytical Dimension only for properties passed as input

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "string",
  "ANALYTICAL_DIM_ID": "AR_AGING",
  "descriptions": {
    "en": "Accounting",
    "it": "Accounting",
    "es": "Accounting"
  },
  "validity": {
    "startDate": "2017-07-21",
    "endDate": "2034-07-21"
  }
}
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Analytical Dimension code.

*** ANALYTICAL_DIM_ID (string):** Analytical dimension label

descriptions (object): Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format (e.g. "en" or "it"). > Descriptions in languages which are not configured in the application will be ignored.

validity (any):

Custom dimensions

Data Model and master data · 3 operations

`[custom_dimension_count]`

Returns the number of Custom Dimensions matching the optional FIQL filter. Use this when only the count is needed, not the Custom Dimension data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL - Filterable properties:

- id
- descriptions
- customAttributes
- validity.startDate
- validity.endDate
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** customDimIdentifier (string):** Custom dimension number

`[custom_dimension_find]`

Returns Custom Dimensions matching the optional FIQL filter. Use this to search or list Custom Dimensions. Supports filtering, sorting, and pagination.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL

- Filterable properties:
- id
- descriptions
- customAttributes
- validity.startDate
- validity.endDate
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** customDimIdentifier (string):** Custom dimension identifier.

[custom_dimension_getById]

Returns one Custom Dimension identified by its ID. Use this when the Custom Dimension ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Id of the Custom Dimension to be retrieved

*** customDimIdentifier (string):** Custom dimension identifier

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Categories

Data Model and master data · 6 operations

[category_addCategory]

Creates a new Category with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "CAT_00",
  "descriptions": {
    "en": "Manual Journals",
    "it": "Scritture Manuali"
  },
  "categoryType": "ENTITY_JOURNAL",
  "defaultForJournal": {
    "periodic": true,
    "enableCarryForward": true,
    "excludeReclassificationsAndNER": false,
    "taxCalculationMethod": "NONE",
    "reverseJournalType": "NONE"
  },
  "advanced": {
    "handleAsAJournal": true,
    "runnableCategory": true,
    "childCategory": true,
    "referenceCategoryForChild": {
      "id": "CAT_REF_01",
      "descriptions": {
        "en": "Reference Category",
        "it": "Categoria di riferimento"
      }
    },
    "monthlySplittingType": "VARIATION",
    "journalModelDefinition": [
      {
        "account": {
          "id": "ACC_1000",
          "description": "Cash and Cash Equivalents"
        },
        "customDimension1": {
          "id": "CD1_001",
          "description": "Custom Dim Element 001"
        },
        "customDimension2": {
          "id": "CD1_001",
          "description": "Custom Dim Element 001"
        },
        "customDimension3": {
          "id": "CD1_001",
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
          "description": "Custom Dim Element 001"
        },
        "customDimension4": {
          "id": "CD1_001",
          "description": "Custom Dim Element 001"
        },
        "customDimension5": {
          "id": "CD1_001",
          "description": "Custom Dim Element 001"
        }
      }
    ]
  },
  "bankingData": {
    "notifyIndividualData": false,
    "notify36381": false,
    "notifyOtherIntergroupItems": true
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Unique ID of the Category, Immutable

*** descriptions (object):** Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format.

*** categoryType (string):** Category type, Immutable

defaultForJournal (any):

advanced (any):

bankingData (any):

[category_categoryBulk]

Performs bulk create, replace, and partial update operations on Categories. Use this tool when multiple Categories must be changed in a single request.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "saveMode": "LOOSE",
  "post": [
    {
      "id": "CAT_00",
      "descriptions": {
        "en": "Manual Journals",
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "it": "Scritture Manuali"
    },
    "categoryType": "ENTITY_JOURNAL",
    "consolidation": {
      "defaultForJournal": {
        "periodic": true,
        "enableCarryForward": true,
        "excludeReclassificationsAndNER": false,
        "taxCalculationMethod": "NONE",
        "reverseJournalType": "NONE"
      },
      "defaultForConsolidationJournals": {
        "overrideCtpSegmentSetEqualToEntity": false,
        "proportionalCalculationMethod": "NONE",
        "equityEvaluationMethod": "NONE",
        "minoritiesCalculationMethod": "NONE",
        "minoritiesCalculationMethodOnEntity1": "NONE",
        "minoritiesCalculationMethodOnEntity2": "NONE"
      },
      "bankingData": {
        "notifyIndividualData": false,
        "notify36381": false,
        "notifyOtherIntergroupItems": true
      }
    },
    "advanced": {
      "handleAsAJournal": true,
      "runnableCategory": true,
      "childCategory": true,
      "referenceCategoryForChild": {
        "id": "CAT_REF_01",
        "descriptions": {
          "en": "Reference Category",
          "it": "Categoria di riferimento"
        }
      },
      "monthlySplittingType": "VARIATION",
      "journalModelDefinition": [
        {
          "account": {
            "id": null,
            "description": null
          },
          "customDimension1": {
            "id": null,
            "description": null
          },
          "customDimension2": {
            "id": null,
            "description": null
          },
          "customDimension3": {
            "id": null,
            "description": null
          },
          "customDimension4": {
            "id": null,
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
            "description": null
          },
          "customDimension5": {
            "id": null,
            "description": null
          }
        }
      ]
    },
    "updateInfo": {
      "user": "anUser",
      "date": "2017-07-21T17:32:28.581+0000",
      "origin": "INPUT_WEB"
    }
  }
],
"put": [
  {
    "id": "CAT_00",
    "descriptions": {
      "en": "Manual Journals",
      "it": "Scritture Manuali"
    },
    "categoryType": "ENTITY_JOURNAL",
    "consolidation": {
      "defaultForJournal": {
        "periodic": true,
        "enableCarryForward": true,
        "excludeReclassificationsAndNER": false,
        "taxCalculationMethod": "NONE",
        "reverseJournalType": "NONE"
      },
      "defaultForConsolidationJournals": {
        "overrideCtpSegmentSetEqualToEntity": false,
        "proportionalCalculationMethod": "NONE",
        "equityEvaluationMethod": "NONE",
        "minoritiesCalculationMethod": "NONE",
        "minoritiesCalculationMethodOnEntity1": "NONE",
        "minoritiesCalculationMethodOnEntity2": "NONE"
      },
      "bankingData": {
        "notifyIndividualData": false,
        "notify36381": false,
        "notifyOtherIntergroupItems": true
      }
    },
    "advanced": {
      "handleAsAJournal": true,
      "runnableCategory": true,
      "childCategory": true,
      "referenceCategoryForChild": {
        "id": "CAT_REF_01",
        "descriptions": {
          "en": "Reference Category",
          "it": "Categoria di riferimento"
        }
      },
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "monthlySplittingType": "VARIATION",
      "journalModelDefinition": [
        {
          "account": {
            "id": null,
            "description": null
          },
          "customDimension1": {
            "id": null,
            "description": null
          },
          "customDimension2": {
            "id": null,
            "description": null
          },
          "customDimension3": {
            "id": null,
            "description": null
          },
          "customDimension4": {
            "id": null,
            "description": null
          },
          "customDimension5": {
            "id": null,
            "description": null
          }
        }
      ]
    },
    "updateInfo": {
      "user": "anUser",
      "date": "2017-07-21T17:32:28.581+0000",
      "origin": "INPUT_WEB"
    }
  }
],
"patch": [
  {
    "key": {
      "id": "CAT_00"
    },
    "data": {
      "descriptions": {
        "it": "Nuova descrizione"
      },
      "defaultForJournal": {
        "periodic": true,
        "enableCarryForward": true
      },
      "advanced": {
        "handleAsAJournal": true,
        "monthlySplittingType": "VARIATION",
        "referenceCategoryForChild": {
          "id": "CAT_REF_01",
          "descriptions": {
            "en": "Reference Category"
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
            }
          }
        }
      }
    }
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Categories to partially update. Each item contains a key identifying the Category and a data object containing only the properties to modify.

[category_countCategory]

Returns the number of Categories matching the optional FIQL filter. Use this when only the count is needed, not the Category data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL (same filterable properties as /elements)

[category_find]

Returns Categories matching the optional FIQL filter. Use this to search or list Categories. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL

Filterable properties:

- id
- descriptions
- categoryType
- consolidation.defaultForJournal.periodic
- consolidation.defaultForJournal.enableCarryForward
- consolidation.defaultForJournal.excludeReclassificationsAndNER
- consolidation.defaultForJournal.taxCalculationMethod
- consolidation.defaultForJournal.reverseJournalType
- consolidation.defaultForConsolidationJournals.overrideCtpSegmentSetEqualToEntity
- consolidation.defaultForConsolidationJournals.proportionalCalculationMethod
- consolidation.defaultForConsolidationJournals.equityEvaluationMethod
- consolidation.defaultForConsolidationJournals.minoritiesCalculationMethodOnEntity1
- consolidation.defaultForConsolidationJournals.minoritiesCalculationMethodOnEntity2
- advanced.handleAsAJournal
- advanced.runnableCategory
- advanced.childCategory
- advanced.referenceCategoryForChild.id
- advanced.monthlySplittingType
- consolidation.bankingData.notifyIndividualData
- consolidation.bankingData.notify36381
- consolidation.bankingData.notifyOtherIntergroupItems
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

[category_getCategoryById]

Returns a single Category given its id

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Category code.

[category_updateCategory]

Updates an existing Category only for properties passed as input. Immutable properties will be ignored.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "string",
  "descriptions": {
    "en": "Manual Journals",
    "it": "Scritture Manuali"
  },
  "defaultForJournal": {
    "periodic": true,
    "enableCarryForward": true,
    "excludeReclassificationsAndNER": false,
    "taxCalculationMethod": "NONE",
    "reverseJournalType": "NONE"
  },
  "advanced": {
    "handleAsAJournal": true,
    "runnableCategory": true,
    "childCategory": true,
    "referenceCategoryForChild": {
      "id": "CAT_REF_01",
      "descriptions": {
        "en": "Reference Category",
        "it": "Categoria di riferimento"
      }
    },
    "monthlySplittingType": "VARIATION",
    "journalModelDefinition": [
      {
        "account": {
          "id": "ACC_1000",
          "description": "Cash and Cash Equivalents"
        },
        "customDimension1": {
          "id": "CD1_001",
          "description": "Custom Dim Element 001"
        },
        "customDimension2": {
          "id": "CD1_001",
          "description": "Custom Dim Element 001"
        },
        "customDimension3": {
          "id": "CD1_001",
          "description": "Custom Dim Element 001"
        },
        "customDimension4": {
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
          "id": "CD1_001",
          "description": "Custom Dim Element 001"
        },
        "customDimension5": {
          "id": "CD1_001",
          "description": "Custom Dim Element 001"
        }
      }
    ]
  },
  "bankingData": {
    "notifyIndividualData": false,
    "notify36381": false,
    "notifyOtherIntergroupItems": true
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Category code.

descriptions (object): Dictionary of translations in various languages. Dictionary key should be in ISO 639-1 format.

defaultForJournal (any):

advanced (any):

bankingData (any):

WOLTERS KLUWER INTELLECTUAL PROPERTY

Currencies

Data Model and master data · 6 operations

[currency_addCurrency]

Creates a new Currency with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "EUR30",
  "description": "EURO-THOUSAND 30",
  "preferred": false,
  "decimalNumbers": 1,
  "referenceCurrency": {
    "id": "EUR",
    "coefficient": 1000
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  },
  "percentageDifference": "0,000",
  "xbrlContent": "string"
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Unique ID of the currency, Immutable

*** description (string):** currency description

preferred (boolean): If enabled, it specifies that the selected currency is the preferred currency. It can't be active on more than one Currency. It is employed as: -default currency by which to visualize data inside the IC matching cockpit; -currency for the insertion of the exchange rates.

*** decimalNumbers (integer):** It must be a value between 0 and 9. If values between 4 and 9 are specified, then this value is invalid for journals on consolidation scenarios whose values are still inserted with three decimal places.

referenceCurrency (any):

*** percentageDifference (string):** Percentage that is defined by the user that the system utilizes in the Diagnostic to verify the FX rate. It must be a value between 0 and 100.

xbrlContent (string): Value to assign to the measure sub-element in order to specify the unit measure used for the value of an item of monetary type in the creation of an XBRL instance template.

[currency_count]

Returns the number of Currencies matching the optional FIQL filter. Use this when only the count is needed, not the Currency data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL - Filterable properties:

- id
- description
- percentageDifference
- referenceCurrency.id
- referenceCurrency.coefficient
- xbrlContent
- updateInfo.origin

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- updateInfo.user
- updateInfo.date

[currency_find]

Returns Currencies matching the optional FIQL filter. Use this to search or list Currencies. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL

- Filterable properties:
- id
- description
- percentageDifference
- referenceCurrency.id
- referenceCurrency.coefficient
- xbrlContent
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

[currency_getById]

Returns one Currency identified by its ID. Use this when the Currency ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Id of the Currency to be retrieved

[currency_originalCurrencyBulk]

Performs bulk create, replace, and partial update operations on Currencies. Use this tool when multiple Currencies must be changed in a single request.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "saveMode": "LOOSE",
  "post": [
    {
      "id": "EUR30",
      "description": "EURO-THOUSAND 30",
      "preferred": false,
      "decimalNumbers": 1,
      "referenceCurrency": {
        "id": "EUR",
        "coefficient": 1000
      },
      "percentageDifference": "0,000",
      "xbrlContent": "string"
    }
  ],
  "put": [
    {
      "id": "EUR30",
      "description": "EURO-THOUSAND 30",
      "preferred": false,
      "decimalNumbers": 1,
      "referenceCurrency": {
        "id": "EUR",
        "coefficient": 1000
      },
      "percentageDifference": "0,000",
      "xbrlContent": "string"
    }
  ],
  "patch": [
    {
      "key": {
        "id": "EUR"
      },
      "data": {
        "description": "EUR New descripton",
        "preferred": true
      }
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Currencies to partially update. Each item contains a key identifying the Currency and a data object containing only the properties to modify.

[currency_updateCurrency]

Updates an existing Currency only for properties passed as input

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "string",
  "description": "EURO-THOUSAND 30",
  "preferred": false,
  "decimalNumbers": 1,
  "referenceCurrency": {
    "id": "EUR",
    "coefficient": 1000
  },
  "percentageDifference": "0,000",
  "xbrlContent": "string"
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** currency code.

description (string): currency description

preferred (boolean): If enabled, it specifies that the selected currency is the preferred currency. It can't be active on more than one Currency. It is employed as: -default currency by which to visualize data inside the IC matching cockpit; -currency for the insertion of the exchange rates.

decimalNumbers (integer): It must be a value between 0 and 9. If values between 4 and 9 are specified, then this value is invalid for journals on consolidation scenarios whose values are still inserted with three decimal places.

referenceCurrency (any):

percentageDifference (string): Percentage that is defined by the user that the system utilizes in the Diagnostic to verify the FX rate. It must be a value between 0 and 100.

xbrlContent (string): Value to assign to the measure sub-element in order to specify the unit measure used for the value of an item of monetary type in the creation of an XBRL instance template.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Scenarios

Data Model and master data · 6 operations

[original_scenario_addOriginalScenario]

Creates a new original scenario with LOOSE save mode (validation ignoring warnings)

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "2017ACT",
  "description": "string",
  "versionDescription": "Actual",
  "year": 2017,
  "active": true,
  "previousScenario": "2016ACT",
  "followingScenario": "2018ACT",
  "referenceScenario1": "2016REF1",
  "referenceScenario2": "2016REF2",
  "referenceScenario3": "2016REF3",
  "referenceScenario4": "2016REF4",
  "referenceScenario5": "2016REF5",
  "customAttributes": {
    "Country": "Italy",
    "Unit group": "1090"
  }
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Original scenario code, Immutable

description (string): Scenario description

versionDescription (string): a free unencoded attribute that is only used by reporting. It allows the user to specify the version to which the scenario refers.

year (string): a free unencoded attribute that is only used by reporting. It allows the user to specify the year to which the scenario refers.scenarios.

active (boolean): specifies whether or not the scenario must be shown in the selection list of scenarios present in different windows of the system. It's used to “put aside” data that isn't interesting, but that the user doesn't want to delete. This information has no effect on the data lock.

previousScenario (string): Scenario used:

- by the system to determine where to perform carry orwards

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- by the reporting to compare data present in the current scenario with data in the previous scenario. The field must be of the same “Type” as the current one. It must be different from the scenario code.

followingScenario (string): The scenario to which the reporting refers when comparing data present in the current scenario with those in the following scenario, usually it allows the user to link "forward" scenarios.It must be of the same “Type” as the current one. It must be different from the scenario code.

referenceScenario1 (string): the scenario that can be used by the reporting, for example, to specify the budget data or forecast data for an actual data. It's usage is optional.It must be of the same “Type” as the current one.

referenceScenario2 (string): the scenario that can be used by the reporting, for example, to specify the budget data or forecast data for an actual data. It's usage is optional.It must be of the same “Type” as the current one.

referenceScenario3 (string): the scenario that can be used by the reporting, for example, to specify the budget data or forecast data for an actual data. It's usage is optional.It must be of the same “Type” as the current one.

referenceScenario4 (string): the scenario that can be used by the reporting, for example, to specify the budget data or forecast data for an actual data. It's usage is optional.It must be of the same “Type” as the current one.

referenceScenario5 (string): the scenario that can be used by the reporting, for example, to specify the budget data or forecast data for an actual data. It's usage is optional.It must be of the same “Type” as the current one.

customAttributes (object): free unencoded attribute that can be used by reporting for special classifications, style formatting, etc. Contains only attributes that is configured on the scenario dimension.

[original_scenario_count]

Returns the number of Original Scenarios matching the optional FIQL filter. Use this when only the count is needed, not the Original Scenario data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL

- Filterable properties
- id
- descriptions
- versionDescription
- year
- active
- previousScenario.id
- followingScenario.id
- referenceScenario1.id
- referenceScenario2.id
- referenceScenario3.id
- referenceScenario4.id
- referenceScenario5.id

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- customAttributes
- updInfo.user
- updInfo.date
- updInfo.origin

[original_scenario_find]

Returns Original Scenarios matching the optional FIQL filter. Use this to search or list Original Scenarios. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL

- Filterable properties
- id
- description
- versionDescription
- year
- active
- previousScenario.id
- followingScenario.id
- referenceScenario1.id
- referenceScenario2.id
- referenceScenario3.id
- referenceScenario4.id
- referenceScenario5.id
- customAttributes
- updInfo.user
- updInfo.date
- updInfo.origin

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter. Use `field:asc` or `field:desc`, such as `id:desc`; separate multiple fields with `;`. Do not use OData syntax such as `year desc`.

[original_scenario_getById]

Returns one Original Scenario identified by its ID. Use this when the Original Scenario ID is already known.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Id of the original scenario to be retrieved

[original_scenario_originalScenarioBulk]

Performs bulk create, replace, and partial update operations on Original Scenarios. Use this tool when multiple Original Scenarios must be changed in a single request.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "saveMode": "LOOSE",
  "post": [
    {
      "id": "2017ACT",
      "description": "string",
      "versionDescription": "Actual",
      "year": 2017,
      "active": true,
      "previousScenario": "2016ACT",
      "followingScenario": "2018ACT",
      "referenceScenario1": "2016REF1",
      "referenceScenario2": "2016REF2",
      "referenceScenario3": "2016REF3",
      "referenceScenario4": "2016REF4",
      "referenceScenario5": "2016REF5",
      "customAttributes": {
        "Country": "Italy",
        "Unit group": "1090"
      }
    }
  ],
  "put": [
    {
      "id": "2017ACT",
      "description": "string",
      "versionDescription": "Actual",
      "year": 2017,
      "active": true,
      "previousScenario": "2016ACT",
      "followingScenario": "2018ACT",
      "referenceScenario1": "2016REF1",
      "referenceScenario2": "2016REF2",
      "referenceScenario3": "2016REF3",
      "referenceScenario4": "2016REF4",
      "referenceScenario5": "2016REF5",
      "customAttributes": {
        "Country": "Italy",
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
        "Unit group": "1090"
      }
    }
  ],
  "patch": [
    {
      "key": {
        "id": "105ACT"
      },
      "data": {
        "descriptions": {
          "en": "Actual Scenario",
          "it": "Scenario Actual"
        },
        "scenarioPrevious": "2018BGD",
        "customAttributes": {
          "Country": "Italia"
        },
        "active": false
      }
    }
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

saveMode (any): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

patch (array): Original Scenarios to partially update. Each item contains a key identifying the Original Scenario and a data object containing only the properties to modify.

[original_scenario_updateOriginalScenario]

Updates an existing Original Scenario only for properties passed as input

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "id": "string",
  "description": "string",
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  "versionDescription": "Actual",
  "year": 2017,
  "active": true,
  "previousScenario": "2016ACT",
  "followingScenario": "2018ACT",
  "referenceScenario1": "2016REF1",
  "referenceScenario2": "2016REF2",
  "referenceScenario3": "2016REF3",
  "referenceScenario4": "2016REF4",
  "referenceScenario5": "2016REF5",
  "customAttributes": {
    "Country": "Italy",
    "Unit group": "1090"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** scenario code.

description (string): Scenario description

versionDescription (string): a free unencoded attribute that is only used by reporting. It allows the user to specify the version to which the scenario refers.

year (string): a free unencoded attribute that is only used by reporting. It allows the user to specify the year to which the scenario refers.scenarios.

active (boolean): specifies whether or not the scenario must be shown in the selection list of scenarios present in different windows of the system. It's used to “put aside” data that isn't interesting, but that the user doesn't want to delete. This information has no effect on the data lock.

previousScenario (string): Scenario used: - by the system to determine where to perform carry orwards - by the reporting to compare data present in the current scenario with data in the previous scenario. The field must be of the same “Type” as the current one. It must be different from the scenario code.

followingScenario (string): The scenario to which the reporting refers when comparing data present in the current scenario with those in the following scenario, usually it allows the user to link "forward" scenarios.It must be of the same “Type” as the current one. It must be different from the scenario code.

referenceScenario1 (string): the scenario that can be used by the reporting, for example, to specify the budget data or forecast data for an actual data. It's usage is optional.It must be of the same “Type” as the current one.

referenceScenario2 (string): the scenario that can be used by the reporting, for example, to specify the budget data or forecast data for an actual data. It's usage is optional.It must be of the same “Type” as the current one.

referenceScenario3 (string): the scenario that can be used by the reporting, for example, to specify the budget data or forecast data for an actual data. It's usage is optional.It must be of the same “Type” as the current one.

referenceScenario4 (string): the scenario that can be used by the reporting, for example, to specify the budget data or forecast data for an actual data. It's usage is optional.It must be of the same “Type” as the current one.

referenceScenario5 (string): the scenario that can be used by the reporting, for example, to specify the budget data or forecast data for an actual data. It's usage is optional.It must be of the same “Type” as the current one.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

customAttributes (object): free unencoded attribute that can be used by reporting for special classifications, style formatting, etc. Contains only attributes that is configured on the scenario dimension.

Scenario periods

Data Model and master data · 7 operations

[original_scenario_period_original_bulk]

Bulk operations on ORIGINAL ScenarioPeriodo. Every item in the JSON body's post array must include descriptions, startDate and endDate. Both dates are mandatory ISO 8601 date-time strings for each new period, not top-level bulk properties; the field name is endDate, not endData.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "scenarioId": "2026CPX",
  "UserInfo-Origin": "INPUT_WEB",
  "saveMode": "LOOSE",
  "patch": null,
  "post": [
    {
      "id": "01",
      "descriptions": {
        "en": "January",
        "it": "Gennaio"
      },
      "startDate": "2026-01-01T00:00:00.000Z",
      "endDate": "2026-01-31T00:00:00.000Z"
    }
  ],
  "put": null,
  "delete": null
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** scenarioId (string):** Scenario code (e.g. STAT1)

UserInfo-Origin (string): Optional origin header for write operations. Must NOT be sent in automated/integration flows.

saveMode (string): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

patch (['array', 'null']): Resources to partially update. Each item contains only the properties to modify for one resource.

post (['array', 'null']): Resources to create. Every item must include descriptions, startDate and endDate as ISO 8601 date-time strings.

put (['array', 'null']): Resources to fully replace. Each item contains the complete desired state of an existing resource.

delete (['array', 'null']): Resources to delete. Each item contains the key identifying the resource to remove.

[original_scenario_period_original_count]

Size of ORIGINAL ScenarioPeriodo

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** scenarioId (string):** Scenario code (e.g. STAT1)

filter (string): Filter expression

[original_scenario_period_original_create]

Creates a new ORIGINAL scenario period. The JSON request body must include descriptions, startDate and endDate. Both dates are mandatory ISO 8601 date-time strings; the field name is endDate, not endData.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "scenarioId": "2026CPX",
  "UserInfo-Origin": "INPUT_WEB",
  "id": null,
  "type": "ORIGINAL",
  "descriptions": {
    "en": "January",
    "it": "Gennaio"
  },
  "startDate": "2026-01-01T00:00:00.000Z",
  "startMonthlyDate": "2026-01-01T00:00:00.000Z",
  "endDate": "2026-01-31T00:00:00.000Z",
  "process": "ACT",
  "blocked": false,
  "populated": true,
  "editSubmittedData": false,
  "periodLength": 31
}
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** scenarioId (string):** Scenario code (e.g. STAT1)

UserInfo-Origin (string): Optional origin header for write operations. Must NOT be sent in automated/integration flows.

id (['string', 'null']): Period code (e.g. 01). Must be null in PUT body; must match path periodId if supplied in POST/PATCH body.

type (['string', 'null']): Always overridden to ORIGINAL from the path. Can be omitted.

*** descriptions (object):** Descriptions keyed by language code

*** startDate (string):** ISO 8601 date-time (e.g. 2026-01-01T00:00:00.000Z)

startMonthlyDate (['string', 'null']): ISO 8601 date-time (e.g. 2026-01-01T00:00:00.000Z)

*** endDate (string):** ISO 8601 date-time (e.g. 2026-01-01T00:00:00.000Z)

process (['string', 'null']):

blocked (['boolean', 'null']):

populated (['boolean', 'null']): Defaults to true server-side if not supplied

editSubmittedData (['boolean', 'null']): ORIGINAL only.

periodLength (['integer', 'null']):

`[original_scenario_period_original_findByIds]`

Find ORIGINAL ScenarioPeriodo items by list of IDs

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "scenarioId": "2026CPX",
  "body": [
    "string"
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** scenarioId (string):** Scenario code (e.g. STAT1)

*** body (array):**

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[original_scenario_period_original_get]

Find ORIGINAL ScenarioPeriodo by ID

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** scenarioId (string):** Scenario code (e.g. STAT1)

*** periodId (string):** Period code validated against CodPeriodo enum (e.g. 01, 02, ... 12)

[original_scenario_period_original_getList]

List of ORIGINAL scenario periods

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** scenarioId (string):** Scenario code (e.g. STAT1)

filter (string): Filter expression

skip (integer): Number of elements to skip (pagination offset)

take (integer): Maximum number of elements to return

sort (string): Sort expression

[original_scenario_period_original_update]

Updates an existing ORIGINAL ScenarioPeriodo

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "scenarioId": "2026CPX",
  "periodId": "string",
  "UserInfo-Origin": "INPUT_WEB",
  "id": null,
  "type": "ORIGINAL",
  "descriptions": {
    "en": "January",
    "it": "Gennaio"
  },
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  "startDate": "2026-01-01T00:00:00.000Z",
  "startMonthlyDate": "2026-01-01T00:00:00.000Z",
  "endDate": "2026-01-31T00:00:00.000Z",
  "process": "ACT",
  "blocked": false,
  "populated": true,
  "editSubmittedData": false,
  "periodLength": 31
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** scenarioId (string):** Scenario code (e.g. STAT1)

*** periodId (string):** Period code validated against CodPeriodo enum (e.g. 01, 02, ... 12)

UserInfo-Origin (string): Optional origin header for write operations. Must NOT be sent in automated/integration flows.

id (['string', 'null']): Period code (e.g. 01). Must be null in PUT body; must match path periodId if supplied in POST/PATCH body.

type (['string', 'null']): Always overridden to ORIGINAL from the path. Can be omitted.

descriptions (object): Descriptions keyed by language code

startDate (string): ISO 8601 date-time (e.g. 2026-01-01T00:00:00.000Z)

startMonthlyDate (['string', 'null']): ISO 8601 date-time (e.g. 2026-01-01T00:00:00.000Z)

endDate (string): ISO 8601 date-time (e.g. 2026-01-01T00:00:00.000Z)

process (['string', 'null']):

blocked (['boolean', 'null']):

populated (['boolean', 'null']): Defaults to true server-side if not supplied

editSubmittedData (['boolean', 'null']): ORIGINAL only.

periodLength (['integer', 'null']):

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Periods

Data Model and master data · 3 operations

[period_countPeriods]

Returns the number of Periods matching the optional FIQL filter. Use this when only the count is needed, not the Period data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL

- Filterable properties:
- id
- periodNumber
- descriptions
- monthDescriptions
- quarterDescriptions
- quarterlyDescriptions
- semesterDescriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

[period_findPeriods]

Returns Periods matching the optional FIQL filter. Use this to search or list Periods. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL

- Filterable properties:

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- id
- periodNumber
- descriptions
- monthDescriptions
- quarterDescriptions
- quarterlyDescriptions
- semesterDescriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter. Use `field:asc` or `field:desc`, such as `id:desc`; separate multiple fields with `;`. Do not use OData syntax such as `id desc`.

[period_getPeriodById]

Returns one Period identified by its ID. Use this when the Period ID is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** id (string):** Period code.

WOLTERS KLUWER INTELLECTUAL PROPERTY

Shared dictionary items

Data Model and master data · 7 operations

[voce_dizionario_bulk]

Performs bulk create, replace, and delete operations on Dictionary Items in the specified database. Use this tool when multiple Dictionary Items must be changed in a single request.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "saveMode": "LOOSE",
  "post": [
    {
      "code": "string",
      "updateInfo": {
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
        "user": "string",
        "date": "2024-01-01T12:00:00Z",
        "origin": "string"
      },
      "descriptions": {
        "it": "string",
        "en": "string",
        "es": "string",
        "fr": "string",
        "de": "string",
        "zh": "string",
        "ru": "string"
      }
    }
  ],
  "put": [
    {
      "code": "string",
      "updateInfo": {
        "user": "string",
        "date": "2024-01-01T12:00:00Z",
        "origin": "string"
      },
      "descriptions": {
        "it": "string",
        "en": "string",
        "es": "string",
        "fr": "string",
        "de": "string",
        "zh": "string",
        "ru": "string"
      }
    }
  ],
  "delete": [
    {
      "code": "string",
      "updateInfo": {
        "user": "string",
        "date": "2024-01-01T12:00:00Z",
        "origin": "string"
      },
      "descriptions": {
        "it": "string",
        "en": "string",
        "es": "string",
        "fr": "string",
        "de": "string",
        "zh": "string",
        "ru": "string"
      }
    }
  ]
}
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

saveMode (string): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

[voce_dizionario_count]

Returns the number of Dictionary Items matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

[voce_dizionario_create]

Creates a new Dictionary Item in the specified database. Use this when a single new dictionary item must be created.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "code": "string",
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  },
  "descriptions": {
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
    "it": "string",
    "en": "string",
    "es": "string",
    "fr": "string",
    "de": "string",
    "zh": "string",
    "ru": "string"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

code (string): Dictionary Item code used to identify the item.

updateInfo (any):

descriptions (any):

[voce_dizionario_deleteById]

Deletes the Dictionary Item synchronously.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Dictionary Item code.

[voce_dizionario_find]

Returns Dictionary Items matching the optional FIQL filter. Use this tool to search or list Dictionary Items. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

skip (integer): Number of matching resources to skip. Minimum: 0.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

take (integer): Maximum number of resources to return.

sort (string): Optional sort expression.

[voce_dizionario_getById]

Returns one Dictionary Item identified by its code. Use this tool when the resource code is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Dictionary Item code.

[voce_dizionario_update]

Updates an existing Dictionary Item identified by its code. Use this when a single existing dictionary item must be modified.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "cod": "aCod",
  "code": "string",
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  },
  "descriptions": {
    "it": "string",
    "en": "string",
    "es": "string",
    "fr": "string",
    "de": "string",
    "zh": "string",
    "ru": "string"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** cod (string):** Dictionary Item code.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

code (string): Dictionary Item code used to identify the item.

updateInfo (any):

descriptions (any):

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

03

Financial Reporting configuration

31 operations

Report definitions 7

Report filters 6

Report formulas 2

Report parameters 2

Report queries 7

Report style sheets 7

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Report definitions

Financial Reporting configuration · 7 operations

[prospetto_bulk]

Performs bulk create, replace, and delete operations on Prospetti in the specified database. Use this tool when multiple Prospetti must be changed in a single request.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "saveMode": "LOOSE",
  "post": [
    {
      "code": "string",
      "input": true,
      "rinumera": true,
      "bloccaStruttura": true,
      "updateInfo": {
        "user": "string",
        "date": "2024-01-01T12:00:00Z",
        "origin": "string"
      },
      "tipoProspetto": "P",
      "dataInizio": "2024-01-01T12:00:00Z",
      "dataFine": "2024-01-01T12:00:00Z",
      "attributoList": [
        "string"
      ],
      "tipoClient": "VBA",
      "tipoFile": "string",
      "linkDocumento": "string",
      "sistema": true,
      "noreport": true,
      "tipoForm": "string",
      "soloDatiUtente": true,
      "ignoraFiltroScenario": true,
      "ignoraFiltroPeriodo": true,
      "ignoraFiltroAzienda": true,
      "eseguiEtl": true,
      "disabilitaEditabilita": true,
      "codMappatura": "string",
      "codImport": "string",
      "codJob": "string",
      "lunghezzaPeriodo": "string",
      "reportList": true,
      "dashboard": true,
      "aperturaWeb": "C",
      "disabilitaCancellazione": true,
      "disabilitaInserimento": true,
      "pivot": true,
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "descriptions": {
        "it": "string",
        "en": "string",
        "es": "string",
        "fr": "string",
        "de": "string",
        "zh": "string",
        "ru": "string"
      },
      "xml": [
        "string"
      ],
      "ordinamentoXml": 1.5,
      "md5sum": "string",
      "template": [
        "string"
      ],
      "ordinamentoTemplate": 1.5,
      "prospettoContoList": [
        {
          "codConto": "string",
          "editabile": "string"
        }
      ],
      "prospettoControlloList": [
        {
          "codControllo": "string",
          "editabile": "string"
        }
      ]
    }
  ],
  "put": [
    {
      "code": "string",
      "input": true,
      "rinumera": true,
      "bloccaStruttura": true,
      "updateInfo": {
        "user": "string",
        "date": "2024-01-01T12:00:00Z",
        "origin": "string"
      },
      "tipoProspetto": "P",
      "dataInizio": "2024-01-01T12:00:00Z",
      "dataFine": "2024-01-01T12:00:00Z",
      "attributoList": [
        "string"
      ],
      "tipoClient": "VBA",
      "tipoFile": "string",
      "linkDocumento": "string",
      "sistema": true,
      "noreport": true,
      "tipoForm": "string",
      "soloDatiUtente": true,
      "ignoraFiltroScenario": true,
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

prospetto_bulk


```
      "ignoraFiltroPeriodo": true,
      "ignoraFiltroAzienda": true,
      "eseguiEtl": true,
      "disabilitaEditabilita": true,
      "codMappatura": "string",
      "codImport": "string",
      "codJob": "string",
      "lunghezzaPeriodo": "string",
      "reportList": true,
      "dashboard": true,
      "aperturaWeb": "C",
      "disabilitaCancellazione": true,
      "disabilitaInserimento": true,
      "pivot": true,
      "descriptions": {
        "it": "string",
        "en": "string",
        "es": "string",
        "fr": "string",
        "de": "string",
        "zh": "string",
        "ru": "string"
      },
      "xml": [
        "string"
      ],
      "ordinamentoXml": 1.5,
      "md5sum": "string",
      "template": [
        "string"
      ],
      "ordinamentoTemplate": 1.5,
      "prospettoContoList": [
        {
          "codConto": "string",
          "editabile": "string"
        }
      ],
      "prospettoControlloList": [
        {
          "codControllo": "string",
          "editabile": "string"
        }
      ]
    }
  ],
  "delete": [
    {
      "code": "string",
      "input": true,
      "rinumera": true,
      "bloccaStruttura": true,
      "updateInfo": {
        "user": "string",
        "date": "2024-01-01T12:00:00Z",
        "origin": "string"
      },
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

prospetto_bulk


```
"tipoProspetto": "P",
"dataInizio": "2024-01-01T12:00:00Z",
"dataFine": "2024-01-01T12:00:00Z",
"attributoList": [
  "string"
],
"tipoClient": "VBA",
"tipoFile": "string",
"linkDocumento": "string",
"sistema": true,
"noreport": true,
"tipoForm": "string",
"soloDatiUtente": true,
"ignoraFiltroScenario": true,
"ignoraFiltroPeriodo": true,
"ignoraFiltroAzienda": true,
"eseguiEtl": true,
"disabilitaEditabilita": true,
"codMappatura": "string",
"codImport": "string",
"codJob": "string",
"lunghezzaPeriodo": "string",
"reportList": true,
"dashboard": true,
"aperturaWeb": "C",
"disabilitaCancellazione": true,
"disabilitaInserimento": true,
"pivot": true,
"descriptions": {
  "it": "string",
  "en": "string",
  "es": "string",
  "fr": "string",
  "de": "string",
  "zh": "string",
  "ru": "string"
},
"xml": [
  "string"
],
"ordinamentoXml": 1.5,
"md5sum": "string",
"template": [
  "string"
],
"ordinamentoTemplate": 1.5,
"prospettoContoList": [
  {
    "codConto": "string",
    "editabile": "string"
  }
],
"prospettoControlloList": [
  {
    "codControllo": "string",
    "editabile": "string"
  }
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      ]
    }
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

saveMode (string): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

[prospetto_count]

Returns the number of Prospetti matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

[prospetto_create]

Creates a new Prospetto in the specified database. Use this when a single new report must be created.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "code": "string",
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

prospetto_create


```
"input": true,
"rinumera": true,
"bloccaStruttura": true,
"updateInfo": {
  "user": "string",
  "date": "2024-01-01T12:00:00Z",
  "origin": "string"
},
"tipoProspetto": "P",
"dataInizio": "2024-01-01T12:00:00Z",
"dataFine": "2024-01-01T12:00:00Z",
"attributoList": [
  "string"
],
"tipoClient": "VBA",
"tipoFile": "string",
"linkDocumento": "string",
"sistema": true,
"noreport": true,
"tipoForm": "string",
"soloDatiUtente": true,
"ignoraFiltroScenario": true,
"ignoraFiltroPeriodo": true,
"ignoraFiltroAzienda": true,
"eseguiEtl": true,
"disabilitaEditabilita": true,
"codMappatura": "string",
"codImport": "string",
"codJob": "string",
"lunghezzaPeriodo": "string",
"reportList": true,
"dashboard": true,
"aperturaWeb": "C",
"disabilitaCancellazione": true,
"disabilitaInserimento": true,
"pivot": true,
"descriptions": {
  "it": "string",
  "en": "string",
  "es": "string",
  "fr": "string",
  "de": "string",
  "zh": "string",
  "ru": "string"
},
"xml": [
  "string"
],
"ordinamentoXml": 1.5,
"md5sum": "string",
"template": [
  "string"
],
"ordinamentoTemplate": 1.5,
"prospettoContoList": [
  {
    "codConto": "string",
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "editabile": "string"
    }
  ],
  "prospettoControlloList": [
    {
      "codControllo": "string",
      "editabile": "string"
    }
  ]
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

code (string): Prospetto code used to identify the report.

input (boolean): Indicates whether the report is used as an input form.

rinumera (boolean): Enables renumbering of report rows or columns.

bloccaStruttura (boolean): Prevents changes to the report structure.

updateInfo (any):

tipoProspetto (string): Prospetto type. P represents a standard report and F represents a financial report.

dataInizio (string): Start date from which the report is valid.

dataFine (string): End date until which the report is valid.

attributoList (array): List of attributes associated with the report.

tipoClient (string): Client type allowed to use the report.

tipoFile (string): File format associated with the report.

linkDocumento (string): Link to the document associated with the report.

sistema (boolean): Indicates whether the report is a system-defined resource.

noreport (boolean): Indicates whether the resource is excluded from report execution.

tipoForm (string): Form type used when the report is displayed or edited.

soloDatiUtente (boolean): Restricts the report to data available to the current user.

ignoraFiltroScenario (boolean): Ignores scenario filters when executing the report.

ignoraFiltroPeriodo (boolean): Ignores period filters when executing the report.

ignoraFiltroAzienda (boolean): Ignores company filters when executing the report.

eseguiEtl (boolean): Runs the ETL process associated with the report.

disabilitaEditabilita (boolean): Disables editing of report data.

codMappatura (string): Mapping code associated with the report.

codImport (string): Import job or definition code associated with the report.

codJob (string): Job code associated with the report.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

lunghezzaPeriodo (string): Period length used by the report.

reportList (boolean): Indicates whether the report is included in report lists.

dashboard (boolean): Indicates whether the report is available in dashboards.

aperturaWeb (string): Web opening mode for the report.

disabilitaCancellazione (boolean): Disables deletion of report data.

disabilitaInserimento (boolean): Disables insertion of report data.

pivot (boolean): Enables pivot mode for report data.

descriptions (any):

xml (array): XML representation of the report configuration.

ordinamentoXml (number): Display order of the XML representation.

md5sum (string): MD5 checksum of the report content.

template (array): Template files or content associated with the report.

ordinamentoTemplate (number): Display order of the report template.

prospettoContoList (array): Accounts linked to the report.

prospettoControlloList (array): Controls linked to the report.

[prospetto_deleteById]

Deletes the Prospetto synchronously.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Prospetto code.

[prospetto_find]

Returns Prospetti matching the optional FIQL filter. Use this tool to search or list Prospetti. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

skip (integer): Number of matching resources to skip. Minimum: 0.

take (integer): Maximum number of resources to return.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

sort (string): Optional sort expression.

[prospetto_getById]

Returns one Prospetto identified by its code. Use this tool when the resource code is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Prospetto code.

[prospetto_update]

Updates an existing Prospetto identified by its code. Use this when a single existing report must be modified.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "cod": "aCod",
  "code": "string",
  "input": true,
  "rinumera": true,
  "bloccaStruttura": true,
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  },
  "tipoProspetto": "P",
  "dataInizio": "2024-01-01T12:00:00Z",
  "dataFine": "2024-01-01T12:00:00Z",
  "attributoList": [
    "string"
  ],
  "tipoClient": "VBA",
  "tipoFile": "string",
  "linkDocumento": "string",
  "sistema": true,
  "noreport": true,
  "tipoForm": "string",
  "soloDatiUtente": true,
  "ignoraFiltroScenario": true,
  "ignoraFiltroPeriodo": true,
  "ignoraFiltroAzienda": true,
  "eseguiEtl": true,
  "disabilitaEditabilita": true,
  "codMappatura": "string",
  "codImport": "string",
  "codJob": "string",
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  "lunghezzaPeriodo": "string",
  "reportList": true,
  "dashboard": true,
  "aperturaWeb": "C",
  "disabilitaCancellazione": true,
  "disabilitaInserimento": true,
  "pivot": true,
  "descriptions": {
    "it": "string",
    "en": "string",
    "es": "string",
    "fr": "string",
    "de": "string",
    "zh": "string",
    "ru": "string"
  },
  "xml": [
    "string"
  ],
  "ordinamentoXml": 1.5,
  "md5sum": "string",
  "template": [
    "string"
  ],
  "ordinamentoTemplate": 1.5,
  "prospettoContoList": [
    {
      "codConto": "string",
      "editabile": "string"
    }
  ],
  "prospettoControlloList": [
    {
      "codControllo": "string",
      "editabile": "string"
    }
  ]
}
```


WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** cod (string):** Prospetto code.

code (string): Prospetto code used to identify the report.

input (boolean): Indicates whether the report is used as an input form.

rinumera (boolean): Enables renumbering of report rows or columns.

bloccaStruttura (boolean): Prevents changes to the report structure.

updateInfo (any):

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

tipoProspetto (string): Prospetto type. P represents a standard report and F represents a financial report.

dataInizio (string): Start date from which the report is valid.

dataFine (string): End date until which the report is valid.

attributoList (array): List of attributes associated with the report.

tipoClient (string): Client type allowed to use the report.

tipoFile (string): File format associated with the report.

linkDocumento (string): Link to the document associated with the report.

sistema (boolean): Indicates whether the report is a system-defined resource.

noreport (boolean): Indicates whether the resource is excluded from report execution.

tipoForm (string): Form type used when the report is displayed or edited.

soloDatiUtente (boolean): Restricts the report to data available to the current user.

ignoraFiltroScenario (boolean): Ignores scenario filters when executing the report.

ignoraFiltroPeriodo (boolean): Ignores period filters when executing the report.

ignoraFiltroAzienda (boolean): Ignores company filters when executing the report.

eseguiEtl (boolean): Runs the ETL process associated with the report.

disabilitaEditabilita (boolean): Disables editing of report data.

codMappatura (string): Mapping code associated with the report.

codImport (string): Import job or definition code associated with the report.

codJob (string): Job code associated with the report.

lunghezzaPeriodo (string): Period length used by the report.

reportList (boolean): Indicates whether the report is included in report lists.

dashboard (boolean): Indicates whether the report is available in dashboards.

aperturaWeb (string): Web opening mode for the report.

disabilitaCancellazione (boolean): Disables deletion of report data.

disabilitaInserimento (boolean): Disables insertion of report data.

pivot (boolean): Enables pivot mode for report data.

descriptions (any):

xml (array): XML representation of the report configuration.

ordinamentoXml (number): Display order of the XML representation.

md5sum (string): MD5 checksum of the report content.

template (array): Template files or content associated with the report.

ordinamentoTemplate (number): Display order of the report template.

prospettoContoList (array): Accounts linked to the report.

prospettoControlloList (array): Controls linked to the report.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Report filters

Financial Reporting configuration · 6 operations

[prosp_filtro_count]

Returns the number of Prospetto Filters matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

[prosp_filtro_create]

Creates a new Prospetto Filter in the specified database. Use this when a single new filter must be created.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "code": "string",
  "sistema": true,
  "tipoClient": "VBA",
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  },
  "xml": [
    "string"
  ],
  "descriptions": {
    "it": "string",
    "en": "string",
    "es": "string",
    "fr": "string",
    "de": "string",
    "zh": "string",
    "ru": "string"
  }
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

code (string): Prospetto Filter code used to identify the filter.

sistema (boolean): Indicates whether the filter is system-defined.

tipoClient (string): Client type allowed to use the filter.

updateInfo (any):

xml (array): XML definition of the filter.

descriptions (any):

[prosp_filtro_deleteById]

Deletes the Prospetto Filter synchronously.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Prosp Filtro code.

[prosp_filtro_find]

Returns Prospetto Filters matching the optional FIQL filter. Use this tool to search or list Prospetto Filters. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

skip (integer): Number of matching resources to skip. Minimum: 0.

take (integer): Maximum number of resources to return.

sort (string): Optional sort expression.

[prosp_filtro_getById]

Returns one Prospetto Filter identified by its code. Use this tool when the resource code is already known.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Prosp Filtro code.

[prosp_filtro_update]

Updates an existing Prospetto Filter identified by its code. Use this when a single existing filter must be modified.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "cod": "aCod",
  "code": "string",
  "sistema": true,
  "tipoClient": "VBA",
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  },
  "xml": [
    "string"
  ],
  "descriptions": {
    "it": "string",
    "en": "string",
    "es": "string",
    "fr": "string",
    "de": "string",
    "zh": "string",
    "ru": "string"
  }
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** cod (string):** Prosp Filtro code.

code (string): Prospetto Filter code used to identify the filter.

sistema (boolean): Indicates whether the filter is system-defined.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

tipoClient (string): Client type allowed to use the filter.

updateInfo (any):

xml (array): XML definition of the filter.

descriptions (any):

Report formulas

Financial Reporting configuration · 2 operations

[prospetto_formula_find]

Returns Prospetto Formulas matching the optional FIQL filter. Use this tool to search or list Prospetto Formulas. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

skip (integer): Number of matching resources to skip. Minimum: 0.

take (integer): Maximum number of resources to return.

sort (string): Optional sort expression.

[prospetto_formula_getById]

Returns one Prospetto Formula identified by its code. Use this tool when the resource code is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Formula name.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Report parameters

Financial Reporting configuration · 2 operations

[prospetto_parametro_find]

Returns Prospetto Parameters matching the optional FIQL filter. Use this tool to search or list Prospetto Parameters. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

skip (integer): Number of matching resources to skip. Minimum: 0.

take (integer): Maximum number of resources to return.

sort (string): Optional sort expression.

[prospetto_parametro_getById]

Returns one Prospetto Parameter identified by its code. Use this tool when the resource code is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Prospetto Parametro code

Report queries

Financial Reporting configuration · 7 operations

[prospetto_query_bulk]

Performs bulk create, replace, and delete operations on Prospetto Queries in the specified database. Use this tool when multiple Prospetto Queries must be changed in a single request.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "saveMode": "LOOSE",
  "post": [
    {
      "code": "string",
      "secured-query": [
        "string"
      ],
      "type": "string",
      "descrizione": "string",
      "versione": "string",
      "drilldown": true,
      "sistema": true,
      "tipoClient": "VBA",
      "descriptions": {
        "it": "string",
        "en": "string",
        "es": "string",
        "fr": "string",
        "de": "string",
        "zh": "string",
        "ru": "string"
      }
    }
  ],
  "put": [
    {
      "code": "string",
      "secured-query": [
        "string"
      ],
      "type": "string",
      "descrizione": "string",
      "versione": "string",
      "drilldown": true,
      "sistema": true,
      "tipoClient": "VBA",
      "descriptions": {
        "it": "string",
        "en": "string",
        "es": "string",
        "fr": "string",
        "de": "string",
        "zh": "string",
        "ru": "string"
      }
    }
  ],
  "delete": [
    {
      "code": "string"
    }
  ]
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

saveMode (string): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

[prospetto_query_count]

Returns the number of Prospetto Queries matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

[prospetto_query_create]

Creates a new Prospetto Query in the specified database. Use this when a single new query must be created.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "code": "string",
  "secured-query": [
    "string"
  ],
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  "type": "string",
  "descrizione": "string",
  "versione": "string",
  "drilldown": true,
  "sistema": true,
  "tipoClient": "VBA",
  "descriptions": {
    "it": "string",
    "en": "string",
    "es": "string",
    "fr": "string",
    "de": "string",
    "zh": "string",
    "ru": "string"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

code (string): Prospetto Query code used to identify the query.

secured-query (array): Query statements to execute securely when creating or replacing a Prospetto Query.

type (string): Query type or execution mode.

descrizione (string): Human-readable description of the query.

versione (string): Query version identifier.

drilldown (boolean): Enables drill-down behavior for query results.

sistema (boolean): Indicates whether the query is system-defined.

*** tipoClient (string):** Client type allowed to use the query.

descriptions (any):

[prospetto_query_deleteById]

Deletes the Prospetto Query synchronously.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Query name.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[prospetto_query_find]

Returns Prospetto Queries matching the optional FIQL filter. Use this tool to search or list Prospetto Queries. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

skip (integer): Number of matching resources to skip. Minimum: 0.

take (integer): Maximum number of resources to return.

sort (string): Optional sort expression.

[prospetto_query_getById]

Returns one Prospetto Query identified by its code. Use this tool when the resource code is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Query name.

[prospetto_query_update]

Updates an existing Prospetto Query identified by its code. Use this when a single existing query must be modified.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "cod": "aCod",
  "code": "string",
  "secured-query": [
    "string"
  ],
  "type": "string",
  "descrizione": "string",
  "versione": "string",
  "drilldown": true,
```

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
  "sistema": true,
  "tipoClient": "VBA",
  "descriptions": {
    "it": "string",
    "en": "string",
    "es": "string",
    "fr": "string",
    "de": "string",
    "zh": "string",
    "ru": "string"
  }
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** cod (string):** Query name.

code (string): Prospetto Query code used to identify the query.

secured-query (array): Query statements to execute securely when updating a Prospetto Query.

type (string): Query type or execution mode.

descrizione (string): Human-readable description of the query.

versione (string): Query version identifier.

drilldown (boolean): Enables drill-down behavior for query results.

sistema (boolean): Indicates whether the query is system-defined.

*** tipoClient (string):** Client type allowed to use the query.

descriptions (any):

Report style sheets

Financial Reporting configuration · 7 operations

`[prospetto_stylesheet_bulk]`

Performs bulk create, replace, and delete operations on Prospetto Style Sheets in the specified database. Use this tool when multiple Prospetto Style Sheets must be changed in a single request.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "saveMode": "LOOSE",
  "post": [
    {
      "code": "string",
      "drillDownDefault": true,
      "sistema": true,
      "foglioStileDefault": true,
      "tipoClient": "VBA",
      "updateInfo": {
        "user": "string",
        "date": "2024-01-01T12:00:00Z",
        "origin": "string"
      },
      "descriptions": {
        "it": "string",
        "en": "string",
        "es": "string",
        "fr": "string",
        "de": "string",
        "zh": "string",
        "ru": "string"
      },
      "xml": [
        "string"
      ],
      "ordinamento": 1.5
    }
  ],
  "put": [
    {
      "code": "string",
      "drillDownDefault": true,
      "sistema": true,
      "foglioStileDefault": true,
      "tipoClient": "VBA",
      "updateInfo": {
        "user": "string",
        "date": "2024-01-01T12:00:00Z",
        "origin": "string"
      },
      "descriptions": {
        "it": "string",
        "en": "string",
        "es": "string",
        "fr": "string",
        "de": "string",
        "zh": "string",
        "ru": "string"
      },
      "xml": [
        "string"
      ],
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

```
      "ordinamento": 1.5
    }
  ],
  "delete": [
    {
      "code": "string",
      "drillDownDefault": true,
      "sistema": true,
      "foglioStileDefault": true,
      "tipoClient": "VBA",
      "updateInfo": {
        "user": "string",
        "date": "2024-01-01T12:00:00Z",
        "origin": "string"
      },
      "descriptions": {
        "it": "string",
        "en": "string",
        "es": "string",
        "fr": "string",
        "de": "string",
        "zh": "string",
        "ru": "string"
      },
      "xml": [
        "string"
      ],
      "ordinamento": 1.5
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

saveMode (string): Controls validation behavior when saving. Allowed values:

- LOOSE: validation warnings are ignored.
- STRICT: validation warnings are treated according to strict validation rules.
- SAVE_ONLY_VALID_ROWS: only rows that pass validation checks are saved.

post (array): Resources to create. Each item contains the complete data required to create a new resource.

put (array): Resources to fully replace. Each item contains the complete desired state of an existing resource.

delete (array): Resources to delete. Each item contains the key identifying the resource to remove.

[prospetto_stylesheet_count]

Returns the number of Prospetto Style Sheets matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

[prospetto_stylesheet_create]

Creates a new Prospetto Style Sheet in the specified database. Use this when a single new style sheet must be created.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "code": "string",
  "drillDownDefault": true,
  "sistema": true,
  "foglioStileDefault": true,
  "tipoClient": "VBA",
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  },
  "descriptions": {
    "it": "string",
    "en": "string",
    "es": "string",
    "fr": "string",
    "de": "string",
    "zh": "string",
    "ru": "string"
  },
  "xml": [
    "string"
  ],
  "ordinamento": 1.5
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

code (string): Prospetto Style Sheet code used to identify the style sheet.

drillDownDefault (boolean): Enables drill-down behavior by default.

sistema (boolean): Indicates whether the style sheet is system-defined.

foglioStileDefault (boolean): Indicates whether this is the default style sheet.

tipoClient (string): Client type allowed to use the style sheet.

updateInfo (any):

descriptions (any):

xml (array): XML definition of the style sheet.

ordinamento (number): Display order of the style sheet.

[prospetto_stylesheet_deleteById]

Deletes the Prospetto Style Sheet synchronously.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Style Sheet code.

[prospetto_stylesheet_find]

Returns Prospetto Style Sheets matching the optional FIQL filter. Use this tool to search or list Prospetto Style Sheets. Supports filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional FIQL filter expression.

skip (integer): Number of matching resources to skip. Minimum: 0.

take (integer): Maximum number of resources to return.

sort (string): Optional sort expression.

[prospetto_stylesheet_getById]

Returns one Prospetto Style Sheet identified by its code. Use this tool when the resource code is already known.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** cod (string):** Style Sheet code.

[prospetto_stylesheet_update]

Updates an existing Prospetto Style Sheet identified by its code. Use this when a single existing style sheet must be modified.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "UserInfo-Origin": "string",
  "cod": "aCod",
  "code": "string",
  "drillDownDefault": true,
  "sistema": true,
  "foglioStileDefault": true,
  "tipoClient": "VBA",
  "updateInfo": {
    "user": "string",
    "date": "2024-01-01T12:00:00Z",
    "origin": "string"
  },
  "descriptions": {
    "it": "string",
    "en": "string",
    "es": "string",
    "fr": "string",
    "de": "string",
    "zh": "string",
    "ru": "string"
  },
  "xml": [
    "string"
  ],
  "ordinamento": 1.5
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

UserInfo-Origin (string): Optional origin identifier used for audit metadata and update tracking.

*** cod (string):** Style Sheet code.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

code (string): Prospetto Style Sheet code used to identify the style sheet.

drillDownDefault (boolean): Enables drill-down behavior by default.

sistema (boolean): Indicates whether the style sheet is system-defined.

foglioStileDefault (boolean): Indicates whether this is the default style sheet.

tipoClient (string): Client type allowed to use the style sheet.

updateInfo (any):

descriptions (any):

xml (array): XML definition of the style sheet.

ordinamento (number): Display order of the style sheet.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

04

DTP and process configuration

28 operations

DTPs 3

Activities 3

Operations 3

Allocation details 3

Calculation rule attributes 3

Calculation rule scripts 4

Checking rules 3

Parameters 3

Special methods 3

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

DTPs

DTP and process configuration · 3 operations

[dtp_count]

Returns the number of DTPs matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** workspaceId (string):** Workspace code.

[dtp_find]

Returns DTPs matching the optional FIQL filter. Use this tool to search or list DTPs. Supports filtering, sorting, and pagination. Resource hierarchy: Workspace

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

[dtp_getById]

Returns one DTP identified by its ID. Use this tool when the resource ID is already known. Resource hierarchy: Workspace

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Dtp code.

Activities

DTP and process configuration · 3 operations

[activity_count]

Returns the number of DTP Activities matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- level
- targetDataset.id
- loop.id
- typology.id
- updateInfo.origin
- updateInfo.user

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- updateInfo.date

*** workspaceId (string):** Workspace code.

*** dtpId (string):** Dtp code.

[activity_find]

Returns DTP Activities matching the optional FIQL filter. Use this tool to search or list DTP Activities. Supports filtering, sorting, and pagination. Resource hierarchy: Workspace > DTP > Activity

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- level
- targetDataset.id
- loop.id
- typology.id
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

*** dtpId (string):** Dtp code.

[activity_getById]

Returns one DTP Activity identified by its ID. Use this tool when the resource ID is already known. Resource hierarchy: Workspace > DTP > Activity

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** dtpId (string):** Dtp code.

*** id (string):** DTP Activity code.

Operations

DTP and process configuration · 3 operations

[operation_count]

Returns the number of DTP Operations matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- operationType
- sourceDataset.id
- specialMethod.id
- referenceDataset.id
- driverDataset.id
- driverTypology.id
- loop.id
- typology.id
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** workspaceId (string):** Workspace code.

*** dtpId (string):** Dtp code.

*** activityId (string):** Activity code.

[operation_find]

Returns DTP Operations matching the optional FIQL filter. Use this tool to search or list DTP Operations. Supports filtering, sorting, and pagination. Resource hierarchy: Workspace > DTP > Activity

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- operationType
- sourceDataset.id
- specialMethod.id
- referenceDataset.id
- driverDataset.id
- driverTypology.id
- loop.id
- typology.id
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

*** dtpId (string):** Dtp code.

*** activityId (string):** Activity code.

[operation_getById]

Returns one DTP Operation identified by its ID. Use this tool when the resource ID is already known. Resource hierarchy: Workspace > DTP > Activity

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** dtpId (string):** Dtp code.

*** id (string):** DTP Operation code.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

*** activityId (string):** Activity code.

Allocation details

DTP and process configuration · 3 operations

[allocation_count]

Returns the number of DTP Allocation details matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** workspaceId (string):** Workspace code.

*** dtpId (string):** Dtp code.

*** activityId (string):** Activity code.

*** operationId (string):** Operation code

[allocation_find]

Returns DTP Allocation details matching the optional FIQL filter. Use this tool to search or list DTP Allocation details. Supports filtering, sorting, and pagination. Resource hierarchy: Workspace > DTP > Activity > Operation > Allocation detail

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

*** dtpId (string):** Dtp code.

*** activityId (string):** Activity code.

*** operationId (string):** Operation code.

`[allocation_getById]`

Returns one DTP Allocation detail identified by its ID. Use this tool when the resource ID is already known. Resource hierarchy: Workspace > DTP > Activity > Operation > Allocation detail

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** dtpId (string):** Dtp code.

*** id (string):** DTP Allocation code.

*** activityId (string):** Activity code.

*** operationId (string):** Operation code.

Calculation rule attributes

DTP and process configuration · 3 operations

`[calculationrulesattribute_operandCount]`

Returns the number of Calculation Rule Attributes matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): FIQL filter

*** workspaceId (string):** Workspace code

[calculationrulesattribute_operandFind]

Returns Calculation Rule Attributes matching the optional FIQL filter. Use this tool to search or list Calculation Rule Attributes. Supports filtering, sorting, and pagination. Resource hierarchy: Workspace > DTP

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): FIQL filter. Filterable fields:

- scriptOperandCode
- logicalDimension
- fieldCode
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Offset for pagination

take (integer): Page size (max 10000)

sort (string): Sorting (e.g. scriptOperandCode:asc;logicalDimension:desc)

*** workspaceId (string):** Workspace code

[calculationrulesattribute_operandGetByKey]

Find Calculation Rule Attribute by composite key

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code

*** scriptOperandCode (string):** Script operand code (key 1)

*** logicalDimension (string):** Logical dimension (key 2)

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Calculation rule scripts

DTP and process configuration · 4 operations

[calculationrulesscript_count]

Returns the number of Calculation Rule Scripts matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** workspaceId (string):** Workspace code.

[calculationrulesscript_elementsFetch]

Returns only selected properties of Calculation Rule Scripts matching the optional FIQL filter. Use this tool instead of find when only specific properties are needed. Specify the properties as a comma-separated list.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** properties (string):** Comma-separated properties to fetch. **Please note that description property is set with user default language**

sort (string): Sort parameter for sorting

filter (string): Filter string which is compliant to FIQL

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

*** workspaceId (string):** Workspace code

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[calculationrulesscript_find]

Returns Calculation Rule Scripts matching the optional FIQL filter. Use this tool to search or list Calculation Rule Scripts. Supports filtering, sorting, and pagination. Resource hierarchy: Workspace > DTP

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

[calculationrulesscript_getById]

Returns one Calculation Rule Script identified by its ID. Use this tool when the resource ID is already known. Resource hierarchy: Workspace > DTP

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Calculation Rule Script code.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Checking rules

DTP and process configuration · 3 operations

[checkingRule_count]

Returns the number of Checking Rules matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** workspaceId (string):** Workspace code.

[checkingRule_find]

Returns Checking Rules matching the optional FIQL filter. Use this tool to search or list Checking Rules. Supports filtering, sorting, and pagination. Resource hierarchy: Workspace > DTP

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

[checkingRule_getById]

Returns one Checking Rule identified by its ID. Use this tool when the resource ID is already known. Resource hierarchy: Workspace > DTP

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Checking rule code.

Parameters

DTP and process configuration · 3 operations

[parameter_count]

Returns the number of Parameters matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** workspaceId (string):** Workspace code.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[parameter_find]

Returns Parameters matching the optional FIQL filter. Use this tool to search or list Parameters. Supports filtering, sorting, and pagination. Resource hierarchy: Workspace > DTP

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

[parameter_getById]

Returns one Parameter identified by its ID. Use this tool when the resource ID is already known. Resource hierarchy: Workspace > DTP

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Parameter code.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Special methods

DTP and process configuration · 3 operations

[specialmethod_count]

Returns the number of Special Methods matching the optional FIQL filter. Use this tool when only the count is needed, not the resource data.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:
- id
- descriptions
- queryBody.oracle
- queryBody.sqlServer
- queryBody.postgres
- queryBody.hana
- updateInfo.origin
- updateInfo.user
- updateInfo.date

*** workspaceId (string):** Workspace code.

[specialmethod_find]

Returns Special Methods matching the optional FIQL filter. Use this tool to search or list Special Methods. Supports filtering, sorting, and pagination. Resource hierarchy: Workspace > DTP

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Filter string which is compliant to FIQL.

- Filterable fields:

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

- id
- descriptions
- queryBody.oracle
- queryBody.sqlServer
- queryBody.postgres
- queryBody.hana
- updateInfo.origin
- updateInfo.user
- updateInfo.date

skip (integer): Skip parameter offset for paging

take (integer): Take parameter page size for paging. Maximum value accepted is 10000

sort (string): Sort parameter for sorting

*** workspaceId (string):** Workspace code.

[specialmethod_getById]

Returns one Special Method identified by its ID. Use this tool when the resource ID is already known. Resource hierarchy: Workspace > DTP

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** workspaceId (string):** Workspace code.

*** id (string):** Special method code.

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

05

User Provisioning

5 operations

Users 5

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Users

User Provisioning · 5 operations

[users_createUser]

Creates a new SCIM 2.0 User. Use this operation to provision a new user. The request body must match UserInput and should include the SCIM core schema URN plus any extension schema URNs used by the payload. For direct HTTP requests, send the headers Content-Type: application/scim+json and Accept: application/scim+json. These are HTTP headers, not properties of the JSON body. Start with the minimal example below and use a unique userName for each new user. Do not send server-managed id or lastLogin. Role provisioning through the TGK extension userRoles has been rejected by the tested deployment with HTTP 406 (The userRole property is not supported); omit userRoles for this deployment. The top-level description attribute and other optional attributes, including dbAllowed, have not been independently verified for this POST. Do not copy a GET response as a create payload. Include extension schema URNs only when supplying those extensions.

Example arguments:

```
{
  "schemas": ["urn:ietf:params:scim:schemas:core:2.0:User"],
  "userName": "SCIM_TEST_20261002_02",
  "active": false
}
```

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** schemas (array):** SCIM schema URNs represented by this user. Include the core User schema and any extension schema URNs present in the payload.

externalId (['string', 'null']): Optional identifier assigned by an external provisioning system.

*** userName (string):** Unique user name/login used to identify the user.

name (any): Structured person name.

userType (string): User type code.

preferredLanguage (string): Preferred language/locale for the user, for example en-US.

*** active (boolean):** Whether the user account is active.

emails (array): Email addresses associated with the user.

phoneNumbers (array): Phone numbers associated with the user.

urn:tgk:params:scim:schemas:extension:2.0:User (any): TGK-specific SCIM user extension.

urn:ietf:params:scim:schemas:extension:enterprise:2.0:User (any): SCIM Enterprise User extension.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

[users_deleteUser]

Deletes the SCIM User identified by userId. Use this operation only when the user should be removed.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** userId (string):** Identifier of the SCIM User.

[users_getUser]

Returns one SCIM User identified by userId. Use this operation when the user identifier is already known.

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** userId (string):** Identifier of the SCIM User.

[users_patchUser]

Partially updates an existing SCIM User identified by userId. Use this operation to change only selected attributes without replacing the complete resource. The minimal example replaces active only; do not use description as a patch path. For direct HTTP requests, send Content-Type: application/scim+json and Accept: application/scim+json as HTTP headers, not JSON body properties.

Example arguments:

```
{
  "api_key": "string",
  "db_id": "string",
  "userId": "string",
  "schemas": [
    "urn:ietf:params:scim:api:messages:2.0:PatchOp"
  ],
  "Operations": [
    {
      "op": "replace",
      "path": "active",
      "value": false
    }
  ]
}
```

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

*** userId (string):** Identifier of the SCIM User.

*** schemas (array):** Must contain urn:ietf:params:scim:api:messages:2.0:PatchOp.

*** Operations (array):** Patch operations to apply in order. Each operation contains: - op: one of add, remove, replace. - path: SCIM attribute path to modify. - value: value to add or replace, when applicable.

[users_searchUsersWithGet]

Searches or lists SCIM Users. Use this operation when the user identifier is not known or when multiple users may match. Supports SCIM filtering, sorting, and pagination.

All descriptions filters must contain the language, eg. descriptions.en=like="value"; The value to filter all data is '$ALL', eg. Dataset_00000(Process='ACT',Scenario='2026_ACT',Period='12',Entity='$ALL')

Parameters:

*** api_key (string):** Required Tagetik API key for this call. Use only the key explicitly provided by the user in the conversation or client system context; never invent one. Sent to Tagetik as the apikey header.

*** db_id (string):** Required Tagetik database ID for this call. Use the database explicitly provided by the user or client system context.

filter (string): Optional SCIM filter expression. Example: userName eq "UserA".

sortBy (string): Optional user attribute used to sort results. Example: userName.

sortOrder (string): Optional sort direction. Allowed values: ascending, descending.

startIndex (integer): Optional 1-based index of the first result to return. Minimum: 1.

count (integer): Optional maximum number of results to return. Minimum: 0.

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

Alphabetical operation index

Select an operation identifier to jump to its complete definition.

account_addAccount 60
account_count 64
account_find 65
account_hierarchy_countAccountHierarchy 81
account_hierarchy_createAccountHierarchy 81
account_hierarchy_fetchAccountHierarchy 82
account_hierarchy_getAccountHierarchyById 82
account_hierarchy_listAccountHierarchy 82
account_hierarchy_relationships_addContoGerarchiaAbbiLowest 84
account_hierarchy_relationships_contoGerarchiaAbbiLowestBulk 84
account_hierarchy_relationships_count 86
account_hierarchy_relationships_deleteContoGerarchiaAbbiLowest 87
account_hierarchy_relationships_find 87
account_hierarchy_relationships_getById 87
account_hierarchy_relationships_updateContoGerarchiaAbbiLowest 88
account_hierarchy_structure_bulkAccountHierarchyStructureNodes 88
account_hierarchy_structure_countAccountHierarchyStructureNodes 91
account_hierarchy_structure_createAccountHierarchyStructureNode 91
account_hierarchy_structure_findAccountHierarchyStructureNodeById 92
account_hierarchy_structure_findAccountHierarchyStructureNodes 92
account_hierarchy_structure_patchAccountHierarchyStructureNode 93
account_hierarchy_updateAccountHierarchy 83
account_originalAccountBulk 67
account_updateAccount 76
activity_count 186
activity_find 187
activity_getById 187
allocation_count 190
allocation_find 190
allocation_getById 191
analytical_workspace_data_extraction_get_analytical_data 10

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

analytical_workspace_data_extraction_get_analytical_data_requirements 12
analyticalDimension_addAnalytical_Dimension 118
analyticalDimension_count 119
analyticalDimension_find 120
analyticalDimension_getById 120
analyticalDimension_originalAnalyticalDimensionBulk 121
analyticalDimension_updateAnalyticalDimension 122
calculationrulesattribute_operandCount 191
calculationrulesattribute_operandFind 192
calculationrulesattribute_operandGetByKey 192
calculationrulesscript_count 193
calculationrulesscript_elementsFetch 193
calculationrulesscript_find 194
calculationrulesscript_getById 194
category_addCategory 125
category_categoryBulk 126
category_countCategory 130
category_find 130
category_getCategoryById 131
category_updateCategory 132
checkingRule_count 195
checkingRule_find 195
checkingRule_getById 196
currency_addCurrency 133
currency_count 134
currency_find 135
currency_getById 135
currency_originalCurrencyBulk 135
currency_updateCurrency 137
custom_dimension_count 123
custom_dimension_find 123
custom_dimension_getById 124
dataset_addDataset 12
dataset_count 13

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

dataset_datasetBulk 14
dataset_deleteDataset 16
dataset_field_addDataset 19
dataset_field_count 20
dataset_field_datasetBulk 20
dataset_field_deleteDatasetField 22
dataset_field_find 22
dataset_field_getById 23
dataset_field_updateDatasetField 23
dataset_find 17
dataset_getById 17
dataset_partitions_addDatasetPartition 24
dataset_partitions_count 25
dataset_partitions_find 26
dataset_partitions_getById 27
dataset_set_offline_setOffline 27
dataset_set_offline_setOffline_2 27
dataset_set_online_setOnline 28
dataset_set_online_setOnline_2 28
dataset_updateDataset 18
datasource_addDatasource 31
datasource_count 32
datasource_datasourceBulk 33
datasource_deleteDatasource 35
datasource_field_addDatasource 37
datasource_field_count 38
datasource_field_datasourceBulk 38
datasource_field_deleteDatasourceField 39
datasource_field_find 40
datasource_field_getById 40
datasource_field_updateDatasourceField 41
datasource_find 35
datasource_getById 36
datasource_updateDatasource 36

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

dictionary_addDictionary 53
dictionary_count 54
dictionary_deleteDictionary 54
dictionary_dictionaryBulk 54
dictionary_find 56
dictionary_getById 57
dictionary_updateDictionary 57
dtp_count 185
dtp_find 185
dtp_getById 186
entity_addEntity 94
entity_count 96
entity_find 98
entity_getById 99
entity_hierarchy_structure_v2_bulkEntityHierarchyStructureNodesV2 112
entity_hierarchy_structure_v2_countEntityHierarchyStructureNodesV2 114
entity_hierarchy_structure_v2_createEntityHierarchyStructureNodeV2 115
entity_hierarchy_structure_v2_fetchEntityHierarchyStructureNodesV2 116
entity_hierarchy_structure_v2_findEntityHierarchyStructureNodesV2 117
entity_hierarchy_structure_v2_findEntityHierarchyStructureNodeV2ById 116
entity_hierarchy_structure_v2_patchEntityHierarchyStructureNodeV2 117
entity_hierarchy_v2_bulkEntityHierarchiesV2 107
entity_hierarchy_v2_countEntityHierarchiesV2 109
entity_hierarchy_v2_createEntityHierarchyV2 109
entity_hierarchy_v2_fetchEntityHierarchiesV2 110
entity_hierarchy_v2_findEntityHierarchiesV2 110
entity_hierarchy_v2_findEntityHierarchyV2ById 111
entity_hierarchy_v2_patchEntityHierarchyV2 111
entity_originalEntityBulk 100
entity_updateEntity 105
operation_count 188
operation_find 188
operation_getById 189
original_scenario_addOriginalScenario 138

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

original_scenario_count 139
original_scenario_find 140
original_scenario_getById 140
original_scenario_originalScenarioBulk 141
original_scenario_period_original_bulk 144
original_scenario_period_original_count 145
original_scenario_period_original_create 145
original_scenario_period_original_findByIds 146
original_scenario_period_original_get 147
original_scenario_period_original_getList 147
original_scenario_period_original_update 147
original_scenario_updateOriginalScenario 142
parameter_count 196
parameter_find 197
parameter_getById 197
period_countPeriods 149
period_findPeriods 149
period_getPeriodById 150
prosp_filtro_count 168
prosp_filtro_create 168
prosp_filtro_deleteById 169
prosp_filtro_find 169
prosp_filtro_getById 169
prosp_filtro_update 170
prospetto_bulk 157
prospetto_count 161
prospetto_create 161
prospetto_deleteById 164
prospetto_find 164
prospetto_formula_find 171
prospetto_formula_getById 171
prospetto_getById 165
prospetto_parametro_find 172
prospetto_parametro_getById 172

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

prospetto_query_bulk 172
prospetto_query_count 174
prospetto_query_create 174
prospetto_query_deleteById 175
prospetto_query_find 176
prospetto_query_getById 176
prospetto_query_update 176
prospetto_stylesheet_bulk 177
prospetto_stylesheet_count 179
prospetto_stylesheet_create 180
prospetto_stylesheet_deleteById 181
prospetto_stylesheet_find 181
prospetto_stylesheet_getById 181
prospetto_stylesheet_update 182
prospetto_update 165
specialmethod_count 198
specialmethod_find 198
specialmethod_getById 199
typology_count 29
typology_elementsFetch 30
typology_find 30
typology_getById 31
users_createUser 201
users_deleteUser 202
users_getUser 202
users_patchUser 202
users_searchUsersWithGet 203
virtual_dataset_addVirtualDataset 42
virtual_dataset_count 43
virtual_dataset_deleteVirtualDataset 43
virtual_dataset_field_addDataset 48
virtual_dataset_field_count 49
virtual_dataset_field_datasetBulk 49
virtual_dataset_field_deleteDatasetField 50

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER

virtual_dataset_field_find 51
virtual_dataset_field_getById 51
virtual_dataset_field_updateDatasetField 52
virtual_dataset_find 43
virtual_dataset_getById 44
virtual_dataset_updateVirtualDataset 44
virtual_dataset_virtualDatasetBulk 45
voce_dizionario_bulk 150
voce_dizionario_count 152
voce_dizionario_create 152
voce_dizionario_deleteById 153
voce_dizionario_find 153
voce_dizionario_getById 154
voce_dizionario_update 154
workspace_addWorkspace 5
workspace_count 6
workspace_deleteWorkspace 6
workspace_find 7
workspace_getById 7
workspace_updateWorkspace 7
workspace_workspaceBulk 9

WOLTERS KLUWER INTELLECTUAL PROPERTY

© 2026 Wolters Kluwer N.V. and/or its subsidiaries. All rights reserved.
INTELLECTUAL PROPERTY OF WOLTERS KLUWER