OData: General settings and Users setup

This article explains how to configure CCH® Tagetik to read and expose data via OData service

May 25, 2022 · Knowledge

Title
OData: General settings and Users setup

Summary
This article explains how to configure CCH® Tagetik to read and expose data via OData service

From Version

Up to Version
5.3 SP21

Addressees

Context

Background Info
The System Administrator is the user entitled to setup configuration from Repository

Procedure
To setup OData service on CCH® Tagetik, it is necessary enable OData in security settings, assign a role with specific functions to the users that intend to use OData and create the endpoints. Endpoints are the access point to read OData from external sources.

Configuration

1. Access Repository.
2. Click on **General Settings** tile.
3. Select **Security**.
4. Tick the check box **Enable public REST APIs** among the Security configuration.

Role creation

1. Click **Users & Roles** tile.
2. Select **Custom roles** below **Roles** menu.
3. Add a new role.
4. Specify the favourite Reference role and save.
5. Access **Enable functions** from Action menu.
6. Add the function **0004077 – Analytical workspace: OData services.**
7. If the role must read Audit data via OData service, add also the function **0001286 – Repository – Audit – Audit – Log Advanced search – Online table.**

User creation

The user creation depends on the authentication type that will be chosen in the definition of the endpoint. The possible authentication is Basic and OAuth 2.0.

Basic authentication

Create the user and assign to it the specific role created in the previous step.

1. Click **Users & Roles** tile.
2. Select **Users**.
3. Add a new user defining code and description.
4. Select **Local user** in the combo box **User type**.
5. Access the tab **Security** and make sure that check box **Password to change** is unticked.
6. Save the user.

7. Click on actions menu and set the password clicking on **Change password**.
8. From Repository homepage.
9. Click **Users & Roles** tile.
10. Select **Users/Roles mapping**.
11. Define a mapping that include the User and the Role created in the previous steps and specify the database on which the user is entitled to read the OData stream.

OAuth2 authentication

This is the preferred kind of authentication to use when connector/BI tool is installed on an external OpenID provider where to register one or more client applications. CCH® Tagetik system administrator has to define one or more Local Users and give them the proper roles. They have to be flagged as Reference Users. Each Reference user represents a different scope in case the framework includes the Client Identity Provider. These users can be marked as disabled since they won't access directly to the application.

1. Click **Users & Roles** tile.
2. Select **Users**.
3. Add a new user defining code and description.
4. Select **Local user** in the combo box **User type**.
5. Access the tab **Security**.
6. Tick the option **Reference user for other users**.
7. Save the user.
8. From Repository homepage click **Users & Roles** tile.
9. Select **Users/Roles mapping**.
10. Define a mapping that include the User and the Role created in the previous steps and specify the database on which the user is entitled to read the OData stream.

Example

Troubleshooting

Technical Requirement

To Learn More

Was this article helpful?

0 0

Choose a general reason

-- Choose a general reason --

Description

Please, leave us some feedback...

Submit