CP&ESG

SAML Authentication

February 20, 2026

Protection: Confidential

Wolters Kluwer

Content

1. Introduction 3
2. Overview of SAML 4
2.1 Single Sign-On Profile 5
2.1.1 SP initiated SSO: Redirect/POST Bindings 5
2.1.2 SP initiated SSO: POST/POST Bindings 6
2.1.3 IDP initiated SSO: POST Binding 6
2.2 Single Log-Out Profile (starting from 5.3.SP25) 7
2.2.1 SP initiated Single Log-Out 7
3. Security configuration 8
3.1 Digital Signature 8
3.2 Encryption 8
3.3 Key Management 8
3.4 SSL/TLS 8
4. Metadata Configuration 8
4.1 Service Provider (SP) Metadata 9
4.2 Identity Provider (IDP) Metadata 11
5. CCH® Tagetik Server Configuration 12
5.1 Authentication Validity Timeout Settings 13
5.2 Hashing Algorithm 13
6. CCH® Tagetik Authentication Configuration 14
6.1 Steps 14
7. User management 16
7.1 SAML Configuration Parameters 16
7.2 Alternate Login Access 17
8. Glossary 18
9. Notes and Copyright 19

1. Introduction

Starting with version 5.0.2, CCH® Tagetik supports Security Assertion Markup Language (SAML) V2.0 for single sign-on (SSO), allowing users to log in once and access the application without re-entering passwords. This guide explains how IT administrators can configure the identity provider, the application server, and CCH® Tagetik so users authenticated via SAML are automatically logged in using their existing credentials.
Experience with JEE servers, CCH® Tagetik authentication, SAML, and identity providers used by SAML is required, as well as admin access to authentication settings in the CCH® Tagetik's Repository.
CCH® Tagetik staff may perform some or all these steps for Cloud customers.
If you have any questions or feedback about this document, please reach out to CCH® Tagetik.

2. Overview of SAML

This section offers an overview of the SAML components pertinent to integration with CCH® Tagetik. For additional information and further detail, readers are encouraged to consult the appendix of this document.
SAML is an XML-based, open-standard data format for exchanging authentication and authorization data between an identity provider, a producer of SAML assertions, and a service provider (SP), a consumer of SAML assertions.
The SAML specification defines three roles:

- the principal (e.g. a user)
- the identity provider (IDP) that is an entity which knows how to authenticate users and provides information about their identity
- the service provider (SP) which, in this case, is the CCH® Tagetik application.

With SAML, the principal requests a service from the service provider, which then gets an identity assertion from an identity provider. This assertion lets the service provider decide whether to grant access to the principal.
CCH® Tagetik's SAML implementation allows three possible Single Sign-On (SSO) profile:

- SP initiated SSO: Redirect/POST Bindings
- SP initiated SSO: POST/POST Bindings
- IDP initiated SSO: POST Binding

And one Single Log-Out (SLO) profile:

- SP initiated SLO

2.1 Single Sign-On Profile

This section describes common flows used with the SSO profile.

2.1.1 SP initiated SSO: Redirect/POST Bindings

This scenario describes an SP-initiated SSO exchange.

In this exchange the user attempts to access a resource on the SP. However, they do not have a current logon session on this site and their federated identity is managed by their IDP. They are sent to the IDP to log on and the IDP provides a SAML web SSO assertion for the user's federated identity back to the SP.

For this specific use case, the HTTP Redirect Binding is used to deliver the SAML <AuthnRequest> message to the IDP and the HTTP POST Binding is used to return the SAML <Response> message containing the assertion to the SP. The following figure illustrates the message flow.




Figure 1 SP-Initiated SSO with Redirect/POST Bindings

2.1.2 SP initiated SSO: POST/POST Bindings

This scenario also describes an SP-initiated SSO exchange, but in this case the HTTP POST binding is used to send the SAML <AuthnRequest> to the IDP. The HTTP POST binding may be necessary for an <AuthnRequest> message in cases where its length precludes the use of the HTTP Redirect binding (which is typical). The message may be long enough to require a POST binding when, for example, it includes many of its optional elements and attributes, or when it must be digitally signed. The figure below shows the message flow.




Figure 2 SP-Initiated SSO with POST/POST Bindings

2.1.3 IDP initiated SSO: POST Binding

In an IDP-initiated use case, the identity provider is configured with specialized links that refer to the desired service providers. These links refer to the local IDP's Single Sign-On Service and pass parameters to the service identifying the remote SP. So instead of visiting the SP directly, the user accesses the IDP site and clicks on one of the links to gain access to the remote SP. This triggers the creation of a SAML assertion that, in this example, will be transported to the service provider using the HTTP POST binding. Figure 5 shows the process flow for an IDP-initiated web SSO exchange.




Figure 3 IDP-Initiated SSO with POST Binding

2.2 Single Log-Out Profile (starting from 5.3.SP25)

Once single sign-on has been achieved, several individual sessions with service providers share a single authentication context. This section discusses SAML's profile for single logout, which allows for reversing the sign-on process.

2.2.1 SP initiated Single Log-Out

In the example shown in Figure 4, a user visiting the sp1.example.com service provider web site decides that they wish to log out of their web SSO session. The identity provider idp.example.org determines that other service providers are also participants in the web SSO session and thus sends <LogoutRequest> messages to each of the other SPs.




Figure 4 SP-initiate Single Log-Out

3.Security configuration

SAML requires configuration of security settings which include cryptographic material used for digital signatures and encryption. The SAML 2.0 protocol enables advanced use of Public Key Infrastructure (PKI) for federation security. The CCH® Tagetik SAML implementation includes:

- Digital signature of SAML Authentication Request sent by the SP to the IDP.
- Digital signature verification of SAML assertions and/or SAML response messages sent by the IDP to the SP.
- Decryption of SAML Response, i.e. decryption of security tokens and assertion data sent by the IDP to the SP.

3.1 Digital Signature

SAML assertions and SAML protocol request and response messages may be signed, with the following benefits. An assertion signed by the asserting party supports assertion integrity, authentication of the asserting party to a SAML relying party, and, if the signature is based on the SAML authority's public-private key pair, non-repudiation of origin. A SAML protocol request or response message signed by the message originator supports message integrity, authentication of message origin to a destination, and, if the signature is based on the originator's public-private key pair, non-repudiation of origin.

3.2 Encryption

Encryption is used as the means to implement confidentiality. The most common motives for confidentiality are to protect the personal privacy of individuals or to protect organizational secrets for competitive advantage or similar reasons. Any of the algorithms defined for use with XML Encryption MAY be used to perform the encryption. Due to US export limitations Java JDK comes with a limited set of cryptography capabilities. Using SAML Encryption might require installation of the Unlimited Strength Jurisdiction Policy Files which removes these limitations.

3.3 Key Management

SAML exchanges involve usage of cryptography for signing and encryption of data. All SP interactions with cryptographic keys are done through a single JKS key store which contains private and public keys:

- SP private key is used to digitally sign SAML authentication requests.
- SAML request data is not encrypted.
- SAML response signature is deemed trusted when the certificate used to create it is included in Key with usage of signing or unspecified in IDP metadata.

3.4 SSL/TLS

Where message integrity and message confidentiality are required, then HTTP over SSL/TLS is mandatory.

4.Metadata Configuration

SAML metadata is an XML document which contains information necessary for interaction with SAML enabled identity or service providers. The document contains e.g., URLs of endpoints, information about supported bindings, identifiers and public keys. Typically, one metadata document will be generated for your own SP and sent to IDP you want to enable single sign-on with. Similarly, IDP will make its own metadata available for you to import into your SP application.

4.1 Service Provider (SP) Metadata

SP metadata contains keys, services and URLs defining SAML endpoints of your CCH® Tagetik application. Metadata is pre-created and, if required by IDP, must be provided to the IDP with whom we want to establish trust (the CCH® Tagetik SAML Auth Configuration templates contain an example of SP Metadata).

Here are shown two examples of the sp metadata file.

For CCH® Tagetik <= 5.3.SP28:

```
<?xml version="1.0" encoding="UTF-8"?>
<md:EntityDescriptor xmlns:md="urn:oasis:names:tc:SAML:2.0:metadata" ID="tagetik_5_prod"
entityID="https://saml.saastagetik.com/tagetikcpm/5/">
  <md:SPSSODescriptor AuthnRequestsSigned="true" WantAssertionsSigned="true"
protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
    <md:KeyDescriptor use="signing">
      <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
        <ds:X509Data>
          <ds:X509Certificate>MIIDUjCCAj…</ds:X509Certificate>
        </ds:X509Data>
      </ds:KeyInfo>
    </md:KeyDescriptor>
    <md:KeyDescriptor use="encryption">
      <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
        <ds:X509Data>
          <ds:X509Certificate>MIIDUjCCAj….</ds:X509Certificate>
        </ds:X509Data>
      </ds:KeyInfo>
    </md:KeyDescriptor>
  <md:SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
Location="https://saml.saastagetik.com/tagetikcpm/saml/SingleLogout”/>
<md:SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Redirect"
Location="https://saml.saastagetik.com/tagetikcpm/saml/SingleLogout”/>
  <md:NameIDFormat>urn:oasis:names:tc:SAML:1.1:nameid-
format:emailAddress</md:NameIDFormat>
<md:NameIDFormat>urn:oasis:names:tc:SAML:2.0:nameid-format:transient</md:NameIDFormat>
<md:NameIDFormat>urn:oasis:names:tc:SAML:2.0:nameid-format:persistent</md:NameIDFormat>
<md:NameIDFormat>urn:oasis:names:tc:SAML:1.1:nameid-format:unspecified</md:NameIDFormat>
<md:NameIDFormat>urn:oasis:names:tc:SAML:1.1:nameid-
format:X509SubjectName</md:NameIDFormat>
<md:AssertionConsumerService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
Location="https://saml.saastagetik.com/tagetikcpm/5/" index="0" isDefault="true"/>
```

For CCH® Tagetik version >= 5.3.SP29:

```
<?xml version="1.0" encoding="UTF-8"?>
<md:EntityDescriptor xmlns:md="urn:oasis:names:tc:SAML:2.0:metadata" ID="tagetik_5_prod"
entityID="https://saml.saastagetik.com/tagetikcpm/5/">
  <md:SPSSODescriptor AuthnRequestsSigned="true" WantAssertionsSigned="true"
protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
    <md:KeyDescriptor use="signing">
      <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
        <ds:X509Data>
          <ds:X509Certificate>MIIDUjCCAj…</ds:X509Certificate>
        </ds:X509Data>
      </ds:KeyInfo>
    </md:KeyDescriptor>
    <md:KeyDescriptor use="encryption">
      <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
        <ds:X509Data>
          <ds:X509Certificate>MIIDUjCCAj….</ds:X509Certificate>
        </ds:X509Data>
      </ds:KeyInfo>
    </md:KeyDescriptor>
  <md:SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
Location="https://saml.saastagetik.com/tagetikcpm/saml2/slo”/>
<md:SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Redirect"
Location="https://saml.saastagetik.com/tagetikcpm/saml2/slo”/>
<md:AssertionConsumerService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
Location="https://saml.saastagetik.com/tagetikcpm/5/" index="0" isDefault="true"/>
</md:SPSSODescriptor>
</md:EntityDescriptor>
```

By using pre-configured metadata, you can perform changes manually in the following metadata template file:
Edit following values, highlighted in bold in section above:

- Replace <EntityDescriptor> ID attribute unique for each CCH® Tagetik application instance with a name which identifies that installation of the application.
- Replace <EntityDescriptor> EntityID attribute (it is the SP unique ID) with the URL of CCH® Tagetik as visible from the IDP followed by path /5/, e.g. **https://saml.saastagetik.com/tagetikcpm/5/**
- Replace <KeyInfo><X509Data><X509Certificate> value both for signing and encryption with your X509 certificate. The body of <X509Certificate> is the DER-encoded data of X509 certificate.
- Replace the endpoint URL Location for the <AssertionConsumerService> with the URL of CCH® Tagetik as visible from the IDP followed by path /5/, e.g. **https://saml.saastagetik.com/tagetikcpm/5/**
- Starting from 5.3.SP25, it is possible to replace the endpoint URL Location for the <SingleLogoutService> with the logout URL of CCH® Tagetik e.g. **https://saml.saastagetik.com/tagetikcpm/saml/SingleLogout for version <= 5.3.SP28** and with **https://saml.saastagetik.com/tagetikcpm/saml/slo for version >= 5.3.SP29**.

Save the Service Provider metadata as an xml file (e.g. sp_metadata.xml) and put it in a location on the server that is accessible from the application server where is running CCH® Tagetik.

For versions of CCH Tagetik <= 5.3.SP28

In case of the <SingleLogoutService> has been set, it is necessary to add the system property it.grupposervizi.easy.saml.singlelogout.enabled to true if you want to enable the Single Logout in SAML authentication. If it is not set the default value is false.

For versions of CCH Tagetik >= 5.3.SP29 and ADFS as SAML provider you need to:

1. Go to the AdfsRelyingPartyTrust configurations and check if there is an encryptionCertificate and what value is set in the SamlResponseSignature property.
2. If there is an encryptionCertificate and the SamlResponseSignature property is set to AssertionOnly, we ask them to change the value of SamlResponseSignature to MessageAndAssertion.
3. To ensure that the changes are applied, disable and re-enable the configuration.

4.2 Identity Provider (IDP) Metadata

Metadata for identity provider must be locally available to the application server where CCH® Tagetik is running in a similar way as pre-configured SP metadata. Please refer to your IDP documentation to know how to obtain IDP metadata file. See the section “Configuring Identity Providers”.

5.CCH® Tagetik Server Configuration

Create a SAML configuration file on the server running CCH® Tagetik. Inside your SAML configuration file, set the following properties:

```
# Service Provider metadata location
tgk.saml.sp.metadata.location=/home/tagetik/saml/metadata/sp_metadata.xml
# Identity Provider metadata location
tgk.saml.idp.metadata.location=/home/tagetik/saml/metadata/idp_metadata.xml
# JKS keystore location
tgk.saml.keystore.location=/home/tagetik/saml/keystore/samlKeystore.jks
# keystore password
tgk.saml.keystore.password=password123
# alias of default private key
tgk.saml.private.key=keyalias
# password of default private key
tgk.saml.private.password=password123
# Alias of the default certificate
tgk.saml.default.key=keyalias
## Multitenant code (required for CCH® Tagetik versions >= 5.2.2). For
## standard CCH® Tagetik installations this property must be set to $
tgk.saml.codMT=$
## URL for external SAML IDP (for CCH® Tagetik versions >= 5.3.SP27)
#tgk.saml.idp.initiated.url=idp_url

## The following properties, related to the load balancer, are valid up to the version
5.3.SP28
## if load balancer/reverse proxy is present, uncomment following properties
## URL schema visible from load balancer/reverse proxy (optional)
#tgk.saml.lb.scheme=https
## URL server name visible from load balancer/reverse proxy server (optional)
#tgk.saml.lb.serverName=saml.saastagetik.com
## URL port visible from load balancer/reverse proxy (optional)
#tgk.saml.lb.serverPort=443
## true if port is included in request URL visible from load balancer/
## reverse proxy server (optional)
#tgk.saml.lb.includeServerPortInRequestURL=false
## URL contextpath visible from load balancer/reverse proxy server (optional)
#tgk.saml.lb.contextPath=/tagetikcpm\
```

Please note that if you are upgrading from a version <= 5.2.1 to a version >= 5.2.2 you must add the property **tgk.saml.codMT**. For standard CCH® Tagetik installations this property must be always set to **$** (see example above). Note that if CCH® Tagetik is deployed in scenarios where multiple back-end servers process SAML messages forwarded by a reverse-proxy, additional properties are required to provide information about front-end URL to the back-end servers.

To enable CCH® Tagetik SAML authentication, the required system properties must be configured as follows:

- ***spring.profiles.active:*** can assume the values:
  - ***tgk_saml*** if the application server running CCH® Tagetik is not beyond a Load Balancer/Reverse Proxy.
  - ***tgk_saml_LB:*** if the application server running CCH® Tagetik is beyond a Load Balancer/Reverse Proxy.
- ***tgk.saml.properties.file:*** this file contains the complete path with the filename to the SAML configuration file.
- ***tgk.saml.idp.initiated.url:*** this property must only be defined if the user needs to log in from the Excel, Word or Powerpoint addins in the case of IDP-based authentication (otherwise it must be left undefined); when defined, it contains the identity provider's URL for an IDP-initiated flow.

For versions of CCH® Tagetik 5.3.SP29 and 5.3.SP30

You have to configured the system property it.grupposervizi.easy.rest.api.reverseproxy equals to the public cpm url (for example if use *https://saml.saastagetik.com/tagetikcpm* to login in CPM the value must be *https://saml.saastagetik.com/tagetikcpm)*

5.1 Authentication Validity Timeout Settings

Some optional properties can be set in order to configure the time window in which the application considers SAML assertions valid.

- **`tgk.saml.maxAuthenticationAge`**: time interval in which the system allows users to single sign-on since their initial authentication with the IDP (based on value AuthInstance of the Authentication statement). Default value is 7200 seconds (2 hours).
- **`tgk.saml.maxAssertionTime`**: validity of assertions processed during the single sign-on process (based on value IssueInstant of Assertion), in seconds. Default value is 3000 seconds (50 minutes).
- **`tgk.saml.responseSkew`**: time skew, in seconds, between IDP and SP system clocks. Default value is 60 seconds.

These properties are available from versions:

- 5.2.0 SP26
- 5.2.1 SP11
- 5.2.2 SP9
- 5.2.3 SP3
- >= 5.2.4
- <= 5.3.SP28

The application server needs to be restarted for this configuration to take effect.

5.2 Hashing Algorithm

Starting from version **5.3.SP5** CCH® Tagetik allows to configure the hashing algorithm used for computing the signature and digest of messages sent to the IDP. The algorithm can be chosen setting the system property `tgk.saml.hashing.algorithm` to one of the following values:

- `sha1` (default)
- `sha256`

6.CCH® Tagetik Authentication Configuration

This section describes how to configure the CCH® Tagetik application to use SAML SSO-based authentication.

6.1 Steps

1. Access the web interface with a CCH® Tagetik user which has administrative privileges and access to the Repository.
2. From the standard CCH® Tagetik 5 web interface, it is necessary to access the Administrative interface by clicking **External Authentication** in the Users & Roles tile





Figure 4 CCH® Tagetik 5 Administrative Interface.

3. If toggle is disabled, enable toggle “Use Third Party Authentication”
4. Select “SAML Authentication” from the “Available authentication types” field.







Figure 5 Configuration of SAML authentication in CCH® Tagetik, authentication types.

5. Set one or more of the above parameters which correspond to the names of the SAML attributes included with the authenticated Assertion. The relative attribute values extracted from SAML assertions will be used for updating authenticated user data at every successful login. The above parameters are all optional.
6. Save the Authentication configuration by clicking on the “save” icon.

After the above steps are completed, this instance of CCH® Tagetik will be enabled for SAML authentication.

7. User management

In CCH® Tagetik, external users, i.e. those users authenticated via external authorities such as Active Directory, initially, must be imported and assigned the appropriate roles and rights with respect to the data. For more information regarding the management of users, their roles and profiles, please refer to the User Management manual available from the CCH® Tagetik web interface.
Otherwise, CCH® Tagetik provides a parameter, “Enabled Login for all user of external authentication mechanism”, which when set permits authenticated users who are not already in the CCH® Tagetik repository to be added automatically without roles or rights.



If "Enabled Login for all users of external authentication mechanism" is set to "true", then the user is automatically created in the Repository if the user is not already defined there.
If there other parameters regarding profiles and rights inheritance set, the new user will have access to functions or data according to the roles and profiles defined. If a previously defined user also has the SAML parameters regarding inheritance of roles and profiles set, then the Repository will be updated. See the table below.

7.1 SAML Configuration Parameters

For versions of CCH® Tagetik >= 5.3.SP32
For Cloud Customers with CCH Tagetik version >= 5.3.SP32 , the "Customize URL for redirect after logout" attribute has no effect when Tagetik-IDP is enabled.

Parameter (Rule/Attribute)	Value
SAML Assertion that contain the user name alternative to the Subject NameID	Name of SAML attribute containing the user name
SAML Assertion: contains the user description	Name of SAML attribute containing user description.
SAML Assertion: contains the first name	Name of SAML attribute containing user first name.
SAML Assertion: contains the last name	Name of SAML attribute containing user last name.
SAML Assertion: contains the entity	Name of SAML attribute containing user entity.
SAML Assertion: contains the department	Name of SAML attribute containing user department.
SAML Assertion: contains the user email	Name of SAML attribute containing user email.
SAML Assertion: contains the user phone	Name of SAML attribute containing user phone.
SAML Assertion: contains the user notes	Name of SAML attribute containing user notes.
SAML Assertion: contains the user area profile	Name of SAML attribute containing user area profile.
SAML: Reading profiles from attributes	Specifies if the area profiles have to be read from the external IDP authentication system.

SAML Assertion: Attribute that contains user profile for inheritance of roles	Name of SAML attribute containing user profile for inheritance of the roles of user. Starting from SP27, It is possible to specify more than one attributes separated by comma (i.e: <attribute1>,<attribute2>)
SAML: Rule for filtering the header with user profile for inheritance of roles	Rule that describes how to retrieve the profiles for the inheritance of roles, starting with value(s) of the attribute user profile for the inheritance of the roles of user. The rules are written in a Java-like (BeanShell) scripting language which allows the definition of variables and the use of functions defined in the application code. Please contact our support for further details.
SAML Assertion: Attribute that contains user profile for Rights inheritance	Name of SAML attribute containing user profile for the inheritance of the rights of user. Starting from SP32, It is possible to specify more than one attributes separated by comma (i.e: <attribute1>,<attribute2>)
SAML: Rule for filtering the header with user profile for Rights inheritance	Rule that describes how to retrieve profiles for the inheritance of rights, starting with value(s) of the attribute user profile for the inheritance of the roles of user. The rules are written in a Java-like (BeanShell) scripting language which allows the definition of variables and the use of functions defined in the application code. Please contact our support for further details.

A few notes

- For CCH® Tagetik versions up to and including 5.1.0 - there is a 30 character limitation for the username. Therefore, for example, the sAMAccountName should be used for AD FS. For OKTA, see the Okta configuration section. For other IDPs, it is necessary to check the documentation of the provider.
- Important to remember that any user who is not authenticated via the Identity Provider, will not be permitted to access the application, even if the user has been configured in CCH® Tagetik.
- Regarding the removal of inactive users, SAML does not permit the removal of a user from the CCH® Tagetik Repository. Inactive user configurations must be removed from CCH® Tagetik manually via the CCH® Tagetik administrative web interface

7.2 Alternate Login Access

When SAML Authentication is enabled, the automatic mechanism that redirects unauthenticated requests to login form page is not available. To authenticate users with username and password with the configured Authentication modes, including the default authentication, it is necessary to connect directly to the URL of the CCH® Tagetik application, i.e. `http://<server>:<port>/tagetikcpm/authenticate`, instead of the normal CCH® Tagetik URL. The usage of an alternative URL for the web interface is not available for the CCH® Tagetik .NET Add-ins. Therefore, users who are not configured to login via SAML or cannot do so, will not be able to login to CCH® Tagetik using the CCH® Tagetik .Net Add-ins.

8.Glossary

The following table provides a short glossary for the terminology which are used in this manual.

AS	Application Server. This middleware software should be understood to mean JEE compliant application servers.
DB	Database
RDBMS	Relational Database Management System, i.e. MS SQL Server.
JEE	Java Platform Enterprise Edition
SAML	Security Assertion Markup Language - Security Assertion Markup Language 2.0 (SAML 2.0) is a version of the SAML standard for exchanging authentication and authorization data between security domains. SAML 2.0 is an XML-based protocol that uses security tokens containing assertions to pass information about a principal (usually an end user) between a SAML authority, that is, an identity provider, and a SAML consumer, that is, a service provider. SAML 2.0 enables web-based authentication and authorization scenarios including cross-domain single sign-on (SSO), which helps reduce the administrative overhead of distributing multiple authentication tokens to the user. For more details see saml-core-2.0-os.pdf (downloaded 13/10/2015 from https://docs.oasis-open.org/security/saml/v2.0/saml-core-2.0-os.pdf). See also https://www.oasis-open.org/committees/tc_home.php?wg_abbrev=security.
PKI	Public Key Infrastructure
SSO	Single Sign On
SP	Service Provider in SAML 2.0.
IDP	Identity Provider in SAML 2.0.

9.Notes and Copyright

Tagetik Software S.r.l. with a sole quotaholder reserves the right to change the contents of this document without prior notice. All trademarks are the property of the trademark owners.
This document and its contents are the sole property of CCH® Tagetik; and are protected by Italian Copyright Law no. 633/1941 and by any applicable international agreements and treaties concerning intellectual property rights. All rights, including the intellectual property rights, are reserved to Tagetik. The user of this document is authorized by Tagetik to make copies of this document for private purposes only in paper and/or electronic formats for the sole purpose of training in relation to the use of Tagetik's software for the benefit of the staff/employees of the above mentioned company. Any other use is hereby expressly forbidden.

CP&ESG

CCH®® Tagetik

Via Roosevelt 103, 55100 Lucca, Italy

Ph. +39 0583 96811 • M. info@tagetik.com

VAT IT 01234830469

wolterskluwer.com

Wolters Kluwer