Tagetik Data Model Repository

5.3.36.543

Tagetik Data Model Repository

[Abstract](#)
[Repository tables](#)

Abstract

This document will describe data tables contained within the Tagetik repository.
When a field begins with "COD_" remember that it stands for the code of the dimension; for example COD_UTENTE is the code of the user (not its description).
When a field begins with "FLAG_" remember that its values are either 0 or 1.

Repository tables

DB
Table name: **REP_DB**
Manage the elements tables of the database. A single installation of Tagetik includes:

- a single centralized Repository database, where the users and their roles (the activities a user can perform in Tagetik) are managed
- one or more Application Databases where data and the data model's dimensions are stored and where the application processes are managed.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_DB	varchar(50)	Yes	Unique Database identifier. The system automatically refers to the Repository database using the same unique identifier code of the database [!]. This cannot be deleted. Mandatory field. It has to coincide with the code recorded in "DB connection status" that can be accessed from the Information menu (in the User's menu located in the bottom half of the Home Page).	Yes	
DESC_DB	varchar(200)	No	Database description.	No	
COD_DB_APPOGGIO	varchar(50)	No	Code of the source reference database. It is useful in the case of a standard environment with which the user sets up its own environment or when two environments are available and the user wants to copy data from one part to another	No	
DESC_DB_APPOGGIO	varchar(200)	No	Description of the source reference database.	No	

Roles
Table name: **REP_RUOLO**
Tagetik provides some predefined roles that essentially cover the majority of the cases of roles assignment to different users. The users can neither modify nor delete their definition.

Tagetik allows the user to define custom roles, if it is necessary to define activities that are different from those expected by system roles.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_RUOLO	varchar(30)	Yes	Unique identifier of the role. **For the system role**: Each system role is identified by a code with a $ character prefix **For the custom roles**: Mandatory field. The first character of the code cannot be $ since this are reserved system roles. The valid characters in Tagetik are characters with ASCII code between 33 and 126, but excluding the following: 61,124,44,39,96, 34,47,92,58,42,63,60 and 62. For further details about valid characters in Tagetik, consult the User manual that can be accessed from the Home page, by the question mark icon "?"	Yes	
DESC_RUOLO	varchar(200)	No	Description of the role	No	
FLAG_BASE	numeric(1)	No	0= for the custom roles	No	

Enable functions and reference roles
Table name: **REP_RUOLO_PADRE**
The table contains the "reference roles" which are used to define the selected role.

A role can be defined from the sum of other roles (not necessarily standard roles). The roles on which a role depends are called parent roles.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_RUOLO	varchar(30)	Yes	Role code	Yes	
COD_RUOLO_PADRE	varchar(30)	Yes	**COD_RUOLO_PADRE**Reference role code.	Yes	

Table name: **REP_RUOLO_FUNZIONE**
For each role, it contains the list of available functions. The table generated by the roles deployment in the Deployed tables tab. All the functions related to the role are listed in this table.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_RUOLO	varchar(30)	Yes	Role code	Yes	
COD_FUNZIONE	varchar(7)	Yes	Function code related to the role.	Yes	
AZIONE	varchar(1)	No	0=Disabled 1=Read only (Only for the tables) 2=Enabled	No	

User
Table name: **REP_UTENTE**
Table containing the list of users who can access the application. Each user can access the application from only one workstation

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_UTENTE	varchar(255)	Yes	Unique ID of the user. It is the code that the user will have to insert in the "User name" field that is present in the login initial window in order to access Tagetik.	Yes	
DESC_UTENTE	varchar(1000)	No	User description	No	
EMAIL	varchar(300)	No	User email address. This address is used by system as the email sender, if in the Repository configuration, the "Mail Session Custom" is specified as the SMTP session used in the send email step and "User" is specified as the "Mail From" rule.	No	
EMAIL_USER	varchar(200)	No	Username used in the authentication procedure for the mail server, if in the Repository configuration, the "Mail Session Custom" is specified as the SMTP session used in the send email step and "User" is specified as the "Mail From" rule.	No	
EMAIL_PWD	varchar(160)	No	Password used in the authentication procedure for the mail server, if in the Repository configuration, the "Mail Session Custom" is specified as the SMTP session used in the send email step and "User" is specified as the "Mail From" rule.	No	
TELEFONO	varchar(300)	No	User's telephone number.	No	
FLAG_BLOCCATO	numeric(1)	No	1 = the user can't access the system. Specifies whether or not the user can access the system.	No	
DATA_CAMBIO_PWD	datetime(8)	No	Date on which the password was lasted modified. It is used by the system to verify whether or not the password has expired.	No	
COD_PWD_REGOLA	varchar(5)	No	Password rule related to the user	No	
NUM_FALLIMENTI	numeric(2)	No	Maximum number of consecutive failed access attempts that the user can perform. It is used by the system to check whether or not it is necessary to disable the user	No	
LINGUA_DESCRIZIONE	numeric(1)	No	Language in which the application (menu items, headers, management fields, message texts) is present-ed. If the language is not available, then the application is presented in the Default Application language. When creating a new user, this field is predefined by the application with the value of the Default for User wizard: Application language field present in the Localization area of the Repository's configuration. If the fields is undefined, the default value is English 0 = IT 1 = EN 2 = FR 3 = DE	No	
COD_NAZIONALITA	varchar(5)	No	User's Language/Country. This information guides the dates and amounts format in Tagetik.	No	
FLAG_PWD_FROM_ADMIN	numeric(1)	No	Specifies the user, at his first access, has to change his password. Once the user has done this, the system automatically resets the value of this field.	No	

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
			It only takes the "Yes" value if the "Minimum length" and "Validity Days" fields are not 0 in the password rule that is related to the user. The system does not take into consideration this field's value if the authentication system is not that of the Repository.		
TIPO_UTENTE	varchar(1)	No	Allows to distinguish the users that can access the application with the sign on check that is not the "Default authentication (Repository)". The possible values are: • E = External user is a user that accesses the application with the sign on checker that is not "Default authentication (Repository)" • L = Local User is a user that accesses the application with the "Default authentication (Repository)" sign on checker	No	
COD_UTENTE_DOMINIO	varchar(255)	No	If the LDAP / JAAS authentication mechanism is enabled, this field contains the user name used to access the LDAP service	No	
FLAG_EREDITA_RUOLO_DB	numeric(1)	No	Specifies if the user is related to a list of reference users. The possible values are: • 1 = Yes in this case, the functions that the user can access on a database are represented by the sum of functions to which the user can access for the assignment of roles plus all the functions that are available to the set of reference users on a given database. The definition of the reference users is performed from the Actions menu: by selecting the "Reference users" option. Note that a user can access a database, if a role has been directly assigned to him on the database, or if at least one of his reference users has a role on the database • 0 = No(default value)	No	
FLAG_UTENTE_RIFERIMENTO	numeric(1)	No	Specifies if the user can be referred to by other users to inherit roles and databases to which he has access.	No	
FLAG_PROFILO_AREA	numeric(1)	No	Specifies if an "area profile" from another user is related to the user. The possible values are: • 1 = Yes in this case, the possibility that the user has to manage an application depends on the area profile to which he is related • 0 = No (default value).	No	
COD_PROFILO_AREA	varchar(255)	No	User's parent group. It has to match the user code if the user is a "Area profile " and if this field is defined.	No	
LINGUA_CAPTION	varchar(2)	Yes	Language in which the application (menu items, headers, management fields, message texts) is present-ed. If the language is not available, then the application is presented in the **Default Application lan-guage** . When creating a new user, this field is predefined by the application with the value of the **Default for User wizard**: Application language field present in the Localization area of the Repository's configuration. If the fields is undefined, the default value is English	No	
FLAG_VISUALIZZAZIONE_SIMBOLICA	numeric(1)	No	Allows the user to configure the symbols set that Tagetik uses in the displaying the indicators of different windows (for example, to highlight the unbalanced amounts in the edit data windows, the existence of overridden amounts in the management window of some tables or to understand / manage the relationship status in the IC matching relationship). The possible values are: • 1= Yes in this case the indicators used are black and white where the form is important • 0 = No (default values) in this case the indicators used are symbols with the same form in which the color	No	

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
			important		
LINGUA_CAPTION_DEFAULT	varchar(2)	Yes	Language in which the application (menu items, headers, management fields, message texts) is presented. Therefore in order to decide in which language to present the application, the system checks if a default application language is available using the following rule: • if the default language is not available, it presents the application in English; • if English is also not available, then it presents the application in Italian.	No	
DATA_INIZIO	datetime(8)	No	**START DATE** Date from which the user can no longer access the application databases that are visible to him. If the login data is before the validity start date, the system does not make visible the application databases on which the user is assigned roles. If it is not defined, the user can access an application database immediately after his is assigned a role on it, on the condition that the Locked temporarily option is disabled.	No	
DATA_FINE	datetime(8)	No	Data from which the user can no longer access the application databases that are visible to him. If the login data is after the validity end date, the system does not make visible the application databases on which the user is assigned roles. If it is not defined, the user can access an application database immediately after his is assigned a role on it, on the condition that the Locked temporarily option is disabled.	No	
GIVENNAME	varchar(710)	No	User name	No	
SURNAME	varchar(710)	No	User family name	No	
COMPANY	varchar(710)	No	Company name	No	
DEPARTMENT	varchar(710)	No	Department name	No	
FLAG_ELIMINATO	varchar(1)	Yes	the user has to be removed and therefore he cannot access the application and has no roles and restrictions	No	
UI_TYPE	varchar(1)	Yes	[TODO: fwk.datamodel.REP_UTENTE.UI_TYPE]	No	
TRIAL_MODE_INFO_OLD_UI	datetime(8)	No	[TODO: fwk.datamodel.REP_UTENTE.TRIAL_MODE_INFO_OLD_UI]	No	
TDL_WARNING_INFO	datetime(8)	No	[TODO: fwk.datamodel.REP_UTENTE.TDL_WARNING_INFO]	No	

Table name: **REP_UTENTE_RIFERIMENTO**
Contains the users relationships.
A user can inherit the roles from one or more users (reference users).
The content of this table is taken into account only for the users who have the FLAG_EREDITA_RUOLO_DB enabled.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_UTENTE	varchar(255)	Yes	Code of the user who inherits the roles from the reference user	Yes	REP_UTENTE
COD_UTENTE_RIFERIMENTO	varchar(255)	Yes	Reference user’s code	Yes	REP_UTENTE

Table name: **REP_UTENTE_DB**
The table contains the list of databases on which the user may work and for each database it specifies whether or not the access is blocked

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_UTENTE	varchar(255)	Yes	COD_UTENTE	Yes	REP_UTENTE
COD_DB	varchar(50)	Yes	COD_DB	Yes	REP_DB
FLAG_BLOCCATO	numeric(1)	No	1=blocked user. A blocked user cannot access the db The block is manual.	No	
DATA_INIZIO	datetime(8)	No	Validity start date for the db access	No	
DATA_FINE	datetime(8)	No	Validity end date for the db access	No	
FLAG_MULTI_RUOLO	numeric(1)	Yes	Flag that specifies if more than one role is related to the db	No	
FLAG_ALLINEA_NO_LIM	varchar(1)	Yes	FLA_ALLINEA_NO_LIMIT	No	

Table name: **REP_UTENTE_DB_RUOLO**
Use the **Users/roles relationships** window to define the list of databases on which the user may work and for each database contextually

assign a role in order to specify the list of activities the user can perform (set of visible menus).

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_UTENTE	varchar(255)	Yes	User code	Yes	REP_UTENTE
COD_DB	varchar(50)	Yes	Code of the Database that the user can access.	Yes	
COD_RUOLO	varchar(30)	Yes	Role code. The specification of the role with which to access the database is provided in this window only if the user is assigned one unique role for the current database. Otherwise, it is necessary to enable the "Multirole" options and then define the list of roles from the "Details" window menu.	Yes	