Tagetik Data Model

5.3.36.543

Tagetik Data Model

[Abstract](#)
[Metadata tables](#)
[Aggregation criteria](#)
[User Views/Limitations](#)
[Data tables](#)
[Appendix A](#)

Abstract

This document will describe the metadata and data tables contained within the Tagetik database.
When a field begins with “COD_” remember that it stands for the code of the dimension; for example COD_SCENARIO is the code of the scenario (not its description).
When a field begins with “FLAG_” remember that its values are either 0 or 1.
In Tagetik for "Table Language" means the language in which the description of the elements in a multilingual table is presented. Most of the metadata tables are multilingual. In the multilingual tables you can manage up to 4 different languages and the description in the language 0 is always present.
In every table there are the following fields:

- Origin (PROVENIENZA): specifies the data's origin. Records added manually will have 'INPUT_WEB' as origin. For a full list of Origins in Tagetik, see Appendix A
- Userupd (USERUPD): specifies the user who executed the last modification or added a new record;
- Dateupd (DATEUPD): The date on which the last modification was executed or a new record added. This fields are always managed by the system

In this document, the table fields considered not relevant for the purpose of reporting have been omitted.

Metadata tables

Table name: **PERIODO**
PERIODO
The period represents the method of dividing a fiscal year into periods of time. Normally, a period represents a month, a quarter or half a year

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_PERIODO	varchar(2)	Yes	Period code. Possible values are 01...13. There is also the possibility to manage these periods starting from an arbitrary month (for example by setting 01 for June)	Yes	
DESC_PERIODO0	varchar(80)	No	Table languages 0: description of the period	No	
DESC_PERIODO1	varchar(80)	No	Table languages 1:description of the period	No	
DESC_PERIODO2	varchar(80)	No	Table languages 2: description of the period	No	
DESC_PERIODO3	varchar(80)	No	Table languages 3: description of the period	No	
DESC_MESE0	varchar(80)	No	Table languages 0: Description of period used in reporting monthly values	No	
DESC_MESE1	varchar(80)	No	Table languages 1: Description of period used in reporting monthly values	No	
DESC_MESE2	varchar(80)	No	Table languages 2: Description of period used in reporting monthly values	No	
DESC_MESE3	varchar(80)	No	Table languages 3: Description of period used in reporting monthly values	No	
DESC_TRIMESTRE0	varchar(80)	No	Table languages 0: Description of period used in reporting quarterly values	No	
DESC_TRIMESTRE1	varchar(80)	No	Table languages 1: Description of period used in reporting quarterly values	No	
DESC_TRIMESTRE2	varchar(80)	No	Table languages 2: Description of period used in reporting quarterly values	No	
DESC_TRIMESTRE3	varchar(80)	No	Table languages 3: Description of period used in reporting quarterly values	No	
DESC_QUADRIMESTRE0	varchar(80)	No	Table languages 0: Description of period used in reporting four-month values	No	
DESC_QUADRIMESTRE1	varchar(80)	No	Table languages 1: Description of period used in reporting four-month values	No	
DESC_QUADRIMESTRE2	varchar(80)	No	Table languages 2: Description of period used in reporting four-month values	No	
DESC_QUADRIMESTRE3	varchar(80)	No	Table languages 3: Description of period used in reporting four-month values	No	
DESC_SEMESTRE0	varchar(80)	No	Table language 0: Description of period used in reporting half year values	No	
DESC_SEMESTRE1	varchar(80)	No	Table language 1: Description of period used in reporting half year values	No	
DESC_SEMESTRE2	varchar(80)	No	Table language 2: Description of period used in reporting half year values	No	
DESC_SEMESTRE3	varchar(80)	No	Table language 3: Description of period used in reporting half year values	No	
DESC_NUM_PERIODO	varchar(5)	No	**DESC_NUM_PERIODO** This is a non-codified free attribute, that can be used by reporting. This attribute is particularly useful when there is alternating management of periods with respect to the calendar months. If, for example the period with 01 code is April in this field, then it is possible to insert 04.	No	

Table name: **SCENARIO**
SCENARIO
This table contains all the working scenarios. There are two different kinds of scenarios:

- Original scenario: includes these two concepts: fiscal year and data versions. For example, we could have:

- a 2008ACT scenario to specify the 2008 fiscal year actual figures
- a 2009B1 scenario to specify the first version of the 2009 fiscal year budget
- a 2009F6 scenario to specify the 2009 fiscal year forecast done after closing the month of June

The original scenario is the scenario in which all the data are entered: amounts, preconsolidation and consolidation adjustments.

- Consolidation scenario: Represents the scenario on which the system performs the consolidation data processing. A consolidation scenario is related to an original scenario and is defined using a Scope of consolidation. In this scenario the "consolidated" data are memorized and cannot be modified manually

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO	varchar(15)	Yes	Scenario code	Yes	
TIPO_SCENARIO	varchar(1)	No	**TIPO_SCENARIO** Type of scenario. Possible values are: • O (original) • C (consolidation)	No	
COD_SCENARIO_ORIGINARIO	varchar(15)	No	**COD_SCENARIO_ORIGINARIO** Represents the original scenario related to the consolidation scenario. Only for "consolidation" scenarios.	No	SCENARIO
DESC_SCENARIO	varchar(200)	No	Scenario description	No	
COD_SCENARIO_PREC	varchar(15)	No	Previous scenario code	No	SCENARIO
COD_SCENARIO_SUCC	varchar(15)	No	Following scenario code	No	SCENARIO
COD_SCENARIO_RIF1	varchar(15)	No	Reference scenario 1: This scenario can be used in reporting, for example to indicate the budget data or the forecast data related to the actual data; its usage is optional.	No	SCENARIO
COD_SCENARIO_RIF2	varchar(15)	No	Reference scenario 2: This scenario can be used in reporting, for example to indicate the budget data or the forecast data related to the actual data; its usage is optional.	No	SCENARIO
COD_SCENARIO_RIF3	varchar(15)	No	Reference scenario 3: This scenario can be used in reporting, for example to indicate the budget data or the forecast data related to the actual data; its usage is optional.	No	SCENARIO
COD_SCENARIO_RIF4	varchar(15)	No	Reference scenario 4: This scenario can be used in reporting, for example to indicate the budget data or the forecast data related to the actual data; its usage is optional.	No	SCENARIO
COD_SCENARIO_RIF5	varchar(15)	No	Reference scenario 5: This scenario can be used in reporting, for example to indicate the budget data or the forecast data related to the actual data; its usage is optional.	No	SCENARIO
COD_AZI_CAPOGRUPPO	varchar(30)	No	**COD_AZI_CAPOGRUPPO** The code of the Holding Entity of the consolidation. Only for "consolidation" scenarios	No	AZIENDA
COD_VALUTA	varchar(5)	No	**COD_VALUTA** The code of the currency the consolidation should be calculated in. Only for "consolidation" scenarios	No	VALUTA
COD_CATEGORIA_GERARCHIA	varchar(2)	No	**COD_CATEGORIA_GERARCHIA** Category grouping. This field always is set to '$' Only for "consolidation" scenarios	No	CATEGORIA_GERARCHIA
COD_CATEGORIA_ELEGER	varchar(30)	No	**COD_CATEGORIA_ELEGER** Code of the category grouping node that specifies the filter on the categories to load onto the consolidation scenario. Only for "consolidation" scenarios.	No	CATEGORIA_GERARCHIA
FLAG_ATTIVO	numeric(1)	No	Specifies if the scenario contains data that is not relevant but the user does not want to delete. This information does not affect locked data.	No	
COD_ESERCIZIO	varchar(15)	No	**COD_ESERCIZIO** Free non codified attribute. Permits the display of the fiscal year to which the scenario refers. Only for "original" scenarios.	No	
DESC_VERSIONE	varchar(200)	No	Free non-codified attribute. Permits the display of the version to which the scenario refers	No	
COD_SCENARIO_RIF_CAMBI	varchar(15)	No	**COD_SCENARIO_RIF_CAMBI** Only for Consolidation scenarios Specifies the original scenario for reading exchange rates in the conversion step.	No	SCENARIO
COD_CONTO_GERARCHIA	varchar(5)	No	**COD_CONTO_GERARCHIA** Account grouping. This field always is set to '$' Only for "consolidation" scenarios	No	CONTO_GERARCHIA
COD_CONTO_ELEGER	varchar(30)	No	**COD_CONTO_ELEGER** Code of the account grouping node that specifies the	No	CONTO_GERARCHIA

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
			filter on the accounts to load onto the consolidation scenario. Only for "consolidation" scenarios.		
ATTRIBUTO1	varchar(2000)	No	**ATTRIBUTO1** Attribute 1: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_SCENARIO'. By assigning the name, the system manages the attribute	No	
ATTRIBUTO2	varchar(2000)	No	**ATTRIBUTO2** Attribute 2: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_SCENARIO'. By assigning the name, the system manages the attribute	No	
ATTRIBUTO3	varchar(2000)	No	**ATTRIBUTO3** Attribute 3: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_SCENARIO'. By assigning the name, the system manages the attribute	No	
ATTRIBUTO4	varchar(2000)	No	**ATTRIBUTO4** Attribute 4: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_SCENARIO'. By assigning the name, the system manages the attribute	No	
ATTRIBUTO5	varchar(2000)	No	**ATTRIBUTO5** Attribute 5: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_SCENARIO'. By assigning the name, the system manages the attribute	No	
ATTRIBUTO6	varchar(2000)	No	**ATTRIBUTO6** Attribute 6: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_SCENARIO'. By assigning the name, the system manages the attribute	No	
ATTRIBUTO7	varchar(2000)	No	**ATTRIBUTO7** Attribute 7: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_SCENARIO'. By assigning the name, the system manages the attribute	No	
ATTRIBUTO8	varchar(2000)	No	**ATTRIBUTO8** Attribute 8: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the	No	

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
			COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_SCENARIO'. By assigning the name, the system manages the attribute		
ATTRIBUTO9	varchar(2000)	No	**ATTRIBUTO9** Attribute 9: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_SCENARIO'. By assigning the name, the system manages the attribute	No	
ATTRIBUTO10	varchar(2000)	No	**ATTRIBUTO10** Attribute 10: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_SCENARIO'. By assigning the name, the system manages the attribute	No	

Table name: **SCENARIO_PERIODO**
This table contains all the working periods for a specific scenario.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO	varchar(15)	Yes	Scenario code	Yes	SCENARIO
COD_PERIODO	varchar(2)	Yes	Period code	Yes	PERIODO
TIPO_SCENARIO	varchar(1)	No	**TIPO_SCENARIO** Type of scenario Possible values are: • O (original) • C (consolidation)	No	
DATA_INIZIO	datetime(8)	No	Starting date of period.	No	
DATA_FINE	datetime(8)	No	Ending date of period	No	
FLAG_BLOCCATO	numeric(1)	No	Specifies if the scenario/period is blocked.	No	
COD_RACCOLTA	varchar(15)	No	**COD_RACCOLTA** Process related to the scenario/period. Only for "original" scenarios.	No	RACCOLTA
FLAG_STORICIZZATO	numeric(1)	No	Specifies if the data related to the Scenario/Period has been archived	No	

Table name: **CATEGORIA**
This table contains all the categories used to classify the data and, in particular, the adjustments

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_CATEGORIA	varchar(30)	Yes	Category code	Yes	
DESC_CATEGORIA0	varchar(330)	No	Table languages 0: category description	No	
DESC_CATEGORIA1	varchar(330)	No	Table languages 1: category description	No	
DESC_CATEGORIA2	varchar(330)	No	Table languages 2: category description	No	
DESC_CATEGORIA3	varchar(330)	No	Table languages 3: category description	No	
FLAG_FIGLIA	numeric(1)	No	This category is always processed and diagnosed together with its reference category.	No	
TIPO_CATEGORIA	varchar(2)	No	**TIPO_CATEGORIA** Category type. Possible values are: • SA (Amount) • RP (Preconsolidation adjustment) • RC (Consolidation adjustment)	No	
FLAG_CONTRIBUTOR	numeric(1)	No	Specifies if the category is managed by the contributor or only by the consolidator	No	
COD_CATEGORIA_RIF	varchar(30)	No	It is a reference category of the child categories (flag_figlia=true).	No	CATEGORIA
FLAG_SALDO_RETTIFICA	numeric(1)	No	Specifies if the category, that technically is an Amount category, has to be processed as a Adjustment category	No	
FLAG_ELABORAZIONE	numeric(1)	Yes	Specifies if the category has to be processed	No	
FLAG_PERIODICO	numeric(1)	No	Specifies if the journal has to be managed in periodic mode.	No	

Table name: **VALUTA**
This table contains all the currencies

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_VALUTA	varchar(5)	Yes	Currency code	Yes	
DESC_VALUTA	varchar(200)	No	Currency description	No	
COD_VALUTA1	varchar(5)	No	Alternative code 1 of the currency	No	
COD_VALUTA2	varchar(5)	No	Alternative code 2 of the currency	No	
NUM_DECIMALI	numeric(1)	No	Number of decimal. Possible values are 0, 1, 2, 3	No	
COD_VALUTA_RIF	varchar(5)	No	Reference currency in case of a derived currency: to use for example a different unit of measurement or even simply a different decimal number	No	VALUTA
COEFFICIENTE_RIF	numeric(22)	No	Transformation Coefficient for changing from one currency to its derived currency.	No	

Table name: **AZIENDA**

AZIENDA

This table contains the "entity".

The Entity dimension in Tagetik can be used to represent the Legal Entity (since the legal structure is represented through relationships between "Entities") and/or to identify, the Entities to submit in a data collection process. In general:

- in case of having to operate a consolidation process, the Entity or a "part" of the Entity should be added to the Entity dimension
- otherwise, the list of Entities to submit can be added on the Entity dimension

The name of this dimension is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = ‘NOME_AZIENDA’.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_AZIENDA	varchar(30)	Yes	Entity code	Yes	
RAGIONE_SOCIALE	varchar(600)	No	Business name	No	
FLAG_AZIENDA	numeric(1)	No	**FLAG_AZIENDA** Tells if the entity it is a division or a real legal entity. Possible values are: • 1 the entity is a real legal entity • 0 the entity is a division	No	
SEDE_LEGALE	varchar(330)	No	The legal headquarters	No	
SEDE_AMMINISTRATIVA	varchar(330)	No	The administrative city	No	
DATA_COSTITUZIONE	datetime(8)	No	The establishment date	No	
TIPO_CONSOLIDAMENTO	varchar(1)	No	**TIPO_CONSOLIDAMENTO** Consolidation type. Possible values are: • I (Line by line) • P (Proportional) • C (Cost) • E (Equity)	No	
PERC_PROPORZIONALE	numeric(15)	No	% proportionality	No	
COD_VALUTA	varchar(5)	No	Currency code	No	VALUTA
EMAIL	varchar(150)	No	Reference e-mail address	No	
TELEFONO	varchar(128)	No	Reference phone number	No	
RESPONSABILE	varchar(330)	No	The person in charge of the management	No	
DATA_INIZIO	datetime(8)	No	Entity validity starting date	No	
DATA_FINE	datetime(8)	No	Entity validity ending date	No	
FLAG_SOLO_CTP	numeric(1)	No	If set, this entity can be admitted only as a counterpart in an intercompany declaration	No	
COD_DEST1_AUT	varchar(30)	No	The default Custom Dimension element used by the system if the Custom Dimension is not managed on adjustments.	No	DEST1
COD_DEST2_AUT	varchar(30)	No	The default Custom Dimension element used by the system if the Custom Dimension is not managed on adjustments.	No	DEST2
COD_DEST3_AUT	varchar(30)	No	The default Custom Dimension element used by the system if the Custom Dimension is not managed on adjustments.	No	DEST3
COD_DEST4_AUT	varchar(30)	No	The default Custom Dimension element used by the system if the Custom Dimension is not managed on adjustments.	No	DEST4
COD_DEST5_AUT	varchar(30)	No	The default Custom Dimension element used by the system if the Custom Dimension is not managed on adjustments.	No	DEST5
ATTRIBUTO1	varchar(2000)	No	Attribute 1: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = ‘NOME_ATTRIBUTO1_AZIENDA’. By assigning the name, the system manages the attribute.	No	
ATTRIBUTO2	varchar(2000)	No	Attribute 2: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = ‘NOME_ATTRIBUTO2_AZIENDA’. By assigning the name, the system manages the attribute.	No	

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
ATTRIBUTO3	varchar(2000)	No	Attribute 3: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO3_AZIENDA'. By assigning the name, the system manages the attribute.	No	
ATTRIBUTO4	varchar(2000)	No	Attribute 4: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc.The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO4_AZIENDA'.By assigning the name, the system manages the attribute.	No	
ATTRIBUTO5	varchar(2000)	No	**ATTRIBUTO5** Attribute 5: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_AZIENDA'. By assigning the name, the system manages the attribute.	No	
DATA_CESSIONE	datetime(8)	No	Entity Assignment date	No	
DESC_AZIENDA0	varchar(2000)	No	Table language 0: Entity Description	No	
DESC_AZIENDA1	varchar(2000)	No	**DESC_AZIENDA1** Table language 1: Entity Description. This field is managed only in the CONFIGURAZIONE table, the value of the 'CAMPO_NUMERO' field corresponds to COD_INFORMAZIONE = 'TRANSLATE_DESCRIPTION_AZIENDA' is equal to 1. Otherwise, this field is always equal to DESC_AZIENDA0.	No	
DESC_AZIENDA2	varchar(2000)	No	**DESC_AZIENDA2** Table language 2: Entity Description. This field is managed only in the CONFIGURAZIONE table, the value of the 'CAMPO_NUMERO' field corresponds to COD_INFORMAZIONE = 'TRANSLATE_DESCRIPTION_AZIENDA' is equal to 1. Otherwise, this field is always equal to DESC_AZIENDA0.	No	
DESC_AZIENDA3	varchar(2000)	No	**DESC_AZIENDA3** Table language 3: Entity Description. This field is managed only in the CONFIGURAZIONE table, the value of the 'CAMPO_NUMERO' field corresponds to COD_INFORMAZIONE = 'TRANSLATE_DESCRIPTION_AZIENDA' is equal to 1. Otherwise, this field is always equal to DESC_AZIENDA0.	No	
COD2_AZIENDA	varchar(30)	No	Other entity code	No	
FLAG_SOLO_CONSOLIDATORE	numeric(1)	No	It is used to specify if on an Entity the user can insert all the data types or only data on the Consolidator's categories.	No	
TIPO_DECONSOLIDAMENTO	varchar(1)	No	**TIPO_DECONSOLIDAMENTO** • 0 = Not to deconsolidate • 1 = Deconsolidate only initial balances • 2 = Deconsolidate from previous period (the system reproposes the P&L and Variations account by the previous period of the same scenario) • 3 = Deconsolidate from current period	No	

Table name: **DEST1**

DEST1

Tagetik allows defining and managing up to five physical dimensions to support the specific characteristics of the business model. They could represent products, customers, cost centers…
For each of them, it is possible to define an unlimited number of logical and independent elements.
The name of the custom dimension is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_DEST1' .
By assigning the name, the system manages the custom dimension.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_DEST1	varchar(30)	Yes	Custom dimension element code	Yes	
DESC_DEST10	varchar(330)	No	Table languages 0: element description	No	
DESC_DEST11	varchar(330)	No	Table languages 1: element description	No	
DESC_DEST12	varchar(330)	No	Table languages 2: element description	No	
DESC_DEST13	varchar(330)	No	Table languages 3: element description	No	
ATTRIBUTO1	varchar(330)	No	**ATTRIBUTO1** Attribute 1: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_DEST1'. By assigning the name, system manages the attribute.	No	
ATTRIBUTO2	varchar(330)	No	**ATTRIBUTO2** Attribute 2: this is a free non-coded attribute that could be used in reporting for specific	No	

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
			classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO2_DEST1'. By assigning the name, system manages the attribute.		
ATTRIBUTO3	varchar(330)	No	**ATTRIBUTO3** Attribute 3: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO3_DEST1'. By assigning the name, system manages the attribute.	No	
ATTRIBUTO4	varchar(330)	No	**ATTRIBUTO4** Attribute 4: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO4_DEST1'. By assigning the name, system manages the attribute.	No	
ATTRIBUTO5	varchar(330)	No	**ATTRIBUTO5** Attribute 5: this is a free non-coded attribute that could be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO5_DEST1'. By assigning the name, system manages the attribute.	No	
DATA_FINE	datetime(8)	No	**DATA_FINE** This information is utilized by the system when determining Custom dimensions 1 belonging to a process since the system only proposes the custom dimensions 1 that are valid for the time space determined by the target scenarios / periods.	No	
DATA_INIZIO	datetime(8)	No	**DATA_INIZIO** This information is utilized by the system when determining Custom dimensions 1 belonging to a process since the system only proposes the custom dimensions 1 that are valid for the time space determined by the target scenarios / periods.	No	

Table name: **CONTO**
This table contains the accounts with their properties.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_CONTO	varchar(30)	Yes	Account code	Yes	
DESC_CONTO0	varchar(2000)	No	Table languages 0: account description	No	
DESC_CONTO1	varchar(2000)	No	Table languages 1: account description	No	
DESC_CONTO2	varchar(2000)	No	Table languages 2: account description	No	
DESC_CONTO3	varchar(2000)	No	Table languages 3: account description	No	
DESC2_CONTO0	varchar(600)	No	Table languages 0: alternative account description	No	
DESC2_CONTO1	varchar(600)	No	Table languages 1: alternative account description	No	
DESC2_CONTO2	varchar(600)	No	Table languages 2: alternative account description	No	
DESC2_CONTO3	varchar(600)	No	Table languages 3: alternative account description	No	
NATURA_CONTO	varchar(1)	No	**NATURA_CONTO** Account nature. Possible values are: • E (Profit & Loss) • P (Balance sheet) • O(Guaranties & Commitments) • A (Other Variations - typically statistical Accounts referred to "Profit & Loss" quantities) • B (Other Stock – typically statistical accounts referred to "Balance sheet" quantities) • F (Financial Planning)	No	
TIPO_CONTO	varchar(1)	No	Account type. Possible values are: • N (Normal) • D (Detail) • F (Variation)	No	
TIPO_CONVERSIONE	varchar(1)	No	**TIPO_CONVERSIONE** Exchange type to use for any conversion. Possible values are: • 0 (None) • 1 (Final exchange rate) • 2 (Profit & Loss exchange rate) • 3 (Previous Final exchange rate) • 4 (Previous Profit & Loss exchange rate) • 5 (Historical Exchange Rate) • 6 (Average FX rate) • 7 (Period average FX rate)	No	

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
			• B (Initial balance exchange rates) • C (Incremental exchange rate)		
FLAG_IC	numeric(1)	No	Specifies if the Account manages the intercompany values or not. Possible values are: • 1 (Yes: the Account can have both intercompany and gross amounts) • 0 (No: the Account cannot have intercompany values)	No	
ATTRIBUTO1	varchar(330)	No	**ATTRIBUTO1** Attribute 1: this is a free non-coded attribute that can be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO1_CONTO'. By assigning the name, system manages the attribute.	No	
ATTRIBUTO2	varchar(330)	No	**ATTRIBUTO2** Attribute 2: this is a free non-coded attribute that can be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO2_CONTO'. By assigning the name, system manages the attribute.	No	
ATTRIBUTO3	varchar(330)	No	**ATTRIBUTO3** Attribute 3: this is a free non-coded attribute that can be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE='NOME_ATTRIBUTO3_CONTO' By assigning the name, system manages the attribute.	No	
ATTRIBUTO4	varchar(330)	No	**ATTRIBUTO4** Attribute 4: this is a free non-coded attribute that can be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO4_CONTO'. By assigning the name, system manages the attribute.	No	
ATTRIBUTO5	varchar(330)	No	**ATTRIBUTO5** Attribute 5: this is a free non-coded attribute that can be used in reporting for specific classifications, conditional formatting, etc. The name of the attribute is specified in the CONFIGURAZIONE table and corresponds to the COD_INFORMAZIONE = 'NOME_ATTRIBUTO5_CONTO'. By assigning the name, system manages the attribute.	No	
COD_CONTO_RATEO_DARE	varchar(30)	No	Account used for generating the counterparty entry for the P&L rows inserted manually	No	CONTO
COD_CONTO_RATEO_AVERE	varchar(30)	No	Account used for generating the counterparty exit for the P&L rows inserted manually	No	CONTO
TIPO_PARAMETRIZZAZIONE	varchar(1)	No	**TIPO_PARAMETRIZZAZIONE** Specifies if the account is used in the parameterization of the financial investments and equity accounts. Possible values are: • X (None) • P (Legal structure) • N (Net Equity)	No	
DATA_INIZIO	datetime(8)	No	Account validity starting date	No	
DATA_FINE	datetime(8)	No	Account validity ending date	No	
FLAG_NUM_MAX_DECIMALE	smallint(2)	Yes	Specifies if the user can perform an edit with 9 decimals on the Other stock or Other variation account.	No	
FLAG_VALUTA_TRANSAZIONE	smallint(2)	Yes	**FLAG_VALUTA_TRANSAZIONE** Specifies if the Account manages the transaction currency or not. Possible values are: • 1 (Yes: the Account can have both intercompany and gross amounts) • 0 (No: the Account cannot have intercompany values)	No	

Aggregation criteria

Tagetik defines a set of Aggregation Criteria used to group dimensions in different ways in order to facilitate their management.

- **Grouping** : with the word "Grouping" Tagetik defines an aggregation structure with the following features:
  - **Multilevel**: the group is composed of more than one level. For each level there is more than one element
  - **Multi-parent**: an element can be referred to more than one parent
  - **Single and only**: there can be only one group

- **Hierarchy**: with the word "Hierarchy" Tagetik defines an aggregation structure with the following features:
  - **Multilevel**: the group is composed of more than one level. For each level, there is more than one element
  - **Single - parent**: an element can be referred only to one parent
  - **Can be more than one:** more than one hierarchy can be created

Hierarchy is used to aggregate entities, accounts and custom dimensions.

Only the accounts support another type of aggregation structure, which is the Financial Statement Template.

Scenario - Grouping
Table name: **SCENARIO_GERARCHIA**
This table contains the definition of the structure of the grouping.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO_GERARCHIA	varchar(2)	Yes	Scenario grouping code. This field always is set to '$'.	Yes	
COD_SCENARIO_ELEGER	varchar(30)	Yes	Node code	Yes	
TIPO_SCENARIO_ELEGER	varchar(1)	No	**TIPO_SCENARIO_ELEGER** Node type. Possible values are: • R (the node is the Root node of the grouping) • N (the node is a generic node of the grouping)	No	
COD_SCENARIO_GERARCHIA_PADRE	varchar(2)	No	Grouping code of the parent node (must be the same to COD_SCENARIO_GERARCHIA).	No	
COD_SCENARIO_ELEGER_PADRE	varchar(30)	No	Parent node code	No	
DESC_SCENARIO_ELEGER0	varchar(330)	No	Table languages 0: node description	No	
DESC_SCENARIO_ELEGER1	varchar(330)	No	Table languages 1: node description	No	
DESC_SCENARIO_ELEGER2	varchar(330)	No	Table languages 2: node description	No	
DESC_SCENARIO_ELEGER3	varchar(330)	No	Table languages 3: node description	No	

Table name: **SCENARIO_GERARCHIA_ABBIM**
This table contains the relationships between scenarios and the first level parent grouping's node

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO	varchar(15)	Yes	Scenario code	Yes	SCENARIO
COD_SCENARIO_GERARCHIA	varchar(2)	Yes	Scenario grouping code. This field always is set to '$'	Yes	SCENARIO_GERARCHIA
COD_SCENARIO_ELEGER	varchar(30)	Yes	Node code	Yes	SCENARIO_GERARCHIA

Category - Grouping
Table name: **CATEGORIA_GERARCHIA**
This table contains the definition of the structure of the grouping.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_CATEGORIA_GERARCHIA	varchar(2)	Yes	Category grouping code. This field always is set to '$'	Yes	
COD_CATEGORIA_ELEGER	varchar(30)	Yes	Node code	Yes	
COD_CATEGORIA_GERARCHIA_PADRE	varchar(2)	No	Grouping code of the parent node (must be the same to COD_CATEGORIA_GERARCHIA)	No	CATEGORIA_GERARCHIA
COD_CATEGORIA_ELEGER_PADRE	varchar(30)	No	Parent node code	No	CATEGORIA_GERARCHIA
FLAG_GENERA_FLAT	numeric(1)	No	Specifies if the flat structure has to be kept aligned.	No	
DESC_CATEGORIA_ELEGER0	varchar(330)	No	Grouping code of the parent node (must be the same to COD_CATEGORIA_GERARCHIA)	No	
DESC_CATEGORIA_ELEGER1	varchar(330)	No	node description	No	
DESC_CATEGORIA_ELEGER2	varchar(330)	No	Table languages 2: node description	No	
DESC_CATEGORIA_ELEGER3	varchar(330)	No	Table languages 3: node description	No	

Table name: **CATEGORIA_GERARCHIA_ABBIM**
This table contains the relationships between categories and the first level parent grouping's node

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_CATEGORIA	varchar(30)	Yes	Category code	Yes	CATEGORIA
COD_CATEGORIA_GERARCHIA	varchar(2)	Yes	Category grouping code. This field always is set to '$'	Yes	CATEGORIA_GERARCHIA
COD_CATEGORIA_ELEGER	varchar(30)	Yes	Node code	Yes	CATEGORIA_GERARCHIA

Table name: **CATEGORIA_GERARCHIA_FLAT**
CATEGORIA_GERARCHIA_FLAT
This table contains the flat grouping table corresponding to the two table above.
This table is the result of transformation performed by the system: the original structure now appears in a horizontal way, a flat way (before was vertical).
This table is full only if for the category grouping is specified that the flat structure has to be kept aligned (CATEGORIA_GERARCHIA.FLAG_GENERA_FLAT = 1)
The root is always added to Node 8 and as a result some of the initial fields may remain empty.

Column Name	Data Type	Mandatory	Comment	PK	Ta
COD_CATEGORIA	varchar(30)	No	Category code	No	CA
DESC_CATEGORIA0	varchar(330)	No	Table languages 0: category description	No	
DESC_CATEGORIA1	varchar(330)	No	Table languages 1: category description	No	
DESC_CATEGORIA2	varchar(330)	No	Table languages 2: category description	No	
DESC_CATEGORIA3	varchar(330)	No	Table languages 3: category description	No	
COD_CATEGORIA_GERARCHIA	varchar(2)	No	Category grouping code. This field always is set to '$'.	No	
COD_CATEGORIA_ELEGER1	varchar(30)	No	Category code	No	
DESC_CATEGORIA_ELEGER1	varchar(330)	No	[TODO: cpm.datamodelxml.CATEGORIA_GERARCHIA_FLAT.DESC_CATEGORIA_ELEGER1]	No	
COD_CATEGORIA_ELEGER2	varchar(30)	No	Node code	No	
DESC_CATEGORIA_ELEGER2	varchar(330)	No	Node description	No	
COD_CATEGORIA_ELEGER3	varchar(30)	No	Node code	No	
DESC_CATEGORIA_ELEGER3	varchar(330)	No	Node description	No	
COD_CATEGORIA_ELEGER4	varchar(30)	No	Node code	No	
DESC_CATEGORIA_ELEGER4	varchar(330)	No	Node description	No	
COD_CATEGORIA_ELEGER5	varchar(30)	No	Node code	No	
DESC_CATEGORIA_ELEGER5	varchar(330)	No	Node description	No	
COD_CATEGORIA_ELEGER6	varchar(30)	No	Node code	No	
DESC_CATEGORIA_ELEGER6	varchar(330)	No	Node description	No	
COD_CATEGORIA_ELEGER7	varchar(30)	No	Node code	No	
DESC_CATEGORIA_ELEGER7	varchar(330)	No	Node description	No	
COD_CATEGORIA_ELEGER8	varchar(30)	No	Node code	No	
DESC_CATEGORIA_ELEGER8	varchar(330)	No	Node description	No	

Entity - Hierarchy
Table name: **AZIENDA_GERARCHIA**
This table contains the definition of the structure of the hierarchy.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_AZIENDA_GERARCHIA	varchar(5)	Yes	Entity hierarchy code	Yes	
COD_AZIENDA_ELEGER	varchar(30)	Yes	Node code	Yes	
TIPO_AZIENDA_ELEGER	varchar(1)	No	**TIPO_AZIENDA_ELEGER** Node type. Possible values are: • R (the node is the Root node of the hierarchy) • N (the node is a generic node of the hierarchy)	No	
COD_AZIENDA_GERARCHIA_PADRE	varchar(5)	No	hierarchy code of the parent node (must be the same to COD_AZIENDA_GERARCHIA)	No	AZIENDA_GERARCHIA
COD_AZIENDA_ELEGER_PADRE	varchar(30)	No	Parent node code	No	AZIENDA_GERARCHIA
FLAG_ORGANIZZAZIONE	numeric(1)	No	Specifies if the hierarchy is an Organization	No	
FLAG_TV	numeric(1)	No	**FLAG_TV** Specifies if the hierarchy is time dependant. A Hierarchy is defined as time-dependent if the relationship between individual elements of a dimension to the hierarchy nodes is not fixed, but rather depends on the scenario /period.	No	
FLAG_GENERA_FLAT	numeric(1)	No	Specifies if the flat structure has to be kept aligned. Only for non-time dependent hierarchy	No	
DESC_AZIENDA_ELEGER0	varchar(2000)	No	Table languages 0: node description	No	
DESC_AZIENDA_ELEGER1	varchar(2000)	No	Table languages 1: node description	No	
DESC_AZIENDA_ELEGER2	varchar(2000)	No	Table languages 2: node description	No	
DESC_AZIENDA_ELEGER3	varchar(2000)	No	Table languages 3: node description	No	

Table name: **AZIENDA_GERARCHIA_ABBI**
This table contains the relationships between entity and the first level parent node of a non-time dependent hierarchy.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_AZIENDA	varchar(30)	Yes	Entity code	Yes	AZIENDA
COD_AZIENDA_GERARCHIA	varchar(5)	Yes	Entity hierarchy code. Only non-time dependent hierarchy	Yes	AZIENDA_GERARCHIA
COD_AZIENDA_ELEGER	varchar(30)	No	Node code	No	AZIENDA_GERARCHIA

Table name: **AZIENDA_GERARCHIA_ABBI_TV**
This table contains the relationships between entity and the first level parent node of a non-time dependent hierarchy.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_AZIENDA	varchar(30)	Yes	Entity code	Yes	AZIENDA
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active original scenario	Yes	SCENARIO_PERIODO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario	Yes	SCENARIO_PERIODO
COD_AZIENDA_GERARCHIA	varchar(5)	Yes	Entity hierarchy code. Only time dependent hierarchy	Yes	AZIENDA_GERARCHIA
COD_AZIENDA_ELEGER	varchar(30)	No	Node code	No	AZIENDA_GERARCHIA

Table name: **AZIENDA_GERARCHIA_FLAT**
AZIENDA_GERARCHIA_FLAT

This table contains the flat hierarchy table corresponding to the two tables above. This table is the result of transformation performed by the system: the original structure now appears in a horizontal way, a flat way (before it was vertical).

This table is full only if for the hierarchy is specified that the flat structure has to be kept aligned (AZIENDA_GERARCHIA.FLAG_GENERA_FLAT = 1)
The root is always added to Node 8 and as a result some of the initial fields may remain empty

Column Name	Data Type	Mandatory	Comment	PK	Parent Tal
COD_AZIENDA	varchar(30)	No	Entity code	No	AZIENDA
COD_AZIENDA_GERARCHIA	varchar(5)	No	Hierarchy code	No	AZIENDA_G
COD_AZIENDA_ELEGER1	varchar(30)	No	Node code	No	
DESC_AZIENDA_ELEGER1	varchar(2000)	No	Node description	No	
COD_AZIENDA_ELEGER2	varchar(30)	No	Node code	No	
DESC_AZIENDA_ELEGER2	varchar(2000)	No	Node description	No	
COD_AZIENDA_ELEGER3	varchar(30)	No	Node code	No	
DESC_AZIENDA_ELEGER3	varchar(2000)	No	Node description	No	
COD_AZIENDA_ELEGER4	varchar(30)	No	Node code	No	
DESC_AZIENDA_ELEGER4	varchar(2000)	No	Node description	No	
COD_AZIENDA_ELEGER5	varchar(30)	No	Node code	No	AZIENDA_G
DESC_AZIENDA_ELEGER5	varchar(2000)	No	Node description	No	
COD_AZIENDA_ELEGER6	varchar(30)	No	[TODO: cpm.datamodelxml.AZIENDA_GERARCHIA_FLAT.COD_AZIENDA_ELEGER6]	No	
DESC_AZIENDA_ELEGER6	varchar(2000)	No	Node code	No	
COD_AZIENDA_ELEGER7	varchar(30)	No	Node code	No	
DESC_AZIENDA_ELEGER7	varchar(2000)	No	Node description	No	
COD_AZIENDA_ELEGER8	varchar(30)	No	Node code	No	
DESC_AZIENDA_ELEGER8	varchar(2000)	No	Node description	No	
DESC_AZIENDA0	varchar(2000)	No	Table language 0: Entity Description	No	
DESC_AZIENDA1	varchar(2000)	No	**DESC_AZIENDA1** Table language 1: Entity Description. This field is managed only in the CONFIGURAZIONE table, the value of the 'CAMPO_NUMERO' field corresponds to COD_INFORMAZIONE = 'TRANSLATE_DESCRIPTION_AZIENDA' is equal to 1. Otherwise, this field is always equal to DESC_AZIENDA0.	No	
DESC_AZIENDA2	varchar(2000)	No	**DESC_AZIENDA2** Table language 2: Entity Description. This field is managed only in the CONFIGURAZIONE table, the value of the 'CAMPO_NUMERO' field corresponds to COD_INFORMAZIONE = 'TRANSLATE_DESCRIPTION_AZIENDA' is equal to 1. Otherwise, this field is always equal to DESC_AZIENDA0.	No	
DESC_AZIENDA3	varchar(2000)	No	**DESC_AZIENDA3** Table language 3: Entity Description. This field is managed only in the CONFIGURAZIONE table, the value of the 'CAMPO_NUMERO' field corresponds to COD_INFORMAZIONE = 'TRANSLATE_DESCRIPTION_AZIENDA' is equal to 1. Otherwise, this field is always equal to DESC_AZIENDA0.	No	

Custom Dimension - Hierarchy
Table name: **DEST1_GERARCHIA**
This table contains the definition of the structure of the hierarchy

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_DEST1_GERARCHIA	varchar(5)	Yes	Custom dimension 1 hierarchy code	Yes	
COD_DEST1_ELEGER	varchar(30)	Yes	Node code	Yes	
TIPO_DEST1_ELEGER	varchar(1)	No	**TIPO_ELEGER** Node type. Possible values are: • R (the node is the Root node of the hierarchy) • N (the node is a generic node of the hierarchy)	No	
COD_DEST1_GERARCHIA_PADRE	varchar(5)	No	Hierarchy code of the parent node (must be the same to COD_DESTx_GERARCHIA)	No	DEST1_GERARCHIA
COD_DEST1_ELEGER_PADRE	varchar(30)	No	Parent node code	No	DEST1_GERARCHIA
FLAG_TV	numeric(1)	No	**FLAG_TV** Specifies if the hierarchy is time dependant. A Hierarchy is defined as time-dependent if the relationship between individual elements of a dimension to the hierarchy nodes is not fixed, but rather depends on the scenario /period.	No	
FLAG_GENERA_FLAT	numeric(1)	No	Specifies if the flat structure has to be kept aligned. Only for non-time dependent hierarchy.	No	
DESC_DEST1_ELEGER0	varchar(330)	No	Table languages 0: node description	No	
DESC_DEST1_ELEGER1	varchar(330)	No	Table languages 1: node description	No	
DESC_DEST1_ELEGER2	varchar(330)	No	Table languages 2: node description	No	
DESC_DEST1_ELEGER3	varchar(330)	No	Table languages 3: node description	No	

Table name: **DEST1_GERARCHIA_ABBI**
Custom dimension element code

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_DEST1	varchar(30)	Yes	Custom dimension element code	Yes	DEST1
COD_DEST1_GERARCHIA	varchar(5)	Yes	Hierarchy code. Only non-time dependent hierarchy	Yes	DEST1_GERARCHIA
COD_DEST1_ELEGER	varchar(30)	No	Node code	No	DEST1_GERARCHIA

Table name: **DEST1_GERARCHIA_ABBI_TV**
This table contains the relationships between custom dimension elements and the first level parent node of a time dependent hierarchy.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_DEST1	varchar(30)	Yes	Custom dimension element code	Yes	DEST1
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active original scenario	Yes	SCENARIO_PERIODO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario.	Yes	SCENARIO_PERIODO
COD_DEST1_GERARCHIA	varchar(5)	Yes	Hierarchy code. Only non-time dependent hierarchy	Yes	DEST1_GERARCHIA
COD_DEST1_ELEGER	varchar(30)	No	Node code	No	DEST1_GERARCHIA

Table name: **DEST1_GERARCHIA_FLAT**
DEST1_GERARCHIA_FLAT
This table contains the flat hierarchy table corresponding to the two tables above.
This table is the result of transformation performed by the system: the original structure now appears in a horizontal way, a flat way (before was vertical).

This table is full only if for the hierarchy is specified that the flat structure has to be kept aligned (DEST1_GERARCHIA.FLAG_GENERA_FLAT = 1)

The root is always added to Node 8 and as a result some of the initial fields may remain empty.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_DEST1	varchar(30)	No	Custom dimension element code	No	DEST1
DESC_DEST10	varchar(330)	No	Table languages 0: Custom dimension element description	No	
DESC_DEST11	varchar(330)	No	Table languages 1: Custom dimension element description	No	
DESC_DEST12	varchar(330)	No	Table languages 2: Custom dimension element description	No	
DESC_DEST13	varchar(330)	No	Table languages 3: Custom dimension element description	No	
COD_DEST1_GERARCHIA	varchar(5)	No	Hierarchy code	No	
COD_DEST1_ELEGER1	varchar(30)	No	Node code	No	
DESC_DEST1_ELEGER1	varchar(330)	No	Node description	No	
COD_DEST1_ELEGER2	varchar(30)	No	Node code	No	
DESC_DEST1_ELEGER2	varchar(330)	No	Node description	No	
COD_DEST1_ELEGER3	varchar(30)	No	Node code	No	
DESC_DEST1_ELEGER3	varchar(330)	No	Node description	No	
COD_DEST1_ELEGER4	varchar(30)	No	Node code	No	
DESC_DEST1_ELEGER4	varchar(330)	No	Node description	No	
COD_DEST1_ELEGER5	varchar(30)	No	Node code	No	
DESC_DEST1_ELEGER5	varchar(330)	No	Node description	No	
COD_DEST1_ELEGER6	varchar(30)	No	Node code	No	
DESC_DEST1_ELEGER6	varchar(330)	No	Node code	No	
COD_DEST1_ELEGER7	varchar(30)	No	Node code	No	
DESC_DEST1_ELEGER7	varchar(330)	No	Node description	No	
COD_DEST1_ELEGER8	varchar(30)	No	Node code	No	
DESC_DEST1_ELEGER8	varchar(330)	No	Node description	No	

Account - Hierarchy
Table name: **CONTO_GERARCHIA**
This table contains the definition of the structure of the hierarchy.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_CONTO_GERARCHIA	varchar(5)	Yes	Account hierarchy code	Yes	
COD_CONTO_ELEGER	varchar(30)	Yes	Node code	Yes	
COD_CONTO_GERARCHIA_PADRE	varchar(5)	No	Hierarchy code of the parent node (must be the same to COD_CONTO_GERARCHIA)	No	CONTO_GERARCHIA
TIPO_CONTO_ELEGER	varchar(1)	No	**TIPO_CONTO_ELEGER** Node type. Possible values are: • R (the node is the Root node of the hierarchy) • N (the node is a generic node of the hierarchy)	No	
COD_CONTO_ELEGER_PADRE	varchar(30)	No	Parent node code	No	CONTO_GERARCHIA
FLAG_GENERA_FLAT	numeric(1)	No	Specifies if the flat structure has to be kept aligned	No	
DESC_CONTO_ELEGER0	varchar(330)	No	Table languages 0: node description	No	
DESC_CONTO_ELEGER1	varchar(330)	No	Table languages 1: node description	No	
DESC_CONTO_ELEGER2	varchar(330)	No	Table languages 2: node description	No	
DESC_CONTO_ELEGER3	varchar(330)	No	Table languages 3: node description	No	

Table name: **CONTO_GERARCHIA_ABBI**
This table contains the relationships between accounts and the first level parent node.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_CONTO	varchar(30)	Yes	Account code	Yes	CONTO
COD_CONTO_GERARCHIA	varchar(5)	Yes	Account hierarchy code	Yes	CONTO_GERARCHIA

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_CONTO_ELEGER	varchar(30)	No	Node code	No	CONTO_GERARCHIA

Table name: **CONTO_GERARCHIA_FLAT**
CONTO_GERARCHIA_FLAT
This table contains the flat hierarchy table corresponding to the two tables above. This table is the result of transformation performed by the system: the original structure now appears in a horizontal way, a flat way (before was vertical).

This table is full only if for the hierarchy is specified that the flat structure has to be kept aligned (CONTO_GERARCHIA.FLAG_GENERA_FLAT = 1)

The root is always added to Node 8 and as a result some of the initial fields may remain empty.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_CONTO	varchar(30)	No	Account code	No	CONTO
DESC_CONTO0	varchar(2000)	No	Table languages 0: account description	No	
DESC_CONTO1	varchar(2000)	No	Table languages 1: account description	No	
DESC_CONTO2	varchar(2000)	No	Table languages 2: account description	No	
DESC_CONTO3	varchar(2000)	No	Table languages 3: account description	No	
COD_CONTO_GERARCHIA	varchar(5)	No	Account hierarchy code	No	
COD_CONTO_ELEGER1	varchar(30)	No	Node code	No	
DESC_CONTO_ELEGER1	varchar(330)	No	Node description	No	
COD_CONTO_ELEGER2	varchar(30)	No	Node code	No	
DESC_CONTO_ELEGER2	varchar(330)	No	Node description	No	
COD_CONTO_ELEGER3	varchar(30)	No	Node code	No	
DESC_CONTO_ELEGER3	varchar(330)	No	Node description	No	
COD_CONTO_ELEGER4	varchar(30)	No	Node code	No	
DESC_CONTO_ELEGER4	varchar(330)	No	Node description	No	
COD_CONTO_ELEGER5	varchar(30)	No	Node code	No	
DESC_CONTO_ELEGER5	varchar(330)	No	Node description	No	
COD_CONTO_ELEGER6	varchar(30)	No	Node code	No	
DESC_CONTO_ELEGER6	varchar(330)	No	Node description	No	
COD_CONTO_ELEGER7	varchar(30)	No	Node code	No	
DESC_CONTO_ELEGER7	varchar(330)	No	Node description	No	
COD_CONTO_ELEGER8	varchar(30)	No	Node code	No	
DESC_CONTO_ELEGER8	varchar(330)	No	Node description	No	

Account - Financial Statement Template
Table name: **VOCE_SCHEMA**
This table contains the list of financial statement templates (F.S.T.).

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCHEMA	varchar(5)	Yes	Financial statement template code	Yes	
DESC_SCHEMA0	varchar(200)	No	Table languages 0: Financial statement template description	No	
DESC_SCHEMA1	varchar(200)	No	Table languages 1: Financial statement template description	No	
DESC_SCHEMA2	varchar(200)	No	Table languages 2: Financial statement template description	No	
DESC_SCHEMA3	varchar(200)	No	Table languages 3: Financial statement template description	No	
FLAG_CONTO	numeric(1)	Yes	Specifies if the FST items will be defined using the Account dimension	No	
FLAG_DEST1	numeric(1)	Yes	Specifies if the FST items will be defined using the Custom dimension 1.	No	
FLAG_DEST2	numeric(1)	Yes	Specifies if the FST items will be defined using the Custom dimension 2.	No	
FLAG_DEST3	numeric(1)	Yes	Specifies if the FST items will be defined using the Custom dimension 3.	No	
FLAG_DEST4	numeric(1)	Yes	Specifies if the FST items will be defined using the Custom dimension 4.	No	
FLAG_DEST5	numeric(1)	Yes	Specifies if the FST items will be defined using the Custom dimension 5.	No	
FLAG_ABBINAMENTO_MULTIPLO	numeric(1)	Yes	Specifies that the dimension can be related to more than one FST item	No	

Table name: **VOCE**
This table contains the F.S.T. lines

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCHEMA	varchar(5)	Yes	F.S.T. code	Yes	VOCE_SCHEMA
COD_VOCE	varchar(30)	Yes	F.S.T. line code	Yes	
DESC_VOCE0	varchar(2000)	No	Table languages 0: F.S.T. line description	No	
DESC_VOCE1	varchar(2000)	No	Table languages 1: F.S.T. line description	No	
DESC_VOCE2	varchar(2000)	No	Table languages 2: F.S.T. line description	No	
DESC_VOCE3	varchar(2000)	No	Table languages 3: F.S.T. line description	No	
TIPO_VOCE	varchar(1)	No	**TIPO_VOCE** Specify the type of the F.S.T. line. Possible values are: • A (Parent line)	No	

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
			• F (Formula) • D (Description)		
FORMULA_VOCE	varchar(max) (-1)	No	If the F.S.T. line is a formula here the formula is specified (with a specific syntax).	No	
ORDINAMENTO	varchar(30)	No	It indicates the sequence with which the F.S.T. items must be shown in the report	No	
FLAG_CAMBIA_SEGNO	numeric(1)	No	It indicates if a Parent line must be show with an inverted sign. Only for "parent" line	No	

Table name: **VOCE_CONTO_ABBI**
This table contains the relationship between the element dimension involved in the F.S.T. and the F.S.T. line.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCHEMA	varchar(5)	No	F.S.T. code	No	VOCE
COD_CONTO	varchar(30)	No	Account Code	No	CONTO
COD_DEST1	varchar(30)	No	Custom dimension 1 element code	No	DEST1
COD_DEST2	varchar(30)	No	Custom dimension 2 element code	No	DEST2
COD_VOCE	varchar(30)	No	F.S.T. line code. Only of type A (parent line)	No	VOCE
COD_DEST3	varchar(30)	No	Custom dimension 3 element code	No	DEST3
COD_DEST4	varchar(30)	No	Custom dimension 4 element code	No	DEST4
COD_DEST5	varchar(30)	No	Custom dimension 5 element code	No	DEST5
ID_DIM_ANALITICA	varchar(36)	No	[TODO: null]	No	
COD_DIM_ANA	varchar(30)	No	[TODO: null]	No	

User Views/Limitations

Table name: **UTENTE**
This table contains, for each user enabled to the Application Database, the data visibility limitations.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_UTENTE	varchar(255)	Yes	User Code	Yes	
DESC_UTENTE	varchar(1000)	No	User description	No	
TIPO_LIM_AZIENDA	varchar(2)	No	**TIPO_LIM_AZIENDA** Specifies if any limitations exist for the Entities manageable by the user. Possible values are: • X: all Entities present in the table are visible to the user. In this case the deployed table UTENTE_LIM_AZIENDA is empty • 00: the Entities visible to the user are limited and are listed in the table UTENTE_LIM_AZIENDA • X = Unrestricted in insertion, submission and display • XV = Restricted in insertion and submission, but not restricted in display • XP = By area profile • VP = Restricted in insertion and submission, display by area profile • 00 = Restricted	No	
TIPO_LIM_DEST1	varchar(2)	No	**TIPO_LIM_DEST1** Specifies if any limitations exist for the custom dimension elements manageable by the user. Possible values are: • X all the custom dimension elements present in the table are manageable by the user. In this case the deployed table UTENTE_LIM_DEST1 is empty • <>X the custom dimension elements manageable by the user are limited and listed in the table UTENTE_LIM_DEST1	No	
TIPO_LIM_DEST2	varchar(2)	No	**TIPO_LIM_DEST2** Specifies if any limitations exist for the custom dimension elements manageable by the user. Possible values are: • X all the custom dimension elements present in the table are manageable by the user. In this case the deployed table UTENTE_LIM_DEST2 is empty • <>X the custom dimension elements manageable by the user are limited and listed in the table UTENTE_LIM_DEST2	No	
TIPO_LIM_DEST3	varchar(2)	No	**TIPO_LIM_DEST3** Specifies if any limitations exist for the custom dimension elements manageable by to the user. Possible values are:	No	

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
			• X all the custom dimension elements present in the table are manageable by the user. In this case the deployed table UTENTE_LIM_DEST3 is empty • <>X the custom dimension elements manageable by the user are limited and listed in the table UTENTE_LIM_DEST3		
TIPO_LIM_DEST4	varchar(2)	No	**TIPO_LIM_DEST4** Specifies if any limitations exist for the custom dimension elements manageable by the user. Possible values are: • X all the custom dimension elements present in the table are manageable by the user. In this case the deployed table UTENTE_LIM_DEST4 is empty • <>X the custom dimension elements manageable by the user are limited and listed in the table UTENTE_LIM_DEST4	No	
TIPO_LIM_DEST5	varchar(2)	No	**TIPO_LIM_DEST5** Specifies if any limitations exist for the custom dimension elements manageable by the user. Possible values are: • X all the custom dimension elements present in the table are manageable by the user. In this case the deployed table UTENTE_LIM_DEST5 is empty • <>X the custom dimension elements manageable by the user are limited and listed in the table UTENTE_LIM_DEST5	No	
TIPO_LIM_SCENARIO	varchar(2)	No	**TIPO_LIM_SCENARIO** Specifies if any limitations exist for the original scenarios manageable by the user. Possible values are: • X all the original scenarios present in the table are manageable by the user. In this case the deployed table UTENTE_LIM_SCENARIO is empty • <>X the original scenarios manageable by the user are limited and listed in the table UTENTE_LIM_SCENARIO	No	
TIPO_LIM_SCENARIO_CONS	varchar(2)	No	**TIPO_LIM_SCENARIO_CONS** Specifies if any limitations exist for the consolidation scenarios visible to the user. Possible values are: • X all the consolidation scenarios present in the table are visible to the user. In this case the deployed table UTENTE_LIM_SCENARIO_CONS is empty • <>X the consolidation scenarios visible to the user are limited and listed in the table UTENTE_LIM_SCENARIO_CONS	No	
TIPO_LIM_CATEGORIA	varchar(2)	No	**TIPO_LIM_CATEGORIA** Specifies if any limitations exist for the categories visible to the user. Possible values are: • X all the categories present in the table are visible to the user. In this case the deployed table UTENTE_LIM_CATEGORIA is empty • <>X the categories visible to the user are limited and listed in the table UTENTE_LIM_CATEGORIA	No	
TIPO_LIM_CONTO	varchar(2)	Yes	**TIPO_LIM_CONTO** Specifies if any limitations exist for the account manageable by the user. Possible values are: • X all the account present in the table are manageable by the user. In this case the deployed table UTENTE_LIM_CONTO is empty • <>X the account manageable by the user are limited and listed in the table UTENTE_LIM_CONTO	No	
TIPO_LIM_WFM_FASE	varchar(2)	Yes	**TIPO_LIM_WFM_FASE** Specifies if any limitations exist for the categories visible to the user. Possible values are: • X all the categories present in the table are visible to the user. In this case the deployed table UTENTE_LIM_WFM_TASK_DEF is empty	No	

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
			• <>X the categories visible to the user are limited and listed in the table UTENTE_LIM_WFM_TASK_DEF		

Table name: **UTENTE_LIM_AZIENDA**
This table contains, for each user that has limitations on entity dimension, the list of the entities that are visible to the user.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_UTENTE	varchar(255)	Yes	User code	Yes	UTENTE
COD_AZIENDA	varchar(30)	Yes	Entity code	Yes	AZIENDA

Table name: **UTENTE_LIM_DEST1**
This table contains, for each user that has limitations on Custom dimension 1, the list of the elements that are manageable by the user.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_UTENTE	varchar(255)	Yes	User code	Yes	UTENTE
COD_DEST1	varchar(30)	Yes	Custom dimension 1 element code	Yes	DEST1
FLAG_SOLO_VISUALIZZA	numeric(1)	No	**FLAG_SOLO_VISUALIZZA** Specifies if the Custom dimension element is visible but not editable by the user. Possible values are: • (1) the element isn't editable but only visible by the user • (0) the element is editable and visible for the user.	No	

Table name: **UTENTE_LIM_SCENARIO**
This table contains, for each user that have limitations on original scenarios, the list of the original scenarios that are visible to the user.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_UTENTE	varchar(255)	Yes	User code	Yes	UTENTE
COD_SCENARIO	varchar(15)	Yes	Original scenario code	Yes	SCENARIO
FLAG_SOLO_VISUALIZZA	numeric(1)	No	**FLAG_SOLO_VISUALIZZAZIONE** Specifies if the original scenario is visible but not editable for the user.Possible values are: • (1) the element isn't editable but only visible by the user • (0) the element is editable and visible for the user.	No	

Table name: **UTENTE_LIM_SCENARIO_CONS**
[TODO: cpm.datamodelxml.UTENTE_LIM_SCENARIO_CONS]

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_UTENTE	varchar(255)	Yes	User code	Yes	UTENTE
COD_SCENARIO	varchar(15)	Yes	Consolidation scenario code	Yes	SCENARIO

Table name: **UTENTE_LIM_CATEGORIA**
This table contains, for each user that have limitations on the category dimension, the list of the categories that are visible to the user.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_UTENTE	varchar(255)	Yes	User code	Yes	UTENTE
COD_CATEGORIA	varchar(30)	Yes	Category code	Yes	CATEGORIA
FLAG_SOLO_VISUALIZZA	numeric(1)	No	**FLAG_SOLO_VISUALIZZA** Specifies if the category is visible but not editable for the user. Possible values are: • (1) the element isn't editable and hidden for the user • (0) the element is editable and visible for the user.	No	

[TODO: undefined]

Data tables

Tagetik allows to store offline data tables whose volume (in terms of number of records) may increase a lot over time. This makes it possible to avoid performance problems for components that operate on the data.

In the SCENARIO_PERIOD table the FLAG_STORICIZZATO flag specifies if the data of a specific Scenario/Period is stored offline.

The data that is stored offline is moved into special tables, whose name is equal to their "online" counterpart but with the addition of the "H_" prefix. For example:

- Online table = DATI_SALDI_LORDI
- Offline table = H_DATI_SALDI_LORDI

Exchange rate
Table name: **DATI_CAMBIO**
DATI_CAMBIO
This table contains the exchange rate.
In this table there are no exchange rates for derived currencies (e.g. Thousand Euro).
The exchange rate will be calculated according to a coefficient and the reference currency exchange rate (Thousand Euro = Euro ex. Rate * 1.000)

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active original scenario	Yes	SCENARIO_PERIODO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario	Yes	SCENARIO_PERIODO
COD_VALUTA	varchar(5)	Yes	Currency code	Yes	VALUTA
CAMBIO_MEDIO	numeric(21)	No	Cumulate average exchange rate	No	
CAMBIO_PERIODO	numeric(21)	No	Period average exchange rate	No	
CAMBIO_FINALE	numeric(21)	No	End of period exchange rate	No	
CAMBIO_QTD	numeric(21)	No	Average QTD Fx rate	No	

Amounts
Table name: **DATI_SALDI_LORDI**
This table contains the original gross amount. These amounts include both the minority and the intercompany quota.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
OID_DATI_SALDI_LORDI	varchar(36)	Yes	OID_DATI_SALDI_LORDI	Yes	
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active original scenario.	Yes	SCENARIO_PERIODO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario	Yes	SCENARIO_PERIODO
COD_AZIENDA	varchar(30)	Yes	Entity code	No	AZIENDA
COD_CONTO	varchar(30)	Yes	Account code	No	CONTO
COD_DEST1	varchar(30)	No	Custom Dimension 1: Custom Dimension element code	No	DEST1
COD_DEST2	varchar(30)	No	Custom Dimension 2: Custom Dimension element code	No	DEST2
COD_DEST3	varchar(30)	No	Custom Dimension 3: Custom Dimension element code	No	DEST3
COD_DEST4	varchar(30)	No	Custom Dimension 4: Custom Dimension element code	No	DEST4
COD_DEST5	varchar(30)	No	Custom Dimension 5: Custom Dimension element code	No	DEST5
COD_CATEGORIA	varchar(30)	Yes	Category code. This is an "Amount" category	No	CATEGORIA
IMPORTO	numeric(27)	Yes	Amount in entity currency	No	
COD_VALUTA	varchar(5)	No	Entity currency code	No	VALUTA
IMPORTO_VALUTA_ORIGINARIA	numeric(27)	Yes	Amount in transaction currency	No	
COD_VALUTA_ORIGINARIA	varchar(5)	No	Transaction currency code	No	VALUTA
NOTE	varchar(1000)	No	Notes	No	

Intercompany
Table name: **DATI_SALDI_IC**
This table contains the intercompany entries

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
OID_DATI_SALDI_IC	varchar(36)	Yes	OID_DATI_SALDI_IC	Yes	
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active original scenario	No	SCENARIO_PERIODO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario	No	SCENARIO_PERIODO
COD_AZIENDA	varchar(30)	Yes	Declaring Entity code	No	AZIENDA
COD_CONTO	varchar(30)	Yes	Account code	No	CONTO
COD_DEST1	varchar(30)	No	Custom Dimension 1: Custom Dimension element code	No	DEST1
COD_DEST2	varchar(30)	No	Custom Dimension 2: Custom Dimension element code	No	DEST2
COD_DEST3	varchar(30)	No	Custom Dimension 3: Custom Dimension element code	No	DEST3
COD_DEST4	varchar(30)	No	Custom Dimension 4: Custom Dimension element code	No	DEST4
COD_DEST5	varchar(30)	No	Custom Dimension 5: Custom Dimension element code	No	DEST5
COD_CATEGORIA	varchar(30)	Yes	Category code. This is an "Amount" category	No	CATEGORIA
COD_AZI_CTP	varchar(30)	No	Counterparty Entity code	No	AZIENDA
COD_DEST2_CTP	varchar(30)	No	Code of the Custom Dimension 2 element used as counterparty	No	DEST2
COD_VALUTA_DOC	varchar(5)	No	Transaction currency code	No	VALUTA
IMPORTO_VALUTA_DOC	numeric(27)	Yes	Amount in transaction currency	No	
COD_VALUTA	varchar(5)	No	Entity currency code	No	VALUTA
IMPORTO	numeric(27)	Yes	Amount in entity currency	No	
NOTE	varchar(1000)	No	Additional information	No	

[TODO: cpm.datamodel.data_tables.consolidated_amounts]
Table name: **DATI_SALDI_CONS_1**
This table contains data related to the Consolidated amounts on the Proportional amount type

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active consolidation scenario	No	SCENARIO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario	No	SCENARIO_PERIODO
COD_AZIENDA	varchar(30)	Yes	Entity code	No	AZIENDA
COD_CONTO	varchar(30)	Yes	Account code	No	CONTO
COD_DEST1	varchar(30)	No	Custom Dimension 1: Custom Dimension element code	No	DEST1
COD_DEST2	varchar(30)	No	Custom Dimension 2: Custom Dimension element code	No	DEST2
COD_DEST3	varchar(30)	No	Custom Dimension 3: Custom Dimension element code	No	DEST3
COD_DEST4	varchar(30)	No	Custom Dimension 4: Custom Dimension element code	No	DEST4
COD_DEST5	varchar(30)	No	Custom Dimension 5: Custom Dimension element code	No	DEST5

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_CATEGORIA	varchar(30)	Yes	Category code. This is an "Amount" category	No	CATEGORIA
COD_AZI_CTP	varchar(30)	No	Counterparty Entity code	No	AZIENDA
COD_DEST2_CTP	varchar(30)	No	Code of the Custom Dimension 2 element used as counterparty	No	DEST2
COD_VALUTA_DOC	varchar(5)	No	Transaction currency code	No	VALUTA
IMPORTO_VALUTA_DOC	numeric(27)	Yes	Amount in transaction currency	No	
COD_VALUTA	varchar(5)	No	Entity currency code	No	VALUTA
IMPORTO	numeric(27)	Yes	Amount in entity currency	No	
COD_VALUTA3	varchar(5)	No	Entity currency	No	VALUTA
NOTE	varchar(1000)	No	Additional information	No	

Table name: **DATI_SALDI_CONS_2**
This table contains data related to the Consolidated amounts on the Converted amount type

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active consolidation scenario	No	SCENARIO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario	No	SCENARIO_PERIODO
COD_AZIENDA	varchar(30)	Yes	Entity code	No	AZIENDA
COD_CONTO	varchar(30)	Yes	Account code	No	CONTO
COD_DEST1	varchar(30)	No	Custom Dimension 1: Custom Dimension element code	No	DEST1
COD_DEST2	varchar(30)	No	Custom Dimension 2: Custom Dimension element code	No	DEST2
COD_DEST3	varchar(30)	No	Custom Dimension 3: Custom Dimension element code	No	DEST3
COD_DEST4	varchar(30)	No	Custom Dimension 4: Custom Dimension element code	No	DEST4
COD_DEST5	varchar(30)	No	Custom Dimension 5: Custom Dimension element code	No	DEST5
COD_CATEGORIA	varchar(30)	Yes	Category code. This is an "Amount" category	No	CATEGORIA
COD_AZI_CTP	varchar(30)	No	Counterparty entity code	No	AZIENDA
COD_DEST2_CTP	varchar(30)	No	Code of the Custom Dimension 2 element used as counterparty	No	DEST2
COD_VALUTA_DOC	varchar(5)	No	Transaction currency code	No	VALUTA
IMPORTO_VALUTA_DOC	numeric(27)	Yes	Amount in transaction currency	No	
COD_VALUTA	varchar(5)	No	Consolidation currency code	No	VALUTA
IMPORTO	numeric(27)	Yes	Amount in consolidation currency	No	
COD_VALUTA3	varchar(5)	No	Entity currency	No	VALUTA
NOTE	varchar(1000)	No	Additional information	No	

Table name: **DATI_SALDI_CONS_3**
This table contains data related to the Consolidated amounts on the Consolidable amount type

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active consolidation scenario	No	SCENARIO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario	No	SCENARIO_PERIODO
COD_AZIENDA	varchar(30)	Yes	Entity code	No	AZIENDA
COD_CONTO	varchar(30)	Yes	Account code	No	CONTO
COD_DEST1	varchar(30)	No	Custom Dimension 1: Custom Dimension element code	No	DEST1
COD_DEST2	varchar(30)	No	Custom Dimension 2: Custom Dimension element code	No	DEST2
COD_DEST3	varchar(30)	No	Custom Dimension 3: Custom Dimension element code	No	DEST3
COD_DEST4	varchar(30)	No	Custom Dimension 4: Custom Dimension element code	No	DEST4
COD_DEST5	varchar(30)	No	Custom Dimension 5: Custom Dimension element code	No	DEST5
COD_CATEGORIA	varchar(30)	Yes	Category code. This is an "Amount" category	No	CATEGORIA
COD_AZI_CTP	varchar(30)	No	Counterparty Entity code	No	AZIENDA
COD_DEST2_CTP	varchar(30)	No	Code of the Custom Dimension 2 element used as counterparty	No	DEST2
COD_VALUTA_DOC	varchar(5)	No	Transaction currency code	No	VALUTA
IMPORTO_VALUTA_DOC	numeric(27)	Yes	Amount in transaction currency	No	
COD_VALUTA	varchar(5)	No	Consolidation currency code	No	VALUTA
IMPORTO	numeric(27)	Yes	Amount in consolidation currency	No	
COD_VALUTA3	varchar(5)	No	Entity currency	No	VALUTA
NOTE	varchar(1000)	No	Additional information	No	

Adjustment
Table name: **DATI_RETT**
DATI_RETT
This table contains the headers of the preconsolidation and consolidation adjustment.

- Preconsolidation adjustment: typically, they are adjustments to the single Entities' accounting standards, with the aim to make them homogeneous with the Consolidation process' accounting standards. Examples of preconsolidation adjustments are:
  - depreciation percentages modification
  - cost allocation criteria modification
  - stock modification
- Consolidation adjustment typically, they are accounting entries that must be inserted in order to produce the Consolidated Financial Statements. Usually one or two Entities of the Consolidation Scenario are involved

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active original scenario.	Yes	SCENARIO_PERIODO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario	Yes	SCENARIO_PERIODO
NUM_RETTIFICA	varchar(200)	Yes	The adjustment number	Yes	

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_AZIENDA1	varchar(30)	No	Entity code for the preconsolidation adjustmentCode of the first entity for the consolidation adjustment	No	AZIENDA
COD_DEST21	varchar(30)	No	Code of the Custom Dimension 2 element used as counterparty for the Entity 1 adjustment	No	DEST2
COD_AZIENDA2	varchar(30)	No	Code of the second entity. Only for consolidation adjustment	No	AZIENDA
COD_DEST22	varchar(30)	No	Code of the Custom Dimension 2 element used as counterparty for the Entity 2 adjustment	No	DEST2
NOTE	varchar(1000)	No	Adjustment description	No	
COD_CATEGORIA	varchar(30)	No	Category code. Specifies the adjustment type	No	CATEGORIA
COD_VALUTA	varchar(5)	No	Currency code	No	VALUTA
FLAG_DOCUMENTO	numeric(1)	No	**FLAG_DOCUMENTO** Specifies if the journal has attached documents. • 0 = the journal does not have attached documents • 1 = the journal has attached documents	No	
FLAG_PERIODICO	numeric(1)	No	Specifies if the journal has to be managed in periodic mode	No	
FLAG_DRAFT	numeric(1)	Yes	[TODO: null]	No	

Table name: **DATI_RETT_RIGA**
This table contains all the adjustment rows, that can be both manual or automatically generated by the system.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
OID_DATI_RETT_RIGA	varchar(36)	Yes	OID_DATI_RETT_RIGA	Yes	
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active original scenario.	Yes	DATI_RETT
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario.	Yes	DATI_RETT
NUM_RETTIFICA	varchar(200)	Yes	The adjustment number	Yes	DATI_RETT
COD_AZIENDA	varchar(30)	Yes	**COD_AZIENDA** Entity code for the preconsolidation adjustment (must be the same as DATI_RETT.COD_AZIENDA1) Declaring Entity Code for the consolidation adjustment	No	AZIENDA
COD_CONTO	varchar(30)	Yes	Account code	No	CONTO
COD_DEST1	varchar(30)	No	Custom Dimension 1: Custom Dimension element code	No	DEST1
COD_DEST2	varchar(30)	No	Custom Dimension 2: Custom Dimension element code	No	DEST2
COD_DEST3	varchar(30)	No	Custom Dimension 3: Custom Dimension element code	No	DEST3
COD_DEST4	varchar(30)	No	Custom Dimension 4: Custom Dimension element code	No	DEST4
COD_DEST5	varchar(30)	No	Custom Dimension 5: Custom Dimension element code	No	DEST5
COD_CATEGORIA	varchar(30)	Yes	Category code. (must be the same as DATI_RETT.COD_CATEGORIA)	No	CATEGORIA
COD_AZI_CTP	varchar(30)	No	Code of Entity element used as counterparty for IC figures adjustment	No	AZIENDA
COD_DEST2_CTP	varchar(30)	No	Code of Custom Dimension 2 element used as counterparty for IC figures adjustment.	No	DEST2
COD_AZI_CTP_SEGMENT	varchar(30)	No	**COD_AZI_CTP_SEGMENT** Segment Ctp Entity code. If the **"Many to many relationship"** field on the journal header is **"No"**, when saving: if the declaring Entity corresponds to the Entity 1 of the header, the system sets this field with the Entity 2 of the header if the declaring Entity corresponds to the Entity 2 of the header, the system sets this field with the Entity 1 of the header	No	AZIENDA
COD_DEST2_CTP_SEGMENT	varchar(30)	No	**COD_DEST2_CTP_SEGMENT** Segment Ctp custom dimension 2 code. If the **"Many to many relationship"** field on the journal header is **"No"**, when saving: if the declaring Entity corresponds to the Entity 1 of the header, the system sets this field with the CTP 2 Custom dimension 2 of the header if the declaring Entity corresponds to the Entity 2 of the header, the system sets this field with the CTP 1 Custom dimension 2 of the header	No	DEST2
COD_VALUTA	varchar(5)	No	**COD_VALUTA** • **Entity journal**: Entity currency code • **Consolidation journal**: Journal currency code	No	VALUTA
IMPORTO	numeric(27)	Yes	**IMPORTO** • **Entity journal** Amount in entity currency • **Consolidation journal** Amount in Journal currency	No	
COD_VALUTA2	varchar(5)	No	**COD_VALUTA2** • **Entity journal**	No	VALUTA

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
			Transaction currency code • **Consolidation journal** Entity currency code		
IMPORTO2	numeric(27)	Yes	**IMPORTO2** • **Entity journal** Amount in transaction currency • **Consolidation journal** Amount in entity currency	No	
NOTE	varchar(1000)	No	Additional information on the adjustment row	No	
FLAG_FORZA_CAMBIO	numeric(1)	No	**FLAG_FORZA_CAMBIO** Specifies if the user wants to override the exchange rate for the conversion of the amount to the Entity's exchange rate on the adjustment's row. • 0 = The exchange rate is not overridden for the record • 1 = The exchange rate is overridden for the record	No	
COD_VALUTA_TRANSAZIONE	varchar(5)	No	[TODO: cpm.datamodelxml.DATI_RETT_RIGA.COD_VALUTA_TRANSAZIONE]	No	VALUTA
IMPORTO_VALUTA_TRANSAZIONE	numeric(27)	No	**IMPORTO_VALUTA_TRANSAZIONE** • **Entity journal** Null • **Consolidation journal** Amount in transaction currency	No	

Table name: **DATI_RETT_RIGA_CONS_1**
This table contains data related to the Consolidated adjustments on the Proportional amount type

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active consolidation scenario	No	SCENARIO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario	No	SCENARIO_PERIODO
NUM_RETTIFICA	varchar(200)	Yes	The adjustment number	No	
COD_AZIENDA	varchar(30)	Yes	Entity code	No	AZIENDA
COD_CONTO	varchar(30)	Yes	Account code	No	CONTO
COD_DEST1	varchar(30)	No	Custom Dimension 1: Custom Dimension element code	No	DEST1
COD_DEST2	varchar(30)	No	Custom Dimension 2: Custom Dimension element code	No	DEST2
COD_DEST3	varchar(30)	No	Custom Dimension 3: Custom Dimension element code	No	DEST3
COD_DEST4	varchar(30)	No	Custom Dimension 4: Custom Dimension element code	No	DEST4
COD_DEST5	varchar(30)	No	Custom Dimension 5: Custom Dimension element code	No	DEST5
COD_CATEGORIA	varchar(30)	Yes	Category code	No	CATEGORIA
COD_AZI_CTP	varchar(30)	No	Code of Entity element used as counterparty for IC figures adjustment	No	AZIENDA
COD_DEST2_CTP	varchar(30)	No	Code of Custom Dimension 2 element used as counterparty for IC figures adjustment	No	DEST2
COD_AZI_CTP_SEGMENT	varchar(30)	No	**COD_AZI_CTP_SEGMENT** Segment Ctp Entity code. If the **"Many to many relationship"** field on the journal header is **"No"**, when saving: if the declaring Entity corresponds to the Entity 1 of the header, the system sets this field with the Entity 2 of the header if the declaring Entity corresponds to the Entity 2 of the header, the system sets this field with the Entity 1 of the header	No	AZIENDA
COD_DEST2_CTP_SEGMENT	varchar(30)	No	Code of Custom Dimension 2 element used as counterparty for IC figures adjustment	No	DEST2
COD_VALUTA	varchar(5)	No	**COD_VALUTA** • **Entity journal** Entity currency code • **Consolidation journal** Journal currency code	No	VALUTA
IMPORTO	numeric(21)	Yes	**IMPORTO** • **Entity journal** Amount in entity currency • **Consolidation journal**	No	

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
			Amount in Journal currency		
COD_VALUTA2	varchar(5)	No	**COD_VALUTA2** • **Entity journal** Transaction currency code • **Cosolidation journal** Entity currency code	No	VALUTA
IMPORTO2	numeric(21)	Yes	**IMPORTO2** • **Entity journal** Amount in transaction currency • **Consolidation** Amount in entity currency	No	
COD_VALUTA3	varchar(5)	No	**COD_VALUTA3** • **Entity journal** Entity currency code • **Cosolidation journal** Journal currency code	No	VALUTA
NOTE	varchar(1000)	No	Additional information on the adjustment row	No	
COD_VALUTA_TRANSAZIONE	varchar(5)	No	**COD_VALUTA_TRANSAZIONE** • **Entity journal** Null • **Cosolidation journal** Transaction currency code	No	VALUTA
IMPORTO_VALUTA_TRANSAZIONE	numeric(21)	No	**IMPORTO_VALUTA_TRANSAZIONE** • **Entity journal** Null • **Consolidation journal** Amount in transaction currency	No	

Table name: **DATI_RETT_RIGA_CONS_2**
This table contains data related to the Consolidated adjustments on the Converted amount type

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active consolidation scenario	No	SCENARIO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario.	No	SCENARIO_PERIODO
NUM_RETTIFICA	varchar(200)	Yes	The adjustment number	No	
COD_AZIENDA	varchar(30)	Yes	Entity code	No	AZIENDA
COD_CONTO	varchar(30)	Yes	Account code	No	CONTO
COD_DEST1	varchar(30)	No	Custom Dimension 1: Custom Dimension element code	No	DEST1
COD_DEST2	varchar(30)	No	Custom Dimension 2: Custom Dimension element code	No	DEST2
COD_DEST3	varchar(30)	No	Custom Dimension 3: Custom Dimension element code	No	DEST3
COD_DEST4	varchar(30)	No	Custom Dimension 4: Custom Dimension element code	No	DEST4
COD_DEST5	varchar(30)	No	Custom Dimension 5: Custom Dimension element code	No	DEST5
COD_CATEGORIA	varchar(30)	Yes	Category code	No	CATEGORIA
COD_AZI_CTP	varchar(30)	No	Code of Entity element used as counterparty for IC figures adjustment	No	AZIENDA
COD_AZI_CTP_SEGMENT	varchar(30)	No	**COD_AZI_SEGMENT** Segment Ctp Entity code. If the **"Many to many relationship"** field on the journal header is **"No"**, when saving: if the declaring Entity corresponds to the Entity 1 of the header, the system sets this field with the Entity 2 of the header if the declaring Entity corresponds to the Entity 2 of the header, the system sets this field with the Entity 1 of the header	No	AZIENDA
COD_DEST2_CTP_SEGMENT	varchar(30)	No	**COD_DEST2_CTP_SEGMENT** Segment Ctp custom dimension 2 code. If the **"Many to many relationship"** field on the journal header is **"No"**, when saving: if the declaring Entity corresponds to the Entity 1 of the header, the system sets this field with the CTP 2 Custom dimension 2 of the header if the declaring Entity corresponds to the Entity 2 of the header, the system sets this field with the CTP 1 Custom dimension 2 of the header	No	DEST2

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_VALUTA	varchar(5)	No	Consolidation currency code	No	VALUTA
IMPORTO	numeric(21)	Yes	Amount in consolidation currency	No	
COD_VALUTA2	varchar(5)	No	Transaction currency code	No	VALUTA
IMPORTO2	numeric(21)	Yes	Amount in transaction currency	No	
COD_VALUTA3	varchar(5)	No	Entity currency code	No	VALUTA
NOTE	varchar(1000)	No	Additional information on the adjustment row	No	

Table name: **DATI_RETT_RIGA_CONS_3**
This table contains data related to the Consolidated adjustments on the Consolidable amount type

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active consolidation scenario.	No	SCENARIO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario.	No	SCENARIO_PERIODO
NUM_RETTIFICA	varchar(200)	Yes	The adjustment number	No	
COD_AZIENDA	varchar(30)	Yes	Entity code	No	AZIENDA
COD_CONTO	varchar(30)	Yes	Account code	No	CONTO
COD_DEST1	varchar(30)	No	Custom Dimension 1: Custom Dimension element code	No	DEST1
COD_DEST2	varchar(30)	No	Custom Dimension 2: Custom Dimension element code	No	DEST2
COD_DEST3	varchar(30)	No	Custom Dimension 3: Custom Dimension element code	No	DEST3
COD_DEST4	varchar(30)	No	Custom Dimension 4: Custom Dimension element code	No	DEST4
COD_DEST5	varchar(30)	No	Custom Dimension 5: Custom Dimension element code	No	DEST5
COD_CATEGORIA	varchar(30)	Yes	Category code	No	CATEGORIA
COD_AZI_CTP	varchar(30)	No	Code of Entity element used as counterparty for IC figures adjustment	No	AZIENDA
COD_DEST2_CTP	varchar(30)	No	Code of Custom Dimension 2 element used as counterparty for IC figures adjustment.	No	DEST2
COD_AZI_CTP_SEGMENT	varchar(30)	No	**COD_AZI_CTP_SEGMENT** Segment Ctp Entity code. If the **"Many to many relationship"** field on the journal header is **"No"**, when saving: if the declaring Entity corresponds to the Entity 1 of the header, the system sets this field with the Entity 2 of the header if the declaring Entity corresponds to the Entity 2 of the header, the system sets this field with the Entity 1 of the header	No	AZIENDA
COD_DEST2_CTP_SEGMENT	varchar(30)	No	**COD_DEST2_CTP_SEGMENT** Segment Ctp custom dimension 2 code. If the **"Many to many relationship"** field on the journal header is **"No"**, when saving: if the declaring Entity corresponds to the Entity 1 of the header, the system sets this field with the CTP 2 Custom dimension 2 of the header if the declaring Entity corresponds to the Entity 2 of the header, the system sets this field with the CTP 1 Custom dimension 2 of the header	No	DEST2
COD_VALUTA	varchar(5)	No	Consolidation currency code	No	VALUTA
IMPORTO	numeric(21)	Yes	Amount in consolidation currency	No	
COD_VALUTA2	varchar(5)	No	Transaction currency code	No	VALUTA
IMPORTO2	numeric(21)	Yes	Amount in transaction currency	No	
COD_VALUTA3	varchar(5)	No	Entity currency code	No	VALUTA
NOTE	varchar(1000)	No	Additional information on the adjustment row	No	

Notes
Table name: **DATI_NOTE**
DATI_NOTE
The notes, which the user can insert from reports, are stored in this table.

These notes are not referred to particular amounts inserted into the previous table but to the dimensions assigned to the report's cell.

Column Name	Data Type	Mandatory	Comment	PK	Parent Table Name
OID_DATI_NOTE	varchar(36)	Yes	OID_DATI_NOTE	Yes	
COD_SCENARIO	varchar(15)	Yes	Scenario code. This is an active original scenario	Yes	SCENARIO_PERIODO
COD_PERIODO	varchar(2)	Yes	Period code. This is a period belonging to the Scenario	Yes	SCENARIO_PERIODO
COD_AZIENDA	varchar(30)	Yes	Entity code	No	AZIENDA
COD_CONTO	varchar(30)	Yes	Account code	No	CONTO
COD_DEST1	varchar(30)	No	Custom Dimension 1: Custom Dimension element code	No	DEST1
COD_DEST2	varchar(30)	No	Custom Dimension 2: Custom Dimension element code	No	DEST2
COD_DEST3	varchar(30)	No	Custom Dimension 3: Custom Dimension element code	No	DEST3
COD_DEST4	varchar(30)	No	Custom Dimension 4: Custom Dimension element code	No	DEST4
COD_DEST5	varchar(30)	No	Custom Dimension 5: Custom Dimension element code	No	DEST5
COD_CATEGORIA	varchar(30)	Yes	Category code	No	CATEGORIA
COD_AZI_CTP	varchar(30)	No	Counterparty Entity code	No	AZIENDA
COD_DEST2_CTP	varchar(30)	No	Code of the Custom Dimension 2 element used as counterparty	No	DEST2
NOTE	varchar(max)(-1)	No	Note	No	

Appendix A

Below are listed the values available for the field ORIGIN (present in most of the table):

Scenario Type	Origin	Description
Original	COPY_PERIOD	Original - Carry forward from previous period
Original	INPUT_WEB	Manual input - Web windows
Original	INPUT_DEFORM	Manual input – reports
Original	MAP_	ETL
Original	QDL	Quick Data Loader
Original	SUB_INPUT_WEB	Submitted manual input - Web windows
Original	SUB_INPUT_DEFORM	Submitted manual input - Reports
Original	SUB_MAP	Submitted ETL
Original	ENV_SYNC	Standard Tables Update
Original	COPY_SEGMENT	Copy Segment
Original	COPY_CONSOLIDATED	Copy consolidated amount on original amount
Original	COPY_GENERAL	Copy amounts and journals
Original	COPY_ORIG	Source origin
Original	PROC_IC_SPREADING	IC spreading reallocation
Original	PROC_IC_SPREADING_CB	IC spreading write off
Original	PROC_IC_BALANCING	IC - automatic balancing
Original	PROC_IC_SPREADING_WOFF	IC - spreading - write off
Original	DEPLOYMENT	Deployments
Original	SUB	SUB
Original	PREL_RESTORE	Original – Carry forward
Original	PREL_COPY_PREVIOUS	Original - Copy from the previous period
Original	PREL_DECONSOLIDATION12	Originals - Deconsolidation 1 and 2
Original	PROC_DECONSOLIDATION3	Original - Deconsolidation 3
Original	PREL_MERGE12	Original - Mergers 1 and 2
Original	PROC_MERGE3	Original - mergers 3
Original	PREL_REVERSE1	Original - Reverse journal 1
Original	PREL_REVERSE2	Original - Reverse journal 2
Original	PREL_REVERSE3	Original - Reverse journal 3
Original	PROC_FININV_DEPLOY	Originals – Loading Financial investments
Original	PROC_COUNTERPARTY	Original - Create automatic Ctps
Original	PROC_DEPRECIATION	Original – Depreciation
Original	PROC_DEFERRED_TAXES	Original - Deferred tax
Original	PROC_CTP_ELIMINATIONS	Original - Eliminations for Ctp
Original	PROC_FI_ELIMINATIONS	Original - Financial investment eliminations from ownership structure
Original	PROC_IC_PROFIT	Original - Intragroup assets assignment
Original	PROC_BALANCING	Original – Balancing
Original	PROC_CALCULATED_BASIC	Originals - Basic calculation logics
Original	PROC_CALCULATED	Originals - calculation logics
Original	PROC_FININV_RECL	Original – Financial investments reclassification
Original	PROC_NETEQUITY_RECL	Original – NER
Original	PROC_CLOSING	Originario - Closing
Original	PROC_MONTHLY_SPLIT	Original - Monthly splitting
Original	PROC_MONTHLY_SPLIT_NEW	Original - New Monthly splitting
Original	PROC_ALG_OPERATIONS	Original - Algebraic operations
Original	PROC_FORECAST	Original - Forecast
Original	PROC_BDG_FN	Financial product
Original	PROC_BDG_DEPRECIATION	Depreciation
Original	PROC_RECLASSIFICATION	Preconsolidation reclassification
Original	PROC_EPU	Original - Pick-up
Original	EPU_DEPLOY	Pick-up loading
Original	CFP_BUDGET	CFP - Copy from budget
Original	CFP_LT_FINANCING	CFP - L/T financing
Original	CFP_FIXED_ASSET	CFP – Assets
Original	CFP_BOND	CFP – Titles
Original	CFP_EXCHRATE_COVERAGE	CFP - Currency hedging
Original	CFP_PROJECT	CFP - Work order
Original	CFP_CASH_IN_OUT	CFP - Collection and payments
Original	CFP_PAYMENT_CALENDAR	CFP - Payment calendar
Original	CFP_SPLITTING	CFP – Weights
Original	CFP_PAYMENT_CALENDAR_WOFF	CFP - Payments calendar - Write off
Original	CFP_SPLITTING_WOFF	CFP - Weights - Write off
Original	CFP_VAT_DOWN_PAYMENT	CFP - VAT – Down payment
Original	CFP_VAT_ACCOUNTING	CFP - VAT – Accounting
Original	CFP_CORRISPETTIVI_WOFF	CFP - Consideration - Write off
Original	CFP_VAT_PAYMENT	CFP - VAT – Payment
Original	CFP_VAT_TRANS_ACCOUNT_WOFF	CFP - VAT - Transitory write off account
Original	CFP_TAXES_PAYMENT	CFP - Taxes – Payment

Original	CFP_TAXES_DOWN_PAYMENT	CFP - Taxes - Down payment
Original	CFP_TAXES_DOWN_PAYMENT_WOFF	CFP - Taxes - Down payment account
Original	CFP_FINAL_EXCHRATE_EVAL	CFP - Evaluation at final FX rate
Original	CFP_TAXES_PL	CFP – P&L Taxes
Original	CFP_TAXES_ACC	CFP – Taxes
Original	CFP_TAXES_DOWN_PAYMENT_DEBT	CFP - Taxes - Debit Down payment
Original	CFP_TAXES_DEFERRED	CFP - Deferred taxes
Original	CFP_TAXES_DEFERRED_WOFF	CFP - Deferred taxes - Write off down payment
Original	CFP_TAX_CREDIT	CFP - Tax credit
Original	CFP_CQNC	CFP – CNQC
Original	CFP_FINANCIAL_RULE	CFP - Financial policy
Original	CFP_INTEREST_PL	CFP - P&L interests
Original	CFP_INTEREST_ACC	CFP - Interests – Accounting
Original	CFP_GROUP_CASH_POOLING	CFP - Cash Pooling
Original	CFP_GROUP_VAT	CFP - Group VAT
Original	CFP	Cash Flow Planning
Original	RULE_DEPLOYMENT	CFP - Rules distribution
Original	EVENT_RULE	CFP - Create events by a rule
Original	EVENT_RULE_MIXED	CFP - Create events by hybrid rule
Original	DIAGNOSTIC	Diagnostic
Original	USER_LIM_WIZARD	Basic admin - User Rights - Simplified management
Original	PROC_TAXES	Taxes
Original	PC_COSTS	Production Control: Costs
Original	PC_VALUES	Production Control: Values
Original	PC_MOVEMENTS	Production Control: Stock transactions
Original	BREAK_BACK	Form - Break Back
Original	PROC_DIVIDENDS	Dividends
Original	ELAB_DEADLINES	Generate Submission deadline dates
Original	CFP_DIVIDENDS	CFP - Dividends
Consolidation	INPUT	Input Derived from INPUT_WEB, INPUT_DEFORM, SUB_INPUT_WEB, SUB_INPUT_DEFORM on original scenarios
Consolidation	MAP	ETL Derived from SUB_MAP or from one of the possible origins starting with ETL_ on original scenarios
Consolidation	PRCO_RESTORE	Consolidation – Carry forward Derived from PREL_RESTORE on original scenarios
Consolidation	PRCO_PERC_CHANGE	Consolidation - percentage change
Consolidation	CONS_BALANCING	Consolidation – Balancing Derived from PROC_BALANCING on original scenarios
Consolidation	CONS_GENEXCHRATE_DEPLOY	CONS_GENEXCHRATE_DEPLOY
Consolidation	CONS_CALCULATED	Consolidation - Calculation rule Derived from PROC_CALCULATED on original scenarios
Consolidation	CONS_CONVERSION_CONV	Consolidation – Conversion
Consolidation	CONS_CONVERSION_DIFF	Consolidation - FX rate differences
Consolidation	CONS_CONVERSION_DIFF_PROP_CHANGE	Consolidation - Conversion - Consolidation percentage change FX rate differences
Consolidation	CONS_CONVERSION_DIFF_RESTORE	Consolidation - Conversion - Carry forward FX rate differences
Consolidation	CONS_CONVERSION_HIST	Consolidation - Conversion at historical FX rate
Consolidation	CONS_EQUITYEVAL_CALC	Consolidation - Evaluation with equity method
Consolidation	CONS_EQUITYEVAL_CHANGE	Consolidation - Equity FX rate
Consolidation	CONS_NETEQUITY_RECL	Consolidation - Net equity accounts reclassification (NER) Derived from PROC_NETEQUITY_RECL on original scenarios
Consolidation	CONS_MINORITY	Consolidation – Minorities
Consolidation	CONS_MINORITY_COPY_PERIOD	Consolidation - Minorities interest - Copy previous period
Consolidation	CONS_DECONSOLIDATION	Consolidation – Deconsolidation
Consolidation	CONS_DECONSOLIDATION_2	Consolidation - Deconsolidation on converted amount
Consolidation	CONS_COPY_PREVIOUS	Consolidation - Copy from previous period Derived from PREL_COPY_PREVIOUS on original scenarios
Consolidation	CONS_EXCHRATE_DEPLOY	Loading FX rates on Consolidation scenarios Derived from PROC_EXCHRATE_DEPLOY on original scenarios
Consolidation	CFP	Cash Flow Planning Derived from one of the possible origins starting with CFP_ on original scenarios
Consolidation	CONS_FORCE_1	Override Proportional amount type
Consolidation	CONS_FORCE_2	Override Converted amount type

Consolidation	CONS_FORCE_3	Override Consolidable amount type
Consolidation	CONS_RECLASSIFICATION	Consolidation - Preconsolidation reclassification