

2

•

95.75 All holes 3 mm and 2 mm holes should be clearance holes for M3 and M2 bolts respectively. The 2.4 mm holes will be threaded for M3 bolts B All 1.55 mm holes in sides are 8 mm deep and threaded for M2 bolts All holes on this face are thru holes 50 40 33 4.25 58 80 UNLESS OTHERWISE SPECIFIED: NAME DATE DRAWN DIMENSIONS ARE IN INCHES **TOLERANCES:** TITLE: CHECKED FRACTIONAL ± ANGULAR: MACH ± BEND ± ENG APPR. TWO PLACE DECIMAL ± THREE PLACE DECIMAL ± MFG APPR. INTERPRET GEOMETRIC Q.A. PROPRIETARY AND CONFIDENTIAL TOLERANCING PER: COMMENTS: THE INFORMATION CONTAINED IN THIS MATERIAL SIZE DWG. NO. REV DRAWING IS THE SOLE PROPERTY OF A Top Panel <INSERT COMPANY NAME HERE>. ANY FINISH REPRODUCTION IN PART OR AS A WHOLE **NEXT ASSY USED ON** WITHOUT THE WRITTEN PERMISSION OF <INSERT COMPANY NAME HERE> IS SCALE: 1:2 WEIGHT: SHEET 2 OF 2 PROHIBITED. APPLICATION DO NOT SCALE DRAWING