Source

Source
- [STRING] ident (Optional)
- [ENUM] spoofed (Optional)
- [STRING] interface (Optional)

Node
- [STRING] location (0..1)
- [STRING] name (0..1)
- [STRING] ident (Optional)
- [ENUM] category (Optional)

Address
- [STRING] address (1)
- [STRING] netmask (0..1)
- [STRING] ident (Optional)
- [ENUM] category (Optional)
- [STRING] vlan-name (Optional)
- [INTEGER] vlan-num (Optional)

User
- [STRING] ident (Optional)
- [ENUM] category (Optional)

UserId
- [STRING] name (0..1)
- [INTEGER] number (0..1)
- [STRING] ident (Optional)
- [ENUM] type (Optional)
- [STRING] tty (Optional)

Process
- [STRING] name (1)
- [INTEGER] pid (0..1)
- [STRING] path (0..1)
- [STRING] arg (0..*)
- [STRING] env (0..*)
- [STRING] ident (Optional)

Service
- [STRING] name (0..1)
- [INTEGER] port (0..1)
- [PORTLIST] portlist (0..1)
- [STRING] protocol (0..1)
- [STRING] ident (Optional)
- [INTEGER] ip_version (Optional)
- [INTEGER] iana_protocol_number (Optional)
- [STRING] iana_protocol_name (Optional)

WebService
- [STRING] url (1)
- [STRING] cgi (0..1)
- [STRING] http-method (0..1)
- [STRING] arg (0..*)

SNMPService
- [STRING] oid (0..1)
- [INTEGER] messageProcessingModel (0..1)
- [INTEGER] securityModel (0..1)
- [STRING] securityName (0..1)
- [INTEGER] securityLevel (0..1)
- [STRING] contextName (0..1)
- [STRING] contextEngineID (0..1)
- [STRING] command (0..1)

Source → Node: 0..1
Node → Address: 0..*
Source → User: 0..1
User → UserId: 1..*
Source → Process: 0..1
Source → Service: 0..1