

*u<sup>b</sup>*

---

*b*

**UNIVERSITÄT  
BERN**

# Advanced Networking and Future Internet

## IX. Audio Compression

**Prof. Dr. Torsten Braun, Institut für Informatik**

Bern, 09.11.2020

# Advanced Networking and Future Internet: Audio Compression

## Table of Contents

1. Introduction
  1. Entropy Encoding
  2. Source Encoding
  3. Digitization of Audio Data
  4. Voice Encoding
2. Waveform Coding
  1. Differential PCM
  2. Linear Prediction
  3. Vector Quantization
3. Vocoding
4. Quality of Audio Encoding
5. MPEG-Audio
  1. MPEG-1 Audio
  2. MPEG-4 Audio



# 1. Introduction

- Uncompressed images, audio and video
- High storage and bandwidth requirements

## Examples

- Stereo audio signal with CD quality
  - 2 channels, sampling rate: 44.1 kHz, quantization: 16 bits per sample
  - Bandwidth: 1.4 Mbps
  - Memory for 1 hour: 605 MB
- Video sequence
  - HDTV: 1920 • 1080 pixels, 24 bits per pixel, 30 frames / s
  - Bandwidth: 1.5 Gbps



# 1. Introduction

## 1. Entropy Encoding

- is lossless,
- is used for different media, and
- does not consider media dependent characteristics.
- Data to be compressed are considered as a sequence of digital values.

### Examples

- Run Length Encoding (RLE)
- Statistical encoding
  - Encoding of characters with different numbers of bits
    - Frequent characters → short bit sequences
    - Infrequent characters → long bit sequences
  - Examples: Huffman and arithmetic encoding
- Directory methods
  - Patterns are often known a priori, e.g., in data bases.
  - Ordering of patterns in table and replacement by index prior to transmission
  - Example: Vector Quantization



# 1. Introduction

## 2. Source Encoding

- is mostly lossy and uses semantics of information to be encoded.
- Original and decoded data is similar but not identical.

### Examples

- Differential encoding
  - encodes differences between individual samples,
  - is useful for large amplitudes, but small differences between samples
  - can be lossy or lossless.
- Transformation encoding
  - Transformation between types of information, e.g., discrete cosine transform: pixel matrix  $\rightarrow$  frequency matrix
  - Transformation of data from one mathematical domain into another one that is more suitable for further compression
  - allows frequency-specific encoding, sub-band coding
  - Example: Discrete Cosine Transformation
    - Audio: one-dimensional DCT (in time)
    - Images: two-dimensional DCT (in space)



# 1. Introduction

## 3. Digitization of Audio Data

- Periodic measurement of amplitudes  
→ sequence of samples
- **A**nalog/**D**igital **C**onverter
  - Transformation of analog audio signal to digital samples
    - Sampling
      - Sampling theorem: sampling rate  $> 2 \cdot$  highest frequency
    - Quantization
      - Resolution depends on available bits for encoding the digital sample.
- **D**igital/**A**nalog **C**onverter
  - Transformation of digital samples into analog audio signal
- ISDN: **P**ulse **C**ode **M**odulation:  
8 bit sample every 125  $\mu$ s



# 1. Introduction

## 4. Voice Encoding


Voice encoding consists of

### – Analysis

- Encoding of voice as a compact set of parameters
  - Open loop
    - No feedback in encoding process
  - Closed loop
    - Extraction of parameters and encoding of differential values
    - *analysis by synthesis*
- Parameter presentation
  - Non voice-specific: **waveform** coding
  - Voice-specific: **vocoding** based on voice modeling

### – Synthesis

- Decoding of parameters and voice reconstruction







## 2. Waveform Coding

- Encoding in time domain
- Approximation of original waveform
- Better quality and more robust than vocoders, but less efficient (higher bandwidth)
- tries to determine relation between different samples

### Options


1. Differential coding: encoding relative to previous value; Calculation of difference can result in smaller values.
2. (Linear) Prediction: coding of difference between waveform and predicted one
3. Vector quantization



## 2. Waveform Coding

### 1. Differential PCM

- Difference of subsequent audio samples is often very small.
- Coding of difference values requires a few bits only.
- Delta Modulation: Encoding of difference values in 1 bit






## 2. Waveform Coding

### 2. Linear Prediction

- Calculation at time  $j$ :  
$$e(j) = y(j) - [a_1y(j-1) + a_2y(j-2) + \dots + a_py(j-p)]$$
  - $y(i)$ : sample
  - $a_i$ : prediction coefficients
  - [predicted value]
- $e(j)$  have a small value range, which allows encoding using a few bits only.
- Optimization of prediction coefficients  $a_i$  to minimize  $E = e^2(0) + e^2(1) + \dots + e^2(p)$ , e.g., every 10-30 ms.






## 2. Waveform Coding

## 3. Vector Quantization

- Vector table = codebook
- Calculation of the closest vector from codebook (smallest sum of error squares or mapping into space):

$$\epsilon(s, v) = \sum_{k=0}^{M-1} (s(k) - v(k))^2$$

- Transmission of vector **index** from table
- Problem: delay
- Codebook design:  
a priori (fixed) after training phase or adaptive






### 3. Vocoding

- Transformation into frequency domain and analysis of frequency spectrum
- Make use of rather slow rate of signal change
- Characterization of waveforms based on various parameters such as
  - voiced / unvoiced
  - signal energy
  - signal duration
  - frequency
- Reconstruction (synthesis) at receiver of a completely new waveform from transmitted parameters
  - sounds often synthetic
  - extremely low bit rates in the area of a few kbps
- Example: **C**ode-**E**xcited **L**inear **P**rediction
  - Pre-calculation of a finite set of waveform templates and storing them in template codebooks at sender and receiver
  - Assignment of waveform to best suited template
  - Accumulation and processing of several samples creates significant (algorithmic/processing) delay.




## 4. Quality of Audio Encoding





# 5. MPEG-Audio

## 1.1 MPEG-1





## 5. MPEG-Audio

### 1.2 MPEG-1 Layers

#### **Layers with increasing complexity and performance**

##### I. Digital Audio Cassette

- HiFi quality at 192 kbps per channel, delay: 20 ms

##### II. Digital Audio and Video Broadcasting

- Near CD quality at 128 kbps per channel, delay: 40 ms

##### III. CD quality over low bit rate channels

- CD quality at 64 kbps per channel, delay: 60 ms





## 5. MPEG-Audio

### 2. MPEG-4


- Efficient coding mechanisms for low bit rates, e.g., based on CELP
- Scalability
- Audio objects, e.g., background sound
- Synthetic / natural / hybrid encoding
- Text-to-speech
- Variants
  - Advanced Audio Coding
  - Audio Lossless Coding



## 5. MPEG-Audio

### 2.1 MPEG-4 Advanced Audio Coding


- AAC encoder
  - Waveform codec using modified DCT ( $\equiv$  1024 PCM input samples), stereo processing, temporal noise shaping, quantization and coding
- Spectral Band Replication
  - Regeneration (instead of transmission) of higher frequencies from lower frequencies using low-bit rate guidance data
- Parametric Stereo
  - Mono-downmix transmission, sophisticated stereo processing considering time and phase differences





## 5. MPEG-Audio

### 2.2 MPEG-4 Audio Lossless Coding



- Frame Block Partition
  - Division of audio data stream into frames and blocks
- Short/Long-Term Prediction
  - Calculation of residual error signal using linear prediction and forward adaptive prediction
- Joint Channel Coding
  - Prediction based on similarity of channels
- Entropy Coding

# Thanks

## for Your Attention

**Prof. Dr. Torsten Braun, Institut für Informatik**

Bern, 09.11.2020

$u^b$

---

<sup>b</sup>  
**UNIVERSITÄT  
BERN**

