

Sukun CMS API

Everything the CMS needs to create, edit, publish, and delete the app's content, plus the public waiting-list endpoint for the marketing site. All endpoints are Supabase Edge Functions and answer one shared JSON envelope.

01 · BASICS

Base URL & authentication

```
https://<PROJECT_REF>.supabase.co/functions/v1
```

Authenticate every `/admin` call one of two ways:

- **Server-to-server (recommended):** header `X-Admin-Key: <ADMIN_API_KEY>`. You'll receive the key privately — keep it on your server, never in browser code.
- **Admin user JWT:** `Authorization: Bearer <supabase-jwt>` of a user listed in the `admin_users` table.

The public `POST /waitlist` endpoint needs no auth at all.

Response envelope

```
{ "success": true, "data": { ... }, "error": null,  
  "meta": { "page": 1, "per_page": 25, "total": 42 } }  
  
{ "success": false, "data": null,  
  "error": { "code": "validation_failed", "message": "...", "meta": null } }
```

`error.code` values: `unauthorized` 401 · `not_found` 404 · `validation_failed` 400/405 · `conflict` 409 (unique violation) · `internal` 500.

Generic CRUD — same five routes for every resource

ROUTE	BEHAVIOR
GET /admin/{resource}	List. <code>?page=</code> <code>?per_page=</code> (max 100, default 25), <code>?search=</code> (case-insensitive match on the resource's text columns), plus the exact-match filters listed per resource, e.g. <code>?status=draft</code> .
GET /admin/{resource}/{id}	Single row.
POST /admin/{resource}	Create. JSON body of writable fields. Unknown fields are rejected with a message listing what is allowed. Returns 201 + the row.
PATCH /admin/{resource}/{id}	Partial update — send only the fields to change. Returns the updated row.
DELETE /admin/{resource}/{id}	Returns <code>{ "deleted": true }</code> . Rows still referenced elsewhere answer 400.

Field discovery: GET /admin/resources returns every resource's id column, writable fields, required-on-create fields, search columns, and filters — build your CMS forms from it instead of reading the SQL schema.

Resource catalog

Bilingual content is always an `*_ar` / `*_en` column pair (Arabic-first product).

RESOURCE	REQUIRED ON CREATE	LIST FILTERS
categories	domain, slug, name_ar, name_en	domain
narrators	name_ar, name_en	—
content	type, slug, title_ar, title_en	type, status, category_id, is_premium
media-assets	content_id, audio_url, duration_sec	content_id, dialect, narrator_id, locale
breathing-patterns	content_id, inhale_sec, exhale_sec, default_cycles	—
article-bodies	content_id, body_md_ar, body_md_en	—
quotes	text_ar, text_en	theme, is_active
quote-schedule	shown_on (date, is the id), quote_id	quote_id
courses	slug, title_ar, title_en	status, is_premium
course-lessons	course_id, position, title_ar, title_en	course_id
assessments	type, slug, title_ar, title_en	type, is_active
assessment-questions	assessment_id, position, text_ar, text_en, options	assessment_id
assessment-outcomes	assessment_id, code, title_ar, title_en	assessment_id
journal-prompts	text_ar, text_en	is_active
habit-templates	intent, name_ar, name_en	intent
badges	code, name_ar, name_en	—
challenges	title_ar, title_en, active_on	active_on
moods	id (smallint), code, label_ar, label_en, emoji, valence	—
context-tags	id (smallint), code, label_ar, label_en	—
waitlist	<i>read-only + delete</i>	country, source

Enum values

- content.type — meditation sleep_story soundscape sleep_music breathing_exercise grounding_exercise article game
- content.status / courses.status — draft published archived
- media-assets.dialect — msa khaleeji egyptian levantine; locale — ar en
- assessments.type — onboarding personality
- habit-templates.intent — build break; default_frequency — hourly daily weekly monthly

Publishing

Content is created as `draft` and invisible in the app until published:

```
POST /admin/content/{id}/publish    → status=published, published_at=now
POST /admin/content/{id}/unpublish  → back to draft
PATCH /admin/content/{id} {"status": "archived"} → archive
```

Media upload (audio & cover art)

1. `POST /admin/storage/upload-url` with `{"bucket": "audio", "path": "meditation/deep-calm/msa.m4a"}` → `{ signed_url, token }`. Buckets: `audio` (private), `covers` (public).
2. `PUT` the file bytes to `signed_url` with the right `Content-Type`.
3. Register it:
 - **Audio:** create a `media-assets` row whose `audio_url` is the *object path inside the bucket* (`meditation/deep-calm/msa.m4a`) — not a full URL. The app exchanges it for a short-lived signed URL at playback time.
 - **Covers:** the bucket is public — store the full URL in `cover_url`:
`https://<PROJECT_REF>.supabase.co/storage/v1/object/public/covers/<path>`

Plan limits (free-tier tuning)

```
GET    /admin/plan-limits
PUT    /admin/plan-limits {"tier":"free","feature":"meditation","max_count":1,"period":"month"}
(upsert)
DELETE /admin/plan-limits?tier=free&feature=meditation
```

Waitlist

```
GET /admin/waitlist?page=1&search=ahmad&country=Kuwait
GET /admin/waitlist/export → CSV (name,email,country,source,created_at)
```

Waitlist signup (marketing site)

```
POST /waitlist
{ "name": "Sara", "email": "sara@example.com", "country": "Kuwait", "source": "landing-page" }
```

- `name`, `email`, `country` required (≤ 200 chars); `source` optional, defaults to `website`.
- Success: 201 { "already_joined": false, "id": "...", "created_at": "..." }.
- Duplicate email (case-insensitive): 200 { "already_joined": true } — the form can always show "you're on the list".

06 • EXAMPLES

curl quick-start

```
BASE="https://<PROJECT_REF>.supabase.co/functions/v1"
KEY="X-Admin-Key: $ADMIN_API_KEY"

# list draft meditations
curl -H "$KEY" "$BASE/admin/content?type=meditation&status=draft"

# create a quote
curl -H "$KEY" -H "Content-Type: application/json" -X POST "$BASE/admin/quotes" \
  -d '{"text_ar": "النص", "text_en": "The text", "theme": "gratitude"}'

# schedule it for a day
curl -H "$KEY" -H "Content-Type: application/json" -X POST "$BASE/admin/quote-schedule" \
  -d '{"shown_on": "2026-09-01", "quote_id": "<uuid>"}'

# publish content
curl -H "$KEY" -X POST "$BASE/admin/content/<uuid>/publish"

# waitlist signup (public)
curl -H "Content-Type: application/json" -X POST "$BASE/waitlist" \
  -d '{"name": "Sara", "email": "sara@example.com", "country": "Kuwait"}'
```

Source of truth: `docs/api/cms-api.md` and `supabase/functions/admin/` in the Sukun repo. Ask for the base URL and `ADMIN_API_KEY` through a private channel.