

# Module Interface Specification for Physiotherapy Companion

Team 11, technically functional

Matthew Huynh

Cieran Diebolt

Vaisnavi Shanthamoorthy

Maham Siddiqui

Eman Ashraf

April 6, 2026

# 1 Revision History

| Date           | Version | Notes                |
|----------------|---------|----------------------|
| Nov 6 - Nov 14 | 1.0     | Preliminary Draft    |
| March 17 - ?   | 2.0     | Starting final draft |

# 2 Symbols, Abbreviations and Acronyms

See SRS Documentation at [SRS](#)

# Contents

|          |                                               |          |
|----------|-----------------------------------------------|----------|
| <b>1</b> | <b>Revision History</b>                       | <b>i</b> |
| <b>2</b> | <b>Symbols, Abbreviations and Acronyms</b>    | <b>i</b> |
| <b>3</b> | <b>Introduction</b>                           | <b>1</b> |
| <b>4</b> | <b>Notation</b>                               | <b>1</b> |
| <b>5</b> | <b>Module Decomposition</b>                   | <b>2</b> |
| <b>6</b> | <b>MIS</b>                                    | <b>2</b> |
| 6.1      | Module - Account Creation . . . . .           | 2        |
| 6.1.1    | Uses . . . . .                                | 3        |
| 6.1.2    | Syntax . . . . .                              | 4        |
| 6.1.3    | Semantics . . . . .                           | 6        |
| 6.1.4    | Environment Variables . . . . .               | 7        |
| 6.1.5    | Assumptions . . . . .                         | 7        |
| 6.1.6    | Access Routine Semantics - Exported . . . . . | 7        |
| 6.1.7    | Local Functions . . . . .                     | 8        |
| 6.1.8    | Access Routine Semantics - Local . . . . .    | 10       |
| 6.2      | Module - Valid user . . . . .                 | 10       |
| 6.2.1    | Uses . . . . .                                | 10       |
| 6.2.2    | Syntax . . . . .                              | 11       |
| 6.2.3    | Semantics . . . . .                           | 11       |
| 6.2.4    | Environment state variables . . . . .         | 11       |
| 6.2.5    | Assumptions . . . . .                         | 11       |
| 6.2.6    | Access Routine Semantics - Exported . . . . . | 11       |
| 6.2.7    | Local Routines . . . . .                      | 12       |
| 6.2.8    | Access Routine Semantics - Local . . . . .    | 13       |
| 6.3      | Module - User Account . . . . .               | 13       |
| 6.3.1    | Uses . . . . .                                | 13       |
| 6.3.2    | Syntax . . . . .                              | 14       |
| 6.3.3    | Semantics . . . . .                           | 14       |
| 6.3.4    | Environment Variables . . . . .               | 14       |
| 6.3.5    | Assumptions . . . . .                         | 15       |
| 6.3.6    | Access Routine Semantics - Exported . . . . . | 15       |
| 6.3.7    | Local Functions . . . . .                     | 15       |
| 6.3.8    | Access Routine Semantics - Local . . . . .    | 15       |
| 6.4      | Module - Exercise Data . . . . .              | 15       |
| 6.4.1    | Uses . . . . .                                | 15       |
| 6.4.2    | Syntax . . . . .                              | 19       |
| 6.4.3    | Semantics . . . . .                           | 22       |

|        |                                               |    |
|--------|-----------------------------------------------|----|
| 6.4.4  | Environment Variables . . . . .               | 22 |
| 6.4.5  | Assumptions . . . . .                         | 23 |
| 6.4.6  | Access Routine Semantics - Exported . . . . . | 23 |
| 6.4.7  | Local Functions . . . . .                     | 24 |
| 6.4.8  | Access Routine Semantics - Local . . . . .    | 25 |
| 6.5    | Module - User Activity . . . . .              | 25 |
| 6.5.1  | Uses . . . . .                                | 25 |
| 6.5.2  | Syntax . . . . .                              | 26 |
| 6.6    | Module - Profile Activity . . . . .           | 27 |
| 6.6.1  | Syntax . . . . .                              | 27 |
| 6.6.2  | Semantics . . . . .                           | 27 |
| 6.6.3  | Environment Variables . . . . .               | 28 |
| 6.6.4  | Assumptions . . . . .                         | 28 |
| 6.6.5  | Access Routine Semantics . . . . .            | 28 |
| 6.6.6  | Local Functions . . . . .                     | 28 |
| 6.7    | Module - Analysis Control Flow . . . . .      | 29 |
| 6.7.1  | Uses . . . . .                                | 29 |
| 6.7.2  | Syntax . . . . .                              | 31 |
| 6.7.3  | Semantics . . . . .                           | 33 |
| 6.7.4  | Environment variables . . . . .               | 33 |
| 6.7.5  | Assumptions . . . . .                         | 33 |
| 6.7.6  | Access Routine Semantics . . . . .            | 33 |
| 6.7.7  | Local Functions . . . . .                     | 33 |
| 6.8    | Module - Analyze . . . . .                    | 34 |
| 6.8.1  | Uses . . . . .                                | 34 |
| 6.8.2  | Syntax . . . . .                              | 34 |
| 6.8.3  | Semantics . . . . .                           | 34 |
| 6.8.4  | Environment variables . . . . .               | 34 |
| 6.8.5  | Assumptions . . . . .                         | 35 |
| 6.8.6  | Access Routine Semantics . . . . .            | 35 |
| 6.8.7  | Local Functions . . . . .                     | 35 |
| 6.9    | Module - Feedback . . . . .                   | 35 |
| 6.9.1  | Uses . . . . .                                | 35 |
| 6.9.2  | Syntax . . . . .                              | 35 |
| 6.9.3  | Semantics . . . . .                           | 35 |
| 6.9.4  | Assumptions . . . . .                         | 36 |
| 6.9.5  | Access Routine Semantics . . . . .            | 36 |
| 6.9.6  | Local Functions . . . . .                     | 36 |
| 6.10   | Module - Metrics . . . . .                    | 36 |
| 6.10.1 | Uses . . . . .                                | 36 |
| 6.10.2 | Syntax . . . . .                              | 36 |
| 6.10.3 | Semantics . . . . .                           | 36 |

|          |                                    |           |
|----------|------------------------------------|-----------|
| 6.10.4   | Assumptions . . . . .              | 36        |
| 6.10.5   | Access Routine Semantics . . . . . | 36        |
| 6.10.6   | Local Functions . . . . .          | 36        |
| 6.10.7   | Local Functions . . . . .          | 36        |
| 6.11     | Module - Draw . . . . .            | 37        |
| 6.11.1   | Uses . . . . .                     | 37        |
| 6.11.2   | Syntax . . . . .                   | 38        |
| 6.11.3   | Semantics . . . . .                | 38        |
| 6.11.4   | Assumptions . . . . .              | 38        |
| 6.11.5   | Access Routine Semantics . . . . . | 39        |
| 6.11.6   | Local Functions . . . . .          | 39        |
| 6.12     | Module - UI . . . . .              | 40        |
| 6.12.1   | Uses . . . . .                     | 40        |
| 6.12.2   | Syntax . . . . .                   | 40        |
| 6.12.3   | Semantics . . . . .                | 40        |
| 6.12.4   | Assumptions . . . . .              | 40        |
| 6.12.5   | Access Routine Semantics . . . . . | 40        |
| 6.12.6   | Local Functions . . . . .          | 40        |
| 6.12.7   | Local Functions . . . . .          | 40        |
| <b>7</b> | <b>Appendix A</b>                  | <b>42</b> |

### 3 Introduction

The following document details the Module Interface Specifications for the PhysioCompanion app. The application is designed to identify users performing prescribed exercises and provide feedback on their form. This tool uses computer vision, specifically OpenCV and MediaPipe, to analyze user video recording and perform analysis. Please note that certain modules exhibit functional overlap, as their respective operations perform equivalent decomposed tasks across different modules.

Complementary documents include the [System Requirement Specifications](#) and [Module Guide](#). The full documentation and implementation can be found at [here](#).

### 4 Notation

The structure of the MIS for modules comes from [Hoffman and Strooper \(1995\)](#), with the addition that template modules have been adapted from [Ghezzi et al. \(2003\)](#). The mathematical notation comes from Chapter 3 of [Hoffman and Strooper \(1995\)](#). For instance, the symbol  $:=$  is used for a multiple assignment statement and conditional rules follow the form  $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | \dots | c_n \Rightarrow r_n)$ .

The following table summarizes the primitive data types used by Physiotherapy Companion.

| Data Type      | Notation     | Description                                                                                   |
|----------------|--------------|-----------------------------------------------------------------------------------------------|
| character      | char         | a single symbol or digit                                                                      |
| integer        | $\mathbb{Z}$ | a number without a fractional component in $(-\infty, \infty)$                                |
| natural number | $\mathbb{N}$ | a number without a fractional component in $[1, \infty)$                                      |
| real           | $\mathbb{R}$ | any number in $(-\infty, \infty)$                                                             |
| float          | $F$          | floating point numbers within (approx.) $(-1.798 \times 10^{308}, 1.798 \times 10^{308})$     |
| object         | $X$          | an abstract representation of a collection of the above, similar to tuple                     |
| array          | $a$          | a collection of a single data type, $n$ entries of the form $(a_0, a_1, a_2, \dots, a_{n-1})$ |
| list           | $L$          | an array of non-fixed length                                                                  |

This specification of PhysioCompanion uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In

addition, PhysioCompanion uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

## 5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

| Level 1                  | Level 2                                                                                               |
|--------------------------|-------------------------------------------------------------------------------------------------------|
| Hardware-Hiding Module   |                                                                                                       |
| Behaviour-Hiding Module  | User Interface Module<br>Home Module<br>Main Module<br>Draw Module                                    |
| Software Decision Module | Database Management Module<br>Generator Module<br>Metrics Module<br>Analyze Module<br>Feedback Module |

Table 1: Module Hierarchy

## 6 MIS

This section describes individual module specifications.

*See Appendix A for information about the variables used throughout this document.*

### 6.1 Module - Account Creation

This module enables the creation of an account for users. It uses a database to store any information that is essential for other modules to perform their actions. A database was used for its ease of manipulation and its comprehensive, multi-functional nature.

The database tables related to this module are:

1. User data (**users**): This table consists of information such as name, role, email, birth-day, license\_no/invite\_code, createdAt and physioID.
2. Invite\_codes (**inviteCodes**): This table contains all valid invite codes that will be used to validate patient account creation on the application.

3. Valid licenses (`validLicenses`): This is used for verification and validation purposes for a physiotherapist account creation.

### 6.1.1 Uses

All the variables used in each class related to account creation are described below.

**/technically-functional/mobile/app/(auth)/create-physio.tsx,**

**/technically-functional/mobile/app/(auth)/create-patient.tsx**

*Variables used in both of the above files are listed below.*

```
const [name, setName] = useState("");
```

Manages the full name input field; initializes as empty string.

```
const [email, setEmail] = useState("");
```

Manages the email address input field; initializes as empty string.

```
const [password, setPassword] = useState("");
```

Manages the password input field; initializes as empty string.

```
const [loading, setLoading] = useState(false);
```

Boolean flag that indicates form submission status. Set to `true` during API calls to disable inputs and show loading indicators.

```
const [birthday, setBirthday] = useState("");
```

Manages the birthday input field; initializes as empty string; valid format is YYYY-MM-DD.

Unique variable in **create-patient.tsx**:

```
const [inviteCode, setInviteCode] = useState("");
```

Manages the invitation code input field; initializes as empty string; valid format is 6 capital alphanumeric characters.

Unique variable in **create-physio.tsx**:

```
const [licenseNumber, setLicenseNumber] = useState("");
```

Manages the physiotherapist license number input field; initializes as empty string; Required for physiotherapist verification; valid format is XX-123456.

**/technically-functional/mobile/lib/authService.ts**

{Imported Variables}

**auth**            Firebase Authentication instance imported from `"/firebase"`. Used for all authentication operations including email checking, sign-in, sign-out, and account creation.



**db** Firestore database instance imported from `"/firebase"`. Used for reading and writing user data, license validation, and invite code management.

{Imported Types}

**None** No external types are imported in this file. All type definitions are inferred or defined inline.

{Imported Functions}

**createUserWithEmailAndPassword**

Firestore Auth function from `"firebase/auth"`. Used to create new user accounts in Firebase Authentication for both physiotherapist and patient registration.

**doc** Firestore function from `"firebase/firestore"`. Used to create document references for users, validLicenses, and inviteCodes collections.

**getDoc** Firestore function from `"firebase/firestore"`. Used to fetch user documents, license documents, and invite code documents from Firestore.

**setDoc** Firestore function from `"firebase/firestore"`. Used to create new user documents in Firestore during registration.

**updateDoc** Firestore function from `"firebase/firestore"`. Used to mark invite codes as used after patient registration.

**serverTimestamp**

Firestore function from `"firebase/firestore"`. Used to set createdAt timestamps on new user documents.

### 6.1.2 Syntax

#### Exported Constants

##### *authService.ts*

**export const registerPatient**

Async function constant that registers a new patient account.

**export const registerPhysio**

Async function constant that registers a new physiotherapist account.

**export const checkEmailExists**

Async function constant that checks if an email address is already registered in the system.

**export const licenseFormatValid**

Async function that validates the format of a physiotherapist license number.

*create-patient.tsx, create-physio.tsx*

See 6.12 for UI export variables.

## Exported Access Programs

*create-patient.tsx*

See 6.12 for UI export programs

*create-physio.tsx*

See 6.12 for UI export programs

*authService.ts*

| Input                                                                                                     | Output                                                                                        | Exceptions                                                                                   |
|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| <b>checkEmailExists(email):</b> Checks if an email is already registered in Firebase Authentication.      |                                                                                               |                                                                                              |
| email: string - User's email address                                                                      | Promise<boolean> - Returns true if email already exists, false otherwise                      | Error - Throws error if there is an error checking email.                                    |
| <b>licenseFormatValid(licenseNumber):</b> Validates physiotherapist license number format (XX-123456).    |                                                                                               |                                                                                              |
| licenseNumber: string - PT license number                                                                 | boolean - Returns true if format is valid, false otherwise                                    | Error - Throws error if there is an error checking licenseNumber.                            |
| <b>registerPhysio:</b> Registers a new physiotherapist account into the database after license validation |                                                                                               |                                                                                              |
| params: {name: string, email: string, password: string, licenseNumber: string}                            | Promise<{uid: string, role: "physio"}> - Returns user ID and role                             | Error - Invalid license format, license not verified, Firebase Auth error                    |
| <b>registerPatient:</b> Registers a new patient account into the database.                                |                                                                                               |                                                                                              |
| params: {name: string, email: string, password: string, inviteCode: string, birthday: string}             | Promise<{uid: string, role: "patient"}> - Returns user ID and role, marks invite code as used | Error - Invalid invite code, inactive/used code, missing physio link, or Firebase Auth error |

Table 2: Exported functions

## Exported Access Programs

p: (name, email, password, licenseNumber, birthday)

**pt**: (name, email, password, inviteCode, birthday)

**user**: p or pt

**e**: user.email

**n**: user.name

**pw**: user.password

**lno**: user.licenseNumber

**code**: user.inviteCode

**bday**: user.birthday

**cat**: user.createdAt

**pid**: user.physioId (for **pt** only)

**v**: user.verified (for **p** only)

**u**: user.uid

**del**: user.deleted (for **pt** only)

**db**: **users** table in database

**db'**: newer version of **users** table

$i, j, k, l, m, n \in \{0 - 9\}$

$a, b \in \{A - Z\}$

$E(e)$ : 'checkEmailExists(e)'

$L(l)$ : 'licenseFormatValid(l)'

$Phy(p)$ : 'registerPhysio(p)'

$Pt(pt)$ : 'registerPatient(pt)'

Function definitions:

$E(e) \implies e \in db.email$

$L(l) \implies \exists l \mid l = (a + b + '-' + 'i' + 'j' + 'k' + 'l' + 'm' + 'n') \in validLicenses$

$Phy(p) \implies db' = db \cup \mathbf{users} \mapsto \{uid \mapsto \{cat, e, lno, n, role : 'physio', v\}\}$

$Pt(pt) \implies db' = db \cup \mathbf{users} \mapsto \{uid \mapsto \{cat, del, e, code, n, pid, role : 'patient'\}\}$

### 6.1.3 Semantics

#### State Variables

See [here](#) for a list of additional state variables.

**first**: user 1

**second**: user 2

**first\_uid**: uid of user 1

**second\_uid**: uid of user 2

#### State Invariant

$\forall first, second \in db, first\_uid \cap second\_uid = \emptyset$

All users have different uids.

#### 6.1.4 Environment Variables

*screen*: The application's display to the user

*touchscreen*: Users will click on the screen to select their desired action

#### 6.1.5 Assumptions

- Patients with the same name have different birthdays.
- Only one person can access user information in the database at a time since many values that are exported are asynchronous values.

#### 6.1.6 Access Routine Semantics - Exported

##### Exported access routines

See [here](#) for state variables being used.

*checkEmailExists*:  $E(e)$

**Pre-condition:**  $e \in db.email$

**Function:**  $E(e) = \text{true}$

**Post-condition:** Returns true if email already exists in database(**users**), false otherwise.

*licenseFormatValid*:  $L(l)$

**Pre-condition:**  $l \in db.validLicenses$

**Function:**  $L(l) = \text{true}$

**Post-condition:** Returns true if license exists in database(**validLicenses**), false otherwise.

*registerPhysio*:  $Phy(p)$

**Pre-condition:**  $(p.name \cap p.email \cap p.pw \cap p.lno \cap p.bday \neq \emptyset) \cap (L(p.lno)) \cap (\neg(E(p.email)))$

**Function:**  $Phy(p)$

**Post-condition:**  $p \in db$

*registerPatient*:  $Pt(pt)$

**Pre-condition:**  $(p.name \cap p.email \cap p.pw \cap p.code \cap p.bday \neq \emptyset) \cap (\neg(E(p.email)))$

**Function:**  $Pt(pt)$

**Post-condition:**  $p \in db$

### 6.1.7 Local Functions

#### *create-patient.tsx*

| Input                                                                | Output                                                          | Exceptions                                                                                                                                                                                                                                                                              |
|----------------------------------------------------------------------|-----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>CreatePatient:</b> Physiotherapist registration screen component. |                                                                 |                                                                                                                                                                                                                                                                                         |
| props: none                                                          | JSX.Element - Renders patient registration form with validation | <b>Validations performed:</b> <ul style="list-style-type: none"><li>• Password: min 6 chars + at least one number</li><li>• Birthday: YYYY-MM-DD format</li><li>• Email: existence check via checkEmailExists()</li><li>• Invite code validation handled by registerPatient()</li></ul> |

Table 3: Account module: CreatePatient function

#### *create-physio.tsx*

| Input                                                               | Output                                                                  | Exceptions                                                                                                                                                                                                                                                                                |
|---------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>CreatePhysio:</b> Physiotherapist registration screen component. |                                                                         |                                                                                                                                                                                                                                                                                           |
| props: none                                                         | JSX.Element - Renders physiotherapist registration form with validation | <b>Validations performed:</b> <ul style="list-style-type: none"><li>• Password: min 6 chars + at least one number</li><li>• Birthday: YYYY-MM-DD format</li><li>• Email: existence check via checkEmailExists()</li><li>• License number validation handled by registerPhysio()</li></ul> |

Table 4: Account module: CreatePhysio function

Both files

| Input                                                                               | Output        | Exceptions                                                                                                                                                                                                                                       |
|-------------------------------------------------------------------------------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>passwordCheck():</b> Internal helper function for password validation.           |               |                                                                                                                                                                                                                                                  |
| params: {password: string}                                                          | string   null | <ul style="list-style-type: none"> <li>• Returns "Password must be at least 6 characters long" if length &lt; 6</li> <li>• Returns "Password must contain at least one number" if no numbers present</li> <li>• Returns null if valid</li> </ul> |
| <b>validateBirthday():</b> Internal helper function for birthday format validation. |               |                                                                                                                                                                                                                                                  |
| params: {birthday: string}                                                          | string   null | <ul style="list-style-type: none"> <li>• Returns "Please enter birthday in YYYY-MM-DD format" if format entered is invalid</li> <li>• Returns null if valid</li> </ul>                                                                           |

Table 5: Account module: CreatePatient and CreatePhysio common functions

*Note: CreatePatient and registerPatient have an important distinction although they seem similar. CreatePatient is the React component which manages the interface, while registerPatient handles the backend logic for making a new patient account. CreatePhysio and registerPhysio have the same distinction.*

**Local Routines (definitions)**

p: (name, email, password, licenseNumber, birthday)

pt: (name, email, password, inviteCode, birthday)

user: p or pt

e: user.email

n: user.name

pw: user.password

lno: user.licenseNumber

code: user.inviteCode

bday: user.birthday

$Pc(pw)$ : 'passwordCheck(pw)'

$Vb(bday)$ : 'validateBirthday(bday)'

Function definitions:

$Pc(pw) \implies pw.length \geq 6 \cap \exists d \mid d \in \{0-9\} \cap d \in pw$

$\text{Date} = \text{'YYYY-MM-DD'} \mid \text{'YYYY'} \in \{0000 - 9999\} \cap \text{'MM'} \in \{01 - 12\} \cap \text{'DD'} \in \{01 - 31\}$

$Vb(bday) \implies bday \in \text{Date}$

*Note: See [6.12](#) for `CreatePhysio` and `CreatePatient` interface specifications.*

### 6.1.8 Access Routine Semantics - Local

## 6.2 Module - Valid user

This module's purpose is to check whether a potential user is authorized to create an account. For feasible implementation purposes, a file with hard coded invite codes and license numbers will be used. The actions accomplishing the module's purpose are within the `registerPhysio` and `registerPatient` functions, which contain internal validation of `inviteCode` and `licenseNumber`.

### 6.2.1 Uses

|                            |                                                                                                                                                               |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>params</code>        | Input object containing patient registration data. Type: <code>{name: string, email: string, password: string, inviteCode: string, birthday: string}</code> . |
| <code>code</code>          | Normalized invite code. Type: <code>string</code> . Computed as <code>params.inviteCode.trim().toUpperCase()</code> .                                         |
| <code>inviteRef</code>     | Firestore document reference to <code>inviteCodes/code</code> . Type: <code>DocumentReference</code> .                                                        |
| <code>inviteSnap</code>    | Firestore document snapshot. Type: <code>DocumentSnapshot</code> .                                                                                            |
| <code>invite</code>        | Data from invite code document. Contains fields: <code>active</code> (boolean), <code>used</code> (boolean), <code>physioId</code> (string).                  |
| <code>physioId</code>      | uid of the physiotherapist that provided invite code. Type: <code>string</code> .                                                                             |
| <code>cred</code>          | Firebase Auth user credential. Type: <code>UserCredential</code> .                                                                                            |
| <code>uid</code>           | Firebase Authentication unique user ID. Type: <code>string</code> .                                                                                           |
| <code>db</code>            | Firestore database instance. Imported from <code>./firebase</code> .                                                                                          |
| <code>auth</code>          | Firebase Authentication instance. Imported from <code>./firebase</code> .                                                                                     |
| <code>licenseNumber</code> | State variable managing license number input. Type: <code>string</code> . Initialized as empty string.                                                        |
| <code>lic</code>           | Normalized license number. Type: <code>string</code> . Computed as <code>params.licenseNumber.trim().toUpperCase()</code> .                                   |
| <code>licSnap</code>       | Firestore document snapshot from <code>validLicenses</code> collection. Type: <code>DocumentSnapshot</code> .                                                 |

### 6.2.2 Syntax

#### Exported Constants

See *authService.ts* exported constants in 6.1.2.

For interface elements, see 6.12.

#### Exported Access Programs

See Table 2 for *registerPatient* and *registerPhysio* details respectively.

#### Function definitions:

This module has components that have been defined in the Account Creation module. See *function definitions in 6.1.2*.

### 6.2.3 Semantics

#### State Variables

See 6.12 for UI state variables.

pt: a patient user type

p: a physio user type

code: a patient invite code

lno: a PT's license number

users: `users` table in database

#### State Invariant

$code['used'] = true \implies \exists pt \mid pt.inviteCode == code$

$\exists p.uid \in users \implies p.licenseNumber \in validLicenses$

### 6.2.4 Environment state variables

*Not applicable*

### 6.2.5 Assumptions

- All practicing physiotherapists have an active and valid license.
- All active invite codes are used by new and active patients only.
- Invite codes and license numbers are unique.

### 6.2.6 Access Routine Semantics - Exported

#### Exported access routines

See [account creation semantics](#) for details of respective functions.



### 6.2.7 Local Routines

Portions that are pertinent to the module are elaborated on below.

#### **registerPatient: Internal Validation Steps**

The function performs the following sequential validations on the invite code:

1. **Existence Check:** Query Firestore `inviteCodes` collection for document with ID = `normalize(inviteCode)`. If not found, throw "Invalid invite code."
2. **Active Check:** If `invite.active`  $\neq$  `true`, throw "Invite code inactive."
3. **Usage Check:** If `invite.used` = `true`, throw "Invite code already used."
4. **Physio Link Check:** If `physioId` = `null` or does not exist, throw "Invite code missing physio link."

Only after all validations pass does the function proceed to:

1. Create Firebase Auth user
2. Create Firestore user document with `role:"patient"` and `uid`
3. Mark invite code as used with `usedBy:uid`

#### **registerPhysio: Internal Validation Steps**

The function performs the following sequential validations on the license number:

1. **Format Check:** Validate license number format using `licenseFormatValid()`. License must match pattern: two uppercase letters, a dash, and six digits (e.g., ON-123456). If format is invalid, throw "Invalid license format (example: ON-123456)."
2. **Existence Check:** Query Firestore `validLicenses` collection for document with ID equal to the normalized license number. If not found, throw "License not verified."
3. **Active Check:** If the license document has `active` field not equal to `true`, throw "License not verified."

Only after all validations pass does the function proceed to:

1. Create Firebase Auth user using `createUserWithEmailAndPassword()`
2. Create Firestore user document with `role:"physio"`, `verified:true`, and `uid`
3. Return `{uid, role:"physio"}`

### 6.2.8 Access Routine Semantics - Local

## 6.3 Module - User Account

This module's purpose is facilitate data manipulation within the user database tables. It was created as a separate component to simplify implementation. Account creation generates a single instance of one of the following objects:

- **Patient object:** {uid, email, name, role: "patient", birthday?, physioId?, inviteCode?, createdAt?, deleted?}
- **Physio object:** {uid, email, name, role: "physio", licenseNumber?, verified?, createdAt?}

### 6.3.1 Uses

#### *useraccount.ts*

**uid:** string; Unique identifier for the user. Used for fetching user data, updating user information, deleting user accounts, and associating patients with physiotherapists.

**email:** string; User's email address for authentication and communication. Used for email existence verification, credential validation, and user authentication.

**name:** string; User's full name. Used for searching users by name, retrieving user database information by name, and patient account deletion verification.

**role:** "patient" | "physio"; User's role in the system. Used for filtering patients by physiotherapist and categorizing users during database information retrieval.

**physioId?:** string; Reference to the physiotherapist assigned to a patient. Used for retrieving all patients belonging to a specific physiotherapist.

**deleted?:** boolean; Soft delete flag indicating whether the user account has been deleted. Used as a filter when querying active patients and during user account deletion operations.

**birthday?:** string; User's birthday. Used as part of patient profile information.

**licenseNumber?:** string; Professional license number for physiotherapists. Used as part of physiotherapist profile information.

**verified?:** boolean; Flag indicating whether a physiotherapist's license has been verified. Used in physiotherapist profile information.

**inviteCode?:** string; Invitation code for patient registration. Used as profile information and account creation validation.

`createdAt?: any`; Timestamp of user account creation. Defined in the interface but not set or read by current methods. Recommended for future audit trail implementation.

### 6.3.2 Syntax

#### Exported Constants

Not Applicable

#### Exported Access Programs

Not Applicable. This module consists of an interface.

### 6.3.3 Semantics

#### State Variables

##### *useraccount.ts*

`private usersCollection: string` Internal state variable storing the Firestore collection name for user documents.

`private validLicensesCollection: string` Internal state variable storing the Firestore collection name for physiotherapist licenses.

`private inviteCodesCollection: string` Internal state variable storing the Firestore collection name for invitation codes.

#### State Invariant

`users`: 'users' database table

`u1`: user 1

`u2`: user 2

`Phy`: set of all users that have role = 'physio'

`Pt`: set of all users that have role = 'patient'

$\forall u1, u2 \in users, u1 \neq u2 \implies u1.email \neq u2.email$

$\forall u1 \in Phy, u1.physioId = \emptyset$

$\forall u1 \in Phy, u1.verified = true$

$\forall u1 \in Pt, u1.deleted = true \implies u1.uid \in \emptyset$

$\forall u1 \in P, u2 \in Phy, \exists u1.physioId = u2.uid$

$\forall id \in \{users.uid\}, \exists u1 | u1.uid = id \cap u1 \in users$

$\forall u1 \in users \cap u1 \in Phy \implies u1 \notin P$

$\forall u2 \in users \cap u2 \in Pt \implies u2 \notin Phy$

### 6.3.4 Environment Variables

Not applicable

### 6.3.5 Assumptions

- If two people have the same name, then it is assumed they have different different roles.
- No two PTs have the same license numbers.

### 6.3.6 Access Routine Semantics - Exported

Not applicable

### 6.3.7 Local Functions

Not applicable. All helper functions are defined as private class functions.

### 6.3.8 Access Routine Semantics - Local

Not applicable

## 6.4 Module - Exercise Data

This module manages exercises that will be performed by the patient. It consists of a data layer (*exerciseData.ts*) and a UI layer (*exercises.tsx*, *[id].tsx*). The data layer provides database operations using the `userExercises` table. The UI layer fulfills the purpose of interfacing between the user and the module and is discussed in [6.12](#). This structure was chosen to enable:

- High cohesion: all constituents serve the same business purpose
- Low coupling: there is no direct communication present between the front end and database. They communicate through the backend.
- Easy maintenance: low coupling allows for maintenance of a single 'part' of the module without affecting the rest of the module.

### 6.4.1 Uses

#### *exerciseData.ts - Functions*

`collection` Firestore function from "firebase/firestore". Used to reference a database collection for exercise operations.

`deleteDoc` Firestore function from "firebase/firestore". Used to delete an exercise document from the `userExercises` collection.

`doc` Firestore function from "firebase/firestore". Used to create a document reference when fetching a single exercise.

`getDoc` Firestore function from "firebase/firestore". Used to fetch a single exercise document by ID.

`getDocs` Firestore function from "firebase/firestore". Used to fetch multiple exercise documents.

`query` Firestore function from "firebase/firestore". Used to create filtered queries on exercise collections.

`where` Firestore function from "firebase/firestore". Used to specify filter conditions (userid, title) in exercise queries.

`addDoc` Firestore function from "firebase/firestore". Used to add a new exercise document to the userExercises collection.

`updateDoc` Firestore function from "firebase/firestore". Used to update exercise fields (description, reps, sets, title) in an existing document.

### **exerciseData.ts - Variables**

`db` Firestore database instance from "./firebase". Used as the database reference for all Firestore operations related to this file.

### **exerciseData.ts - Types**

**Exercise (type)** Type definition defined locally within this file. Represents the exercise data structure with properties: id, title, subtitle, description, demoText, enabled, tags, sets, reps.

### **exercises.tsx - Functions**

`useEffect` React hook from "react". Used to perform side effects when user data, role, or selected user changes.

`useState` React hook from "react". Used to manage local state for user data, exercises, modal visibility, and form values.

`getExercisesById` Function from *exerciseData.ts*. Used to fetch patient's assigned exercises for the patient view.

`getGeneralExercises` Function from *exerciseData.ts*. Used to fetch the master exercise library for physiotherapists.

`getSelectedExercises` Function from *exerciseData.ts*. Used to fetch currently assigned exercises for checkbox state and modal preloading.

`addUserExercise` Function from *exerciseData.ts*. Used to assign an exercise to a patient when a physiotherapist checks a checkbox.

**removeUserExercise** Function from *exerciseData.ts*. Used to remove an exercise assignment when a physiotherapist unchecks a checkbox.

**updateUserExercise** Function from *exerciseData.ts*. Used to save modified exercise instructions (description, sets, reps).

**getCurrentUser** Function from "@lib/temp". Used to fetch the currently authenticated user on component mount.

**getUserRole** Function from "@lib/roleStore". Used to determine if the current user is a patient or physiotherapist.

**getSelectedUserID** Function from "@lib/profileActivity". Used to get the patient ID selected by a physiotherapist.

### **exercises.tsx - Variables**

**userData** State variable storing current authenticated user. Initialized via `getCurrentUser()`.

**userRole** State variable storing user role. Initialized via `getUserRole()`.

**selectedUser**  
State variable storing selected patient ID for physio view. Initialized via `getSelectedUserID()`.

**userExercises**  
State variable storing patient's assigned exercises. Initialized via `getExercisesById()`.

**selectedIds**  
State variable storing titles of checked exercises. Initialized via `getSelectedExercises()`.

**physioExercises**  
State variable storing master exercise library. Initialized via `getGeneralExercises()`.

**roleReady** Boolean state variable indicating role has been loaded.

**modalVisible**  
Boolean state variable controlling modal visibility.

**modalText** State variable storing custom description text in modal.

**modalSets** State variable storing custom sets value in modal.

`modalReps`    State variable storing custom reps value in modal.

`modalExercise`  
              State variable storing exercise being modified in modal.

### *exercises.tsx - Types*

`Exercise`    Type from "../lib/exerciseData". Used to type exercise objects, exercise lists, and modal exercise state.

`UserData`    Type from "@lib/useraccount". Used to type the current user data state.

`UserRole`    Type from "@lib/roleStore". Used to type the user role state ("patient" — "physio").

### *[id].tsx - UI Functions (React Native & Navigation)*

`useLocalSearchParams`  
              Expo Router hook from "expo-router". Used to extract the id parameter from the navigation route.

`useRouter`    Expo Router hook from "expo-router". Used for navigation (goBack and navigate to record screen).

`useVideoPlayer`  
              Expo Video hook from "expo-video". Used to create and configure the video player instance for exercise demonstration videos.

`VideoView`    Component from "expo-video". Used to render the video player UI for exercise demonstrations.

`View`         React Native component from "react-native". Used as a container for layout.

`Text`         React Native component from "react-native". Used to display exercise title, subtitle, description, sets, reps, and UI text.

`StyleSheet`   React Native function from "react-native". Used to create component styles.

`Pressable`    React Native component from "react-native". Used to create touchable buttons (Record, Back, Go Back).

`ScrollView`   React Native component from "react-native". Used to enable scrolling for exercise details content.

`require`       React Native asset loading function. Used to load the local demonstration video file from previously stored tutorial video.

### [id].tsx - React Hooks & Data(Functions)

- useEffect**     React hook from "react". Used to fetch exercise data when the component mounts or when the id parameter changes.
- useState**     React hook from "react". Used to manage the currentExercise state variable.
- getExercise**  
Function from "../..lib/exerciseData". Used to fetch a single exercise document by its ID from the Firestore database. This is a data access function, not UI-related.

### [id].tsx - Variables

- id**             Route parameter extracted from useLocalSearchParams. Contains the exercise ID passed from navigation. Used to fetch the specific exercise from the database.
- videoSource**  
Local variable that conditionally loads a video asset. Returns require() path only for "Seated Knee Flexion-Extension Exercise", otherwise returns null.
- player**        Video player instance created by useVideoPlayer. Used to control video playback (loop, play, pause) in the VideoView component.

### [id].tsx - Imported Types

- Exercise**      Type definition imported from "../..lib/exerciseData". Represents the exercise data structure with properties: id, title, subtitle, description, demoText, enabled, tags, sets, reps. Used to type the currentExercise state.

## 6.4.2 Syntax

### Exported Constants

No exported constants are present in any of the reviewed files (exerciseData.ts, exercises.tsx, [id].tsx).

### Exported Access Programs

*exerciseData.ts*



| Input                                                                                                                  | Output                                                                                              | Exceptions                                                                     |
|------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
| <b>getExercisesById(uid):</b> Retrieves all exercises assigned to a specific user from the "userExercises" collection. |                                                                                                     |                                                                                |
| uid: string - User ID of the patient                                                                                   | Promise<Exercise[]   undefined> - Returns array of exercises or undefined if none found             | Error - Throws error if there is an issue fetching exercises from Firestore    |
| <b>getExercise(exid):</b> Fetches a single exercise document by its ID.                                                |                                                                                                     |                                                                                |
| exid: string - Exercise document ID                                                                                    | Promise<Exercise   undefined> - Returns exercise object or undefined if not found                   | Error - Throws error if there is an issue fetching the exercise from Firestore |
| <b>getGeneralExercises():</b> Retrieves the master exercise library from the "exercises" collection.                   |                                                                                                     |                                                                                |
| None                                                                                                                   | Promise<Exercise[]   undefined> - Returns array of all general exercises or undefined if none found | Error - Throws error if there is an issue fetching exercises from Firestore    |
| <b>getSelectedExercises(uid):</b> Fetches the current list of exercises assigned to a specific user.                   |                                                                                                     |                                                                                |
| uid: string - User ID of the patient                                                                                   | Promise<Exercise[]   undefined> - Returns array of assigned exercises or undefined if none          | Error - Throws error if there is an issue fetching exercises from Firestore    |
| <b>removeUserExercise(uid, exerciseTitle):</b> Deletes an exercise assignment from a user's exercise list.             |                                                                                                     |                                                                                |
| uid: string - User ID of the patient,<br>exerciseTitle: string - Title of the exercise to remove                       | Promise<void> - Returns nothing on successful deletion                                              | Error - Throws error if there is an issue deleting the document from Firestore |
| <b>addUserExercise(uid, exercise):</b> Creates a new exercise assignment for a specific user.                          |                                                                                                     |                                                                                |
| uid: string - User ID of the patient,<br>exercise: Exercise - Exercise object to assign                                | Promise<void> - Returns nothing on successful creation                                              | Error - Throws error if there is an issue adding the document to Firestore     |

*Continued on next page*

| Input                                                                                                                                                                                                                                              | Output                                               | Exceptions                                                                   |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|------------------------------------------------------------------------------|
| <b>updateUserExercise(uid, exerciseTitle, exerciseDescription, exerciseSets, exerciseReps):</b> Modifies an existing user exercise's instructions (description, sets, reps).                                                                       |                                                      |                                                                              |
| uid: string - User ID of the patient,<br>exerciseTitle: string - Title of the exercise,<br>exerciseDescription: string - New description,<br>exerciseSets: string - Number of sets (optional),<br>exerciseReps: string - Number of reps (optional) | Promise<void> - Returns nothing on successful update | Error - Throws error if there is an issue updating the document in Firestore |

Table 6: Exported Access Programs - exerciseData.ts

*exercises.tsx*

| Input                                                                                                                                | Output                                                                                                                                | Exceptions                                                      |
|--------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|
| <b>ExercisesTab():</b> Default exported React component that renders the exercises interface for both patients and physiotherapists. |                                                                                                                                       |                                                                 |
| None - Takes no props                                                                                                                | JSX.Element - Returns a React component with role-based views (patient exercise list or physiotherapist exercise selection interface) | None - No exceptions thrown; returns null while role is loading |

Table 7: Exported Access Programs - exercises.tsx

*[id].tsx*

There are no exported access programs in this file. The file exports only the default React component `ExerciseDetail`, which is a presentation component rather than an access program.

The file **consumes** the following access programs from `exerciseData.ts`:

- `getExercise()` - Fetches exercise data by ID

### 6.4.3 Semantics

#### State Variables

userexercises: userExercises table in the database

exercises: exercises table in user database

users: users table in the database

ue: modified exercise object

uue: unmodified exercise object

assigned: list of assigned exercises

u1: user

exid: exercise id

ex: exercise (object)

#### State Invariant

$\forall e1, e2 \in exercises, e1 \neq e2 \implies e1.title \neq e2.title \cap e1.description \neq e2.description$

$\forall e1 \in exercises, \exists e1.reps, e1.sets \in \mathbb{Z}^+$

$\forall e1, e2 \in userexercises, e1.title = e2.title \not\Rightarrow (e1.id = e2.id \cup e1.reps = e2.reps \cup e1.sets = e2.sets \cup e1.userid = e2.userid)$

$\forall ue, e1 \in userexercises \mid ue.userid = e1.userid \cap ue.title = e1.title, \exists ue.description \neq e1.description \cup ue.sets \neq e1.sets \cup ue.reps \neq e1.reps$

$\forall user \in users, |assigned| \geq 0$

Function definitions

u1: user

uid: uid (e.g. u1.uid)

title: exercise title

Ux: 'getExercisesById(uid)'

Ge: 'getExercise(exid)'

Gen: 'getGeneralExercises()'

Sel: 'getSelectedExercises(uid)'

R: 'removeUserExercise(uid, ex.title)'

A: 'addUserExercise(uid, ex)'  $Ux(uid): \forall ex \in userexercises Ux(uid) = [ex] \mid ex.userid = uid$

$Ge(exid): \forall ex \in exercises, Ge(exid) = [ex] \mid ex.id = exid$

$Gen(): Gen() \rightarrow \{ex\} \in exercises$

$Sel(uid): \forall ex \in userexercises, Sel(uid) = [ex] \mid ex.userid = uid$

$R(uid, title): userexercises' = userexercises - [ex] \mid ex.title = title \cap ex.userid = uid$

$A(uid, ex): userexercises' = userexercises \cup [ex] \mid ex \in exercises \cap (ex \in userexercises \cap ex.userid = uid)$

### 6.4.4 Environment Variables

Not applicable

### 6.4.5 Assumptions

- For the same user, no two exercises with the same name are present. Conversely, no two exercises with the same names can be assigned by a PT to one patient.

### 6.4.6 Access Routine Semantics - Exported

db: database

userexercises: `userExercises` table in the database

exercises: `exercises` table in user database

users: `users` table in the database

ue: modified `exercise` object

assigned: list of assigned exercises

u1: user

exid: exercise id

ex: exercise (object)

*getExercisesById*

**Pre-condition:**  $u1.uid = ex.userid \in \{userexercises.userid\}$

**Function:** `getExercisesById(u1.uid)`

**Post-condition:**  $[ex]$

*getExercise*

**Pre-condition:**  $exid \in \{exercises.id\} \cap exid \neq \emptyset$

**Function:** `getExercises(ex.exid)`

**Post-condition:**  $ex \iff ex.id = exid$

*getGeneralExercises*

**Pre-condition:**  $\exists exercises \in db$  **Function:** `getGeneralExercises()`

**Post-condition:**  $[ex] \neq \emptyset$

*getSelectedExercises*

**Pre-condition:**  $u1 \in users \cap u1.uid = ex.userid$

**Function:** `getSelectedExercises(u1.uid)`

**Post-condition:**  $[ex]$

*removeUserExercise*

**Pre-condition:**  $u1 \in users \cap u1.uid = ex.userid \cap title = ex.title \in userexercises$  **Function:** `getSelectedExercises(u1.uid, ex.title)`

**Post-condition:**  $user[exercises]' = user[exercises] - ex$

*addUserExercise*

**Pre-condition:**  $u1 \in users \cap ex \in exercises$

**Function:** addUserExercise(u1.uid, ex)

**Post-condition:**  $user[exercises]' = user[exercises] + ex$

*updateUserExercise*

**Pre-condition:**  $u1 \in users \cap ex \in exercises \cap ex.userid = u1.uid$

**Function:** addUserExercise(u1.uid, ex.title, ex.description, ex.sets, ex.reps)

**Post-condition:**  $ue = ex \cap (ex(u1.uid, ue.title) \cup ex(u1.uid, ue.description) \cup ex(u1.uid, ue.sets) \cup ex(u1.uid, ue.reps))$

#### 6.4.7 Local Functions

exerciseData.ts

There are no local routines/helper functions present in this file.

exercises.tsx

These functions are UI related. Note that they are included here for readability. They are also in section 6.12.

| Input                                                                                             | Output                                                                                       | Exceptions |
|---------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|------------|
| <b>openExercise(ex):</b> Navigates to the exercise detail page for the selected exercise.         |                                                                                              |            |
| <b>ex:</b> Exercise - The exercise object to view                                                 | <b>void</b> - Navigates to "/exercise/[id]" route using router.push()                        | None       |
| <b>toggleSelection(ex):</b> Toggles exercise selection for a patient (physiotherapist view only). |                                                                                              |            |
| <b>ex:</b> Exercise - The exercise to toggle                                                      | <b>void</b> - Updates selectedIds state and calls onChecked() or onUnchecked()               | None       |
| <b>onChecked(ex):</b> Assigns an exercise to the selected patient.                                |                                                                                              |            |
| <b>ex:</b> Exercise - The exercise to assign                                                      | <b>void</b> - Calls addUserExercise(selectedUser, ex) to save to database and logs selection | None       |
| <b>onUnchecked(id):</b> Removes an exercise assignment from the selected patient.                 |                                                                                              |            |

*Continued on next page*

| Input                                                                                                                                                                                                                             | Output                                                                                                                                                                            | Exceptions |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>id:</b> <code>string</code> - The exercise title to remove                                                                                                                                                                     | <b>void</b> - Calls <code>removeUserExercise(selectedUser, id)</code> to delete from database and logs deselection                                                                | None       |
| <b>modifyInstructions(ex):</b> Opens modal to edit exercise instructions for a patient.                                                                                                                                           |                                                                                                                                                                                   |            |
| <b>ex:</b> <code>Exercise</code> - The exercise to modify                                                                                                                                                                         | <b>Promise&lt;void&gt;</b> - Sets <code>modalExercise</code> state, fetches existing instructions via <code>getSelectedExercises()</code> , and opens modal with preloaded values | None       |
| <b>updateInstructions(ex, newDesc, newSets, newReps):</b> Saves modified exercise instructions to the database.                                                                                                                   |                                                                                                                                                                                   |            |
| <b>ex:</b> <code>Exercise</code> - The exercise being modified, <b>newDesc:</b> <code>string</code> - New description, <b>newSets:</b> <code>string</code> - New sets value, <b>newReps:</b> <code>string</code> - New reps value | <b>void</b> - Calls <code>updateUserExercise(selectedUser, ex.title, newDesc, newSets, newReps)</code> and logs the update                                                        | None       |

Table 8: Local Routines - exercises.tsx

#### 6.4.8 Access Routine Semantics - Local

Not Applicable: they are UI related.

### 6.5 Module - User Activity

This module handles video data of a patient's recorded exercise(s).

#### 6.5.1 Uses

- name
- exercise

- date
- duration
- recent\_video
- recent\_analysis
- overall\_analysis

### 6.5.2 Syntax

#### Exported Constants

*analysis*: recent\_analysis

*recent\_video*: recent\_video

*analysis\_report*: analysis\_report

#### Exported Access Programs

| Access Routine Name                                                                         | Input                                       | Output                 | Exceptions                                             |
|---------------------------------------------------------------------------------------------|---------------------------------------------|------------------------|--------------------------------------------------------|
| <b>Description:</b> adds analysis results to user activity history                          |                                             |                        |                                                        |
| add_analysis_to_user_act                                                                    | <i>user_acc_p</i><br><i>recent_analysis</i> | NA                     | UserNotFoundError<br>SaveError                         |
| <b>Description:</b> saves video recording for user account                                  |                                             |                        |                                                        |
| save_video                                                                                  | <i>user_acc_p</i><br><i>recent_video</i>    | NA                     | UserNotFoundError<br>UploadError<br>VideoTooShortError |
| <b>Description:</b> retrieves analysis data for a specific date                             |                                             |                        |                                                        |
| get_analysis                                                                                | <i>user_acc_p</i><br><i>date</i>            | <i>recent_analysis</i> | UserNotFoundError<br>NoAnalysisError<br>DownloadError  |
| <b>Description:</b> Saves overall analysis (generated by Generator) to User Activity table. |                                             |                        |                                                        |
| save_overall_analysis                                                                       | <i>user_acc_p</i><br><i>date</i>            | <i>recent_analysis</i> | UserNotFoundError<br>NoAnalysisError<br>DownloadError  |

Table 9: Exported Routines

## 6.6 Module - Profile Activity

This module displays past exercises, allows viewing of user profile, and directs to the Performance Statistics Generator module. PTs are able to comment on their patient's submissions.

### 6.6.1 Syntax

#### Exported Constants

NA

#### Exported Access Programs

| Access Routine Name                                                 | Input                           | Output                                | Exceptions                                |
|---------------------------------------------------------------------|---------------------------------|---------------------------------------|-------------------------------------------|
| <b>Description:</b> Displays user profile information               |                                 |                                       |                                           |
| view_profile                                                        | <i>Name</i>                     | UserAccount_P<br>OR<br>UserAccount_PT | User_not_found<br>Download_error          |
| <b>Description:</b> Displays analysis report for user               |                                 |                                       |                                           |
| display_report                                                      | <i>Name</i><br><i>email</i>     | NA                                    | required_field_empty<br>patient_not_found |
| <b>Description:</b> Displays summary information                    |                                 |                                       |                                           |
| display_summary                                                     | <i>Email</i><br><i>Password</i> | NA                                    | wrong_email_password                      |
| <b>Description:</b> Shows patient's past exercises                  |                                 |                                       |                                           |
| p_past_exercises                                                    | <i>Email</i>                    | NA                                    | no_activity                               |
| <b>Description:</b> Provides physical therapist feedback on patient |                                 |                                       |                                           |
| PT_feedback_on_P                                                    | <i>PTcomment</i>                | NA                                    | User_not_found<br>Download_error          |

Table 10: Home Exported Access Routines

### 6.6.2 Semantics

#### State Variables

NA

#### State Invariant

NA



### 6.6.3 Environment Variables

NA

### 6.6.4 Assumptions

TBD

### 6.6.5 Access Routine Semantics

TBD

### 6.6.6 Local Functions

| Access Routine Name                             | Input | Output                                | Exceptions       |
|-------------------------------------------------|-------|---------------------------------------|------------------|
| <b>Description:</b> Gets profile from generator |       |                                       |                  |
| get_profile.gen                                 | NA    | UserAccount_P<br>OR<br>UserAccount_PT | Cannot_access_db |

Table 11: Account Management Access Routines

## 6.7 Module - Analysis Control Flow

This module is responsible for transmitting frames for analysis and the reverse.

### 6.7.1 Uses

*server.py*

*server.py - Functions*

|                  |                                                                                                                           |
|------------------|---------------------------------------------------------------------------------------------------------------------------|
| Flask            | From "flask". Used to create the Flask web application instance and define API routes.                                    |
| jsonify          | From "flask". Used to convert Python dictionaries to JSON responses for API endpoints.                                    |
| request          | From "flask". Used to parse incoming HTTP request data, including JSON payloads and form data.                            |
| CORS             | From "flask_cors". Used to enable Cross-Origin Resource Sharing, allowing the mobile app to communicate with the backend. |
| threading.Lock   | From Python standard library "threading". Used to create a lock for thread-safe access to the pose backend state.         |
| base64.b64decode | From Python standard library "base64". Used to decode base64-encoded image strings sent from the mobile app.              |
| np.frombuffer    | From "numpy". Used to convert decoded image bytes into a NumPy array for image processing.                                |
| cv.imdecode      | From "cv2" (OpenCV). Used to decode a NumPy array into an OpenCV image format (BGR).                                      |
| cv.cvtColor      | From "cv2" (OpenCV). Used to convert images between color spaces (BGR to GRAY) for brightness calculation.                |
| cv.resize        | From "cv2" (OpenCV). Used to resize frames to a standard dimension (640x480) before processing.                           |
| cv.flip          | From "cv2" (OpenCV). Used to mirror images horizontally when using the front camera.                                      |

`os.path.dirname`

From Python standard library "os". Used to get the directory path of the current file.

`os.path.abspath`

From Python standard library "os". Used to get the absolute path of the current file.

`os.path.join`

From Python standard library "os". Used to construct the full file path to the pose landmarker model.

`os.environ` From Python standard library "os". Used to set environment variables (OPENCV\_VIDEOIO\_

`exists` From "os.path". Used to check if the pose landmarker model file exists at the specified path.

`RuntimeError`

Python built-in exception. Used to raise an error when the model file is missing.

`threading` Python standard library module. Used for thread management and locks.

### *server.py - Variables*

`app` Flask application instance created for running the server.

`pose_app` Global instance of the PoseBackend class that manages pose detection state.

`here` Variable storing the directory path of the current Python file.

`model_path` Variable storing the full file system path to the pose\_landmarker\_heavy.task model file.

### *server.py - Types*

`None` No external types are explicitly imported. Type hints use built-in types (str, bool, float, int) and OpenCV/NumPy types implicitly.

### *poseService.ts*

### *poseService.ts - Functions*

`axios.post` From "axios". Used to send HTTP POST requests to the backend server for frame processing, pre-checking, and resetting the backend state.

### *poseService.ts - Variables*

|                         |                                                                                                                                                                                  |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>SERVER_URL</code> | Constant string variable storing the backend server address and port ( <code>http://10.0.0.34 : 5001</code> ). Used as the base URL for all API calls to the Flask server.       |
| <code>mirrored</code>   | Local boolean variable within <code>processFrame</code> and <code>precheckFrame</code> functions. Set to true when facing is "front", indicating the image needs to be mirrored. |
| <code>res</code>        | Local variable storing the axios response object containing the backend response data.                                                                                           |
| <code>headers</code>    | Configuration object passed to <code>axios.post</code> specifying Content-Type as "application/json".                                                                            |
| <code>timeout</code>    | Configuration value set to 15000ms for <code>processFrame</code> and <code>resetBackend</code> , 10000ms for <code>precheckFrame</code> .                                        |

### *poseService.ts - Types*

|                         |                                                                                                                              |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <code>Side</code>       | Type union defining valid knee sides: "RIGHT" — "LEFT". Used to specify which knee is being analyzed.                        |
| <code>Facing</code>     | Type union defining camera orientation: "front" — "back". Used to determine if image mirroring is needed.                    |
| <code>Landmark</code>   | Type defining a 3D pose landmark with x, y, z coordinates (all numbers). Represents a detected body point.                   |
| <code>Connection</code> | Type defining a tuple [number, number] representing an edge between two landmark indices. Used to draw skeleton connections. |

#### `ProcessFrameResponse`

Type defining the response structure from the `process_frame` endpoint, containing landmarks, connections, metrics, and optional error.

#### `PrecheckFrameResponse`

Type defining the response structure from the `precheck_frame` endpoint, containing ok status, lighting and visibility flags, and message.

## 6.7.2 Syntax

### Exported Constants

*poseService.ts*

There are no exported constants.

*server.py*

NA

## Exported Access Programs

server.py

| Input                                                                                                                                       | Output                                                                                  | Exceptions                                                                      |
|---------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| <b>reset_backend():</b> Flask route handler for POST /reset endpoint. Resets pose analyzer state and restarts calibration.                  |                                                                                         |                                                                                 |
| None                                                                                                                                        | JSON - Returns {ok: true}                                                               | Exception - Throws exception if reset fails                                     |
| <b>precheck_frame():</b> Flask route handler for POST /precheck_frame endpoint. Validates lighting, frame composition, and knee visibility. |                                                                                         |                                                                                 |
| JSON body:<br>imageBase64:<br>string, side:<br>string, mirrored:<br>boolean, legsOnly:<br>boolean                                           | JSON - Returns {ok, tooDark, inFrame, kneeVisible, message} or error response           | Exception - Throws exception if frame decoding fails or processing error occurs |
| <b>process_frame():</b> Flask route handler for POST /process_frame endpoint. Processes frame for pose detection and metric calculation.    |                                                                                         |                                                                                 |
| JSON body:<br>imageBase64:<br>string, side:<br>string, mirrored:<br>boolean, legsOnly:<br>boolean                                           | JSON - Returns {landmarks, connections, metrics} or error response with default metrics | Exception - Throws exception if frame decoding fails or processing error occurs |

Table 12: Exported Access Programs - server.py

poseService.ts

| Input                                                                                                                                | Output                                                              | Exceptions                                                        |
|--------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|
| <b>processFrame(imageBase64, side, facing):</b> Sends a single video frame to the backend for pose detection and metric calculation. |                                                                     |                                                                   |
| imageBase64:<br>string - Base64 encoded image frame, side: Side - "RIGHT" or "LEFT", facing: Facing - "front" or "back"              | Promise<ProcessFrame> - Returns landmarks, connections, and metrics | Error - Throws error if request fails or timeout occurs (15000ms) |

*Continued on next page*

| Input                                                                                                                             | Output                                                                                    | Exceptions                                                        |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| <b>precheckFrame(imageBase64, side, facing):</b> Performs pre-recording environment check including lighting and knee visibility. |                                                                                           |                                                                   |
| imageBase64: string - Base64 encoded image frame, side: Side - "RIGHT" or "LEFT", facing: Facing - "front" or "back"              | Promise<PrecheckFrame> - Returns ok status, lighting flags, visibility flags, and message | Error - Throws error if request fails or timeout occurs (10000ms) |
| <b>resetBackend():</b> Resets the backend pose analyzer state and restarts calibration.                                           |                                                                                           |                                                                   |
| None                                                                                                                              | Promise<void> - Resolves when reset is complete                                           | Error - Throws error if request fails or timeout occurs (15000ms) |

Table 13: Exported Access Programs - poseService.ts

### 6.7.3 Semantics

#### State Variables

$f$ : set of video frames

$c$ : calibrating

$cal\_time\_left$ : time left for calibration

#### State Invariant

$\forall b \in \text{Base64} : \text{b64\_to\_bgr\_image}(b) \in F \cup \{\emptyset\}$

$\forall$  operations on  $\text{pose\_app}$  : lock must be acquired first

$\text{resetBackend}() \implies \text{analyzer} = \text{newAnalyzer}() \wedge c = \text{true} \cap \text{cal\_time\_left} = 10.0$

### 6.7.4 Environment variables

### 6.7.5 Assumptions

### 6.7.6 Access Routine Semantics

### 6.7.7 Local Functions

| Access Routine Name                            | Input              | Output            | Exceptions        |
|------------------------------------------------|--------------------|-------------------|-------------------|
| <b>Description:</b> Gets starting form of user |                    |                   |                   |
| get_initial_form                               | <i>input_frame</i> | unprocessed_frame | InvalidFrameError |

Table 14: Local Access Routines (Main)

## 6.8 Module - Analyze

### 6.8.1 Uses

### 6.8.2 Syntax

Exported Constants

Exported Access Programs

| Access Routine Name                                                      | Input                   | Output          | Exceptions                               |
|--------------------------------------------------------------------------|-------------------------|-----------------|------------------------------------------|
| <b>Description:</b> gets metrics from metrics module                     |                         |                 |                                          |
| latest_metrics                                                           | <i>rt_metrics</i>       | <i>NA</i>       | InsufficientDataError                    |
| <b>Description:</b> sends overall analysis to Feedback module            |                         |                 |                                          |
| send_analysis_to_feedback                                                | <i>recent_analysis</i>  | <i>NA</i>       | AnalysisNotFoundError                    |
| <b>Description:</b> performs real time analysis                          |                         |                 |                                          |
| analysis_rt                                                              | <i>processed_frames</i> | recent_analysis | User_not_found<br>Download_error         |
| <b>Description:</b> overall analysis (given at end of recording)         |                         |                 |                                          |
| analysis_overall                                                         | <i>video</i>            | recent_analysis | ConnectionError<br>InsufficientDataError |
| <b>Description:</b> module will correct form (eg. if angle is too small) |                         |                 |                                          |
| adjust_metrics                                                           | <i>processed_frame</i>  | rt_metrics      | UndetectedFormError                      |
| <b>Description:</b> send overall analysis to Database module             |                         |                 |                                          |
| send_analysis_to_db                                                      | <i>overall_analysis</i> | <i>NA</i>       | User_not_found<br>Download_error         |

Table 15: Access Routines for Analysis Module

### 6.8.3 Semantics

State Variables

TBD

State Invariant

TBD

### 6.8.4 Environment variables

*NA*

### 6.8.5 Assumptions

### 6.8.6 Access Routine Semantics

### 6.8.7 Local Functions

| Access Routine Name                                                   | Input | Output                                | Exceptions                       |
|-----------------------------------------------------------------------|-------|---------------------------------------|----------------------------------|
| <b>Description:</b> Gets initial landmarks from the starting position |       |                                       |                                  |
| get_initial_landmarks                                                 | NA    | UserAccount_P<br>OR<br>UserAccount_PT | User_not_found<br>Download_error |

Table 16: Access Routines for Analysis Module

## 6.9 Module - Feedback

This module is responsible for delivering the feedback (e.g. to adjust form) to the Main module.

### 6.9.1 Uses

### 6.9.2 Syntax

Exported Constants

Exported Access Programs

| Access Routine Name                                                                                                | Input                        | Output | Exceptions         |
|--------------------------------------------------------------------------------------------------------------------|------------------------------|--------|--------------------|
| <b>Description:</b> feedback to user given after analysis                                                          |                              |        |                    |
| ex_feedback_to_main                                                                                                | <i>feedback</i>              | NA     | FeedbackEmptyError |
| <b>Description:</b> instructions given by analysis to construct feedback that will be forwarded to the Main module |                              |        |                    |
| given_instruct                                                                                                     | <i>feedback_instructions</i> | NA     | InsEmptyError      |

Table 17: Access Routines for Analysis Module

### 6.9.3 Semantics

State Variables

TODO

State Invariant

TODO



#### 6.9.4 Assumptions

TODO

#### 6.9.5 Access Routine Semantics

TODO

#### 6.9.6 Local Functions

| Access Routine Name                                                               | Input                        | Output          | Exceptions    |
|-----------------------------------------------------------------------------------|------------------------------|-----------------|---------------|
| <b>Description:</b> Constructs feedback based on instructions from Analyze module |                              |                 |               |
| construct_feedback                                                                | <i>feedback_instructions</i> | <i>feedback</i> | InsEmptyError |

Table 18: Feedback Access Routines

### 6.10 Module - Metrics

This module measures metrics (*angle*, *duration*, *height*) that are necessary to construct any corrections to the user's form.

TODO

#### 6.10.1 Uses

#### 6.10.2 Syntax

Exported Constants

Exported Access Programs

#### 6.10.3 Semantics

State Variables

State Invariant

#### 6.10.4 Assumptions

#### 6.10.5 Access Routine Semantics

#### 6.10.6 Local Functions

#### 6.10.7 Local Functions

| Access Routine Name                                                                       | Input                  | Output                                           | Exceptions   |
|-------------------------------------------------------------------------------------------|------------------------|--------------------------------------------------|--------------|
| <b>Description:</b> obtains a frame from Main module                                      |                        |                                                  |              |
| get_frame                                                                                 | <i>processed_frame</i> | NA                                               | NoFrameError |
| <b>Description:</b> calculates metrics from frame provided by Main module                 |                        |                                                  |              |
| calculate_frame                                                                           | <i>processed_frame</i> | <i>angle</i><br><i>height</i><br><i>duration</i> | NoFrameError |
| <b>Description:</b> obtains metrics that need to be adjusted by the user (calls Analysis) |                        |                                                  |              |
| fixed_frame                                                                               | <i>NA</i>              | <i>fixed_metrics</i>                             | NoFrameError |

Table 19: Access Routines for Analysis Module

| Access Routine Name                                                         | Input                                        | Output          | Exceptions      |
|-----------------------------------------------------------------------------|----------------------------------------------|-----------------|-----------------|
| <b>Description:</b> measures the angle between the starting and final plane |                                              |                 |                 |
| measure_angle                                                               | <i>initial_plane</i><br><i>final_plane</i>   | <i>angle</i>    | FrameEmptyError |
| <b>Description:</b> measures difference in initial and final height         |                                              |                 |                 |
| measure_height                                                              | <i>initial_height</i><br><i>final_height</i> | <i>height</i>   | FrameEmptyError |
| <b>Description:</b> measures duration of the performed exercise             |                                              |                 |                 |
| measure_duration                                                            | <i>initial_time</i><br><i>final_time</i>     | <i>duration</i> | FrameEmptyError |

Table 20: Metrics Access Routines

## 6.11 Module - Draw

This module is responsible for drawing landmarks by using *MediaPipe* (external library).

### 6.11.1 Uses

- starting\_frame
- processed\_frames\_list
- unprocessed\_frames\_list
- feedback\_instructions

### 6.11.2 Syntax

#### Exported Constants

- *can\_record*: `good_to_record`
- *fixing\_instructions*: `feedback_instructions`
- *processed*: `processed_frames_list`

#### Exported Access Programs

| Access Routine Name                                                                                 | Input                        | Output                             | Exceptions                             |
|-----------------------------------------------------------------------------------------------------|------------------------------|------------------------------------|----------------------------------------|
| <b>Description:</b> Checks if the recording environment is appropriate (e.g., lighting, background) |                              |                                    |                                        |
| <code>record_check</code>                                                                           | <i>starting_frame</i>        | <i>good_to_record</i>              | UserNotFound<br>Error<br>DownloadError |
| <b>Description:</b> Analyzes the user's starting form against a correct form model                  |                              |                                    |                                        |
| <code>form_check</code>                                                                             | <i>processed_frames_list</i> | <i>feedback_instructions</i>       | UserNotFound<br>Error<br>DownloadError |
| <b>Description:</b> Overlays pose estimation points onto the video feed for user feedback           |                              |                                    |                                        |
| <code>draw_points</code>                                                                            | <i>unprocessed_frames</i>    | <code>processed_frames_list</code> | UserNotFound<br>Error<br>DownloadError |

Table 21: Draw Access Routines

### 6.11.3 Semantics

#### State Variables

*frames*: `unprocessed_frames_list`

#### State Invariant

### 6.11.4 Assumptions

- User's complete form is in frame.
- The application will not draw points if the user does not comply with instructions given by *record\_check*.

### 6.11.5 Access Routine Semantics

TODO

### 6.11.6 Local Functions

| Access Routine Name                                      | Input                     | Output                       | Exceptions  |
|----------------------------------------------------------|---------------------------|------------------------------|-------------|
| <b>Description:</b> Calls MediaPipe's draw functionality |                           |                              |             |
| mpipe_draw                                               | <i>unprocessed_frames</i> | <i>processed_frames_list</i> | MPbusyError |

Table 22: Account Management Access Routines

## 6.12 Module - UI

NA

### 6.12.1 Uses

### 6.12.2 Syntax

Exported Constants

Exported Access Programs

| Access Name | Routine | Input | Output                                | Exceptions                       |
|-------------|---------|-------|---------------------------------------|----------------------------------|
| placeholder |         | NA    | UserAccount_P<br>OR<br>UserAccount_PT | User_not_found<br>Download_error |

### 6.12.3 Semantics

TBD

State Variables

TODO

State Invariant

TODO

### 6.12.4 Assumptions

### 6.12.5 Access Routine Semantics

### 6.12.6 Local Functions

### 6.12.7 Local Functions

TODO

| Access Routine Name | Input                                                                                                                        | Output                                | Exceptions                                                                                                       |
|---------------------|------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|------------------------------------------------------------------------------------------------------------------|
| placeholder         | <i>Name</i><br><i>Role</i><br><i>Birthday</i><br><i>License_no/</i><br><i>Invite_code</i><br><i>Email</i><br><i>Password</i> | UserAccount_P<br>or<br>UserAccount_PT | Input_format_invalid<br>Required_field_empty<br>Account_already_exists<br>Incorrect_creds<br>Invite_code_expired |

Table 24: UI Access Routines

## References

- Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. *Fundamentals of Software Engineering*. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.
- Daniel M. Hoffman and Paul A. Strooper. *Software Design, Automated Testing, and Maintenance: A Practical Approach*. International Thomson Computer Press, New York, NY, USA, 1995. URL <http://citeseer.ist.psu.edu/428727.html>.

## 7 Appendix A

For clarity and readability, the variables used throughout the document are provided below.

Table 25: Variable used throughout MIS

| Name             | Type            | Description                                                             | Used in sections |
|------------------|-----------------|-------------------------------------------------------------------------|------------------|
| name             | String          | Name of the user                                                        | 7.1              |
| role             | String          | Values can be PT or patient                                             | 7.1              |
| email            | String          | Used as login ID                                                        | 7.1              |
| password         | String          | Set by user for login purposes                                          | 7.1              |
| birthday         | String          | User's birthday for verification                                        | 7.1              |
| license_no       | Int             | Verification of PT                                                      | 7.1              |
| invite_code      | String          | Given by PT to patient for registration                                 | 7.1              |
| is_valid         | Boolean         | Used to check validity of user (invite_code, license_no)                | ?                |
| acc_id           | Int             | Identifier assigned to app users                                        | ?                |
| acc_double       | Boolean         | Indicates whether an account already exists in the system               | ?                |
| date             | String          | Date (YYYYMMDD)                                                         | 7.1              |
| time             | String          | Time (s)                                                                | 7.2              |
| recent_analysis  | ADT             | Most recently generated analysis                                        | 7.1              |
| recent_report    | Record          | Generated report of recent_video                                        | TBD              |
| recent_video     | String (JSON)   | Last video recorded by patient                                          | TBD              |
| video            | String (JSON)   | A video in the user database                                            | TBD              |
| report           | Record          | Report(s) sent to Generator module for analysis OR requested by patient | TBD              |
| ex_instruct      | String          | Performance instructions of requested exercise                          | TBD              |
| sets             | String          | Number of sets given by PT                                              | 7.1              |
| repetitions      | String          | Repetitions of exercise per set                                         | 7.1              |
| rest_time        | String          | Rest time between sets                                                  | 7.1              |
| leg_landmarks    | Array           | MediaPipe output of leg                                                 | 7.4              |
| processed_frame  | Image           | Video frame with overlaid markers                                       | 7.4              |
| PT_comment       | String          | PT's comment on patient activity                                        | 7.3              |
| overall_analysis | Abstract object | the overall analysis of all patient activity                            | 7.4              |

Table 25: Variable used throughout MIS (continued)

| Name                            | Type                | Description                                                 | Used in sections |
|---------------------------------|---------------------|-------------------------------------------------------------|------------------|
| processed_frames_list           | List(Image object)  | list of processed_frames                                    | 7.3              |
| feedback_instructions           | Abstract Object     | instructions given from analysis to feedback module         | 7.3              |
| fixed_metrics                   | float               | corrected metrics                                           | 7.3              |
| initial/final_plane/time/height | float               | initial and final measurements                              | 7.3              |
| ins_ui                          | String              | PT's comment on patient activity                            | TBD              |
| unprocessed_frames              | List(Image objects) | Unprocessed frames list                                     | TBD              |
| rt_metrics                      | List(of float)      | Real-time metrics                                           | TBD              |
| input_frame                     | Image               | Input frame                                                 | TBD              |
| exercise                        | String              | Selected exercise                                           | TBD              |
| insights                        | String              | Generated insights                                          | TBD              |
| all_reports                     | List[report]        | All reports are stored in a list                            | TBD              |
| starting_frame                  | Image               | The last frame before recording                             | TBD              |
| good_to_record                  | String              | A message informing user that the system is ready to record | TBD              |

## Appendix — Reflection

The information in this section will be used to evaluate the team members on the graduate attribute of Problem Analysis and Design.

The purpose of reflection questions is to give you a chance to assess your own learning and that of your group as a whole, and to find ways to improve in the future. Reflection is an important part of the learning process. Reflection is also an essential component of a successful software development process.

Reflections are most interesting and useful when they're honest, even if the stories they tell are imperfect. You will be marked based on your depth of thought and analysis, and not based on the content of the reflections themselves. Thus, for full marks we encourage you to answer openly and honestly and to avoid simply writing "what you think the evaluator wants to hear."

Please answer the following questions. Some questions can be answered on the team level, but where appropriate, each team member should write their own response:

1. What went well while writing this deliverable?



2. What pain points did you experience during this deliverable, and how did you resolve them?
3. Which of your design decisions stemmed from speaking to your client(s) or a proxy (e.g. your peers, stakeholders, potential users)? For those that were not, why, and where did they come from?
4. While creating the design doc, what parts of your other documents (e.g. requirements, hazard analysis, etc), if any, needed to be changed, and why?
5. What are the limitations of your solution? Put another way, given unlimited resources, what could you do to make the project better? (LO\_ProbSolutions)
6. Give a brief overview of other design solutions you considered. What are the benefits and tradeoffs of those other designs compared with the chosen design? From all the potential options, why did you select the documented design? (LO\_Explores)
7. What have you learned from implementing another team's module?

## Group - Reflection

1. N/A
2. N/A
3. N/A
4. I think that our other documents such as the [requirements](#), [hazard analysis](#) need to be slightly adjusted as a result of the design documents. With the requirements specifically some of them pertain to how the application design is and after completing our initial draft of the MG and MIS, the design does not necessarily line up with the requirements document. Further, some of the hazards considered should be changed to include a couple more areas for hazards to occur. Lastly for both of the documents, the assumptions should be changed to incorporated design changes that we had not considered during that deliverable.
5. Some limitations on the current system design and with the set scope include the accuracy of the pose estimation, the responsiveness of the application, and the limitation of stored exercises. With more resources, we would like to improve the accuracy of the pose estimation by either using a more advanced model or training our own model specifically for physiotherapy exercises. Further, we would like to improve the responsiveness of the application by optimizing our code and potentially using more powerful hardware to run the application. And finally, although explicitly stated in our scope, we would like to include more exercises and potentially allow for custom exercises to be added by physiotherapists.

6. One alternative design solution we considered was making the application a desktop application rather than an android application. The benefit of this design is that it would allow for more powerful hardware to be used, which could improve the responsiveness and accuracy of the application. However, the tradeoff is a limitation to the accessibility of the application, as not all users may have access to a desktop computer with hardware capable of recording. We ultimately chose the android application design because it allows for greater accessibility and convenience for users, as they can use the application on their mobile devices which are easier to setup and come with recording hardware.
7. Implementing another team's module made it clear that another level of description is needed in order to effectively communicate the design and function of each module to developers. While implementing the Pixelation module for team 7, we found the description of their access program inputs and outputs lacking in detail. With sufficient context from the rest of the documentation we were able to produce what we believed to be the intended functionality of the module, but it required a lot of extra time and effort to interpret the design document. Additionally, because of this vague input and output description, there were no names given to input and output variables, which made it harder to stick to their coding conventions but also even harder to interpret the context of the module.

There was a lack of detail which I feel resonates with our documentation as well. The purposes and usage of each module by other modules should be clearly defined in order to avoid confusion during implementation. Working on the final version of the documentation, we will make sure to include detailed descriptions of each access program's inputs and outputs, as well as any necessary context for understanding the module's function within the overall system.

There was an overall description of modules and their functionality which provided a good high-level overview of each module, something we think should be included in our documentation as well. Additionally the use of assumptions to clarify certain design decisions was helpful, and while we don't believe it to be the correct section to provide context it was a good signifier of a well made assumption.

Overall, this experience has taught us the importance of clear and detailed documentation in order to facilitate effective communication and collaboration between teams.

## **Matthew - Reflection**

1. I think something that went well was our changes to overall workflow. One thing that we recognized was starting our document on google docs and then transferring our sections to GitHub on the last two days the the deliverable was due led to some things going unchecked and the deliverable not turning out the way we had planned. Further it had also resulted in a 'panic' when we had to resolve merge conflicts between our sections soon to the deadline. Overall, we cut google docs for this deliverable and

mainly focused on our sections within GitHub and doing multiple small PRs within the deliverable timeline and that had gone quite well. There are a few days left but a majority of the document has at least been accounted for and hopefully this workflow works for our team.

2. I think one pain point I experienced was time management. I had suggested that since the computing team's workload was quite different to the documentation team's, we could take on small sections within the document with hopes of submitting it early into the project. This did partially go well but with focus split in two areas it was hard to focus on the development side of things for the POC demo. This may be something that improves with time but as of now is currently a work in progress as development on my end is not where I want it to be.
3. I think that our design decisions partially came from speaking with our stakeholder (Kevin Yu) but other decisions were made with typical application creation. For example, the high-level was talked through with Kevin to simulate the timing and feedback delivery that you would encounter during physiotherapy but things like reporting, logging-in as well as account creation were from looking at other applications and aspects that went well from that end.
4. Group Q
5. Group Q
6. Group Q

## **Vaisnavi - Reflection**

1. Something that went well was how we worked on creating more constant pull requests (PRs) to avoid merge conflicts. This worked out well with everyone consistently pushing more PRs early on, allowing someone on the team to review and effectively merge it in. Overall, the organization and collaboration went very smoothly, and it allowed us to ultimately finish ahead of our internal deadline so we had enough time for editing and formatting.
2. I think one of the major pain points through this deliverable was trying to balance both the development side for the POC demo while also trying to contribute to the document. As the main sub-team for the POC demo, we did take on smaller sections, but it was difficult to find that balance in time for both at the start.
3. We believe that most of our major design decisions stemmed directly from our meetings with our stakeholder, Kevin Yu. Throughout the development of this deliverable, a number of ideas that we originally planned had to be changed or completely re-worked based on the feedback we received. In several cases, Kevin helped us recognize that certain features were either not feasible within the course timeline or did not align with

the true purpose and scope of our project. This was extremely helpful overall to have this input to tackle these decisions early on in the process.

4. Group Q
5. Group Q
6. Group Q

## **Maham - Reflection**

1. Despite our (extremely) busy schedules, we made time to meet when we could and offer assistance to any member that needed it. In addition, all of us kept in contact and checked in with each other. I liked that none of us completely abandoned this project, but rather balanced it quite well. Also, the more frequent PR requests strategy (implemented for this deliverable) ended up being immensely helpful.
2. A pain point for me was that a lot of my time and energy was taken up by external tasks. These were, unfortunately, appointments I could not compromise on because they had been scheduled months in advance. I would have loved to give this project more of my focus, and I tried my best to self-organize, but there were some areas I fell short. I will attempt to refine my balancing act for the future.
3. The project is still in the early stages of development, and as a result, we do not have many concrete elements. However, some of developed ideas and design decisions was aided by Kevin, our supervisor. At this stage, we are constructing the foundation of the software, and that knowledge was supplied by him. Eventually, when we do have a functional product, we will want to loop in other stakeholders, e.g. patients, for modifications
4. Group Q
5. Group Q
6. Group Q

## **Cieran - Reflection**

1. During this deliverable there was a need to agree upon implementation tactics. The team met and nailed down an approach for the development of the proof of concept, and I think everyone did a good job of ensuring their thoughts on what the system *was* got at least mentioned when developing the system.
2. I yet again sharked my teammates with procrastination. I have apologized profusely for my lack of initiative with this deliverable and have taken steps to ensure progress is far more consistent and meaningful in the future. As for this deliverable, I worked to catch up my own lack of effort towards the end of the it.

3. I think the design decisions, specifically around the system's allowance for physiotherapists to alter patient's exercise routines, were very influenced by meetings with our advisor. As a team, we wanted to ensure that the system was something wanted by both patients and physiotherapists; designing based off of requirements from past physiotherapy patients and our physiotherapist advisor was a must. Some design decisions, such as checking against public databases for the physiotherapist's identification number, were made in an attempt at security for users of the application.
4. GROUP Q
5. GROUP Q
6. GROUP Q