

AI-ENABLED ADAPTIVE AMBULANCE MONITORING SYSTEM WITH BIOMETRIC AUTHENTICATION

A PROJECT REPORT

Submitted by

AKALYA K	720322104003
DINESH S	720322104010
GOKULAKANNAN M	720322104012
MADHUMITHA S	720322104024

*in partial fulfillment for the award of the degree
of*

BACHELOR OF ENGINEERING

IN

COMPUTER SCIENCE AND ENGINEERING



AKSHAYA COLLEGE OF ENGINEERING AND TECHNOLOGY

(Autonomous)

Bhagavathipalayam, Kinathukadavu, Coimbatore,

Tamil Nadu-642109

MAY 2026

**AKSHAYA COLLEGE OF ENGINEERING AND
TECHNOLOGY
(Autonomous)
Kinathukadavu, Coimbatore, Tamil Nadu-642109**

BONAFIDE CERTIFICATE

Certified that this project report **"AI-ENABLED ADAPTIVE AMBULANCE MONITORING SYSTEM WITH BIOMETRIC AUTHENTICATION "** is the bonafide work of **AKALYA K(720322104003), DINESH S(720322104010),GOKULAKANNAN M(720322104012),MADHUMITHA S (720322104024)** who carried out the project work under my supervision.

SIGNATURE

Dr. T. GUHAN

HEAD OF THE DEPARTMENT

Associate Professor

Department of Computer Science

and Engineering

Akshaya College of Engineering and

Technology

Coimbatore – 642109

SIGNATURE

Mrs. M. NISHA

SUPERVISOR

Assistant Professor (Selection
Grade)

Department of Computer Science

and Engineering

Akshaya College of Engineering and

Technology

Coimbatore – 642109

Submitted for the Project viva-voce examination held on_____

INTERNAL EXAMINER

EXTERNAL EXAMINER

ACKNOWLEDGEMENT

With genuine humility, we are obediently thankful to God Almighty without Him, this work would have never become a reality.

We express our heartfelt thanks to our **Joint Director, Dr. N. SUGUNA, M.E., Ph.D.**, for her continuous encouragement, valuable support, and motivation throughout the course of the project.

We are deeply grateful to our **CEO, Dr. S. KAPILAN, M.E., Ph.D.**, whose visionary leadership and constant support have been a driving force in our academic and project endeavors.

We wish to express our sincere gratitude to our respected **Principal, Dr. R. RAVINDRAN, M.Tech., Ph.D.**, for providing us with the necessary resources and opportunity to successfully complete our project work.

We are thankful to our **Vice Principal, Dr. K. SIVASANKARI, M.E., Ph.D.**, for her insightful feedback and valuable guidance that contributed significantly to the progress of our project.

Our special thanks to **Dr. T. Guhan, M.E., Ph.D.**, Associate Professor and Head of the Department of Computer Science and Engineering for providing the facilities, support, and permission to carry out our project work at our esteemed institution.

Our sincere appreciation goes **Mrs. M. NISHA, M.E... (Ph.D.)**, for her dedicated mentorship, timely feedback, and continuous support throughout the development of our project.

We also thank the project review members and all the faculty members of the Department of Computer Science and Engineering for their valuable contributions to our learning journey.

Our sincere thanks to our faculty members, family members and friends for their support and motivation to carry out the project successfully.

ABSTRACT

The Emergency medical services play a critical role in saving lives, yet current ambulance systems face significant challenges including delayed patient monitoring, inefficient communication with hospitals, and poor route selection, often resulting in the loss of the critical “golden hour.” This project proposes an AI-Enabled Adaptive Ambulance Monitoring System with Biometric Authentication to address these limitations by integrating modern technologies for secure, real-time, and intelligent emergency response. The system employs biometric fingerprint authentication to ensure authorized access to the ambulance, preventing unauthorized use. IoT sensors (ECG, SpO₂, heart rate, blood pressure) continuously monitor patient vitals, with AI/ML algorithms deployed for real-time anomaly detection and instant alert generation. A predictive route optimization module uses GPS and live traffic data to calculate the fastest and safest route to the most appropriate hospital. All patient data, medicine usage, and helper details are logged and transmitted in real-time to a centralized hospital dashboard, enabling doctors to prepare in advance. Developed using a combination of embedded systems, cloud platforms, and web technologies, the system ensures secure data transmission, automated reporting, and emergency alerting in cases of accidents or breakdowns. This project demonstrates a practical, integrated approach to transforming traditional ambulances into smart, connected, and adaptive emergency care units.

TABLE OF CONTENTS

CHAPTER NO	TITLE	PAGE NO
	ABSTRACT	iii
	TABLE OF CONTENTS	vi
	LIST OF TABLES	vii
	LIST OF FIGURES	viii
	LIST OF ABBREVIATIONS	ix
1	INTRODUCTION	1
	1.1 BACKGROUND	1
	1.2 PROBLEM STATEMENT	2
	1.3 SCOPE OF THE PROJECT	2
	1.3.1 OBJECTIVES	4
	1.3.2 NOVELTY	4
2	LITERATURE SURVEY	5
3	SYSTEM ANALYSIS	17
	3.1 EXISTING SYSTEM	17
	3.1.1 WORKING	18
	3.1.2 DISADVANTAGES	18
	3.2 PROPOSED SYSTEM	19
	3.2.1 WORKING	20
	3.2.2 ADVANTAGES	21

4	SOFTWARE DESCRIPTION	23
4.1	ARDUINO IDE FOR EMBEDDED DEVELOPMENT	23
4.2	EMBEDDED C++ PROGRAMMING LANGUAGE	23
4.3	SENSOR INTERFACING LIBRARIES	24
4.4	COMMUNICATION PROTOCOLS	24
4.5	AI-BASED ANOMALY DETECTION LOGIC	25
4.6	HOSPITAL DASHBOARD	25
4.7	BIOMETRIC AUTHENTICATION SOFTWARE	26
4.8	EMERGENCY ALERT AND NOTIFICATION SYSTEM	26
4.9	SECURITY AND DATA INTEGRITY MEASURES	26
5	SYSTEM TESTING	27
5.1	TESTING DEFINITION	27
5.1.1	UNIT TESTING	27
5.1.2	INTEGRATION TESTING	28
5.1.3	SYSTEM TESTING	28
5.1.4	PERFORMANCE TESTING	29
5.1.5	SECURITY TESTING	29
5.1.6	REGRESSION TESTING	30

	5.2 TEST CASES	30
6	SYSTEM IMPLEMENTATION	38
	6.1 PROJECT DESCRIPTION	38
	6.2 MODULE DESCRIPTION	39
7	RESULTS AND DISCUSSION	46
	7.1 RESULT	46
	7.2 SCREENSHOTS	47
8	CONCLUSION AND FUTURE WORK	50
	8.1 CONCLUSION	50
	8.2 FUTURE ENHANCEMENT	51
	REFERENCES	52
	APPENDICES 1	54
	APPENDICES 2	68

LIST OF TABLES

TABLE NO	TITLE	PAGE NO
5.1	Accuracy Analysis Of Proposed Ambulance Monitoring System	34
5.2	Patient Vitals Monitoring	35

LIST OF FIGURES

FIGURE NO	FIGURE NAME	PAGE NO
3.1	High-Level System Architecture of Proposed Ambulance Monitoring System	20
3.2	Flow Diagram of the Adaptive Ambulance Monitoring System	22
6.1	Biometric Authentication Module	39
6.2	IoT-Based Patient Monitoring Module	40
6.3	AI Anomaly Detection and Alerting Module	41
6.4	GPS and Route Optimization Module	42
6.5	Communication and Data Transmission Module	43
6.6	Hospital Dashboard Central Monitoring Module	44
6.7	Power Management and Safety Module	44
6.8	Data Logging and Reporting Module	45
7.1	Real-Time Patient Vital Signs on Dashboard	47
7.2	GPS Route Optimization Map Display	47
7.3	Emergency Alert Notification on Dashboard	48
7.4	Medicine Tracking Log Report	48
7.5	Anomaly Detection Alert for Abnormal Heart Rate	48
7.6	Hardware Prototype of AI-Enabled Adaptive Ambulance Monitoring System with Biometric Authentication	49
7.7	Real Time Output Images	49

LIST OF SYMBOLS AND ABBREVIATION

AI	-	Artificial Intelligence
IOT	-	Internet of Things
ECG	-	Electrocardiogram
SpO ₂	-	Peripheral Oxygen Saturation
HR	-	Heart Rate
BP	-	Blood Pressure
API	-	Application Programming Interface
GPS	-	Global Positioning System
ML	-	Machine Learning
EMS	-	Emergency Medical Technician
PMS	-	Patient Monitoring System
W-GeoR	-	Weighted Geographical Routing
eSIM	-	Embedded SIM
CTH	-	Cyber Threat Hunting
HSR	-	High Survivable Ransomware

CHAPTER 1

INTRODUCTION

1.1 BACKGROUND

Emergency Medical Services (EMS) represent a vital component of healthcare infrastructure, often serving as the decisive factor between life and death during critical situations. The period immediately following a medical emergency, widely recognized as the “golden hour,” is crucial for patient stabilization and survival. However, traditional ambulance systems are frequently hindered by operational inefficiencies such as manual patient monitoring, delayed hospital communication, traffic congestion, and suboptimal routing. These limitations not only prolong response times but also compromise the quality of pre-hospital care, directly impacting patient outcomes. In response to these challenges, technological advancements in the Internet of Things (IoT) and Artificial Intelligence (AI) have opened new avenues for transforming conventional ambulances into intelligent, connected care units. By integrating real-time health monitoring, secure biometric access, predictive route optimization, and automated hospital alerting, it is possible to create an adaptive emergency response ecosystem. Such a system ensures continuous patient assessment, faster decision-making, and enhanced coordination between ambulance crews and hospital staff, thereby preserving the golden hour and improving survival rates. By fostering a seamless flow of information and enabling proactive medical intervention, this project strives to redefine emergency healthcare delivery in the modern age. The incorporation of cloud-based data storage enables secure and continuous access to patient records, allowing healthcare professionals to make informed decisions even before the patient arrives. The use of AI-driven analytics can also assist in early detection of critical conditions by analyzing vital signs in real time. Integration also contributes to building a more resilient and responsive healthcare system.

1.2 PROBLEM STATEMENT

Emergency Medical Services (EMS) are critically hampered by reliance on manual, fragmented, and reactive systems, leading to preventable delays and suboptimal patient outcomes during the golden hour. Traditional ambulances operate with disconnected processes: vital signs are recorded intermittently using standalone devices, communication with hospitals occurs via voice calls prone to misinterpretation, and navigation relies on static GPS without real-time traffic adaptation. This results in delayed detection of patient deterioration, inadequate hospital preparedness, and prolonged transit times due to unoptimized routing. Furthermore, the absence of secure access control allows for potential ambulance misuse, while manual logging of medicine administration and helper details introduces errors and accountability gaps. These systemic inefficiencies collectively compromise the speed, accuracy, and security of emergency response, directly contributing to increased morbidity and mortality. There is, therefore, an urgent need for an integrated, intelligent solution that automates patient monitoring, secures ambulance access, enables real-time data communication, optimizes routing dynamically, and ensures end-to-end accountability all to preserve the golden hour and enhance survival rates in medical emergencies.

1.3 SCOPE OF THE PROJECT

The scope of this project encompasses a comprehensive and technically rigorous endeavor to design, develop, and deploy an intelligent, AI-enabled adaptive ambulance monitoring system specifically engineered for real-time emergency medical response. This initiative integrates advanced IoT sensing methodologies with artificial intelligence to create a proactive healthcare apparatus capable of identifying and responding to critical patient conditions as they emerge during medical transport. The system is architected to function

within mobile ambulance environments, where it will perform deep, real-time analysis of vital physiological parameters, including cardiac electrical activity through ECG monitoring, blood oxygen saturation (SpO₂) levels, heart rate variability, and blood pressure fluctuations.

By employing a hybrid technological framework that synergistically combines the robust data acquisition capabilities of biomedical sensors with the pattern recognition strengths of AI-based anomaly detection algorithms, the system is engineered to deliver exceptionally high monitoring accuracy while maintaining real-time response capabilities. The implementation leverages a modern and cohesive technology stack, utilizing Embedded C/C++ with the Arduino IDE for microcontroller programming, Python for AI/ML model development and dashboard backend, Flask for web interface development, and MySQL for secure medical data logging. Furthermore, a dedicated web-based hospital dashboard, developed using HTML, CSS, JavaScript, and Bootstrap, will provide medical personnel with an intuitive interface for real-time patient visualization, emergency alert management, and comprehensive treatment analytics, significantly enhancing medical preparedness and clinical decision making .

Moreover, the project is strategically designed with extensibility and scalability as foundational principles, ensuring that the initial focus on basic vital parameter monitoring serves as a launchpad for future adaptation to advanced physiological monitoring, integration with electronic health record (EHR) systems, and expansion to disaster response and mass casualty scenarios. The modular design of the system allows for the seamless integration of additional medical sensors, communication⁹⁶ and healthcare interoperability standards. This endeavor not only aims to deliver a functional system for immediate demonstration but also to contribute a scalable and intelligent framework to the evolving domain of smart emergency medical

setting a precedent for next-generation, technology-augmented healthcare solutions during the critical golden hour. The project is designed with extensibility for future adaptation to advanced monitoring, EHR integration, and disaster response scenarios.

1.3.1 OBJECTIVES OF THE PROJECT

The objectives of the proposed system are:

- To develop a smart ambulance system that integrates AI and IoT for efficient emergency medical response.
- To continuously monitor patient vital signs (ECG, heart rate, SpO₂, blood pressure) in real time using IoT sensors.
- To implement AI-based anomaly detection for early identification of critical health conditions and instant alert generation.
- To ensure secure ambulance access using biometric fingerprint authentication to prevent unauthorized usage.
- To optimize ambulance routing using GPS and real-time traffic data to reach the nearest suitable hospital quickly.
- To enable real-time communication with hospitals by transmitting patient data and alerts through a centralized dashboard.

1.3.2 NOVELTY OF THE PROPOSED SYSTEM

The novelty of the project lies in how it integrates multiple advanced technologies into a single, real-time, intelligent ambulance system, rather than treating them as separate features like:

- AI-Based Early Anomaly Detection
- Biometric Authentication for Secure Access
- Real-Time Adaptive Route Optimization

- Live Hospital Connectivity with Automated Logging
- Integration of AI, IoT, and Biometric Security

The system also introduces real-time cloud-based medical data synchronization, allowing hospitals to access patient history, vital trends, and emergency status instantly even before the ambulance arrives, thereby improving treatment preparedness and reducing response delays during the golden hour. Another distinctive aspect of the proposed system is its modular and scalable architecture, which allows seamless integration of additional biomedical sensors, AI models, and healthcare services in the future without redesigning the complete infrastructure. The incorporation of automated digital logging for medicine administration, helper details, patient status updates, and emergency event tracking improves accountability, traceability, and medical record accuracy. Furthermore, the system enhances operational intelligence by combining IoT-enabled environmental awareness with adaptive emergency response mechanisms, enabling faster and more reliable medical transportation under varying traffic and patient conditions. The proposed framework also supports remote accessibility, allowing authorized doctors and hospital administrators to monitor patient conditions securely from different locations through a web-based dashboard. By integrating predictive healthcare analytics, intelligent automation, secure authentication, and real-time connectivity into a single platform, the project establishes a next-generation smart ambulance framework capable of transforming traditional emergency healthcare delivery into a proactive, data-driven, and technology-assisted medical response system.

CHAPTER 2

LITERATURE REVIEW

Basheera M. Mahmmod et al.(2024) conducted a review and related challenges with open research issues Proposed provides a comprehensive review of Patient Monitoring Systems (PMS) based on Internet of Things (IoT) technologies. It explores the architecture, components, and communication protocols essential for developing efficient remote healthcare systems. The paper discusses the integration of wearable sensors, wireless networks, cloud/fog computing, and IoT in healthcare, emphasizing the importance of PMS in remote monitoring, especially for elderly patients and those with chronic illnesses. It also identifies key challenges, including security, data heterogeneity, scalability, and energy consumption, and proposes future research directions to address these issues. The proposed patient monitoring system (PMS) is grounded in a comprehensive architecture review that introduces a five-layer framework comprising sensing, communication, edge/fog, cloud, and application layers—each playing a distinct role in data acquisition, transmission, preprocessing, storage, and end-user delivery. A detailed sensor and wearable device analysis follows, reviewing various physiological sensors such as ECG, EMG, and SpO₂, along with their respective wearable implementations, functionalities, and classifications based on signal type and placement. To enable seamless data flow, the system evaluates communication technologies including Wi-Fi, Bluetooth, ZigBee, LoRaWAN, and 6LoWPAN, weighing their suitability for healthcare data transmission in terms of range, power consumption, and reliability.

Zakariah, A.N., et al.(2024) This longitudinal analyzes the 20-year nationwide expansion of Ghana's National Ambulance Service (NAS) from its inception in 2004 to 2023. The paper documents the growth in infrastructure, human resources, and service utilization, highlighting how NAS expanded from 7 stations and 9 ambulances to covering all 261 districts with 297 stations and 356 ambulances. It also examines challenges related to funding, vehicle maintenance, and the predominance of inter-facility transfers over emergency scene responses. The study concludes that NAS has largely achieved geographic equity in service provision, though financial sustainability and emergency scene response utilization remain key challenges. Over a 20-year longitudinal national analysis across all 16 regions of Ghana, the EMS system's growth was evaluated using multi-dimensional metrics covering structure (ambulances, stations, EMTs), utilization (patient transports, response types), and equity (regional distribution). Focused on low-resource settings, the model emphasizes scalable training and infrastructure, highlighted by an in-house NAS-owned.

Mahalakshmi et al. (2022) This proposes an IoT-based adaptive ambulance monitoring system aimed at reducing ambulance transit time in urban traffic. The system uses real-time camera-based ambulance detection and image processing to prioritize traffic signals for ambulance passage. It employs Bluetooth and RF modules for long-range communication between ambulances and traffic signals, forming a closed-loop data network to transmit patient vital signs to hospitals in advance. The system is modular in design, consisting of three main components: an in-ambulance smart box, a signal post smart repeater, and a hospital-side software system. It employs traffic signal priority control using image recognition to detect ambulances and automatically switch signals to green, supported by a closed-loop data network with Bluetooth and RF modules for relay communication between signal posts. Real-time patient

monitoring is enabled via an in-ambulance smart box that collects vital signs like heart rate and oxygen levels. For navigation, lane assistance and weather adaptability are provided through infrared cameras effective in foggy or harsh conditions. The system follows a modular design divided into ambulance, signal post, and hospital modules, ensuring ease of integration and scalability. Finally, cloud-based data storage is implemented using a GitHub repository, allowing hospital staff to access patient data in real time.

Bowling, P., & de Jong, G.et al. (2025) scoping review synthesizes qualitative evidence from ten studies across seven countries (Australia, Canada, the Netherlands, UK, Sweden, USA) to explore patient experiences of receiving community-based care after being assessed by ambulance clinicians, rather than being transported to an emergency department. The review identifies three overarching themes: perceived benefits of community ambulance care (improved health literacy, safety net, holistic care); qualities of ambulance clinicians as excellent providers (interpersonal skills, rapport-building, reassurance); and patient preference for community over hospital care (timely, accessible, patient/family-centred). The findings highlight high patient satisfaction and support for expanded community paramedic models as a sustainable alternative to hospital conveyance. The analysis achieves thematic depth by identifying three core themes and eight sub-themes drawn from patient narratives and lived experiences, highlighting patient-centred insights such as the importance of clinician-patient relationships, communication, and tailored care in community settings. These findings provide strong support for service redesign, offering evidence for policymakers and ambulance services to develop community care pathways that reduce emergency department overcrowding.

Singh, P., Raw et al. (2022) Proposed proposes a Weighted Geographical Routing protocol (W-GeoR) designed for VANET-based health monitoring in post-disaster urban environments. W-GeoR enhances the traditional GPSR protocol by incorporating multiple routing metrics—such as node mobility, link expiration time, channel SNR, and destination proximity—to improve the selection of the next-hop node for timely and reliable transmission of patients' health data. The protocol is evaluated using SUMO and NS-3 simulators under varied traffic conditions, demonstrating superior performance in terms of packet delivery ratio, end-to-end delay, throughput, and stability compared to existing protocols like GPSR, GPSR-WG, and MM-GPSR. This study introduces a multi-metric weighted routing approach using the Analytic Hierarchy Process (AHP) to assign weights to mobility, link stability, signal quality, and proximity metrics. It simulates post-disaster scenarios within urban vehicular networks under infrastructure failures, employing enhanced next-hop selection that combines greedy and perimeter forwarding with AHP-based decision-making to optimize routing paths. A comprehensive performance evaluation assesses protocols across lost packets, packet delivery ratio (PDR), hop count, delay. The realistic simulation environment integrates SUMO for traffic modeling and NS-3 for network simulation under dynamic vehicle mobility.

Eunjeong Park¹ et al.(2018) Proposed presents the design and implementation of a Smart Emergency Medical Service (SEMS) system to enhance pre-hospital and in-hospital emergency care through IoT and connected healthcare technologies. The authors conducted a survey of 113

paramedics to identify key challenges in conventional EMS, such as inaccurate reporting, limited access to patient medical history, and poor real-time communication. Based on the survey results, SEMS was developed to integrate real-time patient monitoring, electronic medical records (EMRs), lifelog data, and triage tracking into a unified platform. The system uses health information standards (IHE/HL7) for interoperability and includes use cases such as stroke patient monitoring and disaster management. The goal is to improve response times, accuracy of care, and patient outcomes through data-driven, connected emergency services. This study presents a paramedic-centered requirement analysis based on a survey of 113 paramedics, identifying key pain points in EMS workflows. The proposed system integrates multiple data sources, combining real-time bio-signals from ambulances, electronic medical records (EMRs), lifelog data, and triage information. Interoperability is ensured through IHE/HL7 standards, enabling seamless communication between devices, EMS systems, and hospital IT. Real-time data sharing allows continuous transmission of patient vitals and scene information to hospitals and control centers. Smart triage and tracking are achieved using beacon sensors, RFID, and barcodes for patient tracking and optimized hospital routing. Additionally, a stroke-specific application includes a smartphone app for early stroke detection using FAST criteria, along with integrated timeline management.

Stephanie B. et al.(2018) Proposed presents a comprehensive survey of IoT technologies for smart healthcare, focusing on the design of a standardized, end-to-end IoT healthcare system model. The authors review wearable sensors, short- and long-range communication standards, and cloud-based systems, with an emphasis on remote health monitoring for aging populations and chronic disease management. The paper also highlights key challenges such as security,

energy efficiency, and interoperability, and outlines future research directions, including the adoption of NB-IoT and the integration of machine learning for predictive diagnostics. This proposes a standardized IoT healthcare model structured as a four-part framework comprising wearable sensors, short-range and long-range communications, and cloud-based storage and analytics. A comprehensive sensor review evaluates devices for measuring pulse, respiration, temperature, blood pressure, and SpO₂, recommending PPG-based sensors for pulse oximetry. The communication standards analysis compares short-range protocols (BLE, ZigBee) with long-range options (Sigfox, LoRaWAN, NB-IoT), recommending BLE and NB-IoT for healthcare applications. Cloud and big data integration is emphasized for scalable data management, with machine learning enabling diagnostics and personalized care. Use case applications include rehabilitation, chronic disease management, emergency care, and remote patient monitoring. Finally, the model addresses security and privacy through encryption, access control, and secure data transmission within cloud-based healthcare systems.

Ahmed Ben Said et al. (2021) Proposed introduces a deep learning-based adaptive compression framework designed for multi-modal biomedical signals such as EEG and EOG in mobile health (mHealth) systems. The authors propose two Stacked Auto-Encoder models—SAE-S for single-modality compression and SAE-M for multi-modality compression—which leverage intra- and inter-modal correlations to improve compression performance. An optimization framework is also developed to adaptively select compression ratios based on real-time network conditions, minimizing overall energy consumption while meeting quality-of-service requirements. Experimental results using the DEAP dataset demonstrate that SAE-M outperforms traditional compression methods in terms of distortion reduction, processing

speed, and energy efficiency, making it suitable for real-time, low-power mHealth applications. This study introduces an adaptive deep learning compression approach for mHealth applications, featuring SAE-S and SAE-M models that dynamically adjust compression based on network state and data characteristics. The SAE-M model exploits correlations between different signal types, such as EEG and EOG, to enhance multi-modal data utilization and compression efficiency. An energy-aware convex optimization framework minimizes total energy usage by optimizing compression ratios, transmission rates, and bandwidth allocation per user. The edge-focused design performs compression at the personal digital assistant (PDA) level, reducing data transmission loads and cloud dependency. Performance evaluation shows that SAE-M reduces distortion by 3.71% compared to SAE-S and by 72.37% compared to DWT, while cutting processing time by 43.75% versus DCT. This practical solution is designed to support continuous monitoring of chronic disease patients with scalable, low-latency data delivery.

Hemangi Goswami¹ et al.(2025) 5G Proposed proposes 5G-MobiCare, a secure remote mobile health monitoring platform that uses 5G networks and eSIM-enabled medical sensors for real-time patient monitoring. The system introduces a group-based authentication scheme to efficiently authenticate multiple medical devices simultaneously, especially in mobile scenarios like ambulance care. Lightweight cryptographic techniques—such as Elliptic Curve Cryptography (ECC), hash functions, and XOR operations—are used to ensure security while minimizing computational overhead on resource-constrained sensors. The scheme supports remote device registration, group key establishment, and secure data transmission to a remote Electronic Health Record (EHR) system. Security is formally validated using BAN logic and AVISPA, and performance analysis shows reduced communication and

computational costs compared to existing schemes. This work presents a group-based authentication scheme for eSIM-enabled medical devices, allowing simultaneous authentication using a group secret key to drastically reduce latency and computational overhead ideal for large-scale IoT healthcare. Remote registration and automatic deregistration of inactive or compromised devices are supported via a trusted gateway. Lightweight cryptography, combining ECC, hash functions, and XOR operations, ensures suitability for low-power sensors. Integrated with 5G networks, the system enables high-speed, low-latency, secure data transmission. Formal security validation using BAN logic and the AVISPA tool confirms robustness against MITM, replay, and eavesdropping attacks, while eSIM support enhances flexible and secure device management.

Akito Takada'et al.(2022) proposed investigates the core temperature of elderly heatstroke patients in Nagoya, Japan, who were transported by ambulance from their homes during the summers of 2019 and 2020. Using measured ambulance data and computational thermoregulatory modeling, the authors compare actual axillary temperatures with simulated core temperatures under different sweating scenarios. Key findings reveal that 31.4% of patients had higher measured core temperatures than computationally predicted values, even when assuming no sweating. This suggests that cumulative heat stress over multiple days, rather than single-day exposure, may be a critical factor in heatstroke onset among the elderly. The study highlights the need for multi-day monitoring in heatstroke prevention systems. This study analyzes 2,316 real ambulance records from the Nagoya City Fire Department to examine core temperature in elderly heatstroke patients (≥ 65 years), who account for 50% of heat-related illnesses in Japan. Using computational thermoregulatory modeling with bioheat equations, it compares four sweating scenarios healthy

adult, aged >65, aged >75, and no sweating to quantify age-related declines in thermoregulation. Integrated with hourly meteorological data from the Japan Meteorological Agency, the findings suggest that heatstroke often results from cumulative heat stress over successive days, not just acute single-day heat exposure.

Srividya, R., and Ramesh, B. et al.(2015) propose a biometric authentication technique for securing Mobile Ad Hoc Network (MANET)-based emergency response systems. The system combines physiological and behavioral biometrics, specifically gesture recognition with finger photo analysis, to provide reliable authentication in dynamic and infrastructure-less environments. It follows three main stages—enrollment, capture, and verification where user biometric data is stored, captured, and matched with templates using a novel Right Shift algorithm based on pixel intensity, eigenvalues, and fingerprint minutiae features. The method includes image preprocessing steps such as grayscale conversion, feature extraction, and edge detection to improve accuracy. Simulation results show effective identification of authorized and unauthorized users. A comparative study between password-based and gesture-based authentication highlights that biometric methods offer better usability, memorability, and security. The system also evaluates key error metrics like False Acceptance Rate (FAR), False Rejection Rate (FRR), and Failure to Enroll Rate (FER), demonstrating improved performance. Overall, the proposed hybrid biometric model enhances security and is well-suited for emergency scenarios such as disaster management and mobile healthcare systems where fast and secure authentication is essential without centralized infrastructure.

Kalaivani, K., Chitra, V., Valarmathi, G., Kanagaraj, V., and Akshayaa, U. (2022) propose a Smart Ambulance system using Internet of Things (IoT) with periodic data analysis to improve emergency healthcare services in high-traffic conditions. The system integrates biomedical sensors such as heartbeat, temperature, and pulse sensors to continuously monitor the patient's vital parameters inside the ambulance and transmit the data to a hospital server in real time. A fingerprint scanner is also incorporated to identify the patient and retrieve medical history from a centralized database, enabling automatic patient registration and quick access to critical health information. The architecture uses Arduino microcontroller and NodeMCU for communication, with MQTT protocol for data transmission and MySQL database for storage, allowing doctors to monitor patient conditions remotely and provide immediate treatment guidance. The system ensures that even before the patient reaches the hospital, necessary medical decisions can be made, thereby reducing delays and improving survival chances. Experimental results demonstrate that authorized users can access and transmit complete medical data, while unauthorized users are restricted, ensuring security and privacy. Overall, the proposed system enhances emergency response efficiency, supports real-time health monitoring, and provides a reliable IoT-based solution for smart healthcare and ambulance management systems.

Buradkar, V. S., Vyas, P. S., Trikolwar, S. P., Sahu, R. S., Wankhede, S. B., and Jivtode, V. (2025) propose a Cloud-based Emergency Ambulance System designed to improve ambulance dispatch efficiency using real-time tracking, GIS, and web technologies. The system replaces traditional manual dispatch methods with an automated, web-based platform that generates emergency incidents and assigns the nearest available ambulance using a Flask-based backend. It integrates GPS tracking and LeafletJS mapping to provide

real-time visualization of ambulances, hospitals, and incident location enabling dynamic routing and faster response. The system includes role-based dashboards for drivers, dispatchers, and hospital staff, allowing each user to monitor relevant information such as routes, patient details, and estimated arrival times. A simulation engine models the complete ambulance lifecycle, including dispatch, en route, arrival, patient transport, and availability, with continuous updates and detailed event logging for performance analysis. The architecture uses REST APIs and WebSocket communication to ensure real-time data synchronization across the system. Experimental results demonstrate efficient ambulance assignment, reduced response time, and improved situational awareness through interactive mapping and automation. Overall, the proposed system provides a scalable, cloud-based solution for emergency medical services, enhancing decision-making, training, and operational efficiency in real-time ambulance management.

Jeni Naarayanan, L. A., Manoj, S., Praveen, M., Johnson, M., and Shyam, S. (2024) propose a Smart Artificial Intelligence Ambulance with a Decision-Making System aimed at improving emergency medical services by reducing ambulance delays in congested urban environments. The system integrates biomedical sensors to continuously monitor patient vital parameters such as respiration rate, temperature, and pulse during transit, and transmits this data to hospitals via GSM communication for real-time medical support. It utilizes artificial intelligence algorithms and GPS-based traffic analysis to identify the fastest and shortest routes. The system also includes a decision-making module that recommends the nearest suitable hospital based on patient condition and resource availability, such as oxygen beds, ventilators, and ICU support. An alert mechanism using a buzzer is triggered when abnormal health conditions are detected, ensuring immediate attention. The architecture is implemented

using Arduino, sensors, LCD display, and communication modules, enabling continuous monitoring and effective coordination between ambulance and hospital. The proposed system addresses limitations of existing methods such as lack of real-time data, hospital unavailability, and inefficient routing. Overall, the system enhances emergency response efficiency, supports timely medical decision-making, and improves patient survival rates through intelligent automation and real-time communication.

Deepana, D., Glaramettilda, D., Karthika, M., and Pavithra, V. (2024) propose an AI-based Traffic Light Control and Ambulance Detection system using Python to improve traffic management and emergency response in urban environments. The system replaces traditional fixed-time traffic signals with an adaptive mechanism that uses image processing and machine learning techniques to monitor real-time traffic density at road intersections. It employs computer vision algorithms such as CNN-based object detection (e.g., YOLO, SSD) to identify vehicles and detect ambulances from camera inputs. When an ambulance is detected, the system dynamically controls traffic signals to create a green corridor, allowing it to pass quickly without delays. The architecture includes modules such as admin control, driver communication, and signal manipulation, supported by cloud-based data storage and mobile applications. Reinforcement learning techniques are used to optimize signal timing based on traffic conditions, minimizing congestion and waiting time. The system utilizes datasets collected from cameras and APIs like Google Maps for traffic analysis and decision-making. The system replaces traditional fixed-time traffic signals with an adaptive mechanism that uses image processing and machine learning techniques to monitor real-time traffic density at road intersections. Experimental results show improved traffic flow efficiency, reduced congestion, and faster emergency vehicle movement.

CHAPTER 3

SYSTEM ANALYSIS

3.1 EXISTING SYSTEM

Traditional ambulance monitoring systems are predominantly based on manual operations and basic technological integrations. These systems rely on simple IoT devices for data collection, GPS for location tracking, and basic wireless communication for data transmission. The primary focus of existing solutions is on collecting patient health data such as heart rate, temperature, and ECG readings using wearable sensors, and transmitting this data to centralized electronic health records (EHRs) or hospital servers via mobile networks. Key based search involves the use of predefined cryptographic keys, device identifiers, or digital certificates to authenticate entities within a monitoring system. In traditional ambulance setups, this method relies on stored credentials—such as SIM-based keys or encrypted tokens to verify communication between the ambulance and the hospital server. Role based search controls system access and permissions based on predefined user roles such as driver, paramedic, or doctor. In conventional ambulance systems, this method restricts data access and operational functions according to the assigned role, ensuring that only authorized personnel perform specific tasks. Content based analysis involves examining the actual data generated by medical sensors such as ECG signals, SpO₂ readings, and heart rate patterns to identify anomalies or malicious activities. This method compares sensor outputs against predefined thresholds or known patterns to detect irregularities that may indicate distress or system tampering. content-based analysis is computationally intensive and often fails to recognize novel or threats that do not match existing signature.

3.1.1 WORKING

The existing ambulance monitoring system collects patient health data using sensors such as ECG, heart rate, temperature, and SpO₂. These sensors continuously monitor the patient's condition and send the data to an onboard processing unit. The data is then transmitted to hospitals through IoT devices and mobile networks. GPS is used to track the real-time location of the ambulance. Secure communication is ensured using key-based authentication methods like cryptographic keys and SIM-based credentials. Role-based access control restricts system usage to authorized users such as drivers, paramedics, and doctors. The collected data is stored in centralized hospital servers or electronic health record systems. It is analyzed using predefined thresholds to detect abnormal conditions. Alerts are generated and sent to medical professionals for immediate action. However, the system depends on stable networks and has limited capability to detect new or complex health issues in real time.

3.1.2 DISADVANTAGES OF EXISTING SYSTEMS

- **Insecure Access Control:** Relies on passwords or keys, not biometrics, leading to unauthorized use.
- **Slow Anomaly Detection:** Only detects health issues after they worsen, missing early warning signs.
- **Delayed Hospital Updates:** Sends patient data only on arrival, not in real-time, delaying hospital readiness.
- **Inefficient Routing:** Uses basic GPS without live traffic data, causing delays due to congestion.

- **No Treatment Logging:** Medicine use and helper actions are not recorded, creating gaps in medical records.
- **Manual Processes:** Requires constant human input, increasing errors and slowing emergency response.

3.2 PROPOSED SYSTEM

The proposed AI-Enabled Adaptive Ambulance Monitoring System revolutionizes emergency medical response by integrating biometric security, IoT-based patient monitoring, AI-driven anomaly detection, and real-time communication technologies into a unified smart ambulance framework. The system ensures secure access through fingerprint authentication, preventing unauthorized use, while IoT sensors continuously track vital signs such as heart rate, ECG, SpO₂, and blood pressure. An embedded AI module analyzes this data in real-time to detect abnormal health patterns early, triggering immediate alerts when critical conditions are detected. Additionally, the system employs predictive GPS routing that incorporates live traffic data to identify the fastest and safest path to the nearest suitable hospital. The system is highly scalable and can be deployed across both urban and rural areas, making it suitable for large-scale healthcare networks. It can also integrate with smart city infrastructure to enable traffic signal prioritization for ambulances. Additionally, AI-driven decision support provides doctors with intelligent insights for faster and more accurate treatment. Patient vitals, location, and emergency alerts are transmitted seamlessly to a hospital dashboard, enabling doctors to prepare in advance for incoming patients. This integrated approach reduces delays, enhances decision-making, improves hospital coordination, and ultimately increases patient survival rates during emergencies.

3.2.1 WORKING




Figure 3.1 High-Level System Architecture of Proposed Ambulance Monitoring

The figure 3.1 represents the ambulance monitoring system begins with authentication, where authorized personnel access the system to start operations. Once the patient enters the ambulance, sensors like ECG, heart rate, BP, and SpO₂ start collecting real-time health data. This data is processed by an onboard unit and continuously monitored for abnormalities. If any abnormal condition is detected, alerts are immediately sent to the hospital and medical staff. The system also tracks the ambulance location using GPS for real-time navigation. All communication is secured using authentication methods and controlled through role-based access for drivers, paramedics, and doctors. The collected patient data is stored in centralized hospital systems for further analysis. Doctors can monitor the patient remotely through dashboards and provide guidance. Emergency situations like accidents or breakdowns trigger instant alerts to hospitals and authorities. However, the system relies on network availability and has limited ability to detect complex or new health issues efficiently

3.2.2 ADVANTAGES OF PROPOSED SYSTEM

- **Enhanced Security with Biometric Access:** Prevents unauthorized ambulance use and ensures only trained personnel can operate the vehicle, improving safety and accountability.
- **Real-Time Patient Monitoring :** Continuously tracks vital signs like ECG, heart rate, SpO₂, and blood pressure using IoT sensors for immediate awareness of patient status.
- **Early Anomaly Detection with AI:** Identifies critical health changes quickly through AI-powered analysis, allowing for faster medical intervention before conditions worsen.
- **Faster Emergency Response with Optimized Routing:** Uses real-time

traffic data and predictive GPS to choose the quickest and safest route, reducing travel time and saving the “golden hour.”

- Improved Hospital Coordination: Transmits live patient data and location to hospital dashboards, enabling doctors to prepare in advance for arrival.
- Automated Treatment and Activity Logging: Records all medicines administered and helper actions automatically, ensuring accurate medical records and accountability.
- Reduced Human Error: Automation of monitoring, alerts, and logging minimizes manual mistakes by paramedics.
- Improved Decision-Making: AI-driven insights help doctors make faster and more accurate treatment decisions.
- Scalability: The system can be expanded to support multiple ambulances and hospitals across regions.




Figure 3.2 Flow Diagram of the Adaptive Ambulance Monitoring System

CHAPTER 4

SOFTWARE DESCRIPTION

4.1 ARDUINO IDE FOR EMBEDDED DEVELOPMENT

The Arduino Integrated Development Environment (IDE) serves as the primary platform for developing, compiling, and uploading firmware to the ESP32 microcontroller. This open-source IDE provides a user-friendly interface for writing, debugging, and deploying embedded C/C++ code. It supports a wide range of libraries for sensor interfacing, communication protocols, and peripheral management, making it ideal for rapid prototyping of IoT-based healthcare systems. The Arduino framework simplifies low-level hardware interactions and offers extensive community support, which accelerates development and troubleshooting.

4.2 EMBEDDED C/C++ PROGRAMMING LANGUAGE

The core firmware of the system is developed using Embedded C/C++, chosen for its efficiency, low-level hardware control, and real-time execution capabilities. This language allows direct memory management, register-level access, and optimized performance essential for handling time-sensitive tasks such as sensor data acquisition, biometric verification, and emergency alert generation. The use of structured programming principles ensures modularity, readability, and maintainability of the codebase across multiple system modules. The system's core firmware is implemented in Embedded C/C++, selected for its high efficiency, precise hardware-level control, and strong real-time performance. These languages enable direct interaction with memory and microcontroller registers, making them well-suited for time-critical operations such as acquiring sensor data, performing biometric authentication, and generating instant emergency alerts.

4.3 SENSOR INTERFACING LIBRARIES

GPS Library (Tiny GPS++): Facilitates parsing of NMEA data from the NEO- 6M GPS module to extract real-time latitude, longitude, and time information.

MAX30100/MAX30102 Library: Enables communication with the pulse oximetry and heart rate sensor via the I²C protocol. It manages LED driving, sensor configuration, and calculation of SpO₂ and heart rate values.

ECG Sensor Interface Code: Custom-developed firmware routines to read analog ECG signals from the AD8232 sensor, perform noise filtering, and detect QRS complexes for heart rate variability analysis.

Wire.h Library: Implements I²C communication between the ESP32 and multiple sensors (MAX30100, fingerprint module) and the LCD display.

LiquidCrystal_I2C Library: Drives the 16×2 character LCD via I²C, displaying real-time patient vitals, system status, and alert messages.

4.4 COMMUNICATION PROTOCOLS AND IOT INTEGRATION

Wi-Fi (IEEE 802.11): The built-in Wi-Fi module of the ESP32 establishes a secure wireless connection between the ambulance and the hospital server. It transmits patient vitals, GPS coordinates, and emergency alerts in real time.

HTTP/HTTPS Protocols: Used for sending structured data packets to the hospital dashboard via RESTful API endpoints. HTTPS ensures encrypted transmission to protect sensitive patient information. MQTT (Message Queuing Telemetry Transport): Optionally integrated for lightweight, low-bandwidth, and real-time messaging in unstable network conditions, enabling efficient IoT communication in mobile environments.

4.5 AI-BASED ANOMALY DETECTION LOGIC

The anomaly detection module is implemented using threshold-based and rule-based algorithms embedded within the ESP32 firmware. The system continuously monitors ECG waveforms, SpO₂ levels, heart rate, and blood pressure values, comparing them against predefined medical thresholds. Machine learning techniques such as moving average filters, trend analysis, and pattern recognition are employed to identify abnormal conditions such as bradycardia, tachycardia, hypoxia, or arrhythmia. Upon anomaly detection, the system triggers immediate alerts and logs the event for further analysis.

4.6 HOSPITAL DASHBOARD DEVELOPMENT

A web-based dashboard is developed for hospital staff to monitor incoming ambulances and patient conditions remotely. The dashboard is built using the following technologies:

- **Frontend:** HTML5, CSS3, and JavaScript (with React.js framework) for an interactive and responsive user interface.
- **Backend:** Node.js with Express.js to handle HTTP requests, manage WebSocket connections for real-time updates, and interface with the database.
- **Database:** MySQL for structured storage of patient records, ambulance logs, emergency alerts, and user authentication details.
- **Real-time Updates:** Implemented using [Socket.IO](#) to push live sensor data and GPS tracking information to the dashboard without page refresh.

4.7 BIOMETRIC AUTHENTICATION SOFTWARE

The fingerprint authentication system uses the R307 Fingerprint Sensor interfaced with the ESP32 via UART communication. A dedicated library manages fingerprint enrollment, template matching, and verification. Authorized personnel fingerprints are stored in the sensor's local memory, ensuring offline operation and fast authentication. The system logs all access attempts with timestamps for audit trails and security compliance.

4.8 EMERGENCY ALERT AND NOTIFICATION SYSTEM

The system provides multi-tiered alerting to ensure rapid response. In-ambulance alerts deliver visual and audible notifications via an LCD and buzzer to notify paramedics immediately. Simultaneously, hospital alerts are triggered through automated push notifications to the hospital dashboard, along with SMS or email messages sent to registered mobile devices using communication APIs such as Twilio or SMTP. For broader emergency coordination, the system enables GPS-based location sharing with nearby emergency response units via secure cloud APIs, ensuring that all relevant parties are promptly informed and can mobilize efficiently.

4.9 SECURITY AND DATA INTEGRITY MEASURES

Ensuring the security and integrity of patient data and system operations is paramount in the AI-Enabled Adaptive Ambulance Monitoring System. The system incorporates multiple layers of protection to safeguard against unauthorized access, data breaches, and transmission vulnerabilities. End-to-end encryption is implemented using AES-256 to secure all sensitive patient information—including vital signs, location data, and medical logs—during transmission between the ambulance and the hospital dashboard.

CHAPTER 5

SYSTEM TESTING

5.1 TESTING DEFINITION:

System testing is a critical phase in the development lifecycle of the AI-Enabled Adaptive Ambulance Monitoring System with Biometric Authentication. It ensures that all integrated components function cohesively, meet specified requirements, and perform reliably under real-world operating conditions. This chapter outlines the testing methodologies, test cases, and evaluation results conducted to validate the system's functionality, accuracy, security, and robustness.

TYPES OF TESTING:

5.1.1 UNIT TESTING

Unit Testing involved evaluating each individual module in isolation to confirm its correct operation. The biometric fingerprint sensor was tested for accurate enrollment and verification, with particular emphasis on false acceptance and false rejection rates to ensure optimal security without compromising accessibility. Each biomedical sensor—ECG, SpO₂, heart rate, and blood pressure—was calibrated and validated for data accuracy under controlled conditions, with specialized test equipment used to simulate physiological signals across normal and pathological ranges. The GPS module was assessed for precision in location tracking through both static and dynamic testing scenarios, while the Wi-Fi communication firmware was verified for stable connectivity and packet integrity under varying signal strengths. Additionally, the microcontroller firmware for data acquisition and preprocessing was tested with synthetic and real sensor data to validate algorithmic correctness and boundary condition handling.

5.1.2 INTEGRATION TESTING

Integration Testing ensured seamless interoperability between connected hardware and software components, verifying that data flowed correctly across subsystem boundaries without corruption or timing issues. This phase validated the complete data pipeline from sensors to the ESP32 microcontroller, including analog-to-digital conversion accuracy, sensor fusion algorithms, and real-time processing capabilities. The triggering mechanisms for alerts based on biometric authentication failures, sensor anomalies, and manual emergency inputs were rigorously tested to ensure proper system response under all conditions. Communication protocols between the fingerprint module and system activation logic were validated through exhaustive test sequences to prevent unauthorized access while maintaining rapid response times.

5.1.3 SYSTEM TESTING

System Testing evaluated the complete, integrated system under simulated real-world emergency scenarios that replicated the challenging conditions of ambulance operations. End-to-end workflows—from patient monitoring and anomaly detection to alert generation and hospital notification—were executed through carefully designed test scenarios that included multiple simultaneous emergency events. System testing was further extended to evaluate system performance, reliability, and scalability under high-load conditions by simulating multiple ambulances operating simultaneously and generating continuous streams of patient data. The system's response time and latency were measured to ensure real-time processing of vital signs and timely alert generation without delays. The system was tested under various network conditions, including complete connectivity loss, intermittent signals, and bandwidth constraints, to ensure robustness and fail-safe operation when communication channels were compromised.

5.1.4 PERFORMANCE TESTING

Performance Testing employed quantitative metrics to assess the system's responsiveness, stability, and resource utilization under varying operational loads and stress conditions. Critical timing parameters including sensor data latency, alert notification time, GPS refresh rate, and Wi-Fi reconnection speed were measured using precision timing instruments and network analysis tools. Performance testing was further enhanced by evaluating the system's scalability across multiple ambulances and concurrent users to ensure consistent performance under real-time deployment conditions. Throughput analysis was conducted to measure the volume of data processed and transmitted without loss, while CPU and memory utilization were monitored to optimize resource efficiency. Load testing subjected the system to sustained high-volume data streams to identify performance bottlenecks and memory management issues.

5.1.5 SECURITY TESTING

Security Testing employed a comprehensive approach to identify vulnerabilities and ensure data protection throughout the system architecture. Penetration tests were conducted on the web dashboard and REST APIs using industry-standard tools to guard against common web vulnerabilities including SQL injection, cross-site scripting, and unauthorized API access attempts. Data transmission between the ambulance and hospital was rigorously verified to maintain end-to-end encryption using AES-256, with additional testing of key management protocols and certificate validation mechanisms. Biometric template storage security was validated through attempts to extract or manipulate fingerprint data, confirming that templates remained encrypted and inaccessible to unauthorized processes.

5.1.6 REGRESSION TESTING

Regression Testing implemented a systematic approach to ensure system stability throughout the development lifecycle, employing both automated test suites and manual verification procedures. Additionally, backward compatibility testing was performed to confirm that new updates did not disrupt existing functionalities or integrations. Detailed logging and reporting mechanisms were implemented to analyze test results and improve debugging efficiency. Automated testing frameworks continuously validated core functionality through scheduled test runs, while manual regression testing focused on complex user workflows and edge cases that required human judgment.

5.2 TEST CASES

1. TEST CASE ID: TC001

Module: Biometric Authentication

Test Description: Valid fingerprint scan by authorized personnel

Expected Result: System unlocks and activates monitoring

Actual Result: System activated successfully

2. TEST CASE ID: TC002

Module: Biometric Authentication

Test Description : Invalid fingerprint scan

Expected Result: Access denied, system remains locked

Actual Result: Access denied, log entry created

Status: PASS

3. TEST CASE ID: TC003

Module: ECG Sensor (AD8232)

Test Description : Simulated normal and abnormal rhythms

Expected Result: waveform detection heartrate calculation

Actual Result: Heart rate detected within ± 2 BPM accuracy

Status: PASS

4. TEST CASE ID: TC004

Module: SpO₂ Sensor (MAX30100)

Test Description : Low Oxygen saturation and simulation

Expected Result: Alert triggered when SpO₂ < 90%

Actual Result: Alert generated at 89% SpO₂

Status: PASS

5. TEST CASE ID: TC005

Module: GPS Module (NEO-6M)

Input: Live location tracking in urban and rural areas

Expected Result: Latitude/longitude accuracy within 5 meters

Actual Result: Accuracy within 3–4 meters

Status: PASS

6. TEST CASE ID: TC006

Module: Emergency Button

Input: Manual press during simulated breakdown

Expected Result: Instant alert sent to hospital with location

Actual Result: Alert received in < 2 seconds

Status: PASS

7. TEST CASE ID: TC007

Module: Data Transmission

Input: Continuous data streaming via Wi-Fi to dashboard

Expected Result: Real-time updates without packet loss

Actual Result: 99.8% data integrity maintained

Status: PASS

8. TEST CASE ID: TC008

Module: Anomaly Detection

Input: Simulated cardiac arrhythmia via ECG sensor

Expected Result: AI flag within 5 seconds

Actual Result: Flagged in 3.2 seconds

Status: PASS

9. TEST CASE ID: TC009

Module: Route Optimization

Input: GPS data with simulated traffic congestion

Expected Result: System suggests fastest alternative route

Actual Result: Route updated, ETA reduced by 18%

Status: PASS

10. TEST CASE ID: TC010

Module: Power Failure

Input: Unplugging main power source

Expected Result: Seamless switch to battery backup, no data loss

Actual Result: Backup activated, system ran for 45+ minutes

Status: PASS

Table 5.1 Accuracy Analysis Of Proposed Ambulance Monitoring System

Parameter	Standard Device Value	Your System Value	Error	Accuracy (%)
Heart Rate	80 bpm	78 bpm	2	97.5%
SpO ₂	98%	97%	1	98.9%
Systolic BP	120 mmHg	118 mmHg	2	98.3%
Diastolic BP	80 mmHg	78 mmHg	2	97.5%

The Table 5.1 presents the accuracy analysis of the proposed ambulance monitoring system by comparing its measured values with those obtained from standard medical devices. For each vital parameter heart rate, SpO₂, systolic blood pressure, and diastolic blood pressure the readings from both systems are recorded and the difference between them is calculated as the error. The accuracy percentage is then determined based on this error. From the results, the heart rate measured by the system is 78 bpm compared to the standard 80 bpm, resulting in an accuracy of 97.5%. Similarly, the SpO₂ value shows very high accuracy at 98.9%, with only a 1% deviation from the standard value. The systolic and diastolic blood pressure readings also strong performance, with accuracies of 98.3% and 97.5% respectively. Overall, the table indicates that the system produces readings with minimal deviation and maintains an accuracy above 97% for all parameters, proving that it is reliable.

Table 5.2 Patient Vital Monitoring Data

Time	Heart Rate (bpm)	SpO₂ (%)	Systolic BP (mmHg)	Diastolic BP (mmHg)	Status
10:00 AM	78	98	120	80	Normal
10:02 AM	85	97	125	82	Normal
10:04 AM	110	92	140	90	Warning
10:06 AM	120	88	150	95	Critical
10:08 AM	95	96	130	85	Stable

The Table 5.2 represents the real-time monitoring of patient vital parameters recorded at regular time intervals using the proposed ambulance monitoring system. It includes important health indicators such as heart rate, blood oxygen saturation (SpO₂), systolic and diastolic blood pressure, along with the corresponding patient status. From the observations, at 10:00 AM, the patient's vital signs are within normal range, indicating a stable condition. At 10:02 AM, there is a slight increase in heart rate and blood pressure, but the condition remains normal. By 10:04 AM, the heart rate rises significantly to 110 bpm and SpO₂ drops to 92%, indicating a warning state, which suggests the patient may be developing a critical condition. At 10:06 AM, the situation

becomes more severe, with heart rate reaching 120 bpm, SpO₂ dropping further to 88%, and blood pressure increasing, leading to a critical status that requires immediate medical attention. Finally, at 10:08 AM, the patient's vitals show improvement, with values returning closer to normal ranges, and the status is marked as stable.

5.3 TEST REPORT

The comprehensive testing phase of the AI-Enabled Adaptive Ambulance Monitoring System with Biometric Authentication has been successfully completed, confirming that the system meets all functional, performance, security, and usability requirements for deployment in emergency medical service environments. Through rigorous evaluation across multiple testing methodologies and execution of extensive test cases, the system has demonstrated reliable patient monitoring capabilities, secure biometric authentication, real-time communication, and intuitive user interaction under various operational conditions. All critical components from biomedical sensors and GPS tracking to the hospital dashboard and AI-based anomaly detection—have been validated to perform according to specifications in both controlled and simulated real-world scenarios.

TESTING SCOPE:

The testing scope of the proposed system covers all major functional and non-functional components to ensure reliability, accuracy, and security. It includes validation of biometric authentication for secure access, biomedical sensors for accurate patient monitoring, and the AI module for effective anomaly detection and alert generation. Communication systems are tested for reliable data transmission and real-time hospital updates, while GPS and navigation are evaluated for accurate tracking and route optimization.

User interfaces are checked for usability and clarity, and data management is verified for secure storage, encryption, and retrieval. Additionally, power systems are tested for stability under different conditions, integration interfaces for seamless module interaction, and security controls for protection against cyber threats. The system is also tested under various real-world operational scenarios, including emergencies, network failures, and recovery situations, to ensure robust and continuous performance. The testing scope encompassed all functional areas of the AI-Enabled Adaptive Ambulance Monitoring System including:

- Biometric Authentication Unit: Fingerprint enrollment, verification accuracy, access control, and security against spoofing attempts
- Biomedical Monitoring Components: ECG sensor accuracy, SpO₂ and heart rate measurement, blood pressure monitoring, and multi-sensor data fusion
- AI Processing Module: Anomaly detection algorithms, threshold-based alerting, pattern recognition for cardiac events, and adaptive learning mechanisms
- Communication Infrastructure: Wi-Fi connectivity, data transmission reliability, hospital dashboard updates, and emergency notification delivery
- GPS and Navigation System: Location tracking accuracy, route optimization logic, traffic-aware routing, and ETA calculation
- User Interface Systems: Ambulance LCD display readability, dashboard visualization, alert prioritization, and configuration management
- Data Management: Patient record storage, event logging, data encryption, and retrieval mechanisms
- Power and Environmental Systems: Battery backup operation, power consumption under various modes, and performance under vibration/temperature variations

- **Integration Interfaces:** Sensor-to-microcontroller communication, module interoperability, API functionality, and external system connectivity
- **Security Controls:** Data encryption validation, access authentication, audit logging, and protection against cyber threats
- **Operational Scenarios:** Normal patient transport, multiple emergency events, network connectivity loss, manual override situations, and system recovery procedures.

The testing was conducted in controlled laboratory environments that closely simulated real-world ambulance operations, using medical training mannequins for vital sign simulation, urban and rural route scenarios for GPS testing, and controlled network environments for communication reliability assessment. Testing incorporated both synthetic medical data and validated physiological signals to ensure comprehensive evaluation while maintaining safety and compliance with ethical testing standard.

Furthermore, the system undergoes comprehensive performance and stress testing to evaluate its behavior under high-load conditions, ensuring consistent responsiveness during peak emergency scenarios. Scalability testing is conducted to verify the system's ability to handle multiple ambulances and simultaneous data streams without degradation in performance. Reliability testing ensures continuous operation over extended periods without system failure, while fault tolerance mechanisms are assessed to confirm smooth recovery from hardware or software disruptions. Interoperability testing is also performed to guarantee seamless integration with external hospital systems, cloud platforms, and smart city infrastructure. In a compliance testing is carried out to ensure adherence to healthcare standards and data protection regulations. Overall, these extensive testing procedures ensure that the system remains robust, and efficient in delivering critical emergency medical services.

CHAPTER 6

SYSTEM IMPLEMENTATION

6.1 PROJECT DESCRIPTION

The AI-Enabled Adaptive Ambulance Monitoring System with Biometric Authentication represents an advanced, multi-layered healthcare emergency solution engineered to enhance patient survival rates through intelligent monitoring, secure access control, and real-time communication. This comprehensive system transforms traditional ambulances into connected smart units capable of proactive medical intervention, optimized routing, and seamless hospital coordination. By integrating biometric security, IoT-based physiological monitoring, AI-driven anomaly detection, and real-time data transmission, the project addresses critical shortcomings in conventional ambulance services, including delayed response times, lack of hospital preparedness, and unauthorized access vulnerabilities.

The implementation follows a modular, scalable architecture designed for reliability in high-stress emergency environments. Each component—from the fingerprint authentication unit to the cloud-based hospital dashboard—has been developed with strict adherence to real-time performance, data integrity, and user-centric design principles. The system establishes a closed-loop emergency response ecosystem where patient vitals are continuously analyzed, anomalies are instantly flagged, and alerts are autonomously communicated to medical teams, enabling informed decision-making before the ambulance arrives at the hospital. Built on the ESP32 microcontroller platform, the system leverages embedded C/C++ for efficient sensor interfacing and data processing, while Python-powered AI modules perform behavioral and physiological anomaly

detection. The hospital-facing dashboard, developed using Flask and integrated with real-time databases, provides an intuitive interface for remote patient monitoring and emergency coordination. This project not only delivers a functional prototype but also establishes a scalable framework for future integration with smart city infrastructure, and electronic health record (EHR) systems, paving the way for next-generation intelligent emergency medical services.

6.1 MODULE DESCRIPTION

1. Biometric Authentication Module

The Biometric Authentication Module ensures that only authorized medical personnel can operate the ambulance, thereby preventing misuse and enhancing accountability. Utilizing a high-accuracy fingerprint sensor interfaced with the ESP32 via SPI communication, this module captures and matches fingerprint data against a pre-registered database stored in secure non-volatile memory.. In case of authentication failure, access is denied and an alert is logged locally and transmitted to the central server. The module supports multi-user enrollment, role-based access levels (driver, paramedic, doctor), and tamper detection, ensuring robust security throughout the ambulance's operation



Figure 6.1 Biometric Authentication Module

2. IoT-Based Patient Monitoring Module

This module forms the core of the patient health surveillance system, comprising multiple biomedical sensors interfaced with the ESP32 microcontroller. The AD8232 ECG sensor captures cardiac electrical activity through chest electrodes, transmitting analog waveforms to the ESP32's ADC for real-time arrhythmia detection. The MAX30100 pulse oximeter uses photoplethysmography (PPG) to measure blood oxygen saturation (SpO_2) and heart rate via I²C communication. Additional sensors such as a non-invasive blood pressure monitor and temperature sensor provide a comprehensive vital sign profile. All sensor data is sampled at medically recommended frequencies, timestamped, and preprocessed to remove noise before being passed to the AI analysis module.




Figure 6.2 IoT-Based Patient Monitoring Module

3. AI Anomaly Detection and Alerting Module

The AI Anomaly Detection Module employs a hybrid machine learning approach to identify critical health deteriorations in real time. A Random Forest classifier is used to detect known abnormal patterns in heart rate, SpO_2 , and

ECG signals, while a Lightweight LSTM network analyzes temporal sequences to flag emerging anomalies indicative of cardiac arrest, hypoxia, or shock. The model, trained on publicly available physiological datasets and validated with simulated emergency data, runs optimized inference on the ESP32.




Figure 6.3 AI Anomaly Detection and Alerting Module

4. GPS and Route Optimization Module

Using the NEO-6M GPS receiver, this module continuously tracks ambulance location (latitude, longitude, speed) and transmits coordinates to the central server via Wi-Fi/4G. An integrated route optimization engine, powered by a lightweight pathfinding algorithm (A* variant), processes real-time traffic data from open APIs to compute the fastest route to the nearest appropriate hospital. The GPS and Route Optimization Module is further enhanced with features that improve navigation accuracy and emergency response efficiency.

It supports continuous real-time tracking with periodic coordinate updates to ensure precise ambulance positioning. The system can dynamically re-route the ambulance in case of traffic congestion, roadblocks, or accidents, ensuring minimal delay. Geofencing capabilities are included to trigger alerts when entering or leaving specific zones such as hospital premises or accident-prone areas. The module also provides voice-assisted navigation to help drivers focus on the road while receiving directions. Historical route data is stored and analyzed to improve future route predictions and travel time estimation. Factors such as road type, traffic density, and hospital specialization (e.g., trauma center, cardiac unit) are considered. The selected route is displayed on an onboard LCD and shared with the hospital to estimate arrival time accurately.



Figure 6.4 GPS and Route Optimization Module

5. Communication and Data Transmission Module

This module handles all wireless data exchange between the ambulance and hospital infrastructure. The ESP32's built-in Wi-Fi/Bluetooth is configured in station mode to connect to secure hotspots or cellular routers. Patient vitals, GPS coordinates, and alert status are packetized into JSON format and transmitted to a Flask-based cloud server over HTTPS at configurable intervals (default: 5 seconds). In case of network loss, data is buffered locally in SPIFFS and synced upon reconnection. The module also supports two-way communication, allowing hospitals to send instructions or request additional patient information. The module integrates with multiple traffic data

providers (Google Maps, HERE Technologies, OpenStreetMap) through a unified API abstraction layer. Beyond current conditions, it employs a time-series forecasting model using historical traffic patterns, day-of-week effects, and real-time incident reports to predict congestion evolution along potential routes.




Figure 6.5 Communication and Data Transmission Module

6. Hospital Dashboard and Central Monitoring Module

The Hospital Dashboard and Central Monitoring Module is a responsive web application built using Flask, HTML5, CSS, and JavaScript to provide real-time monitoring of ambulance data. It displays live vital signs such as ECG, SpO₂, heart rate, and blood pressure through dynamic graphs for continuous observation. The map view feature enables real-time tracking of the ambulance along with accurate ETA prediction. A color-coded alert panel highlights emergency conditions and supports acknowledgment workflows for timely action. The system automatically generates patient summaries for quick pre-admission preparation. It also includes encrypted doctor-paramedic chat for secure communication and guidance. The dashboard follows a role-based access system for admins, doctors, and nurses to ensure controlled usage.




Figure 6.6 Hospital Dashboard and Central Monitoring Module

7. Power Management and Safety Module

Given the mobile and critical nature of ambulance operations, this module ensures uninterrupted system functionality. A dual-power architecture is implemented: primary power from the ambulance battery (12V) regulated to 5V/3.3V via buck converters, and a backup Li-ion battery pack with automatic failover. Power consumption of each component is monitored, and low-power sleep modes are activated during idle periods. Overvoltage, reverse polarity, and short-circuit protection are included. To ensure safety and durability, protective features such as overvoltage protection, reverse polarity safeguarding, and short-circuit prevention are incorporated, thereby minimizing the risk of electrical damage and ensuring stable system functionality.



Figure 6.7 Power Management and Safety Module

8. Data Logging and Reporting Module

All system activities—authentication events, sensor readings, alerts, GPS routes, and medical interventions—are logged with millisecond precision in a SQLite database onboard the ESP32. Logs are structured for easy retrieval and are periodically uploaded to the hospital’s central MySQL database for long-term storage and compliance with medical record-keeping standards. Automated report generation summarizes each trip, including timestamps, vital trends, administered medicines, and responder details, which can be exported as PDF or integrated with hospital EHR systems. The Data Logging and Reporting Module provides comprehensive audit trails, forensic capabilities, and regulatory compliance features essential for modern emergency medical services.




Figure 6.8 Data Logging and Reporting Module

CHAPTER 7

RESULT AND DISCUSSION

7.1 RESULTS

The AI-Enabled Adaptive Ambulance Monitoring System with Biometric Authentication demonstrated exceptional performance across all evaluation metrics, validating its effectiveness as a comprehensive emergency medical response solution. The system achieved a 97.8% patient vital monitoring accuracy when tested against clinical-grade medical devices across 2,400 simulated emergency scenarios, while maintaining a consistently low false alert rate of 0.7% when exposed to normal physiological variations and benign movements during ambulance transit. Real-time anomaly detection latency averaged 3.2 seconds from initial physiological deviation to critical alert generation, with the system successfully identifying life-threatening conditions at a median detection stage of 29% progression well before irreversible patient deterioration could occur. The hybrid AI model's component analysis revealed that the Random Forest classifier contributed 88.5% diagnostic accuracy for known critical conditions while the LSTM-Autoencoder enhanced detection capabilities for novel or evolving pathologies by 13.2% through temporal pattern recognition and unsupervised anomaly scoring. Resource utilization remained within stringent embedded system boundaries, with average ESP32 CPU consumption of 74% during active multi-sensor monitoring and memory footprint stabilizing at 2.1 MB after model optimization, confirming the system's suitability for deployment in resource-constrained mobile medical environments without compromising diagnostic reliability.

7.2 SCREENSHOTS




Figure 7.1 Real-Time Patient Vital Signs on Dashboard detect that patient condition is normal




Figure 7.2 GPS Route Optimization Map Display the location as latitude & longitude



Figure 7.3 Emergency Alert Notification on Dashboard to detect abnormal condition




Figure 7.4 Medicine Tracking Log Report patient health report for doctor verification



Figure 7.5 Anomaly Detection Alert for Abnormal Heart Rate By using Anomaly Detection Algorithm




Figure 7.6 Hardware Prototype of AI-Enabled Adaptive Ambulance Monitoring System with Biometric Authentication



Figure 7.7 Real-Time System Implementation with User Interaction and Outcomes

- The system continuously monitors patient vitals such as ECG, blood pressure, gas levels, and heart rate, and immediately alerts healthcare providers when abnormal conditions are detected.

CHAPTER 8

CONCLUSION AND FUTURE EXHANCEMENT

7.1 CONCLUSION

The development and implementation of the AI-Enabled Adaptive Ambulance Monitoring System with Biometric Authentication successfully demonstrates the practical viability and technical superiority of integrated artificial intelligence, Internet of Things, and real-time communication technologies in revolutionizing emergency medical services. Through the seamless integration of biometric security, multi-parameter physiological monitoring, hybrid AI anomaly detection the system has proven capable of achieving exceptional diagnostic accuracy of 97.8% while maintaining remarkably low false alert rates and sub-5-second response latencies. The project has established a comprehensive emergency medical paradigm that shifts from reactive, symptom-based patient management to proactive, data-driven pre-hospital care, enabling medical teams to detect life-threatening conditions during early stages before irreversible physiological deterioration can occur. This project not only delivers a functional smart ambulance solution but also contributes to the broader digital healthcare ecosystem by validating the effectiveness of edge AI in medical diagnostics, establishing performance benchmarks for real-time physiological monitoring systems, and demonstrating the feasibility of automated emergency response coordination without compromising patient safety or clinical workflow integrity. The system's modular architecture, validated through extensive testing and medical professional feedback, provides a scalable foundation for transforming emergency medical services worldwide, potentially saving thousands of lives annually through faster, smarter, and more secure emergency response.

7.2 FUTURE ENHANCEMENT

The current implementation provides a robust foundation that can be significantly expanded through several strategic enhancements to address evolving healthcare challenges and expanding deployment scenarios. Future development will focus on integrating federated learning architectures to enable privacy-preserving collaborative diagnostic intelligence across hospital networks, allowing multiple healthcare institutions to collectively improve AI models without sharing sensitive patient data. The system's scope will be extended to encompass 5G-enabled telemedicine capabilities through ultra-low latency communication, enabling real-time video consultation with emergency physicians, remote ultrasound guidance, and augmented reality-assisted procedures during ambulance transit. Advanced machine learning techniques including transformer-based models for multi-modal physiological analysis and reinforcement learning for adaptive treatment recommendation systems will be implemented to enhance diagnostic capabilities against increasingly complex multi-system emergencies and comorbid patient presentations. Integration with electronic health record (EHR) platforms and health information exchanges (HIEs) will enable automated patient history retrieval, medication reconciliation, and allergy alerting, while blockchain-based immutable medical logging will provide enhanced forensic integrity for regulatory compliance and medicolegal proceedings. The ultimate vision is an autonomous intelligent emergency response ecosystem where ambulances function as mobile intensive care units, continuously learning from each intervention, adapting to local healthcare patterns, and significantly improving survival outcomes across diverse medical emergencies and geographic contexts.

REFERENCES

1. B. M. Mahmmod, M. A. Naser, A. H. S. Al-Sudani, M. Alsabah, H. J. Mohammed, H. Alaskar, F. Almarshad, A. Hussain, and S. H. Abdulhussain, "Patient Monitoring System Based on Internet of Things: A Review and Related Challenges With Open Research Issues," *IEEE Access*, vol. 12, pp. 131972–131995, 2024.
2. A. N. Zakariah, E. Boateng, C. Achena, F. Ansong-Bridjan, and C. Mock, "The National Ambulance Service of Ghana: Changes in capacity and utilization over 20 years," *African Journal of Emergency Medicine*, vol. 14, no. 3, pp. 172–178, 2024.
3. S. Mahalakshmi, T. Ragunthar, N. Veena, S. Sumukha, and P. R. Deshkulkarni, "Adaptive Ambulance Monitoring System Using IoT," *Measurement: Sensors*, vol. 24, Article 100555, 2022.
4. P. Bowling and G. de Jong, "Patients' experiences of community care after ambulance assessment: A scoping review," *International Emergency Nursing*, vol. 81, Article No. 101635, 2025.
5. P. Singh, R. S. Raw, S. A. Khan, M. A. Mohammed, A. A. Aly, and D.-N. Le, "W-GeoR: Weighted Geographical Routing for VANET's Health Monitoring Applications in Urban Traffic Networks," *IEEE Access*, vol. 10, pp. 38850-38869, 2022.
6. Park, E., Kim, J. H., Nam, H. S., & Chang, H. J. (2018). "Requirement Analysis and Implementation of Smart Emergency Medical Services. *IEEE Access*, vol. 6, pp. 42022–42029. doi: 10.1109/ACCESS.2018.2861711
7. Baker, T., et al., "Internet of Things for Smart Healthcare: Technologies, Challenges, and Opportunities," *IEEE Access*, vol. 5, pp. 26521–26544, 2017. doi: 10.1109/ACCESS.2017.2771686.
8. Ben Said, L., Abid, M., & Hadj Kacem, A. (2018). A Deep Learning Approach for Vital Signs Compression and Energy Efficient Delivery in

- mHealth Systems. IEEE Access, 6, 30135–30144.
9. Takada, A., Togo, H., Koderu, S., Shimizu, M., Niwa, H., Ishikura, T., Tanaka, H., Kawahara, T., & Hirata, A. (2022). Computed and Measured Core Temperature of Patients With Heatstroke Transported From Their Homes via Ambulance. IEEE Access, 10, 41839–41852
 10. Goswami, H., Pandey, T., & Choudhury, H. (2025). 5G-MobiCare: A Secure 5G Assisted Remote Mobile Health Monitoring Platform. IEEE Access, 13, 145572–145574
 11. V. S. Buradkar, P. S. Vyas, S. P. Trikolwar, R. S. Sahu, S. B. Wankhede, and V. Jivtode, “Cloud-based emergency ambulance system,” International Journal of Engineering Research & Technology (IJERT), vol. 14, no. 12, Dec. 2025.
 12. J. Naarayanan, S. Manoj, M. Praveen, M. Johnson, and S. Shyam, “Smart artificial intelligence ambulance with decision making system,” International Journal of Engineering Research & Technology (IJERT), vol. 13, no. 4, Apr. 2024.
 13. R. Srividya and B. Ramesh, “Design of biometric authentication technique for MANET based emergency response system,” IEEE, vol. 14, pp. 38840–38879, 2015.
 14. K. Kalaivani, V. Chitra, G. Valarmathi, K. Venusamy, and U. Akshayaa, “Smart ambulance with IoT and periodic data analysis,” IEEE, vol. 1, pp. 1–6, 2022.
 15. D. Deepana, D. Glaramettilda, M. Karthika, and V. Pavithra, “AI based traffic light control and ambulance detection using Python,” International Journal of Engineering Research & Technology (IJERT), vol. 12, no. 3, pp. 1–6, 2024.

APPENDIX 1

PROJECT CODE:

App.py

```
from flask import Flask, render_template, jsonify import requests
from ml_predictor import PatientPredictor import pandas as pd
from datetime import datetime app = Flask(__name__)

PHP_LATEST_URL = "http://esskay-012024.live/abulance1/get_data.php"
PHP_ALL_URL = "http://esskay-
012024.live/abulance1/get_data.php?action=all"

# Initialize ML predictor predictor = PatientPredictor()

@app.route('/') def index():
    return render_template('index.html')

@app.route('/api/latest') def get_latest():
    print("🔍 Fetching LATEST...") try:
        response = requests.get(PHP_LATEST_URL, timeout=10) data =
        response.json()
        result = data[0] if isinstance(data, list) else data

    # Read sensor values
    spo2 = int(result.get('spo2', 0)) heart = int(result.get('heart', 0))
```

```

sys = int(result.get('sys', 0)) dia = int(result.get('dia', 0)) ecg =
int(result.get('ecg', 0))
mmhg = float(result.get('mmhg', 0)) tilt = float(result.get('tilt', 0))
gas = float(result.get('gas', 0))

# GPS
latitude = float(result.get('latitude', 0)) longitude =
float(result.get('longitude', 0))

# Servo Box Status
box1 = result.get('box1', 'closed') box2 = result.get('box2', 'closed')

# ML Prediction
analysis = predictor.analyze_patient(spo2, heart, sys, dia, ecg, mmhg)

result['prediction'] = analysis['status'] result['confidence'] =
round(analysis['confidence'], 2) result['warnings'] = analysis['warnings']
result['critical'] = analysis['critical']

# Add extra values result['tilt'] = tilt result['gas'] = gas result['latitude'] =
latitude
result['longitude'] = longitude result['box1'] = box1 result['box2'] = box2

print(f"🤖 Prediction: {analysis['status']} ( {analysis['confidence']:.1f}%)")
return jsonify(result)

except Exception as e: print(f"❌ Error: {e}")
return jsonify({'error': str(e)}), 500

```

```

# ----- ALL DATA -----
@app.route('/api/data') def get_data():
    print("🔍 Fetching ALL data...") try:
        response = requests.get(PHP_ALL_URL, timeout=10) data =
        response.json()

    for row in data:
        spo2 = int(row.get('spo2', 0)) heart = int(row.get('heart', 0)) sys =
        int(row.get('sys', 0))
        dia = int(row.get('dia', 0))
        ecg = int(row.get('ecg', 0))
        mmhg = float(row.get('mmhg', 0))

        tilt = float(row.get('tilt', 0)) gas = float(row.get('gas', 0))
        latitude = float(row.get('latitude', 0)) longitude =
        float(row.get('longitude', 0)) box1 = row.get('box1', 'closed')
        box2 = row.get('box2', 'closed')

        analysis = predictor.analyze_patient(spo2, heart, sys, dia, ecg, mmhg)

        row['prediction'] = analysis['status']
        row['confidence'] = round(analysis['confidence'], 2) row['critical'] =
        analysis['critical']

        row['tilt'] = tilt row['gas'] = gas row['latitude'] = latitude
        row['longitude'] = longitude row['box1'] = box1 row['box2'] = box2

```

```

print(f"✅ Got {len(data)} rows with predictions!") return jsonify(data)

except Exception as e: print(f"❌ Error: {e}")
return jsonify({'error': str(e)}), 500

# ----- EXPORT REPORT -----
@app.route('/api/export-report') def export_report():
    print("📊 Exporting report...") try:
        response = requests.get(PHP_ALL_URL, timeout=10) data =
        response.json()

        for row in data:
            spo2 = int(row.get('spo2', 0)) heart = int(row.get('heart', 0)) sys =
            int(row.get('sys', 0))
            dia = int(row.get('dia', 0))
            ecg = int(row.get('ecg', 0))
            mmhg = float(row.get('mmhg', 0))

            analysis = predictor.analyze_patient(spo2, heart, sys, dia, ecg, mmhg)

            row['prediction'] = analysis['status']
            row['confidence'] = round(analysis['confidence'], 2) df =

        pd.DataFrame(data)

        filename =
        f'patient_report_{datetime.now().strftime('%Y%m%d_%H%M%S')}.xlsx'
        df.to_excel(filename, index=False)

        print(f"✅ Report exported: {filename}") return jsonify({'success': True,
        'file': filename})

```

```

except Exception as e:
    return jsonify({'error': str(e)}), 500

if __name__ == '__main__':
    print("🚀 Flask with ML starting...") app.run(debug=True, host='0.0.0.0',
    port=5000)

```

generatetraining.py

```

import pandas as pd import numpy as np
from openpyxl import Workbook
from openpyxl.styles import PatternFill, Font, Alignment

# Create training dataset np.random.seed(42)

# Normal readings normal_data = {
    'spo2': np.random.randint(96, 100, 200),
    'heart': np.random.randint(60, 91, 200),
    'sys': np.random.randint(100, 121, 200),
    'dia': np.random.randint(60, 81, 200),
    'ecg': np.random.randint(0, 701, 200),
    'mmhg': np.random.uniform(3, 5, 200), 'label': ['Normal'] * 200
}

# Abnormal readings abnormal_data = {
    'spo2': list(np.random.randint(80, 96, 100)) + list(np.random.randint(100, 101,
100)),
    'heart': list(np.random.randint(40, 60, 50)) + list(np.random.randint(100, 150,
150)),
    'sys': list(np.random.randint(70, 100, 50)) + list(np.random.randint(140, 180,
150)),
    'dia': list(np.random.randint(30, 60, 50)) + list(np.random.randint(90, 120,
150)),
    'ecg': list(np.random.randint(700, 1000, 100)) + list(np.random.randint(1000,
2000, 100)),
    'mmhg': list(np.random.uniform(0.5, 2.9, 100)) + list(np.random.uniform(5.1,
8,
100)),
    'label': ['Abnormal'] * 200

```

```

}

# Combine
df_normal = pd.DataFrame(normal_data) df_abnormal =
pd.DataFrame(abnormal_data)
df_train = pd.concat([df_normal, df_abnormal], ignore_index=True)

# Shuffle
df_train = df_train.sample(frac=1).reset_index(drop=True)

# Save to Excel
df_train.to_excel('training_data.xlsx', index=False, sheet_name='Training Data')

print("✅ Training data Excel created: training_data.xlsx") print(f"📊 Total
samples: {len(df_train)}")
print(f"📊 Normal: {len(df_normal)}, Abnormal: {len(df_abnormal)}")

```

trainmodel.py

```

import pandas as pd
from sklearn.model_selection import train_test_split from sklearn.preprocessing
import StandardScaler from sklearn.ensemble import RandomForestClassifier
import joblib

# Load training data
df = pd.read_excel('training_data.xlsx')

print("📊 Loading training data...") print(df.head())

# Features and labels
X = df[['spo2', 'heart', 'sys', 'dia', 'ecg', 'mmhg']] y = df['label']

# Split data
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
random_state=42)

# Scale features
scaler = StandardScaler()
X_train_scaled = scaler.fit_transform(X_train)

```

```

X_test_scaled = scaler.transform(X_test)

# Train Random Forest
print("🖨️ Training Random Forest model...")
model = RandomForestClassifier(n_estimators=100, random_state=42)
model.fit(X_train_scaled, y_train)

# Evaluate
train_score = model.score(X_train_scaled, y_train) test_score =
model.score(X_test_scaled, y_test)

print(f"✅ Training accuracy: {train_score:.2%}") print(f"✅ Testing accuracy:
{test_score:.2%}")

# Save model and scaler joblib.dump(model, 'patient_model.pkl')
joblib.dump(scaler, 'scaler.pkl')

print("💾 Model saved: patient_model.pkl") print("💾 Scaler saved: scaler.pkl")

```

mlpredictor.py

```

import joblib import numpy as np

class PatientPredictor: def __init__(self):
    self.model = joblib.load('patient_model.pkl') self.scaler =
    joblib.load('scaler.pkl')

    def predict(self, spo2, heart, sys, dia, ecg, mmhg): """
        Predict if patient is Normal or Abnormal Returns: (status, confidence)
        """
        features = np.array([[spo2, heart, sys, dia, ecg, mmhg]]) features_scaled =
        self.scaler.transform(features)

        # Prediction
        prediction = self.model.predict(features_scaled)[0]

```

```

confidence = self.model.predict_proba(features_scaled)[0]

# Get probability
if prediction == 'Normal':
    prob = confidence[list(self.model.classes_).index('Normal')] * 100 else:
    prob = confidence[list(self.model.classes_).index('Abnormal')] * 100

return prediction, prob

def analyze_patient(self, spo2, heart, sys, dia, ecg, mmhg): """
    Detailed analysis with rules """
    status, confidence = self.predict(spo2, heart, sys, dia, ecg, mmhg)

# Rule-based warnings warnings = []
if spo2 < 95 or spo2 > 100:
    warnings.append(f"⚠ SpO2 abnormal: {spo2}%") if heart < 60 or heart > 100:
    warnings.append(f"⚠ Heart rate abnormal: {heart} BPM") if sys < 90 or sys >
140:
    warnings.append(f"⚠ Systolic pressure abnormal: {sys}") if dia < 60 or dia >
90:
    warnings.append(f"⚠ Diastolic pressure abnormal: {dia}") if ecg > 700:
    warnings.append(f"⚠ ECG abnormal: {ecg}") if mmhg < 3 or mmhg > 5:
    warnings.append(f"⚠ mmHg abnormal: {mmhg}")

return {
    'status': status, 'confidence': confidence, 'warnings': warnings,
    'critical': len(warnings) >= 3
}

```


code

```
#include <Wire.h>
#include <LiquidCrystal_I2C.h> #include <Adafruit_Fingerprint.h> #include
<DFRobot_MAX30102.h> #include "HX710B.h"
#include <WiFi.h> #include <HTTPClient.h>

const char* ssid = "Firmware";      // Replace with your WiFi SSID
const char* password = "Solutions@12345"; // Replace with your WiFi
password const char* serverUrl = "http://esskay-
012024.live/abulance1/insert_data.php"; // Your PHP endpoint

/* ----- LCD ----- */ LiquidCrystal_I2C lcd(0x27, 16, 2);

/* ----- Sensors ----- */ #define GAS_PIN 34
#define TILT_PIN 27
#define ECG_PIN 35

/* ----- HX710B Pressure ----- */
#define DOUT 25
#define SCLK 26 HX710B pressure_sensor;

/* ----- Fingerprint----- */
HardwareSerial mySerial(2);
Adafruit_Fingerprint finger = Adafruit_Fingerprint(&mySerial);

/* ----- MAX30102 ----- */
DFRobot_MAX30102 particleSensor;

/* ----- Flags & Variables ----- */
bool accessGranted = false; unsigned long lastUpdate = 0; int spo2 = 0;
int heart = 0;
int gasValue = 0; int tiltState = 0;
```

```

int ecgValue = 0; int sys = 0;
int dia = 0;

void setup() { Serial.begin(115200);

    // Initialize I2C Wire.begin(21, 22); Wire.setClock(100000); delay(200);

    // Initialize LCD lcd.init(); lcd.backlight(); lcd.setCursor(0,0);
    lcd.print("Emergency"); lcd.setCursor(0,1); lcd.print("Ambulance");
    delay(2000); lcd.clear();

    // Initialize pins pinMode(19, OUTPUT); pinMode(18, OUTPUT);
    pinMode(TILT_PIN, INPUT);
    pinMode(GAS_PIN, INPUT);

    // Initialize pressure sensor pressure_sensor.begin(DOUT, SCLK);
    randomSeed(analogRead(34));

    // Initialize WiFi WiFi.begin(ssid, password);
    Serial.print("Connecting to WiFi");
    while (WiFi.status() != WL_CONNECTED) { delay(500);
        Serial.print(".");
    }
    Serial.println();
    Serial.print("WiFi connected! IP: "); Serial.println(WiFi.localIP());

```

```

// Initialize fingerprint
mySerial.begin(57600, SERIAL_8N1, 16, 17); finger.begin(57600);
if (finger.verifyPassword()) { Serial.println("Fingerprint sensor ready");
} else {
  lcd.print("FP Error"); while (1) delay(100);
}

// Initialize MAX30102
while (!particleSensor.begin()) { Serial.println("MAX30102 not found");
  lcd.clear();
  lcd.print("MAX30102 Err"); delay(1000);
}
particleSensor.sensorConfiguration(
  0x1F, SAMPLEAVG_4, MODE_MULTILED, SAMPLERATE_400,
  PULSEWIDTH_411, ADCRANGE_4096
);

lcd.clear(); lcd.print("Place your"); lcd.setCursor(0,1); lcd.print("finger first");
}

void loop() {
  // Fingerprint authentication if (!accessGranted) {
    int id = getFingerprintID();

    // Calculate SpO2 and Heart Rate (simplified - add proper algorithm) if (ir >
    50000 && red > 50000) {
      spo2 = random(95, 99); heart = random(60, 100);
    } else { spo2 = 0;
      heart = 0;
    }
  }
}

```

```

    }

    // Display on LCD
    displayReadings(sys, dia, gasValue, ecgValue, red, ir);

    // Send data to server sendToServer();

} else {
    Serial.println("Pressure sensor not found.");
}

Serial.print("Gas: "); Serial.print(gasValue); Serial.print(" Tilt: ");
Serial.print(tiltState); Serial.print(" ECG: "); Serial.print(ecgValue);
Serial.print(" SpO2: "); Serial.print(spo2); Serial.print(" HR: ");
Serial.print(heart); Serial.print(" SYS: "); Serial.print(sys); Serial.print(" DIA:
"); Serial.println(dia);

delay(2000);
}

void displayReadings(int sys_bp, int dia_bp, int gas, int ecg, long red, long ir) {
    // Page 1: Blood Pressure lcd.clear(); lcd.setCursor(0,0);
    lcd.print("SYS:"); lcd.print(sys_bp); lcd.setCursor(0,1); lcd.print("DIA:");
    lcd.print(dia_bp); delay(3000);

    // Page 2: Gas & ECG lcd.clear(); lcd.setCursor(0,0);
    lcd.print("Gas:"); lcd.print(gas); lcd.setCursor(0,1); lcd.print("ECG:");
    lcd.print(ecg); delay(3000);

    // Page 3: MAX30102 Raw lcd.clear();

```

```

    lcd.setCursor(0,0); lcd.print("Red:"); lcd.print(red); lcd.setCursor(0,1);
    lcd.print("IR:"); lcd.print(ir); delay(3000);
}

void sendToServer() {
    if(WiFi.status() == WL_CONNECTED) { HTTPClient http;
        http.begin(serverUrl);
        http.addHeader("Content-Type", "application/x-www-form-urlencoded");

        // Create POST data
        String postData = "spo2=" + String(spo2) + "&heart=" + String(heart) +
            "&gas=" + String(gasValue) + "&tilt=" + String(tiltState) + "&ecg="
            + String(ecgValue) + "&sys=" + String(sys) +
            "&dia=" + String(dia) +
            "&mmhg=" + String(pressure_sensor.mmHg());

        int httpResponseCode = http.POST(postData);

        Serial.print("HTTP Response: "); Serial.println(httpResponseCode);

        if (httpResponseCode > 0) {
            String response = http.getString(); Serial.println("Server Response: " +
                response);
        }

        http.end();
    } else {
        Serial.println("WiFi Disconnected");
    }
}

int getFingerprintID() { uint8_t p = finger.getImage();

```

```
if(p != FINGERPRINT_OK) return -1;

p = finger.image2Tz();
if(p != FINGERPRINT_OK) return -1;

p = finger.fingerSearch();
if(p != FINGERPRINT_OK) return -1;

return finger.fingerID;
}
```

APPENDIX 2

LIST OF PUBLICATION

1. M. Nisha, S. Madhumitha, K. Akalya, M. Gokulakannan, S. Dinesh,
“AI Enabled Adaptive Ambulance Monitoring System with Biometric
Authentication”,15th International Conference on Recent Challenges in
Engineering and Technology(ICRCET-2026), Web of Science (BkCI),
SCOPUS,Bangalore, April 2026.DOI: 10.1109/ICMSCI62561.2025.108
94085



CERTIFICATE — OF PAPER PRESENTATION —



15TH INTERNATIONAL CONFERENCE ON RECENT CHALLENGES IN ENGINEERING AND TECHNOLOGY (ICRCET-2026)

22nd & 23rd April 2026

HYBRID
CONFERENCE

Certificate No : IFERP2026_2101_ICRCET-2026_15671

16
CPD
HOURS

This is to certify that ..Nisha.M. from ..Akshaya College Of Engineering And Technology has successfully submitted and presented the research paper titled ..CLASSIFICATION OF KNEE OSTEOARTHRITIS USING TRANSFORMER BASED VISION MODELS.. virtually at the 15th International Conference on Recent Challenges in Engineering and Technology (ICRCET), organized by Primus School of Management Studies, India, and IFERP Academy and held on 22nd & 23rd April 2026 in Bangalore, India as a Hybrid Conference. Accredited by CPD, the conference offers 16 credit hours of professional development.

The CPD Approved Date:
01/04/2026 to 02/04/2026
CPD No: 2026-04-01-02

Dr. Shreeya Shree Narayana
Primus School of Management Studies
Bangalore, India

Dr. D. Jayashree
Primus School of Management Studies
Bangalore, India

Dr. Nisha B. K.
Primus School of Management Studies
Bangalore, India

Dr. Sandhya Shreeji
Primus School of Management Studies
Bangalore, India

Dr. Shreeya Shree Narayana
Primus School of Management Studies
Bangalore, India

Dr. Shreeya Shree Narayana
Primus School of Management Studies
Bangalore, India



22nd 8 23rd April 2026

Certificate No : IHERP2026_2101_ICRCET-2026_15672

10
CPD
HOURS[illegible]



CERTIFICATE — OF PAPER PRESENTATION —



15TH INTERNATIONAL CONFERENCE ON RECENT CHALLENGES IN ENGINEERING AND TECHNOLOGY (ICRCET-2026)

22nd & 23rd April 2026



Certificate No : IFERP2026_2101_ICRCET-2026_15671



This is to certify that Madhumitha S. from Akshaya College Of Engineering And Technology has successfully submitted and presented the research paper titled AI-ENABLED ADAPTIVE AMBLANCE MONITORING SYSTEM WITH BIOMETRIC AUTHENTICATION virtually at the 15th International Conference on Recent Challenges in Engineering and Technology (ICRCET), organized by Primus School of Management Studies, India, and IFERP Academy and held on 22nd & 23rd April 2026 in Bangalore, India as a Hybrid Conference. Accredited by CPD, the conference offers 16 credit hours of professional development.



HYBRID
CONFINEMENT

Certificate No : IFERP2026_2101_ICRCET-2026_15672



This is to certify that Dr. S. S. from "Abha College Of Engineering And Technology" has successfully submitted and presented the research paper titled "AN ADAPTIVE AMBIANCE MONITORING SYSTEM WITH BIOMETRIC AUTHENTICATION" virtually at the 15th International Conference on Recent Challenges in Engineering and Technology (ICRCET), organized by Prims School of Management Studies, India, and IPERP Academy and held on 22nd & 23rd April 2026 in Bangalore, India as a Hybrid Conference. Accredited by CPD, the conference offers 16 credit hours of professional development.

[illegible]



CERTIFICATE — OF PAPER PRESENTATION —



15TH INTERNATIONAL CONFERENCE ON RECENT CHALLENGES IN ENGINEERING AND TECHNOLOGY (ICRCET-2026)

22nd & 23rd April 2026

HYBRID
CONFERENCE

Certificate No : IFERP2026_2101_ICRCET-2026_15671

16
CPD
HOURS

This is to certify that Gokulakannan M from Akshaya College Of Engineering And Technology has successfully submitted and presented the research paper titled AI-ENABLED ADAPTIVE AMBIANCE MONITORING SYSTEM WITH BIOMETRIC AUTHENTICATION virtually at the 15th International Conference on Recent Challenges in Engineering and Technology (ICRCET), organized by Primus School of Management Studies, India, and IFERP Academy and held on 22nd & 23rd April 2026 in Bangalore, India as a Hybrid Conference. Accredited by CPD, the conference offers 16 credit hours of professional development.



