 Router3

Physical	Config	CLI	Attributes
----------	--------	-----	------------

IOS Command Line Interface

```

Router(config)#interface GigabitEthernet0/0
Router(config-if)#ip address 192.168.1.1 255.255.255.0
Router(config-if)#ip address 192.168.1.1 255.255.255.0
Router(config-if)#
Router(config-if)#
Router(config-if)#exit
Router(config)#
Router(config)#
Router(config)#router rip
Router(config-router)#
Router(config-router)#
Router(config-router)#end
Router#vlan database
% Warning: It is recommended to configure VLAN from config mode,
as VLAN database mode is being deprecated. Please consult user
documentation for configuring VTP/VLAN in config mode.

Router(vlan)#
Router(vlan)#exit
APPLY completed.
Exiting....
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#
Router(config)#
Router(config)#router rip
Router(config-router)#
Router(config-router)#end
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface GigabitEthernet0/0
Router(config-if)#
%SYS-5-CONFIG_I: Configured from console by console

%SYS-5-CONFIG_I: Configured from console by console
ip address 192.168.1.1 255.255.255.0
Router(config-if)#





```

Copy

Paste

Top

Realtime Simulation

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit	Delete
	Successful	Router3	PC_RollNumber2	ICMP		1.849	N	0	(edit)	
	Successful	PC_R...	Router3	ICMP		0.000	N	1	(edit)	

(delete)

(delete)

Automatically Choose Connection Type