

Clustering


Clustering:

- Unsupervised learning
- Requires data, but no labels
- Detect patterns e.g. in
 - Group emails or search results
 - Customer shopping patterns
 - Regions of images
- Useful when don't know what you're looking for
- But: can get gibberish





Clustering

- **Basic idea:** group together similar instances
- **Example:** 2D point patterns




Clustering

- **Basic idea:** group together similar instances
- **Example:** 2D point patterns



Clustering

- **Basic idea:** group together similar instances
- **Example:** 2D point patterns




- **What could “similar” mean?**
 - One option: small Euclidean distance (squared)
$$\text{dist}(\vec{x}, \vec{y}) = \|\vec{x} - \vec{y}\|_2^2$$
 - Clustering results are crucially dependent on the measure of similarity (or distance) between “points” to be clustered

Clustering algorithms


- Partition algorithms (Flat)

- K-means
- Mixture of Gaussian
- Spectral Clustering



- Hierarchical algorithms

- Bottom up – agglomerative
- Top down – divisive



Clustering examples

Image segmentation


Goal: Break up the image into meaningful or perceptually similar regions



[Slide from James Hayes]

Clustering examples


Clustering gene expression data



Eisen et al, PNAS 1998


K-Means

- An iterative clustering algorithm
 - **Initialize:** Pick K random points as cluster centers
 - **Alternate:**
 1. Assign data points to closest cluster center
 2. Change the cluster center to the average of its assigned points
 - **Stop** when no points' assignments change




K-Means

- An iterative clustering algorithm
 - **Initialize:** Pick K random points as cluster centers
 - **Alternate:**
 1. Assign data points to closest cluster center
 2. Change the cluster center to the average of its assigned points
 - **Stop** when no points' assignments change




K-means clustering: Example



- Pick K random points as cluster centers (means)

Shown here for $K=2$


K-means clustering: Example



Iterative Step 1

- Assign data points to closest cluster center


K-means clustering: Example



Iterative Step 2


- Change the cluster center to the average of the assigned points

K-means clustering: Example




- Repeat until convergence

K-means clustering: Example



K-means clustering: Example



K-means clustering: Example

