



Experiment No. 7
Implement Booth's algorithm using c-programming
Name: Jaffari Mohammed Ali Sayyed Naqi Ali
Roll Number: 16
Date of Performance:
Date of Submission:

Aim: To implement Booth's algorithm using c-programming.

Objective -


1. To understand the working of Booths algorithm.
2. To understand how to implement Booth's algorithm using c-programming.

Theory:

Booth's algorithm is a multiplication algorithm that multiplies two signed binary numbers in 2's complement notation. Booth used desk calculators that were faster at shifting than adding and created the algorithm to increase their speed.

The algorithm works as per the following conditions :

1. If Q_n and Q_{n-1} are same i.e. 00 or 11 perform arithmetic shift by 1 bit.
2. If $Q_n Q_{n-1} = 10$ do $A = A - B$ and perform arithmetic shift by 1 bit.
3. If $Q_n Q_{n-1} = 01$ do $A = A + B$ and perform arithmetic shift by 1 bit.



Multiplicand (B) ← 0 1 0 1 (5), Multiplier (Q) ← 0 1 0 0 (4)				
Steps	A	Q	Q-1	Operation
	0 0 0 0	0 1 0 0	0	Initial
Step 1 :	0 0 0 0	0 0 1 0	0	Shift right
Step 2 :	0 0 0 0	0 0 0 1	0	Shift right
Step 3 :	1 0 1 1	0 0 0 1	0	A ← A - B
	1 1 0 1	1 0 0 0	1	Shift right
Step 4 :	0 0 1 0	1 0 0 0	1	A ← A + B
	0 0 0 1	0 1 0 0	0	Shift right
Result	0 0 0 1 0 1 0 0 = +20			

Program:



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
#include <math.h>
```

```
int a = 0, b = 0, c = 0, a1 = 0, b1 = 0, com[5] = { 1, 0, 0, 0, 0};  
int anum[5] = {0}, anumcp[5] = {0}, bnum[5] = {0};  
int acomp[5] = {0}, bcomp[5] = {0}, pro[5] = {0}, res[5] = {0};
```

```
void binary(){  
    a1 = fabs(a);  
    b1 = fabs(b);  
    int r, r2, i, temp;  
    for (i = 0; i < 5; i++){  
        r = a1 % 2;  
        a1 = a1 / 2;  
        r2 = b1 % 2;  
        b1 = b1 / 2;  
        anum[i] = r;  
        anumcp[i] = r;  
        bnum[i] = r2;  
        if(r2 == 0){  
            bcomp[i] = 1;  
        }  
        if(r == 0){  
            acomp[i] = 1;  
        }  
    }  
}
```

```
c = 0;  
for ( i = 0; i < 5; i++){  
    res[i] = com[i] + bcomp[i] + c;  
    if(res[i] >= 2){  
        c = 1;  
    }  
    else  
        c = 0;  
    res[i] = res[i] % 2;  
}  
for (i = 4; i >= 0; i--){  
    bcomp[i] = res[i];  
}
```



```
if (a < 0){
    c = 0;
    for (i = 4; i >= 0; i--){
        res[i] = 0;
    }
    for ( i = 0; i < 5; i++){
        res[i] = com[i] + acomp[i] + c;
        if (res[i] >= 2){
            c = 1;
        }
        else
            c = 0;
        res[i] = res[i]%2;
    }
    for (i = 4; i >= 0; i--){
        anum[i] = res[i];
        anumcp[i] = res[i];
    }
}

if(b < 0){
    for (i = 0; i < 5; i++){
        temp = bnum[i];
        bnum[i] = bcomp[i];
        bcomp[i] = temp;
    }
}

void add(int num[]){
    int i;
    c = 0;
    for ( i = 0; i < 5; i++){
        res[i] = pro[i] + num[i] + c;
        if (res[i] >= 2){
            c = 1;
        }
        else{
            c = 0;
        }
    }
}
```



```
    }
    res[i] = res[i]%2;
}
for (i = 4; i >= 0; i--){
    pro[i] = res[i];
    printf("%d",pro[i]);
}
printf(":");
for (i = 4; i >= 0; i--){
    printf("%d", anumcp[i]);
}
}

void arshift(){
    int temp = pro[4], temp2 = pro[0], i;
    for (i = 1; i < 5 ; i++){
        pro[i-1] = pro[i];
    }
    pro[4] = temp;
    for (i = 1; i < 5 ; i++){
        anumcp[i-1] = anumcp[i];
    }
    anumcp[4] = temp2;
    printf("\nAR-SHIFT: ");
    for (i = 4; i >= 0; i--){
        printf("%d",pro[i]);
    }
    printf(":");
    for(i = 4; i >= 0; i--){
        printf("%d", anumcp[i]);
    }
}

void main(){
    int i, q = 0;
    printf("\t\tBOOTH'S MULTIPLICATION ALGORITHM");
    printf("\nEnter two numbers to multiply: ");
    printf("\nBoth must be less than 16");
    //simulating for two numbers each below 16
    do{
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
printf("\nEnter A: ");
scanf("%d",&a);
printf("Enter B: ");
scanf("%d", &b);
}while(a >=16 || b >=16);

printf("\nExpected product = %d", a * b);
binary();
printf("\n\nBinary Equivalents are: ");
printf("\nA = ");
for (i = 4; i >= 0; i--){
    printf("%d", anum[i]);
}
printf("\nB = ");
for (i = 4; i >= 0; i--){
    printf("%d", bnum[i]);
}
printf("\nB'+ 1 = ");
for (i = 4; i >= 0; i--){
    printf("%d", bcomp[i]);
}
printf("\n\n");
for (i = 0; i < 5; i++){
    if (anum[i] == q){
        printf("\n-->");
        arshift();
        q = anum[i];
    }
    else if(anum[i] == 1 && q == 0){
        printf("\n-->");
        printf("\nSUB B: ");
        add(bcomp);
        arshift();
        q = anum[i];
    }
    else{
        printf("\n-->");
        printf("\nADD B: ");
        add(bnum);
    }
}
```



```
        arshift();
        q = anum[i];
    }
}

printf("\nProduct is = ");
for (i = 4; i >= 0; i--){
    printf("%d", pro[i]);
}
for (i = 4; i >= 0; i--){
    printf("%d", anumcp[i]);
}
}
```

Output:

OUTPUT:-

BOOTH'S MULTIPLICATION ALGORITHM

Enter two numbers to multiply:

Both must be less than 16

Enter A: 10

Enter B: 2

Expected product = 20

Binary Equivalentents are:

A = 01010

B = 00010

B' + 1 = 11110

-->

AR-SHIFT: 00000:00101

-->

SUB B: 11110:00101

AR-SHIFT: 11111:00010

-->

ADD B: 00001:00010

AR-SHIFT: 00000:10001

-->

SUB B: 11110:10001

AR-SHIFT: 11111:01000

-->



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

ADD B: 00001:01000

AR-SHIFT: 00000:10100

Product is = 0000010100

Conclusion -

Our exploration into Booth's algorithm has underscored its crucial role in enhancing the efficiency of binary multiplication. Booth's algorithm adeptly cuts down on the quantity of partial products, leading to a marked reduction in the overall number of necessary operations for multiplication. This not only accelerates computation but also simplifies hardware requirements. Booth's algorithm stands as a potent instrument for fine-tuning multiplication procedures and stands as a fundamental concept within the realm of digital arithmetic. Our experiment has effectively showcased its pragmatic utility in computer architecture and the design of digital circuits.