9/3/21

DBMS

Mid-Semister Exam

Name:- V. Manoj
Roll No:- 19BCS110

6) SQL query

Select * into empty_table from UniversityTable where 1=2;

This query will copy columns from UniversityTable but not data hence 'empty_table' will be empty.

i) Select * into empty_table - will create a table with name 'empty_table'.

ii) from. UniversityTable - Takes columns from 'UniversityTable'.

iii) where 1=2 - Predicate that is always false so no data is copied.

i) let table be,

Zoo EmpTable.

ZPerId. ~~Zoo Emp Table~~	ZPerName.
1	Manoj
2	Sahit
3	Reddy
4	Vanga.

Given query,

Select ZperName from Zoo EmpTable order by 3 asc;

9/3/21

DBMS

Mid-Semister Exam

Name:- V. Manoj
Roll-No:- 19BCS110

6) SQL query

Select * into empty_table from UniversityTable where 1=2;

This query will copy columns from UniversityTable but not data hence 'empty_table' will be empty.

i) Select * into empty_table - will create a table with name 'empty_table'

ii) from UniversityTable - Takes columns from 'UniversityTable'.

iii) where 1=2 - Predicate that is always false so no data is copied.

1) let table be,

Zoo EmpTable.

ZPerId ~~Zoo EmpTable~~	ZPerName.
1	Manoj
2	Sahit
3	Reddy
4	Vamsi.

Given query,

Select ZperName from Zoo EmpTable order by 3 asc;

V. Manoj
19BCS110

Select & from clause in query is correct but order by requires 3rd column inorder to sort the table by observing table there is no 3rd column

Hence the output is "Error".

2) let table be,

employees Table

emp_Id	emp_name	insurance_Policy
1	Manoj	Type-1
2	Sahit	Type-2
3	Reddy	Type-2
4.	Vanga	Type-1.

SQL query:

~~Select T1.emp_Id, T1.emp_name, T1.insurance_policy from employees Table as T1, employees Table as T2 where T1.insurance_Policy =~~

i) Select *
from employees Table
where (select e.emp_name from employees Table)

ii) select e1.Name from employees Table as e1, employees Table as e2 where ~~e1.insurance_policy~~ e1.insurance_Policy = e2.insurance_Policy.

V. Manoj
19B1S1A0

3) let table,

Employee

Name	Salary
Manoj	1,88,888
Sahil	8,88,888
Reddy	3,88,888
Vamy	4,88,888

select *
from (select Name, Salary, dense_rank()
over (order by Sal desc) m from
Employee)
where m = n;.
substitute n for getting m^{th} high

4) The given statement is ~~true partially~~ ~~true & partially~~ false.
For example sql server does not drop views, procedures but drops all the others in table.
Hence given statement is false.

5) let table be, Std_InfoDetails

Std_Id	Std_Department	Std_Course_ID	Std_Course name.
1	cse	5	O.S
2	cse	3	MPC
3	ece	4	BPC
4	cse	5	DBMS.
5.	ECE	2	DAA.

Query

19bcs110

select * from std_InfoDetails
where std_Id % 2 = 0;

Above is for even coloumns

: For odd,

select * from Std_InfoDetails
where std_Id % 2 = 1;

8)

a) Complete

Scholar	Tutorial
Manoj	OS
sahit	DAA
vanga	DBMS

Required

Tutorial
~~DBMS~~ OS
~~OS~~ DBMS
DAA

1) All Scholars

scholar
Manoj
sahit
vanga

2) Scholar And Required

scholar	Tutorial
Manoj	OS
~~Sahit~~	~~DAA~~
~~vanga~~	~~DBMS~~

3) Scholars and Received not Complete.

scholar	Tutorial.
Sahit	DBMS
vanga.	DAA

labs/to

4) Cannot graduate

scholar
Sahit
vanga

~~Queries~~

5) Can graduate

scholar
Manoj