



# Gnome::Gtk3::ComboBoxText

#### Table of Contents

- 0.1 ComboBoxText — A simple, text-only combo box 1 **Synopsis** 2 Methods 2.1 gtk combo box text append 2.2 gtk combo box text prepend 2.3 gtk combo box text insert 2.4 [gtk combo box text ] append text 2.5 [gtk combo box text ] prepend text 2.6 [gtk combo box text ] insert text 2.7
- gtk combo box text remove 2.8 [gtk combo box text ] remove all
- 2.9 gtk combo box text get active text
- 2.10 new

```
unit class Gnome::Gtk3::ComboBoxText;
also is Gnome::Gtk3::ComboBox;
```

#### ComboBoxText — A simple, text-only combo box

### **Synopsis**

```
# Get a fully designed text combobox
my Gnome::Gtk3::ComboBoxText $server-cb .= new(:build-id<serverComboBox>);
my Str $server = $server-cb.get-active-id;
```

#### **Methods**

#### gtk combo box text append

```
method gtk_combo_box_text_append ( Str $id, Str $text )
```

Appends text. See also gnome developer docs.

#### gtk\_combo\_box\_text\_prepend

```
method gtk_combo_box_text_prepend ( Str $id, Str $text )
```

Prepends text. See also gnome developer docs.

This is the same as calling gtk combo box text insert() with a position of 0.

#### gtk\_combo\_box\_text\_insert

```
method gtk_combo_box_text_insert ( Int $position, Str $id, Str $text )
```

Insert text at position. See also gnome developer docs.

#### [gtk\_combo\_box\_text\_] append\_text

```
method gtk_combo_box_text_append_text ( Str $text )
```

Append text. See also gnome developer docs.

### [gtk\_combo\_box\_text\_] prepend\_text

```
method gtk_combo_box_text_prepend_text ( Str $text )
```

Prepend text. See also gnome developer docs.

## [gtk\_combo\_box\_text\_] insert\_text

```
method gtk_combo_box_text_insert_text ( int32 $position, Str $text )
```

Insert text at position. See also gnome developer docs.

#### gtk\_combo\_box\_text\_remove

```
method gtk_combo_box_text_remove ( Int $position )
```

Remove text at position. See also gnome developer docs.

#### [gtk\_combo\_box\_text\_] remove\_all

```
method gtk_combo_box_text_remove_all ( )
```

Remove all text entries. See also gnome developer docs.

# ${\bf gtk\_combo\_box\_text\_get\_active\_text}$

```
method gtk_combo_box_text_get_active_text ( )
```

Get selected entry. See also gnome developer docs.

#### new

```
multi method new ( :$widget! )
```

Create a simple text combobox using a native object from elsewhere. See also Gnome::GObject::Object.

```
multi method new ( Str :$build-id! )
```

Create a simple text combobox using a native object from a builder. See also Gnome::GObject::Object.

Generated using Pod::Render, Pod::To::HTML, Camelia™ (butterfly) is © 2009 by Larry Wall