



Driver Authentication

Abstract

MongoDB supports various authentication strategies across various versions. When authentication is turned on in the database, a driver must authenticate before it is allowed to communicate with the server. This spec defines when and how a driver performs authentication with a MongoDB server.

This report is following a specification from the [Mongodb](#) website and is shown below.

Mongo credential

Drivers SHOULD contain a type called MongoCredential. In this driver it is called

`MongoDB::Authenticate::Credential`.

```
use MongoDB::Authenticate::Credential;
my MongoDB::Authenticate::Credential $cred .= new(
    :username<user>, :password<pencil>,
    :auth-mechanism<SCRAM-SHA-1>
5. );
ok $cred.defined, 'T0';
is $cred.password, "pencil", 'T1';
```

- ✓ **T0:** Credential is defined. Not all named arguments are used. There are also `:source` and `:mechanism-properties`. Btw. the field `mechanism` is named `auth-mechanism` because of the name `authMechanism` used in the url as an option.
- ✓ **T1:** Data can also be retrieved from it again.

Some combinations of credential parameters should fail

```
my $x = {
    $cred .= new(
10. :username<user>, :password<pencil>,
    :auth-mechanism<MONGODB-X509>
    );
}
;
15. dies-ok $x(), 'T2';
```

- ☆☆ **T2:** Mechanism MONGODB-X509 does not expect a password

Credential parameters are set using uri


```

use lib 't';
use Test-support;
use MongoDB::Client;
my MongoDB::Test-support $ts .= new;
20. my Int $p1 = $ts.server-control.get-port-number('s1');
my MongoDB::Client $client .= new(uri("mongodb://localhost:$p1"));
ok $client.defined, 'T3';

```

☆☆ **T3:** Returned client object is defined, even when the uri is not pointing to an existing mongod server.

Normal tests



Bug issues



Todo tests



Summary

