

Deep Learning

Vazgen Mikayelyan



Logistic Regression

Let $(x_i, y_i)_{i=1}^n$, $x_i \in \mathbb{R}^k$, $y_i \in \{0, 1\}$ be our training data.

Logistic Regression

Let $(x_i, y_i)_{i=1}^n$, $x_i \in \mathbb{R}^k$, $y_i \in \{0, 1\}$ be our training data. Consider the function

$$\begin{aligned} f(x) &= f(x^1, x^2, \dots, x^k) = \sigma(w^1 x^1 + w^2 x^2 + \dots + w^k x^k + b) \\ &= \sigma(w^T x + b). \end{aligned}$$

Logistic Regression

Let $(x_i, y_i)_{i=1}^n$, $x_i \in \mathbb{R}^k$, $y_i \in \{0, 1\}$ be our training data. Consider the function

$$\begin{aligned} f(x) &= f(x^1, x^2, \dots, x^k) = \sigma(w^1 x^1 + w^2 x^2 + \dots + w^k x^k + b) \\ &= \sigma(w^T x + b). \end{aligned}$$

Our aim is to find parameters $b, w^1, w^2, \dots, w^k$ such that

$$f(x_i) \approx y_i, i = 1, \dots, n.$$

Logistic Regression

Let $(x_i, y_i)_{i=1}^n$, $x_i \in \mathbb{R}^k$, $y_i \in \{0, 1\}$ be our training data. Consider the function

$$\begin{aligned} f(x) &= f(x^1, x^2, \dots, x^k) = \sigma(w^1 x^1 + w^2 x^2 + \dots + w^k x^k + b) \\ &= \sigma(w^T x + b). \end{aligned}$$

Our aim is to find parameters $b, w^1, w^2, \dots, w^k$ such that

$$f(x_i) \approx y_i, i = 1, \dots, n.$$

We choose cross entropy distance as our loss function:

$$\frac{1}{n} \sum_{l=1}^n (-y_l \log f(x_l) - (1 - y_l) \log (1 - f(x_l))).$$

- 1 Can you represent this model as a neural network?

Questions

- 1 Can you represent this model as a neural network?
- 2 Why do we use the function sigmoid in this case?

- ① Can you represent this model as a neural network?
- ② Why do we use the function sigmoid in this case?
- ③ Why don't we use L^2 distance in this case?

- ① Can you represent this model as a neural network?
- ② Why do we use the function sigmoid in this case?
- ③ Why don't we use L^2 distance in this case?
- ④ Can we do logistic regression when number of classes is greater than 2?

L1 and L2 Regularizations

L1 and L2 Regularizations

In linear regression instead of L^2 loss we use one from this two:

$$\frac{1}{n} \sum_{l=1}^n (f(x_l) - y_l)^2 + \frac{\lambda}{k} \sum_{l=1}^k |w_l|,$$

$$\frac{1}{n} \sum_{l=1}^n (f(x_l) - y_l)^2 + \frac{\lambda}{k} \sum_{l=1}^k w_l^2.$$

1 Softmax Classifier

Softmax Classifier

Let $(x_i, y_i)_{i=1}^n$, $x_i \in \mathbb{R}^k$, $y_i \in \mathbb{R}^m$ (one-hot vectors) be our training data.

Softmax Classifier

Let $(x_i, y_i)_{i=1}^n$, $x_i \in \mathbb{R}^k$, $y_i \in \mathbb{R}^m$ (one-hot vectors) be our training data.
Consider the function

$$f(x) = \left(\frac{e^{w_1^T x + b_1}}{\sum_{i=1}^m e^{w_i^T x + b_i}}, \dots, \frac{e^{w_m^T x + b_m}}{\sum_{i=1}^m e^{w_i^T x + b_i}} \right)$$

Softmax Classifier

Let $(x_i, y_i)_{i=1}^n$, $x_i \in \mathbb{R}^k$, $y_i \in \mathbb{R}^m$ (one-hot vectors) be our training data. Consider the function

$$f(x) = \left(\frac{e^{w_1^T x + b_1}}{\sum_{i=1}^m e^{w_i^T x + b_i}}, \dots, \frac{e^{w_m^T x + b_m}}{\sum_{i=1}^m e^{w_i^T x + b_i}} \right)$$

Our aim is to find parameters $(b_i, w_i)_{i=1}^m$ such that

$$f(x_i) \approx y_i, i = 1, \dots, n.$$

Softmax Classifier

Let $(x_i, y_i)_{i=1}^n$, $x_i \in \mathbb{R}^k$, $y_i \in \mathbb{R}^m$ (one-hot vectors) be our training data. Consider the function

$$f(x) = \left(\frac{e^{w_1^T x + b_1}}{\sum_{i=1}^m e^{w_i^T x + b_i}}, \dots, \frac{e^{w_m^T x + b_m}}{\sum_{i=1}^m e^{w_i^T x + b_i}} \right)$$

Our aim is to find parameters $(b_i, w_i)_{i=1}^m$ such that

$$f(x_i) \approx y_i, i = 1, \dots, n.$$

We choose cross entropy distance as our loss function:

$$\frac{1}{n} \sum_{i=1}^n \left(-y_i^T \log f(x_i) \right).$$

- 1 Can you represent this model as a neural network?

Questions

- 1 Can you represent this model as a neural network?
- 2 Can we use the function sigmoid in this case?

- ① Can you represent this model as a neural network?
- ② Can we use the function sigmoid in this case?
- ③ What to do in the case of multi-label classification?